BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1333585S_04

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number 1333585S_03 lodged with the consent authority or certifier on with application PAN-326890.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Schedule 1 Clause 2A, 4A or 6A of the Environment Planning and Assessment Regulation 2000

Secretary Date of issue: Tuesday, 05 December 2023 To be valid, this certificate must be lodged within 3 months of the date of issue.



| Project summary | | |
|---------------------------|--------------------------|-------------------------------------|
| Project name | DW2_8 Hillview Ave, Banl | <stown_03_04< td=""></stown_03_04<> |
| Street address | 8 HILLVIEW AVENUE BAN | NKSTOWN 2200 |
| Local Government Area | Canterbury-Bankstown Co | uncil |
| Plan type and plan number | Deposited Plan 30757 | |
| Lot no. | 16 | |
| Section no. | - | |
| Project type | separate dwelling house | |
| No. of bedrooms | 4 | |
| Project score | | |
| Water | 40 | Target 40 |
| Thermal Comfort | V Pass | Target Pass |
| Energy | 53 | Target 50 |

Certificate Prepared by

Name / Company Name: NEMCO DESIGN PTY. LTD.

ABN (if applicable): 46166160505

Description of project

Project address

| DW2_8 Hillview Ave, Bankstown_03_04 | |
|-------------------------------------|--|
| 8 HILLVIEW AVENUE BANKSTOWN 2200 | |
| Canterbury-Bankstown Council | |
| Deposited Plan 30757 | |
| 16 | |
| - | |
| | |
| separate dwelling house | |
| 4 | |
| | |
| 518 | |
| 143 | |
| 169.8 | |
| 12.5 | |
| 264 | |
| 0 | |
| | |

Assessor details and thermal loads Assessor number n/a Certificate number n/a Climate zone n/a Area adjusted cooling load (MJ/ n/a m².year) Area adjusted heating load (MJ/ n/a m².year) Ceiling fan in at least one bedroom n/a Ceiling fan in at least one living room n/a or other conditioned area Project score Water 4 40 Target 40 Thermal Comfort Target Pass Pass Energy 53 Target 50

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

| Water Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|---|---------------------|---------------------------------|---|
| Landscape | 4 | | |
| The applicant must plant indigenous or low water use species of vegetation throughout 25 square metres of the site. | ~ | ~ | |
| Fixtures | | • | |
| The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development. | | ~ | ~ |
| The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development. | | ~ | ~ |
| The applicant must install taps with a minimum rating of 4 star in the kitchen in the development. | | ~ | |
| The applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development. | | ~ | |
| Alternative water | | | , |
| Rainwater tank | | | |
| The applicant must install a rainwater tank of at least 2400 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities. | ~ | ~ | ~ |
| The applicant must configure the rainwater tank to collect rain runoff from at least 147.3 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam). | | ~ | ~ |
| The applicant must connect the rainwater tank to: | | | 1 |
| all toilets in the development | | | Image: A set of the set of the |
| at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) | | v | ~ |

| Thermal Comfort Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|---|---------------------|------------------------------|--------------------|
| Do-it-yourself Method | | | |
| General features | | | |
| The dwelling must not have more than 2 storeys. | ~ | ~ | ~ |
| The conditioned floor area of the dwelling must not exceed 300 square metres. | ~ | ~ | ~ |
| The dwelling must not contain open mezzanine area exceeding 25 square metres. | ~ | ~ | ~ |
| The dwelling must not contain third level habitable attic room. | ~ | | ~ |
| Floor, walls and ceiling/roof | - | • | -, |
| The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below. | ~ | ~ | ~ |

| Construction | Additional insulation required (R-Value) | Other specifications |
|--|--|---|
| floor - concrete slab on ground, 82.6 square metres | nil | |
| floor - above habitable rooms or mezzanine, 99.7 square metres, framed | nil | |
| floor - suspended floor above garage, framed | nil | |
| external wall - brick veneer | 2.86 (or 3.40 including construction) | |
| external wall - other/undecided | 3.40 (including construction) | |
| ceiling and roof - flat ceiling / flat roof, framed | ceiling: 4.5 (up), roof: foil/sarking | framed; medium (solar absorptance 0.475-0.70) |

Note • Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

Note • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

| Thermal Comfort Con | nmitments | | | | Show on DA plans | Show on CC/CDC plans & specs | Certifier check | |
|---|--|----------------------------------|--|---|---------------------|------------------------------|------------------------|--|
| Windows, glazed doors and | skylights | | | | | | , | |
| | | | table below, in accordance with for each window and glazed doo | | • | ~ | ~ | |
| The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table. | | | | | ~ | ~ | ~ | |
| The following requirements must also be satisfied in relation to each window and glazed door: | | | | ~ | ~ | ~ | | |
| For the following glass a | nd frame types, the certifier che | eck can be performed by visual | inspection. | | | | ~ | |
| - Aluminium single clear | | | | | | | | |
| - Aluminium double (air) c | lear | | | | | | | |
| - Timber/uPVC/fibreglass | single clear | | | | | | | |
| - Timber/uPVC/fibreglass | double (air) clear | | | | | | | |
| | s/vegetation must be of the heig ne 'overshadowing' column. | pht and distance from the centre | e and the base of the window an | d glazed | ~ | ~ | ~ | |
| Window/glazed door no. | Maximum height (mm) | Maximum width (mm) | Туре | Shading Device (Dimension within 10%) | | | Overshadowing | |
| North facing | | | | | | | | |
| GD2.1 | 2700.00 | 1200.00 | aluminium, single, clear | solid overhang 2250 mm, 3150 mm above head of window or glazed door | | 8 m away | | |
| W2.7 | 2100.00 | 2170.00 | aluminium, single, clear | solid overhang 200 mm, 300 mm above head of window or glazed door | | | 8 m away | |
| | | | | solid overhang 200 mm, 3150 mm above head of window or glazed door | | | 2-4 m high, 5-8 m away | |

| Window/glazed door no. | Maximum height (mm) | Maximum width (mm) | Туре | Shading Device (Dimension within 10%) | Overshadowing |
|------------------------|---------------------|--------------------|--------------------------|--|------------------------|
| W2.6 | 2100.00 | 1200.00 | aluminium, single, clear | solid overhang 2250 mm, 300 mm above head of window or glazed door | 2-4 m high, 5-8 m away |
| East facing | | | | | |
| W2.3 | 2100.00 | 850.00 | aluminium, single, clear | none | >4 m high, 5-8 m away |
| W2.10 | 600.00 | 600.00 | aluminium, single, clear | none | >4 m high, 5-8 m away |
| W2.12 | 600.00 | 1810.00 | aluminium, single, clear | none | >4 m high, 5-8 m away |
| W2.2 | 600.00 | 3000.00 | aluminium, single, clear | none | >4 m high, 5-8 m away |
| W2.8 | 2100.00 | 1570.00 | aluminium, single, clear | none | >4 m high, <2 m away |
| W2.4 | 2100.00 | 850.00 | aluminium, single, clear | none | >4 m high, 5-8 m away |
| W2.11 | 970.00 | 2170.00 | aluminium, single, clear | none | >4 m high, 5-8 m away |
| W2.9 | 970.00 | 2170.00 | aluminium, single, clear | none | >4 m high, 5-8 m away |
| South facing | | | | | |
| SD2.1 | 2400.00 | 4800.00 | aluminium, single, clear | verandah 3300 mm, 2850 mm above base of window or glazed door | >4 m high, 5-8 m away |
| W2.13 | 600.00 | 2650.00 | aluminium, single, clear | eave 450 mm, 268 mm above head of window or glazed door | >4 m high, 5-8 m away |
| West facing | | | | | |
| W2.15 | 970.00 | 2170.00 | aluminium, single, clear | none | >4 m high, <2 m away |
| W2.14 | 970.00 | 2170.00 | aluminium, single, clear | none | >4 m high, <2 m away |
| W2.16 | 970.00 | 2170.00 | aluminium, single, clear | none | >4 m high, <2 m away |
| W2.5 | 2400.00 | 5000.00 | aluminium, single, clear | none | >4 m high, <2 m away |

| Energy Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|--|---------------------|---------------------------------|--------------------|
| Hot water | | | |
| The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric heat pump with a performance of 26 to 30 STCs or better. | ~ | ~ | ~ |
| Cooling system | | | |
| The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 5 Star (old label) | | ~ | ~ |
| The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 5 Star (old label) | | > | ~ |
| The cooling system must provide for day/night zoning between living areas and bedrooms. | | ~ | ~ |
| Heating system | | | |
| The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 5 Star (old label) | | ~ | ~ |
| The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 5 Star (old label) | | × | ~ |
| The heating system must provide for day/night zoning between living areas and bedrooms. | | ~ | ~ |
| Ventilation | | | |
| The applicant must install the following exhaust systems in the development: | | |] |
| At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off | | ~ | ~ |
| Kitchen: individual fan, not ducted; Operation control: manual switch on/off | | ~ | ~ |
| Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off | | ~ | ~ |
| Artificial lighting | | | • |

| Energy Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|---|---------------------|---------------------------------|--------------------|
| The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps: | | | |
| at least 4 of the bedrooms / study; dedicated | | ✓ | v |
| at least 2 of the living / dining rooms; dedicated | | ✓ | ~ |
| the kitchen; dedicated | | ✓ | - |
| all bathrooms/toilets; dedicated | | ~ | - |
| the laundry; dedicated | | ~ | v |
| all hallways; dedicated | | ~ | - |
| Natural lighting | | | |
| The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting. | ~ | ~ | ~ |
| The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting. | ~ | ~ | ~ |
| Other | | | _ |
| The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions. | | ~ | |
| The applicant must install a fixed outdoor clothes drying line as part of the development. | | ` | |

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a V in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a V in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a V in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.