BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A437014

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv Date of issue: Friday, 29, October 2021 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project address						
Project name	Snowdrift 21					
Street address	1/3 Riverview Terrace THREDBO 2625					
Local Government Area	Snowy Monaro Regional Council					
Plan type and number	Deposited Plan 118588					
Lot number	53					
Section number						
Project type						
Dwelling type	Attached dwelling house					
	Attached dwelling house					

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: mark Allsop

ABN (if applicable): N/A

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Hot water			
The applicant must install the following hot water system in the development: gas instantaneous.	\checkmark	\checkmark	~
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures		1	
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		 	~
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		\checkmark	\checkmark
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		\checkmark	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
	ation is not required where the area of new cor	fs) in accordance with the specifications listed in struction is less than 2m2, b) insulation specified	~	~	~
Construction	Additional insulation required (R-value)	Other specifications			
suspended floor with enclosed subfloor: framed (R0.7).	R1.80 (down) (or R2.50 including construction)				

Glazing re	quirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows a	ind glazed do	ors					l	1	
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.					\checkmark	~	~		
The following requirements must also be satisfied in relation to each window and glazed door:						~	~		
Each window or glazed door with improved frames, or pyrolytic low-e glass, or clear/air gap/clear glazing, or toned/air gap/clear glazing must have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. The description is provided for information only. Alternative systems with complying U-value and SHGC may be substituted.						~	~		
Overshadowing buildings or vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column in the table below.					 	~	~		
Windows	and glazed	doors g	lazing r	equireme	nts				
Window / door	oor Orientation		Overshadowing		Shading device	Frame and glass type			
no.		glass inc. frame (m2)	Height (m)	Distance (m)					
W1	NE	1.47	5.8	7.3	none	timber or uPVC, clear/air gap/clear, (U-value: 3.67, SHGC: 0.59)			
W2	SE	4.2	0	0	none	timber or uPVC, clear/air gap/clear, (U-value: 3.67, SHGC: 0.59)			
W3	SE	6.6	0	0	none	timber or uPVC, clear/air gap/clear, (U-value: 3.67, SHGC: 0.59)			
Skylights							<u> </u>	<u> </u>	
The applicant must install the skylights in accordance with the specifications listed in the table below.				\checkmark	 	\checkmark			
The following requirements must also be satisfied in relation to each skylight:						~	~		
Each skylight may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in the table below.							./		

Glazing require	ements			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
_	External awnings and louvres must fully shade the skylight above which they are situated when fully drawn or closed.					~
Skylights glaz	ing requireme	nts				
Skylight number	Area of glazing inc. frame (m2)	Shading device	Frame and glass type			
S1	134.5	external adjustable awning or blind	timber, low-E internal/argon fill/clear external, (or U-value: 2.5, SHGC: 0.456)			
S2	0.92	no shading	timber, low-E internal/argon fill/clear external, (or U-value: 2.5, SHGC: 0.456)			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.