

BASIX[®]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1284359S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Tuesday, 01 March 2022

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning,
Industry &
Environment

Project summary

Project name	7 Neptune St, Revesby - UNIT1
Street address	7 Neptune Street Revesby 2212
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	deposited 414285
Lot no.	A
Section no.	-
Project type	attached dwelling house
No. of bedrooms	4

Project score

Water	✓ 42	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 59	Target 50

Certificate Prepared by

Name / Company Name: Joseph Rafla

ABN (if applicable): N/A

Description of project

Project address

Project name	7 Neptune St, Revesby - UNIT1
Street address	7 Neptune Street Revesby 2212
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan 414285
Lot no.	A
Section no.	-

Project type

Project type	attached dwelling house
No. of bedrooms	4

Site details

Site area (m ²)	324
Roof area (m ²)	165
Conditioned floor area (m2)	144.3
Unconditioned floor area (m2)	17.0
Total area of garden and lawn (m2)	152

Assessor details and thermal loads

Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m ² .year)	n/a
Area adjusted heating load (MJ/m ² .year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a

Project score

Water	✓ 42	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 59	Target 50

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 6 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 6 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 6 star in each bathroom in the development.		✓	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 1000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 60 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> all toilets in the development at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		✓ ✓	✓ ✓

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground, 87.9 square metres	nil	
floor - above habitable rooms or mezzanine, 73.4 square metres, concrete	nil	
floor - suspended floor above garage, concrete	nil	
external wall - cavity brick	0.50 (or 1.17 including construction)	
internal wall shared with garage - single skin masonry	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 1.7 (up), roof: foil backed blanket (55 mm)	gable end vents; light (solar absorptance < 0.475)

Note	• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.














Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
<p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <ul style="list-style-type: none"> For the following glass and frame types, the certifier check can be performed by visual inspection. <ul style="list-style-type: none"> - Aluminium single clear - Aluminium double (air) clear - Timber/uPVC/fibreglass single clear - Timber/uPVC/fibreglass double (air) clear 	✓	✓	✓ ✓

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
North facing					
W1G	1800	900	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W10G	4900	600	aluminium, single, clear	solid overhang 1200 mm, 100 mm above head of window or glazed door	not overshadowed
W2G	1800	1200	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
SD1F	2100	1800	aluminium, single, clear	verandah 2850 mm, 2400 mm above base of window or glazed door	not overshadowed
SD1F	2100	1800	aluminium, single, clear	verandah 1480 mm, 2400 mm above base of window or glazed door	not overshadowed
W5F	2500	1200	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
East facing					

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W3G	600	1800	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W4G	600	1200	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W5G	900	600	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W6G	600	3300	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W7G	600	900	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W2F	600	1800	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W2F	600	1800	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W3F	1200	1800	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
South facing					
W3G	600	1800	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W1F	600	900	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
West facing					
W2G	1800	1800	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W1G	1800	900	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed
W1G	1800	900	aluminium, single, clear	solid overhang 1920 mm, 100 mm above head of window or glazed door	not overshadowed
SD2G	2100	4800	aluminium, single, clear	verandah 4000 mm, 2400 mm above base of window or glazed door	not overshadowed
W2F	600	1800	aluminium, single, clear	eave 450 mm, 100 mm above head of window or glazed door	not overshadowed


Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
SD2F	2100	3000	aluminium, single, clear	verandah 1690 mm, 2400 mm above base of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	✓	✓	✓
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 6 Star (old label)		✓	✓
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 6 Star (old label)		✓	✓
The cooling system must provide for day/night zoning between living areas and bedrooms.		✓	✓
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 6 Star (old label)		✓	✓
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 6 Star (old label)		✓	✓
The heating system must provide for day/night zoning between living areas and bedrooms.		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development: At least 1 Bathroom: no mechanical ventilation (ie. natural); Operation control: n/a Kitchen: individual fan, ducted to façade or roof; Operation control: manual on / timer off Laundry: natural ventilation only, or no laundry; Operation control: n/a		✓ ✓ ✓	✓ ✓ ✓
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps: • at least 4 of the bedrooms / study; dedicated		✓	✓

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<ul style="list-style-type: none"> • at least 3 of the living / dining rooms; dedicated • the kitchen; dedicated • all bathrooms/toilets; dedicated • the laundry; dedicated • all hallways; dedicated 		    	    
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.			
The applicant must install a fixed outdoor clothes drying line as part of the development.			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.