

Scale 1 :100

# Lighting

The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.

## Fixtures

The applicant must ensure new or altered showerheads have a flow rate no greater that 9 litres per minute or 3 star water rating

The applicant must ensure new or altered toilets have a flow rate no greater that 4 litres per average flush or a minimum 3 star water rating

The applicant must ensure new or altered taps have a flow rate no greater that 9 litres per minute or a minimum 3 star water rating

Insulation requirements

The apllicant must construct the new or altered construction (floors, walls, and ceilings/roofs) in accordance with the specifications listed in the table below, except that a) additional insulation is not required where the area of new construction is less than 2 sq. metres b) insulation specified is not required for parts of altered construction where insulation already exists

Construction	Additional insulation required (R-value)	other specifications	
suspended floor with enclosed subfloor frame (R0.7)	R0.60 (down) (or R1.3 including construction)		
external wall: brick veneer	R1.16 (or R1.7 including construction)		
flat ceiling, pitched roof	ceiling: R 3.0 (up), roof: foil/sarking	dark (solar absorptance >0.70)	

#### Glazing Requirements Windows and glazed doors

The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below.

Relevant overshadowing specifications must be satisfied for each window and glazed door.

The following requirements must also be satisfied in relation to each window and glazed door: Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a value of U-value and a solar heat Gain coefficiency (SHGC) no greater than that listed in the table below. Total system U-value and SHGCs must be calculated in accordance with national Fenestrations Rating Council (NFRC) conditions.

For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500mm above the head of the window or glazed door and no more than 2400mm above the sill. Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less

Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.

Pergolas with fixed battens must have battens parallel to the window or glazed door above which they situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50mm

# Windows and glazed doors glazing requirements

window /door no		areaof glass inc. Frame m <sup>2</sup>		adowing Distance (m)		Frame and Glass type
W1 Laundry	S	0.72	0.6	1.2	eaves/verandah/pergola/balcony >=450mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)
W2 bathroon	n E	1.2	0	0	eaves/verandah/pergola/balcony >=450mm	standard aluminium, single clear, (or U-value: 7.57, SHGC: 0.57)
W3 bedroon	n S	0.45	1.0	0.45	eaves/verandah/pergola/balcony >=450mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)
D1 Kitchen	S	6.75	2.046	0.45	eaves/verandah/pergola/balcony >=450mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)

## NOTES:

- All Class 1a building must be fitted with a smoke alarm system in accordance with the Building Code of Australia. The system must be installed and certified by a quilified electrician, owner of the property must be supplied with the certificate
- 2. A termite barrier or combination of barriers must be installed in accordance with AS3660.1. The installer must be quilified and registered with the Australian Pest Controllers Association. Upon completion the owner must be supplied with a written report of the method of treatment and certification

Upon completion of the termite treatment a durable notice must be permanently fixed to the building in a prominent location, such as in the electrical metre box or the like, indicating:

- a) The method of termite risk management.
- b) The date of installation of the system
- c) Where a chemical barrier is used, its life expectancy as listed in the National Registration Authority lable.
- d) The installer's or manufacturers recommendations for the scope and frequency of future inspections for termite activity.
- 3. All wet areas within the development must be treated with a waterproofing system in accordance with the Building Code of Australia. All waterprofing system must be inspected and approved by the certifying authority. Installer must arrange for inspections and certification before the installation of any wall coverings. Upon completion the owner must be supplied with a written report of the method of treatment and certification
- 4. All structural Elements of the existing and proposed building must be checked and certifyied by a chartered Structural engineer, who must provide writen certification to the certifying authority and the owner
- 5. Owner and builder must be aware at all times of their obligation to comply with the requirements of the Basicx certificate. All requirements stipulated in the basicxs certificate must be meet and when installed must be inspected and approved by the certifying authority. Upon completion the owner must be supplied with a written report and certification

		AM	END	MENTS				
No	Date		escri	ntion				
110		Date Description						
		<b>es</b> 1	Ľ					
		<b>~~</b>	$\bigcirc$	) — —				
P. Chrysostomou								
No 12 Tallawalla street								
Beverly Hills 2209								
		N.S						
	Те	el (02) 955	4-93 <sup>′</sup>	74				
Client		(02) >00		, . 				
Chem	Mr	& Mrs Sotirio	s & Ma	aria Panagakis				
at No 87 Oak Drive								
Georges Hall NSW 2198								
	G	eorges Hall	11210 7	2198				
Ich								
JOD	Job Proposed Alterations & Additions							
	at No 87 Oak Drive							
	G	eorges Hall	NSW 2	2198				
Drawn	P.	Chrysosto	mou					
Design		Chrysosto		PROPOSED				
Checke	d <u>P.</u>	Chrysosto	mou	SITE PLAN				
Date	Dec	ember 2021		JIIL LAIN				
Scale	ass	shown						