

Building Sustainability Index www.basix.nsw.gov.au

## Single Dwelling

Certificate number: 1310013S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

**BASIX** 

Date of issue: Saturday, 28 May 2022

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary			
Project name	18 KOONAWARRA ST. VILLAWOOD - unit 1		
Street address	18 KOONAWARRA Street VILLAWOOD 2163		
Local Government Area	Canterbury-Bankstown Council		
Plan type and plan number	deposited 36612		
Lot no.	664/1		
Section no.	-		
Project type	attached dwelling house		
No. of bedrooms	4		
Project score			
Water	√ 40 Target 40		
Thermal Comfort	✓ Pass Target Pass		
Energy	✓ 50 Target 50		

Certificate	Prepared by
-------------	-------------

Name / Company Name: Sight Building Design

ABN (if applicable): 49226834060

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 1/11

## **Description of project**

BASIX

Project address	
Project name	18 KOONAWARRA ST. VILLAWOOD - unit
Street address	18 KOONAWARRA Street VILLAWOOD 2163
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan 36612
Lot no.	664/1
Section no.	-
Project type	
Project type	attached dwelling house
No. of bedrooms	4
Site details	
Site area (m²)	803
Roof area (m²)	172
Conditioned floor area (m2)	139.38
Unconditioned floor area (m2)	18.0
Total area of garden and lawn (m2)	128

Assessor details and thermal loads							
Assessor number	n/a						
Certificate number	n/a						
Climate zone	n/a						
Area adjusted cooling load (MJ/m².year)	n/a						
Area adjusted heating load (MJ/m².year)	n/a						
Ceiling fan in at least one bedroom	n/a						
Ceiling fan in at least one living room or other conditioned area	n/a						
Project score							
Water	<b>4</b> 0	Target 40					
Thermal Comfort	✓ Pass	Target Pass					
Energy	<b>✓</b> 50	Target 50					

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 2/11

## **Schedule of BASIX commitments**

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 20 square metres of the site.	V	<b>✓</b>	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 3 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 3 star in each bathroom in the development.		<b>✓</b>	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	V	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 80 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	V
The applicant must connect the rainwater tank to:			
all toilets in the development		~	-
<ul> <li>at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.)</li> </ul>		•	V
Swimming pool			
The swimming pool must not have a volume greater than 22 kilolitres.	V	V	

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 3/11

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The swimming pool must be outdoors.	<b>V</b>	V	

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 4/11

BASIX

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	V	<b>~</b>	-
The conditioned floor area of the dwelling must not exceed 300 square metres.	V	V	V
The dwelling must not contain open mezzanine area exceeding 25 square metres.	V	V	V
The dwelling must not contain third level habitable attic room.	V	~	
Floor, walls and ceiling/roof		1	
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground, 96.38 square metres	nil	
floor - above habitable rooms or mezzanine, 61 square metres, concrete	nil	
floor - suspended floor above garage, concrete	nil	
external wall - cavity brick	0.50 (or 1.17 including construction)	
external wall - brick veneer	1.86 (or 2.40 including construction)	
external wall - framed (weatherboard, fibre cement, metal clad)	2.00 (or 2.40 including construction)	
internal wall shared with garage - single skin masonry	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 3.5 (up), roof: foil/sarking	unventilated; dark (solar absorptance > 0.70)
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 3.5 (up), roof: thermocellular reflective	framed; medium (solar absorptance 0.475-0.70)

• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

Note

BASIX

Note • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 5/11

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Vindows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the pecifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	<b>→</b>	V
he dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	V	<b>~</b>	V
he following requirements must also be satisfied in relation to each window and glazed door:	~	<b>~</b>	V
<ul> <li>For the following glass and frame types, the certifier check can be performed by visual inspection.</li> </ul>			-
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			
<ul> <li>For other glass or frame types, each window and glazed door must be accompanied with certification showing a U value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range of those listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. Frame and glass types shown in the table below are for reference only.</li> </ul>			•
<ul> <li>Vertical external louvres and blinds must fully shade the window or glazed door beside which they are situated when fully drawn or closed.</li> </ul>		<b>V</b>	-
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total kylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 1.7 square metres that does not have to be listed in the table).	~	~	~

Skylight no.	Maximum area (square metres)	Туре	Shading device
S01	0.60	aluminium, moulded plastic single clear	no shading
S02	0.60	aluminium, moulded plastic single clear	no shading

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North-East facing					

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 6/11

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W01	600	3100	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
W02	2100	850	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
W03	2100	850	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
W04	600	2800	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
W05	600	850	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
W06	1200	2110	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
W07	600	2410	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
W08	600	2410	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
W09	600	1210	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	external louvre/vertical blind (adjustable)	not overshadowed
W10	600	2410	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
South-East facing					
W11	2600	1000	aluminium, single, clear	none	not overshadowed
W12	2100	3300	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed
W13	2600	1000	aluminium, single, clear	none	not overshadowed
North-West facing					
W14	2400	5000	aluminium, single, clear	verandah 5600 mm, 2900 mm above base of window or glazed door	not overshadowed
W15	600	850	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	external louvre/vertical blind (adjustable)	not overshadowed
W16	1200	2110	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 7/11

BASIX

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W17	1200	2110	aluminium, single, clear	external louvre/vertical blind (adjustable)	not overshadowed

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 8/11

BASIX

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	-	~	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 3-phase airconditioning; Energy rating: EER 3.5 - 4.0		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 3-phase airconditioning; Energy rating: EER 3.5 - 4.0		<b>V</b>	V
The cooling system must provide for day/night zoning between living areas and bedrooms.		<b>~</b>	•
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 3-phase airconditioning; Energy rating: EER 3.5 - 4.0		~	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 3-phase airconditioning; Energy rating: EER 3.5 - 4.0		~	~
The heating system must provide for day/night zoning between living areas and bedrooms.		<b>~</b>	V
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, not ducted; Operation control: manual switch on/off		<b>~</b>	•
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		<b>~</b>	~
Laundry: individual fan, not ducted; Operation control: manual switch on/off		<b>V</b>	V
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
at least 4 of the bedrooms / study;			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 9/11

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
at least 1 of the living / dining rooms;		<b>&gt;</b>	•
• the kitchen;			
all bathrooms/toilets;		, i	
• the laundry;		<b>~</b>	-
• all hallways;		<b>V</b>	V
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	V	V	V
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	-	~	-
Swimming pool			
The development must not incorporate any heating system for the swimming pool.		~	
The applicant must install a timer for the swimming pool pump in the development.		~	
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 10/11

## Legend

BASIX

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA\_3\_20\_0 Certificate No.: 1310013S Saturday, 28 May 2022 page 11/11