

BASIX[®]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1205754S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Sunday, 23 May 2021

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning,
Industry &
Environment

Project summary

Project name	310 Pine Brush Road Glen William
Street address	310 Pine Brush Road Glen William 2321
Local Government Area	Dungog Shire Council
Plan type and plan number	deposited 733190
Lot no.	31
Section no.	-
Project type	separate dwelling house
No. of bedrooms	3

Project score

Water	✓ 71	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 82	Target 45

Certificate Prepared by

Name / Company Name: Newcastle Bushfire Consulting

ABN (if applicable): 96831374298

Description of project

Project address

Project name	310 Pine Brush Road Glen William
Street address	310 Pine Brush Road Glen William 2321
Local Government Area	Dungog Shire Council
Plan type and plan number	Deposited Plan 733190
Lot no.	31
Section no.	-

Project type

Project type	separate dwelling house
No. of bedrooms	3

Site details

Site area (m ²)	572600
Roof area (m ²)	376
Conditioned floor area (m2)	183.0
Unconditioned floor area (m2)	14.0
Total area of garden and lawn (m2)	300

Assessor details and thermal loads

Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m ² .year)	n/a
Area adjusted heating load (MJ/m ² .year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a

Project score

Water	✓ 71	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 82	Target 45

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 6 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 6 star in each bathroom in the development.		✓	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 10000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 376 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> all toilets in the development the cold water tap that supplies each clothes washer in the development at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) all hot water systems in the development all indoor cold water taps (not including taps that supply clothes washers) in the development 		✓ ✓ ✓ ✓ ✓	✓ ✓ ✓ ✓ ✓

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - framed (weatherboard, fibre cement, metal clad)	2.00 (or 2.40 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 4.5 (up), roof: foil backed blanket (75 mm)	framed; medium (solar absorptance 0.475-0.70)
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 4.5 (up), roof: foil backed blanket (75 mm)	framed; medium (solar absorptance 0.475-0.70)

Note	• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.


















Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
<p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <ul style="list-style-type: none"> For the following glass and frame types, the certifier check can be performed by visual inspection. <ul style="list-style-type: none"> - Aluminium single clear - Aluminium double (air) clear - Timber/uPVC/fibreglass single clear - Timber/uPVC/fibreglass double (air) clear 	✓	✓	✓ ✓

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
North facing					
W01	2100	800	aluminium, single, clear	eave 2450 mm, 188 mm above head of window or glazed door	not overshadowed
W02	2100	800	aluminium, single, clear	eave 2450 mm, 188 mm above head of window or glazed door	not overshadowed
W03	2100	4400	aluminium, single, clear	eave 3965 mm, 188 mm above head of window or glazed door	not overshadowed
W04	2100	800	aluminium, single, clear	eave 2450 mm, 188 mm above head of window or glazed door	not overshadowed
W05	2100	800	aluminium, single, clear	eave 2450 mm, 188 mm above head of window or glazed door	not overshadowed
W06	400	1700	aluminium, single, clear	eave 450 mm, 464 mm above head of window or glazed door	not overshadowed
W07	400	1700	aluminium, single, clear	eave 450 mm, 464 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W08	400	1700	aluminium, single, clear	eave 450 mm, 464 mm above head of window or glazed door	not overshadowed
W09	400	1700	aluminium, single, clear	eave 450 mm, 464 mm above head of window or glazed door	not overshadowed
W10	400	1700	aluminium, single, clear	eave 450 mm, 464 mm above head of window or glazed door	not overshadowed
East facing					
W11	2100	3000	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W12	2100	600	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W13	2100	600	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W14	2100	1800	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
South facing					
W15	2100	900	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W16	2100	600	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W17	600	900	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W18	600	900	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W19	600	900	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W20	1200	1500	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W21	1200	1500	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W22	1200	1500	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
West facing					
W23	2100	600	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W24	2100	600	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed
W25	2100	600	aluminium, single, clear	eave 450 mm, 188 mm above head of window or glazed door	not overshadowed


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: solar (electric boosted) with a performance of 31 to 35 STCs or better.	✓	✓	✓
Cooling system			
The living areas must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		✓	✓
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		✓	✓
Heating system			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development: At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Laundry: natural ventilation only, or no laundry; Operation control: n/a		✓	✓
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps: <ul style="list-style-type: none"> at least 3 of the bedrooms / study; at least 1 of the living / dining rooms; the kitchen; 		✓ ✓ ✓	✓ ✓ ✓


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<ul style="list-style-type: none"> • all bathrooms/toilets; • the laundry; • all hallways; 		  	  
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.			
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.			
Alternative energy			
The applicant must install a photovoltaic system with the capacity to generate at least 2 peak kilowatts of electricity as part of the development. The applicant must connect this system to the development's electrical system.			
Other			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.			
The applicant must install a fixed outdoor clothes drying line as part of the development.			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.