

BASIX[®]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1266701S_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Monday, 04 April 2022

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning,
Industry &
Environment

Project summary

Project name	New Dwelling house_02
Street address	105 Ernest Street Lakemba 2195
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	deposited 4643
Lot no.	17
Section no.	-
Project type	separate dwelling house
No. of bedrooms	4

Project score

Water	✓ 40	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 52	Target 50

Certificate Prepared by

Name / Company Name: Nam Truong

ABN (if applicable): N/A

Description of project

Project address

Project name	New Dwelling house_02
Street address	105 Ernest Street Lakemba 2195
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan 4643
Lot no.	17
Section no.	-

Project type

Project type	separate dwelling house
No. of bedrooms	4

Site details

Site area (m ²)	639
Roof area (m ²)	258
Conditioned floor area (m2)	266.0
Unconditioned floor area (m2)	44.0
Total area of garden and lawn (m2)	270

Assessor details and thermal loads

Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m ² .year)	n/a
Area adjusted heating load (MJ/m ² .year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a

Project score

Water	✓ 40	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 52	Target 50

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 115 square metres of the site.	✓	✓	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 6 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		✓	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2500 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 258 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		✓	✓

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
floor - suspended floor above garage, concrete	nil	
external wall - cavity brick	0.50 (or 1.17 including construction)	
internal wall shared with garage - single skin masonry	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 4.25 (up), roof: thermocellular reflective	unventilated; medium (solar absorptance 0.475-0.70)

Note	• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.













Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
<p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <ul style="list-style-type: none"> For the following glass and frame types, the certifier check can be performed by visual inspection. <ul style="list-style-type: none"> - Aluminium single clear - Aluminium double (air) clear - Timber/uPVC/fibreglass single clear - Timber/uPVC/fibreglass double (air) clear For other glass or frame types, each window and glazed door must be accompanied with certification showing a U value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range of those listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. Frame and glass types shown in the table below are for reference only. Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column. 	✓	✓	✓ ✓ ✓
	✓	✓	✓

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
North facing					
GW01	1500	2800	aluminium, single, clear	none	2-4 m high, 2-5 m away
FW04	600	1800	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	eave 600 mm, 200 mm above head of window or glazed door	not overshadowed
FW01	600	2100	aluminium, single, clear	eave 600 mm, 200 mm above head of window or glazed door	not overshadowed
GW03	1500	2100	aluminium, single, clear	none	2-4 m high, 2-5 m away
GW02	1500	1600	aluminium, single, clear	none	2-4 m high, 2-5 m away

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
GW03	1500	2100	aluminium, single, clear	none	2-4 m high, 2-5 m away
BW02	600	1200	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	none	2-4 m high, 2-5 m away
FW03	5300	1500	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	eave 600 mm, 200 mm above head of window or glazed door	not overshadowed
FW01	600	2100	aluminium, single, clear	eave 600 mm, 200 mm above head of window or glazed door	not overshadowed
BW03	900	1800	aluminium, single, clear	none	2-4 m high, 2-5 m away
East facing					
GW04	1500	2500	aluminium, single, clear	solid overhang 2000 mm, 400 mm above head of window or glazed door	not overshadowed
FD01	2100	2400	aluminium, single, clear	solid overhang 2000 mm, 200 mm above head of window or glazed door	not overshadowed
FD01	2100	2400	aluminium, single, clear	solid overhang 2000 mm, 200 mm above head of window or glazed door	not overshadowed
South facing					
GW05	900	1500	aluminium, single, clear	none	2-4 m high, 2-5 m away
GW05	900	1500	aluminium, single, clear	none	2-4 m high, 2-5 m away
BW03	900	1800	aluminium, single, clear	none	2-4 m high, 2-5 m away
FW01	600	2100	aluminium, single, clear	eave 600 mm, 200 mm above head of window or glazed door	not overshadowed
FW01	600	2100	aluminium, single, clear	eave 600 mm, 200 mm above head of window or glazed door	not overshadowed
FW02	600	1200	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	eave 600 mm, 200 mm above head of window or glazed door	not overshadowed
GW06	1200	1290	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	none	2-4 m high, 2-5 m away
BW02	900	1290	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	none	2-4 m high, 2-5 m away


Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
GW05	900	1500	aluminium, single, clear	none	2-4 m high, 2-5 m away
FW02	600	1200	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	eave 600 mm, 200 mm above head of window or glazed door	not overshadowed
GW08	1200	2000	aluminium, single, clear	none	2-4 m high, 2-5 m away
West facing					
GD02	2400	3600	aluminium, single, clear	solid overhang 3000 mm, 200 mm above head of window or glazed door	not overshadowed
FW02	600	1200	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	solid overhang 2000 mm, 200 mm above head of window or glazed door	not overshadowed
GW03	1500	2100	aluminium, single, clear	solid overhang 3000 mm, 200 mm above head of window or glazed door	not overshadowed
BD01	2100	2900	aluminium, single, clear	solid overhang 500 mm, 200 mm above head of window or glazed door	not overshadowed
FD01	2100	2400	aluminium, single, clear	solid overhang 2000 mm, 200 mm above head of window or glazed door	not overshadowed
FD01	2100	2400	aluminium, single, clear	solid overhang 2000 mm, 200 mm above head of window or glazed door	not overshadowed
BD01	2100	2900	aluminium, single, clear	solid overhang 500 mm, 200 mm above head of window or glazed door	not overshadowed


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 4 stars.	✓	✓	✓
Cooling system			
The living areas must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		✓	✓
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		✓	✓
Heating system			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development: At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps: <ul style="list-style-type: none"> at least 4 of the bedrooms / study; at least 1 of the living / dining rooms; the kitchen; 		✓ ✓ ✓	✓ ✓ ✓


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<ul style="list-style-type: none"> • all bathrooms/toilets; • the laundry; • all hallways; 		  	  
Natural lighting			
The applicant must install a window and/or skylight in 4 bathroom(s)/toilet(s) in the development for natural lighting.			
Other			
The applicant must install a gas cooktop & gas oven in the kitchen of the dwelling.			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.			
The applicant must install a fixed indoor or sheltered clothes drying line as part of the development.			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.