page 1/6

BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions Certificate number: A465384

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 66/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary Date of issue: Monday, 04, July 2022 To be valid, this certificate must be lodged within 3 months of the date of issue.



Project name	298 Edgar St Condell Park				
Project address Project name Street address Local Government Area Plan type and number	298 edgar Street condell park 2200				
Local Government Area	Canterbury-Bankstown Council				
Plan type and number	Deposited Plan 159803				
Lot number	В				
Section number					
Project type	Project type				
Dwelling type	Separate dwelling house				
Type of alteration and addition	My renovation work is valued at \$50,000 or more and does not include a pool (and/or spa).				





BASIX Certificate number: A465384

page 2/6

 \checkmark

Show on DA Plans

 \checkmark

Certificate Prepared by (please complete before submitting to Council or PCA) Name / Company Name: Astley Homes ABN (if applicable): 90128616090

Planning, Industry & Environment

Planning, Industry & Environment

BASIX Certificate number: A465384

page 4 / 6

~

 \checkmark

 \checkmark

1

 \checkmark

 \checkmark

5

Building Sustainability Index www.basix.nsw.gov.au

BASIX Certificate numbe

	BASIX Certificate number: A465384					
	Glazing requirements	Show on DA Plans	Show of CC/CD Plans & specs			
	Windows and glazed doors					
The applicant must install the windows, glazed doors and shading devices, in accordance with the specifications listed in the table below. Relevant overshadowing specifications must be satisfied for each window and glazed door.						
	The following requirements must also be satisfied in relation to each window and glazed door:					
Each window or glazed door with standard aluminium or timber frames and single clear or toned glass may either match the description, or, have a U-value and a Solar Heat Gain Coefficient (SHGC) no greeter than that listed in the table below. Total system U-values and SHGCs must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.						
	For projections described in millimetres, the leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 mm above the head of the window or glazed door and no more than 2400 mm above the sill.					
Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.						
	Pergolas with fixed battens must have battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.					
	Overshadowing buildings or vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column in the table below.					
	Windows and glazed doors glazing requirements					
	Window / door Orientation Area of Overshadowing Shading device Frame and glass type no. glass Height Distance inc. rest					

ow / door	Orientation		Oversnadowing		Shading device	Frame and glass type	
		glass inc. frame (m2)	Height (m)	Distance (m)			
	N	1.5	870	1770	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)	
	N	1.5	870	1770	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)	
	S	1.5	870	1770	eave/verandah/pergola/balcony >=450 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)	
	S	1.5	870	1770	eave/verandah/pergola/balcony >=750 mm	standard aluminium, single clear, (or U-value: 7.63, SHGC: 0.75)	

Planning, Industry & Environmen

Planning, Industry & Environment

Building Sustainability Index www.basix.nsw.gov.au

In these commitments, "applicant" means the person carrying out the development.

Building Sustainability Index www.basix.nsw.gov.au

PROJECT TITLE REVISIONS
 ISSUE
 DATE
 DESCRIPTION

 1
 01.07.22
 ISSUED FOR DEVELOPMENT APPLICATION
BY K.H BDAA Accreditation Number: 6614 PROJECT ADDRESS 123 Smith St Sydney, NSW 2200 Class 2 Registration Number: DEP0001004 **ASTLEY HOMES P**: 0448 923 373 NOTES ACCREDITED E: info@astleyhomes.com.au Dimensions - Contractors to check all dimensions on site prior to commend construction. Do not scale from this drawing. Use given dimensions. Copyright © This document is copyright. All rights reserved. BUILDING DESIGNER



Planning, Industry & Environment

		э	

DRAWING TITLE Basix DRAWING NO. DA 13 DATE OF ISSU 01.07.22

ISSUED FOR DEVELOPMENT APPLICATION

REVISION NO. 1 DRAWING SCALE

SHEET SIZE

Building Sustainability Index www.basix.nsw.gov.au

Commitments identified with a "v" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.

Commitments identified with a *v* in the *Show on CC/CDC plans & specs* column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a "4/" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

page 6 / 6

			DA Plans	CC/CDC Plans & specs	Check	
ad construction (floor(s), walls, and ceilings/roots) in accordance with the specifications listed in alion is not required where the area of new construction is less than 2m2, b) insulation specified where insulation already exists.				\checkmark	~	
	Additional insulation required (R-value)	Other specifications				
	nil					
	R1.16 (or R1.70 including construction)					
	ceiling: R2.50 (up), roof: foil/sarking	medium (solar absorptance 0.475 - 0.70)				

Building Sustainability Index www.basix.nsw.gov.au

Show on Show on Certifier