

BASIX[®]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1363014S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Tuesday, 13 December 2022

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning,
Industry &
Environment

Project summary

Project name	197 Cooper road, Yagoona
Street address	197 Cooper Road Yagoona 2199
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	deposited 35104
Lot no.	8
Section no.	-
Project type	separate dwelling house
No. of bedrooms	5

Project score

Water	✓ 42	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 50	Target 50

Certificate Prepared by

Name / Company Name: SI TRAN

ABN (if applicable): N/A

Description of project

Project address

Project name	197 Cooper road, Yagoona
Street address	197 Cooper Road Yagoona 2199
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan 35104
Lot no.	8
Section no.	-

Project type

Project type	separate dwelling house
No. of bedrooms	5

Site details

Site area (m ²)	613
Roof area (m ²)	260
Conditioned floor area (m2)	280.0
Unconditioned floor area (m2)	20.0
Total area of garden and lawn (m2)	100

Assessor details and thermal loads

Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m ² .year)	n/a
Area adjusted heating load (MJ/m ² .year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a

Project score

Water	✓ 42	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 50	Target 50

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 4.5 but <= 6 L/min) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		✓	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 900 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 60 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) all hot water systems in the development 		✓ ✓	✓ ✓

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - brick veneer	1.86 (or 2.40 including construction)	
external wall - cavity brick	0.50 (or 1.17 including construction)	
ceiling and roof - flat ceiling / pitched roof	ceiling: 2.75 (up), roof: foil/sarking	unventilated; light (solar absorptance < 0.475)

Note	<ul style="list-style-type: none"> Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	<ul style="list-style-type: none"> In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
<p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <ul style="list-style-type: none"> For the following glass and frame types, the certifier check can be performed by visual inspection. <ul style="list-style-type: none"> - Aluminium single clear - Aluminium double (air) clear - Timber/uPVC/fibreglass single clear - Timber/uPVC/fibreglass double (air) clear 	✓	✓	✓ ✓

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
North facing					
WB2	600	1210	aluminium, single, clear	none	not overshadowed
WB3	600	1210	aluminium, single, clear	none	not overshadowed
WB4	600	1210	aluminium, single, clear	none	not overshadowed
W03	2200	900	aluminium, single, clear	none	not overshadowed
W04	2200	900	aluminium, single, clear	none	not overshadowed
W05	800	800	aluminium, single, clear	none	not overshadowed
W06	600	1800	aluminium, single, clear	none	not overshadowed
W06	600	1800	aluminium, single, clear	none	not overshadowed
W21	2100	800	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W22	800	800	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W23	800	1800	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W24	800	1800	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
East facing					
W09	850	2410	aluminium, single, clear	none	not overshadowed
W10	850	610	aluminium, single, clear	none	not overshadowed
W25	850	2410	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W29	850	2410	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
South facing					
WB5	800	1500	aluminium, single, clear	none	not overshadowed
WB6	800	1500	aluminium, single, clear	none	not overshadowed
W13	1500	800	aluminium, single, clear	none	not overshadowed
W14	1500	800	aluminium, single, clear	none	not overshadowed
W15	1500	800	aluminium, single, clear	none	not overshadowed
W11	3500	500	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W12	3500	500	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W26	2400	1000	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W27	2700	1000	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W28	2400	1000	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W30	1500	800	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W31	1500	800	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W36	3500	500	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
West facing					
WB1	1220	1800	aluminium, single, clear	none	not overshadowed
W01	4600	500	aluminium, single, clear	none	not overshadowed
W02	4600	500	aluminium, single, clear	none	not overshadowed
W16	2300	500	aluminium, single, clear	none	not overshadowed
W17	2576	500	aluminium, single, clear	none	not overshadowed
W32	500	2100	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W33	500	2100	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W34	500	2100	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W35	500	2100	aluminium, single, clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 5 stars.	✓	✓	✓
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 3-phase airconditioning; Energy rating: EER 3.5 - 4.0		✓	✓
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 3-phase airconditioning; Energy rating: EER 3.5 - 4.0		✓	✓
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 3-phase airconditioning; Energy rating: EER 3.5 - 4.0		✓	✓
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 3-phase airconditioning; Energy rating: EER 3.5 - 4.0		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, not ducted; Operation control: manual switch on/off		✓	✓
Kitchen: individual fan, not ducted; Operation control: manual switch on/off		✓	✓
Laundry: individual fan, not ducted; Operation control: manual switch on/off		✓	✓
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
• at least 4 of the bedrooms / study; dedicated		✓	✓
• the kitchen; dedicated		✓	✓
• all bathrooms/toilets; dedicated		✓	✓


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<ul style="list-style-type: none"> the laundry; dedicated 		✓	✓
<ul style="list-style-type: none"> all hallways; dedicated 		✓	✓
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	✓	✓	✓
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	✓	✓	✓
Other			
The applicant must install a gas cooktop & gas oven in the kitchen of the dwelling.		✓	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		✓	
The applicant must install a fixed outdoor clothes drying line as part of the development.		✓	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.