# **BASIX**<sup>°</sup>Certificate

Building Sustainability Index www.basix.nsw.gov.au

### Single Dwelling

Certificate number: 1393878S\_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary Date of issue: Thursday, 15 June 2023 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project summary				
Project name	SD1_221 William Street, Yagoona_02			
Street address	221 William Street Yagoona 2199			
Local Government Area	Canterbury-Bankstown Council			
Plan type and plan number	deposited 1150340			
Lot no.	1			
Section no.	-			
Project type	separate dwelling house - secondary dwelling			
No. of bedrooms	2			
Project score				
Water	V 43 Target 40			
Thermal Comfort	V Pass Target Pass			
Energy	V 50 Target 50			

Name / Company Name: Concetto Design & Associates

ABN (if applicable): 81232070821

## **Description of project**

#### Project address

_02
ıry

Assessor details and thermal lo	oads	
Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m <sup>2</sup> .year)	n/a	
Area adjusted heating load (MJ/m <sup>2</sup> .year)	n/a	
Ceiling fan in at least one bedroom	n/a	
Ceiling fan in at least one living room or other conditioned area	n/a	
Project score		
Water	V 43 Target 40	
Thermal Comfort	Version Pass Target Pass	
Energy	✓ 50 Target 50	

#### Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		<ul> <li></li> </ul>	~
The applicant must install a toilet flushing system with a minimum rating of 6 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 6 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 6 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 100 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		<ul> <li>Image: A second s</li></ul>	~
<ul> <li>the cold water tap that supplies each clothes washer in the development</li> </ul>		<ul> <li>Image: A second s</li></ul>	~

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	<b>~</b>	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - other/undecided	2.40 (including construction)	
ceiling and roof - flat ceiling / pitched roof	ceiling: 4.5 (up), roof: foil/sarking	unventilated; dark (solar absorptance > 0.70)

• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

Note • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check	
Windows, glazed doors and skylights				
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~	
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~	
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~	
• For the following glass and frame types, the certifier check can be performed by visual inspection.			<b>v</b>	
- Aluminium single clear				
- Aluminium double (air) clear				
- Timber/uPVC/fibreglass single clear				
- Timber/uPVC/fibreglass double (air) clear				
<ul> <li>Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column.</li> </ul>	<b>~</b>	<b>~</b>	~	

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
W04	1540	1090	aluminium, single, clear	eave 450 mm, 250 mm above head of window or glazed door	1-2 m high, <1.5 m away
W02	1540	610	aluminium, single, clear	eave 450 mm, 250 mm above head of window or glazed door	1-2 m high, <1.5 m away
W03	1540	610	aluminium, single, clear	eave 450 mm, 250 mm above head of window or glazed door	1-2 m high, <1.5 m away
W05	940	1810	aluminium, single, clear	eave 450 mm, 250 mm above head of window or glazed door	1-2 m high, <1.5 m away
South facing					
W08	510	1570	aluminium, single, clear	eave 450 mm, 250 mm above head of window or glazed door	1-2 m high, <1.5 m away

			_		
Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W07	940	1810	aluminium, single, clear	eave 450 mm, 250 mm above head of window or glazed door	1-2 m high, <1.5 m away
W06	940	1810	aluminium, single, clear	eave 450 mm, 250 mm above head of window or glazed door	1-2 m high, <1.5 m away
West facing					
W01	2140	1810	aluminium, single, clear	eave 450 mm, 250 mm above head of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	~	~	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: airconditioning ducting only; Energy rating: n/a		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: airconditioning ducting only; Energy rating: n/a		~	~
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: airconditioning ducting only; Energy rating: n/a		~	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: airconditioning ducting only; Energy rating: n/a		~	~
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual on / timer off		~	~
Kitchen: individual fan, ducted to façade or roof; Operation control: manual on / timer off		~	~
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	~
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
at least 2 of the bedrooms / study; dedicated		<b>~</b>	~
<ul> <li>at least 1 of the living / dining rooms; dedicated</li> </ul>		✓	~
the kitchen; dedicated		<b>~</b>	<b>v</b>

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets; dedicated		~	~
the laundry; dedicated		<b>~</b>	~
all hallways; dedicated		<b>~</b>	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	<b>~</b>	<b>~</b>	~
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed indoor or sheltered clothes drying line as part of the development.		~	

#### Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vi in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a vi in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vi in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.