

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1408207S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

BASIX

Date of issue: Wednesday, 19 July 2023

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary				
Project name	A-23018 - 8A Woods Road, Sefton NSW			
Street address	8A Woods Road Se	efton 2162		
Local Government Area	Canterbury-Banksto	own Council		
Plan type and plan number	deposited 617038	deposited 617038		
Lot no.	2	2		
Section no.	-			
Project type	separate dwelling h dwelling	separate dwelling house - secondary dwelling		
No. of bedrooms	4	4		
Project score				
Water	4 0	Target 40		
Thermal Comfort	✓ Pass	Target Pass		
Energy	✓ 51	Target 50		

Certificate Prepared by
Name / Company Name: Statiker
ABN (if applicable): 55319613625

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 1/10

Description of project

BASIX

Project address	
Project name	A-23018 - 8A Woods Road, Sefton NSW
Street address	8A Woods Road Sefton 2162
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan 617038
Lot no.	2
Section no.	-
Project type	
Project type	separate dwelling house - secondary dwelling
No. of bedrooms	4
Site details	
Site area (m²)	967
Roof area (m²)	144
Conditioned floor area (m2)	70.93
Unconditioned floor area (m2)	6.43
Total area of garden and lawn (m2)	451
Roof area (m2) of the existing dwelling	193
No. of bedrooms in the existing dwelling	5

Assessor details and thermal loads							
Assessor number	n/a						
Certificate number	n/a						
Climate zone	n/a						
Area adjusted cooling load (MJ/m².year)	n/a						
Area adjusted heating load (MJ/m².year)	n/a						
Ceiling fan in at least one bedroom	n/a						
Ceiling fan in at least one living room or other conditioned area	n/a						
Project score							
Water	✓ 40 Target 40						
Thermal Comfort	✓ Pass Target Pass						
Energy	✓ 51 Target 50						

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 2/10

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 451.24 square metres of the site.	~	~	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		~	V
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		>	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 1500 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 144.32 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		~	-
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	•
a tap that is located within 10 metres of the swimming pool in the development		~	V
Swimming pool	·		

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 3/10

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The swimming pool must not have a volume greater than 42 kilolitres.	V	~	
The swimming pool must have a pool cover.		~	
The swimming pool must be outdoors.	V	~	

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 4/10

BASIX

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	V	~	-
The conditioned floor area of the dwelling must not exceed 300 square metres.	V	V	V
The dwelling must not contain open mezzanine area exceeding 25 square metres.		V	V
The dwelling must not contain third level habitable attic room.		V	V
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	V	-	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - brick veneer	2.86 (or 3.40 including construction)	
external wall - framed (weatherboard, fibre cement, metal clad)	3.00 (or 3.40 including construction)	
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 3.76 (up), roof: foil/sarking	framed; light (solar absorptance < 0.475)
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 3.82 (up), roof: foil/sarking	framed; light (solar absorptance < 0.475)

Note	Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 5/10

BASIX

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check		
Windows, glazed doors and skylights					
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	-	→	-		
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.		~	~		
The following requirements must also be satisfied in relation to each window and glazed door:		<u> </u>	~		
• For the following glass and frame types, the certifier check can be performed by visual inspection.			V		
- Aluminium single clear					
- Aluminium double (air) clear					
- Timber/uPVC/fibreglass single clear					
- Timber/uPVC/fibreglass double (air) clear					
 Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column. 	-	•	V		

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing			
North facing	North facing							
D01	2100	2650	aluminium, single, clear	verandah 3650 mm, 2700 mm above base of window or glazed door	not overshadowed			
W08	600	600	aluminium, single, clear	eave 450 mm, 800 mm above head of window or glazed door	1-2 m high, <1.5 m away			
East facing								
W01	2000	1500	aluminium, single, clear	eave 450 mm, 1200 mm above head of window or glazed door	not overshadowed			
W02	1300	1500	aluminium, single, clear	eave 450 mm, 1200 mm above head of window or glazed door	not overshadowed			
W03	1300	1500	aluminium, single, clear	eave 450 mm, 1200 mm above head of window or glazed door	not overshadowed			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 6/10

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W09	1300	1500	aluminium, single, clear	eave 450 mm, 600 mm above head of window or glazed door	not overshadowed
South facing					
W07	600	600	aluminium, single, clear	eave 450 mm, 1300 mm above head of window or glazed door	1-2 m high, <1.5 m away
W10	600	1500	aluminium, single, clear	eave 450 mm, 800 mm above head of window or glazed door	not overshadowed
West facing					
W04	1300	1500	aluminium, single, clear	eave 450 mm, 500 mm above head of window or glazed door	not overshadowed
W05	600	1800	aluminium, single, clear	eave 450 mm, 1100 mm above head of window or glazed door	not overshadowed
W06	600	600	aluminium, single, clear	eave 450 mm, 500 mm above head of window or glazed door	not overshadowed

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 7/10

BASIX

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 5 stars.	~	✓	-
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 5 star (average zone)		→	
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 5 star (average zone)		~	~
Heating system			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		→	~
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	V
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, not ducted; Operation control: manual switch on/off		•	-
Kitchen: individual fan, not ducted; Operation control: manual switch on/off		•	-
Laundry: individual fan, not ducted; Operation control: manual switch on/off		✓	•
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
at least 4 of the bedrooms / study; dedicated		•	-
at least 2 of the living / dining rooms; dedicated		•	-
the kitchen; dedicated			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 8/10

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets; dedicated		~	~
• the laundry; dedicated		✓	V
all hallways; dedicated		~	V
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	-	~	~
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	-	~	~
Swimming pool			
The development must not incorporate any heating system for the swimming pool.		~	
The applicant must install a timer for the swimming pool pump in the development.		~	
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 9/10

Legend

BASIX

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1408207S Wednesday, 19 July 2023 page 10/10