GENERAL

- 1. THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL AND SPECIFICATIONS AND WITH SUCH OTHER WRITTEN INSTRUCTIONS AS MAY BE ISSUED DURING THE COURSE OF THE CONTRACT. ALL DISCREPANCIES SHALL BE REFERRED TO THE OWNER FOR DECISION BEFORE PROCEEDING WITH THE WORK.
- 2. DIMENSIONS SHALL NOT BE OBTAINED BY SCALING THE DRAWINGS.
- 3. SETTING OUT DIMENSIONS SHOWN ON THE DRAWING SHALL BE VERIFIED BY THE CONTRACTOR.
- 4. DURING CONSTRUCTION, THE STRUCTURE SHALL BE MAINTAINED IN A STABLE CONDITION AND NO PART SHALL BE OVER-STRESSED.

STORMWATER DRAINAGE

- 1. STORMWATER DRAINAGE SHALL BE GENERALLY IN ACCORDANCE WITH AS 3500.3.
- 2. PIPES OF 300mm DIA. AND UNDER SHALL BE UPVC TO AS 1254.
- 3. PIPES OF 375mm DIA. AND LARGER SHALL BE FRC OR CONCRETE CLASS 2 TO AS 1342, RUBBER RING JOINTED UNO.
- 4. PIPES UP TO 150mm DIA. SHALL BE LAID AT A MINIMUM GRADE OF 1.0%. PIPES 225mm DIA. AND OVER TO BE LAID AT A MINIMUM GRADE OF 0.5%. UNO. BEDDING MATERIAL TO AS 2032 OR AS 3725 AS APPROPRIATE.
- 5. MINIMUM COVER TO PIPES 300mm DIA. AND OVER GENERALLY SHALL BE 450mm IN CARPARK & ROADWAY AREAS UNO.
- 6. BACKFILL TRENCHES WITH APPROVED FILL, SUCH AS SANDY LOAM, COMPACTED IN 200mm LAYERS TO 98% OF STANDARD DENSITY TO AS 1289. 5.1.1.
- 7. ANY PIPES OVER 16% GRADE SHALL HAVE CONCRETE BULKHEADS AT ALL JOINTS IN ACCORDANCE WITH AS 3500.3.2.
- 8. PITS SHALL BE OF REINFORCED CONCRETE CONSTRUCTION AS DETAILED. METAL GRATES AT LEVELS INDICATED ALL PITS DEEPER THAN 1000mm TO HAVE CLIMB IRONS.
- 9. BUILD INTO UPSTREAM FACE OF ALL PITS A 3.0m SUBSOIL LINE FALLING TO PITS TO MATCH PIT INVERT.
- 10. ALL LINES TO BE 100 DIA. AT 1% MIN. GRADE (U.N.O.)
- 11. ALL PITS TO BE BENCHED TO HALF PIPE SECTION AND TO HAVE GALVANISED STEEL GRATES AND SURROUNDS.
- 12. ALL PITS TO BE 600 SQUARE UNLESS NOTED OTHERWISE.
- 13. PITS & DOWNPIPE LOCATIONS AND LEVELS MAY BE VARIED TO SUIT SITE CONDITIONS AFTER CONSULTING THE ENGINEER.
- 14. ALL PLANTER BOXES AND BALCONIES TO BE CONNECTED TO THE PROPOSED STORMWATER DRAINAGE LINE.
- 15. SUBSOIL LINE: PIPES AND FITTINGS SHALL BE PERFORATED PLASTIC TO AS 2439 PART 1. LAY PIPES ON FLOOR OF TRENCH GRADED 1% AND OVERLAY WITH FILTER MATERIAL EXTENDING TO WITHIN 200mm OF SURFACE. PROVIDE FILTER FABRIC OF PERMEABLE POLYPROPYLENE BETWEEN FILTER MATERIAL AND TOPSOIL.

RAINWATER TANK NOTES


- PUMP FOR RAINWATER TANK TO BE CONNECTED TO TOILETS, LAUNDRY AND GARDEN TAP FOR IRRIGATION.
- 1. PUMP MUST HAVE MAINS WATER BACKUP WITH AN APPROVED BACKFLOW PREVENTION DEVICE. DEVICE TO BE ACCESSIBLE FOR TESTING.
- 2. A FIRST FLUSH DEVICE OR FILTER BAG IS TO BE INSTALLED.
- 3. RAINWATER TANK MUST NOT BE CONNECTED TO THE MAIN DRINKING WATER SUPPLY.
- 4. RAINWATER TANK MUST CONTAIN A BYPASS OF THE PUMP IN THE EVENT OF A POWER FAILURE.
- 5. RAINWATER TANK MUST BE CONSTRUCTED IN ACCORDANCE WITH AUSTRALIAN STANDARD. AS/NZ 3500.1.2-2021: NATIONAL PLUMBING AND DRAINAGE WATER SUPPLY- ACCEPTABLE SOLUTIONS, WHICH PROVIDES GUIDANCE ON THE DESIGN OF STORMWATER AND RAINWATER REUSE SYSTEMS.
- 6. RAINWATER TANK MUST BE PROVIDED WITH AN AIR GAP (SEE AS/NZ 3500.1.2 AND AS2845.2)
- 7. RAINWATER TANK MUST BE KEPT WELL MAINTAINED AND CLEANED IN ACCORDANCE WITH THE MANUFACTURING REQUIREMENTS AND THE REQUIREMENTS OF SYDNEY WATER.

SYN	SYMBOLS & NOTATION					
	PROPOSED STORMWATER DRAINAGE LINE Ø100 @ 1% MIN GRADE UNLESS NOTED OTHERWISE					
——————————————————————————————————————	Ø90 AG LINE CONNECT TO STORMWATER OUTLET OR VERTICAL SLOT DRAIN					
	GRATED PIT					
150 TG	150 WIDE TRENCH GRATE					
- HP	DENOTES HIGH POINT IN EAVE GUTTER					
DP 125	DOWN PIPE SIZE AND PROJECTION					
DPS 125	DOWN PIPE SPREADER SIZE AND PROJECTION					
1	OVERLAND FLOWS					

BEFORE EXCAVATION FOR PIPEWORK LOCATE DEPTH OF EXISTING SERVICES & CONTACT DIAL BEFORE YOU DIG


IFD TABLE								
DURATION	ARI (Yr)	AEP (%)	INTENSITY (mm/Hr)					
5 mins	20	5	187					
5 mins	100	1	242					

Α	ISSUED FOR DA	09/06/2023	W.T	PROPOSED DUAL OCCUPANCY		m	MSL Consulting	Drawn W. T	Date 09/06/2023
				LOT 37 DP 232662	ARCHITECTURE REFERENCE:	U L	Engineers Pty Limited ABN 72 903 090 591 ACN 142 291 165	Checked/Approved	Scale
				13 GOWLLAND PARADE PANANIA NSW 2213		Suite 102 - 62 Harbour St. Wollongong NSW PO Box 567 Dapto NSW p. 02 4226 5247		Michael Pereira B.E (civil) MIEAust NER	NTS @ A3
	AMENDMENTS		PREPARED FOR:- TONY MARTORANO			a: info@melanginaare.com.gu	Job No 23150 Sheet No CO1	REV A	



UPPER ROOF DRAINAGE PLAN

SCALE 1:200



LOWER ROOF DRAINAGE PLAN

SCALE 1:200

ALL GUTTERS TO HAVE A MINIMUM CROSS SECTIONAL AREA OF 9600mm² U.N.O. EAVES GUTTERS, INCLUDING DOWNPIPES TO BE INSTALLED SO THAT WATER WILL NOT FLOW BACK INTO THE BUILDING. ALL GUTTERS TO BE INSTALLED WITH A MINIMUM 1:500 GRADE OR STEEPER. ALL DOWNPIPES TO BE MIN. Ø125 OR 100x75mm U.N.O AND FITTED VERTICALLY TO THE SOLE OF EAVES GUTTERS.

GUTTERS AND DOWNPIPES TO BE INSTALLED IN GENERAL ACCORDANCE WITH AS3500.3 (2021).

Α	ISSUED FOR DA	09/06/2023	W.T	PROPOSED DUAL OCCUPANCY	i
				LOT 37 DP 232662	ARCHITECTURE REFERENCE:
				13 GOWLLAND PARADE PANANIA NSW 2213	MARTOR DESIGN
	AMENDMENTS			PREPARED FOR:- TONY MARTORANO	




ABN 72 903 080 591
ACN 142 291 165
Suite 102 - 62 Harbour St. Wollongong NSW
PO Box 667 Dapto NSW
p: 02 4226 5247
e: info@mslengineers.com.au
w: www.mslengineers.com.au

Drawn W.T	Date 09/06/2023
Checked/Approved Michael Pereira B.E (civil) MIEAust NER	Scale AS SHOWN @ A3
Job No 23150 Sheet No CO2	REV A

OSD IS NOT REQUIRED AS THE POST-DEVELOPMENT IMPERVIOUS AREA IS LESS THAN 66% OF THE SITE AREA, IN ACCORDANCE WITH COUNCIL'S DEVELOPMENT ENGINEERING STANDARDS - CLAUSE 10.1.2. REFER TO DRAWING CO4 FOR CATCHMENT CALCULATION.

ALL EXISTING LEVELS TO BE CONFIRMED ON SITE AND ENGINEER TO BE NOTIFIED PRIOR TO COMMENCEMENT OF WORK.


DEPTH AND LOCATION OF ALL EXISTING SERVICES TO BE CONFIRMED BY BUILDER ON SITE. ENGINEER TO BE NOTIFIED.



Α	ISSUED FOR DA	09/06/2023	W.T	PROPOSED DUAL OCCUPANCY	4
				LOT 37 DP 232662	ARCHITECTURE REFERENCE:
				13 GOWLLAND PARADE	MARTOR DESIGN
	AMENDMENTS			PANANIA NSW 2213 PREPARED FOR:-TONY MARTORANO	

MSL Consulting
Engineers Pty Limited
ABN 72 903 080 591
ACN 142 291 165
Suite 102 - 62 Harbour St. Wollongong NSW
PO Box 567 Dapto NSW
p: 02 4226 5247
e: info@mslengineers.com.au
w: www.mslengineers.com.au

Drawn W.T	Date 09/06/2023
Checked/Approved Michael Pereira B.E (civil) MIEAust NER	Scale AS SHOWN @ A3
Job No 23150 Sheet No CO3	REV A




Α	ISSUED FOR DA	09/06/2023	W.T	PROPOSED DUAL OCCUPANCY		
				LOT 37 DP 232662 13 GOWLLAND PARADE	ARCHITECTURE REFERENCE: MARTOR DESIGN	
	AMENDMENTS	•		PANANIA NSW 2213 PREPARED FOR:-TONY MARTORANO		

MSL Consulting
Engineers Pty Limited
ABN 72 903 080 591
ACN 142 291 165
Suite 102 - 62 Harbour St. Wollongong NSW
PO Box 567 Dapto NSW
p: 02 4226 5247
e: info@mslengineers.com.au
w: www.mslengineers.com.au



Drawn W.T	Date 09/06/2023
Checked/Approved Michael Pereira B.E (civil) MIEAust NER	Scale AS SHOWN @ A3
Job No 23150 Sheet No CO4	REV A



Α	ISSUED FOR DA	09/06/2023	W.T	PROPOSED DUAL OCCUPANCY		m	MSL Consulting	Drawn w. T	Date 09/06/2023
				LOT 37 DP 232662 ARCHITECTURE REFERENCE: 13 GOWLLAND PARADE MARTOR DESIGN		UL	ACN 142 291 165 Suite 102 - 62 Harbour St. Wollongong NSW	Checked/Approved Michael Pereira B.E (civil) MIEAust NER	Scale AS SHOWN @ A3
	AMENDMENTS		PANANIA NSW 2213 PREPARED FOR:- TONY MARTORANO			p: U2 4225 5247 e: info@mslengineers.com.au	Job No 23150 Sheet N	o C05 REV A	

