

PROPOSED SUBDIVISION & SEMI DETACHED DWELLINGS AT
19 PARK STREET, CAMPSIE

Existing driveway & layback to be extended

New driveway & laybacks

- Timber framed roof to
- National Timber Framing Code & AS1684
 - Refer structural engineers details
 - To external finishes schedule
 - To comply with BASIX requirements

WINDOW SCHEDULE	
Window No.	Window Size (W x H)
W1	900 x 2700
W2	900 x 2700
W3	3540 x 2700
W4	3400 x 2700
W5	3230 x 3060
W6	2700 x 1200
W7	2700 x 1200
W8	2700 x 1200
W9	2700 x 1200
W10	2700 x 1200
W11	2700 x 1200
W12	1200 x 2050
W13	1000 x 2050
W14	1000 x 2050
W15	1000 x 2050
W16	950 x 2050
W17	950 x 2050
W18	950 x 2050
W19	1100 x 2050
W20	850 x 2050
W21	950 x 2050
W22	950 x 2050
W23	950 x 2050
W24	1100 x 2050
W25	850 x 2050
W26	3680 x 2550

DOOR SCHEDULE	
Door No.	Door Size (W x H)
D1	3980 x 2550
D2	4130 x 2700
D3	3530 x 2700
D4	1045 x 2700

DP 392957

No. 8
WEATHERBOARD HOUSE
TILED ROOF

121
DP 3846

No. 21
2 STOREY
BRICK UNITS
TILED ROOF

NATHERS summary for 19 & 19A Park Street Campsie 2194		
Building Elements	Material	Detail
External walls - ground floor	Cavity brick	25mm DeSivaine 148 or the like (total system R value R1.96) (excluding garage) min cavity width 60mm
External walls - first floor	Cavity brick	R2.5 bulk insulation
Internal walls	Lightweight cladding	-
Common walls	Single skin brick	-
Ceilings	Cavity brick	R3.5 bulk insulation to ceilings with roof exposed to outside air (excluding garage)
Floors	Concrete	-
Floor finishes	Tiles - Wet areas, Timber flooring - Living areas, Carpet - bedrooms	-
Roof	Metal Roof - Medium colour	Builders Blanket (Toll - R1.3)
Windows/doors		
ANZ-001-05	Aluminium frame, single glazed ET	U value 4.40 or less and SHGC 0.54
AW5-012-18	Aluminium frame, single glazed comfort plus	U value 4.36 or less and SHGC 0.59
BR2-006-03	Aluminium frame, single glazed 65mm	U value 4.66 or less and SHGC 0.48
ALM-002-01	Aluminium frame, single glazed clear	U value 6.70 or less and SHGC 0.70
ALM-004-03	Aluminium frame, double glazed low e or similar	U value 4.30 or less and SHGC 0.53
If any SHGC values are according to NHERS, Aluminium products may be used if the U-value is the same or lower and the SHGC is within 10% of the above figures. The also applies to changes to the type and thickness of glass required to meet double and acoustic regulations.		
Ceiling fans: 1200mm ceiling fans to bedrooms		
Lighting: Dwellings have been tested with non-ventilated LED downlights as per NATHERS certification.		
Note: Insulation specified must be installed in accordance with Part 3.2.2.1.1 of the BCA.		
Note: In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.		
Note: Self-closing dampers to bathroom, ensuite and laundry exhaust fans.		

BASIX COMMITMENTS NOTES				
REFER TO APPROVED BASIX REPORT				
WATER				
Fixtures	All Shower Heads	All toilet flushing systems	All kitchen taps	All bathroom taps
	4 star (or 5 star <= 7.5 L/min)	4 star	4 star	4 star
	Individual rainwater tanks to collect run off from at least 60 m² of roof area from each dwelling - Tank size min 2000 litres			
Alternative water source	The applicant must connect the rainwater tank to:			
	Landscaping connection	Toilet connection	Laundry connection	Pool top up
	Yes	-	Yes	-
ENERGY	Hot water system: Gas instantaneous with a performance of 5 stars			
	Bathroom ventilation system: Individual fan, ducted to façade or roof; manual switch on/off			
	Kitchen ventilation system: Individual fan, ducted to façade or roof; manual switch on/off			
	Laundry ventilation system: Individual fan, ducted to façade or roof; manual switch on/off			
	Cooling system: 1 Phase air-conditioning EER 3.0 - 3.5 in at least 1 living/bed area (zoned)			
	Heating system: 1 Phase air-conditioning EER 3.0 - 3.5 in at least 1 living/bed area (zoned)			
	Natural lighting: As per BASIX			
	Artificial lighting: As per BASIX			
	Must install a gas cooktop and electric oven.			
	Must install fixed outdoor clothes drying line as part of the development.			

0 2 4 6 8 10
SCALE IN METRES

THESE DRAWINGS ARE DESIGN INTENT DRAWINGS ONLY. NOT USED DURING CONSTRUCTION. IT IS NOT A DETAILED CONSTRUCTION DRAWING AND SHOULD NOT BE USED AS SUCH. IF THIS DRAWING DESCRIBES A COMPONENT TO BE MANUFACTURED, THE BUILDER SHOULD SEEK AND CHECK SHOP DRAWINGS FOR THAT COMPONENT, PREPARED BY THE MANUFACTURER.

USE FIGURED DIMENSIONS ONLY. DO NOT SCALE FROM THIS DRAWING. BUILDER TO BE RESPONSIBLE FOR IDENTIFYING DRAWING DISCREPANCIES PRIOR TO THE WORK DESCRIBED IN THE DRAWING BEING CARRIED OUT.


THE DESIGNER RETAINS COPYRIGHT IN THIS DRAWING WHICH IS NOT TO BE REPRODUCED WITHOUT THE CONSENT OF THE DESIGNER.

KEY	
AC	Air conditioning
BG	Box gutter
CM	Concrete render
CP	Carpet
CPD	Cupboard
CR	Copper roofing
CT	Cooktop
DD	Downpipe
ED	Eastern door
EW	Eastern window
FW	Floor waste
HWS	Hot water system
J	Construction joint
OF	Overflow
PB	Plasterboard
PL	Plaster
RC	Refrigerator
RE	Reinforced concrete
RL	Relative level
RP	Recessed panel
S	Sink
SD	Sink drain
SK	Skylight
SW	Shower waste
TB	Timber battens
TF	Timber flooring
WD	Western door
WW	Western window
CB	Concrete block

REVISION	ISSUE	DATE
A	DEVELOPMENT APPLICATION	18/05/2023
B	DEVELOPMENT APPLICATION	07/07/2023
C	S82A APPLICATION	22/08/2023
FOR S82A / SK / TENDER ISSUE ONLY		



FOR S82A APPLICATION
ISSUE ONLY



GRAPHIO AM
SUITE 3.04, 56 BOWMAN STREET, PYRMONT NSW 2009
TELEPHONE +61 2 9660 0628 EMAIL contact@graphioam.com.au
19 PARK STREET, CAMPSIE
FOR MR TOMI VIDOVIC
SITE / ROOF PLAN
SCALE 1:200 @ A3
S82A_1.00
AUGUST 2023