

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1402126S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

BASIX

Date of issue: Wednesday, 27 September 2023

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary					
Project name	Lancaster Ave DWE	ELLING 3 (LOTB)			
Street address	92-94 Lancaster Av	enue Punchbowl 2196			
Local Government Area	Canterbury-Banksto	own Council			
Plan type and plan number	deposited 11831				
Lot no.	37&38	37&38			
Section no.	-	-			
Project type	separate dwelling he	separate dwelling house			
No. of bedrooms	5	5			
Project score					
Water	4 0	Target 40			
Thermal Comfort	✓ Pass	Target Pass			
Energy	> 50	Target 50			

Certificate Prepared by
Name / Company Name: architek
ABN (if applicable): 79446186147

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1402126S Wednesday, 27 September 2023 page 1/9

Description of project

BASIX

Project address	
Project name	Lancaster Ave DWELLING 3 (LOTB)
Street address	92-94 Lancaster Avenue Punchbowl 2196
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan 11831
Lot no.	37&38
Section no.	-
Project type	
Project type	separate dwelling house
No. of bedrooms	5
Site details	
Site area (m²)	572
Roof area (m²)	275
Conditioned floor area (m2)	135.0
Unconditioned floor area (m2)	20.0
Total area of garden and lawn (m2)	125

Assessor details and thermal loads							
Assessor number	n/a						
Certificate number	n/a						
Climate zone	n/a						
Area adjusted cooling load (MJ/m².year)	n/a						
Area adjusted heating load (MJ/m².year)	n/a						
Ceiling fan in at least one bedroom	n/a						
Ceiling fan in at least one living room or other conditioned area	n/a						
Project score							
Water	✓ 40	Target 40					
Thermal Comfort	✓ Pass	Target Pass					
Energy	> 50	Target 50					

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1402126S Wednesday, 27 September 2023 page 2/9

Schedule of BASIX commitments

BASIX

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 4.5 but <= 6 L/min) in all showers in the development.		~	V
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	-
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		V	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 3200 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	V
The applicant must configure the rainwater tank to collect rain runoff from at least 200 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	V
The applicant must connect the rainwater tank to:			
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		✓	V

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1402126S Wednesday, 27 September 2023 page 3/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	V	~	-
The conditioned floor area of the dwelling must not exceed 300 square metres.	V	V	V
The dwelling must not contain open mezzanine area exceeding 25 square metres.	V	V	V
The dwelling must not contain third level habitable attic room.	V	~	
Floor, walls and ceiling/roof		1	
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - cavity brick	0.50 (or 1.17 including construction)	
external wall - brick veneer	1.86 (or 2.40 including construction)	
external wall - framed (weatherboard, fibre cement, metal clad)	2.00 (or 2.40 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 2.45 (up), roof: foil backed blanket (55 mm)	unventilated; medium (solar absorptance 0.475-0.70)

Note	Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

BASIX

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1402126S Wednesday, 27 September 2023 page 4/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	✓	V
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	-
The following requirements must also be satisfied in relation to each window and glazed door:	~	V	V
• For the following glass and frame types, the certifier check can be performed by visual inspection.			-
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
N01-BUTTLER	600	2100	aluminium, single, clear	eave 450 mm, 200 mm above head of window or glazed door	not overshadowed
East facing					
E01-KIT	2200	800	aluminium, single, clear	eave 450 mm, 200 mm above head of window or glazed door	not overshadowed
E02-DIN	2200	800	aluminium, single, clear	eave 450 mm, 200 mm above head of window or glazed door	not overshadowed
E03-DIN	2200	800	aluminium, single, clear	eave 450 mm, 200 mm above head of window or glazed door	not overshadowed
E04-LIV 5000	2700	3000	aluminium, single, clear	verandah 5000 mm, 2700 mm above base of window or glazed door	not overshadowed
E05-B1 2700	2700	3000	aluminium, single, clear	verandah 2700 mm, 2700 mm above base of window or glazed door	not overshadowed

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1402126S Wednesday, 27 September 2023 page 5/9

BASIX

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing	
South facing						
S01-ENS	900	600	aluminium, single, clear	eave 450 mm, 200 mm above head of window or glazed door	not overshadowed	
West facing	West facing					
W01-B2	1200	2100	aluminium, single, clear	eave 450 mm, 200 mm above head of window or glazed door	not overshadowed	
W02-B3	1200	2100	aluminium, single, clear	eave 450 mm, 200 mm above head of window or glazed door	not overshadowed	
W03-B4	1200	2100	aluminium, single, clear	eave 450 mm, 200 mm above head of window or glazed door	not overshadowed	

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1402126S Wednesday, 27 September 2023 page 6/9

BASIX

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water	·		
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 3 stars.	~	~	-
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 3-phase airconditioning; Energy rating: EER 3.0 - 3.5		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 3-phase airconditioning; Energy rating: EER 3.0 - 3.5		~	V
The cooling system must provide for day/night zoning between living areas and bedrooms.		•	V
Heating system			
The living areas must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		→	V
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		•	V
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: interlocked to light		•	•
Kitchen: no mechanical ventilation (ie. natural); Operation control: n/a		✓	-
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		V	•
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
• at least 4 of the bedrooms / study;		~	-
Natural lighting	<u> </u>		

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1402126S Wednesday, 27 September 2023 page 7/9

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	~	V	V
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.			

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1402126S Wednesday, 27 September 2023 page 8/9

BASIX

Legend

BASIX

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1402126S Wednesday, 27 September 2023 page 9/9