

Suite 2.06 / 56 Delhi Road North Ryde NSW 2113 02 9878 6005 assetgeoenviro.com.au

Our ref: 7250-R1 Rev 5 29 November 2023

John Moran 56 Challenger Parade City Beach WA 6015

By email: jmoran.wa@gmail.com

Dear John,

Proposed Modifications of Development Consent Application Lot 774 Diggins Terrace, Thredbo NSW Geotechnical Assessment

1. Introduction

1.1 General

This report presents our geotechnical assessment for Proposed Modifications of Development Consent Application at Lot 774 Diggins Terrace, Thredbo NSW (the Site). It is understood that modification to the previously approved DA 9373 and MOD 10108 are proposed to rectify unauthorised works.

The assessment was commissioned on 8 May 2023 by John Moran. The work was carried out in accordance with the proposal by AssetGeoEnviro (Asset) dated 11 May 2023, reference 7250-P1.

Documents supplied to us for this assessment comprised:

- Architectural Plans (prepared by: Archispectrum; project: Melaleuca 1, Lot 774 Diggins Terrace Thredbo Village, Kosciuszko NSW; dwg: DA01–DA18; issue for review: 27 November 2023).
- Structural Design for Stairs and Balcony (prepared by: G. Janssen of Janssen Constructions Pty Ltd; dated: 30 March 2021).
- Stair and Roof Structural Design Plans (prepared by: G. Janssen of Janssen Constructions Pty Ltd; Sheets 1 and 2; dated: December 2022).

We have also reviewed previous geotechnical assessments, inspections, and Form 4's by Asset for the development including:

- Geotechnical Assessment Form 4 (ref: 4793-L1 Rev 2; dated: 10 February 2020).
- Geotechnical Slope Risk Assessment (ref: 4793-G2; dated: 31 March 2020).
- Geotechnical Inspection Report (ref: 4793-2-G1-Rev1; dated: 20 March 2020).
- Form 4 Rev 3 Mod (dated: 29 May 2020).
- Form 4 Rev 4 Basement (dated: 23 July 2020).
- Geotechnical Certification Ground Floor Slab and Retaining Wall Footings (ref: 4793-3-G1; dated: 26 April 2021).



- Geotechnical Certification, Terms 8, 9 & 11 of Department of Planning, Industry & Environment (ref: 4793-3-G2; dated: 21 June 2021).
- Geotechnical Certification Terms 14, 15 & 16 of Department of Planning, Industry & Environment (ref: 4793-3-G3; dated: 18 July 2022).

1.2 Development Details

The proposed modifications shown in the plans by Archispectrum include:

- modifying internal stairs
- extending balconies
- external two-storey staircase to southwestern side of lodge

The modifications are generally very minor in nature except for the external stairs which will impose additional loading onto the ground surface. The potential geotechnical impact of the modifications is discussed in Section 2.

1.3 Scope of Work

The main objective is to provide geotechnical assessment of the proposed modifications.

The following scope of work was carried out to achieve the project objectives:

- Review of existing regional maps and reports and other documents relevant to the Site held within our files.
- Review of the supplied documents.
- Engineering assessment and reporting.

This report must be read in conjunction with the attached "Important Information about your Geotechnical Report" and "Important Information about your Landslide Risk Assessment" in Appendix A. Attention is drawn to the limitations inherent in site investigations and the importance of verifying the subsurface conditions inferred herein. Landslide risk considerations presented in this report must be read in conjunction with the attached GeoGuides for Slope Management and Maintenance.

2. Geotechnical Assessment

As noted above, the proposed modifications are generally very minor in nature except for the external stairs which will impose additional loading onto the ground surface.

The inspections of the cut for the basement have shown weathered granite exposed beneath a relatively thin soil mantle around the proposed external stairs. Provided that the footings for the external stairs are taken into the extremely weathered granite, the landslide risk will be within acceptable limits (**Low** with respect to property, and **Acceptable** with respect to life). A conservative allowable bearing pressure of 200kPa may be adopted for footings in the extremely weathered granite, considering the potential landslide risk.



Provided that the development is carried out in accordance with the above recommendations, we consider the impact to be minimal and therefore a Form 4 certification (attached) is applicable.

3. Limitations

In addition to the limitations inherent in site investigations (refer to the attached Information Sheets), it must be pointed out that the recommendations in this report are based on assessed subsurface conditions from limited investigations. To confirm the assessed soil and rock properties in this report, further investigation would be required such as coring and strength testing of rock and should be carried out if the scale of the development warrants, or if any of the properties are critical to the design, construction, or performance of the development.

It is recommended that a qualified and experienced Geotechnical Engineer be engaged to provide further input and review during the design development; including site visits during construction to verify the Site conditions and provide advice where conditions vary from those assumed in this report. Development of an appropriate inspection and testing plan should be carried out in consultation with the Geotechnical Engineer.

This report may have included geotechnical recommendations for design and construction of temporary works (e.g., temporary batter slopes or temporary shoring of excavations). Such temporary works are expected to perform adequately for a relatively short period only, which could range from a few days (for temporary batter slopes) up to six months (for temporary shoring). This period depends on a range of factors including but not limited to: site geology; groundwater conditions; weather conditions; design criteria; and level of care taken during construction. If there are factors which prevent temporary works from being completed and/or which require temporary works to function for periods longer than originally designed, further advice must be sought from the Geotechnical Engineer and Structural Engineer.

Asset accepts no liability where our recommendations are not followed or are only partially followed. The document "Important Information about your Geotechnical Report" in Appendix A provides additional information about the uses and limitations of this report.



Please do not hesitate to contact the undersigned if you have any questions regarding this report or if you require further assistance.

For and on behalf of AssetGeoEnviro

Mark Bartel

Mark Bartel BE, MEngSc, GMQ, CPEng, RPEQ/NER(Civil), DEP/PRE (NSW) Managing Director | Senior Principal Geotechnical Engineer

Encl: 7250-R1 Rev 5 Form 4

Important Information about your Geotechnical Report Important Information about your Landslide Risk Assessment Soil and Rock Explanation Sheets

Document Control

Distribution Register

Сору	Media	Recipient	Location
1	Secure PDF	John Moran	Hydromedial Consulting Group
2	Secure PDF	Mark Bartel	Asset Geotechnical Engineering

Document Status

Rev	Revision Details	Author	Reviewer		Approved for Issue		
			Name	Initials	Name	Initials	Date
0	Initial issue	M. Bartel			M. Bartel	MAB	10 August 2023
1	Updated recommendations	M. Bartel			M. Bartel	MAB	11 August 2023
2	Updated reference documents	M. Bartel			M. Bartel	MAB	19 September 2023
3	Amended project scope	M. Bartel			M. Bartel	MAB	6 November 2023
3	Updated reference documents	M. Bartel			M. Bartel	MAB	29 November 2023



Suite 2.06 / 56 Delhi Road North Ryde NSW 2113 02 9878 6005 assetgeoenviro.com.au

ISO 9001:2015 ISO 14001:2015 ISO 45001:2018 AS/NZS 4801:2001

© Copyright Asset Geotechnical Engineering Pty Ltd. All rights reserved.

AssetGeoEnviro is a registered business name of Asset Geotechnical Engineering Pty Ltd (Asset). This Report has been prepared by Asset for its Client in accordance with a contract between Asset and its Client. The Report may only be used for the purpose for which it was commissioned and is subject to the terms of contract including terms limiting the liability of Asset. Unauthorised use of this document in any form whatsoever is prohibited. Any third party who seeks to rely on this Report without the express written consent of Asset does so entirely at their own risk, and, to the fullest extent permitted by law, Asset accepts no liability whatsoever in respect of any loss or damage suffered by any such third party.



Geotechnical Policy

Kosciuszko Alpine Resorts

Form 4 – Minimal Impact Certification

DA Number: MOD 10108 (DA No. 9373 MOD 1

This form may be used where minor construction works which present minimal or no geotechnical impact on the site or related land are proposed to be erected within the "G" line area of the geotechnical maps.

A geotechnical engineer or engineering geologist must inspect the site and/or review the proposed development documentation to determine if the proposed development requires a geotechnical report to be prepared to accompany the development application. Where the geotechnical engineer determines that such a report is not required then they must complete this form and attach design recommendations where required. A copy of Form 4 with design recommendation, if required, must be submitted with the development application.

Please contact the Alpine Resorts Team in Jindabyne for further information - phone 02 6456 1733.

To complete this form, please place a cross in the appropriate boxes \Box and complete all sections.

1. Declaration made by geotechnical engineer or engineering geologist in relation to a nil or minimal geotechnical impact assessment and site classification

l, Mr 🗙	Ms 🗌	Mrs 🗌	Dr 🗌	Other	
First Na	me				Family Name
Mark					Bartel

OF

Company/organisation

Asset Geotechnical Engineering Pty Ltd (trading as AssetGeoEnviro)

certify that I am a geotechnical engineer /engineering geologist as defined by the "Policy" and I have inspected the site and reviewed the proposed development known as

Lot 774 Diggins Terrace, Thredbo NSW

As a result of my site inspection and review of the following documentation

(List of documentation reviewed)

Architectural Plans (by: Archispectrum; dwg: DA01-18; issue for review: 27/11/2023

Structural Design for Stairs and Balcony (by: Janssen Constructions; 30/3/2021)

Stair and Roof Structural Design (by: Janssen Constructions; December 2022)

I have determined that;

- the current load-bearing capacity of the existing building will not be exceeded or adversely impacted by the proposed development, and
- the proposed works are of such a minor nature that the requirement for geotechnical advice in the form of a geotechnical report, prepared in accordance with the "Policy", is considered unnecessary for the adequate and safe design of the structural elements to be incorporated into the new works, and
- in accordance with AS 2870.1 Residential Slabs and Footings, the site is to be classified as a type

(insert classification type)	
Class P	

I have attached design recommendations to be incorporated in the structural design in accordance with this site classification.

I am aware that this declaration shall be used by the Department as an essential component in granting development consent for a structure to be erected within the "G" line area (as identified on the geotechnical maps) of Kosciuszko Alpine Resorts without requiring the submission of a geotechnical report in support of the development application.

2. Signatures

Signature	Chartered professional status		
Made Bastel	CPEng 35641 NER (Civil)		
Name	Date		
Mark Bartel	29 November 2023		

3. Contact details

Alpine Resorts Team

Shop 5A, 19 Snowy River Avenue P O Box 36, JINDABYNE NSW 2627 Telephone: 02 6456 1733 Facsimile: 02 6456 1736 Email: alpineresorts@planning.nsw.gov.au



Scope of Services

The geotechnical report ("the report") has been prepared in accordance with the scope of services as set out in the contract, or as otherwise agreed, between the Client and Asset Geotechnical Engineering Pty Ltd ("Asset"), for the specific site investigated. The scope of work may have been limited by a range of factors such as time, budget, access and/or site disturbance constraints.

The report should not be used if there have been changes to the project, without first consulting with Asset to assess if the report's recommendations are still valid. Asset does not accept responsibility for problems that occur due to project changes if they are not consulted.

Reliance on Data

Asset has relied on data provided by the Client and other individuals and organizations, to prepare the report. Such data may include surveys, analyses, designs, maps, and plans. Asset has not verified the accuracy or completeness of the data except as stated in the report. To the extent that the statements, opinions, facts, information, conclusions and/or recommendations ("conclusions") are based in whole or part on the data, Asset will not be liable in relation to incorrect conclusions should any data, information or condition be incorrect or have been concealed, withheld, misrepresented, or otherwise not fully disclosed to Asset.

Geotechnical Engineering

Geotechnical engineering is based extensively on judgment and opinion. It is far less exact than other engineering disciplines. Geotechnical engineering reports are prepared for a specific client, for a specific project and to meet specific needs, and may not be adequate for other clients or other purposes (e.g., a report prepared for a consulting civil engineer may not be adequate for a construction contractor). The report should not be used for other than its intended purpose without seeking additional geotechnical advice. Also, unless further geotechnical advice is obtained, the report cannot be used where the nature and/or details of the proposed development are changed.

Limitations of Site Investigation

The investigation program undertaken is a professional estimate of the scope of investigation required to provide a general profile of subsurface conditions. The data derived from the site investigation program and subsequent laboratory testing are extrapolated across the site to form an inferred geological model, and an engineering opinion is rendered about overall subsurface conditions and their likely behavior regarding the proposed development. Despite investigation, the actual conditions at the site might differ from those inferred to exist, since no subsurface exploration program, no matter how comprehensive, can reveal all subsurface details and anomalies.

The engineering logs are the subjective interpretation of subsurface conditions at a particular location and time, made by trained personnel. The actual interface between materials may be more gradual or abrupt than a report indicates.

Therefore, the recommendations in the report can only be regarded as preliminary. Asset should be retained during the project implementation to assess if the report's recommendations are valid and whether changes should be considered as the project proceeds.

Subsurface Conditions are Time Dependent

Subsurface conditions can be modified by changing natural forces or man-made influences. The report is based on conditions that existed at the time of subsurface exploration. Construction operations adjacent to the site, and natural events such as floods, or ground water fluctuations, may also affect subsurface conditions, and thus the continuing adequacy of a geotechnical report. Asset should be kept appraised of any such events and should be consulted to determine if any additional tests are necessary.

Verification of Site Conditions

Where ground conditions encountered at the site differ significantly from those anticipated in the report, either due to natural variability of subsurface conditions or construction activities, it is a condition of the report that Asset be notified of any variations and be provided with an opportunity to review the recommendations of this report. Recognition of change of soil and rock conditions requires experience, and it is recommended that a suitably experienced geotechnical engineer be engaged to visit the site with sufficient frequency to detect if conditions have changed significantly.

Reproduction of Reports

This report is the subject of copyright and shall not be reproduced either totally or in part without the express permission of this Company. Where information from the accompanying report is to be included in contract documents or engineering specification for the project, the entire report should be included to minimize the likelihood of misinterpretation from logs.

Report for Benefit of Client

The report has been prepared for the benefit of the Client and no other party. Asset assumes no responsibility and will not be liable to any other person or organisation for or in relation to any matter dealt with or conclusions expressed in the report, or for any loss or damage suffered by any other person or organisation arising from matters dealt with or conclusions expressed in the report (including without limitation matters arising from any negligent act or omission of Asset or for any loss or damage suffered by any other party relying upon the matters dealt with or conclusions expressed in the report). Other parties should not rely upon the report or the accuracy or completeness of any conclusions and should make their own inquiries and obtain independent advice in relation to such matters.

Data Must Not Be Separated from The Report

The report presents the site assessment and must not be copied in part or altered in any way.

Logs, figures, drawings, test results etc. included in our reports are developed by professionals based on their interpretation of field logs (assembled by field personnel) and laboratory evaluation of field samples. These data should not under any circumstances be redrawn for inclusion in other documents or separated from the report in any way.

Report Recommendations not Followed

Where the recommendations of the report are not followed or are only partially followed, there may be significant implications for the project (e.g., commercial loss, property loss or damage, personal injury, or loss of life). Consult Asset if you are not intending to follow all the report recommendations, to assess what the implications could be. Asset does not accept responsibility where the report recommendations have not been followed or have only been partially followed.

Other Limitations

Asset will not be liable to update or revise the report to consider any events or emergent circumstances or fact occurring or becoming apparent after the date of the report.

Important Information about your Landslide Risk Assessment



BASIS OF THE ASSESSMENT

Our assessment of the stability of the land is presented in the framework of Landslide Risk Management (Australian Geomechanics Society, Vol 42, No 1, March 2007). The attached GeoGuides provide further information on landslide risk management and maintenance.

This assessment is based on a visual inspection of the property and also the immediate adjoining land. Limited subsurface investigation may also have been undertaken as part of this appraisal. Slope monitoring has not been carried out within or adjacent to the property for the purpose of this appraisal. The opinions expressed in this report also take into account our relevant local experience.

The property is within an area where landslip and/or subsidence have occurred, or where there is a risk of landslide. Important factors relating to slope conditions and the impact of development which commonly influence the landslide risks are discussed herein.

An owner's decision to acquire, develop or build on land within an area such as this involves the understanding and acceptance of a level of risk. It is important to recognise that soil and rock movements are an ongoing geological process, which may be affected by development and land management within the site or on ad-joining land. Soil and rock movements may cause visible damage to structures even where the risk of slope failure is considered low. This report is intended only to assess the landslide risk apparent at the time of inspection.

Our opinion is provided on the present landslide risk for the land specifically referenced in the title to this report. Foundations suitable for future building development are discussed in relation to slope stability considerations. Limited foundation advice may be provided. If so, advice is intended to guide the footing design for the proposed development. However, this report is not intended as, is not suitable for, and must not be used in lieu of a detailed foundation investigation for final design and costing of foundations, retaining walls or associated structures.

LIMITATIONS OF THE ASSESSMENT PROCEDURE

The assessment procedures carried out for this appraisal are in accordance with the recommendations in Landslide Risk Management (Australian Geomechanics Society, Vol 42, No 1, March 2007), and with accepted local practice.

The following limitations must be acknowledged:

- the assessment of the stability of natural slopes requires a great degree of judgment and personal experience, even for experienced practitioners with good local knowledge;
- the assessment must be based on development of a sound geological model; slope processes and process rates influencing land sliding or landslide potential will vary according to geomorphologic influences;
- the likelihood that land sliding may occur on a given slope is generally hard to predict and is associated with significant uncertainties;
- different practitioners may produce different assessments of risk;

- actual risk of land sliding cannot be determined; risk changes with time;
- consequences of land sliding need to be considered in a rational framework of risk acceptance;
- acceptable risk in relation to damage to property from landslide activity is subjective; it remains the responsibility of the owner and/or local authority to decide whether the risk is acceptable; the geotechnical practitioner can assist with this judgment;
- the extent and methods of investigation for assessment of landslide risk will be governed by experience, by the perceived risk level, and by the degree to which the risk or consequences of land sliding are accepted for a specific project;
- the assessment may be required at a number of stages of the project or development; frequently (due to time or budget constraints imposed by the client) there will be no opportunity for long-term monitoring of the slope behaviour or groundwater conditions, or for on-going opportunity for the slope processes and performance of structures to be reviewed during and after development; such limitations should be recognised as relevant to the assessment.

DEVELOPMENT ON SLOPES

Some risk of slope instability is always attached to the development of land on slopes.

Guidelines for hillside construction and examples of good practices for hillside developments are described in the attached GeoGuides.

Soil and Rock Explanation Sheets (1 of 2)

excavation logs

natural excavation

hand excavation

backhoe bucket

dozer blade

ripper tooth

excavator bucket

NE

HF

BН

ΕX DZ

R



Other

Log Abbreviations & Notes

METHOD

<u>borehol</u>	<u>borehole logs</u>				
AS	auger screw *				
AD	auger drill *				
RR	roller / tricone				
W	washbore				
CT	cable tool				
HA	hand auger				
D	diatube				
В	blade / blank bit				
V	V-bit				
Т	TC-bit				
* bit shown by suffix e a ADV					

* bit	shown	by	suffix	e.g.	ADV
-------	-------	----	--------	------	-----

<u>coring</u> NMLC, NQ, PQ, HQ

SUPPORT

boreh	ole logs	e	excavation logs
Ν	nil	N	nil
M	mud	S	shoring
С	casing	В	benched
NO	NO rode		

CORE-LIFT

	I	casing installed
--	---	------------------

barrel withdrawn \vdash

NOTES, SAMPLES, TESTS

D	disturbed
D	hulk disturbed
D	
050	thin-walled sample, 50mm diameter
HP	hand penetrometer (kPa)
SV	shear vane test (kPa)
DCP	dynamic cone penetrometer (blows per 100mm penetration)
SPT	standard penetration test
N*	SPT value (blows per 300mm)
	* denotes sample taken
Nc	SPT with solid cone
R	refusal of DCP or SPT

USCS SYMBOLS

- Gravel and gravel-sand mixtures, little or no fines. GW
- GP Gravel and gravel-sand mixtures, little or no fines, uniform gravels
- GΜ Gravel-silt mixtures and gravel-sand-silt mixtures. GC
- Gravel-clay mixtures and gravel-sand-clay mixtures. Sand and gravel-sand mixtures, little or no fines. SW
- SP Sand and gravel sand mixtures, little or no fines.
- SM Sand-silt mixtures.
- SC Sand-clay mixtures.
- ML Inorganic silt and very fine sand, rock flour, silty or clayey fine sand or silt with low plasticity. Inorganic clays of low to medium plasticity, gravelly clays, sandy

DENSITY INDEX very loose

- CL, CI clays.
- Organic silts OL ΜН
- Inorganic silts Inorganic clays of high plasticity. СН
- ОH Organic clays of medium to high plasticity, organic silt
- ΡT Peat, highly organic soils.

MOISTURE CONDITION

- dry moist D
- Μ W
- wet plastic limit Wp
- wi iquid limit

CONSISTENCY

VS	very soft	VL	very loose
S	soft	L	loose
F	firm	MD	medium dense
St	stiff	D	dense
VSt	very stiff	VD	very dense
Н	hard		-
Fh	friable		

Graphic Log





- Known
 - Probable
- Possible

WEATHERING Х

WEA	THERING	STR	STRENGTH		
XW	extremely weathered	VL	very low		
HW	highly weathered	L	low		
MW	moderately weathered	М	medium		
SW	slightly weathered	Н	high		
FR	fresh	VH	very high		
		FH	extremely high		

RQD (%)

sum of intact core pieces > 2 x diameter x 100 total length of core run drilled

DEFECTS:

ype		<u>c</u>	oating
IT	joint	cl	clean
۲	parting	st	stained
SZ	shear zone	ve	veneer
SM	seam	CO	coating
hape		rough	nness
bl	planar	po	polished

pl	planar	ро	polished
cu	curved	sl	slickensided
un	undulating	sm	smooth
st	stepped	ro	rough
ir	irregular	vr	very rough

inclination

measured above axis and perpendicular to core

Soil and Rock Explanation Sheets (2 of 2)



<u>Spacing</u> 200 - 600 600 - 2,000

> 2.000

AS1726-2017

Soils and rock are described in the following terms, which are broadly in accordance with AS1726-2017.

Soil

MOISTURE CONDITION

Description Term

Dry Looks and feels dry. Fine grained and cemented soils are hard, friable or powdery. Uncemented coarse grained soils run freely through hand. Soil feels cool and darkened in colour. Fine grained soils can be moulded. Moist Coarse soils tend to cohere.

Wet As for moist, but with free water forming on hand.

Moisture content of cohesive soils may also be described in relation to plastic limit (W_{P}) or liquid limit (W_L) [>> much greater than, > greater than, < less than, << much less than].

CONSISTENCY OF FINE-GRAINED SOILS

Term	<u>Su (kPa)</u>	<u>Term</u>	<u>Su (kPa)</u>
Very soft	< 12	Very Stiff	>100 <i>−</i> ≤200
Soft	>12 - ≤25	Hard	> 200
Firm	>25 - ≤50	Friable	-
Stiff	>50 – ≤100		

RELATIVE DENSITY OF COARSE-GRAINED SOILS

Term	Density Index (%)	Term	Density Index (%)
Very Loose	< 15	Dense	65 - 85
Loose	15 – 35	Very Dense	>85
Medium Dense	35 – 65	-	

PARTICLE SIZE

Name	Subdivision	<u>Size (mm)</u>
Boulders		> 200
Cobbles		63 – 200
Gravel	coarse	19 – 63
	medium	6.7 – 19
	fine	2.36 - 6.7
Sand	coarse	0.6 - 2.36
	medium	0.21 – 0.6
	fine	0.075 – 0.21
Silt		0.002 - 0.075
Clay		< 0.075

MATERIAL DELINEATION

>65% above 0.075mm Sand or gravel >35% below 0.075mm

Clay or silt

MINOR COMPONENTS

lerm	Proportion by Mas	s:
	<u>coarse grained</u>	fine grained
Trace	≤ 5%	≤ 5%
With	>15% ≤ 30%	>5% – ≤12%

. ..

SOIL ZONING

Layers	Continuous across exposures or sample.
Lenses	Discontinuous, lenticular shaped zones.
Pockets	Irregular shape zones of different material.

SOIL CEMENTING

Easily broken up by hand pressure in water or air. Weakly Moderately Effort is required to break up by hand in water or in air.

USCS SYMBOLS

Symbol	Description
GW	Gravel and gravel-sand mixtures, little or no fines.
GP	Gravel and gravel-sand mixtures, little or no fines, uniform gravels.
GM	Gravel-silt mixtures and gravel-sand-silt mixtures.
GC	Gravel-clay mixtures and gravel-sand-clay mixtures.
SW	Sand and gravel-sand mixtures, little or no fines.
SP	Sand and gravel sand mixtures, little or no fines.
SM	Sand-silt mixtures.
SC	Sand-clay mixtures.
ML	Inorganic silt and very fine sand, rock flour, silty or clayey fine sand or silt with low plasticity.
CL, CI	Inorganic clays of low to medium plasticity, gravelly clays, sandy clays.
OL	Organic silts
MH	Inorganic silts
	· · · · · · · · · · · · · · · · · · ·

- Inorganic clays of high plasticity. СН
- Organic clays of medium to high plasticity, organic silt OH PT Peat, highly organic soils.

Rock

SEDIMENTARY ROCK TYPE DEFINITIONS Ro Co Sa

Rock Type	Definition (more than 50% of rock consists of)
Conglomerate	gravel sized (>2mm) fragments.
Sandstone	sand sized (0.06 to 2mm) grains.
Siltstone	silt sized (<0.06mm) particles, rock is not laminated.
Claystone	clay, rock is not laminated.
Shale	silt or clay sized particles, rock is laminated.
LAYERING	

Term

Description No layering apparent. Layering just visible. Little effect on properties. Massive Poorly Developed Well Developed Layering distinct. Rock breaks more easily parallel to layering.

STRUCTURE	
Term	

<u>Term</u>	Spacing (mm)	Term
Thinly laminated	<6	Medium bedded
Laminated	6 – 20	Thickly bedded
Very thinly bedded	20 - 60	Very thickly bedded
Thinly bedded	60 – 200	

)	I hickly bedde
60	Very thickly b
200	

STRENGTH	(NOTE: Is50 = Point Load	d Strength Index)	
Term	<u>ls50 (MPa)</u>	Term	<u>ls50 (MPa)</u>
Very Low	0.03 - 0.1	High	1.0 - 3.0
Low	0.1 – 0.3	Very High	3.0 – 10.0
Medium	0.3 – 1.0	Extremely High	>10.0

WEATHERING

Term	Description
Residual Soil	Material is weathered to an extent that it has soil properties.
	Rock structures are no longer visible, but the soil has not been significantly transported.
Extremely	Material is weathered to the extent that it has soil properties.
	Mass structures, material texture & fabric of original rock is still visible.
Highly	Rock strength is significantly changed by weathering; rock is dis-
	colored, usually by iron staining or bleaching. Some primary min- erals have weathered to clay minerals.
Moderately	Rock strength shows little or no change of strength from fresh rock; rock may be discolored.
Slightly	Rock is partially discolored but shows little or no change of strength from fresh rock.
Fresh	Rock shows no signs of decomposition or staining.

DEFECT DESCRIPTION

Туре			
Joint	A surface or crack across which the rock has little or no ten- sile strength. May be open or closed.		
Parting	A surface or crack across which the rock has little or no ten- sile strength. Parallel or sub-parallel to layering/bedding. May be open or closed.		
Sheared Zone	Zone of rock substance with roughly parallel, near planar, curved or undulating boundaries cut by closely spaced joints, sheared surfaces or other defects.		
Seam	Seam with deposited soil (infill), extremely weathered insitu rock (XW), or disoriented usually angular fragments of the host rock (crushed).		
Shape .			
Planar	Consistent orientation.		
Curved	Gradual change in orientation.		
Undulating	Wavy surface.		
Stepped	One or more well defined steps.		
Irregular	Many sharp changes in orientation.		
Roughness			
Polished	Shiny smooth surface.		
Slickensided	Grooved or striated surface, usually polished.		
Smooth	Smooth to touch. Few or no surface irregularities.		
Rough	Many small surface irregularities (amplitude generally <1mm). Feels like fine to coarse sandpaper.		
Very Rough	Many large surface irregularities, amplitude generally >1mm. Feels like very coarse sandpaper.		
Coating			
Clean	No visible coating or discolouring.		
Stained	No visible coating but surfaces are discolored.		
Veneer	A visible coating of soil or mineral, too thin to measure; may be patchy		
Coating	Visible coating =1mm thick. Thicker soil material described as seam.		