

Nationwide House Energy Rating Scheme®

NatHERS® Certificate No. #HR-EG4L5O-02

Generated on 18 Dec 2023 using Hero 3.1.0.6

Property

Address unit 1, 1-3 Ferry Rd, Oxley Island, NSW, 2430
Lot/DP Lot 5
NCC Class* 1a
Floor/all Floors 1 of 1 floors
Type New

Plans

Main Plan 18-12-23 REV N
Prepared by CWC

Construction and environment

Assessed floor area (m²)*		Exposure Type
Conditioned*	222.9	Open
Unconditioned*	19.8	NatHERS climate zone
Total	285.8	15 - Williamtown AMO
Garage	43.1	



Accredited assessor

Name Adam Clarke
Business name 10 Star Building Assessments
Email admin@10sba.com
Phone +61 481010999
Accreditation No. 101518
Assessor Accrediting Organisation ABSA
Declaration of interest No Conflict of Interest

NCC Requirements

BCA provisions Volume 2
State/Territory variation Yes

National Construction Code (NCC) requirements


The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J2D2(2)(a) and (3) of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at www.abcb.gov.au.

Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

Thermal performance star rating



Thermal performance (MJ/m²)

Limits taken from ABCB Standard 2022

	Heating	Cooling
Modelled	29.1	21.2
Load limits	47	30

Features determining load limits

Floor type	
(lowest conditioned area)	CSOG
NCC climate zone 1 or 2	N
Outdoor living area	N
Outdoor living area ceiling fan N	

Whole of Home performance rating

No Whole of Home performance rating generated for this certificate.

Verification

To verify this certificate, scan the QR code or visit

<http://www.hero-software.com.au/pdf/HR-EG4L5O-02>.

When using either link, ensure you are visiting <http://www.hero-software.com.au>



* Refer to glossary.

About the ratings

Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

Heating and Cooling Load Limits

Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the *ABCB Standard: NatHERS heating and cooling load limits* for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

Setting options:

Floor type:

- CSOG - Concrete Slab on Ground
- SF - Suspended Floor (or a mixture of CSOG and SF)
- NA - Not Applicable

NCC climate Zone 1 or 2:

- Yes
- No
- NA - Not Applicable

Outdoor living area:

- Yes
- No
- NA - Not Applicable

Outdoor living area ceiling fan:

- Yes
- No
- NA - Not Applicable



Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

Predicted Whole of Home annual impact by appliance

Shows the contribution each appliance has on the home's annual energy use, greenhouse gas emissions and cost without solar.

Energy use:

No Whole of Home performance assessment conducted for this certificate.

Greenhouse gas emissions:

No Whole of Home performance assessment conducted for this certificate.

Cost:

No Whole of Home performance assessment conducted for this certificate.

Certificate check

The checklist covers important items impacting the dwelling's ratings.

It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and who should check each item.

It is not mandatory to complete this checklist.

Approval stage		Construction stage		
Assessor checked	Consent authority/ surveyor checked	Builder checked	Consent authority/ surveyor checked	Occupancy/other

Genuine certificate check

Does this Certificate match the one available at the web address or QR code verification link on the front page?

☐☐☐☐

Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?

☐☐☐☐

Thermal performance check

Windows and glazed doors

Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?

☐☐☐☐☐

Does the installed windows meet the substitution tolerances (AFRC* based SHGC* and U-values*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?

☐☐☐

External walls

Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'External wall type table' on this Certificate?

☐☐☐☐☐

Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?

☐☐☐☐☐

Floor

Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?

☐☐☐☐☐

Ceiling penetrations*

Does the 'quantity' and 'type' of ceiling penetrations* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?

☐☐☐☐☐

Ceiling

Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?

☐☐☐☐☐

Roof

Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?

☐☐☐☐☐

Apartment entrance doors (NCC Class 2 assessments only)

Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.

☐☐☐☐

Exposure*

Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".

☐☐☐☐

Heating and cooling load limits*

Do the load limits settings (shown on page 1) match what is shown on the NatHERS-stamped plans?

☐☐☐☐☐

* Refer to glossary.

Certificate check

Continued

Approval stage		Construction stage		
Assessor checked	Consent authority/ surveyor checked	Builder checked	Consent authority/ surveyor checked	Occupancy/other

Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--	--------------------------	--------------------------	--------------------------	--------------------------

Insulation installation method

Has the insulation been installed according to the NCC requirements?			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--	--	--------------------------	--------------------------	--------------------------

Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
---	--	--------------------------	--------------------------	--------------------------	--------------------------

Whole of Home performance check (not applicable if a Whole of Home assessment is not conducted)

Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed, match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the hot water system meet the additional requirements specified in the NCC?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Provisional values* check

Have provisional values* been used in the assessment and, if so, are they noted in 'Additional notes' table below?	<input type="checkbox"/>	<input type="checkbox"/>			
--	--------------------------	--------------------------	--	--	--

Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.

Room schedule

Room	Zone Type	Area (m ²)
GARAGE	Garage	43.05
LDRY	Unconditioned	6.84
ROBE	Night Time	9.13
ENSUITE	Night Time	11.76
OFFICE	Day Time	8.81
MEDIA	Living	15.19
BED 3	Bedroom	12.48
WC	Unconditioned	2.10
BATH	Unconditioned	8.31
WC	Unconditioned	2.58
ROBE	Night Time	2.88
BED 4	Bedroom	14.53
LINEN	Day Time	3.06
M BED	Bedroom	25.15
HALLWAY	Day Time	7.63
PANTRY	Day Time	7.07
HALLWAY 2	Day Time	12.88
KITCHEN	Kitchen/Living	77.84
BED 2	Bedroom	14.50

Window and glazed door type and performance

Default* windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

Custom* windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
AWS-001-09 A	502/504 Al Sliding Window SG 6Sn	4.94	0.52	0.49	0.55
AWS-005-09 A	514 Al Double Hung Window SG 6Sn	4.75	0.52	0.49	0.55
AWS-013-08 A	541/542 Al Sliding Door DG 4SnClr/10Ar/4	3.39	0.44	0.42	0.46
AWS-018-08 A	549 ED Al Entry Door SG 6Sn	4.75	0.41	0.39	0.43
AWS-019-03 A	549 ED Al Entry Door DG 4/10Ar/4ET	3.42	0.47	0.45	0.49
AWS-066-09 A	RES SERIES 516 FIXED WINDOW SG 6ETClr	3.93	0.63	0.60	0.66
AWS-067-09 A	RES SERIES 516 FIXED WINDOW DG 1_LightBridge_ClrS0_4-12-4	2.14	0.53	0.50	0.56
VAN-004-03 A	SERIES 525 LOUVRE WINDOW SG 6EVanClr	4.66	0.49	0.47	0.51

Window and glazed door *schedule*

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orient-ation	Shading device*
BATH	VAN-004-03 A	W12-B	1400	600	Louvre	90	NNE	None
BATH	AWS-066-09 A	W12-C	1400	900	Fixed	0	NNE	None
BATH	VAN-004-03 A	W12-A	1400	600	Louvre	90	NNE	None
BED 2	AWS-001-09 A	W15	600	2110	Sliding	45	NNE	None
BED 2	VAN-004-03 A	W16-B	1800	600	Louvre	90	ESE	None
BED 2	AWS-066-09 A	W16-C	1800	1200	Fixed	0	ESE	None
BED 2	VAN-004-03 A	W16-A	1800	600	Louvre	90	ESE	None
BED 3	AWS-001-09 A	W14	1500	2410	Sliding	45	NNE	None
BED 4	VAN-004-03 A	W10-B	2400	900	Louvre	90	WNW	None
BED 4	AWS-066-09 A	W10-A	2400	1800	Fixed	0	WNW	None
BED 4	AWS-066-09 A	W11-B	2400	1800	Fixed	0	NNE	None
BED 4	VAN-004-03 A	W11-A	2400	900	Louvre	90	NNE	None
ENSUITE	VAN-004-03 A	W04-B	2400	900	Louvre	90	WNW	None
ENSUITE	VAN-004-03 A	W04-A	2400	900	Louvre	90	WNW	None
ENSUITE	VAN-004-03 A	W03-B	2400	750	Louvre	90	SSW	None

* Refer to glossary.

Window and glazed door *schedule*

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orient-ation	Shading device*
ENSUITE	VAN-004-03 A	W03-A	2400	750	Louvre	90	SSW	None
GARAGE	AWS-018-08 A	GD01	2050	820	Hinged Door	90	WNW	None
GARAGE	AWS-001-09 A	W02	600	2710	Sliding	30	SSW	None
KITCHEN	AWS-067-09 A	ENTRY FIXED	2400	2275	Fixed	0	ESE	None
KITCHEN	AWS-019-03 A	DG06	2400	1500	Hinged Door	90	ESE	None
KITCHEN	AWS-067-09 A	ENTRY FIXED	2400	1175	Fixed	0	ESE	None
KITCHEN	AWS-067-09 A	ENTRY FIXED	2400	825	Fixed	0	ESE	None
KITCHEN	AWS-013-08 A	GD04	2400	2356	Sliding Door	60	WNW	None
KITCHEN	AWS-013-08 A	GD04	2400	7845	Sliding Door	60	WNW	None
KITCHEN	AWS-013-08 A	GD04	2400	271	Sliding Door	60	WNW	None
LDRY	AWS-018-08 A	GD02	2050	920	Hinged Door	90	SSW	None
M BED	AWS-066-09 A	W05-B	2400	900	Fixed	0	WNW	None
M BED	AWS-066-09 A	W06-B	2400	2400	Fixed	0	WNW	None
M BED	VAN-004-03 A	W06-A	2400	600	Louvre	90	WNW	None
M BED	VAN-004-03 A	W05-A	2400	900	Louvre	90	WNW	None
M BED	AWS-001-09 A	W07-B	2400	1824	Sliding	45	NNE	None
M BED	AWS-001-09 A	W07-A	2400	1176	Sliding	45	NNE	None
M BED	AWS-018-08 A	DG03	2400	900	Hinged Door	90	NNE	None
MEDIA	AWS-001-09 A	W18	600	3210	Sliding	30	SSW	None
MEDIA	AWS-001-09 A	W17	600	2710	Sliding	30	ESE	None
OFFICE	VAN-004-03 A	W01-B	1800	600	Louvre	90	ESE	None
OFFICE	AWS-066-09 A	W01-C	1800	1200	Fixed	0	ESE	None
OFFICE	VAN-004-03 A	W01-A	1800	600	Louvre	90	ESE	None
WC	AWS-005-09 A	W13	900	610	Double Hung	45	NNE	None
WC	AWS-018-08 A	GD05	2050	770	Hinged Door	90	WNW	None

* Refer to glossary.

Roof window type and performance value

Default* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

Custom* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

Roof window schedule

Location	Window ID	Window no.	Opening %	Height (mm)	Width (mm)	Orientation	Outdoor shade	Indoor shade
None								

Skylight type and performance

Skylight ID	Skylight description
None	

Skylight schedule

Location	Skylight ID	Skylight No.	Skylight shaft length (mm)	Area (m ²)	Orientation	Outdoor shade	Diffuser	Shaft Reflectance
None								

External door schedule

Location	Height (mm)	Width (mm)	Opening %	Orientation
GARAGE	2400	5000	90	ESE

External wall type

Wall ID	Wall Type	Solar absorptance	Wall Colour	Bulk insulation (R-value)	Reflective wall wrap*
CONC-200-EXP	Precast 200mm Concrete - Exposed	0.50	Medium	0.00	No
EIFS-75EPS-DF	75mm EPS EIFS - Direct Fix	0.50	Medium	2.70	No
HardieTex™, EasyLap™, Hardie™ Fine Texture Cladding and Matrix™ panel (DF)	HardieTex™, EasyLap™, Hardie™ Fine Texture Cladding and Matrix™ panel (DF)	0.50	Medium	2.70	No
SYCON LINEA3	SYCON LINEA Clad Direct-Fix (No Cavity) Stud Wall	0.50	Medium	2.70	No

External wall *schedule*

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* projection (mm)	Vertical shading feature
BATH	EIFS-75EPS-DF	2740	2596	NNE	549	No
BED 2	SYCON LINEA3	2740	3302	NNE	603	Yes
BED 2	SYCON LINEA3	2740	4390	ESE	603	Yes
BED 3	EIFS-75EPS-DF	2740	3899	NNE	549	No
BED 3	EIFS-75EPS-DF	2740	1092	ESE	551	Yes
BED 4	EIFS-75EPS-DF	2740	4390	WNW	551	Yes
BED 4	EIFS-75EPS-DF	2740	3308	NNE	546	No
ENSUITE	EIFS-75EPS-DF	2740	2100	WNW	549	No
ENSUITE	SYCON LINEA3	2740	2100	ESE	2679	Yes
ENSUITE	EIFS-75EPS-DF	2740	5601	SSW	751	Yes
GARAGE	SYCON LINEA3	3090	2387	WNW	2742	Yes
GARAGE	HardieTex™, EasyLap™, Hardie™ Fine Texture Cladding and Matrix™ panel (DF)	3090	6197	ESE		Yes
GARAGE	EIFS-75EPS-DF	3090	601	SSW		No
GARAGE	HardieTex™, EasyLap™, Hardie™ Fine Texture Cladding and Matrix™ panel (DF)	3090	601	NNE	5586	Yes
GARAGE	EIFS-75EPS-DF	3090	6346	SSW	553	Yes
GARAGE	CONC-200-EXP	250	3802	WNW		No
GARAGE	CONC-200-EXP	250	6346	NNE		No
KITCHEN	SYCON LINEA3	2740	5982	ESE	4588	Yes
KITCHEN	EIFS-75EPS-DF	3500	10586	WNW	4264	Yes
KITCHEN	EIFS-75EPS-DF	2740	598	WNW	4255	Yes
LDRY	SYCON LINEA3	2740	1800	SSW	3011	Yes
M BED	EIFS-75EPS-DF	2740	5292	WNW	549	No
M BED	EIFS-75EPS-DF	2740	1833	NNE	480	Yes
M BED	EIFS-75EPS-DF	2740	4450	NNE	8381	Yes

* Refer to glossary.

External wall *schedule*

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* projection (mm)	Vertical shading feature
MEDIA	SYCON LINEA3	3300	3895	SSW	3605	Yes
MEDIA	SYCON LINEA3	3300	525	ESE		No
MEDIA	SYCON LINEA3	3300	593	NNE	5082	Yes
MEDIA	SYCON LINEA3	3300	3375	ESE	600	Yes
OFFICE	SYCON LINEA3	2740	3303	ESE	600	Yes
OFFICE	SYCON LINEA3	2740	1258	NNE	2191	Yes
ROBE	SYCON LINEA3	2740	986	SSW	3011	Yes
ROBE	EIFS-75EPS-DF	2740	1800	SSW	600	Yes
WC	EIFS-75EPS-DF	2740	995	NNE	549	No
WC	EIFS-75EPS-DF	2740	1601	WNW	551	Yes
WC	EIFS-75EPS-DF	2740	1613	SSW	600	Yes

Internal wall *type*

Wall ID	Wall Type	Area (m ²)	Bulk insulation
INT-PB	Internal Plasterboard Stud Wall	78.3	1.50
INT-PB	Internal Plasterboard Stud Wall	141.5	0.00
INT-PB	Internal Plasterboard Stud Wall	21.0	4.00
INT-PB	Internal Plasterboard Stud Wall	1.1	2.70

Floor *type*

Location	Construction	Area (m ²)	Sub-floor ventilation	Added insulation (R-value)	Covering
BATH	CSOG-100: Concrete Slab on Ground (100mm)	8.3	N/A	1.00	Tile
BED 2	CSOG-100: Concrete Slab on Ground (100mm)	14.5	N/A	1.00	Exposed
BED 3	CSOG-100: Concrete Slab on Ground (100mm)	12.5	N/A	1.00	Exposed
BED 4	CSOG-100: Concrete Slab on Ground (100mm)	14.5	N/A	1.00	Exposed
ENSUITE	CSOG-100: Concrete Slab on Ground (100mm)	11.8	N/A	1.00	Tile

Floor type

Location	Construction	Area (m ²)	Sub-floor ventilation	Added insulation (R-value)	Covering
GARAGE	CSOG-100: Concrete Slab on Ground (100mm)	43.1	N/A	1.00	Exposed
HALLWAY	CSOG-100: Concrete Slab on Ground (100mm)	7.6	N/A	1.00	Exposed
HALLWAY 2	CSOG-100: Concrete Slab on Ground (100mm)	12.9	N/A	1.00	Exposed
KITCHEN	CSOG-100: Concrete Slab on Ground (100mm)	77.8	N/A	1.00	Exposed
LDRY	CSOG-100: Concrete Slab on Ground (100mm)	6.8	N/A	1.00	Tile
LINEN	CSOG-100: Concrete Slab on Ground (100mm)	3.1	N/A	1.00	Exposed
M BED	CSOG-100: Concrete Slab on Ground (100mm)	25.2	N/A	1.00	Exposed
MEDIA	CSOG-100: Concrete Slab on Ground (100mm)	15.2	N/A	1.00	Exposed
OFFICE	CSOG-100: Concrete Slab on Ground (100mm)	8.8	N/A	1.00	Exposed
PANTRY	CSOG-100: Concrete Slab on Ground (100mm)	7.1	N/A	1.00	Exposed
ROBE	CSOG-100: Concrete Slab on Ground (100mm)	12.0	N/A	1.00	Exposed
WC	CSOG-100: Concrete Slab on Ground (100mm)	4.7	N/A	1.00	Tile

Ceiling type

Location	Construction	Bulk insulation (R-value)	Reflective wrap*
BATH	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
BED 2	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
BED 3	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
BED 4	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
ENSUITE	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
GARAGE	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
HALLWAY	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
HALLWAY 2	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
KITCHEN	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
KITCHEN	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
LDRY	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes

* Refer to glossary.

Ceiling type

Location	Construction	Bulk insulation (R-value)	Reflective wrap*
LINEN	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
M BED	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
MEDIA	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
OFFICE	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
PANTRY	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
ROBE	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
WC	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes

Ceiling penetrations*

Location	Quantity	Type	Diameter (mm)	Sealed /unsealed
BATH	1	Exhaust Fan	350	Sealed
ENSUITE	1	Exhaust Fan	350	Sealed
KITCHEN	1	Exhaust Fan	350	Sealed
KITCHEN	1	Chimney	350	Sealed

Ceiling fans

Location	Quantity	Diameter (mm)
BED 2	1	900
BED 3	1	900
BED 4	1	900
KITCHEN	1	1500
M BED	1	1200

Roof type

Construction	Added insulation (R-value)	Solar absorptance	Roof Colour
ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	1.30	0.30	Light
FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	1.30	0.30	Light



Thermal bridging *schedule for steel frame elements*

Building element	Steel section dimensions (height x width, mm)	Frame spacing (mm)	Steel thickness (BMT mm)	Thermal Break (R-value)
None				

Explanatory Notes

About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the home's energy value*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary.

Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and

are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

Glossary

Annual energy load	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
AFRC	Australian Fenestration Rating Council
Assessed floor area	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
Ceiling penetrations	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
Conditioned	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
COP	Coefficient of performance
Custom windows	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
Default windows	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
EER	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
Energy use	This is your home's rating without solar or batteries.
Energy value	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
Entrance door	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
Exposure	see exposure categories below
Exposure category - exposed	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
Exposure category - open	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
Exposure category - suburban	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
Exposure category - protected	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
Horizontal shading feature	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
National Construction Code (NCC) Class	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at www.abcb.gov.au .
Net zero home	a home that achieves a net zero energy value*.
Opening percentage	the openability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
Provisional value	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at www.nathers.gov.au
Recommended capacity	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
Reflective wrap (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
Roof window	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
Shading features	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
Solar heat gain coefficient (SHGC)	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
Skylight (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
STCs	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulatory
Thermal breaks	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick, continuous thermal breaks such as polystyrene insulation sheeting, plastic strips or furring channels.
U-value	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
Unconditioned	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions
Vertical shading features	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
Window shading device	a device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)

* Refer to glossary.