

# Nationwide House Energy Rating Scheme®

## NatHERS® Certificate No. 0009285099

Generated on 07 Mar 2024 using BERS Pro v5.1.7 (3.22)

### Property

**Address** Unit B, 1070 Canterbury Road,  
ROSELANDS, NSW, 2196

**Lot/DP** Lot 1 DP 35202

**NCC class\*** 1a

**Floor/all Floors** G of 2 floors

**Type** New Home

### Plans

**Main plan** n/a

**Prepared by** n/a

### Construction and environment

<b>Assessed floor area [m2]*</b>		<b>Exposure type</b>
Conditioned*	141.8	Suburban
Unconditioned*	18.3	
Total	176.2	<b>NatHERS climate zone</b>
Garage	16.1	56 Mascot (Sydney Airport)



### Accredited assessor

**Name** Zoran Cvetkovski

**Business name** Sustainability-Z

**Email** sustainability-z@outlook.com

**Phone** 0414273176

**Accreditation No.** DMN/13/1641

**Assessor Accrediting Organisation**

Design Matters National

**Declaration of interest** Declaration not completed

### NCC Requirements

**NCC provisions** Volume Two

**Strate/Territory variation** Yes

#### National Construction Code (NCC) requirements


The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J3D3 and J3D15 of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at [www.abcb.gov.au](http://www.abcb.gov.au).

Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

### Thermal performance Star rating



### Thermal performance [MJ/m²]

Limits taken from ABCB Standard 2022

	Heating	Cooling
Modelled	22.4	7.3
Load limits	N/A	N/A

#### Features determining load limits

Floor Type (lowest conditioned area)	CSOG
NCC climate zone 1 or 2	No
Outdoor living area	No
Outdoor living area ceiling fan	No

### Whole of Home performance rating

No Whole of Home  
performance rating  
generated for this  
certificate.

### Verification

To verify this certificate,  
scan the QR code or visit  
[hstar.com.au/QR/Generate?  
p=oqzQPnRfr](http://hstar.com.au/QR/Generate?p=oqzQPnRfr).  
When using either link,  
ensure you are visiting  
[hstar.com.au](http://hstar.com.au)



## About the ratings

### Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

### Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value\* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

## Heating & Cooling Load Limits

### Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the *ABC Standard 2022: NatHERS heating and cooling load limits* for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

### Setting Options:

Floor Type:

CSOG – Concrete Slab on Ground  
SF – Suspended Floor (or a mixture of CSOG and SF)  
NA – Not Applicable

NCC Climate Zone 1 or 2:

Yes  
No  
NA – Not Applicable

Outdoor Living Area:

Yes  
No  
NA – Not Applicable

Outdoor Living Area Ceiling Fan:

Yes  
No  
NA – Not Applicable



## Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

## Predicted Whole of Home annual impact by appliance

### Energy use

No Whole of Home performance assessment conducted for this certificate

### Greenhouse gas emissions

No Whole of Home performance assessment conducted for this certificate

### Cost

No Whole of Home performance assessment conducted for this certificate



## Certificate check

The checklist covers important items impacting the dwelling's ratings. It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and by whom each item should be checked. It is not mandatory to complete this checklist.

	Approval Stage		Construction Stage		
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	Occupancy/Other
<b>Genuine certificate check</b>					
Does this Certificate match the one available at the web address or QR code verification link on the front page?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Thermal performance check</b>					
<b>Windows and glazed doors</b>					
Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the installed windows meet the substitution tolerances (AFRC* based SHGC* and U-values*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>External walls</b>					
Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the External wall type table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Floor</b>					
Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Ceiling penetrations*</b>					
Does the 'quantity' and 'type' of ceiling penetrations* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Ceiling</b>					
Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Roof</b>					
Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Apartment entrance doors (NCC Class 2 assessments only)</b>					
Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
<b>Exposure*</b>					
Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
<b>Heating and cooling load limits*</b>					
Do the load limits settings (shown on page 1) match what is shown	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>



## Certificate check

Continued

	Approval Stage		Construction Stage		
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	Occupancy/Other

### Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

#### Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?

☐ ☐ ☐ ☐

#### Insulation installation method

Has the insulation been installed according to the NCC requirements?

☐ ☐ ☐

#### Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?

☐ ☐ ☐ ☐

### Whole of Home performance check (not applicable if a Whole of Home performance assessment is not conducted)

#### Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the Appliance schedule on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or installed, match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

### Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?

☐ ☐ ☐ ☐

Does the hot water system meet the additional requirements specified in the NCC?

☐ ☐ ☐ ☐

#### Provisional values\* check

Have provisional values\* been used in the assessment and, if so, are they noted in 'Additional notes' table below?

☐ ☐ ☐ ☐

#### Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.

#### Additional notes

Rated with provisional values for downlights. All downlights: IC-F /IC-4/ (insulation covered/

including the control gears/) rated as per AS/NZS standard 60598 and IP (sealed) rated as per BS EN

60529:1992, European IEC 60509:1989.



Rated with ceiling fans (1200mm) throughout (as shown on the plans).

All bathrooms with ventilation opening of less than 5% are rated with mechanical ventilation.

Rated with waffle pod slab (175mm)/6.2 and 6.3 as per the NatHERS Technical Note 2023.

Rated with floor covering as specified by the client.

Rated with colours as per the material and finishes schedule (solar absorptance is calculated in the BERS software custom colours tool).

Rated with reduced insulation of R2.5 near the eave in the distance of 580mm (as per the housing provision note 10.8).

Rated with AWS windows.

In the absence of data in BERS for the sliding windows designated as AWS-093-02 ComfortEDGE Series 753 Uv 2.7 SHGC 0.53,

all sliding windows are categorized under AWS-071-25. Therefore, the code AWS-071-25 for fixed windows should be interpreted as applicable to sliding windows.

All coffer ceiling verticals and walls against the roof-space, to be insulated, with the same

insulation as the ceiling insulation.

Where the roof is extended over an open area such as a deck or carport: A barrier to be installed

within the roof space to separate the space above the zoned part of the house and the space above

the open veranda.

## Room schedule

Room	Zone Type	Area [m <sup>2</sup> ]
Garage-GF	Garage	16.13
Powder-GF	Unconditioned	4.89
Ldry/Ptry-GF	Unconditioned	5.67
Sitting-GF	Living	12.08
Kitch/Din/Fam-GF	Kitchen/Living	44.96
Hall/Stairs-GF	Daytime	16.83
M.Bed-FF	Bedroom	16.44
ENS/M.Bed-FF	Nighttime	3.63
WIR/M.Bed-FF	Nighttime	3.15
Bed 2-FF	Bedroom	11.05
Bed 3-FF	Bedroom	14.85
Bath-FF	Unconditioned	7.75
Rumpus-FF	Living	18.05
Seating-FF	Daytime	6.72





## Window and glazed door type and performance

### Default windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
TIM-001-03 W	Timber A SG High Solar Gain Low-E	4.3	0.42	0.40	0.44

### Custom windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
AWS-003-86 A	502/504 Al Sliding Window DG 4-12-4ClimaTech	3.3	0.51	0.48	0.54
AWS-067-09 A	RES SERIES 516 FIXED WINDOW DG 1_LightBridge_ClrS0_4-12-4	2.1	0.53	0.50	0.56
AWS-071-25 A	RES SERIES 616 FIXED WINDOW DG FGIOptEmaClr_4mm_16Ar_4mm	2.7	0.53	0.50	0.56
AWS-088-04 A	Series 755 Comfort Edge Awning Window DG AGG Is SI EA 4/12Ar/4	2.6	0.57	0.54	0.60
AWS-089-46 A	RES SERIES 704 FLUSH SLIDING DOOR DG LightBridge_ClrS0_5-12-5	2.2	0.56	0.53	0.59

## Window and glazed door schedule

Location	Window ID	Window no.	Height [mm]	Width [mm]	Window type	Opening %	Orientation	Window shading device*
Powder-GF	AWS-003-86 A	W15	600	1000	Sliding	45	E	No
Sitting-GF	AWS-071-25 A	W11	900	2650	Sliding	45	W	No
Sitting-GF	TIM-001-03 W	D10	1200	1050	Casement	90	N	No
Sitting-GF	AWS-088-04 A	W10	1800	800	Awning	60	N	No
Kitch/Din/Fam-GF	AWS-067-09 A	W14	600	2000	Fixed	00	E	No
Kitch/Din/Fam-GF	AWS-089-46 A	D17	2400	2500	Sliding	60	S	No
Kitch/Din/Fam-GF	AWS-003-86 A	W12	900	2650	Sliding	45	W	No
Kitch/Din/Fam-GF	AWS-003-86 A	W13	900	2500	Sliding	45	W	No
M.Bed-FF	AWS-003-86 A	W114	1800	2500	Sliding	10	S	No
ENS/M.Bed-FF	AWS-003-86 A	W115	600	1000	Sliding	45	E	No
Bed 2-FF	AWS-003-86 A	W116	900	2000	Sliding	10	E	No
Bed 3-FF	AWS-003-86 A	W111	900	2000	Sliding	10	W	No
Bed 3-FF	AWS-089-46 A	D109	2400	2000	Sliding	60	N	No
Bath-FF	AWS-003-86 A	W118	600	1000	Sliding	45	E	No

\* Refer to glossary.



Location	Window ID	Window no.	Height [mm]	Width [mm]	Window type	Opening %	Orientation	Window shading device*
Rumpus-FF	AWS-003-86 A	W117	900	1500	Sliding	10	E	No
Rumpus-FF	AWS-067-09 A	W112	2000	1200	Fixed	00	W	No
Seating-FF	AWS-003-86 A	W113	600	2000	Sliding	45	W	No

## Roof window\* type and performance value

### Default roof windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

### Custom roof windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

## Roof window\* schedule

Location	Window ID	Window no.	Opening %	Height [mm]	Width [mm]	Orientation	Outdoor shade	Indoor shade
No Data Available								

## Skylight\* type and performance

Skylight ID	Skylight description	Skylight shaft reflectance
No Data Available		

## Skylight\* schedule

Location	Skylight ID	Skylight No.	Skylight shaft length [mm]	Area [m <sup>2</sup> ]	Orientation	Outdoor shade	Diffuser
No Data Available							

## External door schedule

Location	Height [mm]	Width [mm]	Opening %	Orientation
Garage-GF	2400	2800	90	N
Ldry/Ptry-GF	2340	820	90	E
Sitting-GF	1140	1020	90	N



## External wall type

Wall ID	Wall type	Solar absorptance	Wall shade [colour]	Bulk insulation [R-value]	Reflective wall wrap*
EW-1	AAC Timber Stud Frame on Battens	0.16		Anti-glare foil with bulk no gap R2.7	No

## External wall schedule

Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
Garage-GF	EW-1	2970	5500	E	100	No
Garage-GF	EW-1	2970	300	S	100	No
Garage-GF	EW-1	2970	2995	N	2000	No
Powder-GF	EW-1	2800	1890	E	100	No
Ldry/Ptry-GF	EW-1	2800	2190	E	100	No
Sitting-GF	EW-1	2800	3995	W	100	No
Sitting-GF	EW-1	2800	3095	N	2000	Yes
Kitch/Din/Fam-GF	EW-1	2800	4895	E	100	Yes
Kitch/Din/Fam-GF	EW-1	2801	2900	E	100	No
Kitch/Din/Fam-GF	EW-1	2801	2100	S	100	No
Kitch/Din/Fam-GF	EW-1	2800	3700	S	2500	Yes
Kitch/Din/Fam-GF	EW-1	2800	7795	W	100	No
Hall/Stairs-GF	EW-1	2800	5590	W	100	No
M.Bed-FF	EW-1	2800	4095	S	100	Yes
M.Bed-FF	EW-1	2800	4095	W	100	No
ENS/M.Bed-FF	EW-1	2800	2195	E	100	No
ENS/M.Bed-FF	EW-1	2800	1695	S	100	No
WIR/M.Bed-FF	EW-1	2800	1890	E	100	No
Bed 2-FF	EW-1	2800	3690	E	100	No
Bed 3-FF	EW-1	2800	3995	W	100	No
Bed 3-FF	EW-1	2800	3795	N	2000	Yes
Bath-FF	EW-1	2800	1395	N	2000	No
Bath-FF	EW-1	2801	600	N	100	No
Bath-FF	EW-1	2800	3995	E	100	No
Rumpus-FF	EW-1	2800	2690	E	100	No





Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
Rumpus-FF	EW-1	2800	3790	W	100	No
Seating-FF	EW-1	2800	2590	W	100	No

## Internal wall type

Wall ID	Wall type	Area [m <sup>2</sup> ]	Bulk insulation
IW-001	Timber Stud Frame, Direct Fix Plasterboard	15.40	Bulk Insulation, No Air Gap R2.7
IW-002	Timber Stud Frame, Direct Fix Plasterboard	122.92	No insulation

## Floor type

Location	Construction	Area [m <sup>2</sup> ]	Sub-floor ventilation	Added insulation [R-value]	Covering
Garage-GF	Waffle pod slab 225 mm 85mm	16.13	None	Waffle Pod 225mm	Bare
Powder-GF	Waffle pod slab 225 mm 85mm	4.89	None	Waffle Pod 225mm	Ceramic Tiles 8mm
Ldry/Ptry-GF	Waffle pod slab 225 mm 85mm	5.67	None	Waffle Pod 225mm	Ceramic Tiles 8mm
Sitting-GF	Waffle pod slab 225 mm 85mm	12.08	None	Waffle Pod 225mm	Ceramic Tiles 8mm
Kitch/Din/Fam-GF	Waffle pod slab 225 mm 85mm	44.96	None	Waffle Pod 225mm	Ceramic Tiles 8mm
Hall/Stairs-GF	Waffle pod slab 225 mm 85mm	16.83	None	Waffle Pod 225mm	Ceramic Tiles 8mm
M.Bed-FF / Kitch/Din/Fam-GF	Timber Framed Timber Above Plasterboard 19mm	16.43		No Insulation	Cork Tiles or Parquetry 8mm
ENS/M.Bed-FF / Kitch/Din/Fam-GF	Timber Framed Timber Above Plasterboard 19mm	3.63		No Insulation	Ceramic Tiles 8mm
WIR/M.Bed-FF / Kitch/Din/Fam-GF	Timber Framed Timber Above Plasterboard 19mm	3.15		No Insulation	Cork Tiles or Parquetry 8mm
Bed 2-FF / Powder-GF	Timber Framed Timber Above Plasterboard 19mm	1.74		No Insulation	Cork Tiles or Parquetry 8mm
Bed 2-FF / Ldry/Ptry-GF	Timber Framed Timber Above Plasterboard 19mm	5.56		No Insulation	Cork Tiles or Parquetry 8mm
Bed 2-FF / Kitch/Din/Fam-GF	Timber Framed Timber Above Plasterboard 19mm	2.25		No Insulation	Cork Tiles or Parquetry 8mm
Bed 2-FF / Hall/Stairs-GF	Timber Framed Timber Above Plasterboard 19mm	1.24		No Insulation	Cork Tiles or Parquetry 8mm
Bed 3-FF / Garage-GF	Timber Framed Timber Above Plasterboard 19mm	2.53		Bulk Insulation R2.5	Cork Tiles or Parquetry 8mm
Bed 3-FF / Sitting-GF	Timber Framed Timber Above Plasterboard 19mm	12.05		No Insulation	Cork Tiles or Parquetry 8mm



Location	Construction	Area [m <sup>2</sup> ]	Sub-floor ventilation	Added insulation [R-value]	Covering
Bath-FF / Garage-GF	Timber Framed Timber Above Plasterboard 19mm	7.75		Bulk Insulation R2.5	Ceramic Tiles 8mm
Rumpus-FF / Garage-GF	Timber Framed Timber Above Plasterboard 19mm	0.00		Bulk Insulation R2.5	Cork Tiles or Parquetry 8mm
Rumpus-FF / Powder-GF	Timber Framed Timber Above Plasterboard 19mm	0.00		No Insulation	Cork Tiles or Parquetry 8mm
Rumpus-FF / Hall/Stairs-GF	Timber Framed Timber Above Plasterboard 19mm	4.86		No Insulation	Cork Tiles or Parquetry 8mm
Seating-FF / Kitch/Din/Fam-GF	Timber Framed Timber Above Plasterboard 19mm	2.05		No Insulation	Cork Tiles or Parquetry 8mm
Seating-FF / Hall/Stairs-GF	Timber Framed Timber Above Plasterboard 19mm	4.59		No Insulation	Cork Tiles or Parquetry 8mm

## Ceiling type

Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap* [yes/no]
Garage-GF	Plasterboard on Timber	Bulk Insulation R2.5	
Garage-GF	Timber Framed Timber Above Plasterboard	Bulk Insulation R2.5	
Powder-GF	Timber Framed Timber Above Plasterboard	No Insulation	
Ldry/Ptry-GF	Timber Framed Timber Above Plasterboard	No Insulation	
Sitting-GF	Timber Framed Timber Above Plasterboard	No Insulation	
Kitch/Din/Fam-GF	Plasterboard on Timber	Bulk Insulation R5	
Kitch/Din/Fam-GF	Plasterboard on Timber	Bulk Insulation R2.5	
Kitch/Din/Fam-GF	Timber Framed Timber Above Plasterboard	No Insulation	
Hall/Stairs-GF	Timber Framed Timber Above Plasterboard	No Insulation	
M.Bed-FF	Plasterboard on Timber	Bulk Insulation R5	
M.Bed-FF	Plasterboard on Timber	Bulk Insulation R2.5	
ENS/M.Bed-FF	Plasterboard on Timber	Bulk Insulation R5	
WIR/M.Bed-FF	Plasterboard on Timber	Bulk Insulation R5	
Bed 2-FF	Plasterboard on Timber	Bulk Insulation R5	
Bed 3-FF	Plasterboard on Timber	Bulk Insulation R5	
Bed 3-FF	Plasterboard on Timber	Bulk Insulation R2.5	
Bath-FF	Plasterboard on Timber	Bulk Insulation R5	
Rumpus-FF	Plasterboard on Timber	Bulk Insulation R5	
Rumpus-FF	Plasterboard on Timber	Bulk Insulation R2.5	

\* Refer to glossary.



Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap* [yes/no]
Seating-FF	Plasterboard on Timber	Bulk Insulation R5	
Seating-FF	Plasterboard on Timber	Bulk Insulation R2.5	

### Ceiling penetrations\*

Location	Quantity	Type	Diameter [mm]	Sealed/unsealed
Powder-GF	1	Downlights - LED	0	Sealed
Ldry/Ptry-GF	1	Downlights - LED	0	Sealed
Sitting-GF	5	Downlights - LED	0	Sealed
Kitch/Din/Fam-GF	18	Downlights - LED	0	Sealed
Kitch/Din/Fam-GF	1	Exhaust Fans	300	Sealed
Hall/Stairs-GF	4	Downlights - LED	0	Sealed
M.Bed-FF	8	Downlights - LED	0	Sealed
ENS/M.Bed-FF	1	Downlights - LED	0	Sealed
WIR/M.Bed-FF	1	Downlights - LED	0	Sealed
Bed 2-FF	4	Downlights - LED	0	Sealed
Bed 3-FF	6	Downlights - LED	0	Sealed
Bath-FF	2	Downlights - LED	0	Sealed
Bath-FF	1	Exhaust Fans	300	Sealed
Rumpus-FF	8	Downlights - LED	0	Sealed
Seating-FF	1	Downlights - LED	0	Sealed

### Ceiling fans

Location	Quantity	Diameter [mm]
Sitting-GF	1	1200
Kitch/Din/Fam-GF	1	1200
M.Bed-FF	1	1200
Bed 2-FF	1	1200
Bed 3-FF	1	1200
Rumpus-FF	1	1200

## Roof type

Construction	Added insulation [R-value]	Solar absorptance	Roof shade[colour]
Waterproofing Membrane	No Insulation, Only an Air Gap	0.5	Medium
Corrugated Iron Timber Frame	Bulk, Reflective Side Down, No Air Gap Above R1.3	0.32768	Light
Corrugated Iron Timber Frame	Bulk, Reflective Side Down, No Air Gap Above R1.8	0.33	Light

## Thermal bridging schedule for steel frame elements

Building element	Steel section dimensions [height x width, mm]	Frame spacing [mm]	Steel thickness [BMT,mm]	Thermal break [R-value]
No Data Available				

## Appliance schedule

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

Note: A flat assumption of 5W/m<sup>2</sup> is used for lighting, therefore lighting is not included in the appliance schedule.

### Cooling system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				

### Heating system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				

### Hot water system

Appliance/ system type	Fuel type	Hot Water	Minimum efficiency /STC	Zone 3 STC	Zone 3 Substitution tolerance ranges		Assessed daily load [litres]
		CER Zone			lower limit	upper limit	
No Data Available							

### Pool/spa equipment

Appliance/ system type	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available			



Onsite Renewable Energy Schedule

System Type	Orientation	System Size Or Generation Capacity
No Data Available		

Battery Schedule

System Type	Size [Battery Storage Capacity]
No Data Available	



## Explanatory notes

### About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value\* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the home's energy value\*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary.

Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

### Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and

are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

### Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

## Glossary

<b>AFRC</b>	Australian Fenestration Rating Council
<b>Annual energy load</b>	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
<b>Assessed floor area</b>	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
<b>Ceiling penetrations</b>	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
<b>COP</b>	Coefficient of performance
<b>Conditioned</b>	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
<b>Custom windows</b>	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
<b>Default windows</b>	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
<b>EER</b>	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
<b>Energy use</b>	This is your home's rating without solar or batteries.
<b>Energy value</b>	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
<b>Entrance door</b>	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
<b>Exposure</b>	see exposure categories below.
<b>Exposure category – exposed</b>	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
<b>Exposure category – open</b>	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
<b>Exposure category – protected</b>	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
<b>Exposure category – suburban</b>	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
<b>Horizontal shading feature</b>	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
<b>National Construction Code (NCC) Class</b>	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at <a href="http://www.abcb.gov.au">www.abcb.gov.au</a> .
<b>Net zero home</b>	a home that achieves a net zero energy value*.
<b>Opening percentage</b>	the operability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
<b>Provisional value</b>	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at <a href="http://www.nathers.gov.au">www.nathers.gov.au</a>
<b>Recommended capacity</b>	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
<b>Reflective wrap</b> (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
<b>Roof window</b>	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
<b>Shading features</b>	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
<b>Skylight</b> (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
<b>Solar heat gain coefficient (SHGC)</b>	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
<b>STCs</b>	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulator (CER)
<b>Thermal breaks</b>	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick or continuous thermal breaks such as polystyrene insulation sheathing or plastic strips
<b>U-value</b>	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
<b>Unconditioned</b>	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions.
<b>Vertical shading features</b>	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
<b>Window shading device</b>	device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)

\* Refer to glossary.