

# Nationwide House Energy Rating Scheme®

## NatHERS® Certificate No. #HR-EQ1SUU-01

Generated on 19 Jun 2024 using Hero 4.0 (Chenath v3.23)

### Property

**Address** 11 Surrey ave, Georges Hall, NSW, 2198

**Lot/DP**

**NCC Class\*** 1a

**Floor/all Floors** 1 of 3 floors

**Type** New

### Plans

**Main Plan** A received 18/06/2024

**Prepared by** Signs Studio

### Construction and environment

Assessed floor area (m²)*	Exposure Type
<b>Conditioned*</b> 201.6	Suburban
<b>Unconditioned*</b> 17.1	<b>NatHERS climate zone</b>
<b>Total</b> 287.9	56 - Mascot AMO
<b>Garage</b> 69.2	



### Accredited assessor

<b>Name</b>	Bianca Nguyen
<b>Business name</b>	Freeline Studio
<b>Email</b>	bianca.nguyen@freelinestudio.com.au
<b>Phone</b>	+61 426260963
<b>Accreditation No.</b>	101484
<b>Assessor Accrediting Organisation</b>	ABSA
<b>Declaration of interest</b>	No Conflict of Interest

### NCC Requirements

<b>BCA provisions</b>	Volume 2
<b>State/Territory variation</b>	Yes

#### National Construction Code (NCC) requirements


The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J2D2(2)(a) and (3) of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at [www.abcb.gov.au](http://www.abcb.gov.au).

Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

### Thermal performance star rating



### Thermal performance (MJ/m²)

Limits taken from ABCB Standard 2022

	Heating	Cooling
<b>Modelled</b>	16.1	13.9
<b>Load limits</b>	25	18

#### Features determining load limits

Floor type	
(lowest conditioned area)	CSOG
NCC climate zone 1 or 2	N
Outdoor living area	N
Outdoor living area ceiling fan N	

### Whole of Home performance rating

No Whole of Home  
performance rating  
generated for this  
certificate.

### Verification

To verify this certificate, scan the QR code or visit

<http://www.hero-software.com.au/pdf/HR-EQ1SUU-01>.

When using either link, ensure you are visiting <http://www.hero-software.com.au>



\* Refer to glossary.

## About the ratings

### Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

### Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value\* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

## Heating and Cooling Load Limits

### Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the *ABCB Standard: NatHERS heating and cooling load limits* for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

### Setting options:

Floor type:

- CSOG - Concrete Slab on Ground
- SF - Suspended Floor (or a mixture of CSOG and SF)
- NA - Not Applicable

NCC climate Zone 1 or 2:

- Yes
- No
- NA - Not Applicable

Outdoor living area:

- Yes
- No
- NA - Not Applicable

Outdoor living area ceiling fan:

- Yes
- No
- NA - Not Applicable



## Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

## Predicted Whole of Home annual impact by appliance

Shows the contribution each appliance has on the home's annual energy use, greenhouse gas emissions and cost without solar.

### Energy use:

No Whole of Home performance assessment conducted for this certificate.

### Greenhouse gas emissions:

No Whole of Home performance assessment conducted for this certificate.

### Cost:

No Whole of Home performance assessment conducted for this certificate.

## Certificate check

The checklist covers important items impacting the dwelling's ratings.

It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and who should check each item.

It is not mandatory to complete this checklist.

Approval stage		Construction stage		
Assessor checked	Consent authority/ surveyor checked	Builder checked	Consent authority/ surveyor checked	Occupancy/other

### Genuine certificate check

Does this Certificate match the one available at the web address or QR code verification link on the front page?

☐☐☐☐

Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?

☐☐☐☐

### Thermal performance check

#### Windows and glazed doors

Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?

☐☐☐☐☐

Does the installed windows meet the substitution tolerances (AFRC\* based SHGC\* and U-values\*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?

☐☐☐

#### External walls

Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'External wall type table' on this Certificate?

☐☐☐☐☐

Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?

☐☐☐☐☐

#### Floor

Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?

☐☐☐☐☐

#### Ceiling penetrations\*

Does the 'quantity' and 'type' of ceiling penetrations\* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?

☐☐☐☐☐

#### Ceiling

Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?

☐☐☐☐☐

#### Roof

Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?

☐☐☐☐☐

#### Apartment entrance doors (NCC Class 2 assessments only)

Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.

☐☐☐☐

#### Exposure\*

Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".

☐☐☐☐

#### Heating and cooling load limits\*

Do the load limits settings (shown on page 1) match what is shown on the NatHERS-stamped plans?

☐☐☐☐☐

\* Refer to glossary.

## Certificate check

Continued

Approval stage		Construction stage		
Assessor checked	Consent authority/ surveyor checked	Builder checked	Consent authority/ surveyor checked	Occupancy/other

### Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

#### Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--	--------------------------	--------------------------	--------------------------	--------------------------

#### Insulation installation method

Has the insulation been installed according to the NCC requirements?			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--	--	--------------------------	--------------------------	--------------------------

#### Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
---	--	--------------------------	--------------------------	--------------------------	--------------------------

### Whole of Home performance check (not applicable if a Whole of Home assessment is not conducted)

#### Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed, match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

### Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the hot water system meet the additional requirements specified in the NCC?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

#### Provisional values\* check

Have provisional values* been used in the assessment and, if so, are they noted in 'Additional notes' table below?	<input type="checkbox"/>	<input type="checkbox"/>			
--	--------------------------	--------------------------	--	--	--

#### Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.



Room schedule

Room	Zone Type	Area (m²)
KITCHEN/LIVING	Kitchen/Living	97.76
LAUNDRY	Unconditioned	4.84
PANTRY	Day Time	6.09
BATH	Unconditioned	4.36
GUEST	Bedroom	15.04
GARAGE	Garage	69.17
MASTER	Bedroom	21.08
WIR.	Night Time	9.06
ENS.	Night Time	5.16
BATH	Unconditioned	7.86
BED 2	Bedroom	15.55
LOUNGE	Living	50.53

Window and glazed door type and performance

Default\* windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
ALM-003-03 A	Aluminium A DG Air Fill High Solar Gain low-E -Clear	4.30	0.47	0.45	0.49
ALM-004-03 A	Aluminium B DG Air Fill High Solar Gain low-E -Clear	4.30	0.53	0.50	0.56

Custom\* windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

Window and glazed door schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orient-ation	Shading device*
----------	-----------	------------	-------------	------------	-------------	-----------	--------------	-----------------

\* Refer to glossary.



## Window and glazed door *schedule*

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orient-ation	Shading device*
BATH	ALM-003-03 A	W.G10	800	600	Awning	90	ESE	None
BATH	ALM-004-03 A	W.L02	800	1800	Sliding	45	ESE	None
BED 2	ALM-004-03 A	W.L06	2400	2400	Sliding Door	45	NNE	None
BED 2	ALM-003-03 A	W.L05	1750	900	Awning	90	ESE	None
ENS.	ALM-003-03 A	W.L03	1750	900	Awning	90	SSW	None
GUEST	ALM-004-03 A	W.G04	2400	2200	Sliding Door	45	ESE	None
KITCHEN/LIVING	ALM-004-03 A	W.G05	2900	1800	Fixed	0	ESE	None
KITCHEN/LIVING	ALM-003-03 A	W.G03	1850	900	Awning	90	SSW	None
KITCHEN/LIVING	ALM-003-03 A	W.G03	1850	900	Awning	90	SSW	None
KITCHEN/LIVING	ALM-003-03 A	W.G02	1850	3600	Awning	40	WNW	None
KITCHEN/LIVING	ALM-004-03 A	W.G01 BOTTOM RIGHT	2400	450	Fixed	0	WNW	None
KITCHEN/LIVING	ALM-004-03 A	W.G01 BOTTOM LEFT	2400	450	Fixed	0	WNW	None
KITCHEN/LIVING	ALM-004-03 A	W.G01 BOTTOM OVER DOOR	600	2200	Fixed	0	WNW	None
KITCHEN/LIVING	ALM-003-03 A	W.G08	2400	900	Awning	60	NNE	None
KITCHEN/LIVING	ALM-003-03 A	W.G08	2400	900	Awning	60	NNE	None
KITCHEN/LIVING	ALM-004-03 A	W.G09	2400	2500	Sliding Door	45	WNW	None
KITCHEN/LIVING	ALM-004-03 A	W.G09	2400	2500	Sliding Door	45	WNW	None
LAUNDRY	ALM-003-03 A	W.G06	2400	900	Hinged Door	90	ESE	None
LOUNGE	ALM-004-03 A	W.G01 TOP	2700	2200	Fixed	0	WNW	None
LOUNGE	ALM-003-03 A	W.L07	1750	900	Awning	90	NNE	None
LOUNGE	ALM-003-03 A	W.L07	1750	900	Awning	90	NNE	None
LOUNGE	ALM-004-03 A	W.L04	2400	1800	Fixed	0	ESE	None
LOUNGE	ALM-004-03 A	W.L08	2400	2500	Sliding Door	45	WNW	None
LOUNGE	ALM-004-03 A	W.L08	2400	2500	Sliding Door	45	WNW	None

\* Refer to glossary.



Window and glazed door *schedule*

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orient-ation	Shading device*
MASTER	ALM-004-03 A	W.L01	2400	3600	Sliding Door	45	WNW	None
PANTRY	ALM-004-03 A	W.G07	700	1800	Sliding	45	ESE	None
WIR.	ALM-004-03 A	W.L02	800	1800	Sliding	45	SSW	None

Roof window *type and performance value*

Default\* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

Custom\* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

Roof window *schedule*

Location	Window ID	Window no.	Opening %	Height (mm)	Width (mm)	Orient-ation	Outdoor shade	Indoor shade
None								

Skylight *type and performance*

Skylight ID	Skylight description
None	

Skylight *schedule*

Location	Skylight ID	Skylight No.	Skylight shaft length (mm)	Area (m²)	Orient-ation	Outdoor shade	Diffuser	Shaft Reflectance
None								

External door *schedule*

Location	Height (mm)	Width (mm)	Opening %	Orientation
GARAGE	2400	4800	90	WNW
KITCHEN/LIVING	2400	1300	90	WNW





## External wall type

Wall ID	Wall Type	Solar absorptance	Wall Colour	Bulk insulation (R-value)	Reflective wall wrap*
BV-REFL-CAV-REN	Brick Veneer Stud Wall with Reflective Sarking Rendered	0.50	Medium	2.00	Yes
CAV-BRICK-110-110-RENx2	Cavity Brick Wall - 110mm/110mm Rendered Both sides	0.50	Medium	0.00	No
CONC-200-PB	Precast 200mm Concrete - Plasterboard Internally	0.50	Medium	0.00	No

## External wall schedule

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* projection (mm)	Vertical shading feature
BATH	BV-REFL-CAV-REN	3000	1601	ESE		Yes
BATH	BV-REFL-CAV-REN	3000	350	NNE		Yes
BATH	BV-REFL-CAV-REN	3000	2301	ESE	326	Yes
BATH	BV-REFL-CAV-REN	3000	350	NNE		Yes
BED 2	BV-REFL-CAV-REN	3000	3474	NNE	3089	Yes
BED 2	BV-REFL-CAV-REN	3000	4501	ESE	326	Yes
BED 2	BV-REFL-CAV-REN	3000	350	SSW		Yes
ENS.	BV-REFL-CAV-REN	3000	3100	ESE	326	Yes
ENS.	BV-REFL-CAV-REN	3000	1663	SSW	288	No
GARAGE	CONC-200-PB	2400	8815	NNE		No
GARAGE	CONC-200-PB	2400	7847	ESE		No
GARAGE	CONC-200-PB	2400	8815	SSW		No
GARAGE	CAV-BRICK-110-110-RENx2	2400	5134	WNW	348	Yes
GARAGE	CONC-200-PB	2400	2713	WNW		No
GUEST	BV-REFL-CAV-REN	3000	3814	SSW		Yes
GUEST	BV-REFL-CAV-REN	3000	3787	ESE		Yes
KITCHEN/LIVING	BV-REFL-CAV-REN	3000	2413	ESE		Yes
KITCHEN/LIVING	BV-REFL-CAV-REN	3000	5118	SSW		Yes
KITCHEN/LIVING	BV-REFL-CAV-REN	3000	5268	WNW	1316	Yes

\* Refer to glossary.





## External wall *schedule*

Location	Wall ID	Height (mm)	Width (mm)	Orient-ation	Horizontal shading feature* projection (mm)	Vertical shading feature
KITCHEN/LIVING	BV-REFL-CAV-REN	3000	1600	NNE		Yes
KITCHEN/LIVING	BV-REFL-CAV-REN	3000	3321	WNW	1885	Yes
KITCHEN/LIVING	BV-REFL-CAV-REN	3000	6575	NNE		Yes
KITCHEN/LIVING	BV-REFL-CAV-REN	3000	1420	ESE		Yes
KITCHEN/LIVING	BV-REFL-CAV-REN	3000	6794	WNW	3024	Yes
LAUNDRY	BV-REFL-CAV-REN	3000	2301	ESE		Yes
LAUNDRY	BV-REFL-CAV-REN	3000	1730	SSW		Yes
LOUNGE	BV-REFL-CAV-REN	3000	3269	WNW	1907	Yes
LOUNGE	BV-REFL-CAV-REN	3000	4001	NNE	265	No
LOUNGE	BV-REFL-CAV-REN	3000	2824	ESE		Yes
LOUNGE	BV-REFL-CAV-REN	3000	2406	ESE	676	Yes
LOUNGE	BV-REFL-CAV-REN	3000	6756	WNW	1540	Yes
MASTER	BV-REFL-CAV-REN	3000	1200	NNE		Yes
MASTER	BV-REFL-CAV-REN	3000	4001	SSW	288	No
MASTER	BV-REFL-CAV-REN	3000	5268	WNW	1545	Yes
PANTRY	BV-REFL-CAV-REN	3000	2293	NNE		Yes
PANTRY	BV-REFL-CAV-REN	3000	3514	ESE		Yes
WIR.	BV-REFL-CAV-REN	3000	2924	SSW	288	No

## Internal wall *type*

Wall ID	Wall Type	Area (m <sup>2</sup> )	Bulk insulation
BV-NONREFL-CAV	Brick Veneer Stud Wall with Non-Reflective Sarking	13.2	0.00
INT-PB	Internal Plasterboard Stud Wall	103.2	0.00
SGL-BRICK-REND	Single 90mm Brick Wall - Rendered Both Sides	15.6	0.00

## Floor *type*

Location	Construction	Area (m <sup>2</sup> )	Sub-floor ventilation	Added insulation (R-value)	Covering
----------	--------------	------------------------	-----------------------	----------------------------	----------



## Floor type

Location	Construction	Area (m <sup>2</sup> )	Sub-floor ventilation	Added insulation (R-value)	Covering
BATH	SUSP-CONC-150: Suspended Concrete Slab Floor (150mm)	3.8	N/A	0.15	Tile (8mm)
BATH	CSOG-150: Concrete Slab on Ground (150mm)	0.6	N/A	1.30	Tile (8mm)
BATH	TIMB-001: Suspended Timber Floor	7.9	N/A	0.15	Tile (8mm)
BED 2	TIMB-001: Suspended Timber Floor	15.6	N/A	0.15	Timber (19mm)
ENS.	TIMB-001: Suspended Timber Floor	5.2	N/A	0.15	Tile (8mm)
GARAGE	CSOG-150: Concrete Slab on Ground (150mm)	69.2	N/A	1.30	Exposed
GUEST	SUSP-CONC-150: Suspended Concrete Slab Floor (150mm)	13.3	N/A	0.15	Tile (8mm)
GUEST	CSOG-150: Concrete Slab on Ground (150mm)	1.8	N/A	1.30	Tile (8mm)
KITCHEN/LIVING	SUSP-CONC-150: Suspended Concrete Slab Floor (150mm)	46.1	N/A	0.15	Exposed
KITCHEN/LIVING	CSOG-150: Concrete Slab on Ground (150mm)	51.7	N/A	1.30	Exposed
LAUNDRY	CSOG-150: Concrete Slab on Ground (150mm)	4.8	N/A	1.30	Tile (8mm)
LOUNGE	TIMB-001: Suspended Timber Floor	50.5	N/A	0.15	Timber (19mm)
MASTER	TIMB-001: Suspended Timber Floor	21.1	N/A	0.15	Timber (19mm)
PANTRY	CSOG-150: Concrete Slab on Ground (150mm)	6.1	N/A	1.30	Tile (8mm)
WIR.	TIMB-001: Suspended Timber Floor	9.1	N/A	0.15	Timber (19mm)

## Ceiling type

Location	Construction	Bulk insulation (R-value)	Reflective wrap*
BATH	ATTIC-CONCTILE-01: Pitched / Attic Conc Tiled Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
BED 2	ATTIC-CONCTILE-01: Pitched / Attic Conc Tiled Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
ENS.	ATTIC-CONCTILE-01: Pitched / Attic Conc Tiled Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
KITCHEN/LIVING	FLAT-03: Flat Framed / Skillion Tile Roof & Flat PB Ceiling	4.00	Yes
LAUNDRY	FLAT-03: Flat Framed / Skillion Tile Roof & Flat PB Ceiling	4.00	Yes
LOUNGE	ATTIC-CONCTILE-01: Pitched / Attic Conc Tiled Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
MASTER	ATTIC-CONCTILE-01: Pitched / Attic Conc Tiled Roof (Roofspace) & Flat PB Ceiling	4.00	Yes

\* Refer to glossary.



## Ceiling type

Location	Construction	Bulk insulation (R-value)	Reflective wrap*
PANTRY	FLAT-03: Flat Framed / Skillion Tile Roof & Flat PB Ceiling	4.00	Yes
WIR.	ATTIC-CONCTILE-01: Pitched / Attic Conc Tiled Roof (Roofspace) & Flat PB Ceiling	4.00	Yes

## Ceiling penetrations\*

Location	Quantity	Type	Diameter (mm)	Sealed /unsealed
BATH	2	Downlight	200	Sealed
BATH	2	Exhaust Fan	250	Sealed
BED 2	2	Downlight	200	Sealed
ENS.	1	Downlight	200	Sealed
ENS.	1	Exhaust Fan	250	Sealed
GUEST	1	Downlight	200	Sealed
KITCHEN/LIVING	14	Downlight	200	Sealed
KITCHEN/LIVING	1	Exhaust Fan	350	Sealed
LAUNDRY	1	Downlight	200	Sealed
LOUNGE	7	Downlight	200	Sealed
MASTER	3	Downlight	200	Sealed
PANTRY	1	Downlight	200	Sealed
WIR.	1	Downlight	200	Sealed

## Ceiling fans

Location	Quantity	Diameter (mm)
BED 2	1	2400
GUEST	1	2400
KITCHEN/LIVING	2	2400
LOUNGE	2	2400
MASTER	1	2400

\* Refer to glossary.



## Roof type

Construction	Added insulation (R-value)	Solar absorptance	Roof Colour
ATTIC-CONCTILE-01: Pitched / Attic Conc Tiled Roof (Roofspace) & Flat PB Ceiling	1.80	0.85	Dark
FLAT-03: Flat Framed / Skillion Tile Roof & Flat PB Ceiling	1.80	0.85	Dark

## Thermal bridging *schedule for steel frame elements*

Building element	Steel section dimensions (height x width, mm)	Frame spacing (mm)	Steel thickness (BMT mm)	Thermal Break (R-value)
None				

## Appliance *schedule*

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

### Cooling system

Type	Location	Fuel Type	Minimum efficiency / performance	Recommended capacity
No Whole of Home Data				

### Heating system

Type	Location	Fuel Type	Minimum efficiency / performance	Recommended capacity
No Whole of Home Data				

### Hot water system

Type	Fuel type	Hot Water CER Zone	Minimum efficiency / STC	Assessed daily load [litres]
No Whole of Home Data				

### Pool / spa equipment

Type	Fuel type	Minimum efficiency / performance	Recommended capacity
No Whole of Home Data			

## Onsite Renewable Energy *schedule*

Type	Orientatation	Generation Capacity [kW]
No Whole of Home Data		

## Battery *schedule*

Type	Storage Capacity [kWh]
No Whole of Home Data	

## Explanatory Notes

### About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value\* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the home's energy value\*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary.

Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

### Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and

are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

### Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

## Glossary

<b>Annual energy load</b>	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
<b>AFRC</b>	Australian Fenestration Rating Council
<b>Assessed floor area</b>	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
<b>Ceiling penetrations</b>	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
<b>Conditioned</b>	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
<b>COP</b>	Coefficient of performance
<b>Custom windows</b>	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
<b>Default windows</b>	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
<b>EER</b>	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
<b>Energy use</b>	This is your home's rating without solar or batteries.
<b>Energy value</b>	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
<b>Entrance door</b>	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
<b>Exposure</b>	see exposure categories below
<b>Exposure category - exposed</b>	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
<b>Exposure category - open</b>	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
<b>Exposure category - suburban</b>	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
<b>Exposure category - protected</b>	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
<b>Horizontal shading feature</b>	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
<b>National Construction Code (NCC) Class</b>	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at <a href="http://www.abcb.gov.au">www.abcb.gov.au</a> .
<b>Net zero home</b>	a home that achieves a net zero energy value*.
<b>Opening percentage</b>	the openability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
<b>Provisional value</b>	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at <a href="http://www.nathers.gov.au">www.nathers.gov.au</a>
<b>Recommended capacity</b>	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
<b>Reflective wrap (also known as foil)</b>	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
<b>Roof window</b>	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
<b>Shading features</b>	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
<b>Solar heat gain coefficient (SHGC)</b>	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
<b>Skylight (also known as roof lights)</b>	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
<b>STCs</b>	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulatory
<b>Thermal breaks</b>	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick, continuous thermal breaks such as polystyrene insulation sheeting, plastic strips or furring channels.
<b>U-value</b>	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
<b>Unconditioned</b>	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions
<b>Vertical shading features</b>	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
<b>Window shading device</b>	a device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)

\* Refer to glossary.