

SITE PLAN

SCALE: 1:200

DRAWING SCHEDULE

SHEET #	DRAWING TITLE	REV.
/1	SITE ANALYSIS	
/2	LANDSCAPE PLAN	
/3	DETAIL + SPECIFICATION	
/4	SECTIONS	

AN AUTOMATED COMMERCIAL GRADE IRRIGATION SYSTEM SHALL BE PROFESSIONALLY INSTALLED TO ALL GARDEN AREAS, INCLUDING RAISED PLANTERS, UPPER FLOOR PLANTERS AND GARDENS IN NATURAL GROUND. THE SYSTEM SHALL BE DESIGNED AND INSTALLED IN LINE WITH THE IRRIGATION PERFORMANCE SPECIFICATION, BY A LICENCED CONTRACTOR OR LANDSCAPER. THE LICENCED CONTRACTOR SHALL PREPARE AN 'AS BUILT' PLAN OF THE SYSTEM TO THE SUPERINTENDENT FOR STRATA RECORDS, FOR FUTURE MAINTENANCE.

LANDSCAPE PLAN NOTES

This plan should be read in conjunction with the architectural and hydraulics plans. Work specific to these plans should be prepared in accordance to these plans, including specification and details prior to the installation of landscaping, and should not be altered or compromised during landscape construction. **Retaining wall details to engineers design.** Elements such as drainage swales may be incorporated in garden bed areas (using non-flammable mulch) without compromising the capacity or form.

This plan has been prepared for DEVELOPMENT APPLICATION (S34) approval only, not for construction.

This plan has been prepared with reference to **CANTERBURY- BANKSTOWN Councils** Landscaping Guidelines & requirements. Planting proposed using commercially available plant species selected from local

planting lists and the BASIX local plant list and from Sydney Waters "Plant Selector" web site one-drip rated native plants (**acceptable for Basix planting**).

The Design & location of new letter boxes shall be in accordance with Australia Post's "Requirements for Delivery of Mail to Residential Premises" published Feb '97. All noxious weeds listed in Councils weed lists & located on the site shall be continually removed & suppressed. Reinstate all boundary fencing in poor condition with Council approved 1.8m fencing to rear of building line, rake to 1m forward of BL. Pollution, sediment & erosion control devices as specified shall be in place, and maintained for the duration of the construction period. Proposed excavation near existing established trees to be supervised by arborist.

D.A approved landscape plan's are required to be constructed as approved to obtain occupancy certificate. **Permeable areas may be indicated to achieve site coverage restrictions & should be constructed as drawn on this plan.**


LOCATION PLAN

Scale: NTS



HARDSCAPE ITEMS

- Bench seat. Proprietary item to supplier's specification
- Trees proposed to be removed and replaced with new landscaping
- Garden bed-refer landscape design plan
- Organic mulched path
- Concrete Driveway & path
- Lawn as spec.



LEGEND & SCHEDULE

- NOTES:
1. ALL FINAL PLANT QUANTITIES INDICATED ON PLANS SHALL BE CHECKED AND VERIFIED BY SUCCESSFUL LANDSCAPE CONTRACTOR
 2. ANY PLANT SUBSTITUTES REQUIRED DUE TO UNAVAILABILITY SHALL BE RECOMMENDED BY THE LANDSCAPE CONTRACTOR TO BEST MATCH SUBSTITUTED PLANTS AND APPROVED PRIOR TO PURCHASING BY THE LANDSCAPE ARCHITECT
 3. WORKS CERTIFIED FOR FINAL OCCUPANCY CERTIFICATE ARE TO MATCH APPROVED LANDSCAPE PLANS
 4. LANDSCAPE CONTRACTOR SHALL LOCATE AND AVOID SITE STORM WATER & DRAINAGE SERVICES. LOCATE TREES A MINIMUM 1.25M FROM PITS
 5. ALL PLANTING AROUND EXISTING TREES SHALL BE ADJUSTED TO AVOID DAMAGE AND CLASHING WITH SURFACE ROOTS
 6. THE NATURE STRIP (STREET FRONTAGE) FOR THE SITE IS PUBLIC LAND, AND ONLY AUTHORIZED WORKS MAY OCCUR HERE. EXISTING CONDITIONS SUCH AS STREET TREES, COUNCIL PLANTING ETC SHALL BE RETAINED AND PROTECTED DURING CONSTRUCTION, UNLESS SPECIFIC APPROVAL HAS BEEN GRANTED FOR NEW WORK IN THIS AREA.

TREES

- Botanical Name: *Backhousia myrtifolia*
Common Name: Grey Myrtle (Native)
Pot size: 45 LT
Mature H x S: 4-6m x 2-4m
Qty Required: 3
- Botanical Name: *Elaeocarpus eumundi*
Common Name: Eumundi Quandong (Native)
Pot size: 75LT
Mature H x S: 6-11m x 3-5m
Qty Required: 8
- Botanical Name: *Elaeocarpus reticulatus*
Common Name: Blueberry Ash (Native)
Pot size: 75LT
Mature H x S: 8-10m x 6-7m
Qty Required: 5
- Botanical Name: *Flindersia australis*
Common Name: Crow's Ash (Native)
Pot size: 75LT
Mature H x S: 12-15m x 8m
Qty Required: 9
- Botanical Name: *Tristanopsis laurina*
Common Name: Watergum (Native)
Pot size: 75LT
Mature H x S: 8-12m x 6m
Qty Required: 2
- Botanical Name: *Callitris rhomboidea*
Common Name: Port Jackson Pine (Native)
Pot size: 25LT
Mature H x S: 4-6m x 2-3m
Qty Required: 10
- Botanical Name: *Waterhousea floribunda*
Common Name: Weeping Lilly Pilly (Native)
Pot size: 75LT
Mature H x S: 10m x 6m
Qty Required: 6

SHRUBS

- PA Botanical Name: *Plectranthus argentatus*
Common Name: Midgenberry (Native)
Pot size: 200mm
Mature H x S: 0.5-1m x 0.5-1m
Qty Required: 28
- ASB Botanical Name: *Acmena 'Sublime'*
Common Name: Sublime Lilly Pilly (Native)
Pot size: 200mm
Mature H x S: 5m x 2.5m
Qty Required: 26
- BO Botanical Name: *Breynia oblongifolia*
Common Name: Coffee Bush (Native)
Pot size: 300mm
Mature H x S: 1-3m x 1.8m
Qty Required: 20
- EN Botanical Name: *Eremophila nivea*
Common Name: Naringa Coastal Rosemary (Native)
Pot size: 200mm
Mature H x S: 1-2m x 1.5m
Qty Required: 23
- SSN Botanical Name: *Syzygium australe* 'Straight and Narrow'
Common Name: Lilly Pilly (Native)
Pot size: 300mm
Mature H x S: 5-7m x 2m
Qty Required: 19
- WFM Botanical Name: *Westringia fruticosa* 'Mundi'
Common Name: Coastal Rosemary (Native)
Pot size: 200mm
Mature H x S: 0.35m x 1.5m
Qty Required: 19

ACCENT PLANTS

- LA Botanical Name: *Livistona australis*
Common Name: Cabbage Tree Palm (Native)
Pot size: 1m trunks
Mature H x S: 6-10m x 4m
Qty Required: 3
- LN Botanical Name: *Laurus nobilis* (Mopkop)
Common Name: Bay laurel (Exotic)
Pot size: Standard
Mature H x S: 1m x 1m
Qty Required: 4
- SD Botanical Name: *Strobilanthes dyerianus*
Common Name: Persian shield (Exotic)
Pot size: 200mm
Mature H x S: 1.0-1.5m x 1.0m
Qty Required: 19

LAWN


- Lawn
- Softleaf Buffalo
or as spec.

GRASSES + GROUNDCOVERS

- DC Botanical Name: *Dianella caerulea* 'Cassa Blue'
Common Name: Native Flax (Native)
Pot size: 140mm
Mature H x S: 0.4m x 0.5m
Qty Required: 5/m² (284m² total)
- AC Botanical Name: *Arthropodium cirratum*
Common Name: Renga Lily (Native)
Pot size: 140mm
Mature H x S: 0.75-1m x 0.5m
Qty Required: 5/m² (110m² total)
- LT Botanical Name: *Lomandra 'Tanika'*
Common Name: Dwarf Mat Rush (Native)
Pot size: 140mm
Mature H x S: 500mm x 600mm
Qty Required: 5/m² (181m² total)
- DR Botanical Name: *Dichondra repens*
Common Name: Kidney Weed (Native)
Pot size: 140mm
Mature H x S: 0.15m x spreading
Qty Required: 9/m² (120m² total)
- AH Botanical Name: *Actinotus helianthi*
Common Name: Flannel Flower (Native)
Pot size: 140mm
Mature H x S: 0.7m x 0.6
Qty Required: 5/m² (51.8m² total)
- BM Botanical Name: *Brachyscome multifida*
Common Name: Cut-leaf Daisy (Native)
Pot size: 140mm
Mature H x S: 0.4m x .6m
Qty Required: 5/m² (13.5m² total)
- HS Botanical Name: *Hibertia scandens*
Common Name: Snake Vine (Native)
Pot size: Tube stock
Mature H x S: 0.3m x spreading
Qty Required: 5/m² (245m² total)
- PA Botanical Name: *Pennisetum alopecuroides*
Common Name: Swamp Foxtail (Native)
Pot size: 140mm
Mature H x S: 1m x 1m
Qty Required: 5/m² (90m² total)

PLANT IMAGES


Images are indicative only, final planting species may vary, as determined by Council Approval



LEGEND & SCHEDULE

- NOTES:
1. ALL FINAL PLANT QUANTITIES INDICATED ON PLANS SHALL BE CHECKED AND VERIFIED BY SUCCESSFUL LANDSCAPE CONTRACTOR.
 2. ANY PLANT SUBSTITUTES REQUIRED DUE TO UNAVAILABILITY SHALL BE RECOMMENDED BY THE LANDSCAPE CONTRACTOR TO BEST MATCH SUBSTITUTED PLANTS AND APPROVED PRIOR TO PURCHASING BY THE LANDSCAPE ARCHITECT.
 3. WORKS CERTIFIED FOR FINAL OCCUPANCY CERTIFICATE ARE TO MATCH APPROVED LANDSCAPE PLANS.
 4. LANDSCAPE CONTRACTOR SHALL LOCATE AND AVOID SITE STORM WATER & DRAINAGE SERVICES. LOCATE TREES A MINIMUM 1.25M FROM PITS
 5. ALL PLANTING AROUND EXISTING TREES SHALL BE ADJUSTED TO AVOID DAMAGE AND CLASHING WITH SURFACE ROOTS
 6. THE NATURE STRIP (STREET FRONTAGE) FOR THE SITE IS PUBLIC LAND, AND ONLY AUTHORIZED WORKS MAY OCCUR HERE. EXISTING CONDITIONS SUCH AS STREET TREES, COUNCIL PLANTING ETC SHALL BE RETAINED AND PROTECTED DURING CONSTRUCTION, UNLESS SPECIFIC APPROVAL HAS BEEN GRANTED FOR NEW WORK IN THIS AREA.

TREES



Botanical Name: *Buckinghamia celsissima*
Common Name: Ivory Curl Tree(Native)
Pot size: 75Lt
Mature H x S: 5-7m x 5m
Qty Required: 3



Botanical Name: *Flindersia australis*
Common Name: Crow's Ash(Native)
Pot size: 75Lt
Mature H x S: 12-15m x 8m
Qty Required: 1

SHRUBS



Botanical Name: *Acmena 'Sublime'*
Common Name: Sublime Lilly Pilly (Native)
Pot size: 200mm
Mature H x S: 5m x 2.5m
Qty Required: 5



Botanical Name: *Syzygium australe 'Straight and Narrow'*
Common Name: Lilly Pilly (Native)
Pot size: 300mm
Mature H x S: 5-7m x 2m
Qty Required: 4

FERNS AND SHADE TOLERANT



Botanical Name: *Philodendron 'Xanadu'*
Common Name: Xanadu Plant (Exotic)
Pot size: 200mm
Mature H x S: 0.7m x 0.7m
Qty Required: 22



Botanical Name: *Strobilanthes dyerianus*
Common Name: Persian shield (Exotic)
Pot size: 200mm
Mature H x S: 1.0-1.5m x 1.0m
Qty Required: 12



Botanical Name: *Plectranthus argentatus*
Common Name: Silver Spurflower (Native)
Pot size: 200mm
Mature H x S: 0.5-1m x 0.5-1m
Qty Required: 8

ACCENT PLANTS



Botanical Name: *Hydrangea macrophylla 'Blue'*
Common Name: Hydrangea (Exotic)
Pot size: 300mm
Mature H x S: 3m x 1.2m
Qty Required: 15



Botanical Name: *Phoenix roebelenii*
Common Name: Dwarf Date Palm(Exotic)
Pot size: Min 1m Trunk
Mature H x S: 1m x 1m
Qty Required: 2

GRASSES + GROUNDCOVERS



Botanical Name: *Dianella caerulea 'Cassa Blue'*
Common Name: Native Flax (Native)
Pot size: 140mm
Mature H x S: 0.4m x 0.5m
Qty Required: 5/m² @23m² total



Botanical Name: *Arthropodium cirratum*
Common Name: Renga Lily (Native)
Pot size: 140mm
Mature H x S: 0.75-1m x 0.5m
Qty Required: 6/m² @21.5m² total



Botanical Name: *Actinotus helianthi*
Common Name: Flannel Flower (Native)
Pot size: 140mm
Mature H x S: 0.7m x 0.6
Qty Required: 5/m² (7m² total)



Botanical Name: *Brachyscome multifida*
Common Name: Cut-leaf Daisy(Native)
Pot size: 140mm
Mature H x S: 0.4m x .6m
Qty Required: 5/m² (9m² total)



Phoenix roebelenii



Buckinghamia celsissima



Strobilanthes dyerianus



Plectranthus argentatus



Hydrangea



Dianella caerulea 'Cassa Blue'



Arthropodium cirratum










Brachyscome multifida



Philodendron 'Xanadu'


GENERAL NOTE:
Figured dimensions take precedence to scale readings. Verify all dimensions on site. If the plan shows any discrepancy in scale to that indicated on plans, report any discrepancy to the Landscape Architect before proceeding with the work.
© Copyright & Free Landscape Architect Services 18-00-2023
This drawing is protected by copyright. All rights are reserved. Unless permitted under the Copyright Act 1969, no part of this drawing may be reproduced or used in any form or by any means for reproduction, publication, translation or otherwise without the prior written permission of the copyright owner.
If the State or other planning or regulatory authority requires this drawing to be subject to change, alteration or amendment at the discretion of our office.



REFER TO GROUND FLOOR PLAN

Trees
1 FA
Feature planting
1 P. roebelenii
6 P. 'Xanadu'
11m² D. caerulea
4 A. 'Sublime'
S. australe 'Straight & Narrow'
Feature/Scent plant
9 Strobilanthes.d
15 P. argentatus
10 H. macrophylla 'Blue'
Groundcover
8 Philodendron 'Xanadu'
7m² Actinotus helianthi
7.5m² Arthropodium cirratum
11m² Dianella

Trees
3 B. celsissima
Feature planting
1 P. roebelenii
P. 'Xanadu'
8 P. argentatus
12m² D. caerulea
1 A. 'Sublime'
Scent plant
5 H. macrophylla 'Blue'
3 Strobilanthes
14m² A. cirratum
7m² A. helianthi



ATRIUM GARDEN - LEVEL 1
SCALE 1:100

LANDSCAPE WORK SPECIFICATION

PRELIMINARIES

1.01 GENERAL

- The following general conditions should be considered prior to the commencement of landscape works:
- The landscape plans should be read in conjunction with the architectural plans, project arborist's assessment, hydraulic plans, service plans and survey prepared for the proposed development.
 - All services including existing drainage should be accurately located prior to the commencement of landscape installation. Any proposed tree planting which falls close to services will be relocated on site under the instruction of the landscape architect.
 - Installation of conduit for required irrigation, electrical and other services shall be completed prior to the commencement of hardscape works and handstand pour.
 - All outdoor lighting specified by architect or client to be installed by qualified electrician
 - Anomalies that occur in these plans should be brought to our immediate attention.
 - Where an Australian Standard applies for any landscape material testing or installation technique, that standard shall be followed.

1.02 PROTECTION OF ADJACENT FINISHES

The Contractor shall take all precautions to prevent damage to all or any adjacent finishes by providing adequate protection to these areas / surfaces prior to the commencement of the Works

1.03 PROTECTION OF EXISTING TREES

Existing trees identified to be retained shall be done in accordance with (AS)4970-Protection of trees on development sites as well as in accordance with the tree protection measures prepared by project arborist.

Where general works are occurring around such trees, or pruning is required, a qualified Arborist shall be engaged to oversee such works and manage tree health. Existing trees designated on the drawing for retention shall be protected at all times during the construction period. Any soil within the drip-line of existing trees shall be excavated and removed by hand only. No stockpiling shall occur within the root zone of existing trees to be retained.

Any roots larger in diameter than 50mm shall only be severed under instruction by a qualified arborist. Roots smaller than 50mm diameter shall be cut cleanly with a saw.

Temporary fencing shall be installed around the base of all trees to be retained prior to the commencement of landscape works. Where possible this fencing will be located around the drip line of these trees, or a minimum of 3m from the trunk. The fencing shall be maintained for the full construction period.

1.04 EROSION & POLLUTION CONTROL.

The Contractor shall take all proper precautions to prevent the erosion of soil from the subject site. The contractor shall install erosion & sediment control barriers and as required by council, and maintain these barriers throughout the construction period. Note that the sediment control measures adopted should reflect the soil type and erosion characteristics of the site.

- Erosion & pollution control measures shall incorporate the following:
- Construction of a sediment trap at the vehicle access point to the subject site.
 - Sediment fencing using a geotextile filter fabric in the location indicated on the erosion control plan or as instructed on site by the landscape architect.
 - Earth banks to prevent scour of stockpiles
 - Sandbag kerb sediment traps
 - Straw bale & geotextile sediment filter.
 - Exposed banks shall be pegged with an approved Jute matting in preparation for mass planting

Refer to 'Slewies Reference Kit' as prepared by DLWC & WSRCC (1997) for construction techniques

SOIL WORKS

2.01 MATERIALS

Specified Soil Conditioner (Generally to improve site soil)

The specified soil conditioner for site top-soil improvement shall be an organic mix, equal to 'Botany Humus', as supplied by ANL. Note that for sites where soil testing indicates toxins or extremes in pH, or soils that are extremely poor, allow to excavate and supply 300mm of imported soil mix.

New gardens & proposed Planting

New garden and planting areas shall consist of a 50/50 mix of clean site soil (refer d) below) and imported 'Organic Garden Mix' as supplied by ANL or approved equal. All mixes are to comply with AS 4419 Soils for landscaping & garden use, & AS 4454 Composts. Soil conditioners & mulches.

Specified Soil Mix - Turf

The specified soil mix for all turf areas shall be a min 75mm layer of imported soil mix consisting of 80% washed river sand (reasonably coarse), and 20% composted organic matter equivalent to mushroom compost or soil conditioner, or other approved lawn top dress.

Site Topsoil

Site topsoil is to be clean and free of unwanted matter such as gravel, clay lumps, grass, weeds, tree roots, sticks, rubbish and plastics, and any deleterious materials and materials toxic to plants. The topsoil must have a pH of between 5.5 and 7. Use 100% imported soil mix when site soil topsoil runs out.

2.02 INSTALLATION (TO GARDEN OUTSIDE OF TREE PROTECTION ZONES OF TREES RECOMMENDED TO BE RETAINED)

Note: No level changes (Cut or Fill), soil ripping within the Tree Protection Zones of trees to be retained

a) Testing

All testing is to be conducted in accordance with AS 1289 Methods for testing soils for engineering purposes. Site soil shall be given a pH test prior to modifying to ensure conditions are appropriate for planting as stated above. Tests shall be taken in several areas where planting is proposed, and the pH shall be adjusted accordingly with sulphur or lime to suit.

Note that a soil test conducted by the "Sydney Soil Lab" or approved equal shall be prepared for all commercial, industrial and multi-unit residential sites. The successful landscape contractor shall implement the recommendations of this test.

b) Set Out of Individual Trees & Mass Planting Areas

All individual tree planting positions and areas designated for mass planting shall be set out with stakes or another form of marking, ready for inspection and approval. Locate all services.

c) Establishing Subgrade Levels outside of tree protection zones of trees to be retained

Subgrade levels are defined as the finished base levels prior to the placement of the specified material (i.e. soil conditioner). The following subgrade levels shall apply:

- Mass Planting Beds - 300mm below existing levels with specified imported soil mix.
- Turf areas - 100mm below finished surface level.

Note that all subgrades shall consist of a relatively free draining natural material, consisting of site topsoil placed previously by the Civil Contractor. No builders waste material shall be acceptable.

d) Subgrade Cultivation

Cultivate all subgrades to a minimum depth of 100mm in all planting beds and all turf areas, ensuring a thorough breakup of the subgrade into a reasonably coarse blith. Grade subgrades to provide falls to surface and subsurface drains, prior to the placement of the final specified soil mix.

e) Drainage Works

Install surface and subsurface drainage where required and as detailed on the drawing. Drain subsurface drains to outlets provided, with a minimum fall of 1:100 to outlets and / or service pits.

f) Placement and Preparation of Specified Soil Conditioner & Mixes.

- Trees in turf & beds - Holes shall be twice as wide as root ball and minimum 100mm deeper - backfill hole with 50/50 mix of clean site soil and imported 'Organic Garden Mix' as supplied by ANL or approved equal.
 - Mass Planting Beds - Install specified soil conditioner to a compacted depth of 100mm
- Place the specified soil conditioner to the required compacted depth and use a rotary hoe to thoroughly mix the conditioner into the top 300mm of garden bed soil. Ensure thorough mixing and the preparation of a reasonably fine blith and good growing medium in preparation for planting.
- Turf Areas - Install specified soil mix to a minimum compacted depth of 75mm.
- Place the specified soil mix to the required compacted depth and grade to required finished soil levels, in preparation for planting and turfing.

PLANTING

3.01 MATERIALS

a) Quality and Size of Plant Material

All trees supplied above a 25L container size must be grown and planted in accordance with AS 2303:2018 'TREE STOCK FOR LANDSCAPE USE' Certification that trees have been grown to AS 2303:2018 is to be provided upon request of Council's Tree Management Officer.

Below - Ground Assessment

The following plant quality assessment criteria should be followed:

Plant true to type, Good vigour and health, free from pest & disease, free from injury, self-supporting, good stem taper, has been pruned correctly, is apically dominant, has even crown symmetry, free from included bark & stem junctions, even trunk position in pot, good stem structure

Below - Ground Assessment:

Good root division & direction, rootball occupancy, rootball depth, height of crown, non-suckering For further explanation and description of these assessment criteria, refer to Ross Clark's book.

All Plant material shall be to the type and size specified. No substitutions of plant material shall be permitted without written prior approval by the Landscape Architect. No plant shall be accepted which does not conform to the standards listed above.

b) Stakes and Ties

Provide min. 3 No. Stakes and ties to all plants identified as trees in the plant schedule. Stakes shall be sound, unpainted, straight hardwood, free of knots and pointed at one end. They shall be 2200mm x 50mm x 50mm Hardwood, or

approved alternative. Ties shall be 50mm wide hessian webbing material.

c) Fertilisers

Fertilisers shall be approved slow release fertilisers suitable for the proposed planting types. Note that for native plants, specifically Proteaceae family plants including Grevillea species, low phosphorus fertilizers shall be used.

d) Mulch

Mulch shall be an approved equal to 'Forest Blend' as supplied by ANL. Mulch shall be completely free from any soil, weeds, rubbish or other debris.

e) Turf

Turf shall be 'Sir Walter' Buffalo or equivalent (unless stated otherwise), free from any weeds and other grasses, and be in a healthy growing condition.

3.02 INSTALLATION

a) Setting Out

All planting set out shall be in strict accordance with the drawings, or as directed. Note that proposed tree planting located near services should be adjusted at this stage. Notify Landscape Architect for inspection for approval prior to planting.

b) Planting

All plant material shall be planted as soon after delivery as possible. Planting holes for trees shall be excavated as detailed and specified. Plant containers shall be removed and discarded, and the outer roots gently leaved from the soil mass. Immediately set plant in hole and backfill with specified soil mix, incorporating the approved quantity of fertiliser for each plant type. Ensure that plants are set plumb vertically and root balls set to the consolidated finished grades detailed on the drawings. Compact the backfilled soil and saturate by hand watering to expel any remaining air pockets immediately after planting.

c) Staking and Tying

Staking and tying shall be in strict accordance with the drawings and shall occur immediately following plant placement and soil backfilling. All plants identified as 'Trees' on the planting schedule shall be staked with a min. 3 stakes.

d) Mulching

Mulch should be spread so that a compacted thickness of 75mm is achieved after settlement in all planting beds and around each individual plant. Apply immediately following planting and watering in, ensuring that a 50mm radius is maintained around the trunk of each plant. There shall be no mixing of soil and mulch material.

e) Turfing

Moisten soil prior to the turf being laid. Turf shall be neatly butt jointed and true to grade to finish flush with adjacent surfaces. Incorporate a lawn fertilizer and thoroughly water in. Keep turf moist until roots have taken and sods/rolls cannot be lifted. Keep all traffic off turf until this has occurred. Allow for top dressing of all turf areas. All turf shall be rolled immediately following installation.

f) Brick garden edging

Where is required, the Contractor shall install Brick garden edging as detailed on the drawings, to all mass planting beds adjoining turf or gravel mulched areas, and where required. The resultant edge shall be true to line and flush with adjacent surfaces. However, no edging shall be used within the Structural Root Zone (SRZ) of trees to be retained.

HARDSCAPE WORKS

4.01 GENERAL

The Contractor shall undertake the installation of all hardscape works as detailed on the drawing, or where not detailed, by manufacturers specification.

- Paving - refer to typical details provided, and applicable Australian Standards. Permissible paving may be used as a suitable means of satisfying Council permeable surface requirements, while providing a useable, hardwearing, practical surface. In most instances, the client shall nominate the appropriate paving material to be used.

Australian Standards shall be adhered to in relation to all concrete, masonry & metal work. Some details are typical and may vary on site. All hardscape works shall be set out as per the drawings, and inspected and approved by the Landscape Architect prior to installation. All workmanship shall be of the highest standard. Any queries or problems that arise from hardscape variations should be brought to the attention of the Landscape Architect. Your attention is directed to any obligations or responsibilities under the Dividing Fences Act, 1991 in respect of adjoining property owners which may arise from this application. Any enquiries in this regard may be made to the Crown Lands Division on (02) 8836 5332.

IRRIGATION WORKS

5.01 GENERAL (PERFORMANCE SPECIFICATION)

New irrigation systems to planting areas shall be a Commercial Grade Irrigation System conforming to all relevant Australian standards, including AS 3500 & the Electrical Safety Act 2002, Workplace Health & Safety Act 1995, & the latest Sydney Water Code

An automated drip-irrigation system is to be installed to all gardens, planters and lawn areas in accordance with the approved Irrigation Design. This system shall be designed and installed by a qualified and licensed irrigation specialist, to the highest industry standards and to maximise the efficient usage of water. The installer is required to obtain all approvals necessary for the completion of works in accordance with the Laws of Australia, Laws of the State of NSW, Canterbury - Bankstown Council By-Laws and Ordinances.

Drawings:

- The Landscape Contractor nominated Licensed Irrigation Specialist shall provide irrigation drawings for approval upon engagement.

Design Requirements:

- The irrigation system shall be installed prior to all planting works. It shall incorporate a commercially available irrigation system, with sub-surface dripper lines to irrigate all gardens, planters and lawn areas.
- It shall incorporate a suitable back flow prevention device for the scale of works, an in-line filter, check valves, and suitable high and low density poly hose fittings and PVC piping to achieve flow rates suitable for specified planting.
- The irrigation application rate shall not exceed the infiltration rate of the soil or creates run-off.
- The landscape contractor shall check the existing pressure available from the ring mains and size irrigation piping to suit. Supply shall be from local hose cock where available.
- All piping and fittings shall be buried 50mm below the finished soil levels in garden and lawn areas, and secured in position at 500mm centres with galv wire pins.
- Size of pipes shall be selected to ensure the working pressure at the end of the line does not decrease by more than 5%.

Services Co-ordination:

- Co-ordination required by Landscape Contractor or Project Manager to provide required conduit, pipe work and penetration through slabs and planter walls for water and power provisions.
- The Landscape Contractor shall be engaged with the Irrigation Specialist to co-ordinate with the Project Manager to identify the preferred service and conduit locations.
- Project Manager and Landscape Contractor to establish area suitable for irrigation control system with required area, power provision and water supply.

Testing & Defects:

Upon completion of installation, the system shall be tested, including:

- Main Line Pressure Test: The main line is pressurised to test for leaks. All valves are shut and the pressure is taken over a determined length of time.
- Dripper Pressure Test: Measurement at flushing valves are taken and the pressure gauged to make sure it conforms to the manufacturer recommendations. The inlet pressure is then tested under the same conditions to check it does not exceed 300kPa.
- All components are to be satisfactorily functional and operational prior to approval. Should any defect develop, or the capacity or efficiency of the system decline during the agreed maintenance system, then these faults shall be immediately rectified.

Warranty:

- A full 12 month warranty shall be included to cover labour and all parts.

Further Documentation:

- On request, a detailed irrigation performance specification report can be issued.

CONSOLIDATION AND MAINTENANCE


6.01 GENERAL

The consolidation and maintenance period shall be 12 months beginning from the approved completion of the specified construction work (Practical Completion). A qualified landscape maintenance contractor shall undertake the required landscape maintenance works. Consolidation and maintenance shall mean the care and maintenance of Contracted works by accepted landscaping or horticultural practices, ensuring that all plants are in optimum growing conditions and appearance at all times, as well as rectifying any defects that become apparent in the contracted works.

This shall include, but not be limited to, the following items where and as required:


- Watering all planting and lawn areas / irrigation maintenance.
- Clearing litter and other debris from landscaped areas.
- Removing weeds, pruning and general plant maintenance.
- Replacement of damaged, stolen or unhealthy plants.
- Make good areas of soil subsidence or erosion.
- Topping up of mulched areas.
- Spray / treatment for insect and disease control.
- Fertilizing with approved fertilizers at correct rates.
- Mowing lawns & trimming edges each 14 days in summer or 18 days in winter
- Adjusting ties to Stakes
- Maintenance of all paving, retaining and hardscape elements.

On the completion of the maintenance period, the landscape works shall be inspected and at the satisfaction of the superintendent or landscape architect, the responsibility will be signed over to the client.



PROVIDE FENCING AS DETAILED TO ALL TREES PROPOSED TO BE RETAINED ON THE SUBJECT SITE. FENCING TO BE LOCATED TO THE DRIP LINE OF TREES OR AS INDICATED ON PLANS OR DIRECTED ON-SITE BY ARBORIST. NO STOCKPILING WITHIN FENCE PERIMETERS.

TREE PROTECTION ZONE
N.T.S



TYPICAL GARDEN PREPARATION DETAIL
SCALE 1:10

(ONLY APPLICABLE FOR PLANTING AREA OUTSIDE TREE PROTECTION ZONE OF TREES TO BE RETAINED. NO CHANGES ARE TO OCCUR TO EXISTING LEVELS, INCLUDING RIPPING/CULTIVATING OF THE SOIL WITHIN THE TPZ OF TREES TO BE RETAINED ON SITE)

OVERFLOW
(TO SUPPLIER'S SPECIFICATION)

NOTE (BCA COMPLIANCE). WHERE NO EXTERNAL BALUSTRADE IS PROPOSED. THE INTERNAL PLANTER WALL FACE MUST BE NON-CLIMBABLE TO A HEIGHT TO MEET AS & BCA COMPLIANCE.

NOMINATED SURFACE FINISHES & WATER PROOFING (REFER TO SEPARATE DETAILS). FINISHED LEVEL TO ARCHITECT'S DETAILS

NOTE (DRAINAGE & WATER PROOFING). DRAINAGE PITS AND LAYOUT TO BE NOMINATED BY HYDRAULIC ENGINEER TO WORK WITH STRUCTURAL DESIGN AND LANDSCAPE.

THE WATERPROOFING, APPROVED DRAINAGE CELL AND SPECIFIED GEOFABRIC LAYER IN THIS DETAIL ARE INDICATIVE ONLY AND SHOULD BE DETAILED BY THE RELEVANT PROFESSIONAL ENGINEER FOR CONSTRUCTION.


UNDER THE CONSTRUCTION PRACTITIONER BILL, STRUCTURAL WATER-PROOFING SHALL BE DOCUMENTED BY A HYDRAULIC ENGINEER

WATERPROOF MEMBRANE TO TERMINATE INTO DRAINAGE OUTLET PIPE SLOTTED FOR VERTICAL DRAINAGE OPENINGS


PLANTER WALL ON SLAB DETAIL

SCALE: nts

PLANTER DETAIL TO CONFORM AS 4654 2:2012




MASS PLANTING SETOUT
N.T.S



TREE PLANTING DETAIL
SCALE: 1:10

(ONLY APPLICABLE FOR PLANTING AREA OUTSIDE TREE PROTECTION ZONE OF TREES TO BE RETAINED. NO CHANGES ARE TO OCCUR TO EXISTING LEVELS, INCLUDING RIPPING/CULTIVATING OF THE SOIL WITHIN THE TPZ OF TREES TO BE RETAINED ON SITE)



TYPICAL IN SITU RETAINING WALL DETAIL
SCALE 1:10

GENERAL NOTE: Figured dimensions take preference to scale readings. Verify all dimensions on site. If no. Except is not liable for any loss, damage, harm or injury due to the use of the drawings or the information contained therein. The user assumes all responsibility for the use of the drawings or the information contained therein. © Copyright R. & Free Landscape Architectural Services Ltd (L) 2020. All rights reserved. No part of this drawing may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without the prior written permission of the copyright owner. If the date of this drawing is not signed off by the Contractor, it may be subject to change, alteration or amendment at the discretion of the office.		www.dial1100beforeyoudig.com.au DIAL 1100 BEFORE YOU DIG ALIA Associate		www.concept.net.au enquiries@concept.net.au		COUNCIL CANTERBURY- BANKSTOWN		REV A 11.04.22 FOR S4.56 B 16.10.24 FOR S4.56		NOTATION/AMENDMENT		PROJECT: 15 ENTERPRISE AVENUE, PADSTOW NSW		TITLE DETAIL & SPECIFICATION		STATUS FOR S4.56	
SCALE: nts		PROJECT No: LPS34 22-319		PAGE NUMBER: 4		DRAWN: E.W		CHECKED: R.F		DATE: OCTOBER 2024		SCALE: AS SHOWN @ A1		PROJECT No: LPS34 22-319		PAGE NUMBER: 4	

