NORTHVIEW ESTATE, MUSWEI CIVIL WORKS - STAGE 6 & 7

CLIENT: TINDALE POROPERTY

VER

- COVER - COVER - COVER - COVER - GENERAL NOTES - GENERAL ARRANGEMENT - TYPICAL CROSS SECTIO 2 - TYPICAL CROSS SECTIO 2 - TYPICAL CROSS SECTIO - ROAD LONGITUDINAL SEC - RO	Sm7	DO3 - DRAIN DO4 - DRAIN DO5 - DRAIN DO6 - DRAIN DO7 - DRAIN CATCHMEN CATCHMEN SEWER AN SEWER LIN SEWER LIN SEWER DE' SEWER DE' SEWER DE'
TYP001 - TYPICAL CROSS SECTIONS TYP002 - TYPICAL CROSS SECTIONS	· > >	STORMWAI
LS001 - ROAD LONGITUDINAL SECTION LS002 - ROAD LONGITUDINAL SECTION	> >	SEWER AN
LS003 - ROAD LONGITUDINAL SECTION	>	SEWER LIN
LS004 - ROAD LONGITUDINAL SECTION XS001 - CROSS SECTIONS - ROAD 1	> >	- SEWER LIN
- CROSS	>	- SEWER LIN
- CROSS SECTIONS - ROAD	> >	SEWER DE
SECTIONS - ROAD	Þ	SEWER DE
XS006 - CROSS SECTIONS - ROAD 3	> >	SEW011 - SEWER DETAILS
- CROSS SECTIONS - ROAD	>	- LANDSCA
XS009 - CROSS SECTIONS - ROAD 3	Þ	LAND003 - LANDSCAPE PLAN
XS010 - CROSS SECTIONS - ROAD 3	> >	LAND004 - LANDSCAPE PLAN
CROSS SECTIONS - ROAD	Þ	
SWD001 - STORMWATER DRAINAGE PLAN	A	
	> >	
SWD003 - STORMWATER DRAINAGE PLAN SWD004 - BASIN LAYOUT PLAN	> >	
SWD -LS001 - DRAINAGE LONGITUDINAL SECTION	Þ	
SWD -LS002 - DRAINAGE LONGITUDINAL SECTION	A	







Ph: 02 65432475 Email: office @hbsurveys.com.au PO Box 432, SCONE NSW 2337





➣		
>		
	FOR DEVELOPMENT APPROVAL	Α
	Details	version No.

- commencement of any earthworks. GENERAL NOTES

 1. All erosion and sedimentation devices are to be in place prior to the
- 2. All works are to be carried out in accordance with AUSPEC DEVELOPMENT CONSTRUCTION SPECIFICATION.
- All lot dimensions / areas and easements are subject to final survey.
- 4. Make smooth junction with all existing works.
- 5. It is the responsibility of any persons/ contractors using this plan to locate and all underground services prior to the commencement of earthworks. "DIAL BEFORE YOU DIG" and expose
- Surplus excavated material shall be placed where directed or removed from site as directed by superintendent
- 7. The contractor is responsible for protection of and adjustment to all services as may be required.
- 8. Dimensions are to be used in preference to scaling.
- All topsoil and vegetation material is to be removed prior to the placement of any pavement material. Topsoil shall be suitably stockpiled for later reuse.
- 10. Working hours on the site shall be in accordance with council's specification.
- 11. Barricades are to be placed across entry/exits points to the site to prevent general access by the public to the construction site at the completion of each days work.
- 12. Disturbance of the site and surrounding areas to be kept to a minimum.
- The contractors attention is drawn to compliance with general specification and the inspection and Test Plan.
- 14. All disturbed areas shall be topsoiled and seeded within 2 weeks of final formation (refer specification) with the
- regrade area which is to be topsolled, mulched and

IMMEDIATELY after formation. The contractor is to ensure that the regrade area is fully vegetated and stabilised prior to leaving the site.



4. DEMOLITION MATERIALS SHALL BE SENT TO RECYCLE CENTER WHERE EVER POSSIBLE IN PREFERENCE TO LAND FILL.

3. RECORDS OF LOCATION AND VOLUMES DISPOSAL ALL DEMOLITION MATERIALS ARE TO BE PROVIDED THE SUPERINTENDENT.

검유

2. DOCUMENTATION OF LEGAL DISPOSAL OF ASBESTOS SHALL BE PROVIDED TO THE SUPERINTENDENT

SURVEY

SU1 COORDINATES MGA

SU2. DATUM AHD

SU3. ALL CHAINAGES ARE IN METRES

SU4. CONTRACTORS SHALL ARRANGE FOR WORKS SET OUT AND WORKS AS EXECUTED SURVEY AND PLANS TO BE CARRIED OUT BY A REGISTERED SURVEYOR.

SU6. ROAD CONSTRUCTION CONFORMANCE TOLERANCES
SUBGRADE: +0mm / -20mm SUBBASE:+10mm / 0mm BASE +10mm / 0mm

PAVEMENT SEALING SPECIFICATION 1144

1. PAVEMENT PREPARATION

a) THE EXISTING SURFACE TO BE SEALED SHALL BE DRY AND BROOMED BEFORE COMMENCEMENT OF WORK TO ENSURE COMPLETE REMOVAL OF ALL SUPERFICIAL FOREIGN MATTER.

b) ALL DEPRESSIONS OR UNEVEN AREAS ARE TO BE TACK-COATED AND HAVE A CORRECTION COARSE APPLIED TO THE GENERAL LEVEL OF PAVEMENT BEFORE PLACING THE FIRST COAT.

3.PRIMER SEAL WITH 10mm AGGREGATE

a) THE WHOLE OF THE AREA TO BE TREATED WITH $30\,\mathrm{mm}$ AC WEARING COURSE

4. COMPACTION

Uniformly compact asphalt to the standards specified Density as soon as the asphalt has cooled sufficiently to specify the rollers without uniformly sufficiently to be achieved using suitable sized stewheeled or vibratory rollers or combination of stewheeled or vibratory rollers and pneumatic tyre rollers.

5. FINISHED PAVEMENT PROPERTIES

a) FINISHED SURFACES SHALL BE SMOOTH, DENSE TRUE TO SHAPE AND SHALL NOT DEVIATE FROM BOTTOM OF A 3m STRAIGHT EDGE LAID IN DIRECTION BY MORE THAN +: 5mm.

1. EROSION AND SEDIMENTATION CONTROL SHALL BE IN PLACE AND APPROVED PRIOR TO ANY SITE DISTURBANCE

EARTHWORKS

OVER ENTIRE AREA OF EARTHWORKS, VEGETATION, RUBBISH, SLABS, FENCES et REMOVE FROM SITE. etc. tc. AND

3. STRIP TOPSOIL AVERAGE 100mm THICK WHICH SHALL BE RETAINED ON SITE AND UTILISED EFFECTIVELY TO ENCOURAGE APPROPRIATE RE VEGETATION.

4. ANY EXCESS FILL SHALL BE STOCKPILED ON SITE A LOCATION AS AGREED WITH SUPERINTENDENT FOUR USE IN FUTURE STAGES.

5. SELECT FILL FOR BASIN WALLS SHALL BE CONFIRMED SUITABLE FOR USE IN AS DAM WALL MATERIAL BY GEOTECH ENGINEER PRIOR TO COMMENCEMENT OF WALL CONSTRUCTION

6. EXCAVATE AND REMOVE ANY UNSUITABLE SOFT AREAS ENCOUNTERED DURING PROOF ROLLING AND REPLACE WITH APPROVED FILL COMPACTED IN LAYERS IN ACCORDANCE WITH SITE DIRECTION BY GEOTECHNICAL ENGINEER.

7. WHERE HARD ROCK IS EXPOSED IN THE EXCAVATED SUB-GRADE, THIS WILL BE INSPECTED AND A DECISION MADE ON THE LEVEL TO WHICH EXCAVATION IS TAKEN.

. ALL LOT FILLING SHALL BE COMPLETED UNDER LEVEL GEOTECHNICAL SUPERVISION AND CERTIFED.

9. FILLING IS TO BE OF SOUND CLEAN MATERIAL, REASONABLE STANDARD AND FREE FROM LARGE ROCKS, STUMPS, ORGANIC MATTER AND OTHER DEBRIS.

10. PLACING OF FILLING ON THE PREPARED AREAS SHALL NOT COMMENCE UNTIL THE AUTHORITY TO DO SO HAS BEEN OBTAINED FROM SUPERINTENDENT OR GEOTECHNICAL ENGINEER.

11. ALL VERGES ADJACENT TO ROADS AND ALL AREAS ARE TO BE DRESSED WITH 100mm CLEAN SANDY TOPSOIL AND TURFED,

12. TOPSOIL SHALL NOT BE PLACED OVER BI

13. ALL DETENTION BASINS TO BE TOPSOILED AND TURFED.

1. GEOTEXTILE (GEOFABRIC) SHALL BE IN ACCORDANCE WITH AS3706.

DRAWINGS

1. ASBESTOS IF ANY SHALL BE REMOVED BY LICENSED CONTRACTOR TO AN APPROVED FACILITY AND HYGIENIST CLEARANCE CERTIFICATE PROVIDED PRIOR TO GENERAL SITE DEMOLITION.

DEMOLITION

1. ONLY USE PLANS THAT ARE IN COLOUR.

GENERAL

1. CARRY OUT ALL CONCRETE WORK IN ACCORDANCE WITH NATSPEC 0139 MINOR CONCRETE WORKS.

2. VERIFY ALL SETTING OUT DIMENSIONS - IF IN DOUBT ASK

3. DO NOT OBTAIN DIMENSIONS BY SCALING THE DRAWINGS.

4. MINIMUM 28 DAY COMPRESSIVE STRENGTH OF

5. CEMENT SHALL BE GP PORTLAND CEMENT IN ACCORDANCE WITH AS3972 AND BLENDED CEMENTS. NO ADMIXTURES WILL BE USED WITHOUT APPROVAL

6. AGGREGATE AND SAND SHALL BE CLEAN, HARD AND DURABLE IN ACCORDANCE WITH AS 2758.1 CONCRETE AGGREGATES (100% PASSING THE 20mm SIEVE)

7. CLEAR COVER TO ANY REINFORCEMENT NEAREST TO THE CONCRETE SURFACE SHALL BE 50mm.

STORMWATER NOTES:
1. ALL PIPES SHALL BE RUBBER RING JOINTED REINFORCED CONCRETE PIPES OR BOX CULVERTS.

2. ALL STORMWATER DRAINAGE WORKS ARE TO BE CONSTRUCTED TO MUSWELLBROOK COUNCIL'S AUSPEC SPECIFICATIONS

3. THE CONTRACTOR SHALL UNDERTAKE ALL TESTING AND ARRANGE ALL INSPECTIONS AS SET OUT IN THE INSPECTION TEST PLAN AT HIS COST.

4. DRAINAGE STRUCTURES SHALL BE CONSTRUCTED IN ACCORDANCE WITH MUSWELLBROOK COUNCIL'S STANDARD DRAWINGS. STEP RRONS AT 300MM SPACINGS, SHALL BE PROVIDED IN DRAINAGE PITS MORE THAN 1.2M DEEP.

5. CONCRETE FOR DRAINAGE STRUCTURES SHALL HAVE A MINIMUM

COMPRESSIVE STRENGTH OF 25MPa.

6. PIPES SHALL BE CONSTRUCTED IN ACCORDANCE
WITH ASINZS 3725-2007 FOR
SUPPORT TYPE HS2 IN TRENCHES. WHERE SUBSOIL
DRAINAGE IS TO
INSTALLED, APPROPRIATE FILTER MATERIAL WILL BE
SUBSTITUTED FOR
ORDINARY FILL.

AND ACROSS THE TRENCH EXTENDING TO WITHIN 30MM OF THE FINISHED SURFACE LEVEL, OR THE SUBGRADE LEVEL, WHCHEVER IS APPRPRIATE, SHALL BE CONSTRUCTED WHERE SHOWN ON THE DRAWINGS. 7. CEMENT-STABILIZED SANDBAG TRENCHSTOPS PACKED AROUND THE PIPES

8. PIPES WITH SUB-SOIL DRAINAGE SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE DETAIL SHOWN.

9. THE CONTRACTOR SHALL TAKE ALL MEASURES TO PROTECT THE PIPES AND PITS FROM DAMAGE DURING CONSTRUCTION, ANY PES OR STURCTURES
DAMAGED DURING CONSTRUCTION SHALL BE EPLACED BY THE CONTRACTOR AT HIS EXPENSE.

10. PITS TO BE STEEL BAR / WIRE REINFORCED PITS CLASS D DESIGN FOR ALL ROADWAYS, AND IN ACCORDANCE WITH AUS-SPEC.

DA ONLY - NOT FOR CONSTRUCTION

PLANS PREPARED BY

REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN
Surveying the Hunter since 1920 MM HYNDES BAILEY & Co.



NORTHVIEW ESTATE - STAGE 6 & 7 **GENERAL NOTES**

MC / UK / RJ

ORIGINAL DRAWING SIZE: A1 SHEET: NOTE001 FILE: 224103_ST6-7_CIVIL **LGA: MUSWELLBROOK**

⋗ FOR DEVELOPMENT APPROVAL PLAN ISSUE 15 11 2024 REV: A 224103 JOB REF

GENERAL INSTRUCTIONS

- THIS PLAN IS TO BE READ IN CONJUNCTION WITH THE ENGINEERING PLANS, AND ANY OTHER PLANS OR WRITTEN INSTRUCTIONS THAT MAY BE ISSUED AND RELATING TO DEVELOPMENT AT THE
- .. THE SITE SUPERINTENDENT WILL ENSURE THAT ALL SOIL AND WATER MANAGEMENT WORKS ARE LOCATED AS INSTRUCTED IN THIS SPECIFICATION.
- ALL BUILDERS AND SUB-CONTRACTORS WILL BE INFORMED OF THEIR RESPONSIBILITIES IN MINIMISING THE POTENTIAL FOR SOIL EROSION AND POLLUTION TO DOWNSLOPE LANDS AND WATERWAYS.

CONSTRUCTION SEQUENCE

- HENCE WORKS SHALL BE UNDERTAKEN IN THE FOLLOWING SEQUENCE:

 (A) INSTALL SEDIMENT FENCES

 (B) CONSTRUCT OPEN SWALES TO DIVERT WATER FROM SITE AS NECESSARY AND DIRECTED BY THE SITE SUPERINTENDENT.

 (C) CONSTRUCT STABILISED CONSTRUCTION ENTRANCE TO LOCATION AS DETERMINED BY SUPERINTENDENT.
- (D) INSTALL SEDIMENT TRAPS AS SHOWN ON PLAN.

 (E) UNDERTAKE SITE DEVELOPMENT WORKS IN ACCORDANCE WITH THE ENGINEERING PLANS. PHASE DEVELOPMENT SO THAT LAND DISTURBANCE IS CONFINED TO AREAS OF WORKABLE SIZE.
- . FINAL SITE LANDSCAPING WILL BE UNDERTAKEN AS SOON AS POSSIBLE AND WITHIN 20 WORKING DAYS FROM COMPLETION OF CONSTRUCTION ACTIVITIES.

. DURING WINDY WEATHER, LARGE, UNPROTECTED AREAS WILL BE KEPT MOIST (NOT WET) BY SPRINKLING WITH WATER TO KEEP DUST UNDER CONTROL.

SEDIMENT CONTROL

- STOCKPILE SITE SHALL BE AGREE UPON WITH SUPERINTENDENT AND WILL NOT BE LOCATED NEAR HAZARD AREAS, INCLUDING LIKELY AREAS OF CONCENTRATED OR HIGH VELOCITY FLOWS SUCH AS WATERWAYS. INSTALLATION OF SEDIMENT FENCING SHALL BE UNDERTAKEN ON THE DOWN HILL SIDE
- ANY SAND USED IN THE CONCRETE CURING PROCESS (SPREAD OVER THE SURFACE) WILL BE REMOVED AS SOON AS POSSIBLE AND WITHIN 10 WORKING DAYS FROM PLACEMENT.
- WATER WILL BE PREVENTED FROM ENTERING THE PERMANENT DRAINAGE SYSTEM UNLESS IT IS RELATIVELY SEDIMENT FREE, I.E. THE CATCHMENT AREA HAS BEEN PERMANENTLY LANDSCAPED AND/OR ANY LIKELY SEDIMENT HAS BEEN FILTERED THROUGH AN APPROVED STRUCTURE.
- 10. TEMPORARY SOIL AND WATER MANAGEMENT STRUCTURES WILL BE REMOVED ONLY AFTER THE LANDS THEY ARE PROTECTING ARE REHABILITATED.

- 11. ACCEPTABLE RECEPTORS WILL BE PROVIDED FOR CONCRETE AND MORTAR SLURRIES, PAINTS, ACID WASHINGS, LIGHT-WEIGHT WASTE MATERIALS AND LITTER.
- 12. ANY EXISTING TREES WHICH FORM PART OF THE FINAL LANDSCAPING PLAN WILL BE PROTECTED FROM CONSTRUCTION ACTIVITIES BY:

 (A) PROTECTING THEM WITH BARRIER FENCING OR SIMILAR MATERIALS INSTALLED OUTSIDE THE DRIP LINE.

 (B) ENSURING THAT NOTHING IS NAILED TO THEM.


 (C) PROHIBITING PAVING, GRADING, SEDIMENT WASH OR PLACING OF STOCKPILES WITHIN THE DRIP LINE EXCEPT UNDER THE FOLLOWING CONDITIONS.

 (I) ENCROACHMENT ONLY OCCURS ON ONE SIDE AND NO CLOSER TO THE TRUNK THAN EITHER 1.5 METRES OR HALF THE DISTANCE BETWEEN THE OUTER EDGE OF THE DRIP LINE AND THE TRUNK, WHICH EVER IS THE GREATER.
- (II) A DRAINAGE SYSTEM THAT ALLOWS AIR AND WATER TO CIRCULATE THROUGH THE ROOT ZONE (E.G. A GRAVEL BED) IS PLACED UNDER ALL FILL LAYERS OF MORE THAN 300 MILLIMETRES DEPTH.

 (III) CARE IS TAKEN NOT TO CUT ROOTS UNNECESSARILY AND NOT TO COMPACT THE SOIL (III) C AROUND THEM.

SITE INSPECTION & MAINTENANCE

13. RECEPTORS FOR CONCRETE AND MORTAR SLURRIES, PAINTS, ACID WASHINGS, LIGHT-WEIGHT WASTE MATERIALS AND LITTER ARE TO BE EMPTIED AS NECESSARY. DISPOSAL OF WASTE SHALL BE IN A MANNER APPROVED BY THE SITE SUPERINTENDENT.



CONSTRUCTION NOTES STRAW BALES TIGHTLY ABUTTING TOGETHER BALES EMBEDDED 100 MM INTO GROUND 1.2 M STAR PICKET DRIVEN 600 MM INTO GROUND PLAN VIEW 20 METERS MAX. ELEVATION SECTION A - A NYLON OR WIRE BINDINGS — 1.5 M TO → 2 M DISTURBED AREA ANGLE FIRST STAKE TOWARD PREVIOUS BALE

construct the bale filter as close as possible to being parallel to the contours of the stie.

PLACE BALES LENGTHMSE IN A ROW MITH ENDS TIGHTLY ABUTTING, USE STRAW TO FILL ANY GAP BETWEEN BALES, STREWS ARE TO BE PLACED PARALLEL TO GROUND.

-

ENSURE THAT THE MAXIMUM HEIGHT OF THE FILTER IS ONE BALE.

Ņ

- EMBED EACH BALE IN THE GROUND 75MM TO 100MM AND ANCHOR WITH TWO 1.2 METER STAR PICKETS OR STAKES, ANGLE THE FIRST STAR PICKET OR STAKE IN EACH BALE TOWARDS THE PREVIOUSLY LAID BALE. DRIVE THEM 600MM INTO THE GROUND AND, IF POSSIBLE, FLUSH WITH THE TOP OF THE BALES, WHERE STAR PICKETS ARE USED AND THEY PROTRUDE ABOVE THE BALES, ENSURE THEY ARE FITTED WITH SAFETY CAPS.
- WHERE A STRAW BALE FILTER IS CONSTRUCTED DOWNSLOPE FROM A DISTURBED BATTER, ENSURE THE BALES ARE PLACED 1 TO 2 METERS DOWNSLOPE FROM THE TOE.
- ESTABLISH A MAINTENANCE PROGRAM THAT ENSURES THE INTEGRITY OF THE BALES IS RETAINED THEY COULD REQUIRE REPLACEMENT EACH TWO TO FOUR MONTHS.

Ċ

STRAW BALE FILTER

SEDIMENTATION AND EROSION CONTROL

- SE1. LAND DISTURBANCE SHALL BE LIMITED TO THAT NECESSARY FOR IMPLEMENTATION OF THE PLANS OF WORK AND LANDS NOT TO BE DISTURBED SHALL BE CLEARLY MARKED WITH BARRIER FENCES, SEDIMENT FENCING AND STRAW BALE FILTER SHALL BE PLACED AT REGULAR INTERVALS IMMEDIATELY DOWN SLOPE OF ALL UNPROTECTED DISTURBED LANDS
- SE2. INSTALL SEDIMENT FENCING AND STRAW BALE FILTER IN ACCORDANCE WITH DETAILS ABOVE AND LOCAL COUNCIL REQUIREMENTS.
- SE3. THE LOCATION OF "SILT" FENCES, SEDIMENT FENCES STRAW BALE FILTER AND OTHER DEVICES SHALL BE DETERMINED ON SITE IN CONJUNCTION WITH THE SUPERINTENDENT. VARIATIONS ARE PERMITTED TO BEST SUIT THE CIRCUMSTANCES
- SE4. INSTALL TEMPORARY CONSTRUCTION VEHICLE EXIT IN ACCORDANCE WITH TYPICAL DETAILS
- SE6. STRIP TOPSOIL FROM ALL CUT AREAS AND STOCKPILE ON SITE

SE5. STRIP VEGETATION FROM ALL CUT AREAS AND DISPOSE OFF SITE

- SE7. EXCAVATE ALL CUT AREAS AND PLACE COMPACTED FILL WHERE REQUIRED.
- SE8. ALL ADJACENT LANDSCAPE AREAS ARE TO BE STABILISED AND VEGETATED WITHIN 20 DAYS OF COMPLETION.
- SE9. EXCAVATE, LAY AND BACKFILL DRAINAGE LINES. OPEN TRENCH LENGTHS ARE NOT TO EXCEED 25 METRES. WHERE TRENCHES ARE OPEN OVER NIGHT, DIVERT POTENTIAL SURFACE WATER TO A SAFE LOCATION.WITH CONTROL MEASURES.
- SE10. JUTE MESH TO TABLE DRAINS SHALL BE SECURED IN ACCORDANCE WITH MANUFACTURES SPECIFICATION,

NOTE: WHEREVER SEDIMENT AND EROSION CONTROL DEVICES ARE REMOVED EARLIER IN THE CONSTRUCTION SEQUENCE THAN AS SPECIFIED ABOVE, ENSURE THAT THE DISTURBED GROUND IS RE-VEGETATED TO REDUCE THE LIKELIHOOD OF EROSION AND SEDIMENT TRANSPORT FROM THE SITE. ENSURE ALSO THAT SEDIMENT LADEN WATER CAN STILL REACH SEDIMENTATION BASINS FOR TREATMENT.

CONSTRUCTION NOT UNDISTURBED AREA MIN 1.5 M DIRECTION OF FLOW 20 M MAX.

—— (UNLESS STATED OTHERWISE ON SWMP / ESCP) 1.5 M STAR PICKETS AT MAX. 2.5 M CENTRES + PLAN 500 MM 600 MM MIN ᆼ FLOW ✓1.5 M STAR PICKETS AT MAX. 2.5 M CENTRES STAR PICKETS AT MAXIMUM 2.5M SPACINGS ON SOIL, 150 MM X 100 MM
TRENCH WITH COMPACTED
BACKFILL AND ON ROCK,
SET INTO SURFACE
CONCRETE SELF - SUPPORTING GEOTEXTILE

- CONSTRUCT SEDIMENT FENCES AS CLOSE AS POSSIBLE TO BEING PARALLEL TO THE CONTOURS OF THE SITE, BUT WITH SMALL RETURNS AS SHOWN IN THE DRAWNG TO LIMIT THE CATCHMENT AREA OF ANY ONE SECTION. THE CATCHMENT AREA SHOULD BE SMALL ENOUGH TO LIMIT WATER FLOW IF CONCENTRATED AT ONE POINT TO 50 LITRES PER SECOND IN THE DESIGN STORM EVENT, USUALLY THE 10-YEAR EVENT.
- cut a 150-mm deep trench along the upslope line of the fence for the fabric to be entrenched.
- DRIVE 1.5 METER L DOWNSLOPE EDGE (CAPS. OF THE TRENCH. ENSURE ANY STAR PICKETS ARE FITTED WITH SAFETY
- FIX SELF—SUPPORTIN TO THE BASE OF TH BY THE MANUFACTU FENCING. THE USE O TING GEOTEXTILE TO THE UPSLOPE SIDE OF THE POSTS ENSURING IT GOES THE TRENCH. FIX THE GEOTEXTILE TO THE WIRE TIES OR AS RECOMMENDED TURER, ONLY USE GEOTEXTILE SPECIFICALLY PRODUCED FOR SEDIMENT OF SHADE CLOTH FOR THIS PURPOSE IS NOT SATISFACTORY.
- JOIN SECTIONS OF FABRIC AT A SUPPORT POST WITH A 150-MM OVERLAP.
- BACKFILL THE TRENCH OVER THE BASE OF THE FABRIC AND COMPACT IT THOROUGHLY OVER THE GEOTEXTILE.

SEDIMENT FENCE (TYPICAL)

SEDIMENT RUN-OFF CONTROL

RC1 THE CONTRACTOR SHALL INSTALL AND MAINTAIN SOIL EROSION AND SEDIMENT CONTROL MEASURES GENERALLY IN ACCORDANCE WITH THE GUIDELINES OF THE N.S.W. DEPT. OF CONSERVATION AND LAND MANAGEMENT AS NECESSARY TO PREVENT RUN-OFF FROM SITE OF SEDIMENT RESULTING FROM THESE WORKS. SUCH MEASURES SHALL ALSO COMPLY WITH REQUIREMENTS OF COUNCIL.

RC2. GRADE FINISHED SURFACE TO SHED WATER WITHOUT CHANNELING

PLANS PREPARED BY

REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN Surveying the Hunter since 1920 MM HYNDES BAILEY & Co.

Ph: 02 65432475 Emall: office@hbsurveys.com.au (PO Box 26), MUSWELLBROOK NSW 2333





NORTHVIEW ESTATE - STAGE 6 & 7

GENERAL NOTES

DESIGN:


MC / UK / RJ


SHEET: NOTE002


FILE: 224103_ST6-7_CIVIL ORIGINAL DRAWING SIZE: A1 LGA: MUSWELLBROOK


DA ONLY - NOT FOR CONSTRUCTION


			Α		
			A FOR DEVELOPMENT APPROVAL	PLAN ISSUE	
224103	JOB REF:	7 . 1	0 0 1 1 2	15 11 2024	


























Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys. 132 Kelly Street (PO Box 432), SCONE NSW 2337 MM HYNDES BAILEY & CO.
REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN
Surveying the Hunter since 1920 TINDALE DESIGN: MC/UK/RJ

DRAWN:

ROAD LONGITUDINAL SECTION ROAD 1, ROAD 2 AND ROAD 3

MC / UK / RJ

SCALE: H-1:500 V-1:100
ORIGINAL DRAWING SIZE: A1 FILE: 224103_ST6-7_CIVIL LGA: MUSWELLBROOK

FOR DEVELOPMENT APPROVAL PLAN ISSUE 15.11.2024 REV: A JOB REF: 224103

DA ONLY - NOT FOR CONSTRUCTION

603.11 604.5 176.94 609.32 174.55 177.02 611.41 174.43 177.06 613.11 177.09 615 176.16 177.13 (0.976) 617.57 177.38 177.22 617.61 177.22 622.11 177.46

DESIGN LEVEL EXISTING

585 178.01 178.47 (0.454)
586.52 177.81 178.28
590.77 177.24 177.75
591 177.72
595.5 177.29
596.02 175.92 177.24
600 175.51 176.99 (1.478)
603.11 176.93

630 177.25 177.98 (0.726) 630.43 177.25 178.01

648.91 179.21 179.21

178.87 178.96 (0.085

645

F CUT

R.L.170.0

I.P 177.169

L.P.

CHAINAGE LEVEL

570

DESIGN LEVEL EXISTING

0.00 171.13 171.31 (0.182)
0.54 171.12 171.30
1.70 171.12 171.30
3.37 171.09 171.28
4.29 171.08 171.28 0
5 171.27
5.9 171.05 171.25
6.55 171.03 171.24
7.5 171.23 0
7.89 171 171.22 4
8.81 170.97 171.20
10.37 170.92 171.17
14.03 170.92 171.17
14.03 170.92 171.08
15 170.80 171.06 (0.259)
16.48 170.76 171.02 2
23.50 170.74 170.76 N
27.43 170.67 170.62
28.68 170.68 170.56
30 170.67 170.56
30 170.67 170.50
32.86 170.68 170.37 2
32.88 170.66 170.37 3
41.67 169.58 169.88 0
45 169.39 169.67 (0.28)
52.5 169.39 169.67 (0.28)
52.5 169.39 169.47

QUEEN STREET

70

75

168.10

77.90 167.53 79.39 167.54 80 167.56 3 83.89 167.65 167.67 (0.022)

F CUT

30

32

R.L.163.0 85

I.P 171.315

I.P 171,310

113

90

63

109

1 52

220

-0.121)

370

0.529)

50

167.82

167.57

CHAINAGE

ROAD No.1














PLANS PREPARED BY


















































Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com.au 132 Kelly Street (PO Box 432), SCONE NSW 2337 MM HYNDES BAILEY & CO.
REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN
Surveying the Hunter since 1920 PLANS PREPARED BY DESIGN: DRAINAGE LONGITUDINAL SECTION SHEET 3
NORTHVIEW ESTATE - STAGE 6 & 7 SCALE: H-NTS V-NTS
ORIGINAL DRAWING SIZE: A1 FILE: 224103 ST6-7 DRAINAGE LGA: MUSWELLBROOK SHEET: SWD-LS003 FOR DEVELOPMENT APPROVAL PLAN ISSUE

DRAINAGE LINE E - 20%

DRAINAGE LINE F - 20%


15.11.2024


REV: A

JOB REF: 224103

Invert **Surface** HGL Chalnage Level Level 181.250 0 182.1 181.374 150mm225mm 24.27%7.63% Datum El. 165 18L/s 177.430 177.472 19L/s 15.74 176:988 178.4 177:652 E3 176.870 177.97 177.008 22.30 **CLASS 4 RRJ RCP** 37L/s 375mm 8.00% 172.980 173.244 **E4** 75L/s 375mm 172.950 173.149 1.09% 70.95 174.05 172.830 173.040 **E**5 172.800 81.95 174.05 173.024 450mm 1.38% 84L/s 172.530 172.882 **E**6 172.500 101.57 173.65 172.861 81L/s 450mm 2.64% 172.060 **172.843** 118.26 173.37


Chalnage	Invert Level	Surface Level	HGL		2.50%	225	2		
0	186.490	187.44	186,433	Ď	%		क		F1
5.59	186.320	187.42	186.471	₫	Ω,	375	40		F2
	186.010		186.136	3	3%	Ĭ	40L/s		
15.50	185.980	187.08	186.136	Datum El. 165	3.13%20.09%	225mm375mm375mm	45L/s		F3
	183.300		183.533	Ğ	9%	, 3	S/S		
28.84	183.270	184.37	183.519						F4
					14.37%	375mm	116L/s		
	179.110		179.373						
57.79	179.080	180.18	179.368		-				F5
	474 700		475 400		13.78%	375mm	155L/s	CLASS 4 RRJ RCP	
20.00	174.780	455.05	175.180			37	5	P	F6
88.99	174.750 174.660	175.85	175.042 174.942		100% 13.34%	5mm	158L/s		F7
97.99	174.630	175.85	174.939		13	45	19		
	172.850		173.008		34%	375mm450mm	195L/s		F8
111.33	172.820	174.02	173.008		3.33%	600mm	204L/s		
	172.200		172.899						
129.97	172.170	173.37	172.856		1.0	60	22		F9
	172.060		172.843		1.00%	600mm	223L/s		
140.97		173.37	•						A8







MM HYNDES BAILEY & Co.
REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN
Surveying the Hunter since 1920 Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com 132 Kelly Street (PO Box 432), SCONE NSW 2337 **DRAINAGE LINE M - 20% AEP Surface** Invert Chainage HGL Level Level М1 177.920 179.02 178.230 0 Datum El. 165 **CLASS 4 RRJ RCP** 179L/s 375mm 3.49% PLANS PREPARED BY 176.900 177.098 M2 - HEADWALL 29.25 178.7 Surface Invert Chalnage HGL Level Level 249L/s 271L/s 336L/s 375mm 450mm 450mm 1.10% 3.35% 14.03% **N1** 0 167.150 168.25 167.665 Datum 167.000 167.391 **N2** 13.69 167.000 168.1 167.365 El. 145 166.560 166.948 Ν3 166.530 167.73 26.84 166.921 164.580 164.995 CLIENT **N**4 40.74 164.550 165.75 164.936 **CLASS 4 RRJ RCP** 322L/s 450mm 6.89% DESIGN: UK/MC DRAINAGE LONGITUDINAL SECTION SHEET 6
NORTHVIEW ESTATE - STAGE 6 & 7 **DRAINAGE LINE N - 20% AEP** 159.360 159.745 N5 116.01 159.330 160.53 159.702 328L/s 600mm 3.22% 158.730 159.191 N6 134.63 158.700 160 159.136 448L/s 600mm 8.16% FILE: 224103_ST6-7_DRAINAGE SCALE: H-NTS V-NTS
ORIGINAL DRAWING SIZE: A1 SHEET: SWD-LS006 LGA: MUSWELLBROOK 456L/s
600mm
1.05%
456L/s
456L/s
600mm
600m⁻
2.55% 154.930 155.535 **N7** 180.81 154.900 156.2 155.340 154.630 154.580 154.610 154.580 155.180 154.956 155.050 154.875 N8 N9-GPT 191.39 194.24 156 155.6 152.750 152.935 $^{\prime\prime\prime}$ N10 - HEADWALL 208.23 153.65 FOR DEVELOPMENT APPROVAL 15.11.2024 REV: A JOB REF: 224103

MIN HYNDES BAILEY & Co.
REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN
Surveying the Hunter since 1920 Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com.au 132 Kelly Street (PO Box 432), SCONE NSW 2337 PLANS PREPARED BY Invert Surface HGL Chalnage Level Level P1 - Basin 151.750 154.750 152.780 Datum El. 145 TINDALE CLIENT DRAINAGE LINE P - 1% AEP DESIGN: DRAINAGE LONGITUDINAL SECTION SHEET 7
NORTHVIEW ESTATE - STAGE 6 & 7 **CLASS 4 RRJ RCP** 291L/s 375mm 0.66% DRAWN: UK/MC SHEET: SWD-LS007 LGA: MUSWELLBROOK
FILE: 224103_ST6-7_DRAINAGE SCALE: H-NTS V-NTS
ORIGINAL DRAWING SIZE: A1 151.500 **151.856** P2 - HEADWALL \triangleright 38.00 151.5 FOR DEVELOPMENT APPROVAL PLAN ISSUE Invert Surface Chainage HGL Level Level R1 - HEADWALL 174.312 177 0 175.239 Datum El. 165 2763L/s 2.4 x 1.2m 1.00% RCBC 174.000 **175.204** 15.11.2024 REV: A JOB REF: 224103 R2 - HEADWALL 31.20 177







600 Min. ⁴

50

300

TOPSOIL & TURF EXPOSED AREAS


COMPACTED GRAVEL

TOPSOIL & TURF EXPOSED AREAS


COMPACTED GRAVEL

SUB-BASE

BASE



<u>N</u>



- NOTE:

 1. ALL DIMENSIONS IN MILLIMETRES
 2. CONCRETE TO BE 32 MPa UNLESS OTHERWISE SPECIFIED
 3. ALL EXPOSED CORNERS RADII 10mm UNLESS SPECIFIED OTHERWISE
 4. MINIMUM THICKNESS OF CONCRETE TO BE 150mm

PLANS PREPARED BY









STORMWATER NOTES & DETAILS

NORTHVIEW ESTATE - STAGE 6 & 7

MC/UK/RJ

DESIGN: MC / UK / RJ


FILE: 224103_ST6-7_CIVIL MGA94


15.11.2024


REV: A


224103

SUBSOIL TYPICAL INSTALLATION NOTE:
1. TYPE, LOCATION AND EXTENT OF ADDITIONAL SUBSOIL DRAINAGE SHALL BE IN ACCORDANCE WITH A GEOTECHNICAL CONSULTANT'S DEPTH MAY BE VARIED IN A ROCK SUBGRADE.
SEE THE CONSTRUCTION SECTION OF THE MANUAL
OF ENGINEERING STANDARDS FOR TRENCH
MATERIAL SPECIFICATION. EACH ZONE MAY BE
ONE HOMOGENEOUS APPROVED MATERIAL. MAY BE SUBSTITUTED FOR THE FILTER SAND FLUSH POINTS SHALL BE PROVIDED AT UPSTREAM DEAD ENDS & CRESTS & AT MAXIMUM OF 60m A NOMINAL SIZE AGGREGATE (10mm MAXIMUM) "SOCKED" SUBSOIL PIPE 100Ø CLEAN GRADED FILTER SAND OR GRADED AGGREGATE **SUB-SOIL DRAINAGE** ORIGINAL DRAWING SIZE: A1 H.SCALE: 1.500 LGA: MUSWELLBROOK SEE NOTE 2 "SOCKED" SUBSOIL PIPE 100Ø CONT INT 0.5m CLEANOUT PIPE SUBSOIL PIPE STORMWATER TRENCH WITH SUBSOIL (ALL STORMWATER PIPES) FLUSH POINT FOR DEVELOPMENT APPROVAL PLAN ISSUE - CONCRETE SURROUND
BEHIND KERB
FITTED WITH SCREWED
PLASTIC CAP PLASTIC OBLIQUE 'Y' CONNECTOR 100 I.D HAUNCH AND SIDE ⁵ ZONE (MIN LEVEL) BEDDING MATERIAL ⁵ ZONE BACKFILL ZONE 5 SELECT MATERIAL (AS REQUIRED)










SEWER MAINS DEEPER THAN 1.5m TO HAVE VERTICAL RISERS (JUMP UPS) TO A DEPTH NOT MORE THAN 1.5m OR TO THE REQUIRED PROPERTY CONNECTION LEVEL

INSTALL TRENCHSTOPS WHERE APPLICABLE - SEE DETAILS SHEET

GRADE	REQUIREMENT	SPACING S					
5 - 14	TRENCHSTOPS	S = 100/GRADE (%)					
		S = Lp/Grade (%), WHERE					
15 20	CONCRETE BULKHEAD	Lp = 80 x PIPE LENGTH*, m (450 m MAX)					
15 - 29	CONCRETE BULKHEAD	WHERE Lp>100 m - USE INTERMEDIATE TRENCHSTOPS AT SPACING < 100/GRADE (%)					
30 - 50	CONTINUOUS CONCRETE ENCSEMENT OF PIPELINE AND CONCRETE BULKHEADS	S = 100/GRADE (%)					
> 50	SPECIAL DESIGN						


REQUIREMENTS FOR BULKHEADS AND TRENCHSTOPS




SEWER LINE 1
H=1:500 V=1:100

DA ONLY - NOT FOR CONSTRUCTION

PLANS PREPARED BY CLIENT 15.11.2024 CONT. INT: 0.5m PLAN ISSUE SEWER LINE 1 LONG SECTION H.SCALE: ORIGINAL DRAWING SIZE: A1 MGA94 A FOR DEVELOPMENT APPROVAL MM HYNDES BAILEY & Co. NORTHVIEW ESTATE - STAGE 6 & 7 REV: A REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN LGA: MUSWELLBROOK Surveying the Hunter since 1920 DESIGN: JOB REF: FILE: 224103_ST6-7_SEWER WATER Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com.au M. COLE R. JONES 224103 SHEET: SEW-004 132 Kelly Street (PO Box 432), SCONE NSW 2337



SEWER LINE 2



SEWER LINE 3
H=1:500 V=1:100

DA ONLY - NOT FOR CONSTRUCTION

PLANS PREPARED BY


CLIENT

MM HYNDES BAILEY & Co.
REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN
Surveying the Hunter since 1920

TINDALE

SEWER LINE 2 & 3 LONG S	ECTION	H.SCALE: CONT. INT: 0.5m			PLAN ISSUE 15.11			
ORTHVIEW ESTATE - STAGE (3 & 7	ORIGINAL DRAW	VING SIZE: A1	MGA94	Α	FOR DEVELOPMENT APPROVAL	REV: A	
		LGA: MUSWELLBROOK					TEV. A	
ESIGN: M. COLE	DRAWN: M. COLE	FILE: 224103_	ST6-7_SEWER WA	TER			JOB REF:	
R. JONES	M. COLE R. JONES	SHEET: SEW0	005				224103	

Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com.au 132 Kelly Street (PO Box 432), SCONE NSW 2337



DN 150 RRJ uPVC SN8

6.585%

RL.170.0

DEPTH TO INVERT
INVERT
LEVEL
SURFACE
LEVEL
CHAINAGE

SEWER LINE 5


H=1:500 V=1:100


SEWER LINE 4

H=1:500 V=1:100

DA ONLY - NOT FOR CONSTRUCTION

PLANS PREPARED BY CLIENT PLAN ISSUE 15.11.2024 SEWER LINE 4 & 5 LONG SECTION H.SCALE: 1: CONT. INT: 0.5m ORIGINAL DRAWING SIZE: A1 MGA94 FOR DEVELOPMENT APPROVAL MM HYNDES BAILEY & Co. NORTHVIEW ESTATE - STAGE 6 & 7 REV: A REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN LGA: MUSWELLBROOK FILE: 224103_ST6-7_SEWER WATER JOB REF: Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com.au 132 Kelly Street (PO Box 432), SCONE NSW 2337 M. COLE R. JONES M. COLE R. JONES 224103 **SHEET: SEW-006**





SEWER LINE 6

DA ONLY - NOT FOR CONSTRUCTION

PLANS PREPARED BY

MM HYNDES BAILEY & Co.
REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN

REGISTERED SURVEYORS - TOWN PLANNING - CIVIL

Surveying the Hunter since 1920

Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com.au

132 Kelly Street (PO Box 432), SCONE NSW 2337

(HB)

TINDALE

CLIENT

INVERT (5)
INVERT (694)
LEVEL (74)
SURFACE (74)
LEVEL (74)


CHAINAGE 8


SEWER LINE 6 LONG SECTION
SEWER LINE 6 LONG SECTION NORTHVIEW ESTATE - STAGE 6 & 7


DESIGN: DRAWN:


M. COLE
R. JONES M. COLE
R. JONES

ORIGINAL DRAWING SIZE		Α	FOR DEVELOPMENT APPROVAL	REV: A
LGA: MUSWELLBROOK				
FILE: 224103_ST6-7_SI	WER WATER			JOB REF:
SHEET: SEW-007				224103









PLANS PREPARED BY

MM HYNDES BAILEY & Co. **REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN**

Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com.au 132 Kelly Street (PO Box 432), SCONE NSW 2337




TINDALE


CLIENT

						L	GA: MU
SEWER DETAILS IN ACCO SEWER CODE OF AUSTRA NORTHVIEW ESTATE - STAGE	ALIA - SH					O	RIGINAL
	ADDITIONAL	INFORMATION	PROVIDED	IN :	SEW-1200	SERIES	COMMENTARY

DESIGN: DRAWN: M. COLE R. JONES M. COLE R. JONES


			PLAN ISSUE	15.11.2024
ORIGINAL DRAWING SIZE: A1	MGA94	Α	FOR DEVELOPMENT APPROVAL	REV: A
LGA: MUSWELLBROOK				KEV. A
FILE: 224103_ST6-7_SEWER WATE	ER			JOB REF:
SHEET: SEW-008				224103






ADDITIONAL INFORMATION PROVIDED IN SEW-1200 SERIES COMMENTARY

132 Kelly Street (PO Box 432), SCONE NSW 2337







ADDITIONAL INFORMATION PROVIDED IN SEW-1300 SERIES COMMENTARY


SHEET: SEW -009


PLANS PREPARED BY PLAN ISSUE 15.11.2024 **CLIENT** SEWER DETAILS IN ACCORDANCE WITH SEWER CODE OF AUSTRALIA - SHEET 2 ORIGINAL DRAWING SIZE: A1 MGA94 A FOR DEVELOPMENT APPROVAL MM HYNDES BAILEY & Co. NORTHVIEW ESTATE - STAGE 6 & 7 REV: A **REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN LGA: MUSWELLBROOK** DESIGN: DRAWN: JOB REF: FILE: 224103_ST6-7_SEWER WATER M. COLE R. JONES 224103

R. JONES









PLANS PREPARED BY

MM HYNDES BAILEY & Co. **REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN**

Ph; 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com.au 132 Kelly Street (PO Box 432), SCONE NSW 2337



CLIENT


SEWER DETAILS IN ACCORDANCE WITH SEWER CODE OF AUSTRALIA - SHEET 3 NORTHVIEW ESTATE - STAGE 6 & 7


DRAWN:

ADDITIONAL INFORMATION PROVIDED IN SEW-1300 SERIES COMMENTARY

M. COLE R. JONES M. COLE R. JONES

15.11.2024 PLAN ISSUE ORIGINAL DRAWING SIZE: A1 MGA94 FOR DEVELOPMENT APPROVAL REV: A **LGA: MUSWELLBROOK** JOB REF FILE: 224103_ST6-7_SEWER WATER 224103 **SHEET: SEW-010**





COVER AND FRAME

ADDITIONAL INFORMATION PROVIDED IN SEW-1300 SERIES COMMENTAR

-(SEE NOTE 2)-

DA ONLY - NOT FOR CONSTRUCTION

ALL COVERS TO BE WATER TIGHT (SEE NOTE 7)

PLANS PREPARED BY CLIENT 15.11.2024 SEWER DETAILS IN ACCORDANCE WITH PLAN ISSUE SEWER CODE OF AUSTRALIA - SHEET 4 MGA94 ORIGINAL DRAWING SIZE: A1 FOR DEVELOPMENT APPROVAL MM HYNDES BAILEY & Co. NORTHVIEW ESTATE - STAGE 6 & 7 REV: A **REGISTERED SURVEYORS - TOWN PLANNING - CIVIL DESIGN LGA: MUSWELLBROOK** Surveying the Hunter since 1920 DESIGN: DRAWN: FILE: 224103_ST6-7_SEWER WATER JOB REF: M. COLE R. JONES M. COLE R. JONES Ph: 02 65432475 Fax: 02 65434400 Email: office @hbsurveys.com.au 224103 132 Kelly Street (PO Box 432), SCONE NSW 2337 SHEET: SEW-011

