

# BASIX<sup>®</sup>Certificate

Building Sustainability Index [www.basix.nsw.gov.au](http://www.basix.nsw.gov.au)

## Single Dwelling

Certificate number: 1776436S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at [www.basix.nsw.gov.au](http://www.basix.nsw.gov.au)

Secretary

Date of issue: Friday, 06 December 2024

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



### Project summary

Project name	2403660 Mason
Street address	63 BLACK ROCK Road MARTINS CREEK 2420
Local Government Area	Dungog Shire Council
Plan type and plan number	Deposited Plan DP790223
Lot no.	41
Section no.	-
Project type	dwelling house (detached)
No. of bedrooms	4

### Project score

Water	✓ 52	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	✓ 98	Target 70
Materials	✓ -100	Target n/a

### Certificate Prepared by

Name / Company Name: Sorensen Design

ABN (if applicable): 75803073495

# Description of project

Project address	
Project name	2403660 Mason
Street address	63 BLACK ROCK Road MARTINS CREEK 2420
Local Government Area	Dungog Shire Council
Plan type and plan number	Deposited Plan DP790223
Lot no.	41
Section no.	-
Project type	
Project type	dwelling house (detached)
No. of bedrooms	4
Site details	
Site area (m <sup>2</sup> )	66000
Roof area (m <sup>2</sup> )	310
Conditioned floor area (m <sup>2</sup> )	141.0
Unconditioned floor area (m <sup>2</sup> )	14.5
Total area of garden and lawn (m <sup>2</sup> )	500
Roof area of the existing dwelling (m <sup>2</sup> )	0

Assessor details and thermal loads			
Assessor number		n/a	
Certificate number		n/a	
Climate zone		n/a	
Area adjusted cooling load (MJ/ m².year)		n/a	
Area adjusted heating load (MJ/ m².year)		n/a	
Project score			
Water		<div><div></div></div> 52	Target 40
Thermal Performance		<div><div></div></div> Pass	Target Pass
Energy		<div><div></div></div> 98	Target 70
Materials		<div><div></div></div> -100	Target n/a

## Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<b>Fixtures</b>			
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development.		✓	
<b>Alternative water</b>			
<b>Rainwater tank</b>			
The applicant must install a rainwater tank of at least 20000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 310 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> <li>all toilets in the development</li> <li>the cold water tap that supplies each clothes washer in the development</li> <li>at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.)</li> <li>a tap that is located within 10 metres of the swimming pool in the development</li> </ul>		✓ ✓ ✓ ✓	✓ ✓ ✓ ✓

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<b>Swimming Pool</b>			
The swimming pool must not have a volume greater than 40 kilolitres.	✓	✓	
The swimming pool must have a pool cover.		✓	
The swimming pool must be outdoors.	✓	✓	

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<b>Do-it-yourself Method</b>			
General features			
The dwelling must be a Class 1 dwelling according to the National Construction Code, and must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓
The applicant must adopt one of the options listed in the tables below to address thermal bridging in metal framed floor(s), walls and ceiling/roof of the dwelling.	✓	✓	✓
The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the tables below.			✓

Construction	Area - m <sup>2</sup>	Additional insulation required	Options to address thermal bridging	Other specifications
floor - concrete slab on ground, conventional slab.	155.5	nil;not specified	nil	
external wall: framed (metal clad); frame: heavy steel post and beam frame.	all external walls	3.00 (or 3.50 including construction) with one of the measures to address thermal bridging;fibreglass batts or roll + reflective foil in the cavity	<ul style="list-style-type: none"> <li>• Install reflective foil outside the frame to create a minimum 20 mm reflective airspace between frame and veneer, or</li> <li>• Install continuous insulation layer with at least R0.3 on the inside or outside of the frame</li> </ul>	wall colour: please select

Construction	Area - m <sup>2</sup>	Additional insulation required	Options to address thermal bridging	Other specifications
internal wall: plasterboard; frame: timber - H2 treated softwood.	150	none	nil	
ceiling and roof - flat ceiling / pitched roof, framed - metal roof, heavy steel post and beam frame.	310	ceiling: 5 (up), roof: foil backed blanket with one of the measures to address thermal bridging; ceiling: fibreglass batts or roll; roof: foil backed blanket.	<ul style="list-style-type: none"> <li>• Install additional R0.5 (up) (or R5.5 (up) including the additional insulation), or</li> <li>• Install continuous ceiling insulation layer with at least R0.13 above or below the ceiling joists or the bottom chords of the trusses, or</li> <li>• Install two layers of insulation immediately on top of each other, with the top layer of at least R0.5 oriented to cover the ceiling joists or bottom chords of the trusses</li> </ul>	roof space ventilation: wind-driven ventilator(s) + eave vents; roof colour: medium (solar absorptance 0.48-0.59); 0.5 to $\leq$ 1.0% of ceiling area uninsulated

Note	<ul style="list-style-type: none"> <li>• Insulation specified in this Certificate must be installed in accordance with the ABCB Housing Provisions (Part 13.2.2) of the National Construction Code.</li> </ul>
Note	<ul style="list-style-type: none"> <li>• If the additional ceiling insulation listed in the table above is greater than R3.0, refer to the ABCB Housing Provisions (Part 13.2.3 (6)) of the National Construction Code.</li> </ul>
Note	<ul style="list-style-type: none"> <li>• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.</li> </ul>
Note	<ul style="list-style-type: none"> <li>• Thermal breaks must be installed in metal framed walls and applicable roofs in accordance with the ABCB Housing Provisions of the National Construction Code.</li> </ul>

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Ceiling fans			
The applicant must install at least one ceiling fan in at least one daytime habitable space, such as living room.	✓	✓	✓
<ul style="list-style-type: none"> <li>The minimum number and diameter of ceiling fans in a daytime habitable space must be installed in accordance with the ABCB Housing Provisions (Part 13.5.2) of the National Construction Code .</li> </ul>	✓	✓	✓

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Glazed windows, doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each glazed window and door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
The following requirements must also be satisfied in relation to each window and glazed door:	✓	✓	✓
<ul style="list-style-type: none"> <li>The applicant must install windows and glazed doors in accordance with the height and width, frame and glazing types listed in the table.</li> </ul>	✓	✓	✓
<ul style="list-style-type: none"> <li>Each window and glazed door must have a U- value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.</li> </ul>		✓	✓
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	✓	✓	✓

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
<b>North facing</b>					
W01 Living	2400.00	2100.00	aluminium, single glazed (U-value: <=4.0, SHGC: 0.60 - 0.74)	verandah 2400 mm, 2600 mm above base of window or glazed door	not overshadowed
W02 Living	1800.00	1200.00	aluminium, single glazed (U-value: <=4.0, SHGC: 0.60 - 0.74)	verandah 2400 mm, 2000 mm above base of window or glazed door	not overshadowed
W03 Dining	1800.00	1200.00	aluminium, single glazed (U-value: <=4.0, SHGC: 0.60 - 0.74)	verandah 2400 mm, 2000 mm above base of window or glazed door	not overshadowed
W04 Kitchen	1200.00	1200.00	aluminium, single glazed (U-value: <=4.0, SHGC: 0.60 - 0.74)	verandah 2400 mm, 1400 mm above base of window or glazed door	not overshadowed



Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
W05 Media	1800.00	1200.00	aluminium, single glazed (U-value: $\leq 4.0$ , SHGC: 0.60 - 0.74)	verandah 2400 mm, 2000 mm above base of window or glazed door	not overshadowed
W06 Bed	1800.00	1200.00	aluminium, single glazed (U-value: $\leq 4.0$ , SHGC: 0.60 - 0.74)	verandah 2400 mm, 2000 mm above base of window or glazed door	not overshadowed
<b>South facing</b>					
W07 Bed	1200.00	1800.00	aluminium, single glazed (U-value: $\leq 4.0$ , SHGC: 0.60 - 0.74)	verandah 2400 mm, 1400 mm above base of window or glazed door	not overshadowed
W08 Bed	1200.00	1800.00	aluminium, single glazed (U-value: $\leq 4.0$ , SHGC: 0.60 - 0.74)	verandah 2400 mm, 1400 mm above base of window or glazed door	not overshadowed
W09 Bath	900.00	1500.00	aluminium, single glazed (U-value: $\leq 4.0$ , SHGC: 0.60 - 0.74)	verandah 2400 mm, 1100 mm above base of window or glazed door	not overshadowed
W10 Ens	900.00	900.00	aluminium, single glazed (U-value: $\leq 4.0$ , SHGC: 0.60 - 0.74)	verandah 2400 mm, 1100 mm above base of window or glazed door	not overshadowed
W11 Bed	1200.00	1800.00	aluminium, single glazed (U-value: $\leq 4.0$ , SHGC: 0.60 - 0.74)	verandah 2400 mm, 1400 mm above base of window or glazed door	not overshadowed
<b>West facing</b>					
W12 Bed	1200.00	1800.00	aluminium, single glazed (U-value: $\leq 4.0$ , SHGC: 0.60 - 0.74)	eave 2400 mm, 1700 mm above head of window or glazed door	not overshadowed
W13 Living	2400.00	2100.00	aluminium, single glazed (U-value: $\leq 4.0$ , SHGC: 0.60 - 0.74)	eave 2400 mm, 1400 mm above head of window or glazed door	not overshadowed


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<b>Hot water</b>			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric boosted solar with a performance of 26 to 30 STCs or better.	✓	✓	✓
<b>Cooling system</b>			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - ducted; Energy rating: 5.5 star (average zone)		✓	✓
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning - ducted; Energy rating: 5.5 star (average zone)		✓	✓
<b>Heating system</b>			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: wood heater; Energy rating: n/a		✓	✓
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
The wood heater must have a compliance plate confirming that it complies with the relevant Australian standards, and must be installed in accordance with the requirements of all applicable regulatory authorities.			✓
<b>Ventilation</b>			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
<b>Artificial lighting</b>			
The applicant must ensure that a minimum of 80% of light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		✓	✓
<b>Natural lighting</b>			

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	✓	✓	✓
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	✓	✓	✓
<b>Swimming pool</b>			
The applicant must install the following heating system for the swimming pool in the development (or alternatively must not install any heating system for the swimming pool): solar only		✓	
The applicant must install the following pump for the swimming pool in the development, or a pump with a higher energy rating: dual speed with a performance of 5 stars.		✓	
The applicant must install a timer for the swimming pool pump in the development.		✓	
<b>Alternative energy</b>			
The applicant must install a photovoltaic system as part of the development. The applicant must connect this system to the development's electrical system.	✓	✓	✓
The photovoltaic system must consist of: <ul style="list-style-type: none"> <li>• photovoltaic collectors with the capacity to generate at least 15 peak kilowatts of electricity, installed at an angle between 10 degrees and 25 degrees to the horizontal facing north</li> </ul>	✓	✓	✓
<b>Other</b>			
The applicant must install an induction cooktop & electric oven in the kitchen of the dwelling.		✓	
The applicant must install a fixed outdoor clothes drying line as part of the development.		✓	

## Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.