

# Nationwide House Energy Rating Scheme®

## NatHERS® Certificate No. #HR-697LEM-01

Generated on 25 Jan 2025 using Hero 4.1 (Chenath v3.23)

### Property

**Address** Unit 04, 267 VICTORIA STREET,  
Taree, NSW, 2430

**Lot/DP** Lot 19/14 DP 3259

**NCC Class\*** 1a

**Floor/all Floors** 1 of 3 floors

**Type** New

### Plans

**Main Plan** 18.11.24 REV C

**Prepared by** CWC

### Construction and environment

<b>Assessed floor area (m²)*</b>		<b>Exposure Type</b>
<b>Conditioned*</b>	98.1	Suburban
<b>Unconditioned*</b>	5.2	<b>NatHERS climate zone</b>
<b>Total</b>	127.4	15 - Williamstown AMO
<b>Garage</b>	24.0	



### Accredited assessor

**Name** Adam Clarke

**Business name** 10 Star Building Assessments

**Email** admin@10sba.com

**Phone** +61 481010999

**Accreditation No.** 101518

**Assessor Accrediting Organisation** ABSA

**Declaration of interest** No Conflict of Interest

### NCC Requirements

**BCA provisions** Volume 2

**State/Territory variation** Yes

#### National Construction Code (NCC) requirements


The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J2D2(2)(a) and (3) of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at [www.abcb.gov.au](http://www.abcb.gov.au).

Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

### Thermal performance star rating



### Thermal performance (MJ/m²)

Limits taken from ABCB Standard 2022

	Heating	Cooling
<b>Modelled</b>	30.2	20.1
<b>Load limits</b>	42	32

#### Features determining load limits

Floor type	
(lowest conditioned area)	CSOG
NCC climate zone 1 or 2	N
Outdoor living area	N
Outdoor living area ceiling fan N	N

### Whole of Home performance rating

No Whole of Home  
performance rating  
generated for this  
certificate.

### Verification

To verify this certificate, scan  
the QR code or visit

<http://www.hero-software.com.au/pdf/HR-697LEM-01>.

When using either link,  
ensure you are visiting  
<http://www.hero-software.com.au>



\* Refer to glossary.

## About the ratings

### Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

### Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value\* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

## Heating and Cooling Load Limits

### Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the *ABCB Standard: NatHERS heating and cooling load limits* for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

### Setting options:

Floor type:

- CSOG - Concrete Slab on Ground
- SF - Suspended Floor (or a mixture of CSOG and SF)
- NA - Not Applicable

NCC climate Zone 1 or 2:

- Yes
- No
- NA - Not Applicable

Outdoor living area:

- Yes
- No
- NA - Not Applicable

Outdoor living area ceiling fan:

- Yes
- No
- NA - Not Applicable



## Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

## Predicted Whole of Home annual impact by appliance

Shows the contribution each appliance has on the home's annual energy use, greenhouse gas emissions and cost without solar.

### Energy use:

No Whole of Home performance assessment conducted for this certificate.

### Greenhouse gas emissions:

No Whole of Home performance assessment conducted for this certificate.

### Cost:

No Whole of Home performance assessment conducted for this certificate.

## Certificate check

The checklist covers important items impacting the dwelling's ratings.

It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and who should check each item.

It is not mandatory to complete this checklist.

Approval stage		Construction stage		
Assessor checked	Consent authority/ surveyor checked	Builder checked	Consent authority/ surveyor checked	Occupancy/other

### Genuine certificate check

Does this Certificate match the one available at the web address or QR code verification link on the front page?

☐☐☐☐

Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?

☐☐☐☐

### Thermal performance check

#### Windows and glazed doors

Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?

☐☐☐☐☐

Does the installed windows meet the substitution tolerances (AFRC\* based SHGC\* and U-values\*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?

☐☐☐

#### External walls

Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'External wall type table' on this Certificate?

☐☐☐☐☐

Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?

☐☐☐☐☐

#### Floor

Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?

☐☐☐☐☐

#### Ceiling penetrations\*

Does the 'quantity' and 'type' of ceiling penetrations\* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?

☐☐☐☐☐

#### Ceiling

Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?

☐☐☐☐☐

#### Roof

Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?

☐☐☐☐☐

#### Apartment entrance doors (NCC Class 2 assessments only)

Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.

☐☐☐☐

#### Exposure\*

Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".

☐☐☐☐

#### Heating and cooling load limits\*

Do the load limits settings (shown on page 1) match what is shown on the NatHERS-stamped plans?

☐☐☐☐☐

\* Refer to glossary.

## Certificate check

Continued

Approval stage		Construction stage		
Assessor checked	Consent authority/ surveyor checked	Builder checked	Consent authority/ surveyor checked	Occupancy/other

### Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

#### Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--	--------------------------	--------------------------	--------------------------	--------------------------

#### Insulation installation method

Has the insulation been installed according to the NCC requirements?			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--	--	--------------------------	--------------------------	--------------------------

#### Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
---	--	--------------------------	--------------------------	--------------------------	--------------------------

### Whole of Home performance check (not applicable if a Whole of Home assessment is not conducted)

#### Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed, match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

### Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the hot water system meet the additional requirements specified in the NCC?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

#### Provisional values\* check

Have provisional values* been used in the assessment and, if so, are they noted in 'Additional notes' table below?	<input type="checkbox"/>	<input type="checkbox"/>			
--	--------------------------	--------------------------	--	--	--

#### Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.

## Room schedule

Room	Zone Type	Area (m <sup>2</sup> )
Master (1)	Bedroom	13.58
FOYER	Day Time	9.83
WC	Day Time	2.32
BATH	Day Time	6.81
Stairs (TOP)	Day Time	4.41
L'DRY	Unconditioned	5.17
GARAGE	Garage	24.05
BED 3	Bedroom	9.06
KITCHEN	Kitchen/Living	36.22
BED 2	Bedroom	9.92
Hallway	Day Time	6.71
Stairs (MID)	Day Time	7.08

## Window and glazed door type and performance

### Default\* windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

### Custom\* windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
AWS-001-002	RESIDENTIAL SERIES 502/504 SLIDING WINDOW - SINGLE GLAZED	6.38	0.72	0.68	0.75
AWS-005-011	RESIDENTIAL SERIES 514 DOUBLE HUNG - SINGLE GLAZED	4.50	0.54	0.51	0.57
AWS-013-004	RESIDENTIAL SERIES 541/542 SLIDING DOOR -DOUBLE GLAZED	3.43	0.57	0.54	0.60
AWS-018-018	RESIDENTIAL SERIES 549 ENTRY DOOR - SINGLE GLAZED	4.41	0.46	0.44	0.49

## Custom\* windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
AWS-031-047	ARCHITECTURAL SERIES 463 DOUBLE HUNG WINDOW- DOUBLE GLAZED	3.63	0.42	0.40	0.44
AWS-066-002	RESIDENTIAL SERIES 516 FIXED WINDOW - SINGLE GLAZED	3.94	0.47	0.44	0.49
AWS-067-027	RES SERIES 516 FIXED WINDOW	2.19	0.41	0.39	0.43

## Window and glazed door schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orient-ation	Shading device*
BED 2	AWS-005-011	4W10-A	900	803	Double Hung	20	NE	None
BED 2	AWS-005-011	4W10-C	900	803	Double Hung	20	NE	None
BED 2	AWS-066-002	4W10-B	900	803	Fixed	0	NE	None
BED 3	AWS-005-011	4W09-A	900	803	Double Hung	20	NE	None
BED 3	AWS-066-002	4W09-B	900	803	Fixed	0	NE	None
BED 3	AWS-005-011	4W09-C	900	803	Double Hung	20	NE	None
FOYER	AWS-031-047	4W01	1800	735	Double Hung	45	SW	None
FOYER	AWS-018-018	4DG01	2050	920	Hinged Door	90	SW	None
KITCHEN	AWS-031-047	4W05-B	1200	600	Double Hung	45	NE	None
KITCHEN	AWS-067-027	4W05-C	600	600	Fixed	0	NE	None
KITCHEN	AWS-013-004	DG02	2100	2110	Sliding Door	45	NW	None
KITCHEN	AWS-031-047	4W06-C	900	803	Double Hung	45	NE	None
KITCHEN	AWS-031-047	4W06-A	900	803	Double Hung	45	NE	None
KITCHEN	AWS-067-027	4W06-B	900	803	Fixed	0	NE	None
KITCHEN	AWS-067-027	4W03	600	1800	Fixed	0	SW	None
L'DRY	AWS-001-002	4W02	1030	1510	Sliding	45	NE	None
Master (1)	AWS-005-011	4W08-C	900	703	Double Hung	20	NW	None
Master (1)	AWS-005-011	4W08-A	900	703	Double Hung	20	NW	None
Master (1)	AWS-066-002	4W08-B	900	703	Fixed	0	NW	None

\* Refer to glossary.



## Window and glazed door *schedule*

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orient-ation	Shading device*
Master (1)	AWS-005-011	4W07-C	900	883	Double Hung	20	SW	None
Master (1)	AWS-005-011	4W07-A	900	883	Double Hung	20	SW	None
Master (1)	AWS-066-002	4W07-B	900	883	Fixed	0	SW	None
Stairs (MID)	AWS-067-027	4W04-C	1800	822	Fixed	0	SW	None
Stairs (MID)	AWS-031-047	4W04-A	1200	822	Double Hung	45	SW	None
Stairs (MID)	AWS-067-027	4W04-B	600	822	Fixed	0	SW	None
Stairs (MID)	AWS-067-027	4W05-A	1800	600	Fixed	0	NE	None

## Roof window *type and performance value*

### Default\* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

### Custom\* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	SHGC substitution tolerance ranges	
				lower limit	upper limit
None					

## Roof window *schedule*

Location	Window ID	Window no.	Opening %	Height (mm)	Width (mm)	Orient-ation	Outdoor shade	Indoor shade
None								

## Skylight *type and performance*

Skylight ID	Skylight description
None	

## Skylight *schedule*

Location	Skylight ID	Skylight No.	Skylight shaft length (mm)	Area (m <sup>2</sup> )	Orient-ation	Outdoor shade	Diffuser	Shaft Reflectance
None								

## External door *schedule*

Location	Height (mm)	Width (mm)	Opening %	Orientation
GARAGE	2040	3200	90	NE
GARAGE	2040	3200	90	SW
L'DRY	2040	820	90	SE

## External wall *type*

Wall ID	Wall Type	Solar absorptance	Wall Colour	Bulk insulation (R-value)	Reflective wall wrap*
BV-NONREFL-CAV	Brick Veneer Stud Wall with Non-Reflective Sarking	0.50	Medium	2.70	No
CSR-2405	CSR-2405	0.50	Medium	4.00	No
DBL-BRICK-110-110-EXP	Double Brick - 110mm/110mm Exposed	0.50	Medium	0.00	No
PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)	0.50	Medium	2.70	No

## External wall *schedule*

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* projection (mm)	Vertical shading feature
BED 2	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2440	2998	NE	572	Yes
BED 2	CSR-2405	2440	311	SE		Yes
BED 3	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2440	1361	SE	476	Yes
BED 3	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2440	3014	NE	530	Yes
FOYER	BV-NONREFL-CAV	2440	864	SE	3811	Yes
FOYER	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2440	2021	SW		Yes
GARAGE	BV-NONREFL-CAV	2440	2000	NW		Yes

\* Refer to glossary.



## External wall *schedule*

Location	Wall ID	Height (mm)	Width (mm)	Orient-ation	Horizontal shading feature* projection (mm)	Vertical shading feature
GARAGE	DBL-BRICK-110-110-EXP	2440	4008	NE	2988	Yes
GARAGE	DBL-BRICK-110-110-EXP	2440	4008	SW	449	Yes
GARAGE	CSR-2405	2440	231	SE		Yes
Hallway	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2440	199	NW		Yes
Hallway	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	1890	1007	SW	674	Yes
KITCHEN	BV-NONREFL-CAV	2580	2602	NW	574	Yes
KITCHEN	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2580	1010	NE	3046	Yes
KITCHEN	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2580	2531	NW	3040	Yes
KITCHEN	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2580	3103	NE	522	Yes
KITCHEN	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2580	4008	SW	670	Yes
KITCHEN	CSR-2405	2580	885	SE	1797	Yes
KITCHEN	CSR-2405	2580	3428	SE	2936	Yes
L'DRY	BV-NONREFL-CAV	2440	2021	NE		Yes
L'DRY	BV-NONREFL-CAV	2440	2557	SE	3811	Yes
L'DRY	BV-NONREFL-CAV	2440	1816	NW	3828	Yes
Master (1)	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2440	3387	NW	695	Yes
Master (1)	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2440	4008	SW	643	Yes

\* Refer to glossary.

## External wall *schedule*

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* projection (mm)	Vertical shading feature
Master (1)	CSR-2405	2440	817	SE	1889	Yes
Master (1)	CSR-2405	2440	1151	SE		Yes
Stairs (MID)	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2580	2021	SW	719	Yes
Stairs (MID)	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	2580	2021	NE	3046	Yes
Stairs (TOP)	PrimeLine™ weatherboard, Scyon™ Stria™ cladding & Scyon™ Linea™ weatherboard (DF)1	1890	996	SW	674	Yes

## Internal wall *type*

Wall ID	Wall Type	Area (m²)	Bulk insulation
CSR-2405	CSR-2405	85.6	4.00
INT-PB	Internal Plasterboard Stud Wall	11.4	2.00
INT-PB	Internal Plasterboard Stud Wall	57.6	0.00
INT-PB	Internal Plasterboard Stud Wall	1.1	2.70

## Floor *type*

Location	Construction	Area (m²)	Sub-floor ventilation	Added insulation (R-value)	Covering
BATH	LT-CONC-SUBFLR-35: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC)	6.8	N/A	0.15	Tile (8mm)
BED 2	LT-CONC-SUBFLR-35: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC)	9.9	N/A	0.15	Carpet
BED 3	LT-CONC-SUBFLR-35-LINED: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC) - Lined Below	9.1	N/A	4.00	Carpet
FOYER	CSOG-125: Concrete Slab on Ground (125mm)	9.8	N/A	2.00	Tile (8mm)
GARAGE	CSOG-125: Concrete Slab on Ground (125mm)	24.0	N/A	0.00	Exposed
Hallway	LT-CONC-SUBFLR-35: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC)	6.8	N/A	0.15	Vinyl
KITCHEN	LT-CONC-SUBFLR-35: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC)	24.0	N/A	2.00	Vinyl
KITCHEN	LT-CONC-SUBFLR-35-LINED: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC) - Lined Below	12.1	N/A	4.00	Vinyl

\* Refer to glossary.

## Floor type

Location	Construction	Area (m <sup>2</sup> )	Sub-floor ventilation	Added insulation (R-value)	Covering
L'DRY	CSOG-125: Concrete Slab on Ground (125mm)	5.2	N/A	0.00	Tile (8mm)
Master (1)	LT-CONC-SUBFLR-35: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC)	13.6	N/A	0.15	Carpet
Stairs (MID)	LT-CONC-SUBFLR-35: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC)	7.1	N/A	0.15	Vinyl
Stairs (TOP)	LT-CONC-SUBFLR-35: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC)	4.4	N/A	0.15	Vinyl
WC	LT-CONC-SUBFLR-35: Lightweight Concrete Subfloor Panel 35mm (as 42mm FC)	2.3	N/A	0.15	Tile (8mm)

## Ceiling type

Location	Construction	Bulk insulation (R-value)	Reflective wrap*
BATH	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
BED 2	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
BED 3	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
Hallway	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
KITCHEN	FLAT-03: Flat Framed / Skillion Tile Roof & Flat PB Ceiling	4.00	Yes
L'DRY	FLAT-03: Flat Framed / Skillion Tile Roof & Flat PB Ceiling	4.00	No
Master (1)	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	4.00	Yes
Stairs (MID)	FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	4.00	Yes
Stairs (TOP)	ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	4.00	Yes

## Ceiling penetrations\*

Location	Quantity	Type	Diameter (mm)	Sealed /unsealed
BATH	1	Exhaust Fan	300	Sealed
BATH	2	Downlight	100	Sealed
BED 2	2	Downlight	100	Sealed
BED 3	2	Downlight	100	Sealed
FOYER	2	Downlight	100	Sealed
Hallway	2	Downlight	100	Sealed

## Ceiling penetrations\*

Location	Quantity	Type	Diameter (mm)	Sealed /unsealed
KITCHEN	1	Exhaust Fan	250	Sealed
KITCHEN	8	Downlight	100	Sealed
L'DRY	1	Exhaust Fan	250	Sealed
L'DRY	1	Downlight	100	Sealed
Master (1)	3	Downlight	100	Sealed
Stairs (MID)	2	Downlight	100	Sealed
Stairs (TOP)	2	Downlight	100	Sealed
WC	1	Exhaust Fan	250	Sealed
WC	1	Downlight	100	Sealed

## Ceiling fans

Location	Quantity	Diameter (mm)
BED 2	1	1300
BED 3	1	1300
KITCHEN	1	1500
Master (1)	1	1300

## Roof type

Construction	Added insulation (R-value)	Solar absorptance	Roof Colour
ATTIC-METAL-01: Pitched / Attic Metal Roof (Roofspace) & Flat PB Ceiling	1.30	0.50	Medium
FLAT-01: Flat Framed / Skillion Metal Roof & Flat PB Ceiling	1.30	0.50	Medium
FLAT-03: Flat Framed / Skillion Tile Roof & Flat PB Ceiling	0.00	0.50	Medium
FLAT-03: Flat Framed / Skillion Tile Roof & Flat PB Ceiling	1.30	0.50	Medium

## Thermal bridging schedule for steel frame elements

Building element	Steel section dimensions (height x width, mm)	Frame spacing (mm)	Steel thickness (BMT mm)	Thermal Break (R-value)
None				



## Appliance schedule

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

### Cooling system

Type	Location	Fuel Type	Minimum efficiency / performance	Recommended capacity
No Whole of Home Data				

### Heating system

Type	Location	Fuel Type	Minimum efficiency / performance	Recommended capacity
No Whole of Home Data				

### Hot water system

Type	Fuel type	Hot Water CER Zone	Minimum efficiency / STC	Assessed daily load [litres]
No Whole of Home Data				

### Pool / spa equipment

Type	Fuel type	Minimum efficiency / performance	Recommended capacity
No Whole of Home Data			

## Onsite Renewable Energy schedule

Type	Orientatation	Generation Capacity [kW]
No Whole of Home Data		

## Battery schedule

Type	Storage Capacity [kWh]
No Whole of Home Data	

## Explanatory Notes

### About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value\* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the home's energy value\*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary.

Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

### Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and

are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

### Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

## Glossary

<b>Annual energy load</b>	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
<b>AFRC</b>	Australian Fenestration Rating Council
<b>Assessed floor area</b>	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
<b>Ceiling penetrations</b>	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
<b>Conditioned</b>	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
<b>COP</b>	Coefficient of performance
<b>Custom windows</b>	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
<b>Default windows</b>	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
<b>EER</b>	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
<b>Energy use</b>	This is your home's rating without solar or batteries.
<b>Energy value</b>	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
<b>Entrance door</b>	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
<b>Exposure</b>	see exposure categories below
<b>Exposure category - exposed</b>	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
<b>Exposure category - open</b>	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
<b>Exposure category - suburban</b>	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
<b>Exposure category - protected</b>	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
<b>Horizontal shading feature</b>	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
<b>National Construction Code (NCC) Class</b>	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at <a href="http://www.abcb.gov.au">www.abcb.gov.au</a> .
<b>Net zero home</b>	a home that achieves a net zero energy value*.
<b>Opening percentage</b>	the openability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
<b>Provisional value</b>	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at <a href="http://www.nathers.gov.au">www.nathers.gov.au</a>
<b>Recommended capacity</b>	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
<b>Reflective wrap (also known as foil)</b>	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
<b>Roof window</b>	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
<b>Shading features</b>	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
<b>Solar heat gain coefficient (SHGC)</b>	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
<b>Skylight (also known as roof lights)</b>	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
<b>STCs</b>	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulatory
<b>Thermal breaks</b>	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick, continuous thermal breaks such as polystyrene insulation sheeting, plastic strips or furring channels.
<b>U-value</b>	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
<b>Unconditioned</b>	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions
<b>Vertical shading features</b>	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
<b>Window shading device</b>	a device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)

\* Refer to glossary.