

# Nationwide House Energy Rating Scheme®

## NatHERS® Certificate No. 0011658572

Generated on 15 Jan 2025 using BERS Pro v5.2.4 (3.23)

### Property

**Address** 60 Farrell Road,  
BASS HILL, NSW, 2197

**Lot/DP** Lot 207 DP 230871

**NCC class\*** 1a

**Floor/all Floors** G of 2 floors

**Type** New Home

### Plans

**Main plan** Lot 207 No 60 Farrell Road Bass Hill

**Prepared by** GJC

### Construction and environment

<b>Assessed floor area [m2]*</b>	<b>Exposure type</b>
Conditioned* 220.8	Suburban
Unconditioned* 17.0	<b>NatHERS climate zone</b>
Total 278.1	56 Mascot (Sydney Airport)
Garage 40.3	



### Accredited assessor

**Name** Ian Fry

**Business name** Frys Energywise

**Email** comply@frysenergywise.com.au

**Phone** 02 9899 2825

**Accreditation No.** DMN/12/1441

**Assessor Accrediting Organisation** Design Matters National

**Declaration of interest** Declaration completed: no conflicts

### NCC Requirements

**NCC provisions** Volume Two

**Strate/Territory variation** Yes

### National Construction Code (NCC) requirements


The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J3D3 and J3D15 of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at [www.abcb.gov.au](http://www.abcb.gov.au).

Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

### Thermal performance Star rating



### Thermal performance [MJ/m²]

Limits taken from ABCB Standard 2022

	Heating	Cooling
<b>Modelled</b>	18.4	11.7
<b>Load limits</b>	N/A	N/A

### Features determining load limits

Floor Type (lowest conditioned area)	CSOG
NCC climate zone 1 or 2	No
Outdoor living area	No
Outdoor living area ceiling fan	No

### Whole of Home performance rating

No Whole of Home  
performance rating  
generated for this  
certificate.

### Verification

To verify this certificate, scan the QR code or visit [hstar.com.au/QR/Generate?p=iRKoaUOSs](http://hstar.com.au/QR/Generate?p=iRKoaUOSs). When using either link, ensure you are visiting [hstar.com.au](http://hstar.com.au)



## About the ratings

### Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

### Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value\* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

## Heating & Cooling Load Limits

### Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the *ABC Standard 2022: NatHERS heating and cooling load limits* for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

### Setting Options:

Floor Type:

CSOG – Concrete Slab on Ground  
SF – Suspended Floor (or a mixture of CSOG and SF)  
NA – Not Applicable

NCC Climate Zone 1 or 2:

Yes  
No  
NA – Not Applicable

Outdoor Living Area:

Yes  
No  
NA – Not Applicable

Outdoor Living Area Ceiling Fan:

Yes  
No  
NA – Not Applicable



## Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

## Predicted Whole of Home annual impact by appliance

### Energy use

No Whole of Home performance assessment conducted for this certificate

### Greenhouse gas emissions

No Whole of Home performance assessment conducted for this certificate

### Cost

No Whole of Home performance assessment conducted for this certificate

## Certificate check

The checklist covers important items impacting the dwelling's ratings. It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and by whom each item should be checked. It is not mandatory to complete this checklist.

	Approval Stage		Construction Stage		Occupancy/Other
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	
<b>Genuine certificate check</b>					
Does this Certificate match the one available at the web address or QR code verification link on the front page?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Thermal performance check</b>					
<b>Windows and glazed doors</b>					
Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the installed windows meet the substitution tolerances (AFRC* based SHGC* and U-values*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>External walls</b>					
Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the External wall type table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Floor</b>					
Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Ceiling penetrations*</b>					
Does the 'quantity' and 'type' of ceiling penetrations* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Ceiling</b>					
Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Roof</b>					
Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Apartment entrance doors (NCC Class 2 assessments only)</b>					
Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
<b>Exposure*</b>					
Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
<b>Heating and cooling load limits*</b>					
Do the load limits settings (shown on page 1) match what is shown	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>



## Certificate check

Continued

	Approval Stage		Construction Stage		
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	Occupancy/Other

### Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

#### Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?

☐ ☐ ☐ ☐

#### Insulation installation method

Has the insulation been installed according to the NCC requirements?

☐ ☐ ☐

#### Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?

☐ ☐ ☐ ☐

### Whole of Home performance check (not applicable if a Whole of Home performance assessment is not conducted)

#### Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the Appliance schedule on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or installed, match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?

☐ ☐ ☐ ☐ ☐

### Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?

☐ ☐ ☐ ☐

Does the hot water system meet the additional requirements specified in the NCC?

☐ ☐ ☐ ☐

#### Provisional values\* check

Have provisional values\* been used in the assessment and, if so, are they noted in 'Additional notes' table below?

☐ ☐ ☐ ☐

#### Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.

#### Additional notes

Where not noted on plans, default selections to floor coverings and external colours have been used in this

assessment, as noted in the NatHERS Technical Notes. Alternative selections past this point can be made to floor

coverings and external colours, without requiring an amended certificate.

## Room schedule

Room	Zone Type	Area [m <sup>2</sup> ]
LAUNDRY	Unconditioned	8.41
PANTRY	Daytime	7.3
BED 3	Bedroom	12.53
GF BATH	Unconditioned	8.56
BED 2	Bedroom	12.53
ENSUITE	Nighttime	6.49
MASTER WIR	Nighttime	4.77
MASTER SUITE	Bedroom	14.93
DIN FAM KIT	Kitchen/Living	69.74
WIL	Daytime	3.49
LOUNGE	Living	18.73
ENTRY GF HALL	Daytime	19.7
GARAGE	Garage	40.3
BED 4	Bedroom	11.73
ATTIC BATH	Daytime	4.02
STUDY UF HALL	Living	36.05

## Window and glazed door type and performance

### Default windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

### Custom windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
WID-102-001	Aluminium Sliding Window SG 4Clr	6.3	0.76	0.72	0.79
WID-102-030	Aluminium Sliding Window DG 6Clr-8Ar-6PbAS2	3.3	0.45	0.43	0.47
WID-106-030	Aluminium Fixed Window DG 6Clr-8Ar-6PbAS2	2.3	0.52	0.49	0.54
WID-105-030	Aluminium Stacking Door DG 6Clr-8Ar-6PbAS2	3.0	0.49	0.46	0.51

\* Refer to glossary.



## Custom windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
WID-125-031	Aluminium Bifold Door DG 6Clr/12Ar/6PbAS2	3.2	0.39	0.37	0.41
WID-104-001	Aluminium Sliding Door SG 4Clr	6.2	0.74	0.70	0.78
WID-101-014	Aluminium Awning Window DG 6Clr-8Ar-6PbAS2	3.4	0.43	0.41	0.45

## Window and glazed door schedule

Location	Window ID	Window no.	Height [mm]	Width [mm]	Window type	Opening %	Orientation	Window shading device*
LAUNDRY	WID-102-001-003	W08	1200	1200	Sliding	45	NE	No
PANTRY	WID-102-030-001	W20	1200	900	Sliding	45	NW	No
BED 3	WID-102-030-001	W07	1200	1800	Sliding	45	NW	No
GF BATH	WID-102-001-003	W06	600	1500	Sliding	45	NW	No
BED 2	WID-102-030-001	W05	1200	1800	Sliding	45	NW	No
ENSUITE	WID-102-001-003	W04	1200	1200	Sliding	45	NW	No
MASTER SUITE	WID-106-030-002	W27	1800	300	Fixed	00	SW	No
MASTER SUITE	WID-102-030-001	W26	1800	2100	Sliding	30	SW	No
DIN FAM KIT	WID-105-030-002	W10	2400	3600	Sliding	45	NE	No
DIN FAM KIT	WID-125-031-002	W09	1500	1500	Bifold	90	NE	No
DIN FAM KIT	WID-102-030-001	W13	2100	900	Sliding	30	SE	No
DIN FAM KIT	WID-102-030-001	W12	2100	900	Sliding	30	SE	No
DIN FAM KIT	WID-102-030-001	W11	2100	900	Sliding	30	SE	No
LOUNGE	WID-102-030-001	W01	1800	2000	Sliding	30	SW	No
GARAGE	WID-104-001-002	W14	2100	1800	Sliding	45	SE	No
GARAGE	WID-102-001-003	W16	600	2200	Sliding	45	SE	No
STUDY UF HALL	WID-101-014-002	W28	700	2400	Awning	10	SW	No
STUDY UF HALL	WID-106-030-002	S5	350	2400	Fixed	00	N	No

\* Refer to glossary.



## Roof window\* type and performance value

### Default roof windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

### Custom roof windows\*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

## Roof window\* schedule

Location	Window ID	Window no.	Opening %	Height [mm]	Width [mm]	Orientation	Outdoor shade	Indoor shade
No Data Available								

## Skylight\* type and performance

Skylight ID	Skylight description	Skylight shaft reflectance
GEN-04-006a	Single-glazed clear, Timber and Aluminium Frame	0.5

## Skylight\* schedule

Location	Skylight ID	Skylight No.	Skylight shaft length [mm]	Area [m <sup>2</sup> ]	Orientation	Outdoor shade	Diffuser
BED 4	GEN-04-008a	Bed 4 Skylight 1	170	0.54	N	None	No
BED 4	GEN-04-008a	Bed 4 Skylight 2	170	0.54	N	None	No
ATTIC BATH	GEN-04-006a	Attic Bath Skytube	170	0.20	N	None	No
STUDY UF HALL	GEN-04-008a	Study Skylight 1	170	0.54	N	None	No

## External door schedule

Location	Height [mm]	Width [mm]	Opening %	Orientation
LAUNDRY	2340	820	90	SE
ENTRY GF HALL	2040	1200	90	SW
GARAGE	2400	2300	90	NE
GARAGE	2400	4800	90	SW

## External wall type

Wall ID	Wall type	Solar absorptance	Wall shade [colour]	Bulk insulation [R-value]	Reflective wall wrap*
EW-1	Timber Stud Frame Brick Veneer	0.50		Anti-glare foil with bulk no gap R2.5	No
EW-2	Fibro Timber Stud Frame Panel on Battens	0.50		Anti-glare foil with bulk no gap R2.5	No
EW-3	Timber Stud Frame Brick Veneer	0.50		No insulation	No
EW-4	Single Skin Brick	0.50		No insulation	No
EW-5	Fibro Timber Stud Frame Panel on Battens	0.50		Anti-glare foil with bulk no gap R4	No

## External wall schedule

Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
LAUNDRY	EW-1	2700	3295	SE	9400	No
LAUNDRY	EW-1	2700	3295	NW	600	No
LAUNDRY	EW-1	2700	2600	NE	600	No
PANTRY	EW-1	2700	3990	NW	600	No
BED 3	EW-1	2700	3090	NW	600	No
GF BATH	EW-1	2700	2190	NW	600	No
BED 2	EW-1	2700	3090	NW	600	No
ENSUITE	EW-1	2700	2790	NW	600	No
MASTER SUITE	EW-1	2700	1300	SE	10800	No
MASTER SUITE	EW-1	2700	1500	SW	600	No
MASTER SUITE	EW-1	2360	2300	SW	0	No
MASTER SUITE	EW-2	341	2300	SW	600	No
MASTER SUITE	EW-1	2700	400	SW	600	No
MASTER SUITE	EW-1	2700	3595	NW	600	No
DIN FAM KIT	EW-1	2700	8800	NE	3900	No
DIN FAM KIT	EW-1	2700	9495	SE	600	No
LOUNGE	EW-1	2700	2790	SW	1200	No
ENTRY GF HALL	EW-1	2700	1790	SW	1200	No
GARAGE	EW-3	2700	3695	SE	600	No
GARAGE	EW-4	2786	3000	NE	600	No
GARAGE	EW-3	2786	5600	SE	600	No





Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
GARAGE	EW-4	2786	5600	SW	600	No
GARAGE	EW-3	2786	1300	NW	9400	No
BED 4	EW-5	1834	3195	SE	100	No
BED 4	EW-5	1834	1995	NW	100	No
BED 4	EW-5	2432	4200	NE	100	No
ATTIC BATH	EW-5	1834	1490	SE	100	No
STUDY UF HALL	EW-5	1834	7395	SE	100	No
STUDY UF HALL	EW-5	1310	4200	SW	0	No
STUDY UF HALL	EW-2	1122	4200	SW	400	No
STUDY UF HALL	EW-5	1834	5900	NW	100	No
STUDY UF HALL	EW-5	1635	700	SW	100	No
STUDY UF HALL	EW-5	1440	3000	NW	100	No
STUDY UF HALL	EW-5	1635	700	NE	100	No
STUDY UF HALL	EW-5	1834	1195	NW	100	No

## Internal wall type

Wall ID	Wall type	Area [m <sup>2</sup> ]	Bulk insulation
IW-001	Timber Stud Frame, Direct Fix Plasterboard	88.84	Bulk Insulation, No Air Gap R2.5
IW-002	Timber Stud Frame, Direct Fix Plasterboard	123.69	No insulation

## Floor type

Location	Construction	Area [m <sup>2</sup> ]	Sub-floor ventilation	Added insulation [R-value]	Covering
LAUNDRY	Waffle pod slab 300 mm 100mm	8.40	None	Waffle Pod 300mm	Ceramic Tiles 8mm
PANTRY	Waffle pod slab 300 mm 100mm	7.30	None	Waffle Pod 300mm	Ceramic Tiles 8mm
BED 3	Waffle pod slab 300 mm 100mm	12.53	None	Waffle Pod 300mm	Carpet+Rubber Underlay 18mm
GF BATH	Waffle pod slab 300 mm 100mm	8.56	None	Waffle Pod 300mm	Ceramic Tiles 8mm
BED 2	Waffle pod slab 300 mm 100mm	12.53	None	Waffle Pod 300mm	Carpet+Rubber Underlay 18mm
ENSUITE	Waffle pod slab 300 mm 100mm	6.49	None	Waffle Pod 300mm	Ceramic Tiles 8mm



Location	Construction	Area [m <sup>2</sup> ]	Sub-floor ventilation	Added insulation [R-value]	Covering
MASTER WIR	Waffle pod slab 300 mm 100mm	4.77	None	Waffle Pod 300mm	Carpet+Rubber Underlay 18mm
MASTER SUITE	Waffle pod slab 300 mm 100mm	14.93	None	Waffle Pod 300mm	Carpet+Rubber Underlay 18mm
DIN FAM KIT	Waffle pod slab 300 mm 100mm	69.74	None	Waffle Pod 300mm	20/80 Carpet 10mm/Ceramic
WIL	Waffle pod slab 300 mm 100mm	3.49	None	Waffle Pod 300mm	Ceramic Tiles 8mm
LOUNGE	Waffle pod slab 300 mm 100mm	18.73	None	Waffle Pod 300mm	Carpet+Rubber Underlay 18mm
ENTRY GF HALL	Waffle pod slab 300 mm 100mm	19.70	None	Waffle Pod 300mm	Ceramic Tiles 8mm
GARAGE	Waffle pod slab 225 mm 100mm	40.30	None	Waffle Pod 300mm	Bare
BED 4 / BED 3	Timber Framed Timber Above Plasterboard 19mm	0.69		No Insulation	Carpet+Rubber Underlay 18mm
BED 4 / DIN FAM KIT	Timber Framed Timber Above Plasterboard 19mm	9.54		No Insulation	Carpet+Rubber Underlay 18mm
BED 4 / ENTRY GF HALL	Timber Framed Timber Above Plasterboard 19mm	0.98		No Insulation	Carpet+Rubber Underlay 18mm
ATTIC BATH / DIN FAM KIT	Timber Framed Timber Above Plasterboard 19mm	2.82		No Insulation	Ceramic Tiles 8mm
ATTIC BATH / ENTRY GF HALL	Timber Framed Timber Above Plasterboard 19mm	0.73		No Insulation	Ceramic Tiles 8mm
STUDY UF HALL / BED 3	Timber Framed Timber Above Plasterboard 19mm	0.00		No Insulation	Carpet+Rubber Underlay 18mm
STUDY UF HALL / GF BATH	Timber Framed Timber Above Plasterboard 19mm	1.27		No Insulation	Carpet+Rubber Underlay 18mm
STUDY UF HALL / BED 2	Timber Framed Timber Above Plasterboard 19mm	0.63		No Insulation	Carpet+Rubber Underlay 18mm
STUDY UF HALL / MASTER WIR	Timber Framed Timber Above Plasterboard 19mm	0.10		No Insulation	Carpet+Rubber Underlay 18mm
STUDY UF HALL / DIN FAM KIT	Timber Framed Timber Above Plasterboard 19mm	0.00		No Insulation	Carpet+Rubber Underlay 18mm
STUDY UF HALL / WIL	Timber Framed Timber Above Plasterboard 19mm	0.40		No Insulation	Carpet+Rubber Underlay 18mm
STUDY UF HALL / LOUNGE	Timber Framed Timber Above Plasterboard 19mm	8.09		No Insulation	Carpet+Rubber Underlay 18mm
STUDY UF HALL / ENTRY GF HALL	Timber Framed Timber Above Plasterboard 19mm	13.69		No Insulation	Carpet+Rubber Underlay 18mm

## Ceiling type

Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap* [yes/no]
LAUNDRY	Plasterboard on Timber	Bulk Insulation R6	



Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap* [yes/no]
LAUNDRY	Plasterboard on Timber	Bulk Insulation R2.5	
PANTRY	Plasterboard on Timber	Bulk Insulation R6	
PANTRY	Plasterboard on Timber	Bulk Insulation R2.5	
BED 3	Plasterboard on Timber	Bulk Insulation R6	
BED 3	Plasterboard on Timber	Bulk Insulation R2.5	
BED 3	Timber Framed Timber Above Plasterboard	No Insulation	
GF BATH	Plasterboard on Timber	Bulk Insulation R6	
GF BATH	Plasterboard on Timber	Bulk Insulation R2.5	
GF BATH	Timber Framed Timber Above Plasterboard	No Insulation	
BED 2	Plasterboard on Timber	Bulk Insulation R6	
BED 2	Plasterboard on Timber	Bulk Insulation R2.5	
BED 2	Timber Framed Timber Above Plasterboard	No Insulation	
ENSUITE	Plasterboard on Timber	Bulk Insulation R6	
ENSUITE	Plasterboard on Timber	Bulk Insulation R2.5	
MASTER WIR	Plasterboard on Timber	Bulk Insulation R6	
MASTER WIR	Timber Framed Timber Above Plasterboard	No Insulation	
MASTER SUITE	Plasterboard on Timber	Bulk Insulation R6	
MASTER SUITE	Plasterboard on Timber	Bulk Insulation R2.5	
DIN FAM KIT	Plasterboard on Timber	Bulk Insulation R6	
DIN FAM KIT	Plasterboard on Timber	Bulk Insulation R2.5	
DIN FAM KIT	Timber Framed Timber Above Plasterboard	No Insulation	
WIL	Plasterboard on Timber	Bulk Insulation R6	
WIL	Timber Framed Timber Above Plasterboard	No Insulation	
LOUNGE	Plasterboard on Timber	Bulk Insulation R6	
LOUNGE	Timber Framed Timber Above Plasterboard	No Insulation	
ENTRY GF HALL	Plasterboard on Timber	Bulk Insulation R6	
ENTRY GF HALL	Timber Framed Timber Above Plasterboard	No Insulation	
GARAGE	Plasterboard on Timber	No insulation	
BED 4	Plasterboard on Timber	Bulk Insulation R4	
ATTIC BATH	Plasterboard on Timber	Bulk Insulation R4	
STUDY UF HALL	Plasterboard on Timber	Bulk Insulation R4	



## Ceiling penetrations\*

Location	Quantity	Type	Diameter [mm]	Sealed/unsealed
GF BATH	1	Exhaust Fans	300	Sealed
ENSUITE	1	Exhaust Fans	300	Sealed
DIN FAM KIT	1	Exhaust Fans	300	Sealed
ATTIC BATH	1	Exhaust Fans	300	Sealed

## Ceiling fans

Location	Quantity	Diameter [mm]
DIN FAM KIT	1	1200
LOUNGE	1	1200

## Roof type

Construction	Added insulation [R-value]	Solar absorptance	Roof shade [colour]
Roof Tiles Timber Frame	Foil, Gap Above, Reflective Side Down, Anti-glare Up	0.85	Dark

## Thermal bridging schedule for steel frame elements

Building element	Steel section dimensions [height x width, mm]	Frame spacing [mm]	Steel thickness [BMT,mm]	Thermal break [R-value]
No Data Available				

## Appliance schedule

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

Note: A flat assumption of 5W/m<sup>2</sup> is used for lighting, therefore lighting is not included in the appliance schedule.

### Cooling system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				

### Heating system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				



## Hot water system

Appliance/ system type	Fuel type	Hot Water CER Zone	Minimum efficiency /STC	Zone 3 STC	Zone 3 Substitution tolerance ranges		Assessed daily load [litres]
					lower limit	upper limit	
No Data Available							

## Pool/spa equipment

Appliance/ system type	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available			

## Onsite Renewable Energy Schedule

System Type	Orientation	System Size Or Generation Capacity
No Data Available		

## Battery Schedule

System Type	Size [Battery Storage Capacity]
No Data Available	



## Explanatory notes

### About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value\* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the home's energy value\*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary.

Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

### Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and

are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

### Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

## Glossary

<b>AFRC</b>	Australian Fenestration Rating Council
<b>Annual energy load</b>	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
<b>Assessed floor area</b>	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
<b>Ceiling penetrations</b>	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
<b>COP</b>	Coefficient of performance
<b>Conditioned</b>	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
<b>Custom windows</b>	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
<b>Default windows</b>	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
<b>EER</b>	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
<b>Energy use</b>	This is your home's rating without solar or batteries.
<b>Energy value</b>	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
<b>Entrance door</b>	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
<b>Exposure</b>	see exposure categories below.
<b>Exposure category – exposed</b>	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
<b>Exposure category – open</b>	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
<b>Exposure category – protected</b>	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
<b>Exposure category – suburban</b>	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
<b>Horizontal shading feature</b>	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
<b>National Construction Code (NCC) Class</b>	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at <a href="http://www.abcb.gov.au">www.abcb.gov.au</a> .
<b>Net zero home</b>	a home that achieves a net zero energy value*.
<b>Opening percentage</b>	the operability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
<b>Provisional value</b>	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at <a href="http://www.nathers.gov.au">www.nathers.gov.au</a>
<b>Recommended capacity</b>	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
<b>Reflective wrap</b> (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
<b>Roof window</b>	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
<b>Shading features</b>	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
<b>Skylight</b> (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
<b>Solar heat gain coefficient (SHGC)</b>	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
<b>STCs</b>	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulator (CER)
<b>Thermal breaks</b>	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick or continuous thermal breaks such as polystyrene insulation sheathing or plastic strips
<b>U-value</b>	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
<b>Unconditioned</b>	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions.
<b>Vertical shading features</b>	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
<b>Window shading device</b>	device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)

\* Refer to glossary.