

Nationwide House Energy Rating Scheme[®]

NatHERS[®] Certificate No. 0011809134

Generated on 26 Mar 2025 using BERS Pro v5.2.4 (3.23)

Property

Address 9 Surfview Avenue,
Black Head , NSW , 2430

Lot/DP Lot 5 DP 213365

NCC class* 1a

Floor/all Floors G of 2 floors

Type New Home

Plans

Main plan D5377 RevG 21/03/2025

Prepared by Collins W Collins Pty Ltd

Construction and environment

Assessed floor area [m2]*	Exposure type
Conditioned* 253.9	Suburban
Unconditioned* 21.7	
Total 319.3	NatHERS climate zone
Garage 43.7	15 Williamtown



Accredited assessor

Name Tamika Collins

Business name Collins W Collins Pty Ltd

Email energy@collinswcollins.com.au

Phone 0265834411

Accreditation No. 10058

Assessor Accrediting Organisation

HERA

Declaration of interest Declared, refer to "Additional Notes" on page 2

NCC Requirements

NCC provisions Volume Two

State/Territory variation Yes

National Construction Code (NCC) requirements

The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J3D3 and J3D15 of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at www.abcb.gov.au.

Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

Thermal performance Star rating



**NATIONWIDE
HOUSE**
ENERGY RATING SCHEME[®]

50.9 MJ/m²

Predicted annual energy load for heating and cooling based on standard occupancy assumptions.

For more information on your dwelling's rating see:
www.nathers.gov.au

Thermal performance [MJ/m²]

Limits taken from ABCB Standard 2022

	Heating	Cooling
Modelled	25.7	25.1
Load limits	N/A	N/A

Features determining load limits

Floor Type (lowest conditioned area)	CSOG
NCC climate zone 1 or 2	No
Outdoor living area	No
Outdoor living area ceiling fan	No

Whole of Home performance rating

No Whole of Home performance rating generated for this certificate.

Verification

To verify this certificate, scan the QR code or visit hstar.com.au/QR/Generate?p=0HVFQtnjw. When using either link, ensure you are visiting hstar.com.au





About the ratings

Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

Heating & Cooling Load Limits

Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the *ABCB Standard 2022: NatHERS heating and cooling load limits* for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

Setting Options:

Floor Type:

- CSOG – Concrete Slab on Ground
- SF – Suspended Floor (or a mixture of CSOG and SF)
- NA – Not Applicable

NCC Climate Zone 1 or 2:

- Yes
- No
- NA – Not Applicable

Outdoor Living Area:

- Yes
- No
- NA – Not Applicable

Outdoor Living Area Ceiling Fan:

- Yes
- No
- NA – Not Applicable

Predicted Whole of Home annual impact by appliance

Energy use

No Whole of Home performance assessment conducted for this certificate

Greenhouse gas emissions

No Whole of Home performance assessment conducted for this certificate

Cost

No Whole of Home performance assessment conducted for this certificate



Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

* Refer to glossary.

Certificate check

The checklist covers important items impacting the dwelling's ratings. It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and by whom each item should be checked. It is not mandatory to complete this checklist.

	Approval Stage		Construction Stage		Occupancy/Other
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	
Genuine certificate check					
Does this Certificate match the one available at the web address or QR code verification link on the front page?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Thermal performance check					
Windows and glazed doors					
Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the installed windows meet the substitution tolerances (AFRC* based SHGC* and U-values*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
External walls					
Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the External wall type table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Floor					
Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Ceiling penetrations*					
Does the 'quantity' and 'type' of ceiling penetrations* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Ceiling					
Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Roof					
Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Apartment entrance doors (NCC Class 2 assessments only)					
Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
Exposure*					
Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>
Heating and cooling load limits*					
Do the load limits settings (shown on page 1) match what is shown	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

* Refer to glossary.



Certificate check

Continued

	Approval Stage		Construction Stage		Occupancy/Other
	Assessor checked	Consent Authority/ Surveyor checked	Builder checked	Consent Authority Surveyor checked	

Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?

	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--------------------------	--------------------------	--------------------------	--------------------------

Insulation installation method

Has the insulation been installed according to the NCC requirements?

	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--------------------------	--------------------------	--------------------------	--------------------------

Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?

	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--------------------------	--------------------------	--------------------------	--------------------------

Whole of Home performance check (not applicable if a Whole of Home performance assessment is not conducted)

Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the Appliance schedule on this Certificate?

	<input type="checkbox"/>				
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or installed, match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

	<input type="checkbox"/>				
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

	<input type="checkbox"/>				
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?

	<input type="checkbox"/>				
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?

	<input type="checkbox"/>				
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?

	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--------------------------	--------------------------	--------------------------	--------------------------

Does the hot water system meet the additional requirements specified in the NCC?

	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--	--------------------------	--------------------------	--------------------------	--------------------------

Provisional values* check

Have provisional values* been used in the assessment and, if so, are they noted in 'Additional notes' table below?

	<input type="checkbox"/>	<input type="checkbox"/>		
--	--------------------------	--------------------------	--	--

Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.

Additional notes

Assessor is an employee of the Building Design Company



Room schedule

Room	Zone Type	Area [m ²]
Garage 1	Garage	43.71
Entry	Daytime	11.62
Hall	Daytime	5.38
Bedroom 2	Bedroom	17.43
Laundry	Unconditioned	11.83
Rumpus	Living	23.7
Hall 2	Daytime	7.68
Bedroom 3	Bedroom	12.98
Bedroom 4	Bedroom	13.06
Bath	Unconditioned	5.15
Office	Nighttime	5.92
Bedroom 1	Bedroom	19.19
WIR	Nighttime	6.8
Ensuite	Nighttime	9.08
Powder	Unconditioned	4.71
Bedroom 5	Bedroom	14.96
Hall UF	Living	4.29
Linen	Daytime	4.25
Pantry	Daytime	5.24
Kitchen/Living	Kitchen/Living	97.4

Window and glazed door type and performance

Default windows*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
ALM-002-01 A	Aluminium B SG Clear	6.7	0.70	0.67	0.74
	Aluminium B DG Argon				
ALM-006-03 A	Fill High Solar Gain low-E	4.1	0.52	0.49	0.55

* Refer to glossary.



Custom windows*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
BRZ-003-001	Aluminium Louvre Window SG 6Clr	6.0	0.67	0.63	0.70

Window and glazed door schedule

Location	Window ID	Window no.	Height [mm]	Width [mm]	Window type	Opening %	Orientation	Window shading device*
Garage 1	ALM-002-01 A	W14	600	2410	Double Hung	45	S	No
Entry	ALM-006-03 A	W1	2400	600	Fixed	00	E	No
Entry	ALM-006-03 A	W2	2400	600	Fixed	00	E	No
Hall	ALM-006-03 A	W3	2400	600	Fixed	00	E	No
Bedroom 2	ALM-006-03 A	W5	1800	610	Double Hung	45	N	No
Bedroom 2	ALM-006-03 A	W4	2400	2100	Sliding	45	E	No
Laundry	ALM-002-01 A	W6	2350	820	Casement	90	N	No
Laundry	ALM-002-01 A	W7	900	610	Double Hung	45	N	No
Laundry	ALM-002-01 A	W8	600	2410	Sliding	45	W	No
Rumpus	ALM-006-03 A	W9	2400	2400	Sliding	66	N	No
Rumpus	ALM-006-03 A	W10	1200	1800	Double Hung	45	W	No
Bedroom 3	ALM-006-03 A	W11	1200	1800	Double Hung	45	W	No
Bedroom 4	ALM-006-03 A	W12	1200	1800	Double Hung	45	W	No
Bath	BRZ-003-001-001	W13	940	910	Louvre	45	S	No
Office	ALM-006-03 A	W15	1800	1200	Double Hung	37	E	No
Bedroom 1	ALM-006-03 A	W16	1800	1200	Double Hung	37	E	No
Bedroom 1	ALM-006-03 A	W17	2100	1800	Sliding	45	E	No
Bedroom 1	ALM-006-03 A	W18	400	1800	Fixed	00	E	No
Ensuite	BRZ-003-001-001	W30	940	1200	Louvre	90	S	No
Powder	BRZ-003-001-001	W29	1780	610	Louvre	90	S	No
Bedroom 5	ALM-006-03 A	W28	1200	1800	Double Hung	45	W	No
Pantry	ALM-006-03 A	W27	1200	610	Double Hung	45	W	No
Kitchen/Living	ALM-006-03 A	W23	1800	1200	Double Hung	37	N	No
Kitchen/Living	ALM-006-03 A	W33	1800	1800	Double Hung	33	N	No
Kitchen/Living	ALM-006-03 A	W39	2100	2700	Sliding	66	E	No

* Refer to glossary.



Location	Window ID	Window no.	Height [mm]	Width [mm]	Window type	Opening %	Orientation	Window shading device*
Kitchen/Living	ALM-006-03 A	W40	400	2700	Fixed	00	E	No
Kitchen/Living	ALM-006-03 A	W37	2100	2700	Sliding	66	E	No
Kitchen/Living	ALM-006-03 A	W38	400	2700	Fixed	00	E	No
Kitchen/Living	ALM-006-03 A	W34	1200	1800	Double Hung	45	W	No
Kitchen/Living	ALM-006-03 A	W41	1800	1800	Double Hung	33	W	No

Roof window* type and performance value

Default roof windows*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

Custom roof windows*

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
VEL-010-01 W	VELUX VS - Ventilating Skylight DG 3mm LoE 366 / 8.5mm Argon Gap / 5.36mm Clear La	2.5	0.21	0.20	0.22
VEL-011-01 W	VELUX FS - Fixed Skylight DG 3mm LoE 366 / 8.5mm Argon Gap / 5.36mm Clear La	2.6	0.24	0.23	0.25

Roof window* schedule

Location	Window ID	Window no.	Opening %	Height [mm]	Width [mm]	Orientation	Outdoor shade	Indoor shade
WIR	VEL-011-01 W	S3	90	1140	700	S	Yes	Yes
Ensuite	VEL-010-01 W	S4	90	1180	1140	S	Yes	No
Kitchen/Living	VEL-010-01 W	S1	90	700	1140	W	Yes	Yes
Kitchen/Living	VEL-010-01 W	S2	90	700	1140	W	Yes	Yes

Skylight* type and performance

Skylight ID	Skylight description	Skylight shaft reflectance
No Data Available		

Skylight* schedule

Location	Skylight ID	Skylight No.	Skylight shaft length [mm]	Area [m ²]	Orientation	Outdoor shade	Diffuser
No Data Available							

External door schedule

Location	Height [mm]	Width [mm]	Opening %	Orientation
Garage 1	2400	5000	90	E
Garage 1	2040	820	90	S
Entry	2040	1200	90	E

External wall type

Wall ID	Wall type	Solar absorptance	Wall shade [colour]	Bulk insulation [R-value]	Reflective wall wrap*
EW-1	Reverse Timber Stud Frame Brick Veneer	0.50		Bulk Insulation R2.7	No
EW-2	Fibro Timber Stud Frame Panel Direct Fix	0.50		Bulk Insulation R2.7	No
EW-3	Fibro Timber Stud Frame Panel Direct Fix	0.50		Bulk Insulation R5.4	No

External wall schedule

Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
Garage 1	EW-1	2740	2200	N	8900	No
Garage 1	EW-1	2740	6200	E	1000	No
Garage 1	EW-1	2740	6295	S	600	No
Entry	EW-1	2740	3340	E	5100	Yes
Hall	EW-1	2740	1290	E	5100	Yes
Bedroom 2	EW-1	2740	4195	N	0	No
Bedroom 2	EW-1	2740	4250	E	2700	No
Bedroom 2	EW-1	2740	2400	S	10850	No
Laundry	EW-1	2740	2895	N	0	No
Laundry	EW-1	2740	4245	W	7800	No
Rumpus	EW-1	2740	5945	N	4250	No
Rumpus	EW-1	2740	4095	W	600	No

Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature [yes/no]
Bedroom 3	EW-1	2740	3390	W	600	No
Bedroom 4	EW-1	2740	4045	S	0	No
Bedroom 4	EW-1	2740	3345	W	600	No
Bath	EW-1	2740	2490	S	600	No
Office	EW-1	3040	2195	E	600	No
Office	EW-1	3040	2845	S	700	No
Bedroom 1	EW-1	3040	2200	N	9500	No
Bedroom 1	EW-1	3040	3995	E	600	No
Ensuite	EW-2	3040	600	E	3450	No
Ensuite	EW-2	3040	3445	S	100	No
Powder	EW-2	3040	1845	S	100	No
Powder	EW-2	3040	600	W	5300	No
Bedroom 5	EW-1	3040	4695	S	700	No
Bedroom 5	EW-1	3040	3295	W	600	No
Pantry	EW-1	3040	2240	W	600	No
Kitchen/Living	EW-3	3040	6000	N	600	No
Kitchen/Living	EW-1	3040	4700	N	600	No
Kitchen/Living	EW-3	3040	8895	E	5600	No
Kitchen/Living	EW-1	3040	5245	W	575	No
Kitchen/Living	EW-3	3040	4300	W	550	No

Internal wall type

Wall ID	Wall type	Area [m ²]	Bulk insulation
IW-001	Timber Stud Frame, Direct Fix Plasterboard	266.11	Bulk Insulation, No Air Gap R2.7

Floor type

Location	Construction	Area [m ²]	Sub-floor ventilation	Added insulation [R-value]	Covering
Garage 1	Concrete Slab on Ground 150mm	43.66	None	No Insulation	Bare
Entry	Waffle pod slab 300 mm 110mm	11.62	None	Waffle Pod 300mm	Cork Tiles or Parquetry 8mm



Location	Construction	Area [m ²]	Sub-floor ventilation	Added insulation [R-value]	Covering
Hall	Waffle pod slab 300 mm 110mm	5.38	None	Waffle Pod 300mm	Cork Tiles or Parquetry 8mm
Bedroom 2	Waffle pod slab 300 mm 110mm	17.43	None	Waffle Pod 300mm	Cork Tiles or Parquetry 8mm
Laundry	Waffle pod slab 300 mm 110mm	11.83	None	Waffle Pod 300mm	Ceramic Tiles 8mm
Rumpus	Waffle pod slab 300 mm 110mm	23.70	None	Waffle Pod 300mm	Cork Tiles or Parquetry 8mm
Hall 2	Waffle pod slab 300 mm 110mm	7.68	None	Waffle Pod 300mm	Cork Tiles or Parquetry 8mm
Bedroom 3	Waffle pod slab 300 mm 110mm	12.98	None	Waffle Pod 300mm	Cork Tiles or Parquetry 8mm
Bedroom 4	Waffle pod slab 300 mm 110mm	13.06	None	Waffle Pod 300mm	Cork Tiles or Parquetry 8mm
Bath	Waffle pod slab 300 mm 110mm	5.15	None	Waffle Pod 300mm	Ceramic Tiles 8mm
Office / Garage 1	Timber Framed Timber Above Plasterboard 19mm	5.92		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Bedroom 1 / Garage 1	Timber Framed Timber Above Plasterboard 19mm	19.19		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
WIR / Garage 1	Timber Framed Timber Above Plasterboard 19mm	6.77		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Ensuite / Garage 1	Timber Framed Timber Above Plasterboard 19mm	7.01		Bulk Insulation R4	Ceramic Tiles 8mm
Ensuite	Suspended Floor Timber Frame 19mm	1.50	Totally Open	Bulk Insulation, Gap to Floor R4	Ceramic Tiles 8mm
Powder / Bath	Timber Framed Timber Above Plasterboard 19mm	3.60		Bulk Insulation R4	Ceramic Tiles 8mm
Powder	Suspended Floor Timber Frame 19mm	0.65	Totally Open	Bulk Insulation, Gap to Floor R4	Ceramic Tiles 8mm
Bedroom 5 / Hall 2	Timber Framed Timber Above Plasterboard 19mm	0.13		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Bedroom 5 / Bedroom 4	Timber Framed Timber Above Plasterboard 19mm	12.81		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Bedroom 5 / Bath	Timber Framed Timber Above Plasterboard 19mm	0.91		Bulk Insulation R4	Cork Tiles or Parquetry 8mm



Location	Construction	Area [m ²]	Sub-floor ventilation	Added insulation [R-value]	Covering
Hall UF / Hall 2	Timber Framed Timber Above Plasterboard 19mm	4.22		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Linen / Hall 2	Timber Framed Timber Above Plasterboard 19mm	0.87		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Linen / Bedroom 3	Timber Framed Timber Above Plasterboard 19mm	2.71		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Pantry / Bedroom 3	Timber Framed Timber Above Plasterboard 19mm	5.11		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Kitchen/Living / Garage 1	Timber Framed Timber Above Plasterboard 19mm	0.00		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Kitchen/Living / Entry	Timber Framed Timber Above Plasterboard 19mm	6.59		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Kitchen/Living / Hall	Timber Framed Timber Above Plasterboard 19mm	0.20		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Kitchen/Living / Bedroom 2	Timber Framed Timber Above Plasterboard 19mm	1.74		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Kitchen/Living / Laundry	Timber Framed Timber Above Plasterboard 19mm	6.42		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Kitchen/Living / Rumpus	Timber Framed Timber Above Plasterboard 19mm	18.49		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Kitchen/Living / Hall 2	Timber Framed Timber Above Plasterboard 19mm	0.00		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Kitchen/Living / Bedroom 3	Timber Framed Timber Above Plasterboard 19mm	0.00		Bulk Insulation R4	Cork Tiles or Parquetry 8mm
Kitchen/Living	Suspended Floor Timber Frame 19mm	24.85	Totally Open	Bulk Insulation, Gap to Floor R4	Cork Tiles or Parquetry 8mm

Ceiling type

Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap* [yes/no]
Garage 1	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	
Entry	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	



Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap* [yes/no]
Hall	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	
Bedroom 2	Plasterboard on Timber	Bulk Insulation R5	
Bedroom 2	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	
Laundry	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	
Rumpus	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	
Hall 2	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	
Bedroom 3	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	
Bedroom 4	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	
Bath	Timber Framed Timber Above Plasterboard	Bulk Insulation R4	
Office	Plasterboard on Timber	Bulk Insulation R5	
Bedroom 1	Plasterboard on Timber	Bulk Insulation R5	
WIR	Plasterboard on Timber	Bulk Insulation R5	
Ensuite	Plasterboard on Timber	Bulk Insulation R5	
Powder	Plasterboard on Timber	Bulk Insulation R5	
Bedroom 5	Plasterboard on Timber	Bulk Insulation R5	
Hall UF	Plasterboard on Timber	Bulk Insulation R5	
Linen	Plasterboard on Timber	Bulk Insulation R5	
Pantry	Plasterboard on Timber	Bulk Insulation R5	
Kitchen/Living	Plasterboard on Timber	Bulk Insulation R5	

Ceiling penetrations*

Location	Quantity	Type	Diameter [mm]	Sealed/unsealed
Garage 1	9	Downlights - LED	150	Sealed
Entry	3	Downlights - LED	150	Sealed
Hall	2	Downlights - LED	150	Sealed
Bedroom 2	4	Downlights - LED	150	Sealed
Laundry	3	Downlights - LED	150	Sealed
Laundry	1	Exhaust Fans	300	Sealed
Rumpus	5	Downlights - LED	150	Sealed
Hall 2	2	Downlights - LED	150	Sealed
Bedroom 3	4	Downlights - LED	150	Sealed
Bedroom 4	4	Downlights - LED	150	Sealed

* Refer to glossary.



Location	Quantity	Type	Diameter [mm]	Sealed/unsealed
Bath	2	Downlights - LED	150	Sealed
Bath	1	Exhaust Fans	300	Sealed
Office	1	Downlights - LED	150	Sealed
Bedroom 1	4	Downlights - LED	150	Sealed
WIR	2	Downlights - LED	150	Sealed
Ensuite	2	Downlights - LED	150	Sealed
Ensuite	1	Exhaust Fans	300	Sealed
Bedroom 5	4	Downlights - LED	150	Sealed
Linen	1	Downlights - LED	150	Sealed
Pantry	1	Downlights - LED	150	Sealed
Kitchen/Living	20	Downlights - LED	150	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans

Location	Quantity	Diameter [mm]
Bedroom 2	1	1200
Rumpus	1	1200
Bedroom 3	1	1200
Bedroom 4	1	1200
Bedroom 1	1	1200
Bedroom 5	1	1200
Kitchen/Living	2	1400

Roof type

Construction	Added insulation [R-value]	Solar absorptance	Roof shade [colour]
Corrugated Iron Timber Frame	Bulk, Reflective Side Down, No Air Gap Above R1.8	0.50	Medium

Thermal bridging schedule for steel frame elements

Building element	Steel section dimensions [height x width, mm]	Frame spacing [mm]	Steel thickness [BMT,mm]	Thermal break [R-value]
No Data Available				

Appliance schedule



(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

Note: A flat assumption of 5W/m² is used for lighting, therefore lighting is not included in the appliance schedule.

Cooling system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				

Heating system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available				

Hot water system

Appliance/ system type	Fuel type	Hot Water CER Zone	Minimum efficiency /STC	Zone 3 STC	Zone 3 Substitution tolerance ranges		Assessed daily load [litres]
					lower limit	upper limit	
No Data Available							

Pool/spa equipment

Appliance/ system type	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Data Available			

Onsite Renewable Energy Schedule

System Type	Orientation	System Size Or Generation Capacity
No Data Available		

Battery Schedule

System Type	Size [Battery Storage Capacity]
No Data Available	



Explanatory notes

About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the home's energy value*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary.

Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and

are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

Glossary

AFRC	Australian Fenestration Rating Council
Annual energy load	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
Assessed floor area	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
Ceiling penetrations	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
COP	Coefficient of performance
Conditioned	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
Custom windows	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
Default windows	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
EER	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
Energy use	This is your home's rating without solar or batteries.
Energy value	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
Entrance door	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
Exposure	see exposure categories below.
Exposure category – exposed	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
Exposure category – open	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
Exposure category – protected	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
Exposure category – suburban	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
Horizontal shading feature	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
National Construction Code (NCC) Class	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at www.abcb.gov.au .
Net zero home	a home that achieves a net zero energy value*.
Opening percentage	the openability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
Provisional value	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at www.nathers.gov.au
Recommended capacity	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
Reflective wrap (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
Roof window	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
Shading features	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
Skylight (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
Solar heat gain coefficient (SHGC)	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
STCs	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulator (CER)
Thermal breaks	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick or continuous thermal breaks such as polystyrene insulation sheeting or plastic strips
U-value	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
Unconditioned	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions.
Vertical shading features	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
Window shading device	device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)

* Refer to glossary.