

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1333579S 05

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number 1333579S 03 lodged with the consent authority or certifier on 22 June 2023 with application PAN-326890.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Schedule 1 Clause 2A, 4A or 6A of the Environment Planning and Assessment Regulation 2000

Secretary

Date of issue: Friday, 21 March 2025

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary				
Project name	DW1_8 Hillview Ave, Bankstown_0	3_05		
Street address	8 HILLVIEW AVENUE BANKSTOWN 2200			
Local Government Area	Canterbury-Bankstown Council			
Plan type and plan number	Deposited Plan 30757			
Lot no.	16			
Section no.	-			
Project type	separate dwelling house			
No. of bedrooms	3			
Project score				
Water	✓ 40	Target 40		
Thermal Performance	✓ Pass	Target Pass		
Energy	✔ 50	Target 50		
Materials	✓ -1	Target n/a		

Name / Company Name: NEMCO DESIGN PTY. LTD.

ABN (if applicable):

Version: 3.0 / DARWINIA 03 01 0

Description of project

Project address	
Project name	DW1_8 Hillview Ave, Bankstown_03_05
Street address	8 HILLVIEW AVENUE BANKSTOWN 2200
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan 30757
Lot no.	16
Section no.	-
Project type	
Project type	separate dwelling house
No. of bedrooms	3
Site details	
Site area (m²)	511
Roof area (m²)	172
Conditioned floor area (m²)	187.0
Unconditioned floor area (m²)	15.0
Total area of garden and lawn (m²)	270
Roof area of the existing dwelling (m²)	0

Assessor details and therm	al loads	
NatHERS assessor number	n/a	
NatHERS certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/ m².year)	n/a	
Area adjusted heating load (MJ/ m².year)	n/a	
Ceiling fan in at least one bedroom	n/a	
Ceiling fan in at least one living room or other conditioned area	n/a	
Project score		
Water	✓ 40	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	✓ 50	Target 50

BASIX

Target n/a

Materials

Version: 3.0 / DARWINIA_03_01_0

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 40 square metres of the site.	~	~	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2400 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 172.1 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			Ì
all toilets in the development		-	-
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	-

Version: 3.0 / DARWINIA_03_01_0

Department of Planning, Housing and Infrastructure

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Do-it-yourself Method			
General features			
The dwelling must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	V	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			•
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground, 105.6 square metres	nil	
floor - above habitable rooms or mezzanine, 96.4 square metres, framed	nil	
floor - suspended floor above garage, framed	nil	
external wall - brick veneer	2.86 (or 3.40 including construction)	
external wall - other/undecided	3.40 (including construction)	
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 4.5 (up), roof: foil/sarking	framed; medium (solar absorptance 0.475-0.70)

Note • Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.	
Note	In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Department of Planning, Housing and Infrastructure

BASIX

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~
• For the following glass and frame types, the certifier check can be performed by visual inspection.			-
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			
Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column.	~	~	~

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North-East facing					
W1.13	970.00	2170.00	aluminium, single, clear	none	>4 m high, 5-8 m away
W1.12	970.00	2170.00	aluminium, single, clear	none	>4 m high, 5-8 m away
W1.11	970.00	2410.00	aluminium, single, clear	none	>4 m high, <2 m away
W1.3	970.00	2410.00	aluminium, single, clear	none	>4 m high, <2 m away
W1.4	600.00	3000.00	aluminium, single, clear	none	>4 m high, 5-8 m away
South-East facing					
W1.5	2400.00	1370.00	aluminium, single, clear	none	>4 m high, 5-8 m away

Department of Planning, Housing and Infrastructure

page 5/9

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
SD1.1	2400.00	3500.00	aluminium, single, clear	verandah 3600 mm, 2850 mm above base of window or glazed door	>4 m high, 5-8 m away
W1.14	600.00	2650.00	aluminium, single, clear	none	>4 m high, 5-8 m away
South-West facing					
W1.18	600.00	1570.00	aluminium, single, clear	none	>4 m high, <2 m away
W1.17	970.00	1570.00	aluminium, single, clear	none	>4 m high, <2 m away
W1.6	2100.00	1370.00	aluminium, single, clear	none	>4 m high, <2 m away
W1.16	600.00	2170.00	aluminium, single, clear	none	>4 m high, <2 m away
W1.15	600.00	1570.00	aluminium, single, clear	none	>4 m high, <2 m away
W1.7	2100.00	1370.00	aluminium, single, clear	none	>4 m high, <2 m away
W1.8	2100.00	730.00	aluminium, single, clear	none	>4 m high, <2 m away
W1.9	600.00	970.00	aluminium, single, clear	none	>4 m high, <2 m away
North-West facing					
W1.10	2100.00	1200.00	aluminium, single, clear	solid overhang 500 mm, 300 mm above head of window or glazed door	>4 m high, 2-5 m away
W1.1	2400.00	2300.00	aluminium, single, clear	solid overhang 300 mm, 3150 mm above head of window or glazed door	>4 m high, 2-5 m away
W1.2	5550.00	850.00	aluminium, single, clear	none	>4 m high, 2-5 m away
SD1.2	2340.00	2410.00	aluminium, single, clear	solid overhang 1570 mm, 270 mm above head of window or glazed door	>4 m high, 2-5 m away

BASIX

Certificate No.: 1333579S_05

Show on DA plans	Show on CC/CDC plans & specs	Certifier check
~	~	~
	~	~
	~	~
	~	~
	~	~
	~	~
	~	~
		1
	~	_
	~	-

Department of Planning, Housing and Infrastructure

BASIX

Certificate No.: 1333579S_05

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
at least 3 of the bedrooms / study; dedicated		~	_
at least 2 of the living / dining rooms; dedicated		~	-
the kitchen; dedicated		~	V
all bathrooms/toilets; dedicated		V	-
• the laundry; dedicated		✓	
all hallways; dedicated		V	-
Natural lighting		,	
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
The applicant must install a window and/or skylight in 3 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	~
Other			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		-	

BASIX

Legend

BASIX

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.

Department of Planning, Housing and www.basix.nsw.gov.au Version: 3.0 / DARWINIA_03_01_0 Certificate No.: 1333579S_05 Friday, 21 March 2025 page 9/9 Infrastructure