

LEGEND	
NEIGHBOURING STRUCTURES	7///
EXISTING	
PROPOSED WORKS	
BOUNDARY	

Date

01/12/2024

17/02/2024 27/03/2024

Description

Client name DENNIS LAM & STELLA XU Project name Ź KIORA STREET

Project address 7 KIORA STREET PANANIA NSW 2213



87b Talara Road Gymea NSW 2227 ABN 88640425467 gilarchitects.com 0426656649 fgil@gilarchitects.com Nominated Registered Architect Filiberto Gil Registered Architect NSWARB 10420 Registered Building Design Practioner DEP0003634 Registered Principal Design Practioner PDP0001219

DEVELOPMENT **APPLICATION**

NOT FOR CONSTRUCTION

Sheet name

ELEVATIONS	& SECTION	IS

Sheet number	Revision
A120	С

AREAS DESCRIPTION **EXISTING** PROPOSED MAIN DWELLING DETACHED GARAGE 48m² SECONDARY DWELLING 48m² TOTAL 151m² 151m²

GENERAL NOTES

FINISHES TO REMAIN

ALL WORK MUST BE CARRIED OUT IN ACCORDANCE WITH AUSTRALIAN STANDARDS (AS), NATIONAL CONSTRUCTION CODE (NCC), BUILDING CODE OF AUSTRALIA (BCA), CONDITIONS OF CONSENT, PRINCIPAL CERTIFYING AUTHORITY (PCA), AND ALL OTHER RELEVANT AUTHORITIES.

_REFER TO SURVEY DRAWING BY LAND SURVEYOR FOR EXISTING REDUCED LEVELS (RL) STRUCTURES AND SITE CONDITIONS. NO WORKS TO EXISTING DWELLING

EXTERNAL ENVELOPE. EXISTING DWELLING INTERNAL WORKS ONLY. EXISTING DETACHED GARAGE AND WORKSHOP BUILDING CONVERSION INTO

SECONDARY DWELLING WORKS ONLY TO MEET NATIONAL CONSTRUCTION CODE (NCC). MINOR SITE EXCAVATION FOR THE CONNECTION OF NEW SERVICES TO EXISTING SERVICES ON SITE.

REFER TO BASIX FOR WATER, BUILDING AND ENERGY REQUIREMENTS.

_ALL TREES TO REMAIN

ANY CHANGES TO DESIGN AND DOCUMENTATION FROM APPROVED DA ARE SUBJECT TO APPROVAL BY APPOINTED ARCHITECT, COUNCIL AND APPOINTED PCA.

CONSTRUCTION MANAGEMENT NOTES

WASTE MATERIALS ARE TO BE STOCKPILED AND LOADED INTO BINS. SPECIFICATION

FINISHES TO REMAIN

ALL PROTECTION WORKS TO BE CARRIED OUT IN ACCORDANCE WITH COUNCIL SITE MANAGEMENT DCP. ALL CONSTRUCTION AND DEMOLITION WORKS TO COMPLY WITH THE PROVISIONS OF THE BUILDING CODE OF AUSTRALIA.

MEASUREMENTS TO BE CHECKED ON SITE AND ADJUSTED WHERE NECESSARY TO SUIT EXISTING CONDITIONS. LEVELS SHOWN ARE OBTAINED FROM INITIAL SITE WORKS SURVEY BY LAND SURVEYOR.

EXISTING METAL ROOF AND CLADDING EXISTING FASCIA & TRIMS FINISHES EXISTING WINDOW AWNING AND TRIM

TO REMAIN

ABBREVIATIONS EXISTING REDUCED LEVEL REDUCED LEVEL FINISHED FLOOR LEVEL

INCLUDED LEVEL

IL FINISHED FLOOR LEVEL

D ROLLER DOOR

D SLIDING DOOR

P DOWNPIPE

EG EAVES GUTTER

SWPD STORMWATER PIT DRAIN

RWT RAIN WATER TANK

W WINDOW

F FIXED

TOR TOP OF ROOF

TOP TOP OF PARAPET

TOB TOP OF BALUSTRADE

TOF TOP OF BALUSTRADE

TOF TOP OF WALL

BOW BOTTOM OF WALL

GL GLAZED PARTITION

CON CONCRETE

WINDOWS AND DOORS NOTES

_WINDOWS, GLAZED DOORS (GLASS & FRAME) IN ACCORDANCE WITH ARCHITECTURAL SCHEDULE & FINISHES

WINDOWS AND DOORS SIZE INDICATIVE ONLY. _ALL DIMENSIONS TO BE MEASURE ON SITE (M.O.S.)

_REFER TO BASIX FOR ENERGY REQUIREMENTS.

WINDOWS AND DOORS SCHEDULE

ITEM	HEIGHT	WIDTH	FINISH	FRAME	ORIENTATION
W1	1000	2100	GL1	AL1	NORTH
W2	400	1300	GL2	AL2	NORTH
SD1	2100	2400	GL1	AL1	WEST
SD2	2100	1880	GL1	AL1	NORTH

FINISHES AL1 ALUMINIUM FRAMING FINISH: MATCH EXISTING TRIM TM1 TIMBER FRAMING FINISH: MATCH EXISTING TRIM

PA1 EXISTING CLADDING & DOORS FINISH: EXISTING PA2 EXISTING FASCIAS & TRIMS FINISH: EXISTING

PA3 EXISTING GUTTERS, DOWNPIPES, FINISH: EXISTING PA4 EXISTING ROOF SOFFIT

FINISH: EXISTING RF1 NEW METAL ROOF SHEETING FINISH: MATCH EXISTING GL1 GLASS - CLEAR FRAME: AL1

GL2 GLASS - FROSTED FRAME: AL1

BASIX REQUIREMENTS

FIXTURES AND SYSTEMS
SHOWERHEADS: MIN 4 STAR RATING WITH FLOW
RATE GREATER THAN 4.5 BUT LESS THAN OR EQUAL TO 6
LITRES/MIN PLUS SPRAY FORCE AND/OR COVERAGE TESTS.
TOILETS: MIN 4 STAR RATING FLUSHING SYSTEM FOR EACH.
TAPS: MINIMUM 6 STAR RATING.
BASIN TAPS: MINIMUM 6 STAR RATING.
3000L RAINWATER TANK

CONSTRUCTION
SLAB ON GRADE
EXTERNAL WALL: R3.0 (R3.5 INCLUDING CONSTRUCTION)
CEILING/ROOF: CEILING R4.0 (UP) ROOF (NONE)
ROOF SPACE VENTILATION: EXISTING WHIRLYBIRD
ROOF COLOUR: MEDIUM (SOLAR ABSORPTANCE <0.7).

HOT WATER SYSTEM
MIN 5 STAR ELECTRIC INSTANTANEOUS. COOLING & HEATING SYSTEMS
MIN ENERGY RATING EER 3.0 - 3.5

VENTILATION SYSTEMS
MIN EXHAUST SYSTEMS TO BE INSTALLED:

FAN SYSTEMS
ONE CEILING FAN TO BE INSTALL AT THE BEDROOM.
A MIN OF ONE CEILING FAN TO BE INSTALL AT A DAYTIME
HABITABLE SPACE IN ACCORDANCE WITH THE ABCB HOUSING
PROVISIONS (PART 13.5.2) OF THE NATIONAL CONSTRUCTION OTHER MUST INTALL A ELECTRIC COOKTOP AND ELECTRIC OVEN IN THE

KITCHEN.
MUST INSTALL A MIN OF ONE 5KW PV SOLAR SYSTEM ARTIFICIAL LIGHTING
MINIMUM OF 80% OF NEW LIGHT FIXTURES TO BE
FLUOROSCENT, COMPACT FLUORESCENT, OR LIGHT EMITTING
DIODE (LED) LAMPS.

NATURAL LIGHT
A WINDOW/DOOR TO BE INSTALLED IN THE KITCHEN,

GLAZED WINDOWS, DOORS REQUIREMENTS
- WINDOWS & GLAZED DOORS + SHADING
DEVICES AT CONDITIONED SPACES IN ACCORDANCE WITH
ARCHITECTURAL SCHEDULE AND SPECIFICATION LISTED IN THE
BASIX REPORT CERTIFICATE.