

BASIX[®]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1281240S_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number 1281240S lodged with the consent authority or certifier on 22 August 2022 with application DA2022/1391.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Schedule 1 Clause 2A, 4A or 6A of the Environment Planning and Assessment Regulation 2000

Secretary

Date of issue: Friday, 14 March 2025

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary

Project name	2020-57_02
Street address	52 KINKA ROAD SEAL ROCKS 2423
Local Government Area	Mid-Coast Council
Plan type and plan number	Deposited Plan 111267
Lot no.	1
Section no.	-
Project type	separate dwelling house
No. of bedrooms	4

Project score

Water	✓ 78	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	✓ 66	Target 50
Materials	✓ -1	Target n/a

Certificate Prepared by

Name / Company Name: Margaret Skilbeck

ABN (if applicable):

Description of project

Project address

Project name	2020-57_02
Street address	52 KINKA ROAD SEAL ROCKS 2423
Local Government Area	Mid-Coast Council
Plan type and plan number	Deposited Plan 111267
Lot no.	1
Section no.	-

Project type

Project type	separate dwelling house
No. of bedrooms	4

Site details

Site area (m²)	589
Roof area (m²)	240
Conditioned floor area (m²)	174.87
Unconditioned floor area (m²)	16.34
Total area of garden and lawn (m²)	271
Roof area of the existing dwelling (m²)	0

Assessor details and thermal loads

NatHERS assessor number	n/a
NatHERS certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m².year)	n/a
Area adjusted heating load (MJ/m².year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a

Project score

Water	✓ 78	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	✓ 66	Target 50
Materials	✓ -1	Target n/a

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 222.6 square metres of the site.	✓	✓	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development.		✓	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 20000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 240 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> all toilets in the development the cold water tap that supplies each clothes washer in the development 		✓ ✓	✓ ✓

Water Commitments

Show on
DA plans

Show on CC/CDC
plans & specs

Certifier
check

- at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.)
- all hot water systems in the development
- all indoor cold water taps (not including taps that supply clothes washers) in the development



Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Do-it-yourself Method			
General features			
The dwelling must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground, 110.7 square metres	nil	
floor - suspended floor above open subfloor, 29 square metres, framed	0.8 (or 1.5 including construction) (down)	
floor - suspended floor above garage, framed	nil	
external wall - concrete block/plasterboard	1.88 (or 2.40 including construction)	
external wall - framed (weatherboard, fibre cement, metal clad)	2.00 (or 2.40 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 4.25 (up), roof: thermocellular reflective	unventilated; medium (solar absorptance 0.475-0.70)
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 4.04 (up), roof: thermocellular reflective	framed; medium (solar absorptance 0.475-0.70)
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 3.98 (up), roof: thermocellular reflective	framed; medium (solar absorptance 0.475-0.70)

Note	• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.





















Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
<p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <ul style="list-style-type: none"> For the following glass and frame types, the certifier check can be performed by visual inspection. <ul style="list-style-type: none"> Aluminium single clear Aluminium double (air) clear Timber/uPVC/fibreglass single clear Timber/uPVC/fibreglass double (air) clear For other glass or frame types, each window and glazed door must be accompanied with certification showing a U value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range of those listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. Frame and glass types shown in the table below are for reference only. 	✓	✓	✓ ✓
			✓

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
North facing					
W01	2400.00	6300.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	verandah 3600 mm, 3100 mm above base of window or glazed door	not overshadowed
W04	1650.00	3540.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 600 mm, 800 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W12	2400.00	5400.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 450 mm, 850 mm above head of window or glazed door	not overshadowed
East facing					
W02	2400.00	2200.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	verandah 6300 mm, 3100 mm above base of window or glazed door	not overshadowed
W03	1650.00	630.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	verandah 6300 mm, 3100 mm above base of window or glazed door	not overshadowed
W17	1200.00	1800.00	U-value: 5.6, SHGC: 0.369 - 0.451 (aluminium, single, Lo-Tsol Low-e)	none	not overshadowed
South facing					
W07	2400.00	2600.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 700 mm, 420 mm above head of window or glazed door	not overshadowed
W09	600.00	1200.00	U-value: 5.6, SHGC: 0.369 - 0.451 (aluminium, single, Lo-Tsol Low-e)	eave 600 mm, 280 mm above head of window or glazed door	not overshadowed
W10	1050.00	750.00	U-value: 5.6, SHGC: 0.369 - 0.451 (aluminium, single, Lo-Tsol Low-e)	eave 600 mm, 650 mm above head of window or glazed door	not overshadowed
W16	600.00	1200.00	U-value: 5.6, SHGC: 0.369 - 0.451 (aluminium, single, Lo-Tsol Low-e)	eave 350 mm, 450 mm above head of window or glazed door	not overshadowed
West facing					


Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W05	1650.00	630.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 450 mm, 800 mm above head of window or glazed door	not overshadowed
W06	1650.00	2200.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 450 mm, 800 mm above head of window or glazed door	not overshadowed
W08	1400.00	1800.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 600 mm, 400 mm above head of window or glazed door	not overshadowed
W13	1400.00	1100.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 600 mm, 900 mm above head of window or glazed door	not overshadowed
W14	1400.00	1800.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 600 mm, 900 mm above head of window or glazed door	not overshadowed
W15	1400.00	1800.00	U-value: 3.1, SHGC: 0.243 - 0.297 (aluminium: thermally broken, double (air), Lo-Tsol Low-e/clear)	eave 600 mm, 900 mm above head of window or glazed door	not overshadowed


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric heat pump.	✓	✓	✓
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 4.5 star (average zone)		✓	✓
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: ceiling fans; Energy rating: n/a		✓	✓
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 3 star (average zone)		✓	✓
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Laundry: natural ventilation only, or no laundry; Operation control: n/a		✓	✓
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
<ul style="list-style-type: none"> at least 4 of the bedrooms / study; dedicated 		✓	✓


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<ul style="list-style-type: none"> • at least 1 of the living / dining rooms; dedicated • the kitchen; dedicated • all bathrooms/toilets; dedicated • the laundry; dedicated • all hallways; dedicated 		    	    
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.			
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.			
Alternative energy			
The applicant must install a photovoltaic system with the capacity to generate at least 2 peak kilowatts of electricity as part of the development. The applicant must connect this system to the development's electrical system.			
Other			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.