

	K.S.W		
IRUE NORTH NORTH NORTH			
	KEYS:		
		WI	ND DIRECTIONS
			EES TO BE MOVED
AHD			IVATE URTYARDS
	NOISE	IMF	TENTIAL NOISE PACT TRAFFIC & IGHBOURING
	ACCESS	SIT	EACCESS
	$\mathbf{\hat{b}}$	VIE	WS
		NO	RTHERN SUNLIGHT
	NOTES		
	WILL BE MAI 2. REVEGETATIO	ntained in a On WORKS- H.	NT CONTROL STRUCTURES FUNCTIONAL CONDITION AY MULCHING MUST USE
	"DRYLAND" S 3. AREAS NOT	SEED MIXTURE	ED WEED FREE AND A IN ALL APPLICATIONS DING SHOULD BE
	4. REVEGETATIO		I CUT AND FILLS AS SOON
			TOPSOIL STOCKPILE Covered with Poythene Membrane.
			MATERIAL STORAGE AREA
			DELIVERY TRUCK PARKING
	12 cubic bi	n	WASTE BINS
	[]]]]]]]	/////	KERB TURF FILTER
			SEDIMENT FENCE

ΒY	DATE	
JB	JUNE 25	



GTITLE	DO NOT SCALE THE DRAWINGS, READ ALL DIMENSIONS SHOWN.	DRAWN	JB JUNE 25	ISSUE	AMENDMENT	BY	DATE
evations	ALL DIMENSIONS, NOTES ON ALL PLANS AND CONSENT DOCUMENTS MUST BE CHECKED AND VERIFIED BY THE CONTRACTOR PRIOR TO ANY COMMENCEMENT OF ANY BUILDING WORKS ON SITE, TO CLARIFY ANY DISCREPANCIES	_DATE CHECKED SCALE	JACK 1:100	Α	S4.55 SUBMISSION	ЈВ	JUNE 25
DETAILS	BETWEEN ALL PLAN DRAWINGS AND DOCUMENTATION RELEVANT TO THE PROPOSAL / SITE WORKS. GROUND LEVELS MAY VARY DUE TO SITE CONDITIONS. COPYRIGHT - THESE DRAWINGS REMAIN THE PROPERTY OF	JOB NUMBER	23286-01	-			
HENS	DVYNE DESIGN JT PTY LTD AND CAN NOT BE ALTERED OR REPRODUCED WITHOUT WRITTEN CONSENT.	NUMBER IN SET	A02 A	_			



1 Landscape Plan

BASIX CERTIFICATE

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check	Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures				Glazed windows, doors and skylights			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~	The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each glazed window and door.	>	~	~
The applicant must install a toilet flushing system with a minimum rating of 6 star in each toilet in the development.		~	~	The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	>	~
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		~		The following requirements must also be satisfied in relation to each window and glazed door:	~	>	•
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		~		The applicant must install windows and glazed doors in accordance with the height and width, frame and glazing types listed in the table.	~	>	•
Alternative water	1			• Each window and glazed door must have a U- value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC)		~	~
Rainwater tank				conditions.			<u> </u>
The applicant must install a rainwater tank of at least 1500 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~	Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 107 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~	The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	~	~	~
The applicant must connect the rainwater tank to:							
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	~	Energy Commitments		Show on CC/CDC plans & specs	Certifier check
		0.0000000000000000000000000000000000000		Hot water			
Thermal Performance and Materials commitments		Show on CC/CDC plans & specs	Certifier check	The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 5 stars.	~	~	~
Do-it-yourself Method			<u></u>	Cooling system	1	3	
General features				The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase			1
The dwelling must be a Class 1 dwelling according to the National Construction Code, and must not have more than 2 storeys.	~	~	~	airconditioning - non ducted; Energy rating: 5 star (average zone) The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase		~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~	airconditioning - non ducted; Energy rating: 5 star (average zone)		~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.				Heating system		1	
The dwelling must not contain third level habitable attic room.	~	~	~	The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - non ducted; Energy rating: 5 star (average zone)		v	~
	~	×	~	The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning - non ducted; Energy rating: 5 star (average zone)		~	~
Floor, walls and ceiling/roof	1	T	1	Ventilation			-
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	 Image: A set of the set of the	~	The applicant must install the following exhaust systems in the development:		T	
The applicant must adopt one of the options listed in the tables below to address thermal bridging in metal framed floor(s), walls and ceiling/roof of the dwelling.	~	~	~	At least 1 Bathroom: individual fan, open to façade; Operation control: manual switch on/off		~	~
The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the tables below.			~	Kitchen: individual fan, open to façade; Operation control: manual switch on/off		~	-
				Laundry: individual fan, open to façade; Operation control: manual switch on/off			
Thermal Performance and Materials commitments	Show on DA plans		Certifier check	Artificial lighting		•	
Ceiling fans				The applicant must ensure that a minimum of 80% of light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-			T
The applicant must install at least one ceiling fan in at least one daytime habitable space, such as living room.	~	~	~	diode (LED) lamps.		~	_
 The minimum number and diameter of ceiling fans in a daytime habitable space must be installed in accordance with the ABCB Housing Provisions (Part 13.5.2) of the National Construction Code. 	~	~	~	Natural lighting The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.		_	
	,						*
				Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifie check
				Other			
				The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
				The applicant must install a fixed outdoor clothes drying line as part of the development.			1



	JOB DESCRIPTION	
	Prop. SECONDARY DWELLING	LANDSCAPE/ SECTIO
	AT	CLIENT DET
Г	No 42 WOODBINE STREET, YAGOONA	JEREMY STEPHEN

	 	 7
\sim		





/ING TITLE	DO NOT SCALE THE DRAWINGS, READ ALL DIMENSIONS SHOWN.	DRAWN DATE	JB JUNE 25	ISSUE	AMENDMENT	BY DATE
section T DETAILS	ALL DIMENSIONS, NOTES ON ALL PLANS AND CONSENT DOCUMENTS MUST BE CHECKED AND VERIFIED BY THE CONTRACTOR PRIOR TO ANY COMMENCEMENT OF ANY BUILDING WORKS ON SITE, TO CLARIFY ANY DISCREPANCIES BETWEEN ALL PLAN DRAWINGS AND DOCUMENTATION RELEVANT TO THE PROPOSAL / SITE WORKS. GROUND LEVELS MAY VARY DUE TO SITE		JACK 1:100 23286-01	Α	S4.55 SUBMISSION	JB JUNE 25
EPHENS	CONDITIONS. COPYRIGHT - THESE DRAWINGS REMAIN THE PROPERTY OF DVYNE DESIGN JT PTY LTD AND CAN NOT BE ALTERED OR REPRODUCED WITHOUT WRITTEN CONSENT.		A03 A	-		





<u>LEGEND</u>

EXISTING TREES TO BE RETAINED

PROPOSED TREES (REFER TO PLANT SCHEDULE)

LARGE SHRUBS SCREEN PLANTING (VARIABLE HEIGHT 2.0M TO 3.0m)

FEATURE PLANTS (ARCHITECTURAL PLANTING TYPES TO COMPLIMENT VISUAL SCALE)

MASS PLANTED AREAS (MIXED PLANTING HEIGHTS FROM 500mm - 1m HEIGHT)

TURF AREAS (REFER TO TURFING DETAIL AND SPECIFICATION)

COLOURED CONCRETE PAVEMENT

(SELECTED FINISH AS SPECIFIED)

TILING (TILING TO ARCHITECTS SPECIFICATION OR CLIENT SELECTION.)

DECORATIVE GRAVEL (75mm DEPTH, 20mm GRADE NEPEAN RIVER GRAVEL OR AS SELECTED BY CLIENT.)

PROPERTY BOUNDARY LINE

TIMBER EDGING (100mm x 25mm H4 TREATED PINE TO ALL GARDEN BED AREAS ADJOINING TURF OR GRAVEL SURFACES)

MASONRY WALLS (CONSTRUCTION AND FINISH TO ARCHITECT AND/OR ENGINEER'S SPECIFICATION)

STORMWATER PITS (TO HYDRAULIC ENGINEERS SPECIFICATIONS)

STORMWATER PIPE (CONNECTING DOWN PIPE TO KERB INVERT - REFER TO HYDRAULIC ENGINEER'S DETAILS)