BASIX[™]Certificate

Building Sustainability Index www.planningportal.nsw.gov.au/development-and-assessment/basix

Single Dwelling

Certificate number: 1797748S_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.planningportal.nsw.gov.au/definitions

Secretary

Date of issue: Tuesday, 17 June 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



Project summary					
Project name	Chester Hill - Garage Co	Chester Hill - Garage Conversion_02			
Street address	8 MOUNTVIEW Avenue	CHESTER HILL 2162			
Local Government Area	Canterbury-Bankstown Co	ouncil			
Plan type and plan number	Deposited Plan DP29501				
Lot no.	47				
Section no.	-				
Project type	dwelling house (detached) - secondary dwelling			
No. of bedrooms	1				
Project score					
Water	40	Target 40			
Thermal Performance	V Pass	Target Pass			
Energy	68	Target 68			
Materials	13	Target n/a			

Certificate Prepared by

Name / Company Name: MANUEL THOMAS

ABN (if applicable):

Description of project

Project address

Project name	Chester Hill - Garage Conversion_02
Street address	8 MOUNTVIEW Avenue CHESTER HILL 2162
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan DP29501
Lot no.	47
Section no.	-
Project type	
Project type	dwelling house (detached) - secondary dwelling
No. of bedrooms	1
Site details	
Site area (m²)	803
Roof area (m ²)	56
Conditioned floor area (m ²)	34.1
Unconditioned floor area (m ²)	10.55
Total area of garden and lawn (m ²)	75
Roof area of the existing dwelling (m ²)	235
Number of bedrooms in the existing dwelling	8

Assessor details and thermal loads NatHERS assessor number n/a NatHERS certificate number n/a Climate zone n/a Area adjusted cooling load (MJ/ n/a m².year) Area adjusted heating load (MJ/ n/a m².year) **Project score** Water 40 Target 40 Thermal Performance 4 Pass Target Pass Energy V 68 Target 68 Materials 13 Target n/a

page 2/11

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 61 square metres of the site.	~	~	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 6 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 6 star in each bathroom in the development.		~	
Alternative water		•	
Hot water recirculation or diversion system			_
The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the development.		~	~

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Do-it-yourself Method	-	'	
General features			
The dwelling must be a Class 1 dwelling according to the National Construction Code, and must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof	-	·	-
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~
The applicant must adopt one of the options listed in the tables below to address thermal bridging in metal framed floor(s), walls and ceiling/roof of the dwelling.	~	~	~
The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the tables below.			~

Construction	Area - m²	Additional insulation required	Options to address thermal bridging	Other specifications
floor - concrete slab on ground, conventional slab.	51	nil;not specified	nil	
external wall: framed (fibre cement sheet or boards); frame: timber - untreated softwood.	all external walls	3.00 (or 3.50 including construction);fibreglass batts or roll + reflective foil in the cavity	nil	wall colour: Light (solar absorptance < 0.48)
internal wall: plasterboard; frame: timber - untreated softwood.	27	none	nil	

Department of Planning, Housing and BASIX Infrastructure

Constr	uction	Area - m²	Additional insulation required	Options to address thermal bridging	Other specifications		
ceiling and roof - raked ceiling / pitched or skillion roof, framed - metal roof, timber - untreated softwood.		56.31	ceiling: 5.7 (up), roof: foil/ sarking ;ceiling: fibreglass batts or roll; roof: foil/sarking.	nil	roof colour: medium (solar absorptance 0.48-0.59); 0.5 to $_{\leq}$ 1.0% of ceiling area uninsulated		
Note	Insulation specified in this	s Certificate must be installed	d in accordance with the ABCB Housing Provisio	ns (Part 13.2.2) of the National Con	struction Code.		
Note	• If the additional ceiling in	sulation listed in the table above is greater than R3.0, refer to the ABCB Housing Provisions (Part 13.2.3 (6)) of the National Construction Code.					

Note • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Note • Thermal breaks must be installed in metal framed walls and applicable roofs in accordance with the ABCB Housing Provisions of the National Construction Code.

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Ceiling fans			
The applicant must install at least one ceiling fan in at least one daytime habitable space, such as living room.	~	~	~
 The minimum number and diameter of ceiling fans in a daytime habitable space must be installed in accordance with the ABCB Housing Provisions (Part 13.5.2) of the National Construction Code. 	~	`	~

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Glazed windows, doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each glazed window and door.	~	~	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~
• The applicant must install windows and glazed doors in accordance with the height and width, frame and glazing types listed in the table.	~	~	~
• Each window and glazed door must have a U- value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.		~	~
• Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column.	~	~	~
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	~	~	~

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing	
North-East facing	North-East facing					
W01	1030.00	2410.00	aluminium, single glazed (U- value: Undecided, SHGC: Undecided)	eave 300 mm, 300 mm above head of window or glazed door	>4 m high, 5-8 m away	
W02	860.00	1210.00	aluminium, single glazed (U- value: Undecided, SHGC: Undecided)	eave 300 mm, 300 mm above head of window or glazed door	>4 m high, 5-8 m away	
North-West facing						

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
W03	700.00	610.00	aluminium, single glazed (U- value: Undecided, SHGC: Undecided)	eave 300 mm, 300 mm above head of window or glazed door	not overshadowed
W04	860.00	1210.00	aluminium, single glazed (U- value: Undecided, SHGC: Undecided)	eave 300 mm, 300 mm above head of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water		'	
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 4.5 stars.	~	~	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - ducted; Energy rating: 4 Star (old label)		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning - ducted; Energy rating: 4 Star (old label)		`	~
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - ducted; Energy rating: 4 Star (old label)		~	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning - ducted; Energy rating: 4 Star (old label)		~	~
Ventilation			-
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: no mechanical ventilation (ie. natural); Operation control: n/a		 	 Image: A set of the set of the
Kitchen: no mechanical ventilation (ie. natural); Operation control: n/a		 	~
Laundry: natural ventilation only, or no laundry; Operation control: n/a		 Image: A set of the set of the	
Artificial lighting			
The applicant must ensure that a minimum of 80% of light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting- diode (LED) lamps.		~	~
Natural lighting			
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	~	_	~

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Other	-		
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a V in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a V in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a V in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.