CERTIFIED ENERGY - SUMMARY COMMITMENTS TABLE

 \bigcirc

۲ م Accredditation Number: HERA 10056							
Project Details			Accre				
eta Pr	roposed:	Multi Dwelling		Address:	14 Avoca Street Yagoona NSW 2199		
<u>د</u> م	ot Number:	67 & 68		DP NUMBER:	6376		
	NatHERS Certificate Number: HR-XZU4VW-01						
_	Windows						
	For detailed window specifications please refer to NatHERS Certificate (NSW BASIX Thermal Protocol allows for ± 10% tolerance of SHGC Value & U Value =< than which overrides NatHERS Certificate)						
	lazing	(NSW BASIX		tolerance of SHGC Value & U Value =< than v	which overrides NatHERS Certificate) Frame Type		
GI	lazing	GF, H-A	Glass Type Single Glazed Clear	A	uminium (Standard)		
		H-B, H-C	Double Glazed Clear		uminium (Standard)		
			bousic clared clear				
	xternal walls			Requirements			
Br	rick veneer		All Units	Light colour	R2.7 Bulk + Anti-glare foil		
Int	iternal walls						
	avity wall, direct fix plasterboard		All Units				
	avity wall, direct fix plasterboard		All Units				
Ca	avity brick		H-A, H-B	No insulation			
+	oors						
o .	oncrete slab on ground		All Units	R1.0 Bulk insulation			
fu Gu	uspended concrete slab		All Units H-C				
ō S	uspended timber		All Units				
	uspended timber		All Units				
Thermal Comfort	aspended timber		An Units	N2.5 Buik insulation			
De Ce	eiling						
È Ce	eiling	Plasterboard	All Units	R6.0 Bulk insulation			
Ro	oof						
	orrugated iron		All Units	Medium Colour (solar absorptance 0.475-0.2	7)		
	onugated non		All Units	R1.8 Bulk + Reflective side down, No air gap	above (Anticon 75, 80mm)		
Ce	eiling Penetrations						
	ghting specification			Dwelling is rated with Assumed downlight a	s per NatHERS Tech Note "Ceiling Penetrations 9.4 to	9.8"	
Ce	eiling fans			No ceiling fans need to be installed			
0\	vershadowing details			Adjoining units calculated into model calculated	ations		
Sit	10						
	rientation of nominal north elevatio	n		As shown on plans			
		s HAVE been specified, which can be fully cover		for exhaust dampers have been allowed (to all			
	bathrooms, ensuites and internal lat	undry's) at the rate of 0.04 meters squared per	exhaust ran penetration.				
	BASIX Certificate Number: 1798777M						
Fit	xtures		Specification	Alternative water details			
Sh	nower head rating		4 star (> 6 but <= 7.5 L/min)	Rainwater tank size	Individual	2000L	
То	pilet rating		3 star	Connected to:	Garden and lawn areas	All toilets	Laundry
	itchen taps rating		3 star		Yes	Yes	No
	athroom taps rating		3 star				
Lat Vat	ot water	Specification	Rating	Lighting		Alternative Energy	Peak kW
> In	idividual system	Gas instantaneous	6 star	Refer to NatHERS Certificate	Light-emitting diode (LED)	Photovoltaic System (Minimum)	N/A
⊗ Ve	entilation		line a second		Lauradas Polasiat	Individual fan, ducted to	6
BO Ba	athroom Exhaust ontrol switch	Individual fan, ducted to façade or roof Manual switch on/off	Kitchen Exhaust Control switch	Individual fan, ducted to façade or roof Manual switch on/off	Laundry Exhaust Control switch	Individual fan, ducted to Manual switch d	
	ontrol switch	wanuai switch on/on	control switch	Heating	control switch	Wanuai SWITCH C	iiyon
	idividual systems - living areas	3-phase airconditioning	EER 3.0 - 3.5	Individual systems - living areas		3-phase airconditioning	EER 3.0 - 3.5
	idividual systems - bedroom areas	3-phase airconditioning	EER 3.0 - 3.5	Individual systems - bedroom areas		3-phase airconditioning	EER 3.0 - 3.5
Ap	ppliances					,	
	ooktop/oven		Gas cooktop & electric oven		Private Indoor or sheltered clothes drying line		No
	rivate outdoor clothes drying line		Yes		Zoned Air-conditioning		Yes