

BASIX™ Certificate

Building Sustainability Index

www.planningportal.nsw.gov.au/development-and-assessment/basix

Single Dwelling

Certificate number: 1807239S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.planningportal.nsw.gov.au/definitions

Secretary

Date of issue: Wednesday, 06 August 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



Project summary

Project name	3 GUNGAROO PL BEVERLY HILLS
Street address	3 GUNGAROO Place BEVERLY HILLS 2209
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan DP13705
Lot no.	981
Section no.	-
Project type	dwelling house (detached)
No. of bedrooms	5

Project score

Water	✓ 40	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	✓ 74	Target 72
Materials	✓ -61	Target n/a

Certificate Prepared by

Name / Company Name: GEC DESIGN

ABN (if applicable):

Description of project

Project address	
Project name	3 GUNGAROO PL BEVERLY HILLS
Street address	3 GUNGAROO Place BEVERLY HILLS 2209
Local Government Area	Canterbury-Bankstown Council
Plan type and plan number	Deposited Plan DP13705
Lot no.	981
Section no.	-
Project type	
Project type	dwelling house (detached)
No. of bedrooms	5
Site details	
Site area (m²)	665
Roof area (m²)	255
Conditioned floor area (m²)	300.0
Unconditioned floor area (m²)	11.0
Total area of garden and lawn (m²)	257
Roof area of the existing dwelling (m²)	0

Assessor details and thermal loads		
NatHERS assessor number	n/a	
NatHERS certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/ m².year)	n/a	
Area adjusted heating load (MJ/ m².year)	n/a	
Project score		
Water	 40	Target 40
Thermal Performance	 Pass	Target Pass
Energy	 74	Target 72
Materials	 -61	Target n/a

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 6 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 6 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 6 star in each bathroom in the development.		✓	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 3500 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 200 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.)		✓	✓

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Do-it-yourself Method			
General features			
The dwelling must be a Class 1 dwelling according to the National Construction Code, and must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓
The applicant must adopt one of the options listed in the tables below to address thermal bridging in metal framed floor(s), walls and ceiling/roof of the dwelling.	✓	✓	✓
The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the tables below.			✓

Construction	Area - m ²	Additional insulation required	Options to address thermal bridging	Other specifications
floor - above habitable rooms or mezzanine, concrete - suspended; frame: no frame..	141	nil;none	nil	
floor - suspended floor above garage, concrete - suspended; frame: no frame.	170	nil;none	nil	
garage floor - concrete slab on ground.	147	none	nil	

Construction	Area - m ²	Additional insulation required	Options to address thermal bridging	Other specifications
external wall: concrete panel/ plasterboard; frame: no frame.	all external walls	3.14 (or 3.50 including construction);fibreglass batts or roll	nil	wall colour: Medium (solar absorptance 0.48-0.7)
external garage wall: concrete block/plasterboard; frame: no frame.	111	none	nil	
internal wall: plasterboard; frame: timber - untreated softwood.	93	none	nil	
ceiling and roof - flat ceiling / flat roof, concrete - plasterboard internal, no frame.	255	insulation under concrete ;ceiling: fibreglass batts or roll; roof: not specified.	nil	roof colour: medium (solar absorptance 0.48-0.59); ceiling area fully insulated

Note	Insulation specified in this Certificate must be installed in accordance with the ABCB Housing Provisions (Part 13.2.2) of the National Construction Code.
Note	If the additional ceiling insulation listed in the table above is greater than R3.0, refer to the ABCB Housing Provisions (Part 13.2.3 (6)) of the National Construction Code.
Note	In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.
Note	Thermal breaks must be installed in metal framed walls and applicable roofs in accordance with the ABCB Housing Provisions of the National Construction Code.

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Ceiling fans			
The applicant must install at least one ceiling fan in at least one daytime habitable space, such as living room.	✓	✓	✓
The minimum number and diameter of ceiling fans in a daytime habitable space must be installed in accordance with the ABCB Housing Provisions (Part 13.5.2) of the National Construction Code .	✓	✓	✓

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Glazed windows, doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each glazed window and door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
The following requirements must also be satisfied in relation to each window and glazed door:	✓	✓	✓
The applicant must install windows and glazed doors in accordance with the height and width, frame and glazing types listed in the table.	✓	✓	✓
Each window and glazed door must have a U- value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.		✓	✓
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	✓	✓	✓

Skylight no.	Maximum area (m²)	Skylight specification	Shading device
S02	0.60	aluminium, single clear (U: <=7.3, SHGC: 0.75 - 0.83)	no shading
S03	0.80	aluminium, single clear (U: <=7.3, SHGC: 0.75 - 0.83)	no shading
S04	0.80	aluminium, single clear (U: <=7.3, SHGC: 0.75 - 0.83)	no shading
S05	0.80	aluminium, single clear (U: <=7.3, SHGC: 0.75 - 0.83)	no shading

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
North facing					

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
DINNING	2900.00	8200.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	solid overhang 5151 mm, 200 mm above head of window or glazed door	not overshadowed
M.ENS	2100.00	800.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
M.ENS	1800.00	1500.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
M.BED	2700.00	4000.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	solid overhang 1625 mm, 0 mm above head of window or glazed door	not overshadowed
East facing					
ENTRY	4750.00	1800.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
STR	2100.00	550.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
LIVING	2900.00	1500.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
LIVING	2900.00	1500.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
BED3	1700.00	2400.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
South facing					
GUEST ROOM	1700.00	2400.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
FORMAL	4750.00	3200.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
BED1	2700.00	2300.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	solid overhang 2649 mm, 0 mm above head of window or glazed door	not overshadowed
VOID	2600.00	1800.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	solid overhang 3140 mm, 200 mm above head of window or glazed door	not overshadowed
West facing					
GUEST ROOM	600.00	2500.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
ENS	600.00	1000.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
KITCHEN	600.00	610.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
BED1	2100.00	800.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
BED1	2100.00	800.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
BATH	1800.00	1500.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
PDR	600.00	610.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
BED2	2100.00	600.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
BED2	2100.00	600.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed
MENS	600.00	610.00	aluminium, single glazed (U-value: <=5.0, SHGC: 0.74 - 0.90)	none	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	✓	✓	✓
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - ducted; Energy rating: 3 star (average zone)		✓	✓
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning - ducted; Energy rating: 3 star (average zone)		✓	✓
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - ducted; Energy rating: 3 star (average zone)		✓	✓
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning - ducted; Energy rating: 3 star (average zone)		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	✓
Artificial lighting			
The applicant must ensure that a minimum of 80% of light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		✓	✓
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	✓	✓	✓

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The applicant must install a window and/or skylight in 4 bathroom(s)/toilet(s) in the development for natural lighting.	✓	✓	✓
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		✓	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.