

Nationwide House Energy Rating Scheme®

NatHERS® Certificate No. GMIJSSXFMT

Generated on 24 Feb 2026 using FirstRate5: 5.5.5a (3.22)

Property

Address 595 GLENROCK ROAD,
CAVAN, NSW, 2582
Lot/DP L1 DP 1232600
NCC Class* Class 1a
Floor/all Floors
Type New Home

Plans

Main plan Refer to stamped plans
Prepared by J.T & T.I

Construction and environment

Assessed floor area [m²]*	Exposure type
Conditioned* 232.3	suburban
Unconditioned* 72.3	NatHERS climate zone
Total 304.6	24 Canberra Airport
Garage 50.5	



Accredited assessor

Name Tristan Campbell
Business name 7 Star Ratings
Email tristan.c99@outlook.com
Phone 0468480455
Accreditation No. 101570
Assessor Accrediting Organisation
ABSA
Declaration of interest No

NCC Requirements

NCC provisions Volume 2
State/Territory variation Yes

National Construction Code (NCC) requirements


The NCC allows the use of NatHERS accredited software to comply with the energy efficiency requirements for houses (Class 1 buildings) and apartments (Class 2 sole-occupancy units and Class 4 parts of buildings). The applicable requirements for houses are detailed in Specification 42 of NCC Volume Two. For apartments the requirements are detailed in clauses J3D3 and J3D15 of NCC Volume One.

NCC 2022 includes enhanced thermal performance requirements for houses and apartments. It also includes a new whole-of-home annual energy use budget which applies to the major equipment in the home.

The NCC, and associated ABCB Standards and support material, can be accessed at www.abcb.gov.au.

Note, variations and additions to the NCC energy efficiency requirements may apply in some states and territories.

Thermal performance star rating



**NATIONWIDE
HOUSE**
ENERGY RATING SCHEME®

122 MJ/m²

Predicted annual energy load for heating and cooling based on standard occupancy assumptions.

For more information on your dwelling's rating see:
www.nathers.gov.au

Thermal performance [MJ/m²]

Limits taken from ABCB Standard 2022

	Heating	Cooling
Modelled	106.8	15.2
Load limits	N/A	N/A
Features determining load limits		
Floor type (lowest conditioned area)		N/A
NCC climate zone 1 or 2		N/A
Outdoor living area		N/A
Outdoor living area ceiling fan		N/A

Whole of Home performance rating

No Whole of Home performance rating generated for this certificate

Verification

To verify this certificate, scan the QR code or visit <https://www.fr5.com.au/QRCodeLandIng?PublicId=GMIJSSXFMT>. When using either link, ensure you are visiting www.fr5.com.au.





About the ratings

Thermal performance rating

NatHERS thermal software models the expected heating and cooling energy loads using information about the design, construction, climate and common patterns of household use. The thermal performance rating (shown as a star rating on this Certificate) does not take into account appliances, apart from the airflow impacts from ceiling fans.

Whole of Home performance rating

NatHERS Whole of Home software uses the heating and cooling energy loads combined with the energy performance of the home's appliances (heating, cooling, hot water, lighting, pool/spa pump and onsite renewable energy generation and storage) and models the expected energy value* of the whole home. The Whole of Home performance rating is shown as a score out of 100 on this Certificate.

Heating & Cooling Load Limits

Additional information

In some locations under the NCC NatHERS pathway, separate heating and cooling load limits may apply. Minimum required star ratings in northern parts of Australia may also be affected by the presence or absence of an outdoor living area and/or an outdoor living area ceiling fan. Refer to the ABCB NatHERS heating and cooling load limits Standard 2022 for details or contact the relevant local building regulating authority, noting that State and Territory variations may also apply.

Setting options:

Floor type:

CSOG – Concrete Slab on Ground

SF – Suspended Floor (or a mixture of CSOG and SF)

NA – Not Applicable

NCC climate Zone 1 or 2:

Yes

No

NA – not applicable

Outdoor living area:

Yes

No

NA – not applicable

Outdoor living area ceiling fan:

Yes

No

NA – not applicable

Predicted Whole of Home annual impact by appliance

Shows the contribution each appliance has on the home's annual energy use, greenhouse gas emissions and cost without solar

Energy use:

No Whole of Home performance assessment conducted for this certificate.

Greenhouse gas emissions:

No Whole of Home performance assessment conducted for this certificate.

Cost:

No Whole of Home performance assessment conducted for this certificate.

Graph key:



Predicted onsite renewable energy impact

No Whole of Home performance assessment conducted for this certificate.

Certificate check

The checklist covers important items impacting the dwelling's ratings.
It is recommended that the accuracy of the whole certificate is checked.

Note: The boxes indicate when and who should check each item.
It is not mandatory to complete this checklist.

	Approval stage		Construction stage		Occupancy/other
	Assessor checked	Consent authority/surveyor checked	Builder checked	Consent authority/surveyor checked	
Genuine certificate check					
Does this Certificate match the one available at the web address or QR code verification link on the front page?		☐	☐	☐	☐
Does the NatHERS certificate number on the NatHERS-stamped plans match the number on this Certificate?		☐	☐	☐	☐
Thermal performance check					
Windows and glazed doors					
Does the window size, opening type and location shown on the NatHERS-stamped plans or as installed match what is shown in 'Window and glazed door schedule' and 'Roof window schedule' tables on this Certificate?	☐	☐	☐	☐	☐
Does the installed windows meet the substitution tolerances (AFRC* based SHGC* and U-values*) as shown in the 'Window and glazed door type and performance' and 'Roof window type and performance' tables on this Certificate?			☐	☐	☐
External walls					
Does the external wall bulk insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the External wall type table on this Certificate?	☐	☐	☐	☐	☐
Does the external wall shade (colour) match what is shown in the 'External wall type' table on this Certificate?	☐	☐	☐	☐	☐
Floor					
Does the floor insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Floor type' table on this certificate?	☐	☐	☐	☐	☐
Ceiling penetrations*					
Does the 'quantity' and 'type' of ceiling penetrations* (e.g. downlights, exhaust fans, etc) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling penetrations' table on this Certificate?	☐	☐	☐	☐	☐
Ceiling					
Does the ceiling insulation (R-value) shown on the NatHERS-stamped plans or as installed match what is shown in the 'Ceiling type' table on this Certificate?	☐	☐	☐	☐	☐
Roof					
Does the external roof shade (colour) on the NatHERS stamped plans or as installed match what is shown in the 'Roof type' table on this Certificate?	☐	☐	☐	☐	☐
Apartment entrance doors (NCC Class 2 assessments only)					
Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.	☐	☐		☐	☐
Exposure*					
Has the appropriate exposure type (terrain) (shown on page 1) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".	☐	☐		☐	☐
Heating and cooling load limits*					
Do the load limits settings (shown on page 1) match the values in the ABCB Standard 2022: NatHERS heating and cooling load limits for the appropriate climate zone?	☐	☐	☐	☐	☐



Certificate check

Continued

	Approval stage		Construction stage		Occupancy/other
	Assessor checked	Consent authority/surveyor checked	Builder checked	Consent authority/surveyor checked	

Additional NCC requirements for thermal performance (not included in the NatHERS assessment)

Thermal bridging

Does the dwelling meet the NCC requirement for thermal bridging?		☐	☐	☐	☐
--	--	--------------------------	--------------------------	--------------------------	--------------------------

Insulation installation method

Has the insulation been installed according to the NCC requirements?			☐	☐	☐
--	--	--	--------------------------	--------------------------	--------------------------

Building sealing

Does the dwelling meet the NCC requirements for Building Sealing?		☐	☐	☐	☐
---	--	--------------------------	--------------------------	--------------------------	--------------------------

Whole of Home performance check (not applicable if a Whole of Home performance assessment is not conducted)

Appliances

Does the cooling appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the Appliance schedule on this Certificate?	☐	☐	☐	☐	☐
---	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the heating appliance/s type, location and efficiency/performance shown on the NatHERS-stamped plans or installed, match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	☐	☐	☐	☐	☐
---	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the hot water system type and efficiency/performance shown on the NatHERS-stamped plans or as installed match the location and minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	☐	☐	☐	☐	☐
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the pool pump efficiency/performance shown on the NatHERS-stamped plans or as installed match the minimum efficiency/performance requirements shown in the 'Appliance schedule' on this Certificate?	☐	☐	☐	☐	☐
---	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Does the onsite renewable energy system type, orientation and system size or generation capacity shown on the NatHERS stamped plans or installed match the 'Onsite Renewable Energy schedule' on this Certificate?	☐	☐	☐	☐	☐
--	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Additional NCC Requirements for Services (not included in the NatHERS assessment)

Does the lighting meet the artificial lighting requirements specified in the NCC?		☐	☐	☐	☐
---	--	--------------------------	--------------------------	--------------------------	--------------------------

Does the hot water system meet the additional requirements specified in the NCC?		☐	☐	☐	☐
--	--	--------------------------	--------------------------	--------------------------	--------------------------

Provisional values* check

Have provisional values* been used in the assessment and, if so, are they noted in 'Additional notes' table below?	☐	☐			
--	--------------------------	--------------------------	--	--	--

Other NCC requirements

Note: This Certificate only covers the energy efficiency requirements in the NCC. Additional requirements that must also be satisfied include, but are not limited to: condensation, structural and fire safety requirements and any state or territory variations to the NCC energy efficiency requirements.

Additional notes

Fireplace: Fireplace must have zero clearance flue system and damper installed.



Room *schedule*

Room	Zone Type	Area [m²]
WIP	dayTime	7.9
ENTRY	dayTime	15.1
KITCHEN	kitchen	24.5
LIVING DINING	living	61.3
STUDY	dayTime	13.2
BEDROOM 1	bedroom	20
WIR	nightTime	9.7
ENS	nightTime	7.9
BEDROOM 3	bedroom	15.5
BEDROOM 2	bedroom	15.7
BEDROOM 4	bedroom	15.8
BATH	unconditioned	9.5
GARAGE	garage	50.5
WC	dayTime	3.6
LAUNDRY	unconditioned	12.3
HALL	dayTime	22.1

Window and glazed door *type and performance*

Default* windows

Window ID	Window description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
ATB-006-03 B	Al Thermally Broken B DG Argon Fill High Solar Gain low-E -Clear	2.9	0.51	0.48	0.54
ATB-005-03 B	Al Thermally Broken A DG Argon Fill High Solar Gain low-E -Clear	2.91	0.44	0.42	0.46

Custom* windows

Window ID	Window description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
A&L-026-05 A	Al Boutique Fixed Lite Window DG 3/12Ar/3EA	2.22	0.64	0.61	0.67

Window and glazed door *schedule*

Location	Window ID	Window no.	Height [mm]	Width [mm]	Window type	Opening %	Orientation	Window shading device*
ENTRY	ATB-006-03 B	W10	2100	600	fixed	0.0	SE	No
ENTRY	ATB-006-03 B	W09	2100	600	fixed	0.0	SE	No

*Refer to glossary.



ENTRY	ATB-005-03 B	D19	2100	1020	casement	90.0	SE	No
KITCHEN	ATB-005-03 B	W07	1200	2110	awning	40.0	SE	No
KITCHEN	ATB-005-03 B	W08	1200	2110	awning	40.0	SE	No
KITCHEN	ATB-005-03 B	W06	1800	2110	awning	30.0	NE	No
LIVING DINING	A&L-026-05 A	GLAZING ELEVATION 5	431	2956	fixed	0.0	SE	No
LIVING DINING	ATB-005-03 B	W05	1800	2110	awning	30.0	NE	No
LIVING DINING	ATB-006-03 B	D26	2100	2050	sliding	45.0	NE	No
LIVING DINING	ATB-005-03 B	W03	1800	1810	awning	30.0	NW	No
LIVING DINING	A&L-026-05 A	GLAZING ELEVATION 4	522	1810	fixed	0.0	NW	No
LIVING DINING	ATB-006-03 B	D24	2100	2660	sliding	45.0	NW	No
LIVING DINING	A&L-026-05 A	GLAZING ELEVATION 3	2007	2660	fixed	0.0	NW	No
LIVING DINING	ATB-006-03 B	D25	2100	2660	sliding	45.0	NW	No
LIVING DINING	A&L-026-05 A	GLAZING ELEVATION 2	2007	2660	fixed	0.0	NW	No
LIVING DINING	ATB-005-03 B	W04	1800	1810	awning	30.0	NW	No
LIVING DINING	A&L-026-05 A	GLAZING ELEVATION 1	522	1810	fixed	0.0	NW	No
STUDY	ATB-006-03 B	D23	2100	1710	sliding	45.0	NW	No
BEDROOM 1	ATB-006-03 B	D22	2100	2050	sliding	45.0	NW	No
WIR	ATB-005-03 B	W02	1800	910	awning	60.0	NW	No
ENS	ATB-005-03 B	W01	1200	1510	awning	40.0	NW	No
BEDROOM 3	ATB-005-03 B	W16	1200	2110	awning	40.0	NW	No
BEDROOM 2	ATB-005-03 B	W15	1200	2110	awning	40.0	NW	No
BEDROOM 4	ATB-005-03 B	W13	1800	2110	awning	30.0	SE	No
BATH	ATB-005-03 B	W12	1200	1510	awning	40.0	SE	No
GARAGE	ATB-005-03 B	D15	2100	851	casement	90.0	NE	No
LAUNDRY	ATB-005-03 B	W11	1800	1810	awning	30.0	SE	No
HALL	ATB-005-03 B	D01	2100	820	casement	90.0	SW	No

Roof window* type and performance value

Default* roof windows

Window ID	Window description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

Custom* roof windows

Window ID	Window description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit



No Data Available

Roof window* *schedule*

Location	Window ID	Window no.	Opening %	Area [m²]	Width [mm]	Orientation	Outdoor shade	Indoor shade
No Data Available								

Skylight* *type and performance*

Skylight ID	Skylight description	Skylight shaft reflectance
No Data Available		

Skylight* *schedule*

Location	Skylight ID	Skylight No.	Skylight shaft length [mm]	Area [m²]	Orient-ation	Outdoor shade	Diffuser
No Data Available							

External door *schedule*

Location	Height [mm]	Width [mm]	Opening %	Orientation
GARAGE	2400	6000	100.0	SE

External wall *type*

Wall ID	Wall type	Solar absorptance	Wall shade [colour]	Bulk insulation [R-value]	Reflective wall wrap*
1	FC - Fibro clad with R4 Batt + Foil	0.8	Dark	Rockwool batt: R4.0 (R4.0)	No
2	Brick Veneer - BV with R4 Batt + Foil	0.5	Medium	Rockwool batt: R4.0 (R4.0)	No

External wall *schedule*

Location	Wall ID	Height [mm]	Width [mm]	Orientation	Horizontal shading feature* maximum projection [mm]	Vertical shading feature* (yes/no)
WIP	1	2700	736	SE	2671	Yes
ENTRY	2	2700	3552	SE	2384	Yes
KITCHEN	1	2700	6566	SE	2512	Yes
KITCHEN	1	2700	4132	NE	2540	No
LIVING DINING	1	450	2956	SE	0	No
LIVING DINING	1	2700	6242	NE	2542	No
LIVING DINING	1	4050	10464	NW	5689	Yes
STUDY	1	2700	2953	NW	2257	Yes
BEDROOM 1	1	2700	4477	NW	2263	Yes
WIR	1	2700	2170	NW	2249	Yes
ENS	1	2700	1771	NW	2264	Yes

*Refer to glossary.



BEDROOM 3	1	2700	3460	NW	2252	Yes
BEDROOM 2	1	2700	4498	SW	606	No
BEDROOM 2	1	2700	2105	SE	8508	Yes
BEDROOM 2	1	2700	3484	NW	2251	Yes
BEDROOM 4	1	2700	4561	SW	2710	Yes
BEDROOM 4	1	2700	3465	SE	2553	Yes
BATH	1	2700	2082	SE	2553	Yes
GARAGE	2	2700	401	NE	686	Yes
GARAGE	2	2700	2593	NE	0	Yes
GARAGE	2	2700	3007	SW	671	Yes
GARAGE	2	2700	6991	SE	519	No
LAUNDRY	1	2700	3361	SE	2534	Yes
HALL	1	2700	1171	SW	2711	Yes

Internal wall type

Wall ID	Wall type	Area [m²]	Bulk insulation
1	FR5 - Internal Plasterboard Stud Wall	194	
2	INT - Int Wall To Roof R2.5	11.6	Rockwool batt: R2.5 (R2.5)
3	INT - Int Unconditioned Wall R2.5	49.7	Rockwool batt: R2.5 (R2.5)
4	GRG - Garage Int Wall	33.6	Rockwool batt: R2.5 (R2.5)

Floor type

Location	Construction	Area [m²]	Sub-floor ventilation	Added insulation [R-value]	Covering
WIP	FR5 - CSOG: Slab on Ground	7.9	Enclosed	R2.0	Timber
ENTRY	FR5 - CSOG: Slab on Ground	15.1	Enclosed	R2.0	Timber
KITCHEN	FR5 - CSOG: Slab on Ground	24.5	Enclosed	R2.0	Timber
LIVING DINING	FR5 - CSOG: Slab on Ground	61.3	Enclosed	R2.0	Timber
STUDY	FR5 - CSOG: Slab on Ground	13.2	Enclosed	R2.0	Carpet
BEDROOM 1	FR5 - CSOG: Slab on Ground	20	Enclosed	R2.0	Carpet
WIR	FR5 - CSOG: Slab on Ground	9.7	Enclosed	R2.0	Tiles
ENS	FR5 - CSOG: Slab on Ground	7.9	Enclosed	R2.0	Tiles
BEDROOM 3	FR5 - CSOG: Slab on Ground	15.5	Enclosed	R2.0	Carpet



BEDROOM 2	FR5 - CSOG: Slab on Ground	15.7	Enclosed	R2.0	Carpet
BEDROOM 4	FR5 - CSOG: Slab on Ground	15.8	Enclosed	R2.0	Carpet
BATH	FR5 - CSOG: Slab on Ground	9.5	Enclosed	R2.0	Tiles
GARAGE	FR5 - CSOG: Slab on Ground	50.5	Enclosed	R2.0	none
WC	FR5 - CSOG: Slab on Ground	3.6	Enclosed	R2.0	Tiles
LAUNDRY	FR5 - CSOG: Slab on Ground	12.3	Enclosed	R2.0	Tiles
HALL	FR5 - CSOG: Slab on Ground	22.1	Enclosed	R2.0	Timber

Ceiling type

Location	Construction material/type	Bulk insulation R-value [may include edge batt values]	Reflective wrap*
WIP	Plasterboard	R7.0	Yes
ENTRY	Plasterboard	R7.0	Yes
KITCHEN	Plasterboard	R7.0	Yes
LIVING DINING	Plasterboard	R7.0	No
STUDY	Plasterboard	R7.0	Yes
BEDROOM 1	Plasterboard	R7.0	Yes
WIR	Plasterboard	R7.0	Yes
ENS	Plasterboard	R7.0	Yes
BEDROOM 3	Plasterboard	R7.0	Yes
BEDROOM 2	Plasterboard	R7.0	Yes
BEDROOM 4	Plasterboard	R7.0	Yes
BATH	Plasterboard	R7.0	Yes
GARAGE	Plasterboard	R7.0	Yes
WC	Plasterboard	R7.0	Yes
LAUNDRY	Plasterboard	R7.0	Yes
HALL	Plasterboard	R7.0	Yes

Ceiling penetrations*

Location	Quantity	Type	Height [mm]	Width [mm]	Sealed/unsealed
WIP	2	Downlights	50	50	Sealed
ENTRY	3	Downlights	50	50	Sealed
KITCHEN	5	Downlights	50	50	Sealed
KITCHEN	1	Exhaust Fans	250	250	Sealed
LIVING DINING	1	Chimneys	266	266	Sealed

*Refer to glossary.



LIVING DINING	12	Downlights	50	50	Sealed
STUDY	3	Downlights	50	50	Sealed
BEDROOM 1	4	Downlights	50	50	Sealed
WIR	2	Downlights	50	50	Sealed
ENS	2	Downlights	50	50	Sealed
ENS	1	Exhaust Fans	250	250	Sealed
BEDROOM 3	4	Downlights	50	50	Sealed
BEDROOM 2	4	Downlights	50	50	Sealed
BEDROOM 4	3	Downlights	50	50	Sealed
BATH	2	Downlights	50	50	Sealed
BATH	1	Exhaust Fans	250	250	Sealed
GARAGE	10	Downlights	50	50	Sealed
WC	1	Downlights	50	50	Sealed
WC	1	Exhaust Fans	250	250	Sealed
LAUNDRY	3	Downlights	50	50	Sealed
LAUNDRY	1	Exhaust Fans	250	250	Sealed
HALL	5	Downlights	50	50	Sealed

Ceiling fans

Location	Quantity	Diameter [mm]
STUDY	1	1200

Roof type

Construction	Added insulation [R-value]	Solar absorptance	Roof shade [colour]
Cont:Attic-Continuous	0.0	0.8	Dark
Framed:Flat - Flat Framed (Metal Deck)	0.0	0.8	Dark

Thermal bridging *schedule for steel frame elements*

Building element	Steel section dimensions [height x width, mm]	Frame spacing [mm]	Steel thickness [BMT,mm]	Thermal break [R-value]
No Data Available				

Appliance *schedule*

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

Note: A flat assumption of 5W/m2 is used for lighting, therefore lighting is not included in the appliance schedule.

Cooling system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Whole of Home performance assessment conducted for this certificate.				



Heating system

Appliance/ system type	Location	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Whole of Home performance assessment conducted for this certificate.				

Hot water system

Appliance/ system type	Fuel type	Minimum efficiency/ performance	Hot Water CER Zone	Zone 3 STC	Assessed daily load
No Whole of Home performance assessment conducted for this certificate.					

Pool/spa equipment

Appliance/ system type	Fuel type	Minimum efficiency/ performance	Recommended capacity
No Whole of Home performance assessment conducted for this certificate.			

Onsite renewable energy *schedule*

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

System type	Orientation	System size or generation capacity
No Whole of Home performance assessment conducted for this certificate.		

Battery *schedule*

(not applicable if a Whole of Home performance assessment is not conducted for this certificate)

System type	Size [battery storage capacity]
No Whole of Home performance assessment conducted for this certificate.	

Explanatory Notes

About this report

NatHERS ratings are a reliable guide for comparing different dwelling designs and to demonstrate that designs meet the energy efficiency requirements in the National Construction Code.

NatHERS ratings use computer modelling to evaluate a home's energy efficiency and performance. They use localised climate data and standard assumptions on how people use their home to predict the heating and cooling energy loads and energy value* of the whole home. The thermal performance star rating uses the home's building specifications, layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings) to predict the heating and cooling energy loads. The Whole of Home performance rating uses information about the home's appliances and onsite energy generation and storage to estimate the homes energy value*.

The actual energy loads, cost and greenhouse gas emissions of a home may vary from that predicted. This is because the assumptions will not always match the actual occupant usage patterns. For example, the number of occupants and how people use their appliances will vary. Energy efficient homes use less energy, are warmer on cool days, cooler on hot days and cost less to run.

Accredited assessors

For quality assured NatHERS Certificates, always use an accredited or licenced assessor registered with an Assessor Accrediting Organisation (AAO). AAOs have strict quality assurance processes, and professional development requirements ensuring consistently high standards for assessments.

Non-accredited assessors (Raters) have no ongoing training requirements and are not quality assured.

Any queries about this report should be directed to the assessor. If the assessor is unable to address questions or concerns, contact the AAO specified on the front of this certificate.

Disclaimer

The NatHERS Certificate format is developed by the NatHERS Administrator. However, the content in the certificate is entered by the assessor. It is the assessor's responsibility to use NatHERS accredited software correctly and follow the NatHERS Technical Note to produce a NatHERS Certificate.

The predicted annual energy load, cost and greenhouse gas emissions in this NatHERS Certificate are an estimate based on an assessment of the dwelling's design by the assessor. It is not a prediction of actual energy use, cost or emissions. The information and ratings may be used to compare how other dwellings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, behaviour, appliance performance, indoor air temperature and local climate.

Not all assumptions made by the assessor using the NatHERS accredited software tool are presented in this report and further details or data files may be obtained from the assessor.

Glossary

Annual energy load	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
AFRC	Australian Fenestration Rating Council
Assessed floor area	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
Ceiling penetrations	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, range hoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
Conditioned	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
COP	Coefficient of performance
Custom windows	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
Default windows	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
EER	Energy Efficiency Ratio, measure of how much cooling can be achieved by an air conditioner for a single kWh of electricity input
Energy use	This is your homes rating without solar or batteries.
Energy value	The net cost to society including, but not limited to, costs to the building user, the environment and energy networks (as defined in the ABCB Housing Provisions Standard).
Entrance door	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
Exposure category – exposed	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
Exposure category – open	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
Exposure category – suburban	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
Exposure category – protected	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
Horizontal shading feature	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
National Construction Code (NCC) Class	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at www.abcb.gov.au .
Net zero home	a home that achieves a net zero energy value*.
Opening percentage	the openability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
Provisional value	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at www.nathers.gov.au
Recommended capacity	this is the capacity or size of equipment that is recommended by NatHERS to achieve the desired comfort conditions in the zone or zones serviced. This is a recommendation and the final selection sizing should be confirmed by a suitably qualified person.
Reflective wrap (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate air gap and emissivity value, it provides insulative properties.
Roof window	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
Shading features	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
Solar heat gain coefficient (SHGC)	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
Skylight (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.

*Refer to glossary.



STCs	Small-scale Technology Certificates, certificates created by the REC registry for renewable energy technologies that may be bought and sold as part of the Small-scale Renewable Energy Scheme operated by the Clean Energy Regulatory
Thermal breaks	are materials with an R-value greater than or equal to 0.2 that must separate the metal frame from the cladding. This includes, but is not limited to, materials such as timber battens greater than or equal to 20mm thick, continuous thermal breaks such as polystyrene insulation sheeting, plastic strips or furring channels.
U-value	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
Unconditioned	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions.
Vertical shading features	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).
Window shading device	a device fixed to windows that provides shading e.g. window awnings or screens but excludes horizontal* or vertical shading features* (eg eaves and balconies)