

BASIX[®]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1218331S_03

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number 1218331S lodged with the consent authority or certifier on 12 July 2021 with application X/1094/2021.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Schedule 1 Clause 2A, 4A or 6A of the Environmental Planning and Assessment Regulation 2000




Secretary

Date of issue: Monday, 30 May 2022

To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning,
Industry &
Environment

Project summary		
Project name	40WilsonStWentworthFalls_PropRes_210_03	
Street address	40 Wilson Street Wentworth Falls 2782	
Local Government Area	Blue Mountains City Council	
Plan type and plan number	deposited B/3497	
Lot no.	5	
Section no.	-	
Project type	separate dwelling house	
No. of bedrooms	4	
Project score		
Water	 43	Target 40
Thermal Comfort	 Pass	Target Pass
Energy	 48	Target 45

Certificate Prepared by

Name / Company Name: Bio-Building Design Pty Ltd

ABN (if applicable): 67002764196

Description of project

Project address

Project name	40WilsonStWentworthFalls_PropRes_210_03
Street address	40 Wilson Street Wentworth Falls 2782
Local Government Area	Blue Mountains City Council
Plan type and plan number	Deposited Plan B/3497
Lot no.	5
Section no.	-

Project type

Project type	separate dwelling house
No. of bedrooms	4

Site details

Site area (m ²)	3597
Roof area (m ²)	349
Conditioned floor area (m2)	242.85
Unconditioned floor area (m2)	18.35
Total area of garden and lawn (m2)	765

Assessor details and thermal loads

Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m ² .year)	n/a
Area adjusted heating load (MJ/m ² .year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a

Project score

Water	✓ 43	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 48	Target 45

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 150 square metres of the site.	✓	✓	
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 7.5 but <= 9 L/min) in all showers in the development.		✓	✓
The applicant must install a toilet flushing system with a minimum rating of 3 star in each toilet in the development.		✓	✓
The applicant must install taps with a minimum rating of 3 star in the kitchen in the development.		✓	
The applicant must install basin taps with a minimum rating of 3 star in each bathroom in the development.		✓	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 27000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	✓	✓	✓
The applicant must configure the rainwater tank to collect rain runoff from at least 348.86 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		✓	✓
The applicant must connect the rainwater tank to: <ul style="list-style-type: none"> all toilets in the development at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		✓ ✓	✓ ✓

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	✓	✓	✓
The conditioned floor area of the dwelling must not exceed 300 square metres.	✓	✓	✓
The dwelling must not contain open mezzanine area exceeding 25 square metres.	✓	✓	✓
The dwelling must not contain third level habitable attic room.	✓	✓	✓
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	✓	✓	✓

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground, 53.5 square metres	nil	
floor - suspended floor above enclosed subfloor, 195.25 square metres, framed	1.80 (or 2.5 including construction) (down)	
external wall - framed (weatherboard, fibre cement, metal clad)	2.40 (or 2.80 including construction)	
external wall - brick veneer	2.26 (or 2.80 including construction)	
external wall - cavity brick	1.00 (or 1.67 including construction)	
ceiling and roof - flat ceiling / pitched roof	ceiling: 3.2 (up), roof: foil backed blanket (75 mm)	unventilated; light (solar absorptance < 0.475)
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 3.5 (up), roof: foil backed blanket (75 mm)	framed; light (solar absorptance < 0.475)

Note	• Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

















Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	✓	✓	✓
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	✓	✓	✓
<p>The following requirements must also be satisfied in relation to each window and glazed door:</p> <ul style="list-style-type: none"> For the following glass and frame types, the certifier check can be performed by visual inspection. <ul style="list-style-type: none"> - Aluminium single clear - Aluminium double (air) clear - Timber/uPVC/fibreglass single clear - Timber/uPVC/fibreglass double (air) clear For other glass or frame types, each window and glazed door must be accompanied with certification showing a U value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range of those listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. Frame and glass types shown in the table below are for reference only. 	✓	✓	✓ ✓ ✓

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
North facing					
W7	900	2100	aluminium, single, clear	eave 200 mm, 500 mm above head of window or glazed door	not overshadowed
W5	2100	2100	aluminium, single, clear	eave 900 mm, 200 mm above head of window or glazed door	not overshadowed
W8	600	2100	aluminium, single, clear	eave 200 mm, 450 mm above head of window or glazed door	not overshadowed
W3	1200	800	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	eave 900 mm, 400 mm above head of window or glazed door	not overshadowed
W20	1200	800	aluminium, single, clear	eave 900 mm, 150 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W6	2100	2100	aluminium, single, clear	eave 900 mm, 200 mm above head of window or glazed door	not overshadowed
W9	600	600	aluminium, single, clear	eave 200 mm, 240 mm above head of window or glazed door	not overshadowed
W2	1200	2100	aluminium, single, clear	eave 900 mm, 400 mm above head of window or glazed door	not overshadowed
W4	1200	2100	aluminium, single, clear	eave 900 mm, 400 mm above head of window or glazed door	not overshadowed
W10	1200	600	aluminium, single, clear	eave 200 mm, 790 mm above head of window or glazed door	not overshadowed
W21	1200	800	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	eave 900 mm, 150 mm above head of window or glazed door	not overshadowed
W1	1200	2600	aluminium, single, clear	eave 900 mm, 400 mm above head of window or glazed door	not overshadowed
East facing					
W12	600	800	aluminium, single, clear	eave 900 mm, 200 mm above head of window or glazed door	not overshadowed
W16	900	700	aluminium, single, clear	eave 200 mm, 1090 mm above head of window or glazed door	not overshadowed
W23	1200	800	aluminium, single, clear	eave 740 mm, 220 mm above head of window or glazed door	not overshadowed
W13	600	2100	aluminium, single, clear	eave 900 mm, 200 mm above head of window or glazed door	not overshadowed
W11	1200	2100	aluminium, single, clear	eave 900 mm, 200 mm above head of window or glazed door	not overshadowed
W22	1200	600	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	eave 740 mm, 220 mm above head of window or glazed door	not overshadowed
South facing					
W15	1800	600	aluminium, single, clear	eave 200 mm, 500 mm above head of window or glazed door	not overshadowed
W18	1800	600	aluminium, single, clear	eave 500 mm, 300 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Type	Shading Device (Dimension within 10%)	Overshadowing
W14	600	2400	aluminium, single, clear	eave 200 mm, 500 mm above head of window or glazed door	not overshadowed
West facing					
W19	2090	900	aluminium, single, clear	solid overhang 3300 mm, 200 mm above head of window or glazed door	not overshadowed
W17	900	700	U-value: 6.6, SHGC: 0.441 - 0.539 (aluminium, single, tint)	eave 200 mm, 600 mm above head of window or glazed door	not overshadowed


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	✓	✓	✓
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 3-phase airconditioning; Energy rating: EER > 4.0		✓	✓
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 3-phase airconditioning; Energy rating: EER > 4.0		✓	✓
The cooling system must provide for day/night zoning between living areas and bedrooms.		✓	✓
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 3-phase airconditioning; Energy rating: EER > 4.0		✓	✓
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 3-phase airconditioning; Energy rating: EER > 4.0		✓	✓
The heating system must provide for day/night zoning between living areas and bedrooms.		✓	✓
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, not ducted; Operation control: manual switch on/off		✓	✓
Kitchen: individual fan, not ducted; Operation control: manual switch on/off		✓	✓
Laundry: natural ventilation only, or no laundry; Operation control: n/a		✓	✓
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
<ul style="list-style-type: none"> at least 4 of the bedrooms / study; dedicated 		✓	✓


Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
<ul style="list-style-type: none"> • at least 5 of the living / dining rooms; dedicated • the kitchen; dedicated • all bathrooms/toilets; dedicated • the laundry; dedicated • all hallways; dedicated 		    	    
Natural lighting			
The applicant must install a window and/or skylight in 4 bathroom(s)/toilet(s) in the development for natural lighting.			
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.			
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.			
The applicant must install a fixed outdoor clothes drying line as part of the development.			

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a  in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a  in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a  in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.