

Precise Planning



Wastewater Assessment: Proposed subdivision application of 95 Great Southern Road, Bargo, NSW

ENVIRONMENTAL



WATER



WASTEWATER



GEOTECHNICAL



CIVIL



PROJECT
MANAGEMENT



P1504741JR07V01
November 2016

Copyright Statement

Martens & Associates Pty Ltd (Publisher) is the owner of the copyright subsisting in this publication. Other than as permitted by the Copyright Act and as outlined in the Terms of Engagement, no part of this report may be reprinted or reproduced or used in any form, copied or transmitted, by any electronic, mechanical, or by other means, now known or hereafter invented (including microcopying, photocopying, recording, recording tape or through electronic information storage and retrieval systems or otherwise), without the prior written permission of Martens & Associates Pty Ltd. Legal action will be taken against any breach of its copyright. This report is available only as book form unless specifically distributed by Martens & Associates in electronic form. No part of it is authorised to be copied, sold, distributed or offered in any other form.

The document may only be used for the purposes for which it was commissioned. Unauthorised use of this document in any form whatsoever is prohibited. Martens & Associates Pty Ltd assumes no responsibility where the document is used for purposes other than those for which it was commissioned.

Limitations Statement

The sole purpose of this report and the associated services performed by Martens & Associates Pty Ltd is provide a water management assessment report in accordance with the scope of services set out in the contract / quotation between Martens & Associates Pty Ltd and Precise Planning (hereafter known as the Client). That scope of works and services were defined by the requests of the Client, by the time and budgetary constraints imposed by the Client, and by the availability of access to the site.

Martens & Associates Pty Ltd derived the data in this report primarily from a number of sources which may include for example site inspections, correspondence regarding the proposal, examination of records in the public domain, interviews with individuals with information about the site or the project, and field explorations conducted on the dates indicated. The passage of time, manifestation of latent conditions or impacts of future events may require further examination / exploration of the site and subsequent data analyses, together with a re-evaluation of the findings, observations and conclusions expressed in this report.

In preparing this report, Martens & Associates Pty Ltd may have relied upon and presumed accurate certain information (or absence thereof) relative to the site. Except as otherwise stated in the report, Martens & Associates Pty Ltd has not attempted to verify the accuracy of completeness of any such information (including for example survey data supplied by others).

The findings, observations and conclusions expressed by Martens & Associates Pty Ltd in this report are not, and should not be considered an opinion concerning the completeness and accuracy of information supplied by others. No warranty or guarantee, whether express or implied, is made with respect to the data reported or to the findings, observations and conclusions expressed in this report. Further, such data, findings and conclusions are based solely upon site conditions, information and drawings supplied by the Client *etc.* in existence at the time of the investigation.

This report has been prepared on behalf of and for the exclusive use of the Client, and is subject to and issued in connection with the provisions of the agreement between Martens & Associates Pty Ltd and the Client. Martens & Associates Pty Ltd accepts no liability or responsibility whatsoever for or in respect of any use of or reliance upon this report by any third party.

© November 2016
Copyright Martens & Associates Pty Ltd
All Rights Reserved

Head Office
Suite 201, 20 George Street
Hornsby, NSW 2077, Australia
ACN 070 240 890 ABN 85 070 240 890
Phone: +61-2-9476-9999
Fax: +61-2-9476-8767
Email: mail@martens.com.au
Web: www.martens.com.au

Document and Distribution Status							
Author(s)		Reviewer(s)		Project Manager		Signature	
Robert Mehaffey		Jeff Fulton		Jeff Fulton			
Revision No.	Description	Status	Release Date	Document Location			
				File Copy	Precise Planning		
1	Development application	FINAL	11/11/16	1P,1E	1P		

Distribution Types: F = Fax, H = hard copy, P = PDF document, E = Other electronic format. Digits indicate number of document copies.

All enquiries regarding this project are to be directed to the Project Manager.

Contents

1 OVERVIEW.....	5
1.1 Background	5
1.2 Development Proposal	5
1.3 Relevant Guidelines/Standards	5
2 SITE DESCRIPTION	6
2.1 Summary	6
2.2 Field Investigations	7
2.3 Sub-Surface Conditions	8
2.4 Climate Data	9
3 WASTEWATER ASSESSMENT	10
3.1 Proposed Treatment System and Design Effluent Quality	10
3.2 Soil Capability Assessment	11
3.3 Land Capability Assessment for Effluent Re-Use	12
3.4 Hydraulic Load Estimations	13
3.5 Effluent Application Rates for Sub-Surface Irrigation	13
3.6 Soil, Water and Nutrient Modelling Summary	14
3.7 Buffer Setbacks for Effluent Reuse Area	14
3.8 Irrigation Requirements	15
3.9 Summary and Recommendations	15
4 REFERENCES	16
5 ATTACHMENT A – FIGURES	17
6 ATTACHMENT B – TEST PIT LOGS	20
7 ATTACHMENT C – NUTRIENT AND WATER BALANCE MODELS	25
8 ATTACHMENT D – LAB RESULTS	28

1 Overview

1.1 Background

Martens & Associates has prepared this wastewater assessment to support an application for a proposed subdivision at 95 Great Southern Road, Bargo, NSW. This report documents a proposed on-site wastewater management strategy for the large lot (>5,000m²) portion of the proposed subdivision, located on the eastern part of the site, as shown in the Zoning Concept Plan in Attachment A.

1.2 Development Proposal

This wastewater assessment has been prepared by MA as a preliminary study based on the understanding that the site will be subdivided into large lots (>5,000m²) with individual wastewater treatment systems servicing future dwellings on each lot. It should be noted that the following wastewater study is calculated based on the assumption of a five bedroom dwelling on future lots. A detailed subdivision layout has not been provided at this stage.

This wastewater assessment is subject to change depending on the size of subdivided lots and dwellings constructed.

1.3 Relevant Guidelines/Standards

The assessment is prepared in accordance with the following guidelines:

- Australian/ New Zealand Standard 1547 (2012) - *On site Domestic Wastewater Management*
- Department of Local Government, NSW Environment Protection Authority, NSW Health Department, NSW Department of Land and Water Conservation and the NSW Department of Urban Affairs and Planning (1998) - *Environment and Health Protection Guidelines - On-site Sewage Management for Single Households*.
- Wollondilly Shire Council (2011) – On-site Sewage Management System and Greywater Re-use Policy

2 Site Description

2.1 Summary

A summarised site description is provided in Table 1. A site plan is provided in Attachment A.

Table 1: Site description summary.

Element	Description/Detail
Site Address	95 Great Southern Road, Bargo, NSW
Site Area	Approximately 28 ha. Area of the proposed large lot development in the eastern part of the site – approximately 8 ha
Lot/DP	Lot 1 DP996286
Existing site development	Rural, unused dilapidated dwelling and sheds.
Aspect	Northwest (in the proposed large lot development area)
Typical slopes	<5% in the vicinity of the proposed development.
Existing vegetation	Grass paddock with scattered trees.
Neighbouring environment	The site is bordered by Great Southern Road to the west, and Government Road to the east. Low density residential housing neighbours the site in the southwest corner. Grass paddocks neighbour the site on all other borders.
Local Government Area (LGA)	Wollondilly Shire Council
Easements	None based on site investigation and review of survey.
Drainage	Drainage occurs above ground along gullies present on site, flowing northeast, eventually leading into Dogtrap Creek (a minimum distance away of approximately 1000 m). One gully runs from south to north from the southern border of the site. The other gully runs from east to west from the eastern border of the site, meeting the first gully.
Groundwater	No groundwater was encountered during borehole or test pit investigations.

Geology	The Wollongong – Port Hacking 1:100,000 Geological Sheet 9029-9129 (1st Edition, 1985) indicates a presence of two underlying geologies at the site: - Hawkesbury Sandstone consisting of medium to coarse grained quartz sandstone, very minor shale and laminate lenses. - Ashfield Shale consisting of laminite and dark grey siltstone.
Soil Landscape	The Wollongong 1:100,000 Soil and land Resource Series (1st edition, 1990) describes two underlying soil landscapes at the site: - Blacktown consisting of shallow to moderately deep (>100 cm) hardsetting mottled texture contrast soils, red and brown podzolic soils on crests grading to yellow podzolic soils on lower slopes and in drainage lines. - Lucas Heights soil landscape consisting of moderately deep (50–150 cm), hardsetting yellow podzolic soils and yellow soloths.

2.2 Field Investigations

A site inspection was undertaken on 2 November 2016 which included:

- Walkover inspection of the eastern portion of the site to assess existing site conditions, local topography, geology, soil characteristics, hydrology and vegetation.
- Excavation of four test pits using an excavator to a maximum depth of 1.4m below ground level (mBGL) to allow for the characterisation of underlying soils and preliminary groundwater level assessment.
- Collection of representative soils samples from test pits for future reference.

Test pit locations are shown on the investigation site plan in Attachment A and detailed soil profiles are provided in Attachment B.

2.3 Sub-Surface Conditions

Test pit observations indicate the natural soil overlying the rock profile is generally comprised of three layers. Soil characteristics are summarised in Table 2 with detailed test pit logs in Attachment B.

Table 2: Summary of typical soil horizon characteristics for the site.

Layer	Depth (m) ¹	Agricultural Classification	Soil Permeability Category ²
TOPSOIL: Loamy Sand	0.0 – 0.15	LS	2a
SUBSOIL: Sandy Clay	0.15 – 0.45	SC	4a
SUBSOIL: Light to Medium Clay	0.45 – 0.9 ³	LMC	5b

Notes:

¹ Depth varies – indicative only.

² In accordance with Table 8 of NSW Department of Local Government *et al.* (NSW DLG, 1998).

³ Average depth to top of weathered rock from 4 test pits undertaken.

2.4 Climate Data

The nearest rainfall station with adequate data is at Buxton (Amaroo, rain station 068166, rainfall 1966 – present) and nearest station with evaporation records is Badgerys Creek (station 61351, 1967-1984 present).

These stations are considered representative of the site. A comparison of median rainfall and evaporation is provided in Table 3.

Table 3: Comparison of rainfall and Class A Pan evaporation data for the site.

Month	Median Monthly Rainfall (mm)	Median Monthly Class A Pan Evaporation (mm)	Rainfall Surplus Rainfall – Evap. (mm)
January	81.30	182.9	-101.6
February	82.30	151.2	-68.9
March	64.40	136.4	-72.0
April	43.10	99.0	-55.9
May	34.20	65.1	-30.9
June	35.60	51.0	-15.4
July	22.20	58.9	-36.7
August	21.00	89.9	-68.9
September	38.80	120.0	-81.2
October	55.80	142.6	-86.6
November	59.50	168.0	-108.5
December	63.00	201.5	-138.5
Annual	602.20	1466.50	-865.1

3 Wastewater Assessment

3.1 Proposed Treatment System and Design Effluent Quality

Each dwelling located on the future lots are to be serviced by a NSW Department of Health (DOH) approved aerated wastewater treatment system (AWTS). The AWTS is to be located to allow gravity drainage of sewage to the AWTS from the dwelling. Typical AWTS effluent quality is provided in Table 4. This information is also used for the nutrient balance assessment.

Table 4: Typical secondary AWTS effluent quality.

Parameter	Design Value
BOD ₅ (mg/L)	20
Suspended Solids (mg/L)	30
Faecal Coliforms (CFU/100mL)	30
Total Phosphorus (mg/L)	10
Total Nitrogen (mg/L)	27

Treated effluent is to be disposed of via surface or shallow surface drip irrigation. Preliminary assessment of required area for each dwelling is discussed in Section 3.8.

3.2 Soil Capability Assessment

Soil capability assessment has previously been completed by MA on a neighbouring site (35 Government Road, Bargo, NSW). A comparison of subsurface conditions with the neighbouring site indicates similar soil profiles and soil chemical properties. Subsequently, soil chemical properties from laboratory analysis at 35 Government Road are considered representative of soils at 95 Great Southern Road and will be used for soil capability assessment.

A summary of soil chemical properties gathered from 35 Government Road are provided in Table 5, with laboratory report provided in Attachment D.

Table 5: Summary of soil assessment according to criteria specified in NSW Department of Local Government *et al.* (1998).

Parameter	Value	Limitations
pH _{CaCl}	4.0 – 4.6	Moderate/Major
EC (dS/m) ¹	0.015	Minor
Sodicity (cmol(+)/kg) ¹	0.42	Minor
CEC (cmol(+)/kg) ¹	15.1	Minor
P-sorption (mg/kg) ¹	688 ²	Minor

Notes:

¹ Values are calculated as a weighted average based on soil layer depths as described in section 2.3

² Equal to P-sorption of 9,292.5 kg/ha for 0.9 m of soil with bulk density 1.5 T/m³

The limitation posed by pH is not considered significant as soils with this pH currently support excellent vegetation growth on the site. Application of treated effluent is not expected to significantly change the soil pH.

3.3 Land Capability Assessment for Effluent Re-Use

Suitability for on-site effluent re-use is assessed according to Tables 4 and 6 of the NSW Department of Local Government *et al.* (NSW DLG *et al.*, 1998) and summarised in Table 6.

Table 6: Site suitability for on-site effluent management systems, according to NSW Department of Local Government *et al.* (1998).

Feature	Details of Irrigation Areas	Limitation Rating
Flood potential	>1 in 20 yr flood level	Minor
Sun and wind exposure	High	Minor
Slope (%)	Typically <10% (in proposed lots)	Minor
Landform	Upper slopes	Minor
Erosion potential	None (in proposed lots)	Minor
Site drainage	No visible signs of surface dampness	Minor
Fill	None observed	Minor
Rock outcrop	<10% (in proposed lots)	Minor
Geology	No major discontinuities	Minor
Depth to bedrock (m)	0.8 – 1.05	Moderate
Depth to water table (m)	>1.0 m	Minor
Soil permeability Category	2a, 4a and 5b	Minor/Moderate
Coarse fragments (%)	Generally 0 – 20%	Minor

Notes:

¹ Estimates based on local experience and soil landscape book.

The land capability assessment revealed most site features represent a minor limitation to effluent disposal. Based on field investigations topsoil and subsoil material is generally suitable for effluent irrigation.

Moderate limitations posed by depth to bedrock and soil permeability categories will be taken into account with water balance and nutrient modelling assessment as discussed in Section 3.6.

3.4 Hydraulic Load Estimations

Design hydraulic load for a typical dwelling development scenario is noted in Table 7 and has been calculated using allowances from Table H1 of AS/NZS 1547 (2012) and two persons for the first bedroom and one person per bedroom thereafter. The proposed development design scenario is based on a five bedroom dwelling. We note that it is assumed the site will be connected to reticulated water supply.

Table 7: Design wastewater loads for option one.

Bedrooms	Design Occupants	Recommended Wastewater Flow Allowance (L/p/d) ¹	Design Wastewater Load (L/day)
5	6	150	900

Notes:

¹ Based on reticulated water supply (Table H1, AS/NZS 1547, 2012).

3.5 Effluent Application Rates for Sub-Surface Irrigation

Soil properties and corresponding recommended design irrigation rates (DIRs) according to Table M1 of AS/NZS 1547 (2012) are given in Table 8.

Table 8: DIR and soil properties for the site.

Soil Category	Depth (m) ¹	Texture	Structure	Indicative Permeability (K _{sat}) (m/d)	Design Irrigation Rate (DIR) (mm/day)
TOPSOIL	0.0 – 0.15	Loamy sand	Weakly structured	>3.0	5
SUBSOIL	0.15 – 0.45	Sandy clay	Moderately structured	0.5 – 1.5	3.5
DESIGN					3.5 ²

Notes:

¹ Depth of soil horizons varies across the site.

² Design irrigation rate based on moderately structured sandy clay.

Based on a daily hydraulic load of 900 L/day and a design irrigation rate of 3.5 mm/day, a design area of 257 m² is required for the primary irrigation field in accordance with AS/NZS 1547 (2012). A reserve area of 257 m² is to be provided for each system.

3.6 Soil, Water and Nutrient Modelling Summary

Details of the model outputs are summarised in Attachment C of this report. Sustainable irrigation areas are summarised in Table 9.

Table 9: Modelling summary: area required for sustainable irrigation.

Parameter	Area Required (m ²)
Water Balance ¹	519
Nitrogen Uptake	443
Phosphorus Saturation	146
AS/NZS 1547:2012	257 (514 including reserve)
Adopted Design Area	519

Notes:

¹ Area where no wet weather storage is required.

² AS/NZS 1547 (2012) recommends that a reserve field of 100% of the primary field area be retained available for use should it be required.

3.7 Buffer Setbacks for Effluent Reuse Area

Irrigation field areas are located with buffers in accordance with AS/NZS 1547 (2012) *Table R1*, with recommended buffers summarised in Table 10.

Table 10: Adopted buffer setbacks in accordance with AS/NZS 1547 (2012).

Site feature	Recommended setback range (m)
Drainage channels	40
Site boundaries, and roads (upslope) ¹	6
Site boundaries, and roads (downslope) ¹	3
Dwellings and buildings	6 ^x / 3 ^y

Notes:

¹. Sub-surface set-back.

^{x/y}. upslope / downslope of the feature.

These buffer setbacks shall be used for subdivision design purposes.

3.8 Irrigation Requirements

Irrigation areas for individual systems are recommended to be either large drop sprinklers (such as wobblers) for surface irrigation, or if subsurface irrigation is to be used, pressure compensating shallow drip irrigation lines with laterals installed parallel to site contours at 1 m intervals in accordance with AS/NZS 1547 (2012). Appropriate delivery mains with non-return valves and flushing lines would need to be installed in the irrigation system.

Where surface irrigation, areas would be required to be fenced off and sign posted to restrict public access. Scattered trees (that are to be retained) in irrigation areas should be managed by appropriate exclusion zones from the base of trunks and careful hand excavations (where subsurface irrigation is used).

3.9 Summary and Recommendations

The proposed wastewater option and irrigation requirements have been assessed against site soil properties and land capability constraints in accordance with relevant guidelines. The proposed option was assessed using nutrient, soil and water balance models provided in Attachment B.

The sustainable area for effluent disposal is 519 m² which is based on water balance requirements, this shall be used as the adopted design area and shall be used for subdivision design purposes.

This assessment is considered preliminary and a more detailed wastewater management assessment is recommended for each lot at dwelling approval stage.

4 References

Australian / New Zealand Standard 1547 (2012), *On-site domestic wastewater management*

Department of Local Government, NSW Environment Protection Authority, NSW Health Department, NSW Department of Land and Water Conservation and the NSW Department of Urban Affairs and Planning (1998), *Environment and Health Protection Guidelines - On-site Sewage Management for Single Households*

NSW Department of Primary Industries, The Wollongong Port Hacking 1:100,000 Geological Series (1985)

NSW Office of Environment and Heritage, Soil Landscapes of the Wollongong-Port Hacking 1:100,000 Sheet Map (1990)

Wollondilly Shire Council (2011) – On-site Sewage Management System and Greywater Re-use Policy

5 **Attachment A – Figures**

ZONING CONCEPT PLAN

MGA GRID BOUNDARY CO.ORDINATES

1:	E: 277 180.050	N: 6 204 416.164
2:	E: 277 182.770	N: 6 204 405.667
3:	E: 277 214.134	N: 6 204 321.096
4:	E: 277 261.670	N: 6 204 184.572
5:	E: 277 279.753	N: 6 204 127.524
6:	E: 277 638.587	N: 6 204 199.697
7:	E: 278 179.885	N: 6 204 306.592
8:	E: 278 121.253	N: 6 204 602.437

WELLERS ROAD

64

DP 736032

63

DP 736032

1

DP 770601

61

DP 167493

ROAD

SOUTHERN

GREAT

ROAD

HAWTHORNE

ANTHONY

ROAD

1
DP 996286

28.28 Ha

44

DP

45

10336

1

DP 213616

2

131

130

DP

1

0

3

3

6

DP

596515

ROAD

GOVERNMENT


1

DP 571589

2

NOTE
PROPOSED SUBDIVISION IS SUBJECT COUNCIL APPROVAL.
ALL BOUNDARIES, DIMENSIONS AND AREAS ARE TO BE
CONFIRMED BY FINAL SURVEY.

FEATURES LEGEND



E2 ENVIRONMENTAL CONSERVATION ZONE
R2 LOW DENSITY RESIDENTIAL ZONE WITH 700m² MINIMUM LOT SIZE
R5 LARGE LOT RESIDENTIAL ZONE WITH 5000m² MINIMUM LOT SIZE


0 50 100 150
METRES
SCALE: 1:1500



**sydney land
surveyors**
Consulting Surveyors

Ph (02) 9967 0511
152 Sailors Bay Road
Northbridge NSW 2063

IN ASSOCIATION WITH:



AustralianSurveySolutions

ABN 54 146 554 555
PO Box 498
BOWRAL 2576 NSW
T: 1300 49 39 79
M: 0417 49 39 79
enquiry@aussurvey.com.au
www.aussurvey.com.au

CLIENT:
Common Ground Property NSW
PROJECT ADDRESS:
95 Great Southern Road, Bargo

L.G.A: Wollondilly

Datum: A.H.D.

Drawing Title:

CONCEPT ZONING PLAN OVER
LOT 1 DP 996286

Surveyed: PB/ RL

Drawn: PB

Approved: PB

Origin: PM 60494

Date Of Survey: 23 JULY 2016

Drawing Number:

190713

Rev: C Size: A1

Scale: 1: 1 500

Sheet : 1 Of 1

REV.	DATE	DESCRIPTION	BY
C	9/11/16	AMEND ZONING	BW
B	7/09/16	AMEND ZONING	BW
A	23/07/16	INITIAL ISSUE	PB



REV	DESCRIPTION	DATE	DRAWN	DESIGNED	CHECKED	APPROVED
A	FOR PSI	9/11/2016	KT	RM		

PRINTED: 9/17/2016 - USER: KJUN

SCALE

0 20 40 60 80 100 120 140 160 180 200

A1 (A3) 1:2,000 (1:4,000) METRES

GRID	DATUM	PROJECT MANAGER
MGA		JF
DISCLAIMER & COPYRIGHT This plan must not be used for construction unless signed as approved by principal certifying authority. All measurements in millimetres unless otherwise specified. This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates Pty Ltd. (C) Copyright Martens & Associates Pty Ltd		

y n	CLIENT	PRECISE PLANNING
	PROJECT NAME/PLANSET TITLE	
	PRELIMINARY SITE INVESTIGATION	95 GREAT SOUTHERN ROAD, BARGO, NSW



Consulting Engineers
Environment
Water
Geotechnical
Civil

Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: www.martens.com.au

DRAWING TITLE				
INVESTIGATION SITE PLAN SOURCE: NEARMAP (2016)				
PROJECT NO.	PLANSET NO.	RELEASE NO.	DRAWING NO.	REVISION
P1504741	PS02	R01	PS02-J100	A

DRAWING ID: P1504741-PS02-R01-J100

6 Attachment B – Test Pit Logs

CLIENT	Precise Planning	COMMENCED	02/11/2016	COMPLETED	02/11/2016	REF TP201 Sheet 1 OF 1 PROJECT NO. P1504741	
PROJECT	Wastewater Assessment	LOGGED	BM/RM	CHECKED	JF		
SITE	95 Great Southern Road, Bargo, NSW	GEOLOGY	Sandstone/Shale	VEGETATION	Grass		
EQUIPMENT	Excavator	EASTING		RL SURFACE	m	DATUM	AHD
EXCAVATION DIMENSIONS	ø600 mm x 1.00 m depth	NORTHING		ASPECT	West	SLOPE	<5%

Excavation					Sampling		Field Material Description				
METHOD	EXCAVATION RESISTANCE	WATER	DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	AG SYMBOL	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	STRUCTURE AND ADDITIONAL OBSERVATIONS
E	Not Encountered			0.15				LS	Loamy SAND, fine, dark brown, with rootlets.		TOPSOIL
								SC	Sandy CLAY, moderately structured, brown/ orange.		RESIDUAL SOIL
				0.45				LMC	Light to medium CLAY, low to medium plasticity, moderately structured, brown/ orange with grey mottles.	D	
				0.80					SANDSTONE, extremely weathered, orange/ red with grey mottles, inferred very low strength.		WEATHERED ROCK
				1.00					Test Pit terminated at 1.00 m (Target depth reached)		1.00: TP terminated on inferred low strength sandstone.
				1.5							

EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS



(C) Copyright Martens & Associates Pty. Ltd.

MARTENS & ASSOCIATES PTY LTD
Suite 201, 20 George St. Hornsby, NSW 2077 Australia
Phone: (02) 9476 9999 Fax: (02) 9476 8767
mail@martens.com.au WEB: http://www.martens.com.au

**Engineering Log -
TEST PIT**

MARTENS 1.01.8 LIB.GLB Log MARTENS BOREHOLE P1504741TP201-TP204.GPJ <<DrawingFile>> 10/11/2016 11:57 8.30.004 Diagonal Lab and In Situ Tool - DGD [Lib: Martens 1.01.8 2016-10-12 Ppt: Martens 1.01.5 2015-12-17]

CLIENT	Precise Planning		COMMENCED	02/11/2016	COMPLETED	02/11/2016	REF TP202						
PROJECT	Wastewater Assessment		LOGGED	BM/RM	CHECKED	JF	Sheet 1 OF 1						
SITE	95 Great Southern Road, Bargo, NSW		GEOLOGY	Sandstone/Shale	VEGETATION	Grass	PROJECT NO. P1504741						
EQUIPMENT	Excavator		EASTING		RL SURFACE	m	DATUM	AHD					
EXCAVATION DIMENSIONS	ø600 mm x 1.40 m depth		NORTHING		ASPECT	West	SLOPE	<5%					
Excavation			Sampling		Field Material Description								
METHOD	EXCAVATION RESISTANCE	WATER	DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	AG SYMBOL	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	CONSISTENCY	DENSITY	STRUCTURE AND ADDITIONAL OBSERVATIONS
E		Not Encountered	0.15					LS	Loamy SAND, fine, dark brown, with rootlets.				TOPSOIL
			0.35					SC	Sandy CLAY, moderately structured, brown/ orange.				RESIDUAL SOIL
			0.90					LMC	Light to medium CLAY, low to medium plasticity, moderately structured, brown/ orange with grey mottles.		D		
			1.40						SHALE, extremely weathered, grey, clay like properties, inferred extremely low strength.				WEATHERED ROCK
			1.5						Test Pit terminated at 1.40 m (Target depth reached)				1.40: TP terminated on inferred low strength shale.
EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS													
 (C) Copyright Martens & Associates Pty. Ltd.					MARTENS & ASSOCIATES PTY LTD Suite 201, 20 George St. Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767 mail@martens.com.au WEB: http://www.martens.com.au					Engineering Log - TEST PIT			

MARTENS 1.01.8 LIB.GLB Log MARTENS BOREHOLE P1504741TP201-TP204.GPJ <<DrawingFile>> 10/11/2016 11:57 8.30.004 Diagonal Lab and In Situ Tool - DGD [Lib: Martens 1.01.8 2016-10-12 Ppt: Martens 1.01.5 2015-12-17]

CLIENT

Precise Planning

COMPLETED

02/11/2016

REF

TP203

PROJECT

Wastewater Assessment

LOGGED

BM/RM

CHECKED

JF

Sheet

1 OF 1

SITE

95 Great Southern Road, Bargo, NSW

GEOLOGY

Sandstone/Shale

VEGETATION

Grass

PROJECT NO.

P1504741

EQUIPMENT

Excavator

EASTING

RL SURFACE

m

DATUM

AHD

EXCAVATION DIMENSIONS

ø600 mm x 1.40 m depth

NORTHING

ASPECT

West

SLOPE

<5%

Excavation

Sampling

Field Material Description

METHOD

EXCAVATION RESISTANCE

WATER

DEPTH (metres)

DEPTH RL

SAMPLE OR FIELD TEST

RECOVERED

GRAPHIC LOG

AG SYMBOL

SOIL/ROCK MATERIAL DESCRIPTION

MOISTURE CONDITION

CONSISTENCY

DENSITY

STRUCTURE AND ADDITIONAL OBSERVATIONS

E

Not Encountered

0.15

0.50

1.00

1.40

1.5

LS

Loamy SAND, fine, dark brown, with rootlets.

SC

Sandy CLAY, moderately structured, brown/ orange.

LMC

Light to medium CLAY, low to medium plasticity, moderately structured, brown/ orange with grey mottles.

SANDSTONE, extremely weathered, orange/ red with grey mottles, inferred very low strength.

D

TOPSOIL

RESIDUAL SOIL

WEATHERED ROCK

Test Pit terminated at 1.40 m (Target depth reached)

1.40: TP terminated on inferred low strength sandstone.

EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS

martens

(C) Copyright Martens & Associates Pty. Ltd.

MARTENS & ASSOCIATES PTY LTD

Suite 201, 20 George St. Hornsby, NSW 2077 Australia

Phone: (02) 9476 9999 Fax: (02) 9476 8767

mail@martens.com.au WEB: http://www.martens.com.au

Engineering Log -

TEST PIT

MARTENS 1.01.8 LIB.GLB Log MARTENS BOREHOLE P1504741TP201-TP204.GPJ <<DrawingFile>> 10/11/2016 11:57 8.30.004 Diapyl Lab and In Situ Tool - DGD [Lib: Martens 1.01.8 2016-10-12 Prg: Martens 1.01.5 2015-12-17

CLIENT

Precise Planning

COMMENCED

02/11/2016

COMPLETED

02/11/2016

REF

TP204

PROJECT

Wastewater Assessment

LOGGED

BM/RM

CHECKED

JF

Sheet

1 OF 1

SITE

95 Great Southern Road, Bargo, NSW

GEOLOGY

Sandstone/Shale

VEGETATION

Grass

PROJECT NO.

P1504741

EQUIPMENT

Excavator

EASTING

RL SURFACE

m

DATUM

AHD

EXCAVATION DIMENSIONS

ø600 mm x 1.25 m depth

NORTHING

ASPECT

West

SLOPE

<5%

Excavation

Sampling

Field Material Description

METHOD

E

EXCAVATION RESISTANCE

WATER

Not Encountered

DEPTH (metres)

DEPTH RL

0.10

SAMPLE OR FIELD TEST

RECOVERED

GRAPHIC LOG

AG SYMBOL

LS

SOIL/ROCK MATERIAL DESCRIPTION

Loamy SAND, fine, dark brown, with rootlets.

MOISTURE CONDITION

CONSISTENCY

STRUCTURE AND ADDITIONAL OBSERVATIONS

TOPSOIL

DEPTH RL

0.50

SAMPLE OR FIELD TEST

RECOVERED

GRAPHIC LOG

AG SYMBOL

SC

SOIL/ROCK MATERIAL DESCRIPTION

Sandy CLAY, moderately structured, brown/ orange.

MOISTURE CONDITION

CONSISTENCY

STRUCTURE AND ADDITIONAL OBSERVATIONS

RESIDUAL SOIL

DEPTH RL

1.05

SAMPLE OR FIELD TEST

RECOVERED

GRAPHIC LOG

AG SYMBOL

LMC

SOIL/ROCK MATERIAL DESCRIPTION

Light to medium CLAY, low to medium plasticity, moderately structured, brown/ orange with grey mottles.

MOISTURE CONDITION

CONSISTENCY

STRUCTURE AND ADDITIONAL OBSERVATIONS

DEPTH RL

1.25

SAMPLE OR FIELD TEST

RECOVERED

GRAPHIC LOG

AG SYMBOL

SOIL/ROCK MATERIAL DESCRIPTION

SANDSTONE, extremely weathered, orange/ red with grey mottles, inferred very low strength.

MOISTURE CONDITION

CONSISTENCY

STRUCTURE AND ADDITIONAL OBSERVATIONS

WEATHERED ROCK

DEPTH RL

1.5

SAMPLE OR FIELD TEST

RECOVERED

GRAPHIC LOG

AG SYMBOL

SOIL/ROCK MATERIAL DESCRIPTION

Test Pit terminated at 1.25 m (Target depth reached)

MOISTURE CONDITION

CONSISTENCY

STRUCTURE AND ADDITIONAL OBSERVATIONS

1.25: TP terminated on inferred low strength sandstone.

EXCAVATION LOG TO BE READ IN CONJUNCTION WITH ACCOMPANYING REPORT NOTES AND ABBREVIATIONS

martens

(C) Copyright Martens & Associates Pty. Ltd.

MARTENS & ASSOCIATES PTY LTD

Suite 201, 20 George St. Hornsby, NSW 2077 Australia

Phone: (02) 9476 9999 Fax: (02) 9476 8767

mail@martens.com.au WEB: http://www.martens.com.au

Engineering Log -

TEST PIT

MARTENS 1.01.8 LIB.GLB Log MARTENS BOREHOLE P1504741TP201-TP204.GPJ <<DrawingFile>> 10/11/2016 11:57 8.30.004 D:\gel Lab and In Situ Tool - DGD [Lib: Martens 1.01.8 2016-10-12 Prg: Martens 1.01.5 2015-12-17

7 **Attachment C – Nutrient and Water Balance Models**

Effluent Disposal Field - Annual Nutrient Balance Assessment

Method ST-14 Revised 20.3.2007



6/37 Leighton Place, Hornsby, NSW 2077, Ph: (02) 9476 999 Fax: (02) 9476 8767, mail@martens.com.au, www.martens.com.au

PROJECT DETAILS

Project

95 Great Southern Road, Bargo, NSW

Ref. No.

P1504741

Author

RM

Reviewed

JF

Date Created

4/11/2016

STEP 1 : ENTER SITE AND FIELD CHARACTERISTICS


FACTOR	Enter Data	Unit	
Treatment System	AWTS	-	
Effluent flow rate	900	L/day	
Effluent N	27.0	mg/L	
Effluent P	10.0	mg/L	
Design soil depth	0.90	m	
Soil P-sorption	344.0	mg/kg	50% of P-sorption value is used as a conservative measure as per DLG et al. (1998)
Plant N uptake	200.0	kg/ha/year	
Plant P uptake	20.0	kg/ha/year	

STEP 2 : ASSESSMENT

NITROGEN BUDGET FOR RE-USE FIELD		
N generated	8.87	kg/year
N consumed	8.87	kg/year
N balance	0.00	kg/year
Min Area	443	m ²

PHOSPHORUS BUDGET FOR RE-USE FIELD		
P generated	3.29	kg/year
P consumed	0.54	kg/year
P balance	2.75	kg/year
P sorption	137.4	kg P/design soil depth
Field life (for P)	50.0	Years
Min Area	269	m ²

MINIMUM NUTRIENT ASSIMILATION AREA		
Minimum Area	443	m ²



Effluent Disposal Field - Water Balance Assessment

Method 51XX Revised 11.8.2010



6/27 Leighton Place, Hornsby, NSW 2077, Ph: (02) 9476 9999 Fax: (02) 9476 6767, mail@martens.com.au, www.martens.com.au

PROJECT DETAILS

Project

95 Great Southern Rd, Bargo, NSW

Author

RM

Reviewed

JF

Ref. No.

P1504741

Date Created

7/11/2016

STEP 1 : ENTER SITE AND FIELD CHARACTERISTICS

FACTOR

Enter Data

Unit

Notes

Runoff Factor - RF

0.35

%

Daily Effluent Load - DEL

900

L

- Based on 1000L/day

Effluent Disposal Area - A

619.0

m²

Design Percolation Rate (DPR)

1.4

mm/day

Design Irrigation Rate - DIR

1.7

mm/day

Wet-Weather Storage (Kl)

6.0

STEP 2 : ENTER CLIMATE DATA

Source(s):

Evaporation data - Bodderys Creek (D61351) 1967 - 1984

Rainfall data - Baulkham Hills (Amara) NSW (D68166) 1966 - 2013

MONTHLY RAINFALL (mm)

MONTHLY EVAPORATION (mm)

MONTH

Enter Data

Enter Data

JAN

81.30

182.90

FEB

82.30

151.20

MARCH

64.40

136.40

APRIL

43.10

99.00

MAY

34.20

65.10

JUNE

35.60

51.00

JULY

22.20

58.90

AUG

21.00

89.90

SEPT

38.80

120.00

OCT

55.80

142.60

NOV

59.50

168.00

DEC

63.00

201.50

Intensity (mm/month)

Intensity (mm/month)

JAN

FEB

MARCH

APRIL

MAY

JUNE

JULY

AUG

SEPT

OCT

NOV

DEC

STEP 3 : ASSESSMENT

MONTH	NUMBER OF DAYS	MONTHLY RAINFALL (mm)	RETAINED RAINFALL	MONTHLY EVAPORATION	CROP FACTOR	EVAPO-TRANSPIRATION RATE	DESIGN PERCOLATION	AVAILABLE IRRIGATION CAPACITY	EFFLUENT APPLIED	APPLICATION RATE	INCREASE IN PONDING DEPTH OF EFFLUENT	CUMULATIVE PONDING DEPTH OF EFFLUENT FROM PREVIOUS MONTH	DEPTH OF EFFLUENT	PONDING DEPTH OF EFFLUENT	WET-WEATHER STORAGE REQUIRED
-	(days)	(mm/month)	(mm/month)	(mm/month)	-	(mm/month)	(mm/day)	(mm/month)	(L/month)	(mm/month)	(mm)	(mm)	(mm/month)	(mm)	(Kl)
-	DAY	R	RR = R x (1 - RF)	E	CF	ETR = E x CF	DP = DPR x DAYS	AIC = ETR - RR + DP	EA = DEL x DAY	AR = EA / A	D = (AIC - AR)	CPD = PD from previous month	DE = D + CPD	PD	WWS
JAN	31	81.30	52.8	182.90	0.80	146.3	43.4	136.9	27900	53.8	-83.1	0.0	-83.1	0.0	0.0
FEB	28	82.30	53.5	151.20	0.80	121.0	39.2	106.7	25200	48.6	-58.1	0.0	-58.1	0.0	0.0
MARCH	31	64.40	41.9	136.40	0.80	109.1	43.4	110.7	27900	53.8	-56.9	0.0	-56.9	0.0	0.0
APRIL	30	43.10	28.0	99.00	0.80	79.2	42.0	93.2	27000	52.0	-41.2	0.0	-41.2	0.0	0.0
MAY	31	34.20	22.2	65.10	0.65	42.3	43.4	63.5	27900	53.8	-9.7	0.0	-9.7	0.0	0.0
JUNE	30	35.60	23.1	51.00	0.65	33.2	42.0	52.0	27000	52.0	0.0	0.0	0.0	0.0	0.0
JULY	31	22.20	14.4	58.90	0.65	38.3	43.4	67.3	27900	53.8	-13.5	0.0	-13.5	0.0	0.0
AUG	31	21.00	13.7	89.90	0.65	58.4	43.4	88.2	27900	53.8	-34.4	0.0	-34.4	0.0	0.0
SEPT	30	38.80	25.2	120.00	0.80	96.0	42.0	112.8	27000	52.0	-60.8	0.0	-60.8	0.0	0.0
OCT	31	55.80	36.3	142.60	0.80	114.1	43.4	121.2	27900	53.8	-67.5	0.0	-67.5	0.0	0.0
NOV	30	59.50	38.7	168.00	0.80	134.4	42.0	137.7	27000	52.0	-85.7	0.0	-85.7	0.0	0.0
DEC	31	63.00	41.0	201.50	0.80	161.2	43.4	163.7	27900	53.8	-109.9	0.0	-109.9	0.0	0.0

8 **Attachment D – Lab Results**



SOIL TEST REPORT

Page 1 of 2

Scone Research Centre

REPORT NO: SCO15/250R1

REPORT TO: Grant Taylor
Martens & Associates Pty Ltd
Suite 201, 20 George St
Hornsby NSW 2159

REPORT ON: Four soil samples
Your Ref: P1504741
15 Government Road, Bargo, NSW

PRELIMINARY RESULTS
ISSUED: Not issued

REPORT STATUS: Final

DATE REPORTED: 27 January 2016

METHODS: Information on test procedures can be obtained from Scone
Research Centre

TESTING CARRIED OUT ON SAMPLE AS RECEIVED
THIS DOCUMENT MAY NOT BE REPRODUCED EXCEPT IN FULL

SR Young
(Laboratory Manager)

SOIL CONSERVATION SERVICE
Scone Research Centre


Page 2 of 2

Report No: SCO15/250R1
 Client Reference: Grant Taylor
 Martens & Associates Pty Ltd
 Suite 201, 20 George St
 Hornsby NSW 2159

Lab No	Method	C1A/5	C2A/4	C2B/4	C5A/4 CEC & exchangeable cations (cmol (+)/kg)						C5A/4	C8B/1	P9B/2
	Sample Id	EC (dS/m)	pH	pH (CaCl ₂)	CEC	Na	K	Ca	Mg	Al	ESP (%)	P sorp (mg/kg)	EAT
1	4741/102/0.4-0.5/S/01	0.02	5.8	4.3	14.3	0.5	0.1	0.5	3.9	5.7	4.8	650	5
2	4741/103/0.1/S/01	0.01	5.5	4.6	8.8	0.1	0.1	1.2	2.3	1.2	1.8	660	5
3	4741/103/0.3-0.4/S/01	0.01	5.5	4.0	19.5	0.4	0.1	0.4	4.2	12.0	2.3	750	5
4	4741/104/0.15/S/01	<0.01	6.0	4.6	8.2	0.3	<0.1	1.8	2.7	1.1	5.0	700	5

Lab No	Method	P18B/3 (%) Available water capacity		
	Sample Id	FC (0.3 bar)	WP (15 bar)	AWC
1	4741/102/0.4-0.5/S/01	25	11	14
2	4741/103/0.1/S/01	28	10	18
3	4741/103/0.3-0.4/S/01	27	17	10
4	4741/104/0.15/S/01	31	12	19

Field capacity (FC), wilting point (WP) and available water capacity (AWC) = moisture content (%) by weight



END OF TEST REPORT