Precise Planning

Preliminary Flood Study: 45 Noongah Street and 25 Gwynn Hughes Street, Bargo, NSW



ENVIRONMENTAL







WASTEWATER







CIVIL



PROJECT MANAGEMENT



P1504816JR04V01 July 2015

Copyright Statement

Martens & Associates Pty Ltd (Publisher) is the owner of the copyright subsisting in this publication. Other than as permitted by the Copyright Act and as outlined in the Terms of Engagement, no part of this report may be reprinted or reproduced or used in any form, copied or transmitted, by any electronic, mechanical, or by other means, now known or hereafter invented (including microcopying, photocopying, recording, recording tape or through electronic information storage and retrieval systems or otherwise), without the prior written permission of Martens & Associates Pty Ltd. Legal action will be taken against any breach of its copyright. This report is available only as book form unless specifically distributed by Martens & Associates in electronic form. No part of it is authorised to be copied, sold, distributed or offered in any other form.

The document may only be used for the purposes for which it was commissioned. Unauthorised use of this document in any form whatsoever is prohibited. Martens & Associates Pty Ltd assumes no responsibility where the document is used for purposes other than those for which it was commissioned.

Limitations Statement

The sole purpose of this report and the associated services performed by Martens & Associates Pty Ltd is to provide a preliminary flood assessment at the subject site in accordance with the scope of services set out in the contract / quotation between Martens & Associates Pty Ltd and Precise Planning (hereafter known as the Client). That scope of works and services were defined by the requests of the Client, by the time and budgetary constraints imposed by the Client, and by the availability of access to the site.

Martens & Associates Pty Ltd derived the data in this report primarily from a number of sources which included site inspections, correspondence regarding the proposal, examination of records in the public domain, interviews with individuals with information about the site or the project, and field explorations conducted on the dates indicated. The passage of time, manifestation of latent conditions or impacts of future events may require further examination / exploration of the site and subsequent data analyses, together with a re-evaluation of the findings, observations and conclusions expressed in this report.

In preparing this report, Martens & Associates Pty Ltd may have relied upon and presumed accurate certain information (or absence thereof) relative to the site. Except as otherwise stated in the report, Martens & Associates Pty Ltd has not attempted to verify the accuracy of completeness of any such information (including for example survey data supplied by others).

The findings, observations and conclusions expressed by Martens & Associates Pty Ltd in this report are not, and should not be considered an opinion concerning the completeness and accuracy of information supplied by others. No warranty or guarantee, whether express or implied, is made with respect to the data reported or to the findings, observations and conclusions expressed in this report. Further, such data, findings and conclusions are based solely upon site conditions, information and drawings supplied by the Client *etc.* in existence at the time of the investigation.

This report has been prepared on behalf of and for the exclusive use of the Client, and is subject to and issued in connection with the provisions of the agreement between Martens & Associates Pty Ltd and the Client. Martens & Associates Pty Ltd accepts no liability or responsibility whatsoever for or in respect of any use of or reliance upon this report by any third party.



© July 2015 Copyright Martens & Associates Pty Ltd All Rights Reserved

Head Office

Suite 201, 20 George Street, Hornsby, NSW 2077, Australia ACN 070 240 890 ABN 85 070 240 890 **Phone: +61-2-9476-9999** Fax: +61-2-9476-8767 Email: mail@martens.com.au Web: www.martens.com.au

	Document and Distribution Status								
Author(s)			Reviewer(s)		Project Manager		Signature		
Ben Ling		Jeffrey Fulton Daniel Marter		Jeffrey Fulton		Courton			
					Documen	t Location			
Revision No.	Status	Release Date	File Copy	Precise Planning					
1	Draft	07.07.15	1P, 1H	1P					

Distribution Types: F = Fax, H = hard copy, P = PDF document, E = Other electronic format. Digits indicate number of document copies.

All enquiries regarding this project are to be directed to the Project Manager.



Contents

1	INTRODUCTION	5
1.1	Overview	5
1.2	Project Scope	5
1.3	Relevant Guidelines	5
2	HYDROLOGY MODELLING	6
2.1	Overview	6
2.2	Modelling Set-up	6
3	HYDRAULIC MODELLING	9
3.1	Overview	9
3.2	Topographic Data	9
3.3	Modelling Set-up	9
3.4	Results 1	0
4	REFERENCES 1	1
5	ATTACHMENT A: CATCHMENT PLAN & EXISTING SITE SURVEY 1	2
6	ATTACHMENT B: DRAINS MODEL LAYOUT AND RESULTS 1	5
7	ATTACHMENT C: FLOOD IMAGES 1	8



1 Introduction

1.1 Overview

Martens & Associates Pty Ltd has prepared this preliminary flood study to assess the flood extent and impact on the site known as 45 Noongah Street and 25 Gwynn Hughes Street, Bargo, NSW. This report has been prepared to support a proposed rezoning application for this site.

This report assesses the 1% Annual Exceedance Probability (AEP) and the Probable Maximum Flood (PMF) flood planning level.

1.2 Project Scope

Project scope and objectives are:

- 1. Prepare a hydrologic model (DRAINS) for the site to determine the peak flows for the 1% AEP and the PMF storm events.
- 2. Prepare a hydraulic model (1D/2D SMS Tuflow) for the site under existing conditions for the 1% AEP and the PMF.
- 3. Prepare relevant flood maps including flood extents and levels.

1.3 Relevant Guidelines

This report has been prepared in accordance with the following guidelines and policies:

- Institution of Engineers, Australia (2006) Australian Rainfall and Runoff.
- Wollondilly Council (2008) Stormwater Drainage Design "Design Specification D5".
- Wollondilly Shire Council (2010) 'Development Control Plan 2010';
- Wollondilly Shire Council (2008) 'Design Specifications: Sub-Division and Engineering Standards'.
- NSW Floodplain development manual (2005).



2 Hydrology Modelling

2.1 Overview

The DRAINS software package (version 2015.02 – 4 February 2015) was used with the RAFTS hydrological engine to assess the 1% AEP and the PMF peak flow rates for a range of storm durations between 5 mins and 4.5 hours.

2.2 Modelling Set-up

2.2.1 Hydrological Model parameters

The RAFTS (storage routing) engine was used given the rural nature of the site and upslope sub-catchments. Parameters used in the model are based on figures given in Wollondilly Shire Council (2008) Engineering Design Specifications, and are shown in Table 1.

Parameter	Element	Value
IFD Data	2 year ARI 1 hour rainfall intensity ¹	32.0
	2 year ARI 12 hour rainfall intensity ¹	7.7
	2 year ARI 72 hour rainfall intensity ¹	2.2
	50 year ARI 1 hour rainfall intensity ¹	65.3
	50 year ARI 12 hour rainfall intensity ¹	15.3
	50 year ARI 72 hour rainfall intensity ¹	4.8
	G (skewness factor) ²	0.02
	F2 ²	4.29
	F50 ²	15.75
Soil Properties	Impervious Area Initial Losses	0.0
	Impervious Area Continuous Losses	0.0
	Pervious Area Initial Losses	10.0
	Pervious Area Continuous Losses	2.5

 Table 1: Hydrologic modelling setup.

Notes:

¹ - Figures for Bargo from Wollondilly Shire Council (2008) Engineering Design Specification D5 - Drainage Design.

² - Typical figures for Bargo given in Engineers Australia (2006).

2.2.2 Sub-Catchment Properties

Sub-catchments used in the modelling were based on available topographic data provided by LPI and confirmed by site observations. Impervious area proportions were based on available aerial



photography. Sub-catchment boundaries used for modelling are provided in Attachment A. Catchment parameters are summarised below in Table 2.

Sub- Catchment	Area (ha)	Impervious (%)	Vectored Slope (%)	PERN Roughness
CAT 1	620.10	5	3	0.07
CAT 2	98.80	5	2.5	0.07
CAT 3	18.51	1	2.1	0.07
CAT 4	14.50	80	2.1	0.07
CAT 5	31.70	90	2	0.015
CAT 6A11	3.34	0	1.5	0.07
CAT 6A21	55.20	2.4	1.9	0.07
CAT 6A31	120.12	5.7	2.6	0.07
CAT 6B11	2.31	0	1.9	0.07
CAT 6B21	92.48	10.2	1.2	0.07
CAT 6B31	86.30	5	2.2	0.07
SITE	20.65	5	2.2	0.03

 Table 2:
 Details of catchments in RAFTS hydrological modelling.

Notes:

¹ – Catchment details taken from previous modelling performed for 1A Kader Street, Bargo rezoning.

2.2.3 Results

DRAINS modelling results indicated that storm durations of 2 hours and 3 hours resulted in peak critical flows. Cat 1 produces its peak critical flow during the 3 hour storm, while the other catchments produce their peak critical flows during the 2 hour storm.

Results of peak flow rates for each catchment for the 1% AEP and PMF storms are summarised in Table 3.



Sub- Catchment	Storm Event	Duration (Hrs)	Peak Flow (m³/s)
CAT 1	1% AEP	2	55.51
CAT 2	1% AEP	2	12.26
CAT 3	1% AEP	2	2.52
CAT 4	1% AEP	2	6.39
CAT 5	1% AEP	2	18.01
OF 61	1% AEP	2	41.47
SITE	1% AEP	2	5.61
CAT 1	1% AEP	3	58.54
CAT 2	1% AEP	3	11.82
CAT 3	1% AEP	3	2.40
CAT 4	1% AEP	3	4.36
CAT 5	1% AEP	3	9.68
OF 6 ¹	1% AEP	3	40.66
SITE	1% AEP	3	4.54
CAT 1	PMF	2	334.60
CAT 2	PMF	2	60.76
CAT 3	PMF	2	11.89
CAT 4	PMF	2	11.55
CAT 5	PMF	2	25.64
OF 61	PMF	2	215.01
SITE	PMF	2	15.25
CAT 1	PMF	3	310.74
CAT 2	PMF	3	54.97
CAT 3	PMF	3	10.58
CAT 4	PMF	3	9.66
CAT 5	PMF	3	22.12
OF 6 ¹	PMF	3	193.81
SITE	PMF	3	12.55
Notes:			

Table 3: Details of catchments in RAFTS hydrological mod
--

Notes:

¹ - OF6 refers to the cumulative flow generated by sub-catchments 6A1, 6A2, 6A3, 6B1, 6B2 and 6B3.



3 Hydraulic Modelling

3.1 Overview

The SMS Tuflow 1D/2D hydraulic model (SMS 11.2.9 13 Mar 2015) was used to determine existing condition flood water levels and extents for the 1% AEP and PMF storm events.

3.2 Topographic Data

2m topographic data provided by LPI was used to create a 3D surface for the site and the local floodplain environment used in the Tuflow model.

3.3 Modelling Set-up

Tuflow model construction consisted of:

- 1. Development of a 2.0m x 2.0m topographic grid for the 1% AEP storm event simulation, and a 4.0m x 4.0m topographic grid for the PMF storm event simulation.
- 2. Position inflow boundary conditions based on the 1% AEP critical storm duration and the PMF DRAINS model hydrographs.
- 3. Establishment of model boundary extents.
- 4. A 2% computed water slope for the downstream model boundary extent was defined, based on the floodplain slopes of the available topographic data.
- 5. Assigning manning's roughness coefficients based on SIX Maps Viewer Aerials (2014) for hydraulic modelling as shown in Table 4.
- 6. Incorporation of blockages to simulate existing buildings.

 Table 4: Mannings roughness coefficients used in SMS Tuflow modelling.

Catchment Material	Manning's Roughness Applied
Building	0.2
Forest Riparian	0.07
Grassed	0.035
Road	0.012
Urban	0.1



3.4 Results

Results of flood levels and extents for the 1% AEP and PMF critical storm events for existing conditions are given in Attachment C.



4 References

Institution of Engineers, Australia (2006) – Australian Rainfall and Runoff

Land and Property Information NSW (2014) – SIX Maps Viewer

NSW Floodplain development manual (2005).

O'Loughlin, G., Stack, B., (2014) - DRAINS User Manual

Wollondilly Council (2008) – Stormwater Drainage Design "Design Specification D5".

Wollondilly Shire Council (2010) 'Development Control Plan 2010';

Wollondilly Shire Council (2008) 'Design Specifications: Sub-Division and Engineering Standards'.



5 Attachment A: Catchment Plan & Existing Site Survey





REV.	DESCRIPTION	DATE	ISSUED	BAR SCAL	.E						
А	FOR REZONING	07.07.2015	JF								
] (0	250	500	750	1000	1250	150
							UNIT	S - MET	RES		
				-							
				This drawing	must not	be reproduce	(C) Copyright N ed in whole or pa	lartens & Asso art without prio	ciates Pty Ltd r written consent	of Martens & A	Associates

	DESIGNED:	DATUM:	
	BL	mAHD	
)	REVIEWED:	HORIZONTAL RATIO:	
	JF	1:15000	
	PAPER SIZE:	VERTICAL RATIO:	
Pty Ltd	A1	1:15000	

CLIENT / PROJECT Preliminary Flood Study: 45 Noongah Street and 25 Gwynn Hughes Street, Bargo, NSW



Consulting Engineers Environment Water Geotechnical Civil

 THIS PLAN MUST NOT BE USED FOR CONSTRUCTION UNLESS

 SIGNED AS APPROVED BY PRINCIPAL CERTIFYING AUTHORITY

 All measurements in mm unless otherwise specified

Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: http://www.martens.com.au



TITLE:

CATCHMENT PLAN

DRAWING ID:



PROJECT MANAGER: JF

PROJECT NO .: P1504816

FILE: JD02V01 **REVISION**: А



Consulting	Engineers
Environment	
Water	
Geotechnical	
Civil	

DESIGNED:	DATUM:
BL	mAHD
REVIEWED:	HORIZONTAL RATI
JF	1:1500
PAPER SIZE:	VERTICAL RATIO:
A1	1:1500



6 Attachment B: DRAINS Model layout and results











MODEL LAYOUT

REV.	DESCRIPTION	DATE	ISSUED	BAR SCALE
А	FOR REZONING	07.07.2015	JF	
				0 250 500 750 1000 1250 1500
				(C) Copyright Martens & Associates Pty Ltd This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates Pty Ltd





2 HOUR STORM EVENT

DESIGNED:	DATUM:	
BL	mAHD	
REVIEWED:	HORIZONTAL RATIO:	
JF	1:20000	
JF PAPER SIZE:	1:20000 VERTICAL RATIO:	-

CLIENT / PROJECT Preliminary Flood Study: 45 Noongah Street and 25 Gwynn Hughes Street, Bargo, NSW



7 Attachment C: Flood Images





REV.	DESCRIPTION	DATE	ISSUED	BAR SCALE						
А	FOR REZONING	07.07.2015	JF							
				0	25	50	75	100	125	150
				UNITS - METRES						
				 (C) Copyright Martens & Associates Pty Ltd This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates 						

	DESIGNED:	DATUM:	
	BL	mAHD	
50	REVIEWED:	HORIZONTAL RATIO:	
	JF	1:1500	
	PAPER SIZE:	VERTICAL RATIO:	
es Pty Ltd	A1	1:1500	

CLIENT / PROJECT Preliminary Flood Study: 45 Noongah Street and 25 Gwynn Hughes Street, Bargo, NSW



Consulting Engineers Environment Water Geotechnical Civil

 THIS PLAN MUST NOT BE USED FOR CONSTRUCTION UNLESS

 SIGNED AS APPROVED BY PRINCIPAL CERTIFYING AUTHORITY

 All measurements in mm unless otherwise specified

Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: http://www.martens.com.au



TITLE:

1% AEP CRITICAL STORM: TUFLOW MODEL MAP RESULT

DRAWING ID:

SK201

PROJECT MANAGER: JF

PROJECT NO .: P1504816

FILE: JD02V01

REVISION: А



REV.	DESCRIPTION	DATE	ISSUED	BAR SCAL	LE						
А	FOR REZONING	07.07.2015	JF								
				(0	25	50	75	100	125	15
				-							
				UNITS - METRES							
							(C) Copyright	Vartons & Asso	ciatos Dtv I td		
				 (C) Copyright Martens & Associates Pty Ltd This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates 							

	DESIGNED:	DATUM:	
	BL	mAHD	
50	REVIEWED:	HORIZONTAL RATIO:	
	JF	1:1500	
	PAPER SIZE:	VERTICAL RATIO:	
es Pty Ltd	A1	1:1500	

CLIENT / PROJECT Preliminary Flood Study: 45 Noongah Street and 25 Gwynn Hughes Street, Bargo, NSW



Consulting Engineers Environment Water Geotechnical Civil

 THIS PLAN MUST NOT BE USED FOR CONSTRUCTION UNLESS

 SIGNED AS APPROVED BY PRINCIPAL CERTIFYING AUTHORITY

 All measurements in mm unless otherwise specified

Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: http://www.martens.com.au



TITLE:

PMF CRITICAL STORM: TUFLOW MODEL MAP RESULT

DRAWING ID:

SK202

PROJECT MANAGER: JF

PROJECT NO .: P1504816

FILE: JD02V01

REVISION: А