



**MASTERPLAN TRAFFIC AND PARKING IMPACT ASSESSMENT OF  
THE PROPOSED MIXED USE DEVELOPMENT  
AT 13 ENDEAVOUR ROAD, CARINGBAH**



**Address: Shop 7, 720 Old Princes Highway Sutherland NSW 2232  
Postal: P.O Box 66 Sutherland NSW 1499**

**Telephone: +61 2 8355 2440  
Fax: +61 2 9521 7199  
Web: [www.mclarentraffic.com.au](http://www.mclarentraffic.com.au)  
Email: [admin@mclarentraffic.com.au](mailto:admin@mclarentraffic.com.au)**

**Division of RAMTRANS Australia ABN: 45067491678 RPEQ: 19457**

**Transport Planning, Traffic Impact Assessments, Road Safety Audits, Expert Witness**

**Development Type:**           **Mixed Use Development**

**Site Address:**               **13 Endeavour Road, Caringbah**

**Prepared for:**               **Aliro Group**

**Document reference:**       **200318.01FA**

Status	Issue	Prepared By	Checked By	Date
Draft	A	TM / MM / ME	CM	28 <sup>th</sup> August 2020
Draft	B	MM	CM	2 <sup>nd</sup> September 2020
Draft	C	MM	CM	15 <sup>th</sup> September 2020
Final	A	MM	CM	17 <sup>th</sup> September 2020

Please be aware that all information and material contained in this report is the property of McLaren Traffic Engineering. The information contained in this document is confidential and intended solely for the use of the client for the purpose for which it has been prepared and no representation is made or if to be implied as being made to any third party. Any third party wishing to distribute this document in whole or in part for personal or commercial use must obtain written confirmation from McLaren Traffic Engineering prior to doing so. Failure to obtain written permission may constitute an infringement of copyright and may be liable for legal action.

## TABLE OF CONTENTS

<b>1</b>	<b>INTRODUCTION .....</b>	<b>1</b>
1.1	Description and Scale of Development .....	1
1.2	State Environmental Planning Policy (Infrastructure) 2007 .....	2
1.3	Site Description.....	2
1.4	Site Context .....	2
<b>2</b>	<b>EXISTING TRAFFIC AND PARKING CONDITIONS .....</b>	<b>4</b>
2.1	Road Hierarchy .....	4
2.1.1	Captain Cook Drive - West of Gannons Road .....	4
2.1.2	Captain Cook Drive - East of Gannons Road .....	4
2.1.3	Gannons Road .....	4
2.1.4	Endeavour Road.....	5
2.2	Existing Traffic Management .....	5
2.3	Existing Traffic Volumes .....	5
2.3.1	Existing Road Performance .....	6
2.3.2	Existing Approved Road Environment .....	8
2.4	Public Transport.....	10
2.4.1	Pedestrian & Cycling Facilities .....	11
2.5	Future Road and Infrastructure Upgrades .....	13
<b>3</b>	<b>PARKING ASSESSMENT .....</b>	<b>17</b>
3.1	Car Parking Provision .....	17
3.2	Disabled Car Parking .....	19
3.3	Motorcycle Parking Requirements.....	19
3.4	Bicycle Parking Requirements.....	20
3.5	Servicing & Loading .....	20
3.6	Vehicle Access & Parking / Loading .....	22
<b>4</b>	<b>TRAFFIC ASSESSMENT .....</b>	<b>23</b>
4.1	Traffic Generation .....	23
4.2	Trip Assignment .....	26
4.3	Access Scenarios .....	26
4.4	Traffic Impact .....	28
4.4.1	Scenario 1 .....	28
4.4.2	Scenario 2 .....	29
4.4.3	Scenario 3 .....	30
4.4.4	Scenario 4 .....	33
4.4.5	Summary of Findings.....	35
4.4.6	Impacts of Road Infrastructure .....	38
<b>5</b>	<b>CONCLUSION .....</b>	<b>40</b>

# 1 INTRODUCTION

McLaren Traffic Engineering was commissioned by Aliro Group to provide a Masterplan Traffic and Parking Impact Assessment of the proposed Mixed Use Development at 13 Endeavour Road, Caringbah as depicted in **Annexure A** for reference. The subject site was previously operated by Toyota, with the existing site now operationally redundant and will be replaced with future development, the subject of this masterplan report.

It may be necessary to undertake further traffic modelling along the corridor of Captain Cook Drive in consultation with the relevant road authorities (Transport for New South Wales and Sutherland Shire Council) for areas that are not covered within this report.

## 1.1 Description and Scale of Development

The proposed masterplan development consists of a variety of land uses which will be assessed to have the following scale relevant to this traffic and parking report as shown in **Table 1**.

**TABLE 1: PROPOSED MASTERPLAN SCALE**

Land Use	Masterplan Scale
Industrial	25,272m <sup>2</sup> GFA
Ancillary Industrial Office	7,382m <sup>2</sup> GFA
Warehouse	1,824m <sup>2</sup> GFA
Ancillary Warehouse Office	3,846m <sup>2</sup> GFA
Commercial Office & Business Premises	99,286m <sup>2</sup> GFA
Retail	4,307m <sup>2</sup> GFA
Food and Beverage	3,561m <sup>2</sup> GFA
Recreation	860m <sup>2</sup>
Hotel	3,624m <sup>2</sup> GFA 125 rooms & 20 staff

It should be noted that the assessed scale within this report is preliminary and subject to change as the development progresses. This Traffic and Parking Impact Assessment report is limited with respect to external traffic impact to the local road network within close proximity to the site and may be further assessed under the Masterplan scale should the need arise with regards to regional impacts.

As part of the assessment, various vehicular access scenarios will be considered for the proposed Masterplan development and is detailed further in **Section 4.3** of this report. The access arrangements for the subject development will be consistent through all assessed scenarios, being an egress driveway onto Endeavour Road at the south-western portion of the site. A two-way driveway from Endeavour Road at the north-western portion of the site and access from the intersection of Captain Cook Drive / Gannons Road.



## 1.2 State Environmental Planning Policy (Infrastructure) 2007

The proposed development does qualify as a traffic generating development with relevant size and/or capacity under *Clause 104* of the *SEPP (Infrastructure) 2007*. Accordingly, formal referral to the Transport for New South Wales (TfNSW) is necessary as part of the proposal.

## 1.3 Site Description

The existing site consists of a number of office buildings around the site and a large Industrial building on the western portion of the site. The existing facilities on-site are generally consistent with motor showroom and dealership operations, whereby parts delivery, car servicing, fleet management and other ancillary operations are undertaken. The existing site provides 722 car parking spaces. A breakdown of the floor areas associated with the existing use of the site is provided below.

**TABLE 2: EXISTING SCALE OF DEVELOPMENT**

Land Use	Masterplan Scale
Industrial	27,880m <sup>2</sup> GFA
Office Use	13,954m <sup>2</sup> GFA


The subject site is zoned *B7 – Business Park* under Sutherland Shire Council's *Local Environmental Plan 2015* and is subject to their planning controls. It is expected that any land not permissible in the current zone as part of the Masterplan proposal will be subject to a rezoning application to ensure the proposed land uses are permissible on the site and that height requirements of the site comply with Council controls.

The proposed development is generally surrounded by industrial uses to the north, residential development to the south-west, recreational facilities to the south-east (Woollooware Golf Club and playing fields) and east (Solander Grounds) and Shark Park and Leagues Club to the east, with Woollooware Bay newly and under construction Town Centre. Caringbah Train Station is located approximately 1.1km to the south-west and Woollooware Train Station is located approximately 1.5km to the south-east.

The site currently has three (3) existing vehicular access points, one (1) from Captain Cook Drive via the roundabout intersection of Captain Cook Drive / Gannons Road and two (2) from Endeavour Road. In addition, Solander Grounds adjacent to the site has vehicle access into the site via a one-way internal egress road facilitating access to the roundabout intersection of Gannons Road / Captain Cook Drive.

## 1.4 Site Context

The location of the site is shown in aerial imagery and a street map in **Figure 1** and **Figure 2** respectively.



**FIGURE 1: SITE CONTEXT – AERIAL PHOTO**



**FIGURE 2: SITE CONTEXT – STREET MAP**

## **2 EXISTING TRAFFIC AND PARKING CONDITIONS**

### **2.1 *Road Hierarchy***

The road network servicing the site has characteristics as described in the following sub-sections.

#### **2.1.1 Captain Cook Drive - West of Gannons Road**

- Classified State Main Road (No 662);
- Approximately 23m width carriageway, facilitating three traffic flow lanes in each direction, which reduces to two lanes eastbound at the roundabout of Captain Cook Drive / Gannons Road and two (2) spaces on the approach to the roundabout for vehicles travelling eastbound. Kerbside parking is permissible on both sides of the road but is not typically used;
- Signposted 70km/h to the east of Endeavour Road and 60km/h to the west of Endeavour Road;
- Unrestricted kerbside parking permitted along both sides of the road. Provision of “*No Parking*” signage along the southern side of Captain Cook Drive, within proximity to Gannons Road. Kerbside parking along both sides of Captain Cook Drive is typically only utilised between Gannons Road and Endeavour Road during game days at Shark Park;
- No pedestrian facilities are provided between Gannons Road to Endeavour Road;
- Approved 25/26m B-double Route.

#### **2.1.2 Captain Cook Drive - East of Gannons Road**

- Classified Regional Secondary Road (No. 2075);
- Approximately 21m width carriageway, facilitating two traffic flow lanes in each direction and on road bicycle lanes on both sides of the road;
- Signposted 70km/h speed limit;
- ‘*No Stopping*’ restrictions located on both sides of the road;
- Provision of off-road bicycle and pedestrian facilities on the southern side of the road within the verge;
- Approved 25/26m B-double Route.

#### **2.1.3 Gannons Road**

- Unclassified Regional Road (No 7031);
- Approximately 12m width carriageway, facilitating one traffic flow lane in each direction and a parking lane on both sides of the road;
- Signposted 60km/h speed limit;
- Unrestricted kerbside parking permitted along both sides of the road outside of “*No Stopping*” and “*Bus Zone*” signage;

- Provision of off-road bicycle and pedestrian facilities on the eastern side of the road within the verge.

#### 2.1.4 Endeavour Road

- Unclassified Local Road;
- Approximately 12m width carriageway, facilitating one traffic flow lane in each direction and kerbside on both sides of the road;
- Un-signposted – 50 km/h speed limit applies;
- Approved 25/26m B-double Route;
- Unrestricted kerbside parking available on both sides of the road;
- No pedestrian facilities are provided on either side of the road.

### 2.2 **Existing Traffic Management**

- Roundabout controlled intersection Captain Cook Drive / Gannons Road;
- Signalised controlled intersection of The Kingsway / Gannons Road;
- Signalised controlled intersection of The Kingsway / Denman Avenue;
- Priority controlled left in / left out intersection of Dune Walk / Captain Cook Drive
- Signalised controlled intersection of Captain Cook Drive / Foreshore Boulevard;
- Signalised controlled intersection of Captain Cook Drive / Woollooware Road;
- Give-way controlled intersection of Captain Cook Drive / Endeavour Road designed as a seagull intersection;
- Priority controlled intersection of Endeavour Road / Endeavour Road;
- Give-way controlled intersection of Endeavour Road / Northumberland Road / Resolution Drive.

### 2.3 **Existing Traffic Volumes**

Intersection traffic surveys were conducted at the intersections of Captain Cook Drive / Gannons Road and Captain Cook Drive / Endeavour Road on Tuesday the 4<sup>th</sup> of February 2020, between 7:00am to 9:00am and 4:00pm to 6:00pm, representing a typical weekday. The detailed survey results are reproduced in **Annexure B** for reference. The following are relevant to note with respect to collected traffic data:

- Endeavour Road / Captain Cook Drive:
  - AM peak hour period occurred between 7:30am to 8:30am;
  - PM peak hour period occurred between 4:30pm to 5:30pm.
- Captain Cook Drive / Gannons Road:
  - AM peak hour period occurred between 8:00am to 9:00am;
  - PM peak hour period occurred between 4:30pm to 5:30pm.



It should be noted that at the time of surveys being undertaken, construction was underway along Captain Cook Drive along the frontage of the Sharks development which had reduced the carriageway to a single traffic flow lane in each direction through the construction site. This may have had impacts on observed traffic flows at the intersection of Captain Cook Drive / Gannons Road. It should be noted that the total traffic volumes observed during a traffic survey on the 4<sup>th</sup> of November 2016 during the PM peak hour period (survey duration 4:00pm to 7:00pm) at the roundabout of Captain Cook Drive / Gannons Road had a total traffic flow of 3,500 vehicles through the roundabout during the PM peak hour period (4:30pm to 5:30pm), whilst the current survey data observed 3,328 vehicles through the roundabout during the PM peak hour period. This is likely a result of the subject site being unoccupied or displaced vehicle traffic to other routes as a result of construction activity along Captain Cook Drive.

A review of the data from the 4<sup>th</sup> of November 2016, which is reproduced in **Annexure B** for reference, against the current survey results in 2020 indicate that approach flows along Captain Cook Drive east were approximately 100 less in 2020 compared to the 2016 surveys and the approach flows along Captain Cook Drive to the west were 100 less in 2020 compared to the 2016 surveys. Further the left turn movement from Gannons Road into Captain Cook Drive was 100 more in 2020 compared to 2016, which is likely a result of the infrastructure upgrade at the signalised intersection of The Kingsway / Gannons Road (duplication of the right turn lane into Gannons Road which occurred in 2018).

In view of the above, it is considered that the construction activity in front of sharks would have limited impact upon the observed traffic volumes as the surveyed 2020 traffic volumes provide a peak traffic volume of 1,205 and 1,235 vehicles travelling westbound and eastbound respectively. These volumes are within midblock capacities for a single lane (unrestricted) and would be operating at Level of Service (LoS) D based upon the '*RMS Guide to Traffic Generating Developments 2002*'.

### 2.3.1 Existing Road Performance

The performance of the surrounding intersections under the existing 2020 traffic conditions has been assessed using SIDRA INTERSECTION 8.0, **Table 3** summarises the resultant intersection performance data, with full SIDRA results reproduced in **Annexure C**.

As individual intersection modelling is being undertaken (no network model, or microsimulation), the modelled time periods are as that outlined in **Section 2.3** above. Further, the intersection of Captain Cook Drive / Endeavour Road has been modelled as two (2) stages due to the existing seagull arrangement. In addition, on the review of the video footage of the traffic surveys during the AM and PM peak hour periods, the right turn movements into and out of Endeavour Road largely benefited from platooning effects from the signalised intersection of Cawarra Road / Captain Cook Drive which enabled vehicles to turn in large quantities, gaps between southbound platooning vehicles were observed to be up to 70 seconds. To incorporate platooning impacts, the extra bunching input has been used for vehicles travelling southbound along Captain Cook Drive at the intersection of Endeavour Road / Captain Cook Drive.

In addition to this, a review of the right turn movement from Endeavour Road has been undertaken, with the following site observations relevant to note:

- AM Observations:
  - During the AM peak hour period, some vehicles would attempt to turn right, but chose to turn left along Captain Cook Drive due to the opposing right turn movement into Endeavour Road.
  - There was no significant queuing observed for right turn movements from Endeavour Road.
  - There was overflow outside of the right turning lane into Endeavour Road, but only occurred occasionally.
- PM Observations
  - The right turn movement from Captain Cook Drive into Endeavour Road did not overflow.
  - The right turn movement from Endeavour Road onto Captain Cook Drive sometimes had queues that backed up to Endeavour Road which runs north south, but never extended past.

To reflect the above condition, specifically the right turn queue from Endeavour Road during the PM peak hour period, the gap acceptance parameter has been modified for right turn movements from Endeavour Road onto Captain Cook Drive. Default gap acceptance parameters results in 95<sup>th</sup> percentile queue lengths in excess of 400m for the right turn from Endeavour Road during the PM peak hour period, which does not occur.

**TABLE 3: EXISTING INTERSECTION PERFORMANCES (SIDRA INTERSECTION 8.0)**

Intersection	Peak Hour	Degree of Saturation <sup>(1)</sup>	Average Delay <sup>(2)</sup> (sec/vehicle)	Level of Service <sup>(3)(4)</sup>	Control Type	Worst Movement
<b>EXISTING PERFORMANCE</b>						
Captain Cook Drive / Gannons Road	AM	0.649	7.8 (Worst: 17.4)	<b>A</b> (Worst: B)	Roundabout	UT from Captain Cook Drive (E)
	PM	0.65	7.9 (Worst: 17.5)	<b>A</b> (Worst: B)		UT from Captain Cook Drive (E)
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	0.865	10 (Worst: 36.5)	<b>N/A</b> (Worst: C)	Give Way (Seagull)	RT from Endeavour Road (E)
	PM	0.856	10.1 (Worst: 75.1)	<b>N/A</b> (Worst: F)		RT from Endeavour Road (E)

**NOTES:**

- (1) Degree of Saturation is the ratio of demand to capacity for the most disadvantaged movement.
- (2) Average delay is the delay experienced on average by all vehicles. The value in brackets represents the delay to the most disadvantaged movement.
- (3) Level of Service is a qualitative measure of performance describing operational conditions. There are six levels of service, designated from A to F, with A representing the best operational condition and level of service F the worst. The LoS of the intersection is shown in bold, and the LoS of the most disadvantaged movement is shown in brackets.
- (4) N/A – Intersection LoS and Major Road Approach LoS values are Not Applicable for two-way sign control since the average delay is not a good LoS measure due to zero delays associated with major through road movements.
- (5) Results are based upon Stage 1 only

As shown above, the roundabout intersection of Captain Cook Drive / Gannons Road is operating at LoS “A” during both the AM and PM peak hour period. Whilst the intersection of Captain Cook Drive / Endeavour Road is operating with worst turning movement of LoS “C” and LoS “F” during the AM and PM peak hour period respectively.

The right turn movement from Endeavour Road onto Captain Cook Drive during the PM peak hour period is providing a reported 95<sup>th</sup> percentile queue length of 60m. This is consistent with observed conditions and as such the model can be used to forecast future development impacts.

A LoS “A” indicates the roundabout intersection is operating at a high level of efficiency, with low delays and spare capacity. A LoS “C” conditions indicates that an intersection is operating satisfactory with some spare capacity and moderate delays. A LoS “F” condition reflects forced flow, with long delays and queues. The right turn movement from Endeavour Road during the PM peak hour period is operating at LoS “F”, indicating that this movement is operating at capacity.

### 2.3.2 Existing Approved Road Environment

As mentioned in **Section 1** the subject site is operationally redundant and had an approved scale as outlined in **Section 1.3**. The traffic generation of the existing site, relying upon the same traffic generation rates applied in **Section 4** of this report, results in the following traffic generation of the existing approved development as outlined in **Table 4** below.

**TABLE 4: ESTIMATED TRAFFIC GENERATION – EXISTING APPROVAL**

Use	Scale	Peak Period	Generation Rate	Trips	Split
Industrial	27,880m <sup>2</sup> GFA	AM	1 per 100m <sup>2</sup>	279 <sup>(1)</sup>	223 in, 56 out
		PM			56 in, 223 out
Commercial Office	13,954m <sup>2</sup> GFA	AM	2 per 100m <sup>2</sup>	279 <sup>(1)</sup>	223 in, 56 out
		PM			56 in, 223 out
<b>TOTAL</b>	<b>-</b>	<b>AM</b>	<b>-</b>	<b>558</b>	<b>446 in, 112 out</b>
		<b>PM</b>		<b>558</b>	<b>112 in, 446 out</b>

Note: (1) Assumes 80% inbound, 20% outbound during AM peak: Vice versa for PM peak.

As shown above the existing approved development is anticipated to generate **558** vehicle trips in the AM (446 in, 112 out) and PM (112 in, 446 out) peak hour periods. Adopting the same trip assignment as outlined in **Section 4.2** and local distribution as Scenario 1 results in the following intersection performances as summarised in **Table 5** below.

The detailed SIDRA results are reproduced in **Annexure C** for reference.

**TABLE 5: EXISTING PLUS APPROVED SCALE INTERSECTION PERFORMANCES  
(SIDRA INTERSECTION 8.0)**

Intersection	Peak Hour	Degree of Saturation <sup>(1)</sup>	Average Delay <sup>(2)</sup> (sec/vehicle)	Level of Service <sup>(3)(4)</sup>	Control Type	Worst Movement
<b>EXISTING PERFORMANCE + EXISTING APPROVED SCALE</b>						
Captain Cook Drive / Gannons Road	AM	0.73	8.9 (Worst: 19.8)	<b>A</b> (Worst: B)	Roundabout	UT from Captain Cook Drive (E)
	PM	0.72	11.8 (Worst: 29)	<b>A</b> (Worst: C)		UT from Captain Cook Drive (E)
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	1.04	35.2 (Worst: >70)	<b>N/A</b> (Worst: F)	Give Way (Seagull)	RT from Endeavour Road (E)
	PM	0.93	13.3 (Worst: >70)	<b>N/A</b> (Worst: F)		RT from Endeavour Road (E)

NOTES:

- (1) Degree of Saturation is the ratio of demand to capacity for the most disadvantaged movement.
- (2) Average delay is the delay experienced on average by all vehicles. The value in brackets represents the delay to the most disadvantaged movement.
- (3) Level of Service is a qualitative measure of performance describing operational conditions. There are six levels of service, designated from A to F, with A representing the best operational condition and level of service F the worst. The LoS of the intersection is shown in bold, and the LoS of the most disadvantaged movement is shown in brackets.
- (4) N/A – Intersection LoS and Major Road Approach LoS values are Not Applicable for two-way sign control since the average delay is not a good LoS measure due to zero delays associated with major through road movements.
- (5) Results are based upon Stage 1 only

As shown above, the intersection of Captain Cook Drive / Gannons Road is operating at Level of Service “A” under the existing approved scale conditions, indicating acceptable delays and spare capacity. The intersection of Captain Cook Drive / Endeavour Road is




operating with worst turning movement of LoS “F”. This indicates that the intersection of Endeavour Road / Captain Cook Drive requires an infrastructure upgrade. The failing turn movements relate to both right turns into Endeavour Road from Captain Cook Drive during the AM peak hour period and right turns out of Endeavour Road onto Captain Cook Drive during the PM peak hour period.

## **2.4 Public Transport**

The subject site has access to existing bus stop (ID: 222938) located approximately 200m from the south and 330m to the east of the roundabout intersection of Gannons Road / Captain Cook Drive. The bus stop services existing bus route 985 (Cronulla to Miranda via Woollooware Bay) provided by Transdev NSW and provides services every 30 minutes during peak commuter periods and 60 minutes outside peak commuter periods. Further, an existing bus stop (ID: 2229141) located approximately 330m to the south-west of the site located on Taronga Parade. The bus stop services existing bus route 969 (Cronulla to Sutherland) provided by Transdev NSW and provides services every hour.

Caringbah Train Station and Woollooware Train Station are located via a 2.2km walking distance to the south-west and 2.3km walking distance to the south-east from the Gannons Road site access respectively. Both stations service the T4 – Eastern Suburbs and Illawarra Line, providing access between Cronulla and Bondi Junction via the Sydney CBD (Central Station and Town Hall Station). Train services are provided 10 – 15 minutes within commuter peak hour periods and 30 minutes outside commuter peak periods.

The location of the site subject to the surrounding public transport network is shown in **Figure 3** below.



**FIGURE 3: PUBLIC TRANSPORT NETWORK MAP**

#### 2.4.1 Pedestrian & Cycling Facilities

As detailed in **Section 2.1** there are a number of existing bicycle and pedestrian facilities within close proximity to the site along Captain Cook Drive which connect to nearby cycling routes within the Sutherland Shire. **Figure 4** below shows existing constructed bicycle routes. Bicycle routes have already been constructed within close proximity to the site, with the most recent construction completed along the eastern side of Gannons Road to the south of the site which provided shared pedestrian and bicycle facilities. As part of the masterplan development it is recommended that the site provide connectivity to existing pedestrian and bicycle routes to promote sustainable transport.

**Draft**  
**Sutherland Shire**  
Development Control Plan 2015  
under the Environmental Planning & Assessment Act 1979

**Sutherland Shire**  
**Bicycle Network Map**

Reference to Chapter 35 of the  
Draft Sutherland Shire Development Control Plan 2015

Ratio 1 : 95000



**Legend**

- Existing Bicycle Network
- Proposed Bicycle Network
- Existing Railway Corridor - All Railway Corridors
- All Potential Off-Road Regional Routes
- DM Deferred Matter

**NOTE:** Not all routes have been constructed at this point in time. Some cycleways may be removed or added from the Proposed Bicycle Network over time.


Relationship with other Plans:  
These maps are to be read in conjunction with  
Draft Sutherland Shire Development Control Plan 2015.

Sutherland Shire Council  
Environmental Planning Unit

Council File Number: 2015/210250

This map is part of the set of maps included with the DCP.  
It was prepared on 23/03/15.  
It was in effect on TBA.

Action	Date of Original	Amendment No.	1	2	3
Endorse draft					
Public Notice (Draft)					
Exhibition Start					
Exhibition Finish					
Adopt Final					
Public Notice (Final)					
In Effect					



**FIGURE 4: SUTHERLAND SHIRE COUNCIL BICYCLE NETWORK MAP**

## 2.5 Future Road and Infrastructure Upgrades

Cronulla Sharks Leagues Club has undergone a four stage redevelopment consisting of residential apartments and retail land uses. Currently Stage 1 and 2 are completed and would have been captured within the existing 2020 intersection traffic surveys, whilst Stage 3 and Stage 4 are incomplete and under construction. Any future development on the subject site should consider additional traffic loads under the approved Sharks development.

Stage 3 and Stage 4 of the sharks redevelopment consist of the following based upon the *Traffic & Parking Impact Assessment Report* dated 10<sup>th</sup> February 2020 by *McLaren Traffic Engineering (18574.01FF)* and the *Traffic & Parking Impact Assessment Report* dated 11<sup>th</sup> August 2016 by *McLaren Traffic Engineering (15084.05FC)* :

- Stage 3:
  - 238 high density residential developments.
- Stage 4:
  - 255 high density residential developments;
  - 38 hotel rooms;
  - 18,343m<sup>2</sup> Shopping Centre;
  - Revitalised Sharks Leagues Club (4,352m<sup>2</sup> GFA).

The traffic generation as a result of the approved Stage 3 and Stage 4 development is summarised below in **Table 6**.



**TABLE 6: TRAFFIC GENERATION TRIPS PER LAND USE (2013 GUIDELINES)**

Land Use	Rate <sup>(1)</sup> PM Peak Hour	Scale <sup>(1)</sup>	Traffic Generation AM Peak Hour (Trips per hour) <sup>(2)</sup>	Traffic Generation PM Peak Hour (Trips per hour)
High-Density Residential	0.19 trips / unit	493	94	94
Shopping Centre	6.7 trips / 100m <sup>2</sup> GLFA	18,343m <sup>2</sup>	615	1229
Club	168 trips / 8,500m <sup>2</sup>	4,352m <sup>2</sup>	43	86
Hotel	0.5 trips / room	38	19	19
<b>Total</b>	-	-	<b>771</b>	<b>1417</b>

Note: 1- Rates above and scale have been adopted from *MCLaren Traffic Engineering (18574.01FF)* and the *Traffic & Parking Impact Assessment Report dated 11th August 2016 by MCLaren Traffic Engineering (15084.05FC)*

2 – Retail AM peak hour trip rate is assumed to be half of the PM peak hour period

The above traffic generation has been added to the existing traffic volumes and existing traffic volumes plus existing approved scale based upon the trip distribution as outlined within the *Traffic & Parking Impact Assessment Report* dated 10<sup>th</sup> February 2020 by *MCLaren Traffic Engineering (18574.01FF)*. The results of the SIDRA assessment are reproduced in **Table 7** below, with detailed SIDRA outputs reproduced in **Annexure C** for reference.

**TABLE 7: EXISTING INTERSECTION PERFORMANCES (SIDRA INTERSECTION 8.0)**

Intersection	Peak Hour	Degree of Saturation <sup>(1)</sup>	Average Delay <sup>(2)(5)</sup> (sec/vehicle)	Level of Service <sup>(3)(4)</sup>	Control Type	Worst Movement
EXISTING PERFORMANCE						
Captain Cook Drive / Gannons Road	AM	0.649	7.8 (Worst: 17.4)	A (Worst: B)	Roundabout	UT from Captain Cook Drive (E)
	PM	0.65	7.9 (Worst: 17.5)	A (Worst: B)		UT from Captain Cook Drive (E)
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	0.865	10 (Worst: 36.5)	N/A (Worst: C)	Give Way (Seagull)	RT from Endeavour Road (E)
	PM	0.856	10.1 (Worst: 75.1)	N/A (Worst: F)		RT from Endeavour Road (E)
EXISTING PERFORMANCE + SHARKS STAGE 3 & 4						
Gannons Road / Captain Cook Drive	AM	0.74	8.8 (Worst: 18.7)	A (Worst: B)	Roundabout	U-Turn from Captain Cook Drive (E)
	PM	0.75	9.4 (Worst: 19.2)	A (Worst: B)		
Captain Cook Drive / Endeavour Road	AM	0.95	15.8 (Worst: 47.3)	N/A (Worst: D)	Give Way (Seagull)	RT from Captain Cook Drive (S)
	PM	1.01	19.2 (Worst: >70)	N/A (Worst: F)		RT from Endeavour Road (E)
EXISTING PERFORMANCE + SHARKS STAGE 3 & 4 + Existing Approved Scale						
Gannons Road / Captain Cook Drive	AM	0.82	11 (Worst: 22.8)	A (Worst: B)	Roundabout	U-Turn from Captain Cook Drive (E)
	PM	0.95	23.2 (Worst: 86)	B (Worst: F)		RT from Site Access (N)
Captain Cook Drive / Endeavour Road	AM	1.15	79.5 (Worst: >70)	N/A (Worst: F)	Give Way (Seagull)	RT from Captain Cook Drive (S)
	PM	1.11	28.9 (Worst: >70)	N/A (Worst: F)		RT from Endeavour Road (E)

**NOTES:**

- (1) Degree of Saturation is the ratio of demand to capacity for the most disadvantaged movement.
- (2) Average delay is the delay experienced on average by all vehicles. The value in brackets represents the delay to the most disadvantaged movement.
- (3) Level of Service is a qualitative measure of performance describing operational conditions. There are six levels of service, designated from A to F, with A representing the best operational condition and level of service F the worst. The LoS of the intersection is shown in bold, and the LoS of the most disadvantaged movement is shown in brackets.
- (4) Intersection LOS and Major Road Approach LoS are not applicable (N/A) for two-way sign control since the average delays is not a good LOS measure due to zero delays associated with major road movements
- (5) Average delay of seagull intersection (Captain Cook Drive / Endeavour Road) is based upon Stage 1 only.

As shown above, the roundabout intersection of Gannons Road / Captain Cook Drive is expected to operate at LoS “A” during the future conditions once the Sharks development has been completed and occupied in both the AM and PM peak hour periods. Under the existing approved development scale and the sharks development the roundabout is expected to operate at LoS “B”, most noticeable is the degree of saturation during the PM peak hour period, which is approaching 1, indicating that the intersection is almost at full operating capacity.

The intersection of Captain Cook Drive / Endeavour Road is expected to operate with worst turning movement of LoS “D” during the AM peak hour period and LoS “F” during the PM peak hour period indicating that under the Sharks development the intersection is exceeding its capacity during the PM peak hour period and has reached capacity during the AM peak hour period. Under the existing approved development scale and the Sharks development the intersection is expected to operate with worse turning movement of LoS “F” in both the AM and PM peak hour periods. This indicates that the intersection of Endeavour Road / Captain Cook Drive requires an infrastructure upgrade. The failing turn movements relate to both right turns into Endeavour Road from Captain Cook Drive during the AM peak hour period and right turns out of Endeavour Road onto Captain Cook Drive during the PM peak hour period.

Of relevance to note is the degree of saturation for the intersection of Endeavour Road / Captain Cook Drive, which is equal to / exceeding 1, indicating that the right turn movement into Endeavour Road from Captain Cook Drive during the AM peak hour period and the right turn out of Endeavour Road during the PM peak hour period onto Captain Cook Drive is exceeding its operating capacity under the Sharks development scenario and Sharks development plus existing approved scale scenario. Considering this, the intersection of Endeavour Road / Captain Cook Drive will require an infrastructure upgrade.

### **3 PARKING ASSESSMENT**

#### **3.1 Car Parking Provision**

Reference is made to *Sutherland Shire Council's Development Control Plan 2015 - Chapter 27 – B7 Business Park & Chapter 36 – Vehicular Access, Traffic, Parking and Bicycles* which outlines the applicable car parking rates for the proposed mixed-use development.

#### **Chapter 27 – Section 9 – Parking**

##### ***Industrial Premises***

*1 space per 100m<sup>2</sup>, with a minimum of 2 spaces for each industrial unit.*

*Any ancillary office component to an industrial development shall provide 1 space per 30m<sup>2</sup> of gross floor area.*

##### ***Office and Business Premises***

*1 space per 45m<sup>2</sup> GFA*

##### ***Retail Premises***

*1 space per 45m<sup>2</sup> GFA*

##### ***Warehouse or distributions centres***

*1 space per 300m<sup>2</sup>*

#### **Chapter 36 – Table 1 – Car Parking Numbers**

##### ***Hotel or Motel accommodation***

*1 space per 4 rooms; plus,*

*1 space per 2 employees*

It should be noted that to provide a conservative assessment, the ancillary office component for warehouse land uses will be assessed as industrial ancillary office space (i.e. 1 space per 30m<sup>2</sup> GFA). The parking requirements for the site are summarised in **Table 8** below.

The car parking rates outlined within Council's DCP are deemed appropriate for the subject site, considering the lack of available alternative transport modes, specifically rail facilities. Typically, office car parking rates within close proximity to train facilities attempt to reduce vehicular traffic on the road network and as such allow for a reduced car parking rate between 1 space per 60m<sup>2</sup> to 1 space per 80m<sup>2</sup>. The subject site does not benefit from close proximity to heavy or light rail high occupancy transport mode facilities and is largely isolated, as such the Council car parking rates are deemed an acceptable representation of actual car parking demand of the site.



**TABLE 8: DCP CAR PARKING REQUIREMENTS - MASTERPLAN**

Land Use	Scale	Rate	Parking Required
Industrial	25,272m <sup>2</sup> GFA	1 per 100m <sup>2</sup> GFA	252.7
Industrial Ancillary Office	7,382m <sup>2</sup> GFA	1 per 30m <sup>2</sup> GFA	246
Warehouse	1,824m <sup>2</sup> GFA	1 per 300m <sup>2</sup> GFA	6
Warehouse Ancillary Office	3,846m <sup>2</sup> GFA	1 per 30m <sup>2</sup> GFA	128.2
Commercial Office	99,286m <sup>2</sup> GFA	1 per 45m <sup>2</sup> GFA	2206.4
Retail	4,307m <sup>2</sup> GFA	1 per 45m <sup>2</sup> GFA	95.7
Food and Beverage	3,561m <sup>2</sup> GFA	1 per 45m <sup>2</sup> GFA	79.2
Hotel	125 rooms	1 per 4 rooms	31.3
	20 staff <sup>(1)</sup>	1 per 2 staff	10
<b>Total</b>	<b>-</b>	<b>-</b>	<b>3056</b>

Note: 1 – Staff numbers are estimated / assumed and will be required to be determined in detail during the DA stage

As shown above the site is expected to provide **3,056** car parking spaces to comply with Council's car parking requirements for the Masterplan Scale. A reduction in car parking provision may be supported with consideration to shared parking arrangements and an assessment of the temporal variations in peak parking demand of the various uses of the site.

The proposed masterplan development indicates the provision of **1,484** car parking spaces, a shortfall of **1,572** car parking spaces. Considering the proposed land uses, there are no land uses with different peak parking demand periods, such that a lower number of car parking spaces could be justified. The only discount that could be supported is the reduction in retail and food and beverage car parking spaces, adopting the assumption that the provision of retail and food and beverage facilities serves the office component of the site and could be considered ancillary, with the exception to staff car parking demand for the retail and food and beverage land uses.

Adopting a 50% reduction in the car parking requirements for the retail, food and beverage land uses results in a reduction of 88 spaces, reducing to a car parking requirement of **2,968**, which is a shortfall of **1,484** car parking spaces. This is still a significant shortfall in provision of car parking and as such the development should provide additional car parking or investigate alternative solutions / modes of transport to and from the site. The site should investigate the following:

- Expanded bus services along Captain Cook Drive and provision of a new bus stop & deviated service within the site;
- Connect to existing bicycle and pedestrian facilities;
- Restriction to staff density within the site, such as a percentage of all workers working from home:
  - Enforcement and monitoring of this would not be possible.

- Investigate light rail facilities:
  - This recommendation is not feasible and would be required to be part of a much larger scheme and require consultation with State and relevant road authorities.

### 3.2 Disabled Car Parking

Reference is made to the *National Construction Code 2019 (NCC) – Volume 1 - Building Code of Australia's (BCA's) Table D3.5* which designates the following building classes and disabled parking rates to the proposed development uses. The appropriate disabled car parking rates is presented in **Table 9**.

**TABLE 9: DISABLED PARKING REQUIREMENTS - MASTERPLAN**

Land Use	Building Class (NCC / BCA)	Rate (Table D3.5)	Car Spaces Required <sup>(1)</sup>	Disabled Parking Required <sup>(2)</sup>
Industrial	Class 8	1 per 100 spaces	252.7	2.5
Industrial Ancillary Office	Class 5	1 per 100 spaces	246	2.5
Warehouse	Class 7b	1 per 100 spaces	6	0.1
Warehouse Ancillary Office	Class 5	1 per 100 spaces	128.2	1.3
Commercial Office	Class 5	1 per 100 spaces	2206.4	22
Retail	Class 6	1 per 50 spaces	95.7	2
Food and Beverage	Class 6	1 per 50 spaces	79.2	2
Hotel	Class 3	1 per 100 spaces <sup>(3)</sup>	31.3	1
<b>Total</b>	-	-	-	<b>33.4 (34)</b>

Notes: (1) Refer to **Table 8**.

(2) Requirement rounded up to nearest whole number for each individual use.

(3) Rate applied as proposed number of disabled hotels rooms is not available.

It is expected that each building of the masterplan will be assessed at development application stage and will provide the appropriate provision of disabled car parking spaces for each development stage.

### 3.3 Motorcycle Parking Requirements

Reference is made to *Sutherland Shire Council's Development Control Plan 2015 - Chapter 36 – Vehicular Access, Traffic, Parking and Bicycles* which states "Motor cycle parking shall be provided for all non residential development at a rate of 1 motorcycle space per 25 car spaces or part thereof".

Application of this rate results in a requirement of **123** (3056/25) motorcycle spaces for the proposed masterplan. It is noted that *Chapter 27 – B7 Business Park* of the DCP does not outline motorcycle parking requirements, which is the relevant DCP for the subject site, as such the site does not require the provision of motorcycle facilities, but considering the shortfall of car parking motorcycle parking should be provided.

### 3.4 Bicycle Parking Requirements

Reference is made to Sutherland Shire Council's Development Control Plan 2015 – Chapter 36 – Vehicular Access, Traffic, Parking and Bicycles & Chapter 27 – B7 Business Park which state "Bicycle parking spaces must be provided at the rate of 1 space per 10 car parking spaces for the first 200 car spaces, then 1 space per 20 parking spaces thereafter".

Application of this rate results in a requirement of **163** bicycle spaces for the proposed Masterplan scale. It is expected that the site will provide compliant bicycle facilities at the development application stage.

### 3.5 Servicing & Loading

Reference is made to Council's DCP which does not designate specific vehicle sizes required for servicing and loading, although Council's DCP does reference the *RMS Guide to Traffic Generating Developments* for design vehicles. Furthermore, Council requires all servicing and loading be undertaken on-site, with vehicles to achieve forward entry and forward exit from the site.

Reference is made to the *RMS Guide to Traffic Generating Developments 2002*, as adopted by Transport for New South Wales (TfNSW), which states the following regarding servicing and loading vehicle provision applicable to the proposal:

#### **Table 5.1 – Provision of areas for delivery and service vehicles**

##### **Commercial premises** (50% of spaces adequate for trucks)

< 20,000m <sup>2</sup> GFA	1 space per 4,000m <sup>2</sup> GFA
> 20,000m <sup>2</sup> GFA	5+ 1 space per 8,000m <sup>2</sup> over 20,000m <sup>2</sup>

##### **Supermarkets, shops and restaurants** (all spaces adequate for trucks)

< 2,000m <sup>2</sup> GFA	1 space per 400m <sup>2</sup> GFA
> 2,000m <sup>2</sup> GFA	5 + 1 space per 1,000m <sup>2</sup> over 2,000m <sup>2</sup>

##### **Wholesale, Industrial** (all spaces adequate for trucks)

< 8,000m <sup>2</sup> GFA	1 space per 800m <sup>2</sup>
> 8,000m <sup>2</sup> GFA	10 + 1 space per 1,000m <sup>2</sup> over 8,000m <sup>2</sup>

##### **Hotels and Motels** (50% of spaces adequate for trucks)

< 200 bedrooms or bedroom suites	1 space per 50 bedrooms
----------------------------------	-------------------------

Plus

1 space per 1,000m<sup>2</sup> of public area set aside for bar, tavern, lounge and restaurant,

##### **Other uses** (50% of spaces adequate for trucks)

1 space per 2,000m <sup>2</sup>
---------------------------------

The servicing and loading provision requirements for the Masterplan is detailed in **Table 10** below. It is noted that only the truck provision has been shown in the following tables, whereby servicing vehicles sized up to an Australian Standard B99 vehicle can temporarily use standard car parking spaces.

Further, the ancillary industrial office and ancillary warehouse office components are not included in the below table, as loading facilities for these components can be shared with the Warehouse and Industrial requirements.

**TABLE 10: SERVICING AND LOADING PROVISION - MASTERPLAN**

Land Use	Scale	Rate	Servicing and Loading Provision
Industrial	25,272m <sup>2</sup> GFA	10 + 1 space per 1,000m <sup>2</sup> over 8,000 m <sup>2</sup>	27
Warehouse	1,824m <sup>2</sup> GFA	1 space per 800m <sup>2</sup>	2
Commercial Office	99,286m <sup>2</sup> GFA	50% of: 5 + 1 space per 8,000m <sup>2</sup> over 20,000m <sup>2</sup>	8
Retail	4,307m <sup>2</sup> GFA	5 + 1 space per 1,000m <sup>2</sup> over 2,000m <sup>2</sup>	8
Food and Beverage	3,561m <sup>2</sup> GFA	5 + 1 space per 1,000m <sup>2</sup> over 2,000m <sup>2</sup>	7
Hotel	125 rooms	50% of: 1 per 50 rooms	2
<b>Total</b>	<b>-</b>	<b>-</b>	<b>54</b>

It is noted that the servicing and loading provisions outlined above are recommended numbers only. The exact servicing and loading requirements, including vehicle sizes can be determined upon further detail of the proposed developments and users of the proposal. It is recommended that loading facilities are provided based upon the operational requirements for each building, with the potential for buildings to share on-site loading facilities under management plans.

Further, it is expected that waste collection will be conducted by private waste contractors who are to conduct waste collection operations on site within the allocated servicing and loading areas.

The largest vehicle expected to travel to and from the site will be a 12.5m length Heavy Rigid Vehicle for deliveries and waste collection for office and retail components. Industrial and Warehouse components of the site may require the provision of 19m length Articulated Vehicles and is subject to each lot's tenancy size and fitout. Access for service vehicles can be facilitated from any of the road frontages or access points subject to vehicle design swept paths tests and any imposed truck limits. In this regard, heavy vehicle access will be from either Captain Cook Drive / Gannons Road or Endeavour Road. It should be noted that Endeavour Road is an existing approved B-double route.

It is expected that due to the internal road layout, the site will be limited to access to and from the intersection of Gannons Road / Captain Cook Drive by vehicles up to a 12.5m length Heavy Rigid Vehicle, whilst 19m length Articulated Vehicles if required for the development will be restricted to Endeavour Road.

### **3.6 Vehicle Access & Parking / Loading**

The car parking layout as depicted in **Annexure A**, will be assessed at the development application stage to ensure compliance with the relevant Australian Standards, namely AS2890.1:2004, AS2890.2:2018, AS2890.3:2015, AS2890.6:2009 and AS2890.5:2020.

If the masterplan proposal were to be approved, the driveway access, circulation areas and on-site parking areas of any development on the site would be required to comply. It would be a requirement at the Development Application and Construction Certificate stage that each Lot be checked for compliance with parking provision and driveway location requirements.



## **4 TRAFFIC ASSESSMENT**

The impact of the expected traffic generation levels associated with the subject proposal is discussed in the following sub-sections.

### **4.1 *Traffic Generation***

Traffic generation rates for the relevant land uses are provided in the *Roads and Maritime Services (RMS) Guide to Traffic Generating Developments (2002)* and recent supplements and are as follows:

#### **RMS Guide**

##### **3.4.3 Hotels - tourist.**

*NSW based data is not available.*

##### **3.4.1 Motels.**

*Evening peak hour vehicle trips = 0.4 per unit.*

##### **3.5 Office and commercial.**

*Evening peak hour vehicle trips = 2 per 100m<sup>2</sup> gross floor area*

##### **3.6.1 Shopping centres.**

*$V(P) = 56 A(SS)$  vehicle trips per 1000m<sup>2</sup> GLFA*

*Where: A(SS): Specialty shops, secondary retail GLFA*

##### **3.7.2 Restaurants.**

*Evening peak hour vehicle trips = 5 per 100m<sup>2</sup> gross floor area.*

##### **3.10.1 Factories**

*Evening peak hour vehicle trips = 1 per 100m<sup>2</sup> gross floor area*

##### **3.10.2 Warehouses**

*Morning peak hour vehicle trips = 0.5 per 100m<sup>2</sup> gross floor area*

#### **TDT 2013/04a**

##### ***Office blocks***

*Morning peak hour vehicle trips = 1.6 per 100m<sup>2</sup> gross floor area.*

*Evening peak hour vehicle trips = 1.2 per 100m<sup>2</sup> gross floor area.*

In addition to the application of the above rates, the following assumptions have been incorporated in the calculations in order to conservatively estimate the traffic generation of the proposal:

- As no tourist hotel rate is provided in the RMS Guide, the motel rate has been applied as a worst case. A tourist hotel is likely to generate less traffic and is to be designed for tourist coaches and taxi areas within any Porte Cochere.
- The AM and PM rate for hotel uses is assumed to be equivalent;
- The RMS office rate has been applied as the proposed site has access to public transport services;
- The RMS office rate has been applied to the factory and warehouse ancillary office areas;
- Half of the office rate has been adopted for the retail portion of the site to consider a lower density of staff and ancillary use of the development;
- The AM and PM rate for factory uses is assumed to be equivalent;
- The AM and PM rate for warehouse uses is assumed to be equivalent;

It is further noted that the research and surveys behind the RMS traffic generation rates for business parks are predominantly warehouse and factory use with ancillary office areas and not primarily office space as per the proposed masterplan scale. As such, the business park rates have not been applied to the proposed development, as they are deemed to not be applicable.

These assumptions in addition to the applicable RMS Guide traffic generation rates have been applied to the Masterplan scale, with expected traffic generation shown in **Table 11** below.

**TABLE 11: ESTIMATED TRAFFIC GENERATION – MASTERPLAN**

Use	Scale	Peak Period	Generation Rate	Trips	Split
Industrial	25,272m <sup>2</sup> GFA	AM	1 per 100m <sup>2</sup>	253 <sup>(1)</sup>	202 in, 51 out
		PM			51 in, 202 out
Industrial Ancillary Office	7,382m <sup>2</sup> GFA	AM	2 per 100m <sup>2</sup>	148 <sup>(1)</sup>	118 in, 30 out
		PM			30 in, 118 out
Warehouse	1,824m <sup>2</sup> GFA	AM	0.5 per 100m <sup>2</sup>	9 <sup>(1)</sup>	7 in, 2 out
		PM			2 in, 7 out
Warehouse Ancillary Office	3,846m <sup>2</sup> GFA	AM	2 per 100m <sup>2</sup>	77 <sup>(1)</sup>	62 in, 15 out
		PM			15 in, 62 out
Commercial Office	99,286m <sup>2</sup> GFA	AM	2 per 100m <sup>2</sup>	1986 <sup>(1)</sup>	1589 in, 397 out
		PM			397 in, 1589 out
Retail	4,307m <sup>2</sup> GFA	AM	1 per 100m <sup>2</sup>	43 <sup>(1)</sup>	35 in, 8 out
		PM	1 per 100m <sup>2</sup>		8 in, 35 out
Food and Beverage	3,561m <sup>2</sup> GFA	AM	1 per 100m <sup>2</sup>	36 <sup>(1)</sup>	29 in, 7 out
		PM	1 per 100m <sup>2</sup>		7 in, 29 out
Hotel	125 rooms	AM	0.4 per room	50 <sup>(2)</sup>	25 in, 25 out
		PM			25 in, 25 out
<b>TOTAL</b>	<b>-</b>	<b>AM</b>	<b>-</b>	<b>2,602</b>	<b>2067 in, 535 out</b>
		<b>PM</b>		<b>2,602</b>	<b>535 in, 2,067 out</b>

Note: (1) Assumes 80% inbound, 20% outbound during AM peak: Vice versa for PM peak.

(2) Assumes 50% inbound, 50% outbound during AM peak and PM peak hour period

As shown, the traffic generation associated with the proposal is in the order of **2,602** vehicle trips in the AM peak hour period (2,067 inbound, 535 outbound) and **2,602** vehicles trips in the PM peak hour period (535 inbound, 2,067 outbound).

## 4.2 Trip Assignment

The road network and the locations of residential areas surrounding the site have been assessed, in conjunction of an assessment against Journey to Work data and the following traffic assignment has been adopted for all traffic to and from the site:

- 10% to / from Gannons Road;
- 10% to / from Captain Cook Drive (east);
- 40% to / from Captain Cook Bridge:
  - 20% via Toorak Avenue;
  - 20% via Taren Point Road.
- 40% to / from The Boulevard.

As the proposed development is predominantly office space, no alternative trip distribution has been adopted for the retail catchment of the development. It is expected that the retail component of the site is ancillary to the office component such that it will predominantly be used by internal users.

## 4.3 Access Scenarios

As part of the assessment of the masterplan development, multiple access strategies will be assessed under the above trip distribution. The access strategies that will be assessed are summarised in **Table 12** below.

**TABLE 12: ACCESS SCENARIO ASSESSMENT**

Access Scenario	Comments / Assumptions	Endeavour Road / Captain Cook Drive	Captain Cook Drive / Gannons Road	New Road Infrastructure (Endeavour Road New)
<b>Scenario 1</b>	<ul style="list-style-type: none"> <li>Inbound vehicles are split between Endeavour Road and Gannons Road</li> <li>Outbound Vehicles use both Endeavour Road and Gannons Road</li> </ul>	No Changes	No Changes	N/A
<b>Scenario 2</b>	<ul style="list-style-type: none"> <li>Inbound vehicles are split between Endeavour Road / Gannons</li> <li>Outbound Vehicles use both Endeavour Road and Gannons Road</li> </ul>	No Changes	Signalised Intersection  (Retains all vehicle movements)	N/A
<b>Scenario 3</b>	<ul style="list-style-type: none"> <li>Inbound vehicles are split between Endeavour, New Endeavour Road Intersection and Gannons Road</li> <li>Outbound Vehicles use Endeavour Road, New Endeavour Road Intersection and Gannons Road (usage of New Endeavour Road / Gannons Road is based upon equilibrium)</li> </ul>	Right turn out of Endeavour Road banned and added to turn movements for New Endeavour Road Intersection	Signalised Intersection  (Retains all vehicle movements)	Signalised Intersection (New Endeavour Road with Captain Cook Drive)  (Retains all vehicle movements)
<b>Scenario 4</b>	<ul style="list-style-type: none"> <li>Inbound vehicles are split between Endeavour, New Endeavour Road Intersection and Gannons Road</li> <li>Outbound Vehicles use Endeavour Road, New Endeavour Road Intersection and Gannons Road (usage of New Endeavour Road / Gannons Road is based upon equilibrium)</li> </ul>	Signalised Intersection  Right turn out of Endeavour Road banned and added to right turn movement for New Endeavour Road	Signalised Intersection  (Retains all vehicle movements)	Signalised Intersection (New Endeavour Road with Captain Cook Drive)  (Right turn movement into Endeavour Road banned)

Based upon the above assessed scenarios, traffic distributions, vehicles are expected to arrive and depart the site as shown in **Annexure D**.



#### 4.4 Traffic Impact

The traffic generation outlined in **Section 4.1, 4.2 and 4.3** above has been added to the existing traffic volumes recorded and traffic from the approved Stage 3 & 4 Sharks Development. SIDRA INTERSECTION 8.0 was used to assess the intersections performance under the above scenarios. The purpose of this assessment is to compare the existing intersection operations to the future scenario under the increased traffic load. The detailed SIDRA results are reproduced in **Annexure C** for reference, with a summary of results provided in the following subsections:

##### 4.4.1 Scenario 1

A summary of Scenario 1 is provided in **Table 13** below, which assesses the proposed development under existing road infrastructure.

**TABLE 13: INTERSECTION PERFORMANCE (SIDRA INTERSECTION 8.0) – SCENARIO 1**


Intersection	Peak Hour	Degree of Saturation <sup>(1)</sup>	Average Delay <sup>(2)</sup> (sec/vehicle)	Level of Service <sup>(3)(4)</sup>	Control Type	Worst Movement
EXISTING PERFORMANCE + SHARKS STAGE 3 & 4						
Gannons Road / Captain Cook Drive	AM	0.74	8.8 (Worst: 18.7)	A (Worst: B)	Roundabout	U-Turn from Captain Cook Drive (E)
	PM	0.75	9.4 (Worst: 19.2)	A (Worst: B)		
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	0.95	15.8 (Worst: 47.3)	N/A (Worst: D)	Give Way (Seagull)	RT from Captain Cook Drive (S)
	PM	1.01	19.2 (Worst: >70)	N/A (Worst: F)		RT from Endeavour Road (E)
FUTURE PERFORMANCE – SCENARIO 1						
Gannons Road / Captain Cook Drive	AM	1.2	>70 (Worst: >70)	F (Worst: F)	Roundabout	U-Turn from Captain Cook Drive (E)
	PM	5.2	>70 (Worst: >70)	F (Worst: F)		U-Turn from Site Access (N)
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	2.43	>70 (Worst: >70)	N/A (Worst: F)	Give Way (Seagull)	RT from Captain Cook Drive (S)
	PM	1.59	>70 (Worst: >70)	N/A (Worst: F)		RT from Endeavour Road (E)

Notes: Refer to Table 3 Notes

As shown, the intersection of Gannons Road / Captain Cook Drive and Captain Cook Drive / Endeavour Road is operating at LoS “F” indicating that existing access arrangements are unacceptable.

#### 4.4.2 Scenario 2

Scenario 2 assesses the proposed development under a signalised intersection at Captain Cook Drive / Gannons Road / Site Access. The geometry assessed as part of Scenario 2 is shown in **Figure 5** below.



**FIGURE 5: SCENARIO 2 INTERSECTION GEOMETRY**

Based upon the above intersection geometry, the resultant intersection performance is shown in **Table 14** below.

**TABLE 14: INTERSECTION PERFORMANCE (SIDRA INTERSECTION 8.0) –  
SCENARIO 2**


Intersection	Peak Hour	Degree of Saturation <sup>(1)</sup>	Average Delay <sup>(2)</sup> (sec/vehicle)	Level of Service <sup>(3)(4)</sup>	Control Type	Worst Movement
EXISTING PERFORMANCE + SHARKS STAGE 3 & 4						
Gannons Road / Captain Cook Drive	AM	0.74	8.8 (Worst: 18.7)	A (Worst: B)	Roundabout	U-Turn from Captain Cook Drive (E)
	PM	0.75	9.4 (Worst: 19.2)	A (Worst: B)		
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	0.95	15.8 (Worst: 47.3)	N/A (Worst: D)	Give Way (Seagull)	RT from Captain Cook Drive (S)
	PM	1.01	19.2 (Worst: >70)	N/A (Worst: F)		RT from Endeavour Road (E)
FUTURE PERFORMANCE – SCENARIO 2						
Gannons Road / Captain Cook Drive	AM	0.90	37.1	C	Signal	N/A
	PM	0.92	48.7	D		N/A
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	2.43	>70 (Worst: >70)	N/A (Worst: F)	Give Way (Seagull)	RT from Captain Cook Drive (S)
	PM	1.59	>70 (Worst: >70)	N/A (Worst: F)		RT from Endeavour Road (E)

Notes: Refer to Table 3 Notes


As shown above, the intersection of Gannons Road / Captain Cook Drive is expected to operate at LoS “C” in the AM peak hour period and LoS “D” in the PM peak hour period. While this is an acceptable level of service, the intersection of Captain Cook Drive / Endeavour Road is operating at LoS “F”, which is unacceptable. In addition, the extent of road widening required to facilitate the above design is substantial, likely requiring acquisition of land along the eastern side of Gannons Road (i.e. sports fields) and land from the subject site to facilitate the design.

#### 4.4.3 Scenario 3

Scenario 3 assesses the proposed development under a signalised intersection at Captain Cook Drive / Gannons Road / Site Access and a New Signalised Intersection at the bend in Captain Cook Drive at the south west corner of the Toyota Site within a short new road connection between Captain Cook Drive and Endeavour Road that then access the Toyota site along its frontage with Endeavour Road. A brief concept drawing of a potential new intersection is shown in **Annexure E** for reference. The geometry assessed as part of Scenario 3 is shown in **Figure 6** and **Figure 7** below.



**FIGURE 6: SCENARIO 3 INTERSECTION GEOMETRY – GANNONS ROAD / CAPTAIN COOK DRIVE**



**FIGURE 7: SCENARIO 3 – INTERSECTION GEOMETRY – NEW ENDEAVOUR ROAD / CAPTAIN COOK DRIVE**

Based upon the above intersection geometry, the resultant intersection performance is shown in **Table 15** below.

**TABLE 15: INTERSECTION PERFORMANCE (SIDRA INTERSECTION 8.0) – SCENARIO 3**

Intersection	Peak Hour	Degree of Saturation <sup>(1)</sup>	Average Delay <sup>(2)</sup> (sec/vehicle)	Level of Service <sup>(3)(4)</sup>	Control Type	Worst Movement
EXISTING PERFORMANCE + SHARKS STAGE 3 & 4						
Gannons Road / Captain Cook Drive	AM	0.74	8.8 (Worst: 18.7)	A (Worst: B)	Roundabout	U-Turn from Captain Cook Drive (E)
	PM	0.75	9.4 (Worst: 19.2)	A (Worst: B)		
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	0.95	15.8 (Worst: 47.3)	N/A (Worst: D)	Give Way (Seagull)	RT from Captain Cook Drive (S)
	PM	1.01	19.2 (Worst: >70)	N/A (Worst: F)		RT from Endeavour Road (E)
FUTURE PERFORMANCE – SCENARIO 3						
Gannons Road / Captain Cook Drive	AM	0.83	36	C	Signal	N/A
	PM	0.91	41.4	C		N/A
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	9.28	>70 (Worst: >70)	N/A (Worst: F)	Give Way	RT from Captain Cook Drive (S)
	PM	1.2	>70 (Worst: >70)	N/A (Worst: F)		RT from Captain Cook Drive (S)
Captain Cook Drive / NEW Endeavour Road	AM	0.62	15.3	A	Signals	RT from Endeavour Road (E)
	PM	0.76	28.3	B		RT from Endeavour Road (E)

Notes: Refer to Table 3 Notes

As shown above, the intersection of Gannons Road / Captain Cook Drive is expected to operate at LoS “C” in the AM and PM peak hour periods, whilst the newly created proposed signalised intersection of Endeavour Road / Captain Cook Drive as provided in **Annexure E** is expected to operate at LoS “A” and LoS “B” during the AM and PM peak hour periods respectively. This indicates that the intersection of Captain Cook Drive / Endeavour Road are forecast to operated at an acceptable level of service, with additional spare capacity.

Further, the intersection of Captain Cook Drive / Gannons Road has been reduced compared to Scenario 2, and it likely a much more viable option when considering available




road width. Although as Gannons Road requires two (2) approach and two (2) departure lanes, road widening will be required as part of this signalised intersection design.

The intersection of Captain Cook Drive / Endeavour Road (existing) is again expected to operate at LoS “F” even when right turn movements out of Endeavour Road were displaced indicating that the intersection will also require an infrastructure upgrade.

It should be noted that adding a right turn onto the new proposed intersection with Endeavour Road was considered as a sensitivity analysis but resulted in excessive intersection queuing at the new intersection.

#### 4.4.4 Scenario 4

Scenario 4 assesses the same scenario as Scenario 3, except it includes a signalised intersection at the Endeavour Road / Captain Cook Drive intersection to allow right turn movements from Captain Cook Drive into Endeavour Road to be maintained. The geometry adopted for the signalised intersection of Endeavour Road / Captain Cook Drive is shown in **Figure 8** below.



**FIGURE 8: SCENARIO 4 – INTERSECTION GEOMETRY – ENDEAVOUR ROAD / CAPTAIN COOK DRIVE**

Based upon the above intersection geometry, the resultant intersection performance is shown in **Table 16** below.

**TABLE 16: INTERSECTION PERFORMANCE (SIDRA INTERSECTION 8.0) – SCENARIO 4**

Intersection	Peak Hour	Degree of Saturation <sup>(1)</sup>	Average Delay <sup>(2)</sup> (sec/vehicle)	Level of Service <sup>(3)(4)</sup>	Control Type	Worst Movement
EXISTING PERFORMANCE + SHARKS STAGE 3 & 4						
Gannons Road / Captain Cook Drive	AM	0.74	8.8 (Worst: 18.7)	A (Worst: B)	Roundabout	U-Turn from Captain Cook Drive (E)
	PM	0.75	9.4 (Worst: 19.2)	A (Worst: B)		
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	0.95	15.8 (Worst: 47.3)	N/A (Worst: D)	Give Way (Seagull)	RT from Captain Cook Drive (S)
	PM	1.01	19.2 (Worst: >70)	N/A (Worst: F)		RT from Endeavour Road (E)
FUTURE PERFORMANCE – SCENARIO 4						
Gannons Road / Captain Cook Drive	AM	0.83	36	C	Signal	N/A
	PM	0.91	41.4	C		N/A
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	0.78	16.7	B	Signal	N/A
	PM	0.53	13.1	C		N/A
Captain Cook Drive / NEW Endeavour Road	AM	0.62	15.3	A	Signals	RT from Endeavour Road (E)
	PM	0.76	28.3	B		RT from Endeavour Road (E)

Notes: Refer to Table 3 Notes

As shown above the proposed signalised intersection of Captain Cook Drive / Endeavour Road is forecast to operate at LoS “B” and LoS “C” during the AM and PM peak hour period respectively. This indicates acceptable delays and spare capacity


Refer to **Section 4.4.4** for comments regarding Gannons Road / Captain Cook Drive and Captain Cook Drive / New Endeavour Road signalised intersection.

#### 4.4.5 Summary of Findings


Four (4) access strategies have been assessed as part of this proposed masterplan development and Scenarios 1 to 3 have unacceptable traffic impacts upon the surrounding road network. Scenario 4 was the only access strategy that resulted in acceptable traffic impacts as part of the proposed development which requires the provision of three (3) signalised intersections as detailed below:

- Signalised intersection at Captain Cook Drive / Gannons Road;
- Signalised Intersection of Endeavour Road / Captain Cook Drive;
- Signalised Intersection of new Endeavour Road / Captain Cook Drive.


A further detailed review of the results has been undertaken, including refined modelling of turning lane lengths for the signalised intersection of Gannons Road / Captain Cook Drive and Endeavour Road (existing) / Captain Cook Drive to determine the required intersection geometry to facilitate the development via the provision of the three (3) aforementioned signalised intersections. The refined intersection geometry is shown in **Figure 9**, **Figure 10** and **Figure 11**



**FIGURE 9: CAPTAIN COOK DRIVE / GANNONS ROAD LANE LENGTHS**



**FIGURE 10: NEW ENDEAVOUR ROAD / CAPTAIN COOK DRIVE**



**FIGURE 11: ENDEAVOUR ROAD / CAPTAIN COOK DRIVE**

The detailed SIDRA results based upon the above are reproduced in **Annexure C** for reference, with a summary of the results shown in **Table 17** below.

**TABLE 17: INTERSECTION PERFORMANCE (SIDRA INTERSECTION 8.0) –  
SCENARIO 4 REFINED**

Intersection	Peak Hour	Degree of Saturation <sup>(1)</sup>	Average Delay <sup>(2)</sup> (sec/vehicle)	Level of Service <sup>(3)(4)</sup>	Control Type	Worst Movement
EXISTING PERFORMANCE + SHARKS STAGE 3 & 4						
Gannons Road / Captain Cook Drive	AM	0.74	8.8 (Worst: 18.7)	A (Worst: B)	Roundabout	U-Turn from Captain Cook Drive (E)
	PM	0.75	9.4 (Worst: 19.2)	A (Worst: B)		
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	0.95	15.8 (Worst: 47.3)	N/A (Worst: D)	Give Way (Seagull)	RT from Captain Cook Drive (S)
	PM	1.01	19.2 (Worst: >70)	N/A (Worst: F)		RT from Endeavour Road (E)
FUTURE PERFORMANCE – SCENARIO 4 (Refined)						
Gannons Road / Captain Cook Drive	AM	0.83	33.8	C	Signal	N/A
	PM	0.95	41.2	C		N/A
Captain Cook Drive / Endeavour Road <sup>(5)</sup>	AM	0.78	16.7	B	Signal	N/A
	PM	0.53	13.1	C		N/A
Captain Cook Drive / NEW Endeavour Road	AM	0.62	15.3	A	Signals	RT from Endeavour Road (E)
	PM	0.76	28.3	B		RT from Endeavour Road (E)

Notes: Refer to Table 3 Notes

As shown above the results reflect the same or similar results to those detailed in **Table 14**. The provision of three (3) signalised intersection along Captain Cook Drive is required to facilitate the proposed development.

As part of the provision of signalised intersections, it is expected that the corridor of Captain Cook Drive, including all other signalised intersections along the corridor will be required to be linked, to ensure traffic flow efficiency is maintained and optimised for through vehicle movements travelling along Captain Cook Drive. It may be necessary to undertake further traffic modelling along the corridor of Captain Cook Drive in consultation with the relevant road authorities (Transport for New South Wales and Sutherland Shire Council) for areas that are not covered within this report.



#### 4.4.6 Impacts of Road Infrastructure

As a result of the proposed road infrastructure a number of considerations will need to be discussed with the relevant road authorities (Sutherland Shire Council and TfNSW) and local businesses and the community. Midblock traffic flows under the proposed development scale result in the following to the west of the intersection of Endeavour Road / Captain Cook Drive:

- 2,213 peak hour vehicle trips westbound along Captain Cook Drive during the AM peak;
- 2,310 peak hour vehicle trips eastbound along Captain Cook Drive during the AM peak;
- 2,386 peak hour vehicle trips westbound along Captain Cook Drive during the PM peak;
- 1,765 peak hour vehicle trips eastbound along Captain Cook Drive during the PM peak;

The above traffic volumes result in a Level of Service “D” for two (2) traffic flow lanes in one direction. Although based upon traffic modelling will require three (3) traffic flow lanes in each direction at signalised intersections to ensure an acceptable level of service. Considering this, kerbside parking will be required to be removed during peak operating periods along both sides of Captain Cook Drive on the approach and departures to signalised intersections to ensure traffic flow efficiency is maintained along the corridor. To allow for this clearway restrictions during the AM peak hour periods will be necessary on both sides of the road. During the PM peak hour period clearway conditions will only be required for vehicles travelling westbound.

The provision of a new short road connection with Captain Cook Drive from the bend in Endeavour Road will require modifications to the existing traffic flow along Endeavour Road. Traffic flow along Endeavour Road which currently runs parallel with Captain Cook Drive will be required to be restricted to one-way southbound to ensure traffic flow efficiency and road safety considerations are maintained. The sketch in **Annexure E** shows this arrangement. In addition to this kerbside parking will be required to be removed along Endeavour Road to facilitate two (2) approach lanes to the new signalised intersections and to allow sufficient queue length.

The road infrastructure at the intersection of Gannons Road / Captain Cook Drive will require land acquisition along the eastern side of the road, requiring removal of on-street and off-site car parking (sports field). Replacement of off-site car parking can be provided on the subject site, with the provision of a signalised intersection providing safe pedestrian access from the subject site to the Sports Field. As part of any road widening within Gannons Road, existing pedestrian and cycling facilities will need to be reinstated.

The removal of the roundabout intersection at Gannons Road / Captain Cook Drive will remove the ability for vehicles to undertake a safe U-turn movement. It should be noted that the right turn movements into Foreshore Boulevard is not permitted at the existing

signalised intersection of Captain Cook Drive / Foreshore Boulevard. Consideration should be made as part of the development to provide a U-turn facility on-site to facilitate an alternative safe traffic route for this movement. The “U” turn movement (from & to the east along Captain Cook Drive) at the Gannons Road / Captain Cook Drive roundabout is also used by buses associated with the peak event traffic management plan for the transport of spectators attending sporting events at Shark Park.

A high-level concept has been provided for the design of a potential signalised intersection at Gannons Road / Captain Cook Drive and is reproduced in **Annexure F** for reference. The concept has been provided to demonstrate the extent of widening required for the approach and departure lanes for a potential signalised intersection. The high level concept is not based upon any TfNSW requirements or Austroads requirement for signalised intersection and is purely conceptual. Further detailed design of any signalised intersection will be development through the development application stage in consultation with relevant road authorities for all three (3) proposed / required signalised intersections.

## 5 CONCLUSION

The subject Masterplan Mixed Use Development at 13 Endeavour Road, Caringbah (as depicted in **Annexure A**) has been assessed in regards to its traffic and parking impacts. The following outcomes of this masterplan traffic impact assessment are relevant to note:

- The proposal requires the provision of **3,056** car parking spaces based upon Council's DCP requirements. The plans indicate the provision of **1,484** car parking spaces, a shortfall of **1,572** spaces from Council's DCP. The only consideration to a reduction in car parking is based upon the retail components of the site being ancillary to the office component of the development. Adopting a 50% reduction in retail car parking results in the car parking requirements of **2,968** spaces, which is a shortfall of **1,484** car parking spaces from Council's DCP requirement. This is still a significant shortfall in provision of car parking and as such the development should provide additional car parking or investigate alternative solutions / modes of transport to and from the site.
- The car parking layout as depicted in **Annexure A**, will be assessed at the development application stage to ensure compliance with the relevant Australian Standards, namely *AS2890.1:2004*, *AS2890.2:2018*, *AS2890.6:2009* and *AS2890.5:2020*. If the masterplan proposal were to be approved, the driveway access, circulation areas and on-site parking areas of any development on the site would be required to comply. It would be a requirement at the Development Application and Construction Certificate stage that each Lot be checked for compliance with parking provision and driveway location requirements.
- The largest vehicle expected to travel to and from the site will be a 12.5m length Heavy Rigid Vehicle for deliveries and waste collection for office and retail components. Industrial and Warehouse components of the site may require the provision of 19m length Articulated Vehicles and is subject to each lots tenancy size and fitout. Access for service vehicles can be facilitated from either Captain Cook Drive / Gannons Road or Endeavour Road from existing approved B-double routes.
- It is expected that due to the internal road layout, the site will be limited to access to and from the intersection of Gannons Road / Captain Cook Drive by vehicles up to a 12.5m length Heavy Rigid Vehicle, whilst 19m length Articulated Vehicles if required for the development will be restricted to Endeavour Road.
- The traffic generation associated with the proposal is in the order of **2,602** vehicle trips in the AM peak hour period (2,067 inbound, 535 outbound) and **2,602** vehicles trips in the PM peak hour period (535 inbound, 2,067 outbound). This assumes that the retail component of the site does not generate traffic from outside the site and is based upon the retail portion of the site servicing the proposed office space of the development.

- Multiple access strategies have been assessed as part of this masterplan assessment. The only viable option to ensure the development has acceptable traffic impacts upon the local road network is to provide three (3) signalised intersections at the following locations:
  - Signalised intersection at Captain Cook Drive / Gannons Road;
  - Signalised Intersection of Endeavour Road / Captain Cook Drive;
  - Signalised Intersection of new Endeavour Road / Captain Cook Drive.
- A preliminary mark-up / sketch has been provided in **Annexure E** and **Annexure F** for a potential signalised intersection of new Endeavour Road / Captain Cook Drive and Captain Cook Drive / Gannons Road. Further detailed design of required road infrastructure will be part of the development application stage in consultation with road authorities (Sutherland Shire Council and Transport for New South Wales).
- As part of the provision of signalised intersections, it is expected that the corridor of Captain Cook Drive, including all other signalised intersections along the corridor will be required to be linked, to ensure traffic flow efficiency is maintained and optimised for through vehicle movements travelling along Captain Cook Drive. It may be necessary to undertake further traffic modelling along the corridor of Captain Cook Drive in consultation with the relevant road authorities (Transport for New South Wales and Sutherland Shire Council) for areas that are not covered within this report.
- The relevant impacts of the proposed development and required road infrastructure to facilitate the proposed development is summarised below:
  - Removal of kerbside parking on the approach and departure to signalised intersections along both sides of Captain Cook Drive to ensure traffic flow efficiency is maintained along the corridor. Clearway restrictions during the AM peak hour periods will be necessary on both sides of the road, whilst during the PM peak hour period clearway conditions will only be required for vehicles travelling westbound.
  - The provision of a new signalised intersection with Captain Cook Drive that includes a new short road link from the bend in Endeavour Road will require modifications to the existing traffic flow along Endeavour Road. Traffic flow along Endeavour Road which currently runs parallel with Captain Cook Drive will be required to be restricted to one-way southbound to ensure traffic flow efficiency and road safety considerations are maintained.
  - The road infrastructure at the intersection of Gannons Road / Captain Cook Drive will require land acquisition along the eastern side of the road, requiring removal of on-street and off-site car parking (sports field). Replacement of off-site car parking can be provided on the subject site, with the provision of a signalised intersection providing safe pedestrian access from the subject site

to the Sports Field. As part of any road widening within Gannons Road, existing pedestrian and cycling facilities will need to be reinstated.

- The removal of the roundabout intersection at Gannons Road / Captain Cook Drive will remove the ability for vehicles to undertake a safe U-turn movement. Consideration should be made as part of the development to provide a U-turn facility on-site to facilitate an alternative safe traffic route for this movement.



**ANNEXURE A: PROPOSED PLANS**  
**(2 SHEETS)**



Indicative Site Evolution

7.14 Indicative Structure Plan

Use	GFA
Industrial	25,272 sqm
Ancillary Industrial Office	7,382 sqm
Warehouse	1,824 sqm
Ancillary Warehouse Office	3,846 sqm
Office and Business Premises	99,286 sqm
Retail	4,307 sqm
Food & Beverage	3,561 sqm
Recreation	860 sqm
Hotel	3,624 sqm
Total	149,962 sqm
FSR	1.21:1
Car Parking	1,054 Spaces
Surface Car Parking	430 Spaces
Total Car Parking	1,484 Spaces

KEY

(X)

Storey Height

Industrial / Warehouse

Ancillary Industrial / Warehouse Office

Office and Business Premises


Retail

Food & Beverage

Recreation

Hotel

Car Parking / Storage



1:2,000 @ A3



# Site Ground Floor Plan

Scale  
1:2000 @A3

0 10 20 30 40 50 100



Drawing number  
6272\_MPSK\_0010  
Revision number  
[00]

Project number  
6272  
Project name  
TBC

Project address  
13 Endeavour Road, Caringbah  
Client  
Aliro Group

SJB Architects  
Level 2, 490 Crown Street, Surry Hills NSW 2010  
T. 61 2 9380 9911 sjb.com.au  
SJB Architecture (NSW) Pty Ltd  
ABN 20 310 373 425 ACN 081 094 724  
Adam Haddow 7188 John Pradel 7004






**ANNEXURE B: TRAFFIC COUNTS**  
**(5 SHEETS)**

**Job No.** : N5571  
**Client** : McLaren Traffic Engineering  
**Suburb** : Wooloware  
**Location** : 1. Captain Cook Dr/ Gannons Rd/ Site Access  
  
**Day/Date** : Tue, 4th Feb 2020  
**Weather** : Fine  
**Description** : Classified Intersection Count  
: 15 mins Data

	Class 1	Class 2
Classifications	Lights	Heavies




Approach	Gannons Rd												Captain Cook Dr											
Direction	Direction 1 (Left Turn)			Direction 2 (Through)			Direction 3 (Right Turn)			Direction 3U (U Turn)			Direction 4 (Left Turn)			Direction 5 (Through)			Direction 6 (Right Turn)			Direction 6U (U Turn)		
Time Period	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total
7:00 to 7:15	165	0	165	0	0	0	23	1	24	0	0	0	26	1	27	306	12	318	0	0	0	1	0	1
7:15 to 7:30	168	3	171	0	0	0	33	4	37	0	0	0	25	1	26	285	21	306	1	0	1	4	6	10
7:30 to 7:45	212	2	214	0	0	0	30	4	34	0	0	0	32	1	33	263	18	281	0	0	0	3	1	4
7:45 to 8:00	222	4	226	0	0	0	36	0	36	0	0	0	22	1	23	240	15	255	0	0	0	7	0	7
8:00 to 8:15	177	2	179	0	0	0	28	2	30	0	0	0	21	1	22	222	25	247	1	0	1	7	0	7
8:15 to 8:30	202	2	204	0	0	0	36	2	38	0	0	0	34	2	36	246	26	272	0	0	0	4	1	5
8:30 to 8:45	172	2	174	0	0	0	49	7	56	0	0	0	23	1	24	247	33	280	0	0	0	2	0	2
8:45 to 9:00	221	5	226	0	0	0	45	2	47	0	0	0	25	2	27	237	40	277	0	0	0	4	2	6
<b>AM Totals</b>	<b>1,539</b>	<b>20</b>	<b>1,559</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>280</b>	<b>22</b>	<b>302</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>208</b>	<b>10</b>	<b>218</b>	<b>2,046</b>	<b>190</b>	<b>2,236</b>	<b>2</b>	<b>0</b>	<b>2</b>	<b>32</b>	<b>10</b>	<b>42</b>
16:00 to 16:15	126	1	127	0	0	0	22	1	23	0	0	0	19	1	20	197	13	210	0	0	0	4	0	4
16:15 to 16:30	96	2	98	0	0	0	36	0	36	0	0	0	16	0	16	161	10	171	0	0	0	3	0	3
16:30 to 16:45	100	1	101	2	0	2	32	1	33	0	0	0	16	2	18	176	6	182	0	0	0	4	0	4
16:45 to 17:00	105	4	109	0	0	0	33	0	33	0	0	0	14	0	14	171	5	176	0	0	0	5	0	5
17:00 to 17:15	131	0	131	0	0	0	34	1	35	0	0	0	8	1	9	199	4	203	0	0	0	8	0	8
17:15 to 17:30	114	1	115	0	0	0	22	0	22	0	0	0	5	0	5	206	2	208	0	0	0	4	0	4
17:30 to 17:45	100	3	103	0	0	0	36	1	37	0	0	0	11	0	11	184	0	184	0	0	0	5	0	5
17:45 to 18:00	104	0	104	0	0	0	35	0	35	0	0	0	14	0	14	159	3	162	0	0	0	6	0	6
<b>PM Totals</b>	<b>876</b>	<b>12</b>	<b>888</b>	<b>2</b>	<b>0</b>	<b>2</b>	<b>250</b>	<b>4</b>	<b>254</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>103</b>	<b>4</b>	<b>107</b>	<b>1,453</b>	<b>43</b>	<b>1,496</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>39</b>	<b>0</b>	<b>39</b>



Approach	Site Access												Captain Cook Dr												Crossing Pedestrians									
Direction	Direction 7 (Left Turn)			Direction 8 (Through)			Direction 9 (Right Turn)			Direction 9U (U Turn)			Direction 10 (Left Turn)			Direction 11 (Through)			Direction 12 (Right Turn)			Direction 12U (U Turn)												
Time Period	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	B to A	A to B	D to C	C to D	F to E	E to F	H to G	G to H	Total	
7:00 to 7:15	1	0	1	3	0	3	8	0	8	0	0	0	0	0	0	109	32	141	103	7	110	1	0	1	0	0	0	0	0	0	0	0	0	
7:15 to 7:30	0	0	0	3	0	3	5	0	5	0	0	0	0	0	0	110	21	131	57	8	65	1	1	2	0	0	0	0	0	0	0	0	0	
7:30 to 7:45	0	0	0	2	0	2	4	0	4	0	0	0	0	0	0	146	19	165	64	7	71	4	1	5	0	0	0	0	0	0	0	0	0	
7:45 to 8:00	2	0	2	3	0	3	5	0	5	0	0	0	3	0	3	138	30	168	67	5	72	0	0	0	0	0	0	0	0	0	0	0	0	
8:00 to 8:15	0	0	0	4	0	4	0	0	0	0	0	0	0	0	0	110	27	137	88	11	99	1	0	1	0	0	0	0	0	0	0	0	0	
8:15 to 8:30	0	0	0	4	0	4	3	0	3	0	0	0	1	0	1	150	28	178	84	1	85	0	0	0	0	1	0	0	1	0	0	0	2	
8:30 to 8:45	3	0	3	2	0	2	3	0	3	0	0	0	1	0	1	129	14	143	129	23	152	1	1	2	0	0	1	0	0	1	0	0	2	
8:45 to 9:00	1	0	1	3	0	3	2	1	3	0	0	0	4	0	4	132	21	153	74	3	77	1	3	4	0	0	0	0	0	0	0	0	0	
AM Totals	7	0	7	24	0	24	30	1	31	0	0	0	9	0	9	1,024	192	1,216	666	65	731	9	6	15	0	1	1	0	1	1	0	0	4	
16:00 to 16:15	0	0	0	0	0	0	3	0	3	0	0	0	0	0	0	240	9	249	167	1	168	2	0	2	0	0	0	0	0	0	0	0	0	
16:15 to 16:30	1	0	1	1	0	1	2	0	2	0	0	0	0	0	0	282	8	290	170	0	170	3	0	3	0	0	0	0	0	0	0	0	0	
16:30 to 16:45	0	0	0	4	0	4	9	0	9	0	0	0	0	0	0	285	3	288	174	3	177	3	0	3	0	0	0	0	0	0	0	0	0	
16:45 to 17:00	1	0	1	2	0	2	2	0	2	0	0	0	0	0	0	282	6	288	169	1	170	3	0	3	0	0	0	0	0	0	0	0	0	
17:00 to 17:15	0	0	0	2	0	2	3	0	3	0	0	0	0	0	0	343	3	346	141	2	143	8	0	8	0	0	0	0	0	0	0	0	0	
17:15 to 17:30	0	0	0	0	0	0	5	0	5	0	0	0	1	0	1	310	3	313	139	1	140	3	0	3	0	0	0	0	0	0	0	0	0	
17:30 to 17:45	0	0	0	2	0	2	6	0	6	0	0	0	0	0	0	305	1	306	131	0	131	6	0	6	0	0	0	0	0	0	0	0	0	
17:45 to 18:00	0	0	0	1	0	1	3	0	3	0	0	0	0	0	0	254	3	257	129	0	129	3	0	3	0	0	0	0	0	0	0	0	0	
PM Totals	2	0	2	12	0	12	33	0	33	0	0	0	1	0	1	2,301	36	2,337	1,220	8	1,228	31	0	31	0	0	0	0	0	0	0	0	0	

Job No. : N5571  
Client : McLaren Traffic Engineering  
Suburb : Wooloware  
Location : 2. Captain Cook Dr/ Endeavour Rd  
  
Day/Date : Tue, 4th Feb 2020  
Weather : Fine  
Description : Classified Intersection Count  
: 15 mins Data

	Class 1	Class 2
Classifications	Lights	Heavies



Approach		Captain Cook Dr									
Direction											
Time Period		Direction 5 (Through)			Direction 6 (Right Turn)			Direction 6U (U Turn)			
7:00 to 7:15		Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	
7:15 to 7:30		329	7	336	140	1	141	0	0	0	
7:30 to 7:45		327	19	346	156	7	163	0	0	0	
7:45 to 8:00		342	17	359	151	4	155	0	0	0	
8:00 to 8:15		325	13	338	155	2	157	0	0	0	
8:15 to 8:30		324	25	349	88	4	92	0	0	0	
8:30 to 8:45		361	20	381	107	7	114	0	0	0	
8:45 to 9:00		313	28	341	91	7	98	1	0	1	
AM Totals		312	35	347	123	6	129	0	0	0	
16:00 to 16:15		2,633	164	2,797	1,011	38	1,049	1	0	1	
16:15 to 16:30		285	5	290	60	4	64	0	0	0	
16:30 to 16:45		215	5	220	45	4	49	0	0	0	
16:45 to 17:00		246	4	250	46	3	49	0	0	0	
17:00 to 17:15		237	8	245	43	0	43	0	0	0	
17:15 to 17:30		304	3	307	59	0	59	0	0	0	
17:30 to 17:45		261	3	264	57	0	57	0	0	0	
17:45 to 18:00		279	2	281	45	0	45	0	0	0	
PM Totals	208	3	211	42	0	42	0	0	0		
	2,035	33	2,068	397	11	408	0	0	0		



Approach	Endeavour Rd									Captain Cook Dr									Crossing Pedestrians							
Direction	Direction 7 (Left Turn)			Direction 9 (Right Turn)			Direction 9U (U Turn)			Direction 10 (Left Turn)			Direction 11 (Through)			Direction 12U (U Turn)										
Time Period	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total	Lights	Heavies	Total		D to C	C to D	F to E	E to F	H to G	G to H	Total
7:00 to 7:15	46	6	52	6	1	7	0	0	0	26	4	30	166	29	195	0	0	0		0	0	0	0	0	0	0
7:15 to 7:30	26	7	33	3	1	4	0	0	0	44	2	46	138	16	154	0	0	0		0	0	0	0	0	0	0
7:30 to 7:45	51	7	58	3	1	4	0	0	0	38	4	42	168	26	194	0	0	0		0	0	0	0	0	0	0
7:45 to 8:00	32	4	36	7	1	8	0	0	0	53	2	55	164	24	188	0	0	0		0	0	0	0	0	0	0
8:00 to 8:15	38	10	48	7	3	10	0	0	0	41	1	42	179	33	212	0	0	0		0	0	0	0	0	0	0
8:15 to 8:30	45	4	49	9	2	11	0	0	0	47	3	50	188	22	210	0	0	0		0	0	0	0	0	0	0
8:30 to 8:45	64	5	69	7	1	8	0	0	0	37	1	38	205	30	235	0	0	0		0	0	0	1	0	0	1
8:45 to 9:00	34	5	39	10	1	11	0	0	0	36	6	42	162	22	184	0	0	0		0	0	0	0	0	0	0
AM Totals	336	48	384	52	11	63	0	0	0	322	23	345	1,370	202	1,572	0	0	0		0	0	0	0	1	0	1
16:00 to 16:15	156	2	158	52	3	55	0	0	0	28	1	29	270	5	275	0	0	0		0	0	0	0	0	1	1
16:15 to 16:30	130	1	131	39	2	41	0	0	0	24	3	27	300	10	310	0	0	0		0	0	0	1	0	0	1
16:30 to 16:45	138	1	139	51	2	53	0	0	0	25	1	26	310	3	313	0	0	0		0	0	0	1	0	0	1
16:45 to 17:00	164	2	166	42	1	43	0	0	0	23	3	26	315	4	319	0	0	0		0	0	0	0	0	0	0
17:00 to 17:15	185	2	187	72	2	74	0	0	0	15	3	18	311	4	315	0	0	0		0	0	0	0	0	0	0
17:15 to 17:30	143	2	145	33	1	34	0	0	0	21	0	21	308	3	311	0	0	0		0	0	0	0	0	0	0
17:30 to 17:45	112	0	112	26	1	27	0	0	0	9	3	12	310	1	311	0	0	0		0	0	1	0	0	0	1
17:45 to 18:00	82	1	83	29	0	29	0	0	0	24	0	24	298	3	301	0	0	0		0	0	0	0	0	0	0
PM Totals	1,110	11	1,121	344	12	356	0	0	0	169	14	183	2,422	33	2,455	0	0	0		0	0	1	2	0	1	4

**TURNING MOVEMENT SURVEY**

Captain Cook Dr and Gannons Rd, Woollooware

Friday, 4 November 2016

<b>Weather:</b>	Fine
<b>Suburban:</b>	Woollooware
<b>Customer:</b>	McLaren

<b>Survey Start</b>	
<b>AM:</b>	
<b>PM:</b>	16:00


<b>Peakhour</b>	
<b>AM:</b>	
<b>PM:</b>	4:30 PM-5:30 PM

**All Vehicles**

Time		North Approach Captain Cook Dr				East Approach Captain Cook Dr				South Approach Gannons Rd				West Approach Captain Cook Dr				Hourly Total	
Period Start	Period End	U	R	SB	L	U	R	WB	L	U	R	NB	L	U	R	EB	L	Hour	Peak
16:00	16:15	0	7	7	0	0	0	218	23	0	39	1	96	0	146	295	0	3327	
16:15	16:30	0	2	5	4	0	0	185	16	0	42	0	94	0	153	316	0	3402	
16:30	16:45	0	5	5	0	0	0	200	20	0	29	1	110	0	163	342	0	3500	Peak
16:45	17:00	0	8	7	2	0	0	185	12	0	32	0	86	0	143	328	0	3376	
17:00	17:15	0	33	13	16	0	0	225	23	1	27	1	89	0	149	330	0	3361	
17:15	17:30	0	17	10	7	0	0	240	14	0	28	0	72	0	120	407	0	3205	
17:30	17:45	0	14	6	6	0	0	191	14	0	36	0	62	0	110	312	0	2978	
17:45	18:00	0	13	2	1	0	0	211	15	1	31	0	69	0	152	293	0	2948	
18:00	18:15	0	13	5	3	0	0	174	18	0	32	1	64	0	136	305	0	2661	
18:15	18:30	0	9	5	3	0	0	165	12	1	31	1	66	0	111	284	0		
18:30	18:45	0	6	2	1	0	0	175	12	1	29	0	61	0	148	284	2		
18:45	19:00	0	2	1	0	0	0	117	12	0	35	0	60	0	81	192	1		

Peak Time		North Approach Captain Cook Dr				East Approach Captain Cook Dr				South Approach Gannons Rd				West Approach Captain Cook Dr				Peak total	
Period Start	Period End	U	R	SB	L	U	R	WB	L	U	R	NB	L	U	R	EB	L		
16:30	17:30	0	63	35	25	0	0	850	69	1	116	2	357	0	575	1407	0	3500	

**Graphic**



**Light Vehicles**

Time		North Approach Captain Cook Dr				East Approach Captain Cook Dr				South Approach Gannons Rd				West Approach Captain Cook Dr			
Period Start	Period End	U	R	SB	L	U	R	WB	L	U	R	NB	L	U	R	EB	L
16:00	16:15	0	6	7	0	0	0	200	23	0	38	1	93	0	144	286	0
16:15	16:30	0	2	5	4	0	0	170	16	0	42	0	89	0	152	308	0
16:30	16:45	0	5	5	0	0	0	192	20	0	28	1	109	0	162	333	0
16:45	17:00	0	8	7	2	0	0	177	12	0	31	0	85	0	143	323	0
17:00	17:15	0	33	13	16	0	0	223	23	1	27	1	88	0	148	322	0
17:15	17:30	0	17	10	7	0	0	239	14	0	28	0	72	0	119	401	0
17:30	17:45	0	14	6	6	0	0	189	14	0	36	0	60	0	108	307	0
17:45	18:00	0	13	2	1	0	0	210	15	1	29	0	68	0	151	288	0
18:00	18:15	0	13	5	3	0	0	173	18	0	32	1	64	0	135	301	0
18:15	18:30	0	9	5	3	0	0	161	12	1	31	1	65	0	110	279	0
18:30	18:45	0	6	2	1	0	0	174	12	1	29	0	61	0	147	278	0
18:45	19:00	0	2	1	0	0	0	116	12	0	35	0	59	0	81	192	0

**Heavy Vehicles**

Time		North Approach Captain Cook Dr				East Approach Captain Cook Dr				South Approach Gannons Rd				West Approach Captain Cook Dr			
Period Start	Period End	U	R	SB	L	U	R	WB	L	U	R	NB	L	U	R	EB	L
16:00	16:15	0	1	0	0	0	0	18	0	0	1	0	3	0	2	9	0
16:15	16:30	0	0	0	0	0	0	15	0	0	0	0	5	0	1	8	0
16:30	16:45	0	0	0	0	0	0	8	0	0	1	0	1	0	1	9	0
16:45	17:00	0	0	0	0	0	0	8	0	0	1	0	1	0	0	5	0
17:00	17:15	0	0	0	0	0	0	2	0	0	0	0	1	0	1	8	0
17:15	17:30	0	0	0	0	0	0	1	0	0	0	0	0	0	1	6	0
17:30	17:45	0	0	0	0	0	0	2	0	0	0	0	2	0	2	5	0
17:45	18:00	0	0	0	0	0	0	1	0	0	2	0	1	0	1	5	0
18:00	18:15	0	0	0	0	0	0	1	0	0	0	0	0	0	1	4	0
18:15	18:30	0	0	0	0	0	0	4	0	0	0	0	1	0	1	5	0
18:30	18:45	0	0	0	0	0	0	1	0	0	0	0	0	0	1	6	2
18:45	19:00	0	0	0	0	0	0	1	0	0	0	0	1	0	0	0	1

**Cyclists**

Time		North Approach Captain Cook Dr				East Approach Captain Cook Dr				South Approach Gannons Rd				West Approach Captain Cook Dr			
Period Start	Period End	U	R	SB	L	U	R	WB	L	U	R	NB	L	U	R	EB	L
16:00	16:15	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	0
16:15	16:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0
16:30	16:45	0	1	0	1	0	0	0	1	0	0	0	0	0	1	1	0
16:45	17:00	0	0	0	0	0	0	1	0	0	0	0	0	0	0	3	0
17:00	17:15	0	0	0	0	0	0	0	0	0	0	0	0	0	1	2	0
17:15	17:30	0	0	1	0	0	0	0	0	0	0	0	0	0	0	4	0
17:30	17:45	0	0	0	0	0	0	0	0	0	0	0	0	0	1	2	0
17:45	18:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0
18:00	18:15	0	0	0	0	0	0	0	0	0	0	0	1	0	0	2	0
18:15	18:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3	0
18:30	18:45	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	0
18:45	19:00	0	0	0	0	0	0	0	0	0	3	0	0	0	0	0	0



**ANNEXURE C: SIDRA RESULTS**  
**(36 SHEETS)**

## EXISTING

### MOVEMENT SUMMARY



#### Site: 1 [Captain Cook Drive / Gannons Road - Existing AM]

Captain Cook Drive / Gannons Road  
Existing Volumes (4/2/20)  
Peak 8:00AM - 9:00AM  
Site Category: (None)  
Roundabout

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	783	1.4	0.433	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8
2	T1	1	0.0	0.269	7.3	LOS A	1.5	10.9	0.79	0.92	0.79	34.2
3	R2	171	7.6	0.269	11.2	LOS A	1.5	10.9	0.79	0.92	0.79	48.1
3u	U	1	0.0	0.269	12.8	LOS A	1.5	10.9	0.79	0.92	0.79	45.9
Approach		956	2.5	0.433	3.9	LOS A	1.5	10.9	0.14	0.44	0.14	48.6
East: Captain Cook Drive (E)												
4	L2	109	5.5	0.649	10.1	LOS A	5.9	45.0	0.77	0.88	0.94	50.2
5	T1	1076	11.5	0.649	10.2	LOS A	6.0	46.3	0.77	0.87	0.93	56.0
6	R2	1	0.0	0.649	14.4	LOS A	6.0	46.3	0.77	0.86	0.92	40.9
6u	U	20	15.0	0.649	17.4	LOS B	6.0	46.3	0.77	0.86	0.92	55.8
Approach		1206	11.0	0.649	10.4	LOS A	6.0	46.3	0.77	0.87	0.93	55.4
North: Toyota Access (N)												
7	L2	4	0.0	0.008	5.2	LOS A	0.0	0.2	0.68	0.55	0.68	38.8
8	T1	13	0.0	0.031	3.1	LOS A	0.1	1.0	0.68	0.62	0.68	36.0
9	R2	9	11.1	0.031	6.1	LOS A	0.1	1.0	0.68	0.62	0.68	37.9
9u	U	1	0.0	0.031	6.6	LOS A	0.1	1.0	0.68	0.62	0.68	31.2
Approach		27	3.7	0.031	4.5	LOS A	0.1	1.0	0.68	0.61	0.68	36.8
West: Captain Cook Drive (W)												
10	L2	6	0.0	0.415	5.9	LOS A	2.9	23.1	0.51	0.56	0.51	39.6
11	T1	611	14.7	0.415	6.4	LOS A	3.1	23.5	0.50	0.58	0.50	59.4
12	R2	413	9.2	0.415	11.1	LOS A	3.1	23.5	0.48	0.64	0.48	51.8
12u	U	7	57.1	0.415	14.6	LOS B	3.1	23.5	0.48	0.64	0.48	46.7
Approach		1037	12.7	0.415	8.3	LOS A	3.1	23.5	0.50	0.60	0.50	55.9
All Vehicles		3226	9.0	0.649	7.8	LOS A	6.0	46.3	0.50	0.66	0.56	53.2

## MOVEMENT SUMMARY



### Site: 1 [Captain Cook Drive / Gannons Road - Existing PM]

Captain Cook Drive / Gannons Road  
Existing Volumes (4/2/20)  
Peak 4:30PM - 5:30PM  
Site Category: (None)  
Roundabout

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	456	1.3	0.252	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8
2	T1	2	50.0	0.155	7.8	LOS A	0.8	5.7	0.67	0.81	0.67	34.4
3	R2	123	1.6	0.155	9.8	LOS A	0.8	5.7	0.67	0.81	0.67	49.6
3u	U	1	100.0	0.155	15.0	LOS B	0.8	5.7	0.67	0.81	0.67	45.7
Approach		582	1.7	0.252	4.0	LOS A	0.8	5.7	0.15	0.44	0.15	48.9
East: Captain Cook Drive (E)												
4	L2	46	6.5	0.527	11.0	LOS A	4.1	29.1	0.81	0.93	0.95	49.8
5	T1	769	2.2	0.527	10.7	LOS A	4.2	30.0	0.81	0.91	0.94	57.6
6	R2	1	0.0	0.527	15.1	LOS B	4.2	30.0	0.81	0.90	0.94	40.7
6u	U	21	0.0	0.527	17.5	LOS B	4.2	30.0	0.81	0.90	0.94	59.2
Approach		837	2.4	0.527	10.9	LOS A	4.2	30.0	0.81	0.92	0.94	57.1
North: Toyota Access (N)												
7	L2	1	0.0	0.003	8.3	LOS A	0.0	0.1	0.81	0.60	0.81	37.5
8	T1	8	0.0	0.055	6.5	LOS A	0.3	2.1	0.85	0.82	0.85	34.8
9	R2	19	0.0	0.055	9.2	LOS A	0.3	2.1	0.85	0.82	0.85	37.7
9u	U	1	0.0	0.055	10.0	LOS A	0.3	2.1	0.85	0.82	0.85	30.2
Approach		29	0.0	0.055	8.4	LOS A	0.3	2.1	0.84	0.81	0.84	36.5
West: Captain Cook Drive (W)												
10	L2	1	0.0	0.654	6.0	LOS A	6.5	46.0	0.58	0.55	0.58	39.5
11	T1	1235	1.2	0.654	6.2	LOS A	6.6	47.0	0.57	0.56	0.57	59.8
12	R2	630	1.1	0.654	11.0	LOS A	6.6	47.0	0.54	0.61	0.54	52.1
12u	U	17	0.0	0.654	13.4	LOS A	6.6	47.0	0.54	0.61	0.54	59.4
Approach		1883	1.2	0.654	7.9	LOS A	6.6	47.0	0.56	0.58	0.56	56.9
All Vehicles		3331	1.6	0.654	7.9	LOS A	6.6	47.0	0.55	0.64	0.58	55.2

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Existing AM, Stage 1]

Captain Cook Drive / Endeavour Road  
Existing Volumes (4/2/20)  
Peak 7:30AM - 8:30AM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	518	3.3	0.865	26.0	LOS B	12.3	88.4	0.91	1.68	3.17	41.3
Approach		518	3.3	0.865	26.0	NA	12.3	88.4	0.91	1.68	3.17	41.3
East: Endeavour Road (E)												
4	L2	191	13.1	0.112	5.8	LOS A	0.0	0.0	0.00	0.52	0.00	54.5
6	R2	33	21.2	0.250	36.5	LOS C	0.8	6.8	0.91	0.98	0.99	36.6
Approach		224	14.3	0.250	10.3	LOS A	0.8	6.8	0.13	0.59	0.15	50.9
North: Captain Cook Drive (N)												
7	L2	189	5.3	0.204	8.2	LOS A	0.7	5.3	0.48	0.72	0.48	52.1
8	T1	804	13.1	0.224	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		993	11.6	0.224	1.6	LOS A	0.7	5.3	0.09	0.14	0.09	58.3
All Vehicles		1735	9.5	0.865	10.0	NA	12.3	88.4	0.34	0.66	1.02	51.1

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Existing AM, Stage 2]

Captain Cook Drive / Endeavour Road  
Existing Volumes (4/2/20)  
Peak 7:30AM - 8:30AM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1427	5.3	0.378	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1427	5.3	0.378	0.1	NA	0.0	0.0	0.00	0.00	0.00	59.9
East: Endeavour Road (E)												
6	R2	33	21.2	0.021	7.5	LOS A	0.1	0.7	0.59	0.74	0.59	45.6
Approach		33	21.2	0.021	7.5	LOS A	0.1	0.7	0.59	0.74	0.59	45.6
All Vehicles		1460	5.6	0.378	0.2	NA	0.1	0.7	0.01	0.02	0.01	59.6



## MOVEMENT SUMMARY

### Site: 101 [Captain Cook Drive / Endeavour Road - Existing PM, Stage 1 ]

Captain Cook Drive / Endeavour Road  
Existing Volumes (4/2/20)  
Peak 4:30PM - 5:30PM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	208	1.4	0.594	22.9	LOS B	3.2	22.5	0.88	1.11	1.48	42.9
Approach		208	1.4	0.594	22.9	NA	3.2	22.5	0.88	1.11	1.48	42.9
East: Endeavour Road (E)												
4	L2	637	1.1	0.346	5.7	LOS A	0.0	0.0	0.00	0.53	0.00	54.8
6	R2	204	2.9	0.856	75.1	LOS F	8.3	59.7	0.98	1.54	2.94	26.5
Approach		841	1.5	0.856	22.5	LOS B	8.3	59.7	0.24	0.77	0.71	43.7
North: Captain Cook Drive (N)												
7	L2	91	7.7	0.070	6.4	LOS A	0.2	1.8	0.26	0.55	0.26	53.1
8	T1	1258	1.1	0.325	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1349	1.6	0.325	0.5	LOS A	0.2	1.8	0.02	0.04	0.02	59.4
All Vehicles		2398	1.5	0.856	10.1	NA	8.3	59.7	0.17	0.39	0.39	51.2

## MOVEMENT SUMMARY

### Site: 101 [Captain Cook Drive / Endeavour Road - Existing PM, Stage 2 ]

Captain Cook Drive / Endeavour Road  
Existing Volumes (4/2/20)  
Peak 4:30PM - 5:30PM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1066	1.7	0.276	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1066	1.7	0.276	0.0	NA	0.0	0.0	0.00	0.00	0.00	59.9
East: Endeavour Road (E)												
6	R2	204	2.9	0.099	6.9	LOS A	0.4	2.9	0.52	0.74	0.52	46.9
Approach		204	2.9	0.099	6.9	LOS A	0.4	2.9	0.52	0.74	0.52	46.9
All Vehicles		1270	1.9	0.276	1.1	NA	0.4	2.9	0.08	0.12	0.08	58.3

## EXISTING PLUS EXISTING APPROVED SCALE

### MOVEMENT SUMMARY



#### Site: 1 [Captain Cook Drive / Gannons Road - Existing AM + Existing Approved Scale]

Captain Cook Drive / Gannons Road  
Existing Volumes (4/2/20) + Existing Approved Scale  
Peak 8:00AM - 9:00AM  
Site Category: (None)  
Roundabout

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	783	1.4	0.433	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8
2	T1	44	0.0	0.371	8.4	LOS A	2.2	16.4	0.85	0.96	0.91	34.1
3	R2	171	7.6	0.371	12.3	LOS A	2.2	16.4	0.85	0.96	0.91	47.9
3u	U	1	0.0	0.371	13.8	LOS A	2.2	16.4	0.85	0.96	0.91	45.7
Approach		999	2.4	0.433	4.3	LOS A	2.2	16.4	0.18	0.47	0.20	47.7
East: Captain Cook Drive (E)												
4	L2	109	5.5	0.724	12.7	LOS A	7.8	59.4	0.87	1.02	1.18	48.5
5	T1	1076	11.5	0.724	12.7	LOS A	8.0	61.5	0.87	1.01	1.17	53.9
6	R2	44	0.0	0.724	16.8	LOS B	8.0	61.5	0.87	1.00	1.16	39.8
6u	U	20	15.0	0.724	19.8	LOS B	8.0	61.5	0.87	1.00	1.16	53.6
Approach		1249	10.6	0.724	13.0	LOS A	8.0	61.5	0.87	1.01	1.17	52.7
North: Toyota Access (N)												
7	L2	15	0.0	0.034	5.7	LOS A	0.1	1.0	0.71	0.66	0.71	38.5
8	T1	24	0.0	0.142	3.7	LOS A	0.7	5.2	0.75	0.77	0.75	35.6
9	R2	75	1.3	0.142	6.5	LOS A	0.7	5.2	0.75	0.77	0.75	38.5
9u	U	1	0.0	0.142	7.2	LOS A	0.7	5.2	0.75	0.77	0.75	30.8
Approach		115	0.9	0.142	5.8	LOS A	0.7	5.2	0.74	0.76	0.74	37.8
West: Captain Cook Drive (W)												
10	L2	139	0.0	0.501	6.6	LOS A	3.8	28.8	0.63	0.63	0.63	39.4
11	T1	611	14.7	0.501	7.0	LOS A	3.9	30.3	0.62	0.65	0.62	58.8
12	R2	413	9.2	0.501	11.7	LOS A	3.9	30.3	0.61	0.68	0.61	51.7
12u	U	7	57.1	0.501	15.4	LOS B	3.9	30.3	0.61	0.68	0.61	46.6
Approach		1170	11.3	0.501	8.7	LOS A	3.9	30.3	0.62	0.66	0.62	53.1
All Vehicles		3533	8.2	0.724	8.9	LOS A	8.0	61.5	0.59	0.73	0.70	50.7

## MOVEMENT SUMMARY



### Site: 1 [Captain Cook Drive / Gannons Road - Existing PM + Existing Approved Scale]

Captain Cook Drive / Gannons Road  
Existing Volumes (4/2/20) + Existing Approved Scale  
Peak 4:30PM - 5:30PM  
Site Category: (None)  
Roundabout

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	456	1.3	0.252	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8
2	T1	13	7.7	0.208	7.7	LOS A	1.2	8.4	0.79	0.89	0.79	34.3
3	R2	123	1.6	0.208	11.1	LOS A	1.2	8.4	0.79	0.89	0.79	49.3
3u	U	1	100.0	0.208	17.1	LOS B	1.2	8.4	0.79	0.89	0.79	45.4
Approach		593	1.7	0.252	4.3	LOS A	1.2	8.4	0.18	0.47	0.18	48.5
East: Captain Cook Drive (E)												
4	L2	46	6.5	0.716	23.5	LOS B	7.9	56.4	0.98	1.20	1.63	42.7
5	T1	769	2.2	0.716	22.6	LOS B	8.6	61.3	0.99	1.21	1.64	48.7
6	R2	11	0.0	0.716	26.6	LOS B	8.6	61.3	1.00	1.22	1.64	36.1
6u	U	21	0.0	0.716	29.0	LOS C	8.6	61.3	1.00	1.22	1.64	50.1
Approach		847	2.4	0.716	22.8	LOS B	8.6	61.3	0.99	1.21	1.64	48.1
North: Toyota Access (N)												
7	L2	44	0.0	0.131	9.3	LOS A	0.6	4.5	0.84	0.85	0.84	37.1
8	T1	44	0.0	0.686	17.2	LOS B	5.8	40.3	0.97	1.33	1.57	31.6
9	R2	286	0.0	0.686	19.9	LOS B	5.8	40.3	0.97	1.33	1.57	33.9
9u	U	1	0.0	0.686	20.7	LOS B	5.8	40.3	0.97	1.33	1.57	27.8
Approach		375	0.0	0.686	18.3	LOS B	5.8	40.3	0.96	1.27	1.49	33.9
West: Captain Cook Drive (W)												
10	L2	33	0.0	0.681	6.2	LOS A	7.0	49.8	0.64	0.58	0.64	39.3
11	T1	1235	1.2	0.681	6.4	LOS A	7.2	51.1	0.63	0.59	0.63	59.4
12	R2	630	1.1	0.681	11.2	LOS A	7.2	51.1	0.60	0.62	0.60	52.0
12u	U	17	0.0	0.681	13.5	LOS A	7.2	51.1	0.60	0.62	0.60	59.2
Approach		1915	1.1	0.681	8.0	LOS A	7.2	51.1	0.62	0.60	0.62	56.3
All Vehicles		3730	1.4	0.716	11.8	LOS A	8.6	61.3	0.67	0.79	0.87	49.8

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Existing AM, Stage 1 +Existing Approved Scale]

Captain Cook Drive / Endeavour Road  
Existing Volumes (4/2/20) + Existing Approved Scale  
Peak 7:30AM - 8:30AM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	518	3.3	1.039	126.5	LOS F	47.7	343.3	1.00	4.04	11.12	19.3
Approach		518	3.3	1.039	126.5	NA	47.7	343.3	1.00	4.04	11.12	19.3
East: Endeavour Road (E)												
4	L2	191	13.1	0.112	5.8	LOS A	0.0	0.0	0.00	0.52	0.00	54.5
6	R2	33	21.2	0.233	40.5	LOS C	0.9	7.6	0.93	0.99	1.00	35.2
Approach		224	14.3	0.233	10.9	LOS A	0.9	7.6	0.14	0.59	0.15	50.4
North: Captain Cook Drive (N)												
7	L2	323	3.1	0.343	8.7	LOS A	1.5	10.8	0.52	0.80	0.60	51.8
8	T1	948	11.1	0.261	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1271	9.0	0.343	2.2	LOS A	1.5	10.8	0.13	0.20	0.15	57.6
All Vehicles		2013	8.1	1.039	35.2	NA	47.7	343.3	0.36	1.23	2.97	37.8

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Existing AM, Stage 2 + Existing Approved Scale]

Captain Cook Drive / Endeavour Road  
Existing Volumes (4/2/20) + Existing Approved Scale  
Peak 7:30AM - 8:30AM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1494	5.0	0.396	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1494	5.0	0.396	0.1	NA	0.0	0.0	0.00	0.00	0.00	59.9
East: Endeavour Road (E)												
6	R2	33	21.2	0.022	7.7	LOS A	0.1	0.7	0.60	0.75	0.60	45.5
Approach		33	21.2	0.022	7.7	LOS A	0.1	0.7	0.60	0.75	0.60	45.5
All Vehicles		1527	5.4	0.396	0.2	NA	0.1	0.7	0.01	0.02	0.01	59.6

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Existing PM, Stage 1 + Existing Approved Scale]

Captain Cook Drive / Endeavour Road  
Existing Volumes (4/2/20) + Existing Approved Scale  
Peak 4:30PM - 5:30PM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	208	1.4	0.624	24.7	LOS B	3.4	24.0	0.90	1.14	1.57	42.0
Approach		208	1.4	0.624	24.7	NA	3.4	24.0	0.90	1.14	1.57	42.0
East: Endeavour Road (E)												
4	L2	637	1.1	0.346	5.7	LOS A	0.0	0.0	0.00	0.53	0.00	54.8
6	R2	204	2.9	0.932	113.1	LOS F	12.0	86.2	0.99	1.85	4.09	20.8
Approach		841	1.5	0.932	31.7	LOS C	12.0	86.2	0.24	0.85	0.99	39.4
North: Captain Cook Drive (N)												
7	L2	124	5.6	0.094	6.4	LOS A	0.3	2.5	0.26	0.56	0.26	53.1
8	T1	1291	1.1	0.333	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1415	1.5	0.333	0.6	LOS A	0.3	2.5	0.02	0.05	0.02	59.3
All Vehicles		2464	1.5	0.932	13.3	NA	12.0	86.2	0.17	0.41	0.48	49.0

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Existing PM, Stage 2 + Existing Approved Scale]

Captain Cook Drive / Endeavour Road  
Existing Volumes (4/2/20) + Existing Approved Scale  
Peak 4:30PM - 5:30PM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1333	1.4	0.345	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1333	1.4	0.345	0.0	NA	0.0	0.0	0.00	0.00	0.00	59.9
East: Endeavour Road (E)												
6	R2	204	2.9	0.119	7.3	LOS A	0.5	3.4	0.58	0.81	0.58	46.7
Approach		204	2.9	0.119	7.3	LOS A	0.5	3.4	0.58	0.81	0.58	46.7
All Vehicles		1537	1.6	0.345	1.0	NA	0.5	3.4	0.08	0.11	0.08	58.5

## EXISTING PLUS SHARKS STAGE 3 & 4

### MOVEMENT SUMMARY



#### Site: 1 [Captain Cook Drive / Gannons Road - Future AM + Sharks]

Captain Cook Drive / Gannons Road  
 Future Volumes (4/2/20) + Sharks 3 & 4  
 Peak 8:00AM - 9:00AM  
 Site Category: (None)  
 Roundabout

Movement Performance - Vehicles													
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h	
South: Gannons Rd (S)													
1	L2	783	1.4	0.433	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8	
2	T1	1	0.0	0.441	9.0	LOS A	2.8	20.6	0.88	1.00	0.99	33.7	
3	R2	253	5.1	0.441	12.9	LOS A	2.8	20.6	0.88	1.00	0.99	47.5	
3u	U	1	0.0	0.441	14.5	LOS B	2.8	20.6	0.88	1.00	0.99	44.9	
Approach		1038	2.3	0.441	4.9	LOS A	2.8	20.6	0.22	0.50	0.24	48.4	
East: Captain Cook Drive (E)													
4	L2	157	3.8	0.738	11.6	LOS A	8.3	62.6	0.86	0.97	1.13	49.2	
5	T1	1186	10.5	0.738	11.7	LOS A	8.5	64.9	0.86	0.96	1.12	55.0	
6	R2	1	0.0	0.738	15.9	LOS B	8.5	64.9	0.86	0.95	1.11	40.3	
6u	U	25	12.0	0.738	18.7	LOS B	8.5	64.9	0.86	0.95	1.11	55.3	
Approach		1369	9.7	0.738	11.8	LOS A	8.5	64.9	0.86	0.96	1.12	54.3	
North: Toyota Access (N)													
7	L2	4	0.0	0.010	6.0	LOS A	0.0	0.3	0.73	0.60	0.73	38.4	
8	T1	13	0.0	0.036	3.9	LOS A	0.2	1.3	0.75	0.68	0.75	35.9	
9	R2	9	11.1	0.036	6.9	LOS A	0.2	1.3	0.75	0.68	0.75	37.7	
9u	U	1	0.0	0.036	7.4	LOS A	0.2	1.3	0.75	0.68	0.75	31.0	
Approach		27	3.7	0.036	5.3	LOS A	0.2	1.3	0.74	0.67	0.74	36.6	
West: Captain Cook Drive (W)													
10	L2	6	0.0	0.485	6.5	LOS A	3.6	28.4	0.64	0.62	0.64	39.3	
11	T1	688	13.1	0.485	7.0	LOS A	3.9	29.5	0.63	0.64	0.63	58.8	
12	R2	413	9.2	0.485	11.6	LOS A	3.9	29.5	0.62	0.68	0.62	51.6	
12u	U	7	57.1	0.485	15.3	LOS B	3.9	29.5	0.62	0.68	0.62	46.5	
Approach		1114	11.8	0.485	8.8	LOS A	3.9	29.5	0.63	0.65	0.63	55.6	
All Vehicles		3548	8.2	0.738	8.8	LOS A	8.5	64.9	0.60	0.73	0.71	52.6	



## MOVEMENT SUMMARY



### Site: 1 [Captain Cook Drive / Gannons Road - Future PM + Sharks]

Captain Cook Drive / Gannons Road  
 Future Volumes (4/2/20) + Sharks Stage 3 & 4  
 Peak 4:30PM - 5:30PM  
 Site Category: (None)  
 Roundabout

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	456	1.3	0.252	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8
2	T1	2	50.0	0.268	8.4	LOS A	1.5	10.6	0.75	0.86	0.75	34.3
3	R2	199	1.0	0.268	10.3	LOS A	1.5	10.6	0.75	0.86	0.75	49.5
3u	U	1	100.0	0.268	15.9	LOS B	1.5	10.6	0.75	0.86	0.75	45.5
Approach		658	1.5	0.268	4.8	LOS A	1.5	10.6	0.23	0.50	0.23	49.0
East: Captain Cook Drive (E)												
4	L2	84	3.6	0.636	12.7	LOS A	6.0	42.5	0.89	1.03	1.15	48.7
5	T1	850	2.0	0.636	12.4	LOS A	6.2	44.4	0.90	1.01	1.14	56.2
6	R2	1	0.0	0.636	16.8	LOS B	6.2	44.4	0.90	1.00	1.14	39.9
6u	U	29	0.0	0.636	19.2	LOS B	6.2	44.4	0.90	1.00	1.14	57.6
Approach		964	2.1	0.636	12.6	LOS A	6.2	44.4	0.90	1.01	1.14	55.4
North: Toyota Access (N)												
7	L2	1	0.0	0.004	10.6	LOS A	0.0	0.1	0.88	0.65	0.88	36.7
8	T1	8	0.0	0.073	8.8	LOS A	0.4	3.0	0.92	0.89	0.92	34.0
9	R2	19	0.0	0.073	11.5	LOS A	0.4	3.0	0.92	0.89	0.92	36.8
9u	U	1	0.0	0.073	12.3	LOS A	0.4	3.0	0.92	0.89	0.92	29.7
Approach		29	0.0	0.073	10.8	LOS A	0.4	3.0	0.92	0.88	0.92	35.7
West: Captain Cook Drive (W)												
10	L2	1	0.0	0.748	8.0	LOS A	9.5	67.3	0.79	0.70	0.86	38.9
11	T1	1330	1.1	0.748	7.9	LOS A	9.5	67.3	0.77	0.70	0.83	58.7
12	R2	630	1.1	0.748	12.2	LOS A	9.2	65.1	0.74	0.69	0.78	51.6
12u	U	17	0.0	0.748	14.6	LOS B	9.2	65.1	0.74	0.69	0.78	58.7
Approach		1978	1.1	0.748	9.4	LOS A	9.5	67.3	0.76	0.69	0.81	56.2
All Vehicles		3629	1.4	0.748	9.4	LOS A	9.5	67.3	0.70	0.74	0.80	54.3

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future AM, Stage 1 + Sharks]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks)  
 Peak 7:30AM - 8:30AM  
 Site Category: (None)  
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	518	3.3	0.953	47.3	LOS D	21.4	154.1	0.97	2.42	5.60	33.3
Approach		518	3.3	0.953	47.3	NA	21.4	154.1	0.97	2.42	5.60	33.3
East: Endeavour Road (E)												
4	L2	191	13.1	0.112	5.8	LOS A	0.0	0.0	0.00	0.52	0.00	54.5
6	R2	33	21.2	0.281	41.4	LOS C	0.9	7.7	0.92	0.99	1.03	34.9
Approach		224	14.3	0.281	11.0	LOS A	0.9	7.7	0.14	0.59	0.15	50.3
North: Captain Cook Drive (N)												
7	L2	189	5.3	0.204	8.2	LOS A	0.7	5.3	0.48	0.72	0.48	52.1
8	T1	881	11.9	0.243	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1070	10.7	0.243	1.5	LOS A	0.7	5.3	0.08	0.13	0.08	58.4
All Vehicles		1812	9.1	0.953	15.8	NA	21.4	154.1	0.34	0.84	1.67	47.3

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future AM, Stage 2 + Sharks]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks)  
 Peak 7:30AM - 8:30AM  
 Site Category: (None)  
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1537	4.9	0.407	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1537	4.9	0.407	0.1	NA	0.0	0.0	0.00	0.00	0.00	59.9
East: Endeavour Road (E)												
6	R2	33	21.2	0.023	7.8	LOS A	0.1	0.7	0.61	0.76	0.61	45.5
Approach		33	21.2	0.023	7.8	LOS A	0.1	0.7	0.61	0.76	0.61	45.5
All Vehicles		1570	5.2	0.407	0.2	NA	0.1	0.7	0.01	0.02	0.01	59.6

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future PM, Stage 1 + Sharks]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks)  
 Peak 4:30PM - 5:30PM  
 Site Category: (None)  
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	208	1.4	0.688	29.2	LOS C	3.9	27.6	0.92	1.19	1.77	40.0
Approach		208	1.4	0.688	29.2	NA	3.9	27.6	0.92	1.19	1.77	40.0
East: Endeavour Road (E)												
4	L2	637	1.1	0.346	5.7	LOS A	0.0	0.0	0.00	0.53	0.00	54.8
6	R2	204	2.9	1.012	183.9	LOS F	20.3	145.5	1.00	2.42	6.21	14.8
Approach		841	1.5	1.012	48.9	LOS D	20.3	145.5	0.24	0.99	1.51	33.3
North: Captain Cook Drive (N)												
7	L2	91	7.7	0.070	6.4	LOS A	0.2	1.8	0.26	0.55	0.26	53.1
8	T1	1353	1.0	0.349	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1444	1.5	0.349	0.4	LOS A	0.2	1.8	0.02	0.03	0.02	59.4
All Vehicles		2493	1.5	1.012	19.2	NA	20.3	145.5	0.17	0.45	0.66	45.4

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future PM, Stage 2 + Sharks]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks)  
 Peak 4:30PM - 5:30PM  
 Site Category: (None)  
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1147	1.6	0.297	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1147	1.6	0.297	0.0	NA	0.0	0.0	0.00	0.00	0.00	59.9
East: Endeavour Road (E)												
6	R2	204	2.9	0.104	7.0	LOS A	0.4	3.1	0.54	0.76	0.54	46.8
Approach		204	2.9	0.104	7.0	LOS A	0.4	3.1	0.54	0.76	0.54	46.8
All Vehicles		1351	1.8	0.297	1.1	NA	0.4	3.1	0.08	0.11	0.08	58.3

## EXISTING PLUS SHARKS STAGE 3 & 4 PLUS EXISTING APPROVED SCALE

### MOVEMENT SUMMARY



#### Site: 1 [Captain Cook Drive / Gannons Road - Future AM + Sharks + Existing Approved Scale]

Captain Cook Drive / Gannons Road

Future Volumes (4/2/20) + Sharks 3 & 4 + Existing Approved Scale

Peak 8:00AM - 9:00AM

Site Category: (None)

Roundabout

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	783	1.4	0.433	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8
2	T1	44	0.0	0.586	12.4	LOS A	4.3	31.3	0.94	1.08	1.20	32.9
3	R2	253	5.1	0.586	16.2	LOS B	4.3	31.3	0.94	1.08	1.20	45.9
3u	U	1	0.0	0.586	17.8	LOS B	4.3	31.3	0.94	1.08	1.20	43.5
Approach		1081	2.2	0.586	6.0	LOS A	4.3	31.3	0.26	0.54	0.33	47.1
East: Captain Cook Drive (E)												
4	L2	157	3.8	0.823	16.0	LOS B	11.7	88.0	0.97	1.16	1.50	46.5
5	T1	1186	10.5	0.823	15.9	LOS B	12.1	91.8	0.97	1.15	1.49	51.7
6	R2	44	0.0	0.823	19.9	LOS B	12.1	91.8	0.97	1.13	1.48	38.5
6u	U	25	12.0	0.823	22.8	LOS B	12.1	91.8	0.97	1.13	1.48	52.0
Approach		1412	9.4	0.823	16.2	LOS B	12.1	91.8	0.97	1.15	1.49	50.6
North: Toyota Access (N)												
7	L2	15	0.0	0.039	6.7	LOS A	0.2	1.2	0.77	0.72	0.77	38.1
8	T1	24	0.0	0.166	4.7	LOS A	0.9	6.5	0.81	0.86	0.81	35.3
9	R2	75	1.3	0.166	7.4	LOS A	0.9	6.5	0.81	0.86	0.81	38.2
9u	U	1	0.0	0.166	8.2	LOS A	0.9	6.5	0.81	0.86	0.81	30.6
Approach		115	0.9	0.166	6.7	LOS A	0.9	6.5	0.81	0.84	0.81	37.4
West: Captain Cook Drive (W)												
10	L2	139	0.0	0.583	8.0	LOS A	5.2	39.6	0.76	0.77	0.83	39.1
11	T1	688	13.1	0.583	8.3	LOS A	5.3	40.9	0.76	0.77	0.81	58.2
12	R2	413	9.2	0.583	12.7	LOS A	5.3	40.9	0.75	0.75	0.78	51.4
12u	U	7	57.1	0.583	16.6	LOS B	5.3	40.9	0.75	0.75	0.78	46.3
Approach		1247	10.6	0.583	9.8	LOS A	5.3	40.9	0.75	0.76	0.80	52.9
All Vehicles		3855	7.5	0.823	11.0	LOS A	12.1	91.8	0.70	0.84	0.92	49.7

## MOVEMENT SUMMARY



### Site: 1 [Captain Cook Drive / Gannons Road - Future PM + Sharks + Existing Approved Scale]

Captain Cook Drive / Gannons Road

Future Volumes (4/2/20) + Sharks Stage 3 & 4 + Existing Approved Scale

Peak 4:30PM - 5:30PM

Site Category: (None)

Roundabout

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	456	1.3	0.252	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8
2	T1	13	7.7	0.347	8.6	LOS A	2.1	15.0	0.85	0.95	0.87	34.0
3	R2	199	1.0	0.347	11.9	LOS A	2.1	15.0	0.85	0.95	0.87	48.9
3u	U	1	100.0	0.347	18.5	LOS B	2.1	15.0	0.85	0.95	0.87	44.9
Approach		669	1.5	0.347	5.3	LOS A	2.1	15.0	0.27	0.53	0.28	48.4
East: Captain Cook Drive (E)												
4	L2	84	3.6	0.883	42.2	LOS C	15.5	110.4	1.00	1.51	2.57	35.1
5	T1	850	2.0	0.883	41.0	LOS C	17.3	122.7	1.00	1.52	2.57	39.3
6	R2	12	0.0	0.883	44.7	LOS D	17.3	122.7	1.00	1.53	2.58	30.7
6u	U	29	0.0	0.883	47.1	LOS D	17.3	122.7	1.00	1.53	2.58	40.3
Approach		975	2.1	0.883	41.3	LOS C	17.3	122.7	1.00	1.52	2.57	38.8
North: Toyota Access (N)												
7	L2	44	0.0	0.169	12.0	LOS A	0.9	6.3	0.91	0.91	0.91	36.2
8	T1	52	0.0	0.948	82.5	LOS F	16.8	117.4	1.00	2.59	3.73	20.5
9	R2	286	0.0	0.948	85.2	LOS F	16.8	117.4	1.00	2.59	3.73	21.4
9u	U	1	0.0	0.948	86.0	LOS F	16.8	117.4	1.00	2.59	3.73	18.8
Approach		383	0.0	0.948	76.4	LOS F	16.8	117.4	0.99	2.39	3.41	22.3
West: Captain Cook Drive (W)												
10	L2	33	0.0	0.779	9.0	LOS A	11.1	78.2	0.86	0.76	0.97	38.8
11	T1	1330	1.1	0.779	8.8	LOS A	11.1	78.2	0.84	0.75	0.94	58.3
12	R2	630	1.1	0.779	13.1	LOS A	10.9	76.8	0.81	0.73	0.88	51.3
12u	U	17	0.0	0.779	15.4	LOS B	10.9	76.8	0.81	0.73	0.88	58.3
Approach		2010	1.1	0.779	10.2	LOS A	11.1	78.2	0.83	0.74	0.92	55.4
All Vehicles		4037	1.3	0.948	23.2	LOS B	17.3	122.7	0.79	1.05	1.45	43.7

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future AM, Stage 1 + Sharks + Existing Approved Scale]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks) + Existing Approved Scale  
 Peak 7:30AM - 8:30AM  
 Site Category: (None)  
 Giveway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	518	3.3	1.153	309.1	LOS F	98.9	711.9	1.00	6.74	20.63	9.8
Approach		518	3.3	1.153	309.1	NA	98.9	711.9	1.00	6.74	20.63	9.8
East: Endeavour Road (E)												
4	L2	191	13.1	0.112	5.8	LOS A	0.0	0.0	0.00	0.52	0.00	54.5
6	R2	33	21.2	0.401	63.2	LOS E	1.3	10.8	0.95	1.02	1.13	28.9
Approach		224	14.3	0.401	14.2	LOS A	1.3	10.8	0.14	0.60	0.17	48.2
North: Captain Cook Drive (N)												
7	L2	323	3.1	0.343	8.7	LOS A	1.5	10.8	0.52	0.80	0.60	51.8
8	T1	1025	10.2	0.280	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1348	8.5	0.343	2.1	LOS A	1.5	10.8	0.12	0.19	0.14	57.8
All Vehicles		2090	7.8	1.153	79.5	NA	98.9	711.9	0.34	1.86	5.23	25.9

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future AM, Stage 2 + Sharks + Existing Approved Scale]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks) + Existing Approved Scale  
 Peak 7:30AM - 8:30AM  
 Site Category: (None)  
 Giveway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1604	4.7	0.424	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1604	4.7	0.424	0.1	NA	0.0	0.0	0.00	0.00	0.00	59.9
East: Endeavour Road (E)												
6	R2	33	21.2	0.024	7.9	LOS A	0.1	0.8	0.63	0.78	0.63	45.4
Approach		33	21.2	0.024	7.9	LOS A	0.1	0.8	0.63	0.78	0.63	45.4
All Vehicles		1637	5.0	0.424	0.2	NA	0.1	0.8	0.01	0.02	0.01	59.6

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future PM, Stage 1 + Sharks + Existing Approved Scale]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks) + Existing Approved Scale  
 Peak 4:30PM - 5:30PM  
 Site Category: (None)  
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	208	1.4	0.725	32.5	LOS C	4.2	30.1	0.94	1.23	1.91	38.6
Approach		208	1.4	0.725	32.5	NA	4.2	30.1	0.94	1.23	1.91	38.6
East: Endeavour Road (E)												
4	L2	637	1.1	0.346	5.7	LOS A	0.0	0.0	0.00	0.53	0.00	54.8
6	R2	204	2.9	1.107	307.6	LOS F	35.5	255.1	1.00	3.29	9.50	9.8
Approach		841	1.5	1.107	78.9	LOS F	35.5	255.1	0.24	1.20	2.30	26.1
North: Captain Cook Drive (N)												
7	L2	124	5.6	0.094	6.4	LOS A	0.3	2.5	0.26	0.56	0.26	53.1
8	T1	1386	1.0	0.358	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1510	1.4	0.358	0.6	LOS A	0.3	2.5	0.02	0.05	0.02	59.3
All Vehicles		2559	1.4	1.107	28.9	NA	35.5	255.1	0.17	0.52	0.93	40.5

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future PM, Stage 2 + Sharks + Existing Approved Scale]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks) + Existing Approved Scale  
 Peak 4:30PM - 5:30PM  
 Site Category: (None)  
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1414	1.3	0.366	0.0	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1414	1.3	0.366	0.0	NA	0.0	0.0	0.00	0.00	0.00	59.9
East: Endeavour Road (E)												
6	R2	204	2.9	0.127	7.5	LOS A	0.5	3.6	0.60	0.83	0.60	46.6
Approach		204	2.9	0.127	7.5	LOS A	0.5	3.6	0.60	0.83	0.60	46.6
All Vehicles		1618	1.5	0.366	1.0	NA	0.5	3.6	0.08	0.10	0.08	58.6



## FUTURE SCENARIO 1 & 2

### MOVEMENT SUMMARY



#### Site: 1 [Captain Cook Drive / Gannons Road - Future AM + Sharks + SC 1]

Captain Cook Drive / Gannons Road  
 Future Volumes (4/2/20) + Sharks 3 & 4 + SC1  
 Peak 8:00AM - 9:00AM  
 Site Category: (None)  
 Roundabout

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	783	1.4	0.433	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8
2	T1	208	0.0	1.008	102.2	LOS F	31.7	227.3	1.00	2.79	5.51	18.5
3	R2	253	5.1	1.008	106.1	LOS F	31.7	227.3	1.00	2.79	5.51	22.1
3u	U	1	0.0	1.008	107.7	LOS F	31.7	227.3	1.00	2.79	5.51	21.5
Approach		1245	1.9	1.008	40.2	LOS C	31.7	227.3	0.37	1.25	2.05	31.9
East: Captain Cook Drive (E)												
4	L2	157	3.8	1.197	382.2	LOS F	170.0	1282.0	1.00	6.82	18.08	8.3
5	T1	1186	10.5	1.197	381.9	LOS F	192.5	1438.7	1.00	7.06	18.48	8.5
6	R2	208	0.0	1.197	385.4	LOS F	192.5	1438.7	1.00	7.28	18.86	8.1
6u	U	25	12.0	1.197	388.4	LOS F	192.5	1438.7	1.00	7.28	18.86	8.5
Approach		1576	8.4	1.197	382.5	LOS F	192.5	1438.7	1.00	7.07	18.49	8.4
North: Toyota Access (N)												
7	L2	57	0.0	0.187	9.7	LOS A	1.0	7.0	0.87	0.87	0.87	37.0
8	T1	65	0.0	0.825	28.4	LOS B	10.6	74.2	1.00	1.66	2.05	28.9
9	R2	329	0.3	0.825	31.2	LOS C	10.6	74.2	1.00	1.66	2.05	30.8
9u	U	1	0.0	0.825	31.9	LOS C	10.6	74.2	1.00	1.66	2.05	25.7
Approach		452	0.2	0.825	28.1	LOS B	10.6	74.2	0.98	1.56	1.90	31.1
West: Captain Cook Drive (W)												
10	L2	626	0.0	1.050	135.4	LOS F	80.7	578.7	1.00	3.48	7.82	16.6
11	T1	688	13.1	1.050	133.2	LOS F	92.4	711.5	1.00	3.66	7.96	19.8
12	R2	413	9.2	1.050	137.0	LOS F	92.4	711.5	1.00	3.72	8.01	19.2
12u	U	7	57.1	1.050	141.8	LOS F	92.4	711.5	1.00	3.72	8.01	18.4
Approach		1734	7.6	1.050	134.9	LOS F	92.4	711.5	1.00	3.61	7.92	18.4
All Vehicles		5007	5.8	1.197	179.6	LOS F	192.5	1438.7	0.84	3.93	9.24	14.9

## MOVEMENT SUMMARY



### Site: 1 [Captain Cook Drive / Gannons Road - Future PM + Sharks + SC1]

Captain Cook Drive / Gannons Road  
 Future Volumes (4/2/20) + Sharks Stage 3 & 4 + SC1  
 Peak 4:30PM - 5:30PM  
 Site Category: (None)  
 Roundabout

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	456	1.3	0.252	2.3	LOS A	0.0	0.0	0.00	0.34	0.00	48.8
2	T1	56	1.8	0.418	9.0	LOS A	2.7	19.3	0.87	0.98	0.96	34.0
3	R2	199	1.0	0.418	12.5	LOS A	2.7	19.3	0.87	0.98	0.96	48.9
3u	U	1	100.0	0.418	19.2	LOS B	2.7	19.3	0.87	0.98	0.96	44.9
Approach		712	1.4	0.418	5.7	LOS A	2.7	19.3	0.31	0.57	0.35	47.2
East: Captain Cook Drive (E)												
4	L2	84	3.6	0.934	53.3	LOS D	20.4	145.4	1.00	1.69	3.11	31.8
5	T1	850	2.0	0.934	52.0	LOS D	22.7	161.5	1.00	1.71	3.12	35.1
6	R2	55	0.0	0.934	55.5	LOS D	22.7	161.5	1.00	1.72	3.13	28.2
6u	U	29	0.0	0.934	57.9	LOS E	22.7	161.5	1.00	1.72	3.13	36.0
Approach		1018	2.0	0.934	52.5	LOS D	22.7	161.5	1.00	1.71	3.12	34.4
North: Toyota Access (N)												
7	L2	208	0.0	1.003	153.3	LOS F	18.3	128.0	1.00	2.82	4.33	15.1
8	T1	215	0.0	5.202	7572.1	LOS F	1518.6	10630.2	1.00	28.79	48.60	0.5
9	R2	1259	0.0	5.202	7574.8	LOS F	1518.6	10630.2	1.00	28.79	48.60	0.5
9u	U	1	0.0	5.202	7575.6	LOS F	1518.6	10630.2	1.00	28.79	48.60	0.5
Approach		1683	0.0	5.202	6657.2	LOS F	1518.6	10630.2	1.00	25.58	43.13	0.6
West: Captain Cook Drive (W)												
10	L2	162	0.0	0.890	15.7	LOS B	19.6	138.6	1.00	1.05	1.51	36.6
11	T1	1330	1.1	0.890	15.0	LOS B	20.0	141.2	1.00	1.02	1.47	53.9
12	R2	630	1.1	0.890	18.5	LOS B	20.0	141.2	1.00	0.97	1.40	48.4
12u	U	17	0.0	0.890	20.9	LOS B	20.0	141.2	1.00	0.97	1.40	54.6
Approach		2139	1.0	0.890	16.1	LOS B	20.0	141.2	1.00	1.01	1.45	50.4
All Vehicles		5552	0.9	5.202	2034.6	LOS F	1518.6	10630.2	0.91	8.53	14.25	1.8

## MOVEMENT SUMMARY

▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future AM, Stage 1 + Sharks + SC1&2]

Captain Cook Drive / Endeavour Road  
Future Volumes (4/2/20) (Sharks) + SC1&2  
Peak 7:30AM - 8:30AM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	518	3.3	2.433	2601.8	LOS F	389.5	2803.5	1.00	13.77	51.26	1.4
Approach		518	3.3	2.433	2601.8	NA	389.5	2803.5	1.00	13.77	51.26	1.4
East: Endeavour Road (E)												
4	L2	191	13.1	0.112	5.8	LOS A	0.0	0.0	0.00	0.52	0.00	54.5
6	R2	33	21.2	1.325	996.8	LOS F	14.9	123.0	1.00	1.83	4.37	3.3
Approach		224	14.3	1.325	151.8	LOS F	14.9	123.0	0.15	0.71	0.64	16.8
North: Captain Cook Drive (N)												
7	L2	809	1.2	0.846	15.1	LOS B	11.9	83.9	0.82	1.39	2.12	47.6
8	T1	1501	7.0	0.402	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		2310	5.0	0.846	5.3	LOS A	11.9	83.9	0.29	0.49	0.74	54.9
All Vehicles		3052	5.4	2.433	456.8	NA	389.5	2803.5	0.40	2.76	9.31	7.0

## MOVEMENT SUMMARY

▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future AM, Stage 2 + Sharks + SC1&2]

Captain Cook Drive / Endeavour Road  
Future Volumes (4/2/20) (Sharks) + SC1&2  
Peak 7:30AM - 8:30AM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1857	4.0	0.489	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.8
Approach		1857	4.0	0.489	0.1	NA	0.0	0.0	0.00	0.00	0.00	59.8
East: Endeavour Road (E)												
6	R2	33	21.2	0.031	8.8	LOS A	0.1	0.9	0.71	0.86	0.71	44.6
Approach		33	21.2	0.031	8.8	LOS A	0.1	0.9	0.71	0.86	0.71	44.6
All Vehicles		1890	4.3	0.489	0.2	NA	0.1	0.9	0.01	0.01	0.01	59.6

## MOVEMENT SUMMARY

▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future PM, Stage 1 + Sharks + SC1&2]

Captain Cook Drive / Endeavour Road  
Future Volumes (4/2/20) (Sharks) + SC1&2  
Peak 4:30PM - 5:30PM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	208	1.4	0.898	65.4	LOS E	7.6	53.7	0.98	1.60	3.37	28.6
Approach		208	1.4	0.898	65.4	NA	7.6	53.7	0.98	1.60	3.37	28.6
East: Endeavour Road (E)												
4	L2	637	1.1	0.346	5.7	LOS A	0.0	0.0	0.00	0.53	0.00	54.8
6	R2	204	2.9	1.592	1135.2	LOS F	102.3	734.0	1.00	5.84	19.68	3.0
Approach		841	1.5	1.592	279.7	LOS F	102.3	734.0	0.24	1.82	4.77	10.7
North: Captain Cook Drive (N)												
7	L2	252	2.8	0.188	6.4	LOS A	0.7	5.2	0.28	0.57	0.28	53.2
8	T1	1514	0.9	0.391	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1766	1.2	0.391	1.0	LOS A	0.7	5.2	0.04	0.08	0.04	58.8
All Vehicles		2815	1.3	1.592	89.0	NA	102.3	734.0	0.17	0.71	1.70	24.2

## MOVEMENT SUMMARY

▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future PM, Stage 2 + Sharks + SC1&2]

Captain Cook Drive / Endeavour Road  
Future Volumes (4/2/20) (Sharks) + SC1&2  
Peak 4:30PM - 5:30PM  
Site Category: (None)  
Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	2387	0.8	0.615	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.7
Approach		2387	0.8	0.615	0.1	NA	0.0	0.0	0.00	0.00	0.00	59.7
East: Endeavour Road (E)												
6	R2	204	2.9	0.352	13.5	LOS A	1.3	9.4	0.89	1.01	1.08	41.5
Approach		204	2.9	0.352	13.5	LOS A	1.3	9.4	0.89	1.01	1.08	41.5
All Vehicles		2591	0.9	0.615	1.2	NA	1.3	9.4	0.07	0.08	0.08	58.5

## FUTURE SCENARIO 2 (Gannons Road / Captain Cook Drive Only)

### MOVEMENT SUMMARY

 **Site: 1v [Captain Cook Drive / Gannons Road - Future AM + Sharks + SC 2]**

Captain Cook Drive / Gannons Road

Future Volumes (4/2/20) + Sharks 3 & 4 + SC2

Peak 8:00AM - 9:00AM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 105 seconds (Site Optimum Cycle Time - Minimum Delay)

Variable Sequence Analysis applied. The results are given for the selected output sequence.


Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	783	1.4	0.433	4.5	LOS A	0.0	0.0	0.00	0.47	0.00	47.8
2	T1	208	0.0	0.675	51.1	LOS D	10.5	73.2	1.00	0.85	1.04	25.0
3	R2	253	5.1	0.894	64.9	LOS E	15.2	111.0	1.00	1.08	1.43	28.1
Approach		1244	1.9	0.894	24.5	LOS B	15.2	111.0	0.37	0.65	0.46	36.9
East: Captain Cook Drive (E)												
4	L2	157	3.8	0.849	52.5	LOS D	24.4	182.4	1.00	0.99	1.18	32.9
5	T1	1186	10.5	0.849	46.1	LOS D	24.4	186.4	1.00	0.99	1.18	37.3
6	R2	233	0.0	0.899	68.4	LOS E	14.0	98.1	1.00	1.04	1.46	24.4
Approach		1576	8.2	0.899	50.0	LOS D	24.4	186.4	1.00	0.99	1.22	34.2
North: Toyota Access (N)												
7	L2	82	0.0	0.107	22.9	LOS B	2.6	18.2	0.66	0.63	0.66	32.3
8	T1	65	0.0	0.333	38.4	LOS C	6.0	41.9	0.89	0.72	0.89	27.3
9	R2	336	0.3	0.333	38.8	LOS C	6.0	41.9	0.89	0.73	0.89	28.9
Approach		483	0.2	0.333	36.0	LOS C	6.0	41.9	0.85	0.71	0.85	29.2
West: Captain Cook Drive (W)												
10	L2	633	0.0	0.630	15.7	LOS B	14.1	98.8	0.73	0.81	0.73	36.9
11	T1	688	13.1	0.630	35.2	LOS C	15.1	117.2	0.93	0.80	0.93	42.0
12	R2	413	9.2	0.847	63.1	LOS E	11.7	88.5	1.00	0.96	1.32	29.6
Approach		1734	7.4	0.847	34.7	LOS C	15.1	117.2	0.87	0.84	0.95	36.5
All Vehicles		5037	5.6	0.899	37.1	LOS C	24.4	186.4	0.79	0.83	0.90	35.0

#### Phase Timing Summary

Phase	A	B	E	F
Phase Change Time (sec)	0	35	55	83
Green Time (sec)	29	14	22	16
Phase Time (sec)	35	20	28	22
Phase Split	33%	19%	27%	21%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

#### Output Phase Sequence



## MOVEMENT SUMMARY



Site: 1v [Captain Cook Drive / Gannons Road - Future PM + Sharks + SC 2]

Captain Cook Drive / Gannons Road

Future Volumes (4/2/20) + Sharks 3 & 4 + SC2

Peak 4:30PM - 5:30PM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 115 seconds (Site Optimum Cycle Time - Minimum Delay)

Variable Sequence Analysis applied. The results are given for the selected output sequence.

### Movement Performance - Vehicles


Mov ID	Turn	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)											
1	L2	456	1.3 0.252	4.4	LOS A	0.0	0.0	0.00	0.47	0.00	47.8
2	T1	56	1.8 0.248	55.4	LOS D	2.9	20.9	0.95	0.74	0.95	24.3
3	R2	199	1.0 0.921	76.5	LOS F	13.5	95.2	1.00	1.14	1.57	26.1
Approach		711	1.3 0.921	28.6	LOS C	13.5	95.2	0.35	0.68	0.51	36.5
East: Captain Cook Drive (E)											
4	L2	84	3.6 0.715	52.5	LOS D	16.4	117.2	0.98	0.85	1.01	33.1
5	T1	850	2.0 0.715	46.1	LOS D	16.7	118.6	0.98	0.85	1.01	37.3
6	R2	55	0.0 0.362	63.3	LOS E	3.1	21.5	0.99	0.75	0.99	25.3
Approach		989	2.0 0.715	47.6	LOS D	16.7	118.6	0.98	0.85	1.01	36.0
North: Toyota Access (N)											
7	L2	208	0.0 0.303	21.2	LOS B	6.8	47.5	0.76	0.70	0.76	32.8
8	T1	215	0.0 0.920	62.4	LOS E	34.0	238.1	1.00	1.18	1.34	23.2
9	R2	1259	0.0 0.920	63.0	LOS E	34.0	238.1	1.00	1.20	1.34	24.3
Approach		1682	0.0 0.920	57.8	LOS E	34.0	238.1	0.97	1.14	1.27	25.0
West: Captain Cook Drive (W)											
10	L2	162	0.0 0.887	44.8	LOS D	25.2	177.7	1.00	0.99	1.22	29.7
11	T1	1330	1.1 0.887	39.6	LOS C	25.2	177.7	1.00	1.00	1.24	39.9
12	R2	630	1.1 0.892	69.0	LOS E	20.3	143.5	1.00	1.00	1.34	28.2
Approach		2122	1.0 0.892	48.8	LOS D	25.2	177.7	1.00	1.00	1.26	34.7
All Vehicles		5504	0.9 0.921	48.7	LOS D	34.0	238.1	0.90	0.97	1.12	31.4

### Phase Timing Summary

Phase	A	B	D	E	F
Phase Change Time (sec)	0	31	46	58	96
Green Time (sec)	25	9	6	32	13
Phase Time (sec)	31	15	12	38	19
Phase Split	27%	13%	10%	33%	17%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

### Output Phase Sequence



## FUTURE SCENARIO 3 & 4

### MOVEMENT SUMMARY



**Site: 1v [Captain Cook Drive / Gannons Road - Future AM + Sharks + SC 3]**

Captain Cook Drive / Gannons Road

Future Volumes (4/2/20) + Sharks 3 & 4 + SC3

Peak 8:00AM - 9:00AM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

Variable Sequence Analysis applied. The results are given for the selected output sequence.

#### Movement Performance - Vehicles


Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	783	1.4	0.433	4.5	LOS A	0.0	0.0	0.00	0.47	0.00	47.8
2	T1	208	0.0	0.820	42.6	LOS D	21.1	152.2	0.86	0.82	0.93	26.3
3	R2	253	5.1	0.820	53.1	LOS D	21.1	152.2	0.99	0.96	1.13	31.0
Approach		1244	1.9	0.820	20.7	LOS B	21.1	152.2	0.35	0.62	0.39	38.3
East: Captain Cook Drive (E)												
4	L2	157	3.8	0.221	33.6	LOS C	6.2	44.8	0.72	0.77	0.72	37.7
5	T1	1186	10.5	0.827	40.3	LOS C	33.4	254.4	0.98	0.92	1.04	39.6
6	R2	233	0.0	0.799	64.6	LOS E	14.2	99.4	1.00	0.89	1.16	24.6
Approach		1576	8.2	0.827	43.2	LOS D	33.4	254.4	0.95	0.90	1.03	36.2
North: Toyota Access (N)												
7	L2	83	0.0	0.222	31.2	LOS C	6.1	42.9	0.75	0.66	0.75	30.3
8	T1	67	0.0	0.222	29.3	LOS C	6.1	42.9	0.75	0.66	0.75	28.9
9	R2	62	1.6	0.185	38.2	LOS C	2.8	20.1	0.81	0.68	0.81	28.6
Approach		212	0.5	0.222	32.7	LOS C	6.1	42.9	0.76	0.66	0.76	29.3
West: Captain Cook Drive (W)												
10	L2	220	0.0	0.618	36.5	LOS C	20.2	150.1	0.86	0.83	1.05	31.4
11	T1	688	13.1	0.618	31.7	LOS C	21.0	163.1	0.87	0.79	0.94	43.1
12	R2	413	9.2	0.753	63.0	LOS E	12.3	92.9	1.00	0.87	1.11	29.4
Approach		1321	9.7	0.753	42.3	LOS C	21.0	163.1	0.91	0.82	1.01	35.7
All Vehicles		4353	6.5	0.827	36.0	LOS C	33.4	254.4	0.76	0.79	0.83	36.2

#### Phase Timing Summary

Phase	A	B	E
Phase Change Time (sec)	0	51	75
Green Time (sec)	45	18	39
Phase Time (sec)	51	24	45
Phase Split	43%	20%	38%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

#### Output Phase Sequence





## MOVEMENT SUMMARY



**Site: 1v [Captain Cook Drive / Gannons Road - Future PM + Sharks + SC 3]**

Captain Cook Drive / Gannons Road

Future Volumes (4/2/20) + Sharks 3 & 4 + SC3

Peak 4:30PM - 5:30PM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

Variable Sequence Analysis applied. The results are given for the selected output sequence.


Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	456	1.3	0.252	4.4	LOS A	0.0	0.0	0.00	0.47	0.00	47.8
2	T1	56	1.8	0.075	29.1	LOS C	2.1	14.7	0.67	0.65	0.67	29.2
3	R2	199	1.0	0.905	78.4	LOS F	14.7	103.9	1.00	1.14	1.52	25.7
Approach		711	1.3	0.905	27.1	LOS B	14.7	103.9	0.33	0.67	0.48	37.1
East: Captain Cook Drive (E)												
4	L2	84	3.6	0.156	40.9	LOS C	3.7	26.4	0.79	0.75	0.79	35.1
5	T1	850	2.0	0.744	42.7	LOS D	22.9	163.0	0.97	0.86	0.99	38.6
6	R2	84	0.0	0.864	77.7	LOS F	5.6	38.9	1.00	0.93	1.50	22.6
Approach		1018	2.0	0.864	45.5	LOS D	22.9	163.0	0.96	0.85	1.01	36.2
North: Toyota Access (N)												
7	L2	237	0.0	0.589	33.7	LOS C	19.1	133.9	0.85	0.90	1.18	29.7
8	T1	216	0.0	0.589	31.7	LOS C	19.1	133.9	0.85	0.90	1.18	28.3
9	R2	243	0.0	0.483	33.7	LOS C	11.1	77.7	0.83	0.75	0.83	29.8
Approach		696	0.0	0.589	33.1	LOS C	19.1	133.9	0.84	0.85	1.06	29.3
West: Captain Cook Drive (W)												
10	L2	72	0.0	0.910	45.6	LOS D	37.5	264.7	1.00	1.02	1.21	29.7
11	T1	1330	1.1	0.910	39.1	LOS C	37.7	266.4	1.00	1.02	1.20	40.0
12	R2	630	1.1	0.850	64.9	LOS E	19.8	140.1	1.00	0.94	1.21	28.9
Approach		2032	1.1	0.910	47.3	LOS D	37.7	266.4	1.00	1.00	1.21	35.4
All Vehicles		4457	1.1	0.910	41.4	LOS C	37.7	266.4	0.86	0.89	1.02	34.7

### Phase Timing Summary

Phase	A	B	D	F
Phase Change Time (sec)	0	40	52	69
Green Time (sec)	34	6	11	45
Phase Time (sec)	40	12	17	51
Phase Split	33%	10%	14%	43%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Inter-green Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

### Output Phase Sequence





## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future AM, Stage 1 + Sharks + SC3]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks) + SC3  
 Peak 7:30AM - 8:30AM  
 Site Category: (None)  
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total	Flows HV	Deg. Satn %	Average Delay sec	Level of Service	95% Back of Queue Vehicles	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	518	3.3	9.286	14941.9	LOS F	601.3	4327.2	1.00	6.89	27.19	0.2
Approach		518	3.3	9.286	14941.9	NA	601.3	4327.2	1.00	6.89	27.19	0.2
East: Endeavour Road (E)												
4	L2	191	13.1	0.112	5.8	LOS A	0.0	0.0	0.00	0.52	0.00	54.5
Approach		191	13.1	0.112	5.8	NA	0.0	0.0	0.00	0.52	0.00	54.5
North: Captain Cook Drive (N)												
7	L2	189	5.3	0.204	8.2	LOS A	0.7	5.3	0.48	0.72	0.48	52.1
8	T1	2121	5.0	0.561	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.8
Approach		2310	5.0	0.561	0.8	LOS A	0.7	5.3	0.04	0.06	0.04	59.1
All Vehicles		3019	5.2	9.286	2564.7	NA	601.3	4327.2	0.20	1.26	4.70	1.4

## MOVEMENT SUMMARY

### ▽ Site: 101 [Captain Cook Drive / Endeavour Road - Future PM, Stage 1 + Sharks + SC3]

Captain Cook Drive / Endeavour Road  
 Future Volumes (4/2/20) (Sharks) + SC3  
 Peak 4:30PM - 5:30PM  
 Site Category: (None)  
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total	Flows HV	Deg. Satn %	Average Delay sec	Level of Service	95% Back of Queue Vehicles	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
3	R2	208	1.4	1.202	428.3	LOS F	50.4	357.4	1.00	4.37	14.71	7.4
Approach		208	1.4	1.202	428.3	NA	50.4	357.4	1.00	4.37	14.71	7.4
East: Endeavour Road (E)												
4	L2	637	1.1	0.346	5.7	LOS A	0.0	0.0	0.00	0.53	0.00	54.8
Approach		637	1.1	0.346	5.7	NA	0.0	0.0	0.00	0.53	0.00	54.8
North: Captain Cook Drive (N)												
7	L2	91	7.7	0.070	6.4	LOS A	0.2	1.8	0.26	0.55	0.26	53.1
8	T1	1674	0.8	0.432	0.1	LOS A	0.0	0.0	0.00	0.00	0.00	59.9
Approach		1765	1.2	0.432	0.4	LOS A	0.2	1.8	0.01	0.03	0.01	59.5
All Vehicles		2610	1.2	1.202	35.8	NA	50.4	357.4	0.09	0.50	1.18	37.6

## MOVEMENT SUMMARY



### Site: 101 [Proposed NEW INTERSECTION WITH END ROAD AM PEAK (SHARK VOLUME) - SC3]

END ROAD / Captain Cook Drive (New Intersection)

FUTURE (Sharks) + SC3

Peak 7:30AM - 8:30AM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

#### Movement Performance - Vehicles


Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	2109	0.0	0.618	17.2	LOS B	26.4	184.7	0.71	0.64	0.71	46.7
Approach		2109	0.0	0.618	17.2	LOS B	26.4	184.7	0.71	0.64	0.71	46.7
East: Endeavour Road(E)												
4	L2	1	0.0	0.257	38.2	LOS C	6.5	45.8	0.79	0.77	0.79	36.3
6	R2	301	0.0	0.257	38.2	LOS C	6.5	45.8	0.79	0.77	0.79	36.5
Approach		302	0.0	0.257	38.2	LOS C	6.5	45.8	0.79	0.77	0.79	36.5
North: Captain Cook Drive (N)												
7	L2	1034	0.0	0.619	6.3	LOS A	6.9	48.2	0.25	0.65	0.25	52.9
8	T1	1279	0.0	0.375	14.1	LOS A	13.1	91.4	0.57	0.51	0.57	48.7
Approach		2313	0.0	0.619	10.6	LOS A	13.1	91.4	0.43	0.57	0.43	50.5
All Vehicles		4724	0.0	0.619	15.3	LOS B	26.4	184.7	0.57	0.62	0.57	47.6

#### Phase Timing Summary

Phase	A	C
Phase Change Time (sec)	0	76
Green Time (sec)	70	38
Phase Time (sec)	76	44
Phase Split	63%	37%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

#### Output Phase Sequence



## MOVEMENT SUMMARY

 **Site: 101 [Proposed NEW INTERSECTION WITH END ROAD PM PEAK (SHARK VOLUME) + SC3]**

END ROAD / Captain Cook Drive (New Intersection)

FUTURE (Sharks) + SC3 (END volumes added)

Peak 4:30PM - 5:30PM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

### Movement Performance - Vehicles


Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	1562	0.0	0.583	25.6	LOS B	22.3	155.9	0.79	0.71	0.79	42.3
Approach		1562	0.0	0.583	25.6	LOS B	22.3	155.9	0.79	0.71	0.79	42.3
East: Endeavour Road(E)												
4	L2	1	0.0	0.755	35.5	LOS C	30.2	211.2	0.90	0.87	0.90	37.3
6	R2	1238	0.0	0.755	35.6	LOS C	30.2	211.2	0.90	0.87	0.90	37.5
Approach		1239	0.0	0.755	35.6	LOS C	30.2	211.2	0.90	0.87	0.90	37.5
North: Captain Cook Drive (N)												
7	L2	268	0.0	0.160	5.9	LOS A	0.9	6.3	0.12	0.61	0.12	53.2
8	T1	2044	0.0	0.762	28.8	LOS C	32.9	230.3	0.90	0.81	0.90	40.7
Approach		2312	0.0	0.762	26.2	LOS B	32.9	230.3	0.81	0.79	0.81	41.9
All Vehicles		5113	0.0	0.762	28.3	LOS B	32.9	230.3	0.83	0.78	0.83	40.8

### Phase Timing Summary

Phase	A	C
Phase Change Time (sec)	0	61
Green Time (sec)	55	53
Phase Time (sec)	61	59
Phase Split	51%	49%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

### Output Phase Sequence



## FUTURE SCENARIO 4 – ENDEAVOUR ROAD / CAPTAIN COOK DRIVE ONLY

### MOVEMENT SUMMARY

 **Site: 101v [Captain Cook Drive / Endeavour Road - Future AM, Stage 1 + Sharks + SC4]**

Captain Cook Drive / Endeavour Road  
Future Volumes (4/2/20) (Sharks) + SC4  
Peak 7:30AM - 8:30AM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

Variable Sequence Analysis applied. The results are given for the selected output sequence.


Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	2213	3.4	0.430	0.5	LOS A	3.5	25.3	0.18	0.11	0.18	59.2
3	R2	518	3.3	0.778	43.2	LOS D	27.5	197.9	0.95	0.88	0.98	34.6
Approach		2731	3.4	0.778	8.6	LOS A	27.5	197.9	0.32	0.26	0.33	52.2
East: Endeavour Road (E)												
4	L2	191	13.1	0.153	32.9	LOS C	3.7	28.9	0.71	0.74	0.71	38.1
Approach		191	13.1	0.153	32.9	LOS C	3.7	28.9	0.71	0.74	0.71	38.1
North: Captain Cook Drive (N)												
7	L2	189	5.3	0.765	32.3	LOS C	34.3	250.6	0.85	0.84	1.15	40.6
8	T1	2121	5.0	0.765	24.3	LOS B	35.2	256.5	0.85	0.80	0.94	42.7
Approach		2310	5.0	0.765	25.0	LOS B	35.2	256.5	0.85	0.80	0.95	42.5
All Vehicles		5232	4.4	0.778	16.7	LOS B	35.2	256.5	0.57	0.52	0.62	46.8

#### Phase Timing Summary

Phase	A	B
Phase Change Time (sec)	0	70
Green Time (sec)	64	44
Phase Time (sec)	70	50
Phase Split	58%	42%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

#### Output Phase Sequence



## MOVEMENT SUMMARY

 **Site: 101v [Captain Cook Drive / Endeavour Road - Future PM, Stage 1 + Sharks + SC4]**

Captain Cook Drive / Endeavour Road  
Future Volumes (4/2/20) (Sharks) + SC4  
Peak 4:30PM - 5:30PM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

### Movement Performance - Vehicles


Mov ID	Turn	Demand Flows Total veh/h	Deg. Satn HV % v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)											
2	T1	2386	0.8 0.455	0.5	LOS A	4.0	27.9	0.18	0.12	0.18	59.2
3	R2	208	1.4 0.348	38.6	LOS C	9.2	65.4	0.81	0.79	0.81	36.2
Approach		2594	0.8 0.455	3.6	LOS A	9.2	65.4	0.23	0.17	0.23	56.3
East: Endeavour Road (E)											
4	L2	637	1.1 0.532	41.1	LOS C	15.2	107.4	0.87	0.82	0.87	35.2
Approach		637	1.1 0.532	41.1	LOS C	15.2	107.4	0.87	0.82	0.87	35.2
North: Captain Cook Drive (N)											
7	L2	91	7.7 0.529	22.6	LOS B	20.1	143.3	0.66	0.64	0.79	45.7
8	T1	1674	0.8 0.529	16.6	LOS B	20.8	146.4	0.66	0.61	0.70	47.0
Approach		1765	1.2 0.529	16.9	LOS B	20.8	146.4	0.66	0.61	0.70	46.9
All Vehicles		4996	1.0 0.532	13.1	LOS A	20.8	146.4	0.46	0.41	0.48	49.1

### Phase Timing Summary

Phase	A	B
Phase Change Time (sec)	45	0
Green Time (sec)	69	39
Phase Time (sec)	75	45
Phase Split	63%	38%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

### Output Phase Sequence





## FUTURE SCENARIO 3 & 4– REFINEMENT OF TURNING LANE LENGTHS

### MOVEMENT SUMMARY

 **Site: 1v [Captain Cook Drive / Gannons Road - Future AM + Sharks + SC 3 - Refinement of Lane Lengths]**

Captain Cook Drive / Gannons Road

Future Volumes (4/2/20) + Sharks 3 & 4 + SC3

Peak 8:00AM - 9:00AM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

Variable Sequence Analysis applied. The results are given for the selected output sequence.

#### Movement Performance - Vehicles


Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	783	1.4	0.433	4.5	LOS A	0.0	0.0	0.00	0.47	0.00	47.8
2	T1	208	0.0	0.386	42.3	LOS C	9.9	69.6	0.87	0.77	0.87	26.5
3	R2	253	5.1	0.826	60.4	LOS E	15.9	116.5	1.00	0.97	1.21	29.1
Approach		1244	1.9	0.826	22.1	LOS B	15.9	116.5	0.35	0.62	0.39	37.8
East: Captain Cook Drive (E)												
4	L2	157	3.8	0.191	28.7	LOS C	5.6	40.4	0.65	0.75	0.65	39.8
5	T1	1186	10.5	0.828	34.3	LOS C	31.4	239.3	0.89	0.85	0.95	42.4
6	R2	233	0.0	0.799	64.6	LOS E	14.2	99.4	1.00	0.89	1.16	24.6
Approach		1576	8.2	0.828	38.2	LOS C	31.4	239.3	0.88	0.84	0.95	38.1
North: Toyota Access (N)												
7	L2	83	0.0	0.267	36.9	LOS C	6.7	47.0	0.81	0.70	0.81	29.0
8	T1	67	0.0	0.267	35.0	LOS C	6.7	47.0	0.81	0.70	0.81	27.6
9	R2	62	1.6	0.256	47.6	LOS D	3.2	22.6	0.90	0.72	0.90	26.7
Approach		212	0.5	0.267	39.4	LOS C	6.7	47.0	0.84	0.71	0.84	27.8
West: Captain Cook Drive (W)												
10	L2	220	0.0	0.536	31.3	LOS C	18.0	133.6	0.78	0.79	0.99	32.8
11	T1	688	13.1	0.536	26.0	LOS B	19.0	147.7	0.79	0.73	0.86	46.1
12	R2	413	9.2	0.806	63.6	LOS E	13.6	102.9	1.00	0.88	1.12	29.3
Approach		1321	9.7	0.806	38.7	LOS C	19.0	147.7	0.85	0.79	0.96	37.0
All Vehicles		4353	6.5	0.828	33.8	LOS C	31.4	239.3	0.72	0.76	0.79	37.0

#### Phase Timing Summary

Phase	A	B	E
Phase Change Time (sec)	0	58	82
Green Time (sec)	52	18	32
Phase Time (sec)	58	24	38
Phase Split	48%	20%	32%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

#### Output Phase Sequence



## MOVEMENT SUMMARY

 **Site: 1v [Captain Cook Drive / Gannons Road - Future PM + Sharks + SC 3 - Refinement of Lane Lengths]**

Captain Cook Drive / Gannons Road

Future Volumes (4/2/20) + Sharks 3 & 4 + SC3

Peak 4:30PM - 5:30PM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 123 seconds (Site Optimum Cycle Time - Minimum Delay)

Variable Sequence Analysis applied. The results are given for the selected output sequence.


Movement Performance - Vehicles												
Mov ID	Turn	Demand Flows Total veh/h	Deg. HV %	Average Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Gannons Rd (S)												
1	L2	456	1.3	0.252	4.4	LOS A	0.0	0.0	0.00	0.47	0.00	47.8
2	T1	56	1.8	0.077	30.5	LOS C	2.2	15.3	0.68	0.65	0.68	28.9
3	R2	199	1.0	0.955	101.4	LOS F	17.3	122.3	1.00	1.29	1.78	22.2
Approach		711	1.3	0.955	33.6	LOS C	17.3	122.3	0.33	0.71	0.55	34.8
East: Captain Cook Drive (E)												
4	L2	84	3.6	0.151	40.8	LOS C	3.7	26.7	0.78	0.75	0.78	35.1
5	T1	850	2.0	0.758	43.1	LOS D	24.7	176.2	0.96	0.85	0.99	38.5
6	R2	84	0.0	0.886	81.1	LOS F	5.8	40.4	1.00	0.96	1.58	22.1
Approach		1018	2.0	0.886	46.0	LOS D	24.7	176.2	0.95	0.85	1.02	36.0
North: Toyota Access (N)												
7	L2	237	0.0	0.604	35.6	LOS C	20.0	139.9	0.86	0.91	1.20	29.3
8	T1	216	0.0	0.604	33.6	LOS C	20.0	139.9	0.86	0.91	1.20	27.9
9	R2	243	0.0	0.496	35.4	LOS C	11.5	80.8	0.84	0.75	0.84	29.3
Approach		696	0.0	0.604	34.9	LOS C	20.0	139.9	0.85	0.86	1.08	28.9
West: Captain Cook Drive (W)												
10	L2	72	0.0	0.874	37.7	LOS C	33.8	238.9	0.99	0.96	1.10	31.7
11	T1	1330	1.1	0.874	31.4	LOS C	34.2	241.6	0.99	0.96	1.10	43.7
12	R2	630	1.1	0.923	69.9	LOS E	25.4	179.3	1.00	0.96	1.26	27.9
Approach		2032	1.1	0.923	43.5	LOS D	34.2	241.6	0.99	0.96	1.15	36.7
All Vehicles		4457	1.1	0.955	41.2	LOS C	34.2	241.6	0.86	0.88	1.01	34.8

### Phase Timing Summary

Phase	A	B	D	F
Phase Change Time (sec)	0	42	54	72
Green Time (sec)	36	6	12	45
Phase Time (sec)	42	12	18	51
Phase Split	34%	10%	15%	41%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

### Output Phase Sequence



## MOVEMENT SUMMARY

 **Site: 101v [Captain Cook Drive / Endeavour Road - Future AM, Stage 1 + Sharks + SC4 - Refinement of Lane Lengths]**

Captain Cook Drive / Endeavour Road  
Future Volumes (4/2/20) (Sharks) + SC4

Peak 7:30AM - 8:30AM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

Variable Sequence Analysis applied. The results are given for the selected output sequence.

### Movement Performance - Vehicles


Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	2213	3.4	0.430	0.5	LOS A	3.5	25.3	0.18	0.11	0.18	59.2
3	R2	518	3.3	0.778	43.2	LOS D	27.5	197.9	0.95	0.88	0.98	34.6
Approach		2731	3.4	0.778	8.6	LOS A	27.5	197.9	0.32	0.26	0.33	52.2
East: Endeavour Road (E)												
4	L2	191	13.1	0.153	32.9	LOS C	3.7	28.9	0.71	0.74	0.71	38.1
Approach		191	13.1	0.153	32.9	LOS C	3.7	28.9	0.71	0.74	0.71	38.1
North: Captain Cook Drive (N)												
7	L2	189	5.3	0.765	32.3	LOS C	34.3	250.6	0.85	0.84	1.15	40.6
8	T1	2121	5.0	0.765	24.3	LOS B	35.2	256.5	0.85	0.80	0.94	42.7
Approach		2310	5.0	0.765	25.0	LOS B	35.2	256.5	0.85	0.80	0.95	42.5
All Vehicles		5232	4.4	0.778	16.7	LOS B	35.2	256.5	0.57	0.52	0.62	46.8

### Phase Timing Summary

Phase	A	B
Phase Change Time (sec)	0	70
Green Time (sec)	64	44
Phase Time (sec)	70	50
Phase Split	58%	42%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

### Output Phase Sequence



## MOVEMENT SUMMARY

 **Site: 101v [Captain Cook Drive / Endeavour Road - Future PM, Stage 1 + Sharks + SC4 - Refinement of Lane Lengths]**

Captain Cook Drive / Endeavour Road  
Future Volumes (4/2/20) (Sharks) + SC4

Peak 4:30PM - 5:30PM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

### Movement Performance - Vehicles


Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	2386	0.8	0.455	0.5	LOS A	4.0	27.9	0.18	0.12	0.18	59.2
3	R2	208	1.4	0.348	38.6	LOS C	9.2	65.4	0.81	0.79	0.81	36.2
Approach		2594	0.8	0.455	3.6	LOS A	9.2	65.4	0.23	0.17	0.23	56.3
East: Endeavour Road (E)												
4	L2	637	1.1	0.532	41.1	LOS C	15.2	107.4	0.87	0.82	0.87	35.2
Approach		637	1.1	0.532	41.1	LOS C	15.2	107.4	0.87	0.82	0.87	35.2
North: Captain Cook Drive (N)												
7	L2	91	7.7	0.529	22.6	LOS B	20.1	143.3	0.66	0.64	0.79	45.7
8	T1	1674	0.8	0.529	16.6	LOS B	20.8	146.4	0.66	0.61	0.70	47.0
Approach		1765	1.2	0.529	16.9	LOS B	20.8	146.4	0.66	0.61	0.70	46.9
All Vehicles		4996	1.0	0.532	13.1	LOS A	20.8	146.4	0.46	0.41	0.48	49.1

### Phase Timing Summary

Phase	A	B
Phase Change Time (sec)	45	0
Green Time (sec)	69	39
Phase Time (sec)	75	45
Phase Split	63%	38%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

### Output Phase Sequence



## MOVEMENT SUMMARY



### Site: 101 [Proposed NEW INTERSECTION WITH END ROAD AM PEAK (SHARK VOLUME) - SC3 - Refinement of Lane Lengths]

END ROAD / Captain Cook Drive (New Intersection)

FUTURE (Sharks) + SC3

Peak 7:30AM - 8:30AM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

#### Movement Performance - Vehicles


Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Back of Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)												
2	T1	2109	0.0	0.618	17.2	LOS B	26.4	184.7	0.71	0.64	0.71	46.7
Approach		2109	0.0	0.618	17.2	LOS B	26.4	184.7	0.71	0.64	0.71	46.7
East: Endeavour Road(E)												
4	L2	1	0.0	0.257	38.2	LOS C	6.5	45.8	0.79	0.77	0.79	36.3
6	R2	301	0.0	0.257	38.2	LOS C	6.5	45.8	0.79	0.77	0.79	36.5
Approach		302	0.0	0.257	38.2	LOS C	6.5	45.8	0.79	0.77	0.79	36.5
North: Captain Cook Drive (N)												
7	L2	1034	0.0	0.619	6.3	LOS A	6.9	48.2	0.25	0.65	0.25	52.9
8	T1	1279	0.0	0.375	14.1	LOS A	13.1	91.4	0.57	0.51	0.57	48.7
Approach		2313	0.0	0.619	10.6	LOS A	13.1	91.4	0.43	0.57	0.43	50.5
All Vehicles		4724	0.0	0.619	15.3	LOS B	26.4	184.7	0.57	0.62	0.57	47.6

#### Phase Timing Summary

Phase	A	C
Phase Change Time (sec)	0	76
Green Time (sec)	70	38
Phase Time (sec)	76	44
Phase Split	63%	37%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

#### Output Phase Sequence



## MOVEMENT SUMMARY



**Site: 101 [Proposed NEW INTERSECTION WITH END ROAD PM PEAK (SHARK VOLUME) + SC3 Refinement of Lane Lengths]**

END ROAD / Captain Cook Drive (New Intersection)

FUTURE (Sharks) + SC3 (END volumes added)

Peak 4:30PM - 5:30PM

Site Category: (None)

Signals - Fixed Time Isolated Cycle Time = 120 seconds (Site Optimum Cycle Time - Minimum Delay)

### Movement Performance - Vehicles


Mov ID	Turn	Demand Flows Total veh/h	Deg. HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Prop. Queue Distance m	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: Captain Cook Drive (S)											
2	T1	1562	0.0	0.583	25.6	LOS B	22.3	155.9	0.79	0.79	42.3
Approach		1562	0.0	0.583	25.6	LOS B	22.3	155.9	0.79	0.79	42.3
East: Endeavour Road(E)											
4	L2	1	0.0	0.755	35.5	LOS C	30.2	211.2	0.90	0.90	37.3
6	R2	1238	0.0	0.755	35.6	LOS C	30.2	211.2	0.90	0.90	37.5
Approach		1239	0.0	0.755	35.6	LOS C	30.2	211.2	0.90	0.90	37.5
North: Captain Cook Drive (N)											
7	L2	268	0.0	0.160	5.9	LOS A	0.9	6.3	0.12	0.12	53.2
8	T1	2044	0.0	0.762	28.8	LOS C	32.9	230.3	0.90	0.90	40.7
Approach		2312	0.0	0.762	26.2	LOS B	32.9	230.3	0.81	0.81	41.9
All Vehicles		5113	0.0	0.762	28.3	LOS B	32.9	230.3	0.83	0.83	40.8

### Phase Timing Summary

Phase	A	C
Phase Change Time (sec)	0	61
Green Time (sec)	55	53
Phase Time (sec)	61	59
Phase Split	51%	49%

See the Phase Information section in the Detailed Output report for more detailed information including input values of Yellow Time and All-Red Time, and information on any adjustments to Intergreen Time, Phase Time and Green Time values in cases of Pedestrian Actuation, Phase Actuation and Phase Frequency values (user-specified or implied) less than 100%.

### Output Phase Sequence







**ANNEXURE D: ADOPTED TRIP DISTRIBUTIONS**  
**(4 SHEETS)**



## Scenario 1 & 2 - Inbound Distribution




Scenario 1 & 2 - Outbound Distribution






Scenario 3 & 4 - Inbound Distribution



Scenario 3 & 4 - Outbound Distribution






**ANNEXURE E: SKETCH OF POTENTIAL NEW  
INTERSECTION AT ENDEAVOUR ROAD / CAPTAIN  
COOK DRIVE**

**(1 SHEET)**





Left-Turn only - Subject to Swept Path Testing

STOP Line for  
left-turning vehicles

Location and arrangement of  
parking subject to detailed design

Driveway: No Entry, Left ONLY (Subject to traffic modelling)

NO Right Turn

Mark-Up / Sketch  
ONLY  
Subject to detailed  
Concept design





**ANNEXURE F: SKETCH OF POTENTIAL NEW  
INTERSECTION AT GANNONS ROAD / CAPTAIN COOK  
DRIVE  
(1 SHEET)**



