# **Appendix 5: Flood Mapping**

Flood Hazard Levels RE1 zoned land proposed to be zoned B4



Flood Hydraulic Categories RE1 zoned land proposed to be zoned B4





Flood Hazard Levels B4 zoned land proposed to be zoned B3

# **Appendix 6: Traffic Management Assessment**

#### Cessnock Commercial Precinct, Assessment of Traffic Management Measures

## BITZIOS

#### Issue History

File Name	Prepared by	Reviewed by	lssued by	Date	Issued to
P2225.001T Traffic Management Phase Testing Cessnock City Centre	T. Bleasdale	A. Ahmed	S. Brooke	01-05-17	Scott Christie, Cessnock City Council Scott.Christie@cessnock.nsw.gov.au
P2225.002T Traffic Management Phase Testing Cessnock City Centre	T. Bleasdale	A. Ahmed	S. Brooke	16-05-17	Scott Christie, Cessnock City Council Scott Christie@cessnock.nsw.gov.au

#### Cessnock Commercial Precinct, Assessment of Traffic Management Measures

#### 1. INTRODUCTION

Cessnock City Council has commissioned Bitzios Consulting to undertake traffic assessment of several traffic management and parking improvement measures that are identified to improve accessibility and parking within the Cessnock City Centre. This technical note summarises the findings of the assessment.

#### 1.1 BACKGROUND

Cessnock City Council has identified several traffic management and parking improvement measures to upgrade the Cessnock Commercial Precinct. It is suggested that the measures are implemented in six different phases with each phase containing one or more measures. These phases are summarised in Table 1.1.

Phase	Improvement Measures
Phase 1	Cooper Street and Charlton Street one way including a shared zone
Phase 2	Keen Street connection from Wollombi Road (one-way traveling from Wollombi Road to Keene Street)
Phase 3	Keene Street multi-level car park
Phase 4	Charlton Street multi-level car park
Phase 5	Charlton Street connection to Allandale Road
Phase 6	Connection of South Street to James Street (Cessnock South)

Table 1.1: Proposed Improvement Measures and Phasing

Bitzios consulting previously developed the 2015 AM and PM base traffic models for the whole of the Cessnock Local Government Area (LGA) using Aimsun mesoscopic model. The base model was used to develop future year traffic models and fed into the development of a 30-year transport strategy (to 2041) for the LGA. As part of the strategy, several key infrastructure improvement measures were proposed. While the preferred improvements are required to support the 2041 projects traffic volumes, there are opportunities to implement the proposed upgrade in stages. A robust staging methodology was developed as part of the commission. It was proposed that the ultimate improvements identified to service the 2041 traffic to be implemented in two stages; in 2021 and 2031.

Project No: P2225

Version: 002

The assessment was undertaken for the 2031 traffic conditions. For the purposed of this assessment, the 2031 proposed road network was adopted. The 2031 proposed network includes the following key improvements:

- upgrade Wollombi Road to four lanes, two lanes in each direction;
- upgrade Maitland Road to four lanes, two lanes in each direction;
- upgrade Old Maitland Road to four lanes, two lanes in each direction;
- seal section of Old Maitland Road;

essnock Commercial Precinct. Assessment of Traffic Management Measures

- new link between Old Maitland Road and Hunter Expressway;
- new Full interchange with Old Maitland Road and Hunter Expressway;
- Main Road upgrade to four lanes, two lanes in each direction;
- Southern Outer CBD By-Pass;
- Northern Outer CBD By-Pass;
- Oakey Creek Road and O'Conners Road upgrade; and
- New signals throughout Cessnock LGA.

The proposed infrastructure improvements are summarised in Figure 1.1.



Figure 1.1: Cessnock LGA Infrastructure Improvements – 2031 Proposed Network

The proposed measures are predicted to improve traffic conditions within Cessnock City Centre. The key measures in and around the city centre include:

- the proposed upgrade of Wollombi Road to four lanes was identified in the Bellbird North development traffic impact assessment report. As part of this improvement, it is proposed to introduce traffic signals at a few intersections on Wollombi Road including Darwin Street, West Avenue and Alexander Street;
- as part of the Bellbird North development, a signalised intersection is also proposed on Wollombi Road just to the west of its intersection with Allandale Road. This intersection would service the existing car park entrance; and
- as part of the 30-year strategy, it is proposed to implement an outer CBD bypass. The bypass is
  expected to reduce traffic through the city centre. By 2031, it is proposed to introduce the Southern
  Outer CBD bypass (as shown in Figure 1.1) to connect Wollombi Road and Aberdare Road. This is
  also expected to reduce substantial traffic through the city centre.

Project No: P2225

Version: 002

#### 2. METHODOLOGY

#### 2.1.1 Overview

Traffic performance for phase 1 and 2 were assessed together and then sequential phases added up to Phase 4. Phases 5 and 6 were assessed as individual cases. A simple three-stage methodology was adopted for the traffic assessment:

- Network Upgrade;
- Traffic Assessment; and
- Reporting.

#### 2.1.2 Network Update

The Aimsun model network was updated to reflect the proposed changes. These included introduction of turn bans to establish one-way streets, introduction of new signalised intersections and rationalisation of car parking spaces.

#### 2.1.3 Traffic Assessment

The Aimsun 'Hybrid Modelling' feature was utilised to assess the traffic performance of the proposed traffic management measures. In the hybrid model, the whole network was run in mesoscopic simulator with the exception of the core Cessnock City Centre area. A microsimulation pocket was defined within the City Centre area simulator as shown in Figure 2.1. Traffic within the microsimulation pocket was modelled using the microscopic simulator. The use of microscopic simulator enables accurate assessment of the impact of the proposed traffic improvement measures.



#### Figure 2.1: Mesoscopic and Microscopic Areas

Traffic performance for each phase was compared with the 2031 base case using the following criteria:

- changes in traffic volumes;
- intersection Level of Service (LOS); and
- travel times.

#### 2.1.4 Reporting

The outcomes from the network assessment was summarised briefly.

Project No: P2225

Version: 002

#### 3. PROPOSED IMPROVEMENTS

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

Cessnock City Council provided several traffic management and parking improvement measures to be implemented in each of the six phases. Improvement measures that are identified in each phase are summarised in the following sections.

#### 3.1 PHASE 1 AND 2

This phase involves the introduction of a shared zone around the Cessnock Town Square. Figure 3.1 shows the layout of the Town Square plan. The proposed shared zone includes a section of Cooper Street between Keene Street and Vincent Street and, an approximately 100m section of Charlton Street north and south of Cooper Street. To compliment the shared zone, Cooper Street will be restricted to one way, eastbound, between Keene Street and Vincent Street. It is also proposed to restrict the proposed shared zone on Charlton Street south of Cooper Street to one-way operation. As part of this phase it is proposed to extend Keene Street to join Wollombi Road. The new section of Keene Street will be restricted to one-way operation (southbound). This will provide a 'left-in' entry from Wollombi Road. Alterations were made to the signals at Vincent Street / Cooper Street to cater for these changes.



Figure 3.1: Phase 1, Town Square Shared Zone

#### 3.2 PHASE 3

This phase involves the proposed upgrade of the existing carpark on the western side of Keene Street to a multi-level carpark with an additional 140 parking spaces. The proposed carpark would offset the potential loss of parking spaces on Cooper Street resulting from the implementation of the Town Square proposal. The proposed car park will also offset the loss of approximately 48 car parking spaces north of Cooper Street between Charlton Street and Keene Street due to the implementation of the Town Square proposal. Figure 3.2 shows the location of the proposed multi-level carpark.

Project No: P2225

Version: 002



Figure 3.2: Phase 3 Carpark Location

#### 3.3 PHASE 4

Phase 4 involves the proposed upgrade of the existing carpark on the eastern side of Charlton Street to a multi-level carpark with an additional 160 parking spaces. The proposed carpark would offset the potential loss of parking spaces on Cooper Street resulting from the implementation of the Town Square proposal. The proposed car park will also offset the loss of approximately 56 car parking spaces south of Cooper Street between Charlton Street and Keene Street due to the implementation of the Town Square proposal. Figure 3.3 shows the location of the proposed multi-level carpark. Changes to the signal phase timing at the intersection of Vincent Street / Hall Street was made to give additional green time to the Hall Street traffic movements.

Project No: P2225

Version: 002



Figure 3.3 Phase 3 Carpark Location

essnock Commercial Precinct, Assessment of Traffic Management Measures

#### 3.4 PHASE 5

As part of phase 5, it is proposed to extend Charlton Street all the way to Wollombi Road to form a fourth leg at the existing Allandale Road / Maitland Road / Wollombi Road intersection. The proposed Charlton Street extension will provide an alternative access to the car park spaces on Charlton Street via Maitland Road / Wollombi Road.

It was required to change the existing signal phasing arrangement at the intersection of Allandale Road, Maitland Road, Wollombi Road and Vincent Road. Figure 3.4 shows the proposed Charlton Street extension to Allandale Road.

Project No: P2225

Version: 002



Figure 3.4: Charlton Street Two-way connection to Allandale Road

ent of Traffic Management Measur

#### 3.5 PHASE 6

Project No: P2225

This phase involves a southern inner city bypass connecting South Avenue/Snape Street in the east and James Street in the west. This would allow vehicles travelling between East and West to avoid the Cessnock City Centre. Figure 3.5 shows the proposed connection between South Avenue/Snape Street and James street.



Figure 3.5: Connection of South Street to James Street (Cessnock South)

#### 3.6 OTHER MODIFICATIONS

During the course of the study the following improvement was identified:

Reduction of green time on the eastbound Cooper Street at its intersection with Vincent Street. This
was implemented in the model to attract less number of vehicular trips using the shared zone.

#### 4. PHASE ASSESSMENT CRITERIA

The traffic performance of each phase was assessed and compared with the 2031 base case using the following three assessment criteria:

- traffic volumes;
- intersection level of service (LOS); and

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

travel times.

#### 4.1.1 Traffic Volumes

Traffic volumes at key intersections and along key routes for each of the proposed phases were compared with the 2031 base case.

#### 4.1.2 Intersection Level of Service

Intersection level of service was assessed at 10 key intersections around the Cessnock City Centre. For priority intersections including roundabouts, intersections level of service was determined by the worst

Project No: P2225

Version: 002



approach delay, while for signalised intersections, level of service was determined through the average approach delay. Figure 4.1 shows the location of these 10 intersections. All four key intersections on Vincent Street were included in the assessment.





Figure 4.1: Intersections Included in the Impact Assessment

#### 4.1.3 Travel Times

Travel times were assessed along 4 different routes around the Cessnock City Centre. The routes assessed were:

- North to South Allandale Road to Aberdare Road Via Maitland Road and Vincent Street;
- East to West Maitland Road / Victoria Street to Wollombi Road / Mount View Road;
- East to West North Avenue / South Avenue to Cooper Street / Cumberland Street; and
- North to South Wollombi Road / Darwin Street to Aberdare Road / Vincent Street.

Figure 4.2 shows the four travel times routes.

The travel time summary is included in Attachment B.

Project No: P2225

Version: 002



Figure 4.2: Travel Time Routes for Cessnock City Centre

Version: 002

Project No: P2225



#### 5. ASSESSMENT RESULTS

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

#### 5.1 OVERVIEW

As suggested by Cessnock City Council, Phase 1 and 2 were assessed together. Each of the remaining four phases was assessed as standalone phase. The assessment results are summarised below.

#### 5.2 PHASE 1 & 2

#### 5.2.1 Traffic Volume

The combined phase 1 and 2 is predicted to substantially alter traffic volumes at the following locations.

- the AM peak traffic volumes on the eastbound Cooper Street between Charlton Street and Vincent Street are predicted to reduce from 240 to 110 vehicles;
- during the PM peak, the eastbound traffic on Cooper Street will be reduced by 270 vehicles (from 390 to 120 vehicles), this represents a reduction of 70%. The reduction is due to proposed introduction of the shared zone and corresponding reduction of the posted speed limit to 10km/h. The slow speed environment will attract less vehicles on this section;
- the proposed extension of Keene Street to Wollombi Road is predicted to decrease eastbound traffic on Cooper Street between Darwin Street and Charlton Street. In the PM peak the eastbound traffic will be reduced by 255 vehicles, a decrease of 64%; and
- traffic at the intersection of Hall Street / Vincent Street will be increased by 270 vehicles during the PM
  peak, this represents an increase of 57%. The proposed closure of the westbound traffic on Cooper
  Street is predicted to divert majority of traffic to Hall Street.

Figure 5.1 shows the reduced traffic volumes on Cooper street and the increase in traffic along Hall Street due to the proposed town centre share zone.

Project No: P2225

Version: 002



#### 5.2.2 Intersection Assessment

Project No: P2225

The AM and PM peak intersection LoS results for Phase 1 & 2 are compared with the 2031 base case and presented in Table 5.1.

on: 00

Intersection	P	M	P	M
	Base Case	Phase 1 & 2	Base Case	Phase 1 & 2
Wollombi Road / Darwin Street	А	A	A	A
	(12)	(14)	(11)	(13)
Wollombi Road / Maitland Road /	В	В	В	B
Allandale Road	(20)	(18)	(21)	(19)
Maitland Road / Vincent Street	A	A	B	B
	(14)	(13)	(16)	(16)
Maitland Road / Victoria Street	A	A	A	A
	(9)	(7)	(4)	(6)
Darwin Street / North Avenue	A	A	A	A
	(8)	(4)	(10)	(12)
Charlton Street / Cooper Street	A	В	A	В
an on the second s	(10)	(25)	(6)	(25)
Vincent Street / Cooper Street	В	С	C	С
	(29)	(34)	(33)	(35)
Cooper Street / Cumberland Street	A	A	A	A
	(4)	(3)	(4)	(3)
Vincent Street / Hall Street	В	В	В	В
A company of the Advance of the Adva	(15)	(16)	(16)	(25)
Vincent Street / Aberdare Road /	В	В	В	В
Snape Street	(22)	(23)	(25)	(27)

Table 5.1: Phase 1 & 2 LoS Results 2031 AM & PM

essnock Commercial Precinct, Assessment of Traffic Management Measures

The assessment shows that during the AM and PM peak periods, the Charlton Street / Cooper Street intersection delays increase up to 19 seconds. The LoS is predicted to change from A to B. This is attributed to the introduction of shared zone and associated 10km/h speed limit along Cooper Street and Charlton Street. The intersection of Vincent Street / Cooper Street has a predicted LoS change from B to C with increase delay time of 5 seconds. This is attributed to the changed traffic signals.

Despite the predicted increase in traffic volumes at the Vincent Street / Hall Street intersection, the intersection would continue to operate at LoS B.

#### 5.2.3 Travel Time

The proposed reduction of speed limit will increase the PM peak travel time along the eastbound Cooper Street between Charlton Street and Cumberland Street by 29 seconds as compared to the 2031 base scenario. This is shown graphically in Figure 5.2.

Version: 002





Version: 002

Project No: P2225

Travel times on the other three routes are not predicted to changes significantly.



## Cessnock Commercial Precinct, Assessment of Traffic Management Measures

### 5.3 PHASE 1,2 & 3

#### 5.3.1 Traffic Volumes

No significant redistribution of traffic volumes was observed due the proposed multi-level carpark on Keene Street compared to the Phase 1 & 2 scenario.

#### 5.3.2 Intersection Assessment

The AM and PM peak LoS results for Phase 3 are compared to the Phase 1 & 2 scenario and presented in Table 5.2.

Internet or	A	M	Р	Μ
Intersection	Phase 1 & 2	Phase 1, 2 & 3	Phase 1 & 2	Phase 1, 2 & 3
Wollombi Road / Darwin	A	A	A	A
Street	(14)	(13)	(13)	(13)
Wollombi Road / Maitland	B	B	B	B
Road / Allandale Road	(18)	(18)	(19)	(19)
Maitland Road / Vincent	A	A	B	B
Street	(13)	(13)	(16)	(15)
Maitland Road / Victoria	A	A	A	A
Street	(7)	(7)	(6)	(6)
Darwin Street / North	A	A	A	A
Avenue	(4)	(10)	(12)	(11)
Charlton Street / Cooper	B	B	B	B
Street	(25)	(25)	(25)	(25)
Vincent Street / Cooper	C	C	C	C
Street	(34)	(33)	(35)	(35)
Cooper Street /	A	B	A	A
Cumberland Street	(3)	(3)	(3)	(4)
Vincent Street / Hall	B	B	B	B
Street	(16)	(17)	(25)	(21)
Vincent Street / Aberdare	B	B	B	B
Road / Snape Street	(23)	(23)	(27)	(26)

#### Table 5.2: Phase 3 LoS Results 2031 AM & PM

With the introduction of the multi-level on Keene Street there are no significant increases in delays predicted. The intersection of Vincent Street / Hall Street is predicted to see a decrease in delay time of 4seconds. All the key City Centre intersections would continue to operate at LoS between A and C.

#### 5.3.3 Travel Time

The proposed reduction of speed limit will increase the PM peak travel time along the eastbound Cooper Street between Charlton Street and Cumberland Street by 34 seconds as compared to the 2031 base scenario, this is an increase of 5 seconds from the Phase 1 & 2 scenario. This is shown graphically in Figure 5.3.

Project No: P2225

Version: 002





Version: 002

Project No: P2225

Travel times on the other three routes are not predicted to changes significantly.



#### 5.4 PHASE 1,2,3 & 4

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

#### 5.4.1 Overview

The Town Square proposal will result in loss of approximately 56 parking spaces and the closure of the existing car park access in the south of Cooper Street between Charlton Street and Keene Street. The closure of the access is expected to result in additional traffic being diverted to Hall Street and Charlton Street south of Cooper Street.

#### **Traffic Volume** 5.4.2

The proposed multi-level carpark on Charlton Street is expected to contribute to an increase in traffic volumes at the following locations on Cooper Street:

- traffic volume on Hall Street eastbound between Charlton Street and Vincent Street is predicted to increase by 50 vehicles during the PM peak, representing a 16% increase, from the Phase 1,2, & 3 scenario. This is an increase of 170 vehicles from the base case during the PM peak, representing an increase of 105%. This is due to the increased capacity of the Charlton Street carpark combined with the shared zone around Cooper Street and Charlton Street; and
- traffic volume on Hall Street westbound between Cumberland Street and Vincent Street is predicted to increase by 130 vehicles during the PM peak, representing an 87% increase, from the Phase 1,2, & 3 scenario. This is an increase of 240 vehicles from the base case during the PM peak, representing an increase of 600%, as shown in Figure 5.4. This is due to the increased capacity of the Charlton Street carpark combined with the shared zone around Cooper Street and Charlton Street.



Figure 5.4:

5.4.3 Intersection Assessment

> The AM and PM peak intersection LoS results for Phase 4 are compared with the Phase 1,2, & 3 scenario and presented in Table 5.3.

Project No: P2225

Version: 002

Intersection	A	M	P	M
	Phase 1, 2 & 3	Phase 1, 2,3 & 4	Phase 1, 2 & 3	Phase 1, 2, 3 &4
Wollombi Road / Darwin Street	A	A	A	A
	(13)	(13)	(13)	(11)
Wollombi Road / Maitland	B	B	B	B
Road / Allandale Road	(18)	(17)	(19)	(16)
Maitland Road / Vincent Street	A	A	B	B
	(13)	(11)	(15)	(17)
Maitland Road / Victoria Street	A	B	A	A
	(7)	(17)	(6)	(7)
Darwin Street / North Avenue	A	A	A	A
	(10)	(11)	(11)	(9)
Charlton Street / Cooper Street	B	B	B	B
	(25)	(26)	(25)	(25)
Vincent Street / Cooper Street	C	C	C	C
	(33)	(31)	(35)	(37)
Cooper Street / Cumberland	A	A	A	A
Street	(3)	(4)	(4)	(4)
Vincent Street / Hall Street	B	B	B	B
	(17)	(16)	(21)	(21)
Vincent Street / Aberdare Road	B	B	B	B
/ Snape Street	(23)	(24)	(26)	(24)

Table 5.3: Phase 4 LoS Results 2031 AM & PM

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

The intersection assessment shows an increase in delay at the Maitland Road / Victoria Street intersection of 10 seconds. This results in a predicted LoS change from A to B. During the PM there is no significant changes to intersection performance due to the new Charlton Street carpark.

#### 5.4.4 Travel Time

Travel time results show that traffic on Cooper Street will experience a substantial increase in travel times:

 the eastbound traffic would experience an increase of around 33 seconds during the PM peak compared to the base case, similar to Phase 1,2, & 3 scenario, as seen in Figure 5.5.

Version: 002



Figure 5.5: Cooper Street Eastbound Travel Time PM

Version: 002

Project No: P2225

### 5.5 PHASE 5

#### 5.5.1 Overview

As part of the 2031 base case assessment, a signalised intersection was assumed on Wollombi Road just to the west of its intersection with Allandale Road. For the purpose of this assessment, it was assumed that the signalised intersection would be replaced by the proposed Charlton Street link.

The traffic signal phase arrangement at the Wollombi Road / Allandale Road / Maitland Road / Vincent Road was modified to incorporate the new Charlton Street link. A new phase was introduced to service vehicles on the link.

#### 5.5.2 Traffic Volume

No significant redistribution of traffic volumes was observed due the proposed new connection of Charlton Street to Allandale Road. The Charlton Street link is predicted to service approximately 65 vehicles during the AM peak and 160 vehicles during the PM peak.

#### 5.5.3 Intersection Assessment

The AM and PM peak intersection LoS results for Phase 5 are compared with the 2031 and presented in Table 5.4.

Intersection	A	М	P	M
	Base Case	Phase 5	Base Case	Phase 5
Wollombi Road / Darwin Street	A	A	A	A
	(12)	(13)	(11)	(14)
Wollombi Road / Maitland	B	B	B	B
Road / Allandale Road	(20)	(26)	(21)	(24)
Maitland Road / Vincent Street	A	B	B	B
	(14)	(18)	(16)	(25)
Maitland Road / Victoria Street	A	A	A	A
	(9)	(5)	(4)	(2)
Darwin Street / North Avenue	A	A	A	A
	(9)	(9)	(10)	(11)
Charlton Street / Cooper Street	A	A	A	A
	(10)	(8)	(6)	(7)
Vincent Street / Cooper Street	B	B	C	C
	(29)	(26)	(33)	(35)
Cooper Street / Cumberland	C	C	C	C
Street	(30)	(38)	(31)	(38)
Vincent Street / Hall Street	B	B	B	B
	(15)	(15)	(16)	(17)
Vincent Street / Aberdare Road	B	B	B	B
/ Snape Street	(22)	(21)	(25)	(25)

Table 5.4:	Phase 5 LoS Results AM & PM
------------	-----------------------------

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

#### Project No: P2225

Version: 002

The proposed introduction of Charlton Street connection to Allandale Road is predicted to result in an increase in traffic delays at the Wollombi Road / Allandale Road / Maitland Road / Vincent Road intersection during both in the AM and PM peak periods:

- traffic at the Maitland Road / Vincent Street intersection would experience an increase of average delay during the peak periods of up to 9 seconds. Despite increase in delays, the intersection would continue to operate at LoS B; and
- traffic at the Wollombi Road / Maitland Road / Allandale Road intersection would experience an
  increase of average delay of 6 seconds during the AM peak. LoS will change from A to B.

#### 5.5.4 Travel Time

essnock Commercial Precinct, Assessment of Traffic Management Measures

Travel time results show an increase in the PM peak eastbound travel times along Wollombi Road / Maitland Road by up to 24 seconds. This is shown graphically in Figure 5.6. The increase is primarily between Mount View Road and Allandale Road. This is attributed to additional delays at the Wollombi Road / Maitland Road / Allandale Road intersection as a result of the introduction of the additional phase in the traffic signal to service the traffic at the Charlton Street connection.



Figure 5.6: Wollombi Road / Maitland Road Travel Time Comparison PM Peak

Project No: P2225

Version: 002



#### 5.6 PHASE 6

#### 5.6.1 Overview

Figure 5.7 shows the location of the proposed southern inner city bypass.

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

#### 5.6.2 Traffic Volume

It is predicted that during the AM peak approximately 300 vehicles would use the southern city bypass. In the PM peak this will increase to 360 vehicles.

The proposed bypass is predicted to reduce the PM peak westbound traffic volumes on North Avenue by 55 vehicles (or 10%).





#### 5.6.3 Intersection Assessment

The AM and PM peak LoS results for Phase 6 are compared with the 2031 scenario and presented in Table 5.5.



Version: 002

Intersection	A	M	PI	M
	Base Case	Phase 6	Base Case	Phase 6
Wollombi Road / Darwin	A	A	A	A
Street	(12)	(13)	(11)	(10)
Wollombi Road / Maitland	B	B	B	B
Road / Allandale Road	(20)	(19)	(21)	(17)
Maitland Road / Vincent	A	A	B	B
Street	(14)	(14)	(16)	(17)
Maitland Road / Victoria	A	B	A	A
Street	(9)	(18)	(4)	(4)
Darwin Street / North Avenue	A	A	A	A
	(9)	(8)	(10)	(10)
Charlton Street / Cooper	A	A	A	A
Street	(10)	(6)	(6)	(6)
Vincent Street / Cooper	B	B	C	C
Street	(29)	(28)	(33)	(35)
Cooper Street / Cumberland	C	C	C	C
Street	(30)	(33)	(31)	(34)
Vincent Street / Hall Street	B	B	B	B
	(15)	(15)	(16)	(16)
Vincent Street / Aberdare	B	B	B	B
Road / Snape Street	(22)	(22)	(25)	(24)

#### Table 5 5 Dhace 6 LoS Deculto AM 8 DM

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

The proposed southern inner city by-pass is predicted to result in similar intersection performance as compared to the 2031 base case scenario.

#### 5.6.4 **Travel Time**

The travel time results show no significant changes due to the proposed by-pass.

#### 5.7 SHARED ZONE TRAFFIC VOLUMES

A summary of the predicted traffic volumes for the town centre shared zone up to Phase 4 can be seen in Figure 5.8 and Table 5.6.

Project No: P2225

Version: 002



Figure 5.8: Town Centre Shared Zone Traffic Volumes

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

		ļ	۹M				PM	
	Base Case	Phase 1 & 2	Phase 1,2 & 3	Phase 1,2,3 & 4	Base Case	Phase 1 & 2	Phase 1,2 & 3	Phase 1,2,3 & 4
Cooper Street between Keene Street and Charlton Street	697	120	118	107	778	114	99	111
Cooper Street between Charlton Street and Vincent Street	745	120	116	116	906	156	120	117
Charlton Street north of Cooper Street	228	161	152	150	491	219	154	148
Charlton Street between Cooper Street and Car Park Exit	348	25	26	39	209	73	71	64

Table 5.6: Town Centre Shared Zone Traffic Volumes

Project No: P2225

Version: 002



#### 6. SUMMARY AND CONCLUSIONS

essnock Commercial Precinct. Assessment of Traffic Management Measures

Cessnock City Council has commissioned Bitzios Consulting to undertake traffic assessment of several traffic management and parking improvement measures that are identified to improve accessibility and parking within the Cessnock City Centre. This technical note summarises the findings of the assessment.

As part of the Cessnock Commercial Precinct upgrade, a total of six phases have been identified containing one or more traffic management and parking improvement measures. As instructed by Cessnock City Council, Phase 1 and 2 were assessed together then Phase 3 and 4 added sequentially, Phase 5 and Phase were assessed as individual cases.

The assessment was undertaken for the 2031 traffic conditions. For the purposed of this assessment, the 2031 proposed road network was adopted. The 2031 proposed network includes a number key improvements in and around the city centre including Wollombi Road upgrade to four-lane, a signalised intersection just the west of Allandale Road / Maitland Road intersection and an outer CBD bypass.

A simple three-stage methodology was adopted for undertaking the traffic assessment. The Aimsun 'Hybrid Modelling' feature was utilised to assess the traffic performance of the proposed traffic management measures.

The traffic performance of each phase was assessed and compared with the 2031 base case using the following three assessment criteria: traffic volumes, intersection LoS and travel times.

#### Phase 1 and 2

Traffic volumes on the eastbound Cooper Street are predicted to reduce due to the introduction of shared zone and the associated 10km/h speed zone. In the AM peak, the traffic volumes would reduce from 240 to 110 vehicles. In the PM peak, it would reduce from 390 to 120 vehicles.

The proposed Keene Street extension to Wollombi Road would reduce the eastbound traffic volumes on Cooper Street between Darwin Street and Charlton Street by 255 vehicles.

The proposed closure of the westbound traffic on Cooper Street is predicted to divert majority of traffic to the Vincent Street / Hall Street intersection.

The average delay at the Charlton Street / Cooper Street intersection would increase up to 19 seconds. The LoS is predicted to change from A to B.

The proposed reduction of speed limit will increase the PM peak travel time along the eastbound Cooper Street between Charlton Street and Cumberland Street by 29 seconds as compared to the 2031 base scenario.

#### Phase 1,2 & 3

No significant redistribution of traffic volumes was observed due the proposed multi-level carpark on Keene Street. Generally, the intersection delays and travel times would remain similar to the Phase 1 and 2 scenario.

#### Phase 1,2,3 & 4

The Town Square proposal will result in loss of approximately 56 parking spaces and the closure of the existing car park access in the south of Cooper Street between Charlton Street and Keene Street.

The proposed car park additions combined with the shared zone along cooper street would increase traffic on Hall Street eastbound by 50 vehicles during the PM peak compared to the Phase 1,2 & 3 scenario and an increase of 170 vehicles from the base case.

Project No: P2225

Version: 002

The proposed car park additions combined with the shared zone along cooper street would increase traffic on Hall Street westbound by 130 vehicles during the PM peak compared to the Phase 1,2 & 3 scenario and an increase of 240 vehicles from the base case.

The average delay at the Maitland Road / Victoria Street intersection would increase up to 10 seconds. The LoS is predicted to change from A to B.

#### Phase 5

Cessnock Commercial Precinct, Assessment of Traffic Management Measures

The Charlton Street link is predicted to service approximately 65 vehicles during the AM peak and 160 vehicles during the PM peak.

Traffic at the Wollombi Road / Allandale Road / Maitland Road / Vincent Road intersection would experience additional delays both in the AM and PM peak periods. The eastbound travel times along Wollombi Road / Maitland Road would go up to 24 seconds. This is attributed to additional delays at the Wollombi Road / Maitland Road / Allandale Road intersection as a result of the introduction of an additional phase in the traffic signal to service the traffic at the Charlton Street connection.

#### Phase 6

It is predicted that during the AM peak approximately 300 vehicles would use the southern city bypass. In the PM peak this will increase to 360 vehicles.

The proposed bypass is predicted to reduce the PM peak westbound traffic volumes on North Avenue by 55 vehicles (or 10%).

The proposed southern inner city by-pass is predicted to result in similar intersection performance as compared to the 2031 base case scenario with the travel time results show no significant changes.

Project No: P2225

Version: 002

ATTACHMENT A

INTERSECTION ASSESSMENT SUMMARY

$ \  \  \  \  \  \  \  \  \  \  \  \  \ $	AM Peak																	2				
								Base Model		Phas	ie 1+2		Phase 1,	2 & 3		Phase 1, 2,	8.4	*	14465		Phas	e 6
mutuality         mutuality <t< th=""><th></th><th></th><th>Aimsun Code</th><th></th><th>To</th><th>Tum</th><th></th><th>Delay (s)</th><th></th><th></th><th></th><th></th><th>_</th><th>LoS</th><th></th><th>Delay (s)</th><th></th><th></th><th></th><th></th><th></th><th></th></t<>			Aimsun Code		To	Tum		Delay (s)					_	LoS		Delay (s)						
Description         Description <thdescription< th=""> <thdescription< th=""></thdescription<></thdescription<>		Wollombi Road	1001	Wollombi Road (E)	Wollombi Road (W)	F	510	20	-			483	23	8	487	23	8	442	24			
$ = \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ $		Darwin Street	30001		Darwin Street (S)	2	274	20				242	22	8	228	22	m	242	21			
			30000	Darwin Street (S)	Wollombi Road (E)	ĸ	242	20				198	19	8	218	20	8	204	19		1855	
member (into)         member (			2000		Wollombi Road (W)	-	213	-				199	2	¥	195	2	A	230	2			
Matrix         Matrix<			No.	Wollombi Road (W)	Darwin Street (S)	œ	124	17				191	20	8	159	19	œ	138	18			
		_	2002		Wollombi Road (E)	-	702	~	┥	+		669		A	729	е	A		4	+	202	_
Match field				AI			2065	12.03		+		-	13.24	A	2016	13.10	4	-	13.25		_	
Method         Method<		Wollombi Road	13069	Allandale Road (N)	Wollombi Road (W)	α,	378	49					4	<b>с</b> ,	337	35	<b>с</b> ,	242	59			
Matcher         Matcher <t< th=""><th></th><th>Maluand Hoad</th><th>14/00/41</th><th></th><th>Cuarton Street (S)</th><th>-</th><th>-</th><th>• :</th><th></th><th>_</th><th></th><th></th><th>-</th><th><b>C</b> 1</th><th>-</th><th>-</th><th><b>K</b> 1</th><th>ß</th><th>2</th><th></th><th>_</th><th></th></t<>		Maluand Hoad	14/00/41		Cuarton Street (S)	-	-	• :		_			-	<b>C</b> 1	-	-	<b>K</b> 1	ß	2		_	
Mathematical (b)         Mathematical (b)<		Alandale Koad	13390		Maigand Koad (E)		112	8					77		238	1	<b>D</b> 1	140	8	_		
Month         Month <th< th=""><th></th><th>Charlton Street</th><th>13002</th><th>Maitland Road (E)</th><th>Allandale Road (N)</th><th>œ</th><th>102</th><th>25</th><th></th><th></th><th></th><th></th><th>27</th><th>8</th><th>123</th><th>28</th><th>8</th><th>128</th><th>32</th><th></th><th>***</th><th></th></th<>		Charlton Street	13002	Maitland Road (E)	Allandale Road (N)	œ	102	25					27	8	123	28	8	128	32		***	
Matrix         Matrix<			130901		Wollombi Road (W)	F	543		_	_				¥	574	en .	A	352	4			
1000         Mandelect()         F         0         A         A         A         A         A         A         A         A         A         A         A         A         A         A         A         A         A         A			2422240		Chartton Street (S)	2	0	0	A				•	¥	0	0	A	149	4			00
Matrix         Matrix<			2422244	Chartton Street (S)	Maitland Road (E)	æ	0	•	A	_			0	A	0	0	A	31	44			2010
Nome         Annotation         In			2422243		Allandale Road (N)	H	0	0	A	_			0	A	0	0	A	23	69			
			24200		Wollombi Road (W)	-	0	0	A	_		_	0	¥	•	0	A	13	41			
100         Munuchlant(i)         1         201         210 <th< th=""><th></th><th></th><th>2422039</th><th>Wollombi Road (W)</th><th>Chartton Street (S)</th><th>œ</th><th>0</th><th>0</th><th>A</th><th>_</th><th></th><th></th><th>0</th><th>A</th><th>0</th><th>0</th><th>A</th><th>9</th><th>150</th><th></th><th></th><th></th></th<>			2422039	Wollombi Road (W)	Chartton Street (S)	œ	0	0	A	_			0	A	0	0	A	9	150			
101         Antocho Factory         1         201         3         4         40         3         40         4			13063		Maitland Road (E)	-	203	21	8	1425	1003		20	8	715	21	8	637	20			
100         Minu (fact(s)         Mont (Fact(s))         1         216         139         1         2301         142         1         2301         142         2301         142         2301         142         2301         142         2301         142         2301         142         2301         142         2301         142         2301         142         2301         142         2301         143			130021		Allandale Road (N)	_	221							¥	214	3			5			
100         Interfaction         1         200				AI			2158	20.09					17.78	8	2201	16.62			26.47			
0000         Manachisat(5)         Manachisat(5)         L         123         22         L         23         L         13         L         13         L	-	Maitland Road	120839	Maitland Road (E)	Maitland Road (W)	H	502	23	80	1		632	21	80	543	19	8	498	38		1	
One         Materical (S) (Materical (S) (Materic		Vincent Street	13003		Vincent Street (S)	-	83	21	œ	0.000		22	22	8	27	12	A	26	31		_	
1000         Mather local (%)         1 <th1< th=""></th1<>			13000	Vincent Street (S)	Maitland Road (E)	œ	128	32	U			79	32	U	34	28	8	11	48			
(10)         Mandelad(0)         Mandelad(0) <thmandelad(0)< th=""> <thma< th=""><th></th><th></th><th>130021</th><th></th><th>Maitland Road (W)</th><th>2</th><th>143</th><th>13</th><th>A</th><th></th><th></th><th>149</th><th>10</th><th>A</th><th>155</th><th>12</th><th>A</th><th>131</th><th>6</th><th></th><th>558</th><th></th></thma<></thmandelad(0)<>			130021		Maitland Road (W)	2	143	13	A			149	10	A	155	12	A	131	6		558	
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $			13034	Maitland Road (W)	Vincent Street (S)	æ	181	19	8		000	146	18	8	127	17	8	164	13		6.255	
			13/825		Maitland Road (E)	T	731	2	A	742	3 A	782	3	A	825	3	A	647	3			
				AI			1768	13.75	A			1810	12.80	A	1711	10.63	A		18.40	-		
		Maitland Road	131267	Maitland Road (E)	Maitland Road (W)	H	751	9	A	-		783	e	A	789	16	8	654	2		-	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		Victoria Street	121258		Victoria Street (S)	_	1	80	×		_	<b>v</b> 2	4	¥	ŝ	19	œ	e0	4		_	
Untrol         Material Fland (0)         Value fland (0) <thvalue (0)<="" fland="" th="">         Value fland (0)<!--</th--><th></th><th></th><th>131208</th><th>Victoria Street (S)</th><th>Maitland Road (E)</th><th>æ</th><th>10</th><th>29</th><th>U</th><th>Bc.</th><th></th><th>9</th><th>28</th><th>ш</th><th>e</th><th>32</th><th>с U</th><th>13</th><th>15</th><th></th><th></th><th></th></thvalue>			131208	Victoria Street (S)	Maitland Road (E)	æ	10	29	U	Bc.		9	28	ш	e	32	с U	13	15			
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$			131270		Maitland Road (W)	2	93	21	œ	_		81	13	¥	91	43	U	11	10			
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$			131200	Maitland Road (W)	Victoria Street (S)	æ	69	17	6	_		99	20	•	54	28	6	46	17			
No.         And         Trand         Fight			131295		Maitland Road (E)	-	784	11			_	199	10	A	760	15		_	7	-		
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$				All			1714	9.19					7.33	A	1702	17.48			5.22	2	_	
With Manual (N)         Definition (S)         1         2         3         23         1         A         260		Danwin Street	1904	Darwin Street (N)	North Avenue (W)	α,	2	s i	۷.	_			ŝ	٩ .	45	s ا	A -	20	с I			_
0500       Muth Amene (F)       F       112       2       A       20       1       1       1       1		aniiany unioki	2014				522		٢.			_		۰ ،	807		< •					
With Manual (N)         Manual (N)         N         111         2         A         21         A         22         1         A         22         1         A         22         1         A         23         2         A         23         3			00005-7	(L)	Contractions (C)		3	N P	۲ ،				- •	< 4	8 6	- :	( <	5 3	2			70.00
Openal         Demonstrate(5)         1         300         7         51         7         7         51         7         7         51         7			1000	Internet weating (c)	North Avenue AM	4	137	- 11	۲ م	_			2 0	ব	78		বে	i și	3 4		2 40	e 10
With Street (s)         The strest (s)         The st			P+CHF6		Danuin Street (S)		348		( 4	M				۹	19	, c		308	, c			
0000 0000 0000 0000         The main Street Ni         T         220 000         5         A         276 000         200 000			\$26.7	Darwin Street (S)	North Avenue (E)	æ	2	-	A				2	A	30	0	A	2	-			4
2000         Image: second			9904		Darwin Street (N)	F	220	\$	A	272	2 A		2	A	275	2	A	215	16		0	4
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$			2425216		North Avenue (W)	1	23		¥	92	2 A		e	۲	66	2	A	17	4		4	4
W01         W01 <th></th> <th></th> <th>105-10</th> <th>North Avenue (W)</th> <th>Darwin Street (S)</th> <th>æ</th> <th>24</th> <th>80</th> <th>A</th> <th>205</th> <th>7 A</th> <th></th> <th>2</th> <th>A</th> <th>257</th> <th>7</th> <th>A</th> <th>19</th> <th>14</th> <th></th> <th></th> <th></th>			105-10	North Avenue (W)	Darwin Street (S)	æ	24	80	A	205	7 A		2	A	257	7	A	19	14			
Journel         Journel <t< th=""><th></th><th></th><th>11501</th><th></th><th>North Avenue (E)</th><th>H ·</th><th>290</th><th>4</th><th>A .</th><th>63</th><th>5 A</th><th></th><th>4</th><th>A .</th><th>83</th><th>ŝ</th><th>A .</th><th>236</th><th>14</th><th></th><th></th><th>*501</th></t<>			11501		North Avenue (E)	H ·	290	4	A .	63	5 A		4	A .	83	ŝ	A .	236	14			*501
The image of the imag			242005		Darwin Street (N)	-	142	E	۷.	+	+	-	2	۷.	16/	2	Υ.		3	-	+	
Constraint         Constraint <thconstraint< th="">         Constraint         Constrai</thconstraint<>				All and a second			1721	a de	۰ ۲				10.8	¥	1912	10.91	A		- 12	_	_	
Constraint         Constraint <thconstraint< th="">         Constraint         Constran</thconstraint<>		Charlton Street	1630	Charlton Street (N)	Cooper Street (W)	∝ .	58	~ ~	A				7 1	AV#		<b>.</b> .	AV#					
CooperStreet(E)         CooperStreet(K)         CooperStre		nonper serect	1000		Craner Street (S)					_			. :	() =				n 10				
Outper street()         Diamation Street(s)				Conner Chant (E)	Cooper Street (E)	0	63	- \$	< <	_			₂.	K NAM	8 0	2 •	VAN	17	7 6			
Charator Street (S)         L         T 154         9         A         0         -1         MMA         0         -1         MMA         10         -1         MMA         12         8         A         17         24         B         17         24         B         25         21         B         32         A         6         4           Chardton Street (S)         T         4         4         A         8         25         B         9         25         B         7         3         A         6         4           Chardton Street (N)         T         4         4         8         25         B         9         25         B         7         3         A         6         4         4         6         4         6         4         6         4         6         4         6         4         6         4         6			0.85		Cooper Street MI		127	2 01	(∢	, ,			- 1	AWA	, .		AVA	106	. 2		00	
Outdot/Steel(5)         Constraint(5)         R         39         2         A         17         24         B         15         21         B         32         A         25         2           ChardorSteel(5)         T         4         4         A         8         55         B         14         B         32         A         25         2           ChardorSteel(5)         T         4         4         A         8         35         B         14         25         B         7         3         A         25         4           ChardorSteel(6)         T         4         4         8         35         B         14         35         B         7         3         A         3         4         4			05.810		Charlton Street (S)	-	154	6	A			•	7	AVA		7	#NA	162	. 60		8	a
Charlton Street [9] T [ 4 ] 4 ] A [ 8 ] 25   B   9   25   B   14   26   B   7   3   A   6   4   4			(E 87)	Chartton Street (S)	Cooper Street (E)		30	2	. 4	17 2	-	11	24		25	21		52				
			CE 10-8		Chartton Street (N)	-	4	1 1	۲	. 69		: თ	25	6	14	26		7			4	. 4
											-	•						10				-

P2225 Cessnock Phasing Comparison AMSUN Turn Comparison AM Peak

AM Peak								Gase Model	ſ	đ	Cat non		ЧÜ	0.001.00		a have			and a second			Dhora C	
								Date Muuci	1		717 350		-	2 T 7 0 2		10011	-		PT BAR			LINES	4
Time	ID	Intersection	Aimsun Code	From	To	Tum	Modelled	Delay (s)	LoS	Modelled D	Delay (s)	LoS Mo	Modelled Del	Delay (s)	LoS Mod	Modelled Delay (s)	(s) LoS	Modelled	d Delay (s)	s) LoS	Modelled	Delay (s)	( LoS
			05.59.8		Cooper Street (W)	ſ	4	7	٨	0	÷	AVA			AN	۰ ۱۰	1N#	+	e	A	10	т	A
				Cooper Street (M)	Chartton Street (S)	œ	147	4	A	0	7	WA WA	•		AVA		AV#		4	A	63	4	A
			CE19-11		Cooper Street (E)	F	310	ę	¥	35	9	¥	37	9	0.00	31 5	×	279	e	¥	263	e	¥
	7,8%		0619-02		Chartton Street (N)	Ļ	81	4	۷ (	85	15	< 0	81	5		-	-	200	2 0 10	< <	88	4 a	< •
	Vincent	Street		Vincent Street (N)	Cooper Street (W)	æ	104	36	: 0	0	- I-	ANA	-				*		26	: 0	8 8	35	0
	Cooper Street	Street	13000		Vincent Street (S)	Ŧ	127	31	U	112	21	8	66			-	-22		25	8	127	33	U
			10001		Cooper Street (E)	-	27	35	υ	31	27	8	31				8		25	8	36	41	U
				Cooper Street (E)	Vincent Street (N)	ĸ	26	30	U	28	23	8			191				30	U	28	25	8
			13005		Cooper Street (W)	H	145	24	B	0	τ	AVA		10110	450	_		asis	28	8	153	24	8
			130000		Vincent Street (S)	-	34	22	œ	98	29	8	arevo:						27	8	27	20	•
				Vincent Street (S)	Cooper Street (E)	R	2	48	0	9	38	U I	sear 			-	U		26	60	•	7	AVA
			130922		Vincent Street (N)	F	103	23	œ	143	25	60							23	8	66	23	8
			800	Contraction of the second second	Cooper Street (W)	<u>ا</u> د	₽,	27	<u>م</u>	0 2	ۍ ب	AVA						φ.	11		12	21	
				(M) teans radoon	Vincent Street (5) Cooper Street (E)	× +	7 06	27	0 00	54	20		46	67		42 62		107	88	U 00	t 8	40 26	<u>م</u> د
	_		10007		Vincent Street (N)	-	149	31	0	38	88	i w		2				36	28	60	146	29	6
				AI			819	28.80	8	531	34.01			32.52		480 30.63	C E	130	26.45	8	800	28.19	8
	Cumber	Cumberland Street		Cumberland Street (N)	Cooper Street (W)	Я	0	۳	ANA	74	2	A	72		A	3	A		7	HNH.	72	26	8
	Cooper	Cooper Street	0530-2		Cumberland Street (S)	F	212	<i>с</i>	4	235	2	4	222	5		83	4		4	4	150	4	4
					Cooper Street (E)	-	232	~	×	265	2	A	250			33	A		un -	4	27	0	×
				Cooper Street (E)	Cumberland Street (N)	∝ ⊦	21		< •	1	en e	4 <	45			42 3	4 <	6	e 2	< 0	23	4 4	< □
			05240		Cumber Street (W)	- 3	\$ \$	. 4	٤ م	07		4 4				4 4	4 4		47 6	⊳⊲	112	6 4	ם⊲
				Cumberland Street (S)	Cooper Street (E)	. œ	3	. 01	. <	; •	• •	AWA					N#	- 24.5	0 0	<	- 1	, w	< <
					Cumberland Street (N)		151	2	. <	152	m	A	- 220			78 3	A	186	4	4	114	O,	۷
			0520-9		Cooper Street (W)	2	201	2	A	164	<b>m</b>	A	a			82 3	A		25	80	24	33	U
				Cooper Street (W)	Cumberland Street (S)	Ж	\$	4	A	39	3	A	32			30	A		9	×	45	\$	A
			0530-11		Cooper Street (E)	F	123	4	¥	72		A	65			8	A		9	×	48	ŝ	4
	-		CE20-12		Cumberland Street (N)	,	142	4	۷.	16		-	-	-	-			-	8 9		27	5	< (
				AI	and the second second		1471	4.22	<	1151	3.00			+	+			+	CN:07		+	70.75	. د
	Vincent Street Hall Street	Street	131065	Vincent Street (N)	Hall Street (W) Vincent Street (S)	∝ ⊢	35 127	8	<  <	121	11	@ ∢	99 114	9 9	 	132 22 105 14	@ ∢	39	10	4 4	31	13	4 4
			131066		Hall Street (E)	د	•	17	8	0	7	ANA			10.00				7	AN#		17	8
				Hall Street (E)	Vincent Street (N)	œ	0	7	AWA	0	7	AWA	_		1000		-		7	AN#		7	AN#
			131073		Hall Street (M)	H -	105	22	8	102	24	8			<b>6</b>	rie:			20	80		20	<b>m</b>
			12051		Vincent Street (S)	ہ ب		24		с» с	58	0	53X		_				\$			32	0
					Vincent Street (N)	Ľ +	- 8	7 a		174	<del>.</del> a				402				- a			7 9	A A
			131064		Hall Street (W)	د .	2		. ∢	45	÷₽	۲		. 9					10	4	41	4	< ◄
			131008	Hall Street (M)	Vincent Street (S)	Я	10	36	U	F	34	v	- 00	9		1022			32	U	1	31	O
			131070		Hall Street (E)	н	100	53	۵ ۵	145	8	۵ ۵	2000	2 2	- 	802	<	93	23	6 6	06	22	<u>م</u>
			100	AII	אוורפוור אמביר ווא	-	554	15.34		909	16.29	o a		6.55	+	-		603	15.33	o a	502	14.78	• •
	Váne ant	fine ant Ctreat	121020	Incant Graat All	Criana Creat (M)	0		47		10	34							V	17	a a	-	4	: a
	Aberdar	'e Street			Vincent Street (S)	4 1	61	19	0 00	61	3 8	0 00	65	24		58 24	0 00	99	15	0 00	69	25	00
	Snape :	Snape Street	131082		Aberdare Street (E)	-	60	9	۲	43	7	٩		2		_	4	55	7	4	48	ŝ	4
				Aberdare Street (E)	Vincent Street (N)	æ	79	25	8	56	22	80		E	8		80	86	23	80	55	24	8
			135050		Snape Street (M)	E	149	22	œ	177	24	8	0852	32			8	188	23	8	180	23	œ
			_		Vincent Street (S)	-	116	31	U	122	31	U		8			8	126	31	U	111	32	U
			131075	Vincent Street (S)	Aberdare Street (E)	α,	2 8	29	υı	110	8 8	0 0	1000	8				86	58		91	25	
			131078		Vincent Street (N)		88		л «	125	8 :			4 5			20 0	8 3	22	20 <	\$	2 5	ъ «
				Snane Street 000	Vincent Street (%)	<u>ہ</u> د	214	2 8	cc	5 5	1	< a		t y	 			8 7	22	ca	2 5	20	c a
				5	Aherdare Street (F)		110	3	) a	106	24	. a		2 2		186 27	) a	5 151	3 22		171	23	
-	÷	-					:	1	-	-	4	-	-	2	-	_	1 	-	1	i 	-	1	i

# P2225 Cessnock Phasing Comparison AMSUN Turn Comparison AM Peak

_	
E.	
8	
÷Ĕ.	
5	
ŏ.	
F	
5	
ŏ	
<u> </u>	
g	
<u> </u>	
S	
ē	
<u>ح</u>	
-	3
×	÷
×.	2
2	ŝ
5	ŝ
õ	5
æ	5
0	É
ŝ	5
Ř	Ē
2	2

irison	
Compa	
Turn	
VISUN	Peak

P2255 Cessnock Ph	ssnock	P2225 Cessnock Phasing Comparison	arison																				
AM Peak	company	5																					
	-							Base Model		-	phase 1+2			Phase 1, 2 &		Phase 1, 2, 3 & 4	3 & 4		Phase 5			Phase 6	
Time	a 1	Intersection	Aimsun Code	From	To	Tum	Modelled	Delay (s)	LoS	Modelled	Delay (s)	I Sol	fodelied	elay (s)	M Sol	Turm Modelled Delay(e) Los	/ (s)	s Model	ed Delay (	so) LoS	Modelle	Delay (s)	LoS
			131066		Vincent Street (N)	٦	0	ŀ	<b>VN</b> #	1	19	8	1	19	8	1	19 B	2	19	8	0	÷	¥N#
				AII .			938	22.28		1087	23.27	8	1095	23.27	8	22.28 B 1087 23.27 B 1095 23.27 B 974 23.77	77 B	108	1082 21.06 B	8	666	22.13	•

omparison	Phasing Co	Cessnock	522
-----------	------------	----------	-----

P2225

Page 205 of 209	

Total         Total <th< th=""><th>ID Intersection Carle</th><th>A</th><th>Barwin Street</th><th>Scotter Dan</th><th></th><th></th><th>M</th><th>A class</th><th>Mediand Road 340500</th><th>Allandale Road soore</th><th>0082</th><th>10051</th><th>1005000</th><th>Database Cha</th><th>active and a second</th><th>and Mod</th><th>0063</th><th>0005</th><th>M</th><th>N SHOT</th><th>VINCERI Street</th><th>62025</th><th>Doma Mark</th><th>10035</th><th>Mailant Road U.S. Mail</th><th>0.083</th><th>490.05</th><th>0.076</th><th>a case Mean</th><th>All</th><th>Darwin Street 10.1 Dan</th><th>North Avenue</th><th>86.4 Not</th><th>166.67</th><th>10000</th><th>100</th><th>2421056</th><th>Noth Noth</th><th>11-300 11-300</th><th>201</th><th>d 0564-10</th><th>Cooper Street</th><th>SETIO Second</th><th>CERS</th><th>0.6540</th><th>Cha</th><th>CCU-C DENAU</th><th>COD COD</th><th>CENSICS</th><th>061912</th></th<>	ID Intersection Carle	A	Barwin Street	Scotter Dan			M	A class	Mediand Road 340500	Allandale Road soore	0082	10051	1005000	Database Cha	active and a second	and Mod	0063	0005	M	N SHOT	VINCERI Street	62025	Doma Mark	10035	Mailant Road U.S. Mail	0.083	490.05	0.076	a case Mean	All	Darwin Street 10.1 Dan	North Avenue	86.4 Not	166.67	10000	100	2421056	Noth Noth	11-300 11-300	201	d 0564-10	Cooper Street	SETIO Second	CERS	0.6540	Cha	CCU-C DENAU	COD COD	CENSICS	061912
Text         Text <th< td=""><td>From</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>atland Road (E)</td><td></td><td></td><td>atland Road (W)</td><td></td><td></td><td></td><td>ictions Street (S)</td><td></td><td></td><td></td><td>(14)</td><td></td><td></td><td></td><td></td><td></td><td>-</td><td>Avenue (N)</td><td></td><td></td><td>hartton Street (N)</td><td></td><td>6</td><td>ĩ</td><td></td><td>hariton Street (S)</td><td></td><td></td><td></td><td></td></th<>	From																			atland Road (E)			atland Road (W)				ictions Street (S)				(14)						-	Avenue (N)			hartton Street (N)		6	ĩ		hariton Street (S)				
Totality	To	Weborrbi Road (M)	Darwin Street (S)	Mollombi Road (E)	MORENTE HORE (M)	Molicente Road (E)		Mollombi Road (M)	Chartton Street (S)	Matiand Road (E)	Alandae Road (N)	Wollombi Road (W)	Chariton Street (S)	Mattand Road (E)	Mendale Mode (N)	Chartron Street (S)	Mattand Road (E)	Allandale Road (N)	~	Mattand Road (M)	vincent Street (S) Matland Road (E)	Matiand Road (M)	Vincent Street (S)	Matland Road (E)	Matland Rirad (W)	Victoria Street (S)	Mattand Road (E)	Matiand Road (M)	victoria Street (S) Mattand Road (E)		Noth Avenue [W]	Uarwin Street (S) North Avenue (F)	Darwn Street (N)	Noth Arenue (W)	Darwin Street (S)	Noffin Average (E) Denven Street (N)	Noth Avenue [W]	Darwin Street (S)	North Avenue (E) Darwin Street (N)		Cooper Street (M)	Chartton Street (S)	Cooper Street (L)	Cooper Street IN0	Charlton Street (S)	Cooper Street (E)	Charlton Street (%)	cooper ourse (ry) Charlton Street (S)	Cooper Street (E)	Charlton Street (N)
Tubulot         <		-	-	œ	- 0	_ 2		œ	-	a i	œ	H.		α,		- a	-	1		ы :	μ	-	α	-	ŀ	تر .	α	цî	×		α,		œ	F	<u> </u>	× ⊢	1	α,			œ	-	- 0	¢ ⊢	1	α	-	- cc	с н	4
Name 15         Name 15 <t< td=""><td></td><td>699</td><td>313</td><td>8</td><td>8 E</td><td>905</td><td>2300</td><td>868</td><td>0</td><td>8</td><td>149</td><td>540</td><td>0 0</td><td>0 0</td><td>5 C</td><td>o c</td><td>223</td><td>502</td><td>2025</td><td>88</td><td>e (j</td><td>148</td><td>136</td><td>98 I</td><td>1009</td><td>0</td><td>7</td><td>25</td><td>26</td><td>1665</td><td>15</td><td>310</td><td>8</td><td>176</td><td>88</td><td>5482</td><td>130</td><td>8</td><td>215</td><td>2100</td><td>106</td><td>- 8</td><td>87 8</td><td>8</td><td>67</td><td>8</td><td>0 7</td><td>1 25</td><td>316</td><td>74</td></t<>		699	313	8	8 E	905	2300	868	0	8	149	540	0 0	0 0	5 C	o c	223	502	2025	88	e (j	148	136	98 I	1009	0	7	25	26	1665	15	310	8	176	88	5482	130	8	215	2100	106	- 8	87 8	8	67	8	0 7	1 25	316	74
America         America <t< td=""><td>Delay (s)</td><td>m</td><td>14</td><td>24</td><td>7 7</td><td>ţ, en</td><td>6/ 01</td><td>49</td><td>0</td><td>Б (</td><td>27</td><td>m</td><td></td><td>•</td><td>&gt; c</td><td>- c</td><td>8</td><td>0</td><td>20.85</td><td>8 9</td><td>2 8</td><td>13</td><td>51</td><td>6</td><td>10.04</td><td>4</td><td>6</td><td>9</td><td>2 9</td><td>3.99</td><td>un s</td><td>0 0</td><td>1 01</td><td>æ</td><td>0.</td><td>n in</td><td>(7)</td><td>0</td><td>- 0</td><td>951</td><td>04.0</td><td>21 0</td><td>4 4</td><td>о ю</td><td>9</td><td>(T) -</td><td></td><td>2 11</td><td>r m</td><td>4</td></t<>	Delay (s)	m	14	24	7 7	ţ, en	6/ 01	49	0	Б (	27	m		•	> c	- c	8	0	20.85	8 9	2 8	13	51	6	10.04	4	6	9	2 9	3.99	un s	0 0	1 01	æ	0.	n in	(7)	0	- 0	951	04.0	21 0	4 4	о ю	9	(T) -		2 11	r m	4
America         Tennel 1 AA         Tennel 1 AA         America		A	×	æ	¢¢	> <	<	0	≪	в	ß	<	< -	¢.	< <	¢ م	æ	4	8	æ 0	ъс	•	6	4	Þ d	. ∢	B	4	< <	4	₹ -	c 4	. «	¢	¢ ·	< <	¢	æ.	< <	A	¢.	< <	ξ.	< ∢	×	4	AWA A	ε «	: <	4
Tend 1 A A         matrix 1 A           Matrix 1 A         Matrix 1 A         Matri		129	8	8	5/1	5 8	2455	402	0	191	5	661	0 0		5 6		109	82	2177	619	8 5	<u>8</u>	8	69	715	0	æ	8	z 88	1680	9	ig to	3	35	8	8 28	8	<u>1</u> 2	26 [2]	2143	0 0	⇒ 8	B		0	8	14 c	. 0	- 17	¢
Theorem ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) (	telay (s)	12	21	8	7 18	₹ ao	12.63	8	0	17	83	4	0 0	0 0	-	o c	2	2	19.35	12	2 g	1 2	æ	0	2/0	10	26	18	2~	609	<i>т</i> с	o +	- 0	12	0	D 4	0	₽,		12.24	÷.	- S	8 8	1				17	. ~	4F
Protect 1-5 (2)         Activation (2)         Activa		_					×	_				¥	< -	4	< 4			A		_				+	-				_	A				4	A ·	V V	¢	4	< <	A.	-				1104			10.000	0	
1         A matrix F F A         A matrix F A	-						-	í.	2		10						1000				-			-			144				16	515 H			524	204	187	149	88	2156 %	0.	0 6	8 0	0 0	0	12.4.3	5.84		5 <del>(</del> ]	1
Model         Data bits         Model         Data bits         Model	8	-					324	\$		æ :	8	4	0 0		5 6		8	2	106	_				-	270	1 10			-	169	-+	0 -	10	4	0	4 14	(7)	œ	9 -	356	۹. ۲.				1 1			: # 	9	ų
						-	A 23	3	ں ح	a :		4	~ .				6	e	21.	-				A		· (2)				A 15	4 8	न के	. (2)	4	88 E	E N	5	= 1 	n (2	A 19	-3211	2 19	01			1912233 1	237). 188	NA D	· 4	2
Index         Annual         Annual<											80							6		_				-	-	_			_		0	8 -	2	2 23	8	n 14	e g	01	5 2					2 57	~	8	8 -	1.57		
Matrice         Educional         Educional <theducional< th=""> <theducional< th=""> <thedu< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td>A</td><td></td><td></td><td>≪ 1</td><td></td><td>&lt;</td><td>&lt;</td><td>۹.,</td><td>¢ . «</td><td>&lt; &lt;</td><td>æ</td><td>4</td><td>_</td><td></td><td></td><td></td><td></td><td></td><td>_</td><td></td><td></td><td></td><td></td><td>A P</td><td>≪ :</td><td>&lt; &lt;</td><td>&lt;</td><td>æ</td><td>₹ 1</td><td>&lt; &lt;</td><td>¢</td><td>≪ .</td><td>&lt; &lt;</td><td>4 A</td><td>-</td><td></td><td></td><td>AVI</td><td>ANA</td><td>æ</td><td>A North</td><td>V/N#</td><td>&lt;</td><td>4</td></thedu<></theducional<></theducional<>							A			≪ 1		<	<	۹.,	¢ . «	< <	æ	4	_						_					A P	≪ :	< <	<	æ	₹ 1	< <	¢	≪ .	< <	4 A	-			AVI	ANA	æ	A North	V/N#	<	4
Among Line         Control         Contro         Control         Control	Modellec	662	52	8	8 E	59 95	2162	218	101	140	19	474	12	8 .	> 8	Re	250	122	2181	53 F	2 8	287	135	9 <u>9</u>	1702	5	æ	64	46 714	1500	64	ξ Ξ	82	213	128	231	129	R	Z/3	2045		_	0		_	_	_	_		
「10000000 1000000 1000000		6	91	<b>ह</b> (	N 8	8 0	14.14	4	ų	81	8	6	∞ )	e e	> 2	8 K	88	m	23.86	8	3 V.	0	51	5	5 - 5	- 10	8	0		242	un i		7	2	0 .	e vo	4	5	∞ •1	11.40		a (	0 1	2	7	4	0 -	r 10	) 4	1
	_	æ	æ	æ	< <	> <	4	٥	0	0	ø	<	< 1	u. 1	< 0	5 u	æ	4	Ð	a (	20	<	æ	4	Ð 4	4	æ	4	< <	A	۷.	< 4	<	4	4 .	< <	4	4	< <	A	∢ .	< <	< -	< <	<	¢	4 4	€ ∢	. <	4
	Modelled	59	326	8	89	200	2300	998	0	21	<u>8</u>	8	0 0	0 0	5 0	9 C	18	202	2048	88	8 9	191	123	8	233	'n	ŧ	2	764	1618	5	312	212	137	200	न ह	87	ß	212	1938	(0) (0)	5 000	8	5	75	8	o	3 50	307	17.0
	Delay (s)	æ	11	8	4 8	સું ભ	10.01	ま	0	έ	83	ŝ	0 0	0 (	5 C	9 C	16	2	17.02	27	9 8	0	18	E	1010	ų.	17	10	£ 9	4.20	भ ः	o -	7	7	0 .	* *	m	0	e n	9.61	(n) -	- 0	7	9 10	9	m.	7 4	1 4	r en	4

PHI Peak					-	Ī		Rece Model	ľ	e Ho	143		Dhared 1	6.3		Second 2 1			Contraction of the local division of the loc			Division C.	
			Amenu-					100010-0007			_	1	-										
Time	Q	Inters ection	Code	From	To	Tum	Modelled	Delay (s)	LoS h	Modelled De	Delay Is) Lo	LoS Modelled	elled Delay (s)	(s) LoS	Modelled	ed Delay (s)	LoS	Modelled	Delay (s)	LoS	Modelled	Delay (s)	LoS
	Vince	ent Sneet	00902	Ancent Sreet (N)	Cooper Street (M)	α	138	8	۵	-			_			1	AWA	8	8	0	113	8	ш
	Coop	Cooper Street	0000		Vincent Street (S)	+	12	47	٥	200							8	121	ų	0	13	6	0
			145003		Cooper Street (E)	i.	37	iß	٥							_	0	\$	ß	0	4	18	۵
			PEOD	Cooper Street (E)	Vincent Street (N)	α	81 1	1 <b>8</b> (	0 1		-	_					m	19	£ :	0	8	4	0
			0000		Cooper Street (M)		1/3	5 8	n (			~~				_	VN#	<u>8</u> 5	5 8	ы с	₿ 9	R 19	ъζ
			COTAL	Areard Graat (S)	Contar Stead (E)	. a		3 8	2						_	_	> a	2 0	3 -	4MM	2 0	3 9	
			00802	for many based	Vincent Street (N)	-	, 82	8 10	e en	137	8 8	0 6	140	æ	- 8	8	-	181	- 88	Ð	281	2 98	a a
			0000		Cooper Street (M)	1	22	21	Ð								AWA	27	3J	0	8	8	Ð
			CONSC	Cooper Street (M)	Vincent Street (S)	α	80	8	в							_	ш	9	8	0	7	21	Ð
			16602		Cooper Street (E)		8	8	æ 1	3 (		_					0 1	2	B 1	æ i	218	10	ш. і
			144005		Vincent Street (N)	-	148	810	æ (	-		+	+	-	-	+	ш <	671 671	12	ъ «	98) 98)	2,62	а с
						4	1041	20.12				-	2			+		5/01	85	0	NAU 1	35	» د
	5	Cumberland Street		cumberland Street (h)	Cooper Street (M) Cumbed and Street (S)	x .	e 1	N (8	< 4	0	- 0	#NUA U A 145		VIN#	10	N 0	< 4	R	g 4	0 4	5 8	<b>z</b> , ⊲	U 4
	5		(Ess)		Conter Street (E)		191		. ∢	8	_						< ∢	8	9	4	99	10	4
			10030	Corper Street (E)	Cumberland Street (N)	œ	æ	4	4	11							4	5	9	~	14	40	<
			2020		Cooper Street (M)	Ŀ.	121	2	A	23	_					en	*	155	(8)	Q	116	8	0
			9-9220		Cumberland Street (S)	ų,	146	0	Ą	15						æ	4	: 25	4	¥	Ŧ	e	4
			10000	Cumberland Street (S)	Cooper Street (E)	œ	47	co.	A	e		A 4				-	≪.	4	9	<	11	9	¢
			0000		Cumberland Street (N)	H.	15	m	¢	8			2 2	A.		5	¢	123	ŝ	<	151	4	«
			06209		Cooper Street (M)	-1	177	(15)	ج	212			2	4		5	<	<i>1</i> 8	99	0	8	R	0
			CEO-10	Cooper Street (M)	Cumberland Street (S)	α	18	(1)	4	<b>F</b> ] :	m 1	A 23	-	4	3	æ .	¢	5	w -	<	Ŧ	4	¢
			11-920		Cooper Street (E)		8	4 •	< •	æ §	m (	A .		< -	22	4 .	< >	<u>8</u> s	9 0	< •	<u>8</u> ;	9 4	< •
ł	+		2000		cumentand other (N)		1/7	413	< •	nu u	346	0.6	907 30	-	8 301	237	c .	en a	37.05	< <	8	1967	c .
	Mine	Annant Sreet	0.007	40 Annant Street (M)	Hal Street MD	α	970	10	< 4			+		+	+	+	¢ 4	20	11		64 57	11	ه د
	C Bert	and Chevel	e1925	full and the manual	Viewoord Chood /Cl	- -	s	2 0			-	_			_	_		ŝ	1	V	ð	. 0	4
		10010	0.1066		Hal Street E)	. 2	3 0	2 77	AW#		_	< c1			_	_	co	5	: 9	ĊŎ	5 01	2	<
			- 21813 -	Hall Street (E)	Vincent Street (N)	α	0	77	\$NVA		-					-	AWA	0	5	AMA	0	77	#N/W
			0.813		Hal Street (W)	Ļ	8	18	æ		-						æ	41	Ø	æ	82	8	B
			128.0		Vincent Street (S)	ŗ	13	18	æ		_	_	_			_	4	14	2	æ	2	17	æ
	270		1983	Ancent Street (S)	Hal Street (E)	œ	d)	8	Ð							-	AWA	0	7	ØN/A	0	7	#N/A
			0.00		Vincent Street (N)	)	16	12	<							-	æ	110	7	V	118	12	<
			0.971		Hat Street (VI)	-	24	17	æ							-	æ	8	22	æ	27	8	æ
			10005	Hall Street (M)	Vincent Street (S)	α,	ę :	8	æ 1				-			_	0	<u>ب</u>	83	Φ.	10	8	0,
			0.000		Hat Street (c)		3 9	77	ъа	8	R S	10 0	5 8	b C	8 2 2	9.8	n c	2	8 8	D d	38	12	n a
					A A second reasons		472	16.45	8	100				+	-	+	-	105	16.95	6	480	16.01	a
	Vince	fincent Street	C 695 C	Ancent Street (N)	Snape Street (W)	я	9	8	m	Ģ				┝	9		0	9	88.	æ.	9	24	Ð
	Aberi	Aberdare Road	10400		Vincent Street (S)	÷	\$	31	U	8					001		0	30	8	O	98	8	æ
	Shap	Snape Sireel	2005		Aberdate Road (E)	4	3	=	æ	8		A 8	_	_	81		≪	8	ŝ	<	8	9	¢
			4asta	Herdare Road (E)	Vincent Street (N)	α,	93	8 8	т с						4 2		a .	8	KG 8	ω (	4	₽ 8	m a
			1000		Shape Sheet (W)		Εž	4 H	n a	22					[g] (S		n a	2	38	Ба	7	5 6	n a
			directed in	Annant Graat (C)	VIII.00 0 0 0 0 0	- 0	0	8.8	ь с	2 5					121		6 0	100	8 8	0 0	7 0	5 8	<b>6</b> a
			- ANDE	fol table in party	Vincent Shout Ali	¢	5 8	3 %	> a	2 12	3 2	- d			4 (g		) a	20	8 2	> a	3 8	3 8	a a
			216422		Snape Street (W)	4	128	1	5 K	140	: ¢	A 142	10 10	~	193		4	8	2 5	< <	116	1 1	2 4
_			13-1024	Shape Street (W)	Vincent Street (S)	œ	223	8	0	329	8	0 25			219	10	m	224	8	ö	304	8	æ
			21005		Aberdare Road (E)	на	ن ا	8	æ.	218	8	8		0	162	2	ш.,	171	81	0	187	8	m i
	+		0.936		Vincent Street (N)	-	æ	8	0	1	88	0	800	0	9	-	0	0	30 m	0	9	8	0
	-		1	-		1	1011	21.00	р	1000	20.02	H 10	14 mil	0	1021	2010	D	1411	27.04	D	1114	- 20,00	9

P2225 Cessnock Phasing Comparison

ATTACHMENT B

TRAVEL TIME SUMMARY

#### P2225 Cessnock Phasing Comparison AIMSUN Travel Time Comparison AM Peak

Southbound

Sectio ombi Ro

North Avenue South Avenue

Aberdare Street

Northbound

Sections Aberdare Street South Avenue North Avenue Wollombi Road Base

(Km)

0.00

0.22 0.59

0.83

0.00 0.24

0.60 0.82

Di

0.00

0.22 0.37 0.24

(Km)

0.00 0.24

0.36

Southbound				Base	Ph	ase 1+2	Phas	e 1, 2 & 3	Phase	1, 2, 3 & 4	P	hase 5	P	nase 6
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulativ Model
erguson Street	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
/incent Street	0.3	0.30	0:01:02	0:01:02	0:00:57	0:00:57	0:00:55	0:00:55	0:00:50	0:00:50	0:01:25	0:01:25	0:00:57	0:00:57
Cooper Street	0.37	0.67	0:01:08	0:02:10	0:00:55	0:01:52	0:00:55	0:01:51	0:00:52	0:01:42	0:00:59	0:02:24	0:01:10	0:02:07
Aberdare Street	0.47	1.14	0:01:04	0:03:14	0:01:10	0:03:02	0:01:09	0:02:59	0:01:12	0:02:55	0:01:05	0:03:29	0:01:07	0:03:14
tanal de avecad					Di-		Disc		and the second					
Northbound	<u> </u>	Cumulative	() () () () () () () () () () () () () (	Base	Ph	ase 1+2	Phas	e 1, 2 & 3	Phase	1, 2, 3 & 4		nase s	P	nase 6
Sections	Distance (Km)	Distance (Km)	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulativ Model
Aberdare Street	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Cooper Street	0.47	0.47	0:01:15	0:01:15	0:01:17	0:01:17	0:01:16	0:01:16	0:01:19	0:01:19	0:01:13	0:01:13	0:01:15	0:01:15
Maitland Road	0.37	0.84	0:00:56	0:02:11	0:00:52	0:02:10	0:00:52	0:02:09	0:00:50	0:02:09	0:00:57	0:02:10	0:00:55	0:02:10
Ferguson Street	0.31	1.15	0:00:46	0:02:57	0:00:49	0:02:58	0:00:49	0:02:57	0:00:50	0:02:59	0:00:54	0:03:04	0:00:46	0:02:56
		et						D						
Eastbound				Base	Ph	ase 1+2	Phas	e 1, 2 & 3	Phase	1, 2, 3 & 4	-	hase-5	P	nase 6
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulativ Model
Jountview Street	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Allandale Road	0.53	0.53	0:01:26	0:01:26	0:01:20	0:01:20	0:01:23	0:01:23	0:01:28	0:01:28	0:01:25	0:01:25	0:01:26	0:01:26
/ictoria Road	0.43	0.96	0:00:45	0:02:11	0:00:40	0:02:00	0:00:41	0:02:04	0:00:47	0:02:15	0:00:44	0:02:09	0:00:59	0:02:25
				5.650.03										
Westbound			. <u>1</u>	Base	Ph	ase 1+2	Phas	e 1, 2 & 3	Phase	1, 2, 3 & 4		hase 5	P	nase 6
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulativ Model
/ictoria Road	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Mandale Road	0.43	0.43	0:01:19	0:01:19	0:01:15	0:01:15	0:01:18	0:01:18	0:01:29	0:01:29	0:01:27	0:01:27	0:01:23	0:01:23
Mountview Street	0.53	0.96	0:01:05	0:02:24	0:01:05	0:02:20	0:01:05	0:02:23	0:01:08	0:02:37	0:00:59	0:02:26	0:01:07	0:02:30
Eastbound		1		Base	Ph	ase 1+2	Phas	e 1, 2 & 3	Phase	1, 2, 3 & 4	P	hase 5	P	nase 6
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulativ Model
South Avenue	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Charlton Street	0.38	0.38	0:00:38	0:00:38	0:00:38	0:00:38	0:00:39	0:00:39	0:00:37	0:00:37	0:00:38	0:00:38	0:00:37	0:00:37
Cumberland Street	0.17	0.55	0:00:44	0:01:23	0:01:19	0:01:57	0:01:24	0:02:03	0:01:20	0:01:57	0:00:46	0:01:24	0:00:44	0:01:20
Vestbound				Base	Dis	ase 1+2	Phor	e 1. 2 & 3	Phase	1.2.38.4		hase 5	D	nase 6
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulativ Model
Cumberland Street	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Charlton Street	0.00	0.00	0:00:43	0:00:43	#########	#######################################	########	#######################################	########	###########	0:00:48	0:00:48	0:00:43	0:00:43

 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 <t

0:00:43 0:01:35 0:00:43 0:01:37 0:00:43 0:01:37 0:00:46 0:01:40 0:00:42 0:01:33 0:00:49 0:01:40

 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 0:00:00
 <t

# P2225 Cessnock Phasing Comparison AIMSUN Travel Time Comparison PM Peak

outhbound	100			Base	Ph	ase 1+2	Phase	e 1, 2 & 3	Phase	1, 2, 3 & 4		tase 5	- Pł	hase 6
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model										
erguson Street	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
/incent Street	0.3	0.30	0:00:55	0:00:55	0:00:53	0:00:53	0:00:53	0:00:53	0:00:50	0:00:50	0:01:03	0:01:03	0:00:52	0:00:52
Cooper Street	0.37	0.67	0:01:22	0:02:17	0:01:00	0:01:53	0:01:00	0:01:53	0:01:01	0:01:51	0:01:21	0:02:24	0:01:01	0:01:54
Aberdare Street	0.47	1.14	0:01:19	0:03:36	0:01:23	0:03:15	0:01:19	0:03:12	0:01:23	0:03:14	0:01:21	0:03:45	0:01:22	0:03:16

Sections	Distance (Km)	Distance (Km)	Model	Cumulative Model										
Aberdare Street	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Cooper Street	0.47	0.47	0:01:21	0:01:21	0:01:26	0:01:26	0:01:24	0:01:24	0:01:31	0:01:31	0:01:26	0:01:26	0:01:19	0:01:19
Maitland Road	0.37	0.84	0:00:57	0:02:18	0:00:54	0:02:19	0:00:54	0:02:17	0:00:50	0:02:21	0:00:54	0:02:20	0:00:55	0:02:14
Ferguson Street	0.31	1.15	0:00:44	0:03:02	0:00:51	0:03:10	0:00:50	0:03:07	0:00:44	0:03:05	0:00:57	0:03:17	0:00:49	0:03:03

Eastbound				Base	Ph	ase 1+2	Phase	e 1, 2 & 3	Phase	1,2.384		hase 5	Pt	nase 6
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model										
Mountview Street	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Allandale Road	0.53	0.53	0:01:35	0:01:35	0:01:32	0:01:32	0:01:31	0:01:31	0:01:36	0:01:36	0:01:26	0:01:26	0:01:41	0:01:41
Victoria Road	0.43	0.96	0:00:37	0:02:12	0:00:37	0:02:09	0:00:37	0:02:08	0:00:43	0:02:19	0:00:38	0:02:05	0:00:39	0:02:20

Westbound			i	Base	Ph	ase 1+2	Phase	1,2&3	Phase	1, 2, 3 & 4			Pł	nase 6
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model										
Victoria Road	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Allandale Road	0.43	0.43	0:01:12	0:01:12	0:01:17	0:01:17	0:01:21	0:01:21	0:01:21	0:01:21	0:01:36	0:01:36	0:01:22	0:01:22
Mountview Street	0.53	0.96	0:00:53	0:02:04	0:00:56	0:02:12	0:00:58	0:02:19	0:00:51	0:02:12	0:00:54	0:02:30	0:00:55	0:02:17

Eastbound				Base	Ph	ase 1+2	Phase	1,2&3	Phase	1, 2, 3 & 4		hase 5	P	nase 6
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model										
South Avenue	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Charlton Street	0.38	0.38	0:00:39	0:00:39	0:00:38	0:00:38	0:00:40	0:00:40	0:00:42	0:00:42	0:00:40	0:00:40	0:00:38	0:00:38
Cumberland Street	0.17	0.55	0:00:45	0:01:24	0:01:15	0:01:53	0:01:18	0:01:58	0:01:15	0:01:57	0:00:46	0:01:26	0:00:48	0:01:26

Westbound	Base		Phase 1+2		Phase 1, 2 & 3		Phase 1, 2, 3 & 4		Phase 5		Phase 6			
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model
Cumberland Street	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
Charlton Street	0.17	0.17	0:00:43	0:00:43	########	******	########	*******	*****	*****	0:00:51	0:00:51	0:00:42	0:00:42
South Avenue	0.38	0.55	0:00:37	0:01:19	******	******	******	******	*****	*****	0:00:36	0:01:28	0:00:35	0:01:18

Southbound			Base		Phase 1+2		Phase 1, 2 & 3		Phase 1, 2, 3 & 4		Phase 5		Phase 6	
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model
Wollombi Road	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
North Avenue	0.22	0.22	0:00:22	0:00:22	0:00:21	0:00:21	0:00:22	0:00:22	0:00:22	0:00:22	0:00:21	0:00:21	0:00:21	0:00:21
South Avenue	0.37	0.59	0:00:29	0:00:51	0:00:30	0:00:52	0:00:30	0:00:52	0:00:30	0:00:51	0:00:29	0:00:51	0:00:29	0:00:50
Aberdare Street	0.24	0.83	0:00:48	0:01:39	0:00:52	0:01:44	0:00:51	0:01:43	0:00:47	0:01:39	0:00:49	0:01:40	0:00:50	0:01:41

Northbound			Base		Phase 1+2		Phase 1, 2 & 3		Phase 1, 2, 3 & 4		Phase 5		Phase 6	
Sections	Distance (Km)	Cumulative Distance (Km)	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model	Model	Cumulative Model
Aberdare Street	0.00	0.00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00	0:00:00
South Avenue	0.24	0.24	0:00:21	0:00:21	0:00:21	0:00:21	0:00:21	0:00:21	0:00:21	0:00:21	0:00:21	0:00:21	0:00:23	0:00:23
North Avenue	0.36	0.60	0:00:31	0:00:52	0:00:30	0:00:50	0:00:29	0:00:49	0:00:30	0:00:51	0:00:30	0:00:51	0:00:30	0:00:53
Wollombi Road	0.22	0.82	0:00:57	0:01:49	0:01:04	0:01:55	0:01:05	0:01:54	0:01:05	0:01:56	0:00:58	0:01:50	0:00:58	0:01:51