

CIVIL ENGINEERING & INFRASTRUCTURE SERVICES ASSESSMENT REPORT

**LAKES BUSINESS PARK
(SOUTHERN PRECINCT)
11-13 LORD STREET
BOTANY NSW**

***Prepared For:*
DEXUS Property Group
PO BOX R1822
ROYAL EXCHANGE NSW 1225**

***Prepared by:*
Costin Roe Consulting
Level 1, 8 Windmill Street
WALSH BAY NSW 2000**

Rev: A

DOCUMENT VERIFICATION

Project Title	Lake Business Park (Southern Precinct)
Document Title	Civil Engineering Feasibility Report
Project No.	Co9759.01
Description	Civil engineering report for proposed planning application.
Client Contact	Mr James Mah-Chut, DEXUS

	Name	Signature
Prepared by	Mark Wilson	
Checked by	Grant Roe	
Issued by	Mark Wilson	
File Name	9759.01-03.rpt.docx	

Document History

Date	Revision	Issued to	No. Copies
24 Apr. 2015	DRAFT	Mr James Mah-Chut, DEXUS	PDF
11 May 2015	A	Mr James Mah-Chut, DEXUS	PDF
13 May 2015	B	Mr James Mah-Chut, DEXUS	PDF

TABLE OF CONTENTS

1	INTRODUCTION	1
1.1	Introduction & Scope	1
1.2	Site Description	2
1.3	Proposed Application	2
2	INFRASTRUCTURE SERVICES	4
2.1	Potable Water (drinking water)	4
2.2	Waste Water (sewer)	5
2.3	Power	7
2.4	Natural Gas	8
2.5	Telecommunications	9
4	ACCESS AND TRANSPORTATION	10
4.1	Site Access and Parking	10
4.2	Pedestrian Facilities and Transportation	10
5	EROSION AND SEDIMENT CONTROL	11
5.1	Background	11
5.2	Pre-Construction	11
5.3	During Construction	11
5.4	Post Construction	12
6	STORMWATER DRAINAGE	13
6.1	Site Drainage	13
6.1.1	Existing Drainage System	13
6.1.2	Proposed Drainage System	13
6.1.3	Legal Point of Discharge	14
6.2	Stormwater Quantity (On Site Detention)	14
6.3	Stormwater Quality Management	15
6.4	Rainwater Reuse	16

6.5	External Catchments and Overland Flow	17
7	CONCLUSION	18
8	REFERENCES	19

1 INTRODUCTION

1.1 Introduction & Scope

Costin Roe Consulting Pty Ltd has been commissioned by DEXUS to undertake a site conditions and infrastructure services assessment to assist in the Planning Application Stage for a change of zoning at the Lakes Business Park (Southern Precinct), Lord Street, Botany, NSW. The proposed zoning change is from B7-Business to B4-Mixed Use.

The information provided in this Report is intended to inform the Master Planners of the opportunities and constraints associated with the civil engineering requirements and for the provision of infrastructure services to the site. Specifically the report provides the following information:

- Stormwater Management Requirements including stormwater quality and quantity;
- Layout and capacity of existing service networks;
- Indicative utility demands for the current development proposals where available;
- Current service infrastructure delivery programs from the primary utility suppliers where available;
- Service infrastructure assets required onsite; and
- Indicative trunk infrastructure service layouts.

The assessment considers the supply and management of the following services and considerations for the development of the site:

- Potable Water (drinking water);
- Waste Water (sewer);
- Power;
- Natural Gas;
- Telecommunications;
- Stormwater quantity and quality; and
- External Stormwater Catchments and Overland Flow.

1.2 Site Description

The property is located on the southern side of Lord Street in the suburb of Botany as shown in **Figure 1.1**.



Figure 1.1 Locality Plan (Source: SIX Maps 2015)

The property comprises an approximate area of 2.98 Ha and is bounded by Lord Street to the north, Booralee Park to the east, light industrial and residential land to the north and west. The northern side of Lord Street comprises light industrial development including the Northern Precinct of the Lakes Business Park.

The site is located within the bounds of Botany City Council (BCC), therefore the engineering requirements of the BCC *Development Control Plan 2013* will need to be considered for the development.

1.3 Proposed Application

The proposed application is for the rezoning of the land from B7-Business to B4-Mixed Use with the intention of future commercial/ residential development of the land to take place. An indicative Masterplan Layout of the development site has been produced for DEXUS by Tony Caro Architecture Pty Ltd as shown in **Figure 1.2**.




Figure 1.2. Development Masterplan Layout

The proposed layout incorporates 9 residential and commercial buildings of five, six and eight stories. Three, two level basement car parks are also proposed to service the development.

There are approximately 658 units proposed for the development site. Commercial uses totalling an area of 1,174m² are proposed for ground floor fronting Lord Street.

2 INFRASTRUCTURE SERVICES

An overview of the existing and proposed infrastructure network layouts are outlined in the following sections. Reference to **Appendix C** should be made for Dial-Before-You-Dig information for each particular service.

2.1 Potable Water (drinking water)

Sydney Water is the servicing authority for potable water in the suburb of Botany.

Water supply infrastructure is present in the vicinity of the development site. Two CICL water supply mains, DN100 and DN200, run parallel to the northern boundary of the site on Lord Street. A hydrant, connecting to a 100mm CICL pipe, is located on the junction of the southern site boundary and Daniel Street.

Subject to capacity requirements of Sydney Water and the final Masterplan Layout, it is proposed that the connection to the development site be made via a tee into the existing 200mm main at the north-west corner of the development site.

Potable Water Demand

Typical water demand rates for different land uses are provided in **Table 2.1** below.

Land Use	Design Criteria	Units	Potable Water Demand
Single Dwelling Residential (14 - 17 dwelling/net ha)	Max Day Demand	kL/dwelling/day	2.2
Town House (<30 units/net ha)	Max Day Demand	kL/unit/day	1.6
Multi/ high Rise Units	Max Day Demand	kL/N Floor Ha/day	33.5
Light Industrial	Max Day Demand	kL/N Ha/day	40
Medium Industrial	Max Day Demand	kL/N Ha/day	66
Suburban Commercial	Max Day Demand	kL/N Ha/day	40
City Rise Commercial/ shopping Centre	Max Daily Demand	kL/floor Ha/day	63

Table 2.1 Water Demand Unit Rates

Utilising the multi-unit rate of 33.5kL/ N Floor Ha/day over approximately 82,650m² of residential development, a demand for the development in the order of 276 kL/day is expected.

Potable Water Capacity

In order to gain an understanding of capacity of the existing water mains to service the development, the empirical guide to pipe servicing capacity contained in the Water Supply Code of Australia (Sydney Water Version) was used. This is shown in **Table 2.2** below.

Nominal Size of Main DN			Capacity of Main (single direction feed)			
DICL PN36	PVC PN16	PE PN16 PE80B & PE100	Residential (Lots – 500m2)	Rural Residential (lots)	General/ Light Industrial (ha)	High Usage Industrial (ha)
100	100	125	40	-	-	-
150	150	180	160	125	23	-
200	200	250	400	290	52	10
250	250	315	650	470	84	24

Table 2.2 Empirical Sizing of Reticulation Mains

Based on the empirical sizing guidelines, the required demand can be seen to be somewhere near the capacity expected of the existing DN200 and DN100 mains present in Lord Street. The current information does not enable us to estimate the extent of other properties being serviced by the water main and further investigations will be required in this regard. Confirmation of the capacity of the existing system will need to be confirmed via a Section 73 Application to Sydney Water performed by a Sydney Water qualified Quickcheck agent.

Potable Water Supply

The strategy and design for the required extension of the system will need to be performed by a Sydney Water Service Coordinator.

A qualified Hydraulic Engineer shall design internal water and fire system water supply to service the proposed development sites. This will be investigated as part of the detailed design and assessed as part of future separate building development applications.

Notwithstanding the further investigations and applications required with Sydney Water, it is considered that water supply will be able to be provided to the development site.

It should also be noted that rainwater reuse will be employed on this development for non-potable applications including toilet flushing and irrigation. This will be further discussed in **Section 7** of the report.

2.2 Waste Water (sewer)

Sydney Water is the servicing authority for sewage disposal in the suburb of Botany.

Waste water infrastructure is present in the vicinity of the development site. A 225mm CI sewer main, approximately 35m in length runs into the site from Lord Street on the North, with a maintenance hole on the southern end. This pipe run connects to a 225mm CI pressure sewer main running along the northern boundary of the site, with approximately four (4) connection points and three (3) maintenance holes. A connection point to a 225mm CI pressure sewer main also exists on the southern site boundary, on Daniel Street.

Waste Water Service Demand

The design criteria used to forecast future sewer loadings are generally taken from the Sydney Water Area Planning Design Criteria Guide and are expressed as an Equivalent Population for a particular land use. The Average Dry Weather Flow (ADWF) per Equivalent Population (EP) is taken as 180 L/day or 0.0021 L/s ($\text{ADWF (L/s)} = 0.0021 \times \text{EP}$). Alternatively an estimate of the ADWF can be made based on 80% of the expected potable water demand.

Values for typical development types are summarised in **Table 2.3**.

Item	Units	Adopted Value	Source
Single Dwelling Residential	EP/dwelling	3.5	SWC Area Planning Design Criteria Guide
Medium Density Residential (townhouses up to 4 storeys)	EP/dwelling	3.0	SWC Area Planning Design Criteria Guide
High Density Unit Development (up to 200-400 Bedrooms/ Ha)	EP/Bedroom	0.275	SWC Area Planning Design Criteria Guide
Light Industrial	EP/ha	75	SWC Area Planning Design Criteria Guide
Heavy Industrial	EP/ha	150	SWC Area Planning Design Criteria Guide
Commercial	EP/ha	75	SWC Area Planning Design Criteria Guide
High Density Commercial	EP/ha	300 - 800	WSA 02-2002-2.2
Reserves	EP/ha	20	SWC Area Planning Design Criteria Guide

Table 2.3. Sewer Design Loading Criteria

An estimate of the Average Dry Weather Flow (ADWF) for the project has been calculated based on 80% of the expected 276kL demand. An ADWF of 220 kL/day or 2.5 L/s has been estimated for the development.

Note that the design of sewer mains will apply a peaking factor to the ADWF to get the Peak Daily Dry Weather Flow (PDWF), and include the peak (rainfall dependent) inflow and infiltration and the groundwater (non-rainfall) dependent infiltration. The peaking factor will vary depending on the size of the upstream catchment and would normally be within a range of 2 to 5, i.e. 5-12.5 L/s.

Waste Water Capacity

The existing DN225 main in Lord Street is expected to have a capacity in the order of 26 l/s.

Waste Water Removal

Connection of the site waste water is proposed to be made on the northern side of the development at the existing DN225 main on Lord St.

Given the capacity of the connecting main is well above the required output from the development it is expected that the existing main will be sufficient to cater for the development. The extent of the upstream catchment being serviced by the main however is not known and confirmation of the proposed strategy will need to be

performed in conjunction with Sydney Water via a Sydney Water qualified Water Service Coordinator during project application stage.

Notwithstanding the further investigations and applications required with Sydney Water, it is considered that waste water reticulation will be able to be provided to the development site.

2.3 Power

Ausgrid is the servicing authority for energy adjacent to the site.

The Ausgrid plans show that high voltage (HV) cables, with a capacity of 132kV and low voltage (LV) cables are present in Lord Street (north side and south side). The DBYD information also suggests there are conduits present within the property; however details of these are unclear. In any event it would be expected these lines will be made redundant during future works. Further checks would need to be provided by an accredited electrical consultant during detain design stage.

Power Demand

An estimate of the power demand for the Precinct has been estimated using average values for different land uses typically adopted by Integral Energy. These rates are generally considered to be reasonably conservative but are appropriate for preliminary estimation purposes.

Table 2.4 presents the unit rates applied to the power usage calculation and the estimated total power usage for the development.

Land Use	Rate (kW/unit/day)
Residential Dwelling (per dwelling)	5
Light Industrial, Employment, Town Centre, Village Centres, Schools (per m2)	0.04

Table 2.4. Preliminary Power Usage Estimate

To give a reasonable estimate of the daily usage for a multi-unit development such as the Lakes Park Development, a diversity factor should be applied to the usage estimate to make allowance for the variation in usage across the development and the difference between a residential dwelling and unit. For this calculation a typical diversity factor of 0.5 to 0.8 is applied to the sum of the total power usage presented in **Table 2.4**, giving a maximum demand estimate for the Southern Precinct of approximately 1.7-2.8 MW per day.

Power Capacity and Supply

In order to confirm capacity, further investigation and applications will be required with Ausgrid by a qualified electrical consultant. It should be noted that the demand from the proposed development can be compared to the existing light industrial use on the land. Applying a demand rate of 0.04 kW/m2/day for the existing light industrial use over the 3 Ha property, a demand of 1.2 MW/day is calculated. This is lower than the expected demand of the proposed development and some amplification may be required to suite the expected demand range of the development.

Notwithstanding the further investigations and applications required with Ausgrid, it is considered that power supply will be able to be provided to the development site.

2.4 Natural Gas

Jemena is the servicing authority for gas supply adjacent to the site.

Gas infrastructure is available in the form of a secondary high pressure main, 1050kPa capacity, running along the northern site boundary, connecting into the site from Lord Street. A steel main of 100mm also runs along the northern boundary at an average distance of 3.5m from the boundary line.

Natural Gas Demand

Jemena use an energy demand of 20 gigajoules per year to estimate the average annual domestic usage of natural gas for residential dwellings. This usage rate typically equates to the utilisation of a natural gas hot water tank, cook top and heating point.

Table 2.5 presents the natural gas usage estimate for the project, assuming supply to residential units only. This estimate uses a conversion factor of $39.6 \text{ m}^3 / \text{GJ}$ to convert the estimated energy usage into a volume of gas (Roarty, 2008).

Land Use	Number of Dwellings/ Units	Rate (GJ/dwelling/yr)	Conversion Rate (m ³ /GJ)	Usage (GK/yr)	Usage (GJ/day)	Usage (m ³ /day)
Residential Dwellings	450	20	39.6	9000	25	990

Table 2.5. Natural Gas Usage Estimate

The estimated natural gas usage for residential dwellings in the Southern Precincts is approximately $990 \text{ m}^3/\text{day}$.

It should be noted that this natural gas demand estimate excludes demands from commercial premises. Without details of the specific proposed land uses it is difficult to estimate a gas demand for these areas. To meet BASIX requirements, it is expected that the residential units will require a natural gas connection.

Natural Gas Capacity and Supply

The existing DN100 main will have a carrying capacity in the order of $80\text{-}100 \text{ m}^3/\text{hour}$ or $1920\text{-}2400 \text{ m}^3/\text{day}$. Sufficient capacity for gas supply is expected however confirmation by specific application to Jemena will be required to confirm this.

Notwithstanding the further investigations and applications required with Jemena, it is considered that gas supply will be able to be provided to the development site if required. We would expect this to be on an as needs basis for individual lots.

2.5 Telecommunications

Existing local telecommunications services are present on Lord Street.

An Optus fibre optic cable runs through the eastern half of the site and along Lord Street, to the north.

The Telstra plans show that a 100mm PVC conduit with 1-2 ducts exist within the site, connecting to a footway access chamber across the road on Lord Street.

We expect that the existing local cable network would not have the capacity to service the proposed development and that new underground cabling would be required to suit the project requirements. Normally this would be completed on a project by project basis.

Demand and capacity calculations have not been provided for telecommunications as these are not readily quantifiable like the other services provided. The requirements for telecommunications would need to be formalised via a Telstra Smart Community (or similar) registration.

Notwithstanding the further investigations and applications required with Telstra, it is considered that telecommunication infrastructure will be able to be provided to the development site.

4 ACCESS AND TRANSPORTATION

4.1 Site Access and Parking

The proposed development will require access for passenger vehicles and medium commercial vehicles (12.5m rigid) for uses such as deliveries, garbage pickup and the like. The specific traffic movements and the effect of the development on the overall road network are discussed in a report by Traffix Pty Ltd.

The design vehicle for the estate is the 12.5m rigid vehicle. Access and parking will be provided in accordance with Australian Standards AS/NZS2890.1 Parking Facilities Part 1: Off-street car parking, AS 2890.2 Parking Facilities Part 2: Off-street commercial vehicle facilities and AS/NZS 2890.6 Parking Facilities Part 6: Off-street parking for people with disabilities. The number of parking spaces will be provided in accordance with council policy and these are expected to be via basement level parking within the building footprint.

Access from Lord Street to basement level carparks will be made via standard driveway crossings. Driveway crossings will be defined based on Botany Council Requirements and the above mentioned Australian Standards.

4.2 Pedestrian Facilities and Transportation

The site is located within easy access of public transport. Botany road, which is 225m to the west of the property, provides access to bus routes with regular services to the city and Port Botany. A bus stop is located approximately 50m to the north of the intersection of Lord Street with Botany Road.

A pedestrian path is located along the site frontage on Lord Street which extends to Botany Road. This path allows easy connection to the public transport route discussed above.

5 EROSION AND SEDIMENT CONTROL

5.1 Background

During the construction phase of the development, an Erosion and Sediment Control Program will be implemented to minimise water quality impacts. A detailed Erosion and Sediment Control Program will be employed throughout the construction works and a concept for this will be defined during the Development Application stage of the development site. The Erosion and Sediment Control Program will be defined based on normal engineering guidelines including The Landcom publication, Managing Urban Stormwater: Soils and Construction (The Blue Book) and the requirements of Botany Bay City Council. It is expected that the program will include measure such as temporary sediment basins, silt fences, cut-off drains for polluted stormwater and diversion channels for clean stormwater run-off.

The following sections provide information to identify controls and procedures that will be incorporated into the Erosion and Sediment Control program at Development Application Stage.

5.2 Pre-Construction

The following minimum requirements are to be met prior to commencement of construction:

- Protection of downstream receiving waters. The proximity to Botany Bay will require additional considerations to ensure that receiving waters are protected.
- Sediment fences are to be constructed on the upstream edges of the designated buffer strips and at the base of fill embankments.
- Areas for plant and construction material storage are to be designated along with associated drains and spillage holding ponds.
- Diversion banks are to be created at the upstream boundaries of construction activities to ensure upstream runoff is diverted around any exposed areas. Catch drains are to be created at the downstream boundary of construction activities.
- Silt fences and/or sand bags are to be placed along the catch drains to slow flow, reduce scour and capture some sediment from runoff.
- Construction of temporary sediment basins.
- Site personnel are to be educated to the sediment and erosion control measures implemented on site.

5.3 During Construction

The following minimum requirements are to be met during construction:

- Progressive re-vegetation of filled areas and filled batters.
- Construction activities are to be confined to the necessary construction areas.

- The provision of a construction exit (truck shaker) to minimise the tracking of debris from tyres of vehicles leaving the site onto public roads. Only one construction exit will be nominated to limit the movement of construction equipment.
- Topsoil and temporary stockpile location will be nominated to coincide with areas already disturbed. A sediment fence is to be constructed around the downstream side of the stockpile and a diversion drain at the upstream side if required.
- Regular inspection and maintenance of silt fences, sediment basins and other erosion control measures are to be made. These should be undertaken weekly, monthly and following major rainfall events. Following rainfall events greater than 50mm inspection of erosion control measures and removal of collected material should be undertaken. Replacement of any damaged measures should be performed immediately.

5.4 Post Construction

The following minimum requirements are to be met post construction:

- The contractor/ developer will be responsible for the maintenance of erosion and sediment control devices from the possession of the site until the site is accepted “Off Maintenance” or until stabilisation has occurred to the satisfaction of the superintendent and council.
- Key stormwater areas requiring maintenance for operational phase of the project following construction are piped stormwater system, bio-retention areas, field inlet pit inserts and rainwater tanks.

6 STORMWATER DRAINAGE

6.1 Site Drainage

6.1.1 Existing Drainage System

As part of the existing industrial/ commercial development on the property, an extensive in-ground drainage system is present. This system comprises grated inlet pits, sealed junction pits, down pipe connections and in-ground pipes which convey stormwater from buildings, car parks, hardstand areas and other extensive paved areas to the legal point of discharge.

A detention basin is located on the Lord Street frontage of the property at the north-west corner of the site prior to discharge from property into council owned infrastructure in Lord Street. The detention basin provides approximately 500m³ of active storage which attenuates post development flows to pre-developed flows. The detention storage and site discharge rate is based on the council policy which was present at the time of construction of the existing development and allows for a staged discharge for different average recurrence interval (ARI) storms and storm durations.

6.1.2 Proposed Drainage System

As per general engineering practice and the guidelines of BCC, the proposed stormwater drainage system for the development will comprise a minor and major system to safely and efficiently convey collected stormwater run-off from the development to the legal point of discharge. Details of the proposed system for the development will be defined during the Development Application Stage of the project. An option for a stormwater layout and Stormwater Management Concept has been included in this report to show that a suitable Stormwater Management Strategy is achievable for a mixed use residential/ commercial development.

The minor system is to consist of a piped drainage system which has been designed to accommodate the 1 in 20-year ARI storm event (Q20). This results in the piped system being able to convey all stormwater runoff up to and including the Q20 event. The major system will be designed to cater for storms up to and including the 1 in 100-year ARI storm event (Q100). The major system will employ the use of defined overland flow paths, such as roads and open channels, to safely convey excess run-off from the site.

The design of the stormwater system for this site will be based on relevant national design guidelines, Australian Standard Codes of Practice, the standards of PCC and accepted engineering practice. Runoff from buildings will generally be designed in accordance with AS 3500.3 National Plumbing and Drainage Code Part 3 – Stormwater Drainage. Overall site runoff and stormwater management will generally be designed in accordance with the Institution of Engineers, Australia publication “Australian Rainfall and Runoff” (1988 Edition), Volumes 1 and 2 (AR&R).

Water quality and re-use are to be considered in the design to ensure that the detrimental effects of increased pollution loads in stormwater resulting from the development are mitigated, that BCC Water Quality Objectives are met and that the demand on potable water resources is reduced.

6.1.3 Legal Point of Discharge

The legal point of discharge is a point specified by Council where stormwater from a property can be discharged. The legal point of discharge is usually Council's stormwater infrastructure, where available, or street kerb and channel for smaller developments.

Legal discharge for the development is council infrastructure located in Lord Street. Connection to existing in-ground piped drainage system is available at the north-western corner of the property. This is consistent with the location of the outlet of the on-site detention system for the existing development on the property.

6.2 Stormwater Quantity (On Site Detention)

Botany City Council adopts the principles of water quantity management, also known as “On-site Detention (OSD)”, to ensure the cumulative effect of development does not have a detrimental effect on the existing stormwater infrastructure and watercourses located within their LGA downstream from the particular site.

Section 10 of Botany City Councils DCP2013 requires that stormwater runoff generated for all storm durations up to and including the 100- year ARI will be detained to the pre-developed 5-year ARI storm flow.

A simplified conservative DRAINS model was set up to determine an order of magnitude storage requirement for the 3 Ha development. The concept modelling showed that an OSD system with an active storage in the order of 1200m³ is required to achieve the pre-development 5 year ARI flow for ARI storms to the 100-year ARI storm.

Potential configurations for the management of stormwater detention could comprise an in-ground tank (30L x 20W x 2H) or an above ground basin, or a combination of the two. The provision of an above ground basin would enable the integration of a bio-retention system (required for water quality discussed below) within the OSD basin, maximising the efficiency of land use on the site. An option for an open basin configuration has been included in **Appendix A** of the report.

If an open basin is adopted for stormwater detention in the final engineering strategy for the development (at development application/ construction certificate stage) then the water surface elevation of stored water within the detention basin will need to be designed such that the water surface matches the existing staged water levels. This is to ensure that there is no effect on flooding levels and/or detrimental effect on adjoining properties as a result of flooding.

It should be noted that there is a large difference in the required size of the detention basin between the existing basin and proposed basin. This is due to a change in councils on-site detention policy which occurred in December 2013. The new policy provides a restriction on the site discharge rate which greatly increases the requirement for detention storage. The approximate storage size nominated in this concept reflects this change.

Consideration to flooding requirements will also need to be accounted for in the detail design of the development. Further discussion on this matter has been included in **Section 6.5** of this report.

Notwithstanding the final configuration and design details of the preferred stormwater detention solution for the development, we confirm that several different methods of achieving stormwater management and flood storage requirements are available. The chosen solution will be dependent on the final building form and designed during Development Application Stage.

6.3 Stormwater Quality Management

There is a need to provide a design which incorporates the principles of Water Sensitive Urban Design (WSUD) and to target pollutants that are present in the stormwater so as to minimise the adverse impact these pollutants could have on receiving waters and to also meet the requirements specified by BCC.

Water quantity and water quality treatment measures will be adopted to meet the requirements as per the City of Botany Bay Development Control Plan and the Botany Bay & Catchment Water Quality Improvement Plan (BBWQIP) respectively.

The BBWQIP nominates that the following stormwater pollution reduction targets be met (presented in terms of annual percentage pollutant reductions on developed catchments):

Gross Pollutants	90%
Total suspended solids (TSS)	80%
Total phosphorous (TP)	55%
Total nitrogen (TN)	40%

Roof, hardstand, car parking, roads and other extensive paved areas are required to be treated by the Stormwater Treatment Measures (STM). The STM shall be sized according to the whole catchment area of the Site. The STM for the development are based on a treatment train approach as discussed in the NSW EPA document *Managing Urban Stormwater: Treatment Techniques* to ensure that all of the objectives above are met.

A strategy for the site has been proposed to show that Councils objectives can be met. The strategy would be subject to more detailed design during concept design and project application stage of the development. Treatment of the stormwater runoff generated by the development site will be performed via a treatment train approach. The proposed stormwater measures have been sized using MUSIC modelling software.

A treatment train of STM's which would meet councils policy has been described below and shown in drawings contained in **Appendix A**. The system comprises the following components:

- Pre-treatment of surface runoff via a gross pollutant trap or pit inserts for surface inlet pits. This will provide removal of coarse sediments, some fine sediments,

some nutrients, gross pollutants/ rubbish and hydrocarbons. The provision of upstream pre-treatment will assist in reducing the potential for early on-set sedimentation of the bio-retention system;

- Secondary/ tertiary treatment via rainwater reuse; and
- Tertiary Treatment via filtration through a bio-retention system or proprietary filtration system. MUSIC modelling of the site shows that an filtration area of 300m² will be required to meet council policy. The bio-retention system will require an extended detention depth of 300mm and media filter layer 500mm thick. A bio-retention system can be incorporated within the on-site detention basin and can form part of landscape and urban design features.

Incorporation of additional STM's and water sensitive urban design elements on individual sites (such as buffers, bio-retention/ rain-gardens, rainwater reuse, and gross pollutant trap or other suitable hydrodynamic separation units) are encouraged and may be introduced during detailed or Development Application design stages. All stormwater must be treated before discharging into council's stormwater system or downstream receiving waters.

The MUSIC model layout and results can be found in **Appendix D** of the report.

Notwithstanding the final configuration and design details of the preferred stormwater quality management solution for the development, we confirm that several different methods of achieving stormwater quality requirements are available. The chosen solution will be dependent on the final building form and designed during Development Application Stage.

6.4 Rainwater Reuse

Stormwater harvesting refers to the collection of stormwater from the developments internal stormwater drainage system for re-use in non-potable applications. Stormwater from the stormwater drainage system can be classified as either rainwater, where the flow is from roof areas only, or stormwater where the flow is from all areas of the development.

Rainwater harvesting will be provided for this development with re-use for non-potable applications. Specific details of the system will be provided as part of future individual building development applications and the general requirements for the rainwater reuse systems are discussed here. Internal non-potable reuse includes such applications as toilet flushing and car washing while external applications would include landscape irrigation. The aim is to reduce the water demand for the development and to satisfy the requirements of Councils reuse policy.

In general terms the rainwater harvesting system will be an in-line tank for the collection and storage of rainwater. At times when the rainwater storage tank is full rainwater can pass through the tank and continue to be discharged via gravity into the stormwater drainage system. Rainwater from the storage tank will be pumped for distribution throughout the development in a dedicated non-potable water reticulation system.

Rainwater tanks are to be sized with reference to the NSW Department of Environment and Conservation document *Managing Urban Stormwater: Harvesting and Reuse*, using a simple water balance analysis to balance the supply and demand, based on the base water demands and the requirement of Botany Council to provide a reduction in non-potable water demand.

6.5 External Catchments and Overland Flow

An assessment of the development in the context of external catchments and overland flows external to the development site has been completed by WMA Water. Reference to the WMA Water report should be made for confirmation of the 1% Annual Exceedence Probability (AEP) water levels and site management during the a 1% EAP storm events.

The proposed development area is to be defined to be clear of the 1% AEP flood zone and the building envelope defined so that the minimum floor level of the building is set above the 1% AEP water level (RL 5.4m AHD) plus council required freeboard of 500mm.

The threshold of basement level car park is required to be set 300mm above the 1% AEP water level.

As noted previously, if an open basin is adopted for stormwater detention in the final engineering strategy (defined during development application/ construction certificate stage) then the water surface elevation of stored water within the detention basin and landscaped areas will need to be designed such that the water surface matches the existing staged water levels and storage volumes. The staged volumes are defined in the WMA Water report and included in Table 6.1. This is to ensure that there is no effect on the 1% AEP water level and/or detrimental effect on adjoining properties as a result of the development.

Elevation (m AHD)	Storage (m ³)
3.9	0
4	3
4.1	24
4.2	72
4.3	134
4.4	207
4.5	289
4.6	377
4.7	473
4.8	577
4.9	689
5.0	808
5.1	933
5.2	1064
5.3	1202
5.4	1348

Table 6.1. Staged Storage Requirements

7 CONCLUSION

This Site Conditions & Infrastructure Services Assessment Report has been prepared to support the proposal to rezone the existing B7-Business zoning at the Lakes Business Park (Southern Precinct), Lord Street, Botany, NSW to be B4-Mixed Use Zoning.

An overview of services and Botany City Council requirements for stormwater and access has been provided to assist in the stage one due diligence process for the proposed adjusted zoning of the site.

All major services are located in the vicinity of the site, including:

- Potable Water (drinking water);
- Waste Water (sewer);
- Power;
- Natural Gas; and
- Telecommunications.

The existing services have the capacity, or can be amplified, to satisfy the demands of the B4 residential development. Connection of these services to the development site is available and any servicing for the site would be completed at no cost to Government and would not impinge on the services of existing surrounding landowners.

A Stormwater Management Strategy has been provided to show that the requirements of Botany City Council can be met. Specific discussion on the objectives for water quantity (on-site detention) and water quality has been made and also discussion on the potential strategies available to meet these requirements. It is expected that detention storage in the order of 1200m³ will be required to meet water quantity objectives. This would comprise 500m³ as an open basin (to match existing) and the remaining 700m³ comprising either above ground basins or tank arrangements. Water quality objectives can be met via a number of Water Sensitive Urban Design measures or by proprietary water quality measures. A bio-retention filtration system with a surface area of 300m² would be meet councils load based pollution reduction requirements.

Consideration of overland flow requirements will also need to be made as part of the preferred Stormwater Management solution for the development. The floor levels of proposed buildings will be set at the 1% AEP water level of RL 5.4m AHD plus 500mm freeboard in accordance with the requirements of Botany City Council and the NSW Floodplain Development Manual.

Accordingly, based on the site conditions of the land and the availability of infrastructure services to the land, the development site and its extended land area provides an opportunity to make available additional residential and commercial development in a short timeframe given the proposed change in Land Zone is supported by the Botany Bay Masterplanners.

8 REFERENCES


Managing Urban Stormwater: Harvesting and Reuse – 2006 (NSW DEC);
Managing Urban Stormwater: Source Control – 1998 (NSW EPA);
Managing Urban Stormwater: Treatment Techniques – 1997 (NSW EPA);
Managing Urban Stormwater: Soils & Construction – 2004(LANDCOM);
Botany City Council – DCP 2013: Part 3G – Stormwater Management;
Botany City Council – DCP 2013: Part 10 – Stormwater Management Technical Guidelines; and
Water Sensitive Urban Design – “Technical Guidelines for Western Sydney” by URS Australia Pty Ltd, May 2004

Appendix A


Proposed Development Layout

PLANNING PROPOSAL MASTERPLAN


SCHEMATIC CONCEPT PLAN



SCHEMATIC ISOMETRIC



VEHICULAR CIRCULATION DIAGRAM



MASTERPLAN DETAILS

TOTAL GFA: 66,930 m²
SITE AREA: 29,770 m²
FSR: 2.25:1

NOTES

- MIXED USE
- CASA HEIGHT COMPLIANT
- BUILDING HEIGHTS COMPLY WITH MAX RL=AHD 33.00

LAKES BUSINESS PARK
SOUTH PRECINCT


DEXUS

PLANNING PROPOSAL MASTERPLAN

DWG NO. SK_002
PROJECT No. 1503
PLOT DATE 8/5/15
SCALE 1:2000 @ A3

Appendix B

Drawings by Costin Roe Consulting



LEGEND:

LEVELS DATUM IS AHD.

EXISTING SITE LEVELS AND DETAILS BASED ON SURVEY INFORMATION PROVIDED BY LINKER SURVEYING DATED 16.04.15

- [Symbol] - SGGP, SINGLE GRATED GULLY PIT
- [Symbol] - SJP, SEALED JUNCTION PIT
- [Symbol] - DRAINAGE LINE
- [Symbol] - DENOTES STORMWATER MANAGEMENT BASIN AREA

STORMWATER MANAGEMENT REQUIREMENTS

STORMWATER QUALITY

GROSS POLLUTANTS	90%
TOTAL SUSPENDED SOLIDS (TSS)	80%
TOTAL PHOSPHOROUS (TP)	55%
TOTAL NITROGEN (TN)	40%

REDUCTIONS ARE PRESENTED IN TERMS OF ANNUAL PERCENTAGE POLLUTANT REDUCTIONS ON THE DEVELOPED CATCHMENT.

STORMWATER QUANTITY

STORMWATER RUNOFF GENERATED FOR ALL STORM DURATIONS UP TO AND INCLUDING THE 100 YEAR ARI WILL BE DETAINED TO THE PRE-DEVELOPED 5 YEAR ARI STORM FLOW. CAPACITY OF EXISTING DETENTION BASIN & LANDSCAPE STORAGE TO BE PROVIDED IN NEW OPEN DETENTION BASIN TO ENSURE NO CHANGE IN THE OVERLAND FLOW OR FLOODING FOLLOWING DEVELOPMENT AS PER THE BELOW STORAGE TABLE.

STORAGE TABLE


ELEVATION (m AHD)	STORAGE (m³)
3.9	0
4.0	3
4.1	24
4.2	72
4.3	134
4.4	207
4.5	289
4.6	377
4.7	473
4.8	577
4.9	689
5.0	808
5.1	933
5.2	1064
5.3	1202
5.4	1348

NOTE:

DRAWINGS TO BE READ IN CONJUNCTION WITH REPORT C09759.01-03.rpt BY COSTIN ROE CONSULTING. THESE DRAWINGS ARE CONCEPTUAL IN NATURE & PREPARED FOR THE SOLE PURPOSE OF DEMONSTRATING THAT STORMWATER MANAGEMENT FOR A PROPOSED MIXED USE DEVELOPMENT IS ACHIEVABLE.



FOR INFORMATION



Appendix C

Dial Before You Dig Information





Asplund plans show the position of assets at the time of installation and may indicate the location of underground assets. Asplund plans should not be used as the only means of identifying underground assets. Asplund plans show more than the presence or absence of Asplund assets in the area. **Persons working near electricity networks must exercise care and will be held responsible for any damage caused.** Asplund plans should be used in conjunction with other information to establish the location of underground cables and associated assets. **Asplund plans are not a substitute for a safe working method.** If an electric shock even if not fatal is caused, any work in the vicinity of any cable should only be performed after the following steps have been taken:

- Work should be carried out in accordance with the Asplund Work Code for Work Code of Practice for Excavation and Work Code Guide for Work Under Ground Assets.
- Work should be carried out in accordance with the National Standard NS156.
- Do not cut, excavate, near poles, or towers until the stability of the surrounding area has been confirmed.
- Do not cut, excavate, near poles, or towers until the stability of the surrounding area has been confirmed.
- Do not cut, excavate, near poles, or towers until the stability of the surrounding area has been confirmed.


Asplund plans should be used in conjunction with other information to establish the location of underground assets. Asplund plans show more than the presence or absence of Asplund assets in the area. **Persons working near electricity networks must exercise care and will be held responsible for any damage caused.** Asplund plans should be used in conjunction with other information to establish the location of underground cables and associated assets. **Asplund plans are not a substitute for a safe working method.** If an electric shock even if not fatal is caused, any work in the vicinity of any cable should only be performed after the following steps have been taken:


- Work should be carried out in accordance with the Asplund Work Code for Work Code of Practice for Excavation and Work Code Guide for Work Under Ground Assets.
- Work should be carried out in accordance with the National Standard NS156.
- Do not cut, excavate, near poles, or towers until the stability of the surrounding area has been confirmed.
- Do not cut, excavate, near poles, or towers until the stability of the surrounding area has been confirmed.
- Do not cut, excavate, near poles, or towers until the stability of the surrounding area has been confirmed.

Asplund plans should be used in conjunction with other information to establish the location of underground assets. Asplund plans show more than the presence or absence of Asplund assets in the area. **Persons working near electricity networks must exercise care and will be held responsible for any damage caused.** Asplund plans should be used in conjunction with other information to establish the location of underground cables and associated assets. **Asplund plans are not a substitute for a safe working method.** If an electric shock even if not fatal is caused, any work in the vicinity of any cable should only be performed after the following steps have been taken:

- Work should be carried out in accordance with the Asplund Work Code for Work Code of Practice for Excavation and Work Code Guide for Work Under Ground Assets.
- Work should be carried out in accordance with the National Standard NS156.
- Do not cut, excavate, near poles, or towers until the stability of the surrounding area has been confirmed.
- Do not cut, excavate, near poles, or towers until the stability of the surrounding area has been confirmed.
- Do not cut, excavate, near poles, or towers until the stability of the surrounding area has been confirmed.

10





WARNING

Ausgrid's plans show the position of assets at the time of installation and may not account for subsequent changes to road alignments, fences or buildings. The plans show no more than the presence or absence of Ausgrid assets in the street.

Persons working near electricity networks must exercise care and will be held responsible for any damage caused.

You must excavate by hand or use vacuum excavation to establish the location of Ausgrid underground cables and associated assets.

Underground: Working near a cable may result in electric shock even if no contact is made. Any work in the vicinity of any cable should only be performed using safe work methods developed in accordance with the recommendations included in WorkCover Code of Practice for Excavation and WorkCover Guide for Work Near Underground Assets.

as well as recommendations of Ausgrid's Network Standard NS 106.

Overhead: Do not excavate near poles or towers until the stability of the foundation has been assessed by Ausgrid. Cables or earth conductors may be present close to substations, poles or towers.

Workers must maintain safe approach distances and follow applicable WorkCover Code of Practice.

NOTE: You must keep this plan on site during excavation works and have on site a person trained to read this plan.

MA1331	MA4850	MA13321
MA13313	MA13344	MA13322
MA13321	MA13332	MA13341

MA13321GMLA0

Distribution - 44505632

19 Mar 2015

Page 1 of 1

1:251

15 metres

Ausgrid

MA133

MA133

MA133

MA133

Asset ID	Asset Name	Asset Type
42	42-54	42-54
44	44-54	44-54
50	50-54	50-54
52	52-54	52-54
58	58-54	58-54
64	64-54	64-54
66	66-54	66-54
68	68-54	68-54
70	70-54	70-54
72	72-54	72-54
74	74-54	74-54
76	76-54	76-54
78	78-54	78-54
80	80-54	80-54
82	82-54	82-54
84	84-54	84-54
86	86-54	86-54
88	88-54	88-54
90	90-54	90-54
92	92-54	92-54
94	94-54	94-54
96	96-54	96-54
98	98-54	98-54
100	100-54	100-54

WARNING

Ausgrid's plans show the position of assets at the time of installation and may not account for subsequent changes to road alignments, fences or buildings. The plans show no more than the presence or absence of Ausgrid assets in the street.

Persons working near electricity networks must exercise care and will be held responsible for any damage caused.

You must excavate by hand or use vacuum excavation to establish the location of Ausgrid underground cables and associated assets.

Underground: Working near a cable may result in electric shock, even if no contact is made. Any work in the vicinity of any cable should only be performed using safe work methods developed in accordance with the recommendations included in WorkCover Code of Practice for Excavation and WorkCover Guide for Work Near Underground Assets.

Overhead: Do not excavate near poles or towers until the stability of the foundation has been assessed by Ausgrid. Cables or earth conductors may be present close to substations, poles or towers.

Workers must maintain safe approach distances and follow applicable WorkCover Code of Practice.

NOTES: You must keep this plan on site during excavation works and have on site a person trained to read this plan.

MA1311

MA1312

MA1313

MA1314

MA1315

MA1316

MA1317

MA1318

MA1319

MA1320

MA1321

MA1322

MA1323

MA1324

MA1325

MA1326

MA1327

MA1328

MA1329

MA1330

MA1331

MA1332

MA1333

MA1334

MA1335

MA1336

MA1337

MA1338

MA1339

MA1340

MA1341

MA1342

MA1343

MA1344

MA1345

MA1346

MA1347

MA1348

MA1349

MA1350

MA1351

MA1352

MA1353

MA1354

MA1355

MA1356

MA1357

MA1358

MA1359

MA1360

MA1361

MA1362

MA1363

MA1364

MA1365

MA1366

MA1367

MA1368

MA1369

MA1370

MA1371

MA1372

MA1373

MA1374

MA1375

MA1376

MA1377

MA1378

MA1379

MA1380

MA1381

MA1382

MA1383

MA1384

MA1385

MA1386

MA1387

MA1388

MA1389

MA1390

MA1391

MA1392

MA1393

MA1394

MA1395

MA1396

MA1397

MA1398

MA1399

MA1400

MA1401

MA1402

MA1403

MA1404

MA1405

MA1406

MA1407

MA1408

MA1409

MA1410

MA1411

MA1412

MA1413

MA1414

MA1415

MA1416

MA1417

MA1418

MA1419

MA1420

MA1421

MA1422

MA1423

MA1424

MA1425

MA1426

MA1427

MA1428

MA1429

MA1430

MA1431

MA1432

MA1433

MA1434

MA1435

MA1436

MA1437

MA1438

MA1439

MA1440

MA1441

MA1442

MA1443

MA1444

MA1445

MA1446

MA1447

MA1448

MA1449

MA1450

MA1451

MA1452

MA1453

MA1454

MA1455

MA1456

MA1457

MA1458

MA1459

MA1460

MA1461

MA1462

MA1463

MA1464

MA1465

MA1466

MA1467

MA1468

MA1469

MA1470

MA1471

MA1472

MA1473

MA1474

MA1475

MA1476

MA1477

MA1478

MA1479

MA1480

MA1481

MA1482

MA1483

MA1484

MA1485

MA1486

MA1487

MA1488

MA1489

MA1490

MA1491

MA1492

MA1493

MA1494

MA1495

MA1496

MA1497

MA1498

MA1499

MA1500

MA1501

MA1502

MA1503

MA1504

MA1505

MA1506

MA1507

MA1508

MA1509

MA1510

MA1511

MA1512

MA1513

MA1514

MA1515

MA1516

MA1517

MA1518

MA1519

MA1520

MA1521

MA1522

MA1523

MA1524

MA1525

MA1526

MA1527

MA1528

MA1529

MA1530

MA1531

MA1532

MA1533

MA1534

MA1535

MA1536

MA1537

MA1538

MA1539

MA1540

MA1541

MA1542

MA1543

MA1544

MA1545

MA1546

MA1547

MA1548

MA1549

MA1550

MA1551

MA1552

MA1553

MA1554

MA1555

MA1556

MA1557

MA1558

MA1559

MA1560

MA1561

MA1562

MA1563

MA1564

MA1565

MA1566

MA1567

MA1568

MA1569

MA1570

MA1571

MA1572

MA1573

MA1574

MA1575

MA1576

MA1577

MA1578

MA1579

MA1580

MA1581

MA1582

MA1583

MA1584

MA1585

MA1586

MA1587

MA1588

MA1589

MA1590

MA1591

MA1592

MA1593

MA1594

MA1595

MA1596

MA1597

MA1598

MA1599

MA1600

MA1601

MA1602

MA1603

MA1604

MA1605

MA1606

MA1607

MA1608

MA1609

MA1610

MA1611

MA1612

MA1613

MA1614

MA1615

MA1616

MA1617

MA1618

MA1619

MA1620

MA1621

MA1622

MA1623

MA1624

MA1625

MA1626

MA1627

MA1628

MA1629

MA1630

MA1631

MA1632

MA1633

MA1634

MA1635

MA1636

MA1637

MA1638

MA1639

MA1640

MA1641

MA1642

MA1643

MA1644

MA1645

MA1646

MA1647

MA1648

MA1649

MA1650

MA1651

MA1652

MA1653

MA1654

MA1655

MA1656

MA1657

MA1658

MA1659

MA1660

MA1661

MA1662

MA1663

MA1664

MA1665

MA1666

MA1667

MA1668

MA1669

MA1670

MA1671

MA1672

MA1673

MA1674

MA1675

MA1676

MA1677

MA1678

MA1679

MA1680

MA1681

MA1682

MA1683

MA1684

MA1685

MA1686

MA1687

MA1688

MA1689

MA1690

MA1691

MA1692

MA1693

MA1694

MA1695

MA1696

MA1697

MA1698

MA1699

MA1700

MA1701

MA1702

MA1703

MA1704

MA1705

MA1706

MA1707

MA1708

MA1709

MA1710

MA1711

MA1712

MA1713

MA1714

MA1715

MA1716

MA1717

MA1718

MA1719

MA1720

MA1721

MA1722

MA1723

MA1724

MA1725

MA1726

MA1727

MA1728

MA1729

MA1730

MA1731

MA1732

MA1733

MA1734

MA1735

MA1736

MA1737

MA1738

MA1739

MA1740

MA1741

MA1742

MA1743

MA1744

MA1745

MA1746

MA1747

MA1748

MA1749

MA1750

MA1751

MA1752

MA1753

MA1754

MA1755

MA1756

MA1757

MA1758

MA1759

MA1760

MA1761

MA1762

MA1763

MA1764

MA1765

MA1766

MA1767

MA1768

MA1769

MA1770

MA1771

MA1772

MA1773

MA1774

MA1775

MA1776

MA1777

MA1778

MA1779

MA1780

MA1781

MA1782

MA1783

MA1784

MA1785

MA1786

MA1787

MA1788

MA1789

MA1790

MA1791

MA1792

MA1793

MA1794

MA1795

MA1796

MA1797

MA1798

MA1799

MA1800

MA1801

MA1802

MA1803

MA1804

MA1805

MA1806

MA1807

MA1808

MA1809

MA1810

MA1811

MA1812

MA1813

MA1814

MA1815

MA1816

MA1817

MA1818

MA1819

MA1820

MA1821

MA1822

MA1823

MA1824

MA1825

MA1826

MA1827

MA1828

MA1829

MA1830

MA1831

MA1832

MA1833

MA1834

MA1835

MA1836

MA1837

MA1838

MA1839

MA1840

MA1841

MA1842

MA1843

MA1844

MA1845

MA1846

MA1847

MA1848

MA1849

MA1850

MA1851

MA1852

MA1853

MA1854

MA1855

MA1856

MA1857

MA1858

MA1859

MA1860

MA1861

MA1862

MA1863

MA1864

MA1865

MA1866

MA1867

MA1868

MA1869

MA1870

MA1871

MA1872

MA1873

MA1874

MA1875

MA1876

MA1877

MA1878

MA1879

MA1880

MA1881

MA1882

MA1883

MA1884

MA1885

MA1886

MA1887

MA1888

MA1889

MA1890

MA1891

MA1892

MA1893

MA1894

MA1895

MA1896

MA1897

MA1898

MA1899

MA1900

MA1901

MA1902

MA1903

MA1904

MA1905

MA1906

MA1907

MA1908

MA1909

MA1910

MA1911

MA1912

MA1913

MA1914

MA1915

MA1916

MA1917

MA1918

MA1919

MA1920

MA1921

MA1922

MA1923

MA1924

MA1925

MA1926

MA1927

MA1928

MA1929

MA1930

MA1931

MA1932

MA1933

MA1934

MA1935

MA1936

MA1937

MA1938

MA1939

MA1940

MA1941

MA1942

MA1943

MA1944

MA1945

MA1946

MA1947

MA1948

MA1949

MA1950

MA1951

MA1952

MA1953

MA1954

MA1955

MA1956

MA1957

MA1958

MA1959

MA1960

MA1961

MA1962

MA1963

MA1964

MA1965

MA1966

MA1967

MA1968

MA1969

MA1970

MA1971

MA1972

MA1973

MA1974

MA1975

MA1976

MA1977

MA1978

MA1979

MA1980

MA1981

MA1982

MA1983

MA1984

MA1985

MA1986

MA1987

MA1988

MA1989

MA1990

MA1991

MA1992

MA1993

MA1994

MA1995

MA1996

MA1997

MA1998

MA1999

MA2000

MA2001

MA2002

MA2003

MA2004

MA2005

MA2006

MA2007

MA2008

MA2009

MA2010

MA2011

MA2012

MA2013

MA2014

MA2015

MA2016

MA2017

MA2018

MA2019

MA2020

MA2021

MA2022

MA2023

MA2024

MA2025

MA2026

MA2027

MA2028

MA2029

MA2030

MA2031

MA2032

MA2033

MA2034

MA2035

MA2036

MA2037

MA2038

MA2039

MA2040

MA2041

MA2042

MA2043

MA2044

MA2045

MA2046

MA2047

MA2048

MA2049

MA2050

MA2051

MA2052

MA2053

MA2054

MA2055

MA2056

MA2057

MA2058

MA2059

MA2060

MA2061

MA2062

MA2063

MA2064

MA2065

MA2066

MA2067

MA2068

MA2069

MA2070

MA2071

MA2072

MA2073

MA2074

MA2075

MA2076

MA2077

MA2078

MA2079

MA2080

MA2081

MA2082

MA2083

MA2084

MA2085

MA2086

MA2087

MA2088

MA2089

MA2090

MA2091

MA2092

MA2093

MA2094

MA2095

MA2096

MA2097

MA2098

MA2099

MA2100

MA2101

MA2102

MA2103

MA2104

MA2105

MA2106

MA2107

MA2108

MA2109

MA2110

MA2111

MA2112

MA2113

MA2114

MA2115

MA2116

MA2117

MA2118

MA2119

MA2120

MA2121

MA2122

MA2123

MA2124

MA2125

MA2126

MA2127

MA2128

MA2129

MA2130

MA2131

MA2132

MA2133

MA2134

MA2135

MA2136

MA2137

MA2138

MA2139

MA2140

MA2141

MA2142

MA2143

MA2144

MA2145

MA2146

MA2147

MA2148

MA2149

MA2150

MA2151

MA2152

MA2153

MA2154

MA2155

MA2156

MA2157

MA2158

MA2159

MA2160

MA2161

MA2162

MA2163

MA2164

MA2165

MA2166

MA2167

MA2168

MA2169

MA2170

MA2171

MA2172

MA2173

MA2174

MA2175

MA2176

MA2177

MA2178

MA2179

MA2180

MA2181

MA2182

MA2183

MA2184

MA2185

MA2186

MA2187

MA2188

MA2189

MA2190

MA2191

MA2192

MA2193

MA2194

MA2195

MA2196

MA2197

MA2198

MA2199

MA2200

MA2201

MA2202

MA2203

MA2204

MA2205

MA2206

MA2207

MA2208

MA2209

MA2210

MA2211

MA2212

MA2213

MA2214

MA2215

MA2216

MA2217

MA2218

MA2219

MA2220

MA2221

MA2222

MA2223

MA2224

MA2225

MA2226

MA2227

MA2228

MA2229

MA2230

MA2231

MA2232

MA2233

MA2234

MA2235

MA2236

MA2237

MA2238

MA2239

MA2240

MA2241

MA2242

MA2243

MA2244

MA2245

MA2246

MA2247

MA2248

MA2249

MA2250

MA2251

MA2252

MA2253

MA2254

MA2255

MA2256

MA2257

MA2258

MA2259

MA2260

MA2261

MA2262

MA2263

MA2264

MA2265

MA2266

MA2267

MA2268

MA2269

MA2270

MA2271

MA2272

MA2273

MA2274

MA2275

MA2276

MA2277

MA2278

MA2279

MA2280

MA2281

MA2282

MA2283

MA2284

MA2285

MA2286

MA2287

MA2288

MA2289

MA2290

MA2291

MA2292

MA2293

MA2294

MA2295

MA2296

MA2297

MA2298

MA2299

MA2300

MA2301

MA2302

MA2303

MA2304

MA2305

MA2306

MA2307

MA2308

MA2309

MA2310

MA2311

MA2312

MA2313

MA2314

MA2315

MA2316

MA2317

MA2318

MA2319

MA2320

MA2321

MA2322

MA2323

MA2324

MA2325

MA2326

MA2327

MA2328

MA2329

MA2330

MA2331

MA2332

MA2333

MA2334

MA2335

MA2336

MA2337

MA2338

MA2339

MA2340

MA2341

MA2342

MA2343

MA2344

MA2345

MA2346

MA2347

MA2348

MA2349

MA2350

MA2351

MA2352

MA2353

MA2354

MA2355

MA2356

MA2357

MA2358

MA2359

MA2360

MA2361

MA2362

MA2363

MA2364

MA2365

MA2366

MA2367

MA2368

MA2369

MA2370

MA2371

MA2372

MA2373

MA2374

MA2375

MA2376

MA2377

MA2378

MA2379

MA2380

MA2381

MA2382

MA2383

MA2384

MA2385

MA2386

MA2387

MA2388

MA2389

MA2390

MA2391

MA2392

MA2393

MA2394

MA2395

MA2396

MA2397

MA2398

MA2399

MA2400

MA2401

MA2402

MA2403

MA2404

MA2405

MA2406

MA2407

MA2408

MA2409

MA2410

MA2411

MA2412

MA2413

MA2414

MA2415

MA2416


MA2417

MA2418

MA2419

MA2420

MA242



WARNING

Ausgrid's plans show the position of assets at the time of installation and may not account for subsequent changes to road alignments, fences or buildings. The plans show no more than the presence or absence of Ausgrid assets in the street.

Persons working near electricity networks must exercise care and will be held responsible for any damage caused.

You must excavate by hand or use vacuum excavation to establish the location of Ausgrid underground cables and associated assets.

Underground: Working near a cable may result in electric shock, even if no contact is made. Any work in the vicinity of any cable should only be performed using safe work methods developed in accordance with the recommendations included in WorkCover Code of Practice for Excavation and WorkCover Guide for Work Near Underground Assets.

as well as recommendations of Ausgrid's Network Standard NS106.

Overhead: Do not excavate near poles or towers until the stability of the foundation has been assessed by Ausgrid. Cables or earth conductors may be present close to substations, poles or towers.

Workers must maintain safe approach distances and follow applicable WorkCover Code of Practice.

NOTICE: You must keep this plan on site during excavation works and have on site a person trained to read this plan.

MA13311	MA13312	MA13313
MA13314	MA13315	MA13316
MA13317	MA13318	MA13319

MA13313GMLA0

Distribution - 44505632

REVISIONS ONLY - NOT FOR CONSTRUCTION


19 Mar 2015

Page 1 of 1

1:251

0 15 metres

Ausgrid



JOINT DETAIL REPORT		
Ref.	Joint Ref.	Joint Description
13	000205	7/0.007V CABLE JOINT
14	000206	7/0.007V CABLE JOINT
15	000207	7/0.007V CABLE JOINT
16	000208	7/0.007V CABLE JOINT
17	000209	7/0.007V CABLE JOINT
18	000210	7/0.007V CABLE JOINT
19	000211	7/0.007V CABLE JOINT
20	000212	7/0.007V CABLE JOINT
21	000213	7/0.007V CABLE JOINT
22	000214	7/0.007V CABLE JOINT
23	000215	7/0.007V CABLE JOINT
24	000216	7/0.007V CABLE JOINT
25	000217	7/0.007V CABLE JOINT
26	000218	7/0.007V CABLE JOINT
27	000219	7/0.007V CABLE JOINT
28	000220	7/0.007V CABLE JOINT
29	000221	7/0.007V CABLE JOINT
30	000222	7/0.007V CABLE JOINT
31	000223	7/0.007V CABLE JOINT
32	000224	7/0.007V CABLE JOINT
33	000225	7/0.007V CABLE JOINT
34	000226	7/0.007V CABLE JOINT
35	000227	7/0.007V CABLE JOINT
36	000228	7/0.007V CABLE JOINT
37	000229	7/0.007V CABLE JOINT
38	000230	7/0.007V CABLE JOINT
39	000231	7/0.007V CABLE JOINT
40	000232	7/0.007V CABLE JOINT
41	000233	7/0.007V CABLE JOINT
42	000234	7/0.007V CABLE JOINT
43	000235	7/0.007V CABLE JOINT
44	000236	7/0.007V CABLE JOINT
45	000237	7/0.007V CABLE JOINT
46	000238	7/0.007V CABLE JOINT
47	000239	7/0.007V CABLE JOINT
48	000240	7/0.007V CABLE JOINT
49	000241	7/0.007V CABLE JOINT
50	000242	7/0.007V CABLE JOINT
51	000243	7/0.007V CABLE JOINT
52	000244	7/0.007V CABLE JOINT
53	000245	7/0.007V CABLE JOINT
54	000246	7/0.007V CABLE JOINT
55	000247	7/0.007V CABLE JOINT
56	000248	7/0.007V CABLE JOINT
57	000249	7/0.007V CABLE JOINT
58	000250	7/0.007V CABLE JOINT
59	000251	7/0.007V CABLE JOINT
60	000252	7/0.007V CABLE JOINT
61	000253	7/0.007V CABLE JOINT
62	000254	7/0.007V CABLE JOINT
63	000255	7/0.007V CABLE JOINT
64	000256	7/0.007V CABLE JOINT
65	000257	7/0.007V CABLE JOINT
66	000258	7/0.007V CABLE JOINT
67	000259	7/0.007V CABLE JOINT
68	000260	7/0.007V CABLE JOINT
69	000261	7/0.007V CABLE JOINT
70	000262	7/0.007V CABLE JOINT
71	000263	7/0.007V CABLE JOINT
72	000264	7/0.007V CABLE JOINT
73	000265	7/0.007V CABLE JOINT
74	000266	7/0.007V CABLE JOINT
75	000267	7/0.007V CABLE JOINT
76	000268	7/0.007V CABLE JOINT
77	000269	7/0.007V CABLE JOINT
78	000270	7/0.007V CABLE JOINT
79	000271	7/0.007V CABLE JOINT
80	000272	7/0.007V CABLE JOINT
81	000273	7/0.007V CABLE JOINT
82	000274	7/0.007V CABLE JOINT
83	000275	7/0.007V CABLE JOINT
84	000276	7/0.007V CABLE JOINT
85	000277	7/0.007V CABLE JOINT
86	000278	7/0.007V CABLE JOINT
87	000279	7/0.007V CABLE JOINT
88	000280	7/0.007V CABLE JOINT
89	000281	7/0.007V CABLE JOINT
90	000282	7/0.007V CABLE JOINT
91	000283	7/0.007V CABLE JOINT
92	000284	7/0.007V CABLE JOINT
93	000285	7/0.007V CABLE JOINT
94	000286	7/0.007V CABLE JOINT
95	000287	7/0.007V CABLE JOINT
96	000288	7/0.007V CABLE JOINT
97	000289	7/0.007V CABLE JOINT
98	000290	7/0.007V CABLE JOINT
99	000291	7/0.007V CABLE JOINT
100	000292	7/0.007V CABLE JOINT

WARNING

Ausgrid's plans show the position of assets at the time of installation and may not account for subsequent changes to road alignments, fences or buildings. The plans show no more than the presence or absence of Ausgrid assets in the street. Persons working near electricity networks must exercise care and will be held responsible for any damage caused. You must excavate by hand or use vacuum excavation to establish the location of Ausgrid underground cables and associated assets. Underground Working near a cable may result in electric shock, even if no contact is made. Any work in the vicinity of any cable should only be performed using safe work methods developed in accordance with the recommendations included in WorkCover Code of Practice for Excavation and WorkCover Guide for Work Near Underground Assets, as well as recommendations of Ausgrid's Network Standard NS106. Overhead: Do not excavate near poles or towers until the stability of the foundation has been assessed by Ausgrid. Cables or earth conductors may be present close to substations, poles or towers. Workers must maintain safe approach distances and follow applicable WorkCover Code of Practice. NOTE: You must keep this plan on site during excavation works and have on site a person trained to read this plan.

MA13311

MA13312

MA13313

MA13314

MA13315

MA13316

MA13317

MA13318

MA13319

MA13320

MA13321

MA13322

MA13323

MA13324

MA13325

MA13326

MA13327

MA13328

MA13329

MA13330

MA13331

MA13332

MA13333

MA13334

MA13335

MA13336

MA13337

MA13338

MA13339

MA13340

MA13341

MA13342

MA13343

MA13344

MA13345

MA13346

MA13347

MA13348

MA13349

MA13350

MA13351

MA13352

MA13353

MA13354

MA13355

MA13356

MA13357

MA13358

MA13359

MA13360

MA13361

MA13362

MA13363

MA13364

MA13365

MA13366

MA13367

MA13368

MA13369

MA13370

MA13371

MA13372

MA13373

MA13374

MA13375

MA13376

MA13377

MA13378

MA13379

MA13380

MA13381

MA13382

MA13383

MA13384

MA13385

MA13386

MA13387

MA13388

MA13389

MA13390

MA13391

MA13392

MA13393

MA13394

MA13395

MA13396

MA13397

MA13398

MA13399

MA13400

MA13401

MA13402

MA13403

MA13404

MA13405

MA13406

MA13407

MA13408

MA13409

MA13410

MA13411

MA13412

MA13413

MA13414

MA13415

MA13416

MA13417

MA13418

MA13419

MA13420

MA13421

MA13422

MA13423

MA13424

MA13425

MA13426

MA13427

MA13428

MA13429

MA13430

MA13431

MA13432

MA13433

MA13434

MA13435

MA13436

MA13437

MA13438

MA13439

MA13440

MA13441

MA13442

MA13443

MA13444

MA13445

MA13446

MA13447

MA13448

MA13449

MA13450

MA13451

MA13452

MA13453

MA13454

MA13455

MA13456

MA13457

MA13458

MA13459

MA13460

MA13461

MA13462

MA13463

MA13464

MA13465

MA13466

MA13467

MA13468

MA13469

MA13470

MA13471

MA13472

MA13473

MA13474

MA13475

MA13476

MA13477

MA13478

MA13479

MA13480

MA13481

MA13482

MA13483

MA13484

MA13485

MA13486

MA13487

MA13488

MA13489

MA13490

MA13491

MA13492

MA13493

MA13494

MA13495

MA13496

MA13497

MA13498

MA13499

MA13500

MA13501

MA13502

MA13503

MA13504

MA13505

MA13506

MA13507

MA13508

MA13509

MA13510

MA13511

MA13512

MA13513

MA13514

MA13515

MA13516

MA13517

MA13518

MA13519

MA13520

MA13521

MA13522

MA13523

MA13524

MA13525

MA13526

MA13527

MA13528

MA13529

MA13530

MA13531

MA13532

MA13533

MA13534

MA13535

MA13536

MA13537

MA13538

MA13539

MA13540

MA13541

MA13542

MA13543

MA13544

MA13545

MA13546

MA13547

MA13548

MA13549

MA13550

MA13551

MA13552

MA13553

MA13554

MA13555

MA13556

MA13557

MA13558

MA13559

MA13560

MA13561

MA13562

MA13563

MA13564

MA13565

MA13566

MA13567

MA13568

MA13569

MA13570

MA13571

MA13572

MA13573

MA13574

MA13575

MA13576

MA13577

MA13578

MA13579

MA13580

MA13581

MA13582

MA13583

MA13584

MA13585

MA13586

MA13587

MA13588

MA13589

MA13590

MA13591

MA13592

MA13593

MA13594

MA13595

MA13596

MA13597

MA13598

MA13599

MA13600

MA13601

MA13602

MA13603

MA13604

MA13605

MA13606

MA13607

MA13608

MA13609

MA13610

MA13611

MA13612

MA13613

MA13614

MA13615

MA13616

MA13617

MA13618

MA13619

MA13620

MA13621

MA13622

MA13623

MA13624

MA13625

MA13626

MA13627

MA13628

MA13629

MA13630

MA13631

MA13632

MA13633

MA13634

MA13635

MA13636

MA13637

MA13638

MA13639

MA13640

MA13641

MA13642

MA13643

MA13644

MA13645

MA13646

MA13647

MA13648

MA13649

MA13650

MA13651

MA13652

MA13653

MA13654

MA13655

MA13656

MA13657

MA13658

MA13659

MA13660

MA13661

MA13662

MA13663

MA13664

MA13665

MA13666

MA13667

MA13668

MA13669

MA13670

MA13671

MA13672

MA13673

MA13674

MA13675

MA13676

MA13677

MA13678

MA13679

MA13680

MA13681

MA13682

MA13683

MA13684

MA13685

MA13686

MA13687

MA13688

MA13689

MA13690

MA13691

MA13692

MA13693

MA13694

MA13695

MA13696

MA13697

MA13698

MA13699

MA13700

MA13701

MA13702

MA13703

MA13704

MA13705

MA13706

MA13707

MA13708

MA13709

MA13710

MA13711

MA13712

MA13713

MA13714

MA13715

MA13716

MA13717

MA13718

MA13719

MA13720

MA13721

MA13722

MA13723

MA13724

MA13725

MA13726

MA13727

MA13728

MA13729

MA13730

MA13731

MA13732

MA13733

MA13734

MA13735

MA13736

MA13737

MA13738

MA13739

MA13740

MA13741

MA13742

MA13743

MA13744

MA13745

MA13746

MA13747

MA13748

MA13749

MA13750

MA13751

MA13752

MA13753

MA13754

MA13755

MA13756

MA13757

MA13758

MA13759

MA13760

MA13761

MA13762

MA13763

MA13764

MA13765

MA13766

MA13767

MA13768

MA13769

MA13770

MA13771

MA13772

MA13773

MA13774

MA13775

MA13776

MA13777

MA13778

MA13779

MA13780

MA13781

MA13782

MA13783

MA13784

MA13785

MA13786

MA13787

MA13788

MA13789

MA13790

MA13791

MA13792

MA13793

MA13794

MA13795

MA13796

MA13797

MA13798

MA13799

MA13800

MA13801

MA13802

MA13803

MA13804

MA13805

MA13806

MA13807

MA13808

MA13809

MA13810

MA13811

MA13812

MA13813

MA13814

MA13815

MA13816

MA13817

MA13818

MA13819

MA13820

MA13821

MA13822

MA13823

MA13824

MA13825

MA13826

MA13827

MA13828

MA13829

MA13830

MA13831

MA13832

MA13833

MA13834

MA13835

MA13836

MA13837

MA13838

MA13839

MA13840

MA13841

MA13842

MA13843

MA13844

MA13845

MA13846

MA13847

MA13848

MA13849

MA13850

MA13851

MA13852

MA13853

MA13854

MA13855

MA13856

MA13857

MA13858

MA13859

MA13860

MA13861

MA13862

MA13863

MA13864

MA13865

MA13866

MA13867

MA13868

MA13869

MA13870

MA13871

MA13872

MA13873

MA13874

MA13875

MA13876

MA13877

MA13878

MA13879

MA13880

MA13881

MA13882

MA13883

MA13884

MA13885

MA13886

MA13887

MA13888

MA13889

MA13890

MA13891

MA13892

MA13893

MA13894

MA13895

MA13896

MA13897

MA13898

MA13899

MA13900

MA13901

MA13902

MA13903

MA13904

MA13905

MA13906

MA13907

MA13908

MA13909

MA13910

MA13911

MA13912

MA13913

MA13914

MA13915

MA13916

MA13917

MA13918

MA13919

MA13920

MA13921

MA13922

MA13923

MA13924

MA13925

MA13926

MA13927

MA13928

MA13929

MA13930

MA13931

MA13932

MA13933

MA13934

MA13935

MA13936

MA13937

MA13938

MA13939

MA13940

MA13941

MA13942

MA13943

MA13944

MA13945

MA13946

MA13947

MA13948

MA13949

MA13950

MA13951

MA13952

MA13953

MA13954

MA13955

MA13956

MA13957

MA13958

MA13959

MA13960

MA13961

MA13962

MA13963

MA13964

MA13965

MA13966

MA13967

MA13968

MA13969

MA13970

MA13971

MA13972

MA13973

MA13974

MA13975

MA13976

MA13977

MA13978

MA13979

MA13980

MA13981

MA13982

MA13983

MA13984

MA13985

MA13986

MA13987

MA13988

MA13989

MA13990

MA13991

MA13992

MA13993

MA13994

MA13995

MA13996

MA13997

MA13998

MA13999

MA14000

MA14001

MA14002

MA14003

MA14004

MA14005

MA14006

MA14007

MA14008

MA14009

MA14010

MA14011

MA14012

MA14013

MA14014

MA14015

MA14016

MA14017

MA14018

MA14019

MA14020

MA14021

MA14022

MA14023

MA14024

MA14025

MA14026

MA14027

MA14028

MA14029

MA14030

MA14031

MA14032

MA14033

MA14034

MA14035

MA14036

MA14037

MA14038

MA14039

MA14040

MA14041

MA14042

MA14043

MA14044

MA14045

MA14046

MA14047

MA14048

MA14049

MA14050

MA14051

MA14052

MA14053

MA14054

MA14055

MA14056

MA14057

MA14058

MA14059

MA14060

MA14061

MA14062

MA14063

MA14064

MA14065

MA14066

MA14067

MA14068

MA14069

MA14070

MA14071

MA14072

MA14073


MA14074

MA14075


MA14076

MA14077

MA140




MAROUBRA IC



THIS MAP UPDATED ON 10/02/2015
THIS PLAN IS DIAGRAMATIC ONLY. DISTANCES
SCALED FROM THIS PLAN MAY NOT BE ACCURATE.
DATE ALTERED:..... BY:.....

K3B	MAIA	MAIB
K3D	MAIC	MAID
K6B	MA4A	MA4B

ADJOINING MAPS



NETWORK AREA



MUNICIPALITY AREA

Jemena

KEY

MAX ALLOWABLE OPERATING PRESSURE

T	TRUNK PIPELINE	7000 kPa
P	PRIMARY MAIN	3500 kPa
S	SECONDARY MAIN	1050 kPa
400	NETWORK MAIN	400 kPa
300	NETWORK MAIN	300 kPa
210	NETWORK MAIN	210 kPa
100	NETWORK MAIN	100 kPa
30	NETWORK MAIN	30 kPa
7	NETWORK MAIN	7 kPa
2	NETWORK MAIN	2 kPa
PR 2-2-3	STEEL MAIN PROJECT NUMBER	
P	PRESSURE MONITORING STATION	
V	VALVE	
S	SYSTEM PRESSURE REGULATOR	
S	SIPHON	
123	NETWORK NODE	
123S	NETWORK VALVE NODE	
123	VALVE NUMBER	
6NB	6 INCH CAST IRON MAIN	
150MM	150MM STEEL MAIN	
110MM PE/NY	110MM POLYETHYLENE/NYLON MAIN	
6NB 50MM NY	50MM NYLON INSERTED INTO 6NB MAIN CAST IRON MAIN	
1.2MBL	DISTANCE IN METRES OF MAIN FROM BOUNDARY LINE	
1957	YEAR LAID	
---	MUNICIPALITY BOUNDARY	
---	NETWORK BOUNDARY	
123	HOUSE NUMBER	

MAROUBRA IC

Cable Plan



For all Telstra DBYD plan enquiries -
email - Telstra.Plans@team.telstra.com
For urgent onsite contact only - ph 1800 653 935 (bus hrs)

TELSTRA CORPORATION LIMITED A.C.N. 051 775 556

Generated On 19/03/2015 16:48:37

Sequence Number: 44505633

CAUTION: Fibre optic and/ or major network present in plot area. Please read the Duty of Care and contact Telstra Plan Services should you require any assistance.

The above plan must be viewed in conjunction with the Mains Cable Plan on the following page



WARNING - Due to the nature of Telstra underground plant and the age of some cables and records, it is impossible to ascertain the precise location of all Telstra plant from Telstra's plans. The accuracy and/or completeness of the information supplied can not be guaranteed as property boundaries, depths and other natural landscape features may change over time, and accordingly the plans are indicative only. Telstra does not warrant or hold out that its plans are accurate and accepts no responsibility for any inaccuracy shown on the plans.

It is your responsibility to locate Telstra's underground plant by careful hand pot-holing prior to any excavation in the vicinity and to exercise due care during that excavation.

Please read and understand the information supplied in the duty of care statement attached with the Telstra plans. TELSTRA WILL SEEK COMPENSATION FOR LOSS CAUSED BY DAMAGE TO ITS PLANT.

Telstra plans and information supplied are valid for 60 days from the date of issue. If this timeframe has elapsed, please reapply for plans.

Mains Cable Plan



For all Telstra DBYD plan enquiries -
email - Telstra.Plans@team.telstra.com
For urgent onsite contact only - ph 1800 653 935 (bus hrs)

TELSTRA CORPORATION LIMITED A.C.N. 051 775 556

Generated On 19/03/2015 16:49:03

Sequence Number: 44505633

CAUTION: Fibre optic and/ or major network present in plot area. Please read the Duty of Care and contact Telstra Plan Services should you require any assistance.

WARNING - Due to the nature of Telstra underground plant and the age of some cables and records, it is impossible to ascertain the precise location of all Telstra plant from Telstra's plans. The accuracy and/or completeness of the information supplied can not be guaranteed as property boundaries, depths and other natural landscape features may change over time, and accordingly the plans are indicative only. Telstra does not warrant or hold out that its plans are accurate and accepts no responsibility for any inaccuracy shown on the plans.

It is your responsibility to locate Telstra's underground plant by careful hand pot-holing prior to any excavation in the vicinity and to exercise due care during that excavation.

Please read and understand the information supplied in the duty of care statement attached with the Telstra plans. TELSTRA WILL SEEK COMPENSATION FOR LOSS CAUSED BY DAMAGE TO ITS PLANT.

Telstra plans and information supplied are valid for 60 days from the date of issue. If this timeframe has elapsed, please reapply for plans.



WARNING: This document is confidential and may also be privileged. Confidentiality nor privilege is not waived or destroyed by virtue of it being transmitted to an incorrect addressee. Unauthorised use of the contents is therefore strictly prohibited. Any information contained in this document that has been extracted from our records is believed to be accurate, but no responsibility is assumed for any error or omission. Optus Plans and information supplied are valid for 30 days from the date of issue. If this timeline has elapsed please raise a new enquiry.

Sequence Number: 44505634

Date Generated: 19/03/2015



For all Optus DBYD plan enquiries –
Email: Fibre.Locations@optus.net.au
For urgent onsite assistance contact 1800 505 777
Optus Limited ACN 052 833 208



Appendix D

MUSIC MODELLING INFORMATION



	Sources	Residual Load	% Reduction
Flow (ML/yr)	32.6	31.8	2.5
Total Suspended Solids (kg/yr)	6660	673	89.9
Total Phosphorus (kg/yr)	13.5	5.37	60.2
Total Nitrogen (kg/yr)	94	46.6	50.5
Gross Pollutants (kg/yr)	792	0	100

