



- FLOOD HAZARD VULNERABILITY CLASSIFICATION**
- H1 Generally safe for vehicles, people and buildings.
 - H2 Unsafe for small vehicles.
 - H3 Unsafe for vehicles, children and the elderly.
 - H4 Unsafe for vehicles and people.
 - H5 Unsafe for vehicles and people. All building types vulnerable to structural damage. Some less robust building types vulnerable to failure.
 - H6 Unsafe for vehicles and people. All building types considered vulnerable to failure.

N 100 0 100 200 300 m
Scale: 1:10,000

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.
Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

- LEGEND**
- Two-Dimensional Model Boundary
 - Modelled Stormwater Drainage System

**ARIAH PARK AND SPRINGDALE
FLOODPLAIN RISK MANAGEMENT STUDY AND PLAN**

Figure 2.23
(Sheet 2 of 2)

FLOOD HAZARD VULNERABILITY CLASSIFICATION AT ARIA PARK
1% AEP