CONDITIONS OF DEVELOPMENT CONSENT

DA No:DA-38/2011Property:47 Hill Road, WENTWORTH POINTDescription:Construction of 4 to 8 storey residential flat building consisting of 251
apartments above 2 levels of car parking with associated landscaping,
road and drainage works

1. The following 'deferred commencement' conditions which must be satisfied before consent can operate:

Garbage Collection

- Amended architectural plans incorporating the following items shall be submitted to Council for assessment:
 - i. Garbage collection shall be carried out within the building on site.
 - i. All required swept paths and parking bay dimension shall be shown on the plan.
 - ii. Vehicles shall enter and leave the site in forward direction.
 - iii. The proposed column positions shall be clear from turning and parking area.
 - iv. All design shall incorporate the maximum size vehicle intended to be used on the premises.

2. **Ground floor/podium level apartments**

- Amended architectural and landscaping plans incorporating the following items shall be submitted to Council for assessment:
 - i. All ground floor or podium level units are to achieve a minimum of 25 m² of private courtyard space with minimum dimension 4 metres.
 - i. 80% of ground floor /podium level apartments are to have direct pedestrian access to their respective street frontage or podium level.

3. Basement Storage

• Amended architectural plans and details shall be submitted to Council for assessment that demonstrate sufficient storage is provided for all units within the development in the form of a combined total of internal and basement storage which meets or exceeds the SEPP 65 and Homebush Bay West DCP requirements for unit bedroom number.

4. Approved Plans – Deferred Commencement

The development is to be carried out generally in accordance with the following plans as numbered below, except as modified by the deferred commencement condition of approval:

A002 Site PlanScott CarverB5 August 2011A101 Level 1 - Floor PlanScott CarverB5 August 2011A102 Level 2 - Floor PlanScott CarverB5 August 2011A103 Level 3 - Floor PlanScott CarverB5 August 2011A104 Level 4 - Floor PlanScott CarverB5 August 2011A105 Level 5 - Floor PlanScott CarverB5 August 2011A106 Level 6 - Floor PlanScott CarverB5 August 2011A107 Level 7 - Floor PlanScott CarverB5 August 2011A108 Level 8 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A110 Level 10 - Floor PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A302 Elevations - Sheet 2Scott CarverB5 August 2011A304 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 August 2011Reference20100150Scott CarverS August 2011Lo01 Landscape PlanScott CarverS August 2011A14Scott CarverS August 2011
A102 Level 2 - Floor PlanScott CarverB5 August 2011A103 Level 3 - Floor PlanScott CarverB5 August 2011A104 Level 4 - Floor PlanScott CarverB5 August 2011A105 Level 5 - Floor PlanScott CarverB5 August 2011A106 Level 6 - Floor PlanScott CarverB5 August 2011A107 Level 7 - Floor PlanScott CarverB5 August 2011A108 Level 8 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A110 Level 10 - Floor PlanScott CarverB5 August 2011A111 Roof PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 august 2011Reference20100150Scott CarverB5 august 2011Reference20100150Scott CarverB5 August 2011Landscape DA Final sheetsScott CarverA7 February 2011
A103 Level 3 - Floor PlanScott CarverB5 August 2011A104 Level 4 - Floor PlanScott CarverB5 August 2011A105 Level 5 - Floor PlanScott CarverB5 August 2011A106 Level 6 - Floor PlanScott CarverB5 August 2011A107 Level 7 - Floor PlanScott CarverB5 August 2011A108 Level 8 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A110 Level 10 - Floor PlanScott CarverB5 August 2011A111 Roof PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A303 Elevations - Sheet 2Scott CarverB5 August 2011A304 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 August 2011A304 Elevations - Sheet 5Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 August 2011A304 Elevations - Sheet 5Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 August 2011LD001 Landscape PlanScott CarverA7 February 2011LD001 Landscape DA Final sheetsScott CarverS August 2011
A104 Level 4 - Floor PlanScott CarverB5 August 2011A105 Level 5 - Floor PlanScott CarverB5 August 2011A106 Level 6 - Floor PlanScott CarverB5 August 2011A107 Level 7 - Floor PlanScott CarverB5 August 2011A108 Level 8 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A110 Level 10 - Floor PlanScott CarverB5 August 2011A111 Roof PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A302 Elevations - Sheet 2Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott Carver5 August 2011Landscape DA Final sheetsScott Carver5 August 2011
A105 Level 5 - Floor PlanScott CarverB5 August 2011A106 Level 6 - Floor PlanScott CarverB5 August 2011A107 Level 7 - Floor PlanScott CarverB5 August 2011A108 Level 8 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A110 Level 10 - Floor PlanScott CarverB5 August 2011A111 Roof PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A302 Elevations - Sheet 2Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 August 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott CarverB5 August 2011Landscape DA Final sheetsScott CarverB5 August 2011
A105 Level 5 - Floor PlanScott CarverB5 August 2011A106 Level 6 - Floor PlanScott CarverB5 August 2011A107 Level 7 - Floor PlanScott CarverB5 August 2011A108 Level 8 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A110 Level 10 - Floor PlanScott CarverB5 August 2011A111 Roof PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A302 Elevations - Sheet 2Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverB5 August 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott CarverB5 August 2011Landscape DA Final sheetsScott CarverB5 August 2011
A106 Level 6 - Floor PlanScott CarverB5 August 2011A107 Level 7 - Floor PlanScott CarverB5 August 2011A108 Level 8 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A110 Level 10 - Floor PlanScott CarverB5 August 2011A111 Roof PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A302 Elevations - Sheet 2Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott CarverB5 August 2011
A108 Level 8 - Floor PlanScott CarverB5 August 2011A109 Level 9 - Floor PlanScott CarverB5 August 2011A110 Level 10 - Floor PlanScott CarverB5 August 2011A111 Roof PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A302 Elevations - Sheet 2Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott CarverB5 August 2011
A109 Level 9 - Floor PlanScott CarverB5 August 2011A110 Level 10 - Floor PlanScott CarverB5 August 2011A111 Roof PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A302 Elevations - Sheet 2Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott Carver5 August 2011Landscape DA Final sheetsScott CarverS august 2011
A110 Level 10 - Floor PlanScott CarverB5 August 2011A111 Roof PlanScott CarverB5 August 2011A301 Elevations - Sheet 1Scott CarverB5 August 2011A302 Elevations - Sheet 2Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott CarverB5 August 2011
A111 Roof PlanScott CarverB5 August 2011A301 Elevations – Sheet 1Scott CarverB5 August 2011A302 Elevations – Sheet 2Scott CarverB5 August 2011A303 Elevations – Sheet 3Scott CarverB5 August 2011A304 Elevations – Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott CarverB5 August 2011
A301 Elevations - Sheet 1Scott CarverB5 August 2011A302 Elevations - Sheet 2Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott CarverB5 august 2011Landscape DA Final sheetsScott CarverScott CarverScott 2011
A302 Elevations - Sheet 2Scott CarverB5 August 2011A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott Carver5 August 2011Landscape DA Final sheetsScott Carver5 August 2011
A303 Elevations - Sheet 3Scott CarverB5 August 2011A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott Carver5 August 2011Landscape DA Final sheetsScott Carver5 August 2011
A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott Carver5 August 2011Landscape DA Final sheetsScott Carver5 August 2011
A304 Elevations - Sheet 4Scott CarverA7 February 2011LD001 Landscape PlanScott CarverB5 august 2011Reference20100150Scott Carver5 August 2011Landscape DA Final sheetsScott Carver5 August 2011
Reference20100150Scott Carver5 August 2011Landscape DA Final sheets5 August 2011
Reference20100150Scott Carver5 August 2011Landscape DA Final sheets5
Landscape DA Final sheets
1-14
3550-CC-001 Site and Lucas Consulting B 25 July 2011
Concept Drainage Plan Engineers
Sheet 1 of 4
3550-CC-002 Sediment Lucas Consulting B 25 July 2011
and Erosion Control Plan Engineers
Sheet 2 of 4
3550-CC-003 Park Street Lucas Consulting B 25 July 2011
North Long Section and Engineers
Typical Section Sheet 3 of
3550-CC-004 Stormwater Lucas Consulting B 25 July 2011
Drainage Long Section Engineers
Sheet 4 of 4
BASIX Certificate number: Ecospecifier P/L 07 February
352182M_022011BASIX Certificate number:Ecospecifier P/L07Februari
BASIX Certificate number: Ecospecifier P/L 07 February 352131M_02 2011
20101140.1/16212A/RO/YK Acoustic Logic 16 Decembe
– Wentworth Point Marina – Consultancy Pty 2010
Block D DA Noise Ltd
Assessment
0129160RP01 Final Block Environmental April 2011
D Consolidated Report, Resources
Burroway Road, Homebush Management
Bay NSW Final
Site and Waste Lucas Consulting Revision 1 13 December
Management Plan Engineers 2010

The plans will not be "stamped" by Council until the modifications required by the deferred commencement condition have been incorporated into revised plans.

(Note:- modifications to the approved plans will require the lodgement and consideration by Council of a modification pursuant to Section 96 of the Environmental Planning and Assessment Act).

<u>Reason</u>:- to confirm and clarify the terms of Council's approval.

5. <u>Time period of consent</u>

This consent shall lapse five (5) years from the date of determination unless the approved building, engineering or construction work has been physically commenced in accordance with this consent.

Development consent for the use of land does not lapse if the approved use of any land, building or work is actually commenced prior to the date on which the consent would otherwise lapse.

<u>*Reason*</u>:- to satisfy the requirements of Section 95 of the Environmental Planning and Assessment Act.

6. Auburn Development Contributions Plan 2007

Development Contributions are payable in accordance with Auburn Council Council's Section 94 Development Contribution Plan 2007, which has been prepared under Section 94 of the Environmental Planning and Assessment Act 1979, as amended.

The amounts payable will be adjusted in accordance with the section titled Review of Contribution rates and are generally indexed on a quarterly basis by the Consumer Price Index CPI (all Groups Sydney) unless otherwise stated in the plan.

Contributions will be adjusted at the payment date in accordance with the plan and payment is to be made prior to the issue of a Construction Certificate.

Council's Development Contribution Plan 2007 is available for inspection at Council's Customer Services Centre, Civic Place, 1 Susan Street, Auburn or on line at www.auburn.nsw.gov.au.

<u>*Reason*</u>: To ensure that the development complies with the Auburn DCP 2007: Section 94 Development Contributions.

7. <u>Auburn DCP 2007 – Homebush Bay West</u>

A sum of **\$829,460.83** is to be paid to Council for the purpose of traffic management, community facilities, provision of public open space in the Homebush Bay West area and plan administration.

The above sum is broken down to the following items:

Item	Amount
Traffic Management	\$160,853.61
Open Space – District Acquisition and	\$394,583.48
Embellishment	

Community facilities	\$217,428.56
Plan administration	\$56,595.18
TOTAL	\$829,460.83

<u>*Reason*</u>:- to provide traffic management, community facilities, provision of public open space in the Homebush Bay West area and plan administration.

8. **Provision of Adaptable Units**

The proposed development shall provide a minimum of 20% of the total units as adaptable in accordance with the relevant Australian Standards and DCP requirements, with the exception that only 10% of the car parking spaces must comply with the relevant standards for adaptable units. Details demonstrating compliance shall be submitted to the PCA prior to the release of the Construction Certificate.

<u>*Reason*</u>:- to provide adaptable units in accordance with the DCP requirements.

9. **Public Domain**

The new areas of public domain are to be in accordance with the relevant Public Domain Manual for Homebush Bay West (Wentworth Point).

Details demonstrating compliance are to be submitted to the Principal Certifying Authority, prior to the issue of a construction certificate.

<u>Reason</u>:- to ensure compliance with the relevant public domain plans.

10. Submission of Construction Certificate

Construction works are not to commence until such time that a construction certificate for the proposed works has been issued by Council or an Accredited Certifier.

NOTES:

Where an Accredited Certifier issues a construction certificate, a copy of the following documents must be forwarded to Council within 7 days of issue, together with payment of the Council's adopted registration fee: determination; application to which it relates; construction certificate issued; plans and specifications; any fire safety schedule; and any other documents lodged with the certificate.

Any modification involving building works to the approved development made under Section 96 of the Environmental Planning and Assessment Act 1979 requires the submission of an amended construction certificate.

<u>Reason</u>:- to comply with the requirements of Section 81A of the Environmental Planning and Assessment Act and clause 142 of the Environmental Planning and Assessment Regulation 2000.

11. No alteration without prior Council approval

The completed building is not to be altered externally in character or colour without the prior consent of Council.

<u>*Reason*</u>:- to ensure the external appearance of the development is not obtrusive or offensive and does not degrade the visual quality of the surrounding area.

12. <u>Appointment of Principal Certifying Authority/Notice of Commencement of</u> <u>Work</u>

Site works are not to commence until:-

- a) a construction certificate for the building work has been issued by the consent authority, and
- b) the person having the benefit of the development consent has:
 - i) appointed a principal certifying authority for the building work, and
 - ii) notified the principal certifying authority that the person will carry out the building work as an owner-builder, if that is the case, and
- b1) the principal certifying authority has, no later than 2 days before the building work commences:
 - i) notified the consent authority and the council (if the council is not the consent authority) of his or her appointment, and
 - ii) notified the person having the benefit of the development consent of any critical stage inspections and other inspections that are to be carried out in respect of the building work, and
- b2) the person having the benefit of the development consent, if not carrying out the work as an owner-builder, has:
 - i) appointed a principal contractor for the building work who must be the holder of a contractor licence if any residential building work is involved, and
 - ii) notified the principal certifying authority of any such appointment, and
 - iii) unless that person is the principal contractor, notified the principal contractor of any critical stage inspections and other inspections that are to be carried out in respect of the building work, and
- c) the person having the benefit of the development consent has given at least 2 days' notice to the council of the person's intention to commence the erection of the building.

<u>Reason</u>:- to comply with the requirements of Section 81A of the Environmental Planning and Assessment Act

13. Principal Certifying Authority

- 1) The person having the benefit of a development consent or complying development certificate for development involving building work or subdivision work may appoint the consent authority, the council or an accredited certifier as the principal certifying authority for the development.
- 1A) Despite subsection (1), such an appointment may not be made by any contractor or other person who will carry out the building work or subdivision work unless the contractor or other person is the owner of the land on which the work is to be carried out.

- 2) Despite subsection (1), an accredited certifier must not be appointed as the principal certifying authority for development involving subdivision work unless the subdivision to which the work relates is of a kind identified by an environmental planning instrument as one in respect of which an accredited certifier may be a certifying authority.
- 3) A principal certifying authority for building work or subdivision work to be carried out on a site is required to be satisfied:
 - a) that a construction certificate or complying development certificate has been issued for such of the building work or subdivision work as requires development consent and over which the principal certifying authority has control, before the work commences on the site, and
 - b) that the principal contractor for the work is the holder of the appropriate licence and is covered by the appropriate insurance, in each case if required by the *Home Building Act 1989*, before any residential building work over which the principal certifying authority has control commences on the site, unless the work is to be carried out by an owner-builder, and
 - c) that the owner-builder is the holder of any owner-builder permit required under the *Home Building Act 1989*, before an owner-builder commences on the site any residential building work over which the principal certifying authority has control, and
 - d) that building work or subdivision work on the site has been inspected by the principal certifying authority or another certifying authority on such occasions (if any) as are prescribed by the regulations and on such other occasions as may be required by the principal certifying authority, before the principal certifying authority issues an occupation certificate or subdivision certificate for the building or work, and
 - e) that any preconditions required by a development consent or complying development certificate to be met for the work before the issue of an occupation certificate or subdivision certificate have been met, before the principal certifying authority issues the occupation certificate or subdivision certificate.
- 4) A principal certifying authority must also comply with such other requirements of a like or different nature as may be imposed on principal certifying authorities by the regulations.

Note. Section 81A prohibits the commencement of building work or subdivision work unless the consent authority has been notified of the appointment of a principal certifying authority for the work. Section 109D (2) prohibits the issue of an occupation certificate authorising the occupation and use of a new building except by the principal certifying authority appointed for the erection of the building. Section 109D (3) prohibits the issue of a subdivision certificate for a subdivision involving subdivision work except by the principal certifying authority appointed for the result for the carrying out of the subdivision.

<u>*Reason*</u>:- to comply with the requirements of Section 109E of the Environmental Planning and Assessment Act.

14. Provision of Street Numbers

A street number is to be displayed in a prominent position at the entrance to the premises. Numbers are to be of a colour contrasting with the wall to which they are affixed.

Reason:- to clearly identify the street number of the property.

15. Compliance with the Building Code of Australia

All building work must be carried out in accordance with the requirements of the Building Code of Australia.

<u>*Reason*</u>:- to ensure compliance with the requirements of the Building Code of Australia and to comply with Clause 98 of the Environmental Planning and Assessment Regulation 2000.

16. Insurance requirements under the Home Building Act 1989

A contract of insurance for residential building work must be in force before any building works commence, where the works are being undertaken by a builder and tradesperson and the works have a market value of greater than \$12,000 (or as varied from time to time by the Home Building Act 1989).

If the work is to be carried out as an owner-builder, an Owner-builder Permit must be obtained if the market value of the labour AND materials needed to complete the work is greater than \$5,000 (or as varied from time to time by the Home Building Act 1989).

NOTE: Evidence of the contract of insurance or owner builder permit, if required, must be submitted with the application for construction certificate. The construction certificate will not be released by Council unless this evidence is provided.

<u>*Reason:*</u>- to comply with Clause 98 of the Environmental Planning and Assessment Regulation 2000.

17. Disabled Access & Facilities

Access and facilities for people with disabilities must be provided in accordance with the relevant requirements of the Building Code of Australia (for all new building work) and in addition, with the relevant requirements of the 'Disability (Access to Premises – Building) Standards 2010' (including for existing buildings, whether or not any works are proposed). Details of the proposed access, facilities and car parking for people with disabilities are to be included in the plans/specifications for the **construction certificate**.

<u>Reason</u>: to ensure compliance with the requirements of the Building Code of Australia

18. Commonwealth Disability Discrimination Act

The Commonwealth Disability Discrimination Act 1992 commenced the 'Disability (Access for Premises – Buildings) Standards 2010' on 1 May 2011 and now applies to all new buildings and affected parts of existing buildings. Submission and/or approval of this application does not imply or confer compliance with either the Act or the new Access Standard. Applicants should satisfy themselves and make their own inquiries to the Human Rights and Equal Opportunity Commission.

<u>Reason:</u> to provide advice on the requirements of the Commonwealth Disability Discrimination Act 1992

19. Replacement of Principal Certifying Authorities

Unless the relevant authority so approves in writing, a person may not be appointed to replace another person as the principal certifying authority for development.

A principal certifying authority appointed to replace another principal certifying authority must ensure that notice of the appointment and of the approval of that appointment is given to the consent authority (and, if the consent authority is not the council, to the council) within 2 days of the appointment.

<u>*Reason*</u>:- to comply with the requirements of Section 109EA of the Environmental Planning and Assessment Act and clause 162 of the Environmental Planning and Assessment Regulation.

20. Notice to Allow Inspections

To allow a principal certifying authority or another certifying authority time to carry out critical stage inspections or any other inspections required by the principal certifying authority, the principal contractor for a building site, or the owner-builder, must notify the principal certifying authority at least 48 hours before building work is commenced at the site if a critical stage inspection is required before the commencement of the work.

<u>*Reason*</u>:- to comply with the requirements of Clause 163 of the Environmental Planning and Assessment Regulation.

21. Erection of Signs

A rigid and durable sign must be erected in a prominent position on any site on which building work, subdivision work or demolition work is being carried out:-

- a) showing the name, address and telephone number of the principal certifying authority for the work, and
- b) showing the name of the principal contractor (if any) for any building work and a telephone number on which that person may be contacted outside working hours, and
- c) stating that unauthorised entry to the work site is prohibited.

Any such sign is to be maintained while the building work, subdivision work or demolition work is being carried out, but must be removed when the work has been completed.

Note: Principal certifying authorities and principal contractors must also ensure that signs required by this clause are erected and maintained (see clause 227A which currently imposes a maximum penalty of \$1,100.

<u>Reason</u>:- to comply with the requirements of Clause 98A and 136B of the Environmental Planning and Assessment Regulations.

22. BASIX Requirements

Under Clause 97A(3) of the Environmental Planning & Assessment Regulation 2000, it is a condition of this development consent that all the commitments listed in each relevant BASIX Certificate for the development are fulfilled. In this condition:-

a) Relevant BASIX Certification means:-

- i) A BASIX Certificate that was applicable to the development when this development consent was granted (or, if the development consent is modified under Section 96 of the Act, a BASIX Certificate that is applicable to the development when this development consent is modified) or;
- ii) If a replacement BASIX Certificate accompanies any subsequent application for a construction certificate, the replacement BASIX Certificate; and
- b) BASIX Certificate has the meaning given to that term in the Environmental Planning & Assessment Regulation 2000.

<u>Reason</u>:- to ensure compliance with the commitments of the approved BASIX Certificate.

23. Construction/Demolition Hours

Site works, building works and demolition works, including the delivery of materials or equipment to and from the property are to be carried out between the hours of 7.00 am and 6.00 p.m. only from Mondays to Fridays and between 8.00 am and 4.00 p.m. only on Saturdays. No construction works or deliveries for the construction are to take place on Sundays or public holidays.

Prior to commencement of any demolition or construction work the applicant is to erect signs on the site, which are clearly visible from the footpaths adjoining the site boundaries, which state the permitted construction/demolition hours. These signs must also state "Any instances of site works, building works, demolition works or deliveries outside the permitted hours can be reported to Auburn Council on 9735-1222 during office hours or 0417-287-113 outside office hours".

<u>*Reason*</u>:- to reduce nuisance to the surrounding properties during the construction period.

24. Infrastructure Fee

The infrastructure inspection fee in accordance with Councils Fees and Charges Schedule shall be paid prior to the issue of the Construction Certificate.

<u>*Reason*</u>: to contribute to the cost of inspection and identification of any damage to Council's infrastructure as a result of the development.

25. <u>Maintain plans on-site</u>

A copy of the construction certificate, the approved plans & specifications and development consent conditions must be kept on the site at all times and be available to the Council officers upon request.

<u>Reason</u>:- to ensure a record of the approved plans are readily available.

26. **PCA – Inspection of Works – General & Site Management**

The building works are to be inspected by the principal certifying authority (or other

suitably qualified person on behalf of the applicant if permitted by the PCA) to monitor compliance with Council's approval and the relevant standards of construction.

Documentary evidence of compliance with Council's approval and relevant standards of construction is to be maintained by the principal certifying authority.

Upon inspection of each stage of construction, the principal certifying authority (or other suitably qualified person on behalf of the applicant) is also required to ensure that adequate provisions are made for the following measures (*as applicable*), to ensure compliance with the terms of Council's approval:

- Sediment control measures
- Provision of perimeter fences or hoardings for public safety and restricted access to building sites.
- Maintenance of the public place free from unauthorised materials, waste containers or other obstructions.

<u>*Reason*</u>:- to ensure the development is adequately monitored during the construction phase.

27. <u>Items not to be placed on roadway</u>

The following items must not be placed on the footpath, roadway or nature strip at any time:-

- a) Building materials, sand, waste materials or construction equipment;
- b) Bulk bins/waste skips/containers; or
- c) Other items that may cause a hazard to pedestrians.

<u>*Reason*</u>:- to ensure the public is not inconvenienced, placed in danger and to prevent harm to the environment occurring.

28. Sign Concerning Unauthorized Entry To The Site

A sign must be erected in a prominent position stating that unauthorised entry to the site is not permitted. The sign must also name the builder or other person responsible for the site and a telephone number at which the builder or other person can be contacted outside working hours. Where Council is not the Principal Certifying Authority, the sign shall also display the name and contact details of the nominated Principal Certifying Authority. The sign is to be removed when the building works have been completed.

<u>*Reason*</u>:- to restrict public access to the site and to provide suitable contact details in a clear and conspicuous position.

29. <u>Toilet accommodation for people working at the site</u>

Suitable toilet accommodation is to be provided at the work site at all times. If temporary toilet accommodation is proposed, it must:-

- Have a hinged door capable of being fastened from both inside and outside,
- Be constructed of weatherproof material,
- Have a rigid and impervious floor; and
- Have a receptacle for, and supply of, deodorising fluid.

<u>*Reason*</u>:- to ensure suitable toilet accommodation is provided for workers.

30. Excavated and Filled Areas

All excavated and filled areas shall be battered to a slope not steeper than two (2) horizontal to one (1) vertical and the fill area shall continue a minimum of one metre past the edge of the house, or similarly be retained in accordance with a retaining wall detail approved by Council. In the event that the retaining wall exceeds 600 mm when measured vertically from the base of the cut, the wall shall be designed by a practicing Structural Engineer, the details submitted to Council, and approved prior to work commencing.

<u>*Reason*</u>:- to adequately retain excavated and filled areas and prevent soil movement, which may be detrimental to the subject or adjoining premises.

31. Fencing of Construction Sites – Rental details to be provided to the PCA

Public access to the site and building works, materials and equipment on the site is to be restricted, when work is not in progress or the site is unoccupied.

A temporary hoarding or fence is to be provided to protect the public, located to the perimeter of the site (unless the site is separated from the adjoining land by an existing structurally adequate fence, having a minimum height of 1.5 metres). Hoardings or fences are to have a minimum height of 1.8 metres and be constructed of solid plywood sheeting (painted white) or of cyclone wire fencing with geotextile fabric attached to the inside of the fence, to provide dust control.

Hoardings or fences are to be structurally adequate and be constructed in a good and workmanlike manner and the use of poor quality materials or steel reinforcement mesh as fencing is not permissible.

The public safety provisions and temporary fences must be in place prior to the commencement of any demolition, excavation or building works and be maintained throughout construction.

Note:

Should ANY part of the fence or hoarding encroach beyond the boundaries of the site, it will be necessary to:-

- Make payment to Council for the rental of the road reserve area in accordance with Council's adopted charges (per metre per month – minimum 3 months) BEFORE the fence/hoarding is erected.
- Supply evidence that the road reserve rental fee has been paid to the PCA and to any authorised Council officer.
- Comply with Council's specifications for the erection of Class A Hoardings.

<u>*Reason*</u>:- to provide protection to public places and to prevent unauthorised access to the site.

32. Sedimentation Control

Prior to the commencement of site works, the following measures are to be implemented on the site to assist with sedimentation control during the construction phase of the project:-

- a) A dish shaped diversion drain or similar structure will be constructed above the proposed building works to divert run-off to a stable discharge area such as dense ground cover. This diversion drain is to be lined with turf or otherwise stabilised.
- b) A sediment-trapping fence using a geotechnical fabric specifically designed for such purpose and installed to manufacturer's specifications is to be placed below the construction area.
- c) Vegetation and/or existing building structures will be cleared from the construction site only, other areas to remain undisturbed.
- d) Restricting vehicle access to one designated point and having these driveways adequately covered at all times with blue metal or the like.
- e) A vehicle wheel wash, cattle grid, wheel shaker or other appropriate device, shall be installed prior to commencement of any site works or activities, to prevent mud and dirt leaving the site and being deposited on the street.
- f) Building operations such as brick cutting, washing tools or brushes and mixing mortar are not permitted on public roadways or footways or in any other locations which could lead to the discharge of materials into the stormwater drainage system.
- g) Stockpiles of topsoil, sand, aggregate, soil or other material shall not be located on any drainage line or easement, natural watercourse, footpath or roadway and shall be protected with adequate sediment controls.
- h) The installation of gutters, downpipes, and the connection of downpipes to the stormwater disposal system prior to the fixing of the roof cladding.

Such measures are to be maintained at all times to the satisfaction of Council and the PCA. Failure to do so may result in the issue of penalty infringement notices.

<u>*Reason*</u>:- to minimise soil erosion and control sediment leaving the site during construction and to prevent water pollution from occurring.

33. Sediment Control

Temporary measures shall be provided and regularly maintained during demolition, excavation and construction to prevent sediment and polluted waters discharging from the site. Plans showing such measures in accordance with the NSW Department of Housing, Managing Urban Stormwater, Soils and Construction Manual dated March 2004 shall be submitted to and approved by the Principal Certifying Authority *prior to the issue of a Construction Certificate*.

<u>*Reason*</u>:- to ensure sediment and erosion controls are maintained during the construction process to prevent water pollution from occurring.

34. Dust Suppression

Dust suppression measures are to be employed at all times during all site works.

<u>*Reason*</u>:- to reduce dust pollution to the surrounding area.

35. Display of Warning Sign for Soil and Water Management

Throughout the construction/remediation/demolition period, a warning sign for soil and water management must be displayed on the most prominent point of the building

site, visible to both the street and site works.

<u>*Reason*</u>:- to ensure all building workers are aware of the need to maintain the sediment and erosion control devices.

36. Engineering Design – Basement Excavation

The following engineering details or design documentation (where appropriate) shall be submitted to the Principal Certifying Authority (Council or accredited certifier) **prior** to the issuing of a construction certificate:-

- a) Documentary evidence prepared by a suitably qualified *professional geotechnical engineer* shall be submitted to the certifying authority, that confirms the suitability and stability of the site for the proposed excavation and building as well as certifying the suitably and adequacy of the proposed design and construction of the building for the site.
- b) A report shall be prepared by a *professional engineer* and submitted to the certifying authority prior to the issuing of a construction certificate, detailing the proposed methods of excavation, shoring or pile construction, including details of vibration emissions and detailing any possible damage which may occur to adjoining or nearby premises that may be caused by the proposed building and excavation works.

Any practices or procedures specified in the engineer's report in relation to the avoidance or minimisation of structural damage to nearby premises, are to be fully complied with and incorporated into the plans and specifications for the **construction certificate**.

A copy of the engineer's report is to be submitted to the Council, if the Council is not the certifying authority.

- c) Driven type piles/shoring must not be provided unless a geotechnical engineer's report is submitted to the certifying authority, prior to the issuing of a construction certificate, which states that damage should not occur to any adjoining premises and public place as a result of the works.
- d) The installation of ground or rock anchors underneath any adjoining premises including (a public roadway or public place) must not be carried out without the specific written consent of the owners of the affected adjoining premises and (where applicable) details of compliance must be provided to the certifying authority **prior to the commencement of any excavation or building works**.

<u>*Reason*</u>:- to ensure the proposed method of excavation is suitable for the site and to prevent damage from occurring to adjoining premises.

37. Excavations Extending Below the Base of Footings of Adjoining Development

Where excavations extend below the level of the base of the footings of a building on an adjoining allotment of land, the person causing the excavation must preserve and protect the building from damage and, if necessary, underpin and support the adjoining building in an approved manner. The person causing the excavation must give the owner of the adjoining property at least seven (7) days written notice of its intention to excavate below the level of the base of the footing. The person must also furnish the adjoining property owner with particulars of the proposed work. <u>Reason</u>:- to ensure the support for neighbouring buildings.

38. Dilapidation Report - Prior to Excavation of Basement

A dilapidation report prepared by a *professional engineer* or suitably qualified building professional shall be submitted to the Principal Certifying Authority **prior to the commencement of demolition, excavation or building works.**

The report shall detail the current condition and status of all buildings, including ancillary structures (*i.e. including dwellings, residential flat buildings, commercial/industrial building, garages, carports, verandahs, fences, retaining walls, swimming pools and driveways etc.*) located upon all of the premises adjoining the subject site

The report is to be supported with photographic evidence of the status of the buildings and a copy of the report must also be forwarded to the Council and to the owners of each of the abovestated premises, prior to the commencement of any works. The applicant shall bear the full cost of this report.

<u>*Reason*</u>:- to enable the monitoring of any potential damage that may be caused to adjoining premises as a result of excavating and building in close proximity to the adjoining premises.

39. Survey Documentation

A Registered Surveyors check survey certificate or *compliance certificate* is to be forwarded to the principal certifying authority (and a copy is to be forwarded to the Council, if the Council is not the principal certifying authority), detailing compliance with Council's approval at the following stage/s of construction:-

- a) Prior to construction of the footings or first completed floor slab (prior to the pouring of concrete), showing the area of the land, building and boundary setbacks.
- b) Prior to construction of the first completed floor/floor slab (prior to pouring of concrete), showing the area of land, building and boundary setbacks and verifying that the building is being constructed at the approved levels.
- c) Prior to construction of each floor level showing the land, building and boundary setbacks and verifying that the building is being constructed at the approved level.
- d) On completion of the erection of the building showing the area of the land, the position of the building and boundary setbacks and verifying that the building has been constructed at the approved levels.

<u>*Reason*</u>:- to ensure each stage of the development complies with the approved plans.

40. Footpath area to be illuminated

Where any hoarding or awning is constructed over the public place, the footpath area shall be kept illuminated between sunset and sunrise.

<u>*Reason*</u>:- the ensure the safety of pedestrians when passing the site.

41. Fencing Of Construction Sites – A Type Hoarding

A separate application is to be made to Council for Approval under Section 68 of the Local Government Act 1993 to erect a hoarding or scaffolding in a public place and such application is to include:

- A payment to Council for the following fees in accordance with Council's adopted charges:
 - Hoarding/Structure Application Fee
 - Rental of Footpath Area (per metre per month minimum 3 months rental)
 - Footpath Bond
- Submit the following documents to Council with your application:
 - Certificate of Currency for Public Liability Insurance
 - Certificate of Currency for Worker's Compensation Insurance
 - Letter indemnifying Council against claims and expenses made in relation to the existence of the structure and/or traffic provisions
 - Traffic/Pedestrian Control Plan
- Comply with Council's specifications for the erection of Class A Hoardings.
- Supply evidence to the PCA and to any authorised Council officer that the road reserve rental fee has been paid.

Note: Public access to the site and building works, materials and equipment on the site is to be restricted, when work is not in progress or the site is unoccupied.

A temporary hoarding or fence is to be provided to protect the public, located to the perimeter of the site (unless the site is separated from the adjoining land by an existing structurally adequate fence, having a minimum height of 1.5 metres). Hoardings or fences are to have a minimum height of 1.8 metres and be constructed of solid plywood sheeting (painted white) or of cyclone wire fencing with geotextile fabric attached to the inside of the fence, to provide dust control.

Hoardings or fences are to be structurally adequate and be constructed in a good and workmanlike manner and the use of poor quality materials or steel reinforcement mesh as fencing is not permissible.

The public safety provisions and temporary fences must be in place prior to the commencement of any demolition, excavation or building works and be maintained throughout construction.

<u>*Reason:*</u> to provide protection to public places and to prevent unauthorised access to the site.

42. Soil and Water Management Plan – Large sites

A Soil and Water Management Plan (also known as an Erosion and Sediment Control Plan) shall be prepared according to the NSW EPA's *Managing Urban Stormwater: Construction Activities.* This Plan shall be implemented prior to commencement of any site works or activities. All controls in the Plan shall be maintained at all times. A copy of the Soil and Water Management Plan must be kept on-site at all times and made available to Council officers on request.

<u>*Reason*</u>:- to ensure sediment and erosion controls are maintained during the construction process to prevent water pollution from occurring.

43. Sediment Removal from Vehicle Wheels – Large sites

A vehicle wheel wash, cattle grid, wheel shaker or other appropriate device, shall be installed in accordance with the Soil and Water Management Plan, prior to commencement of any site works or activities, to prevent mud and dirt leaving the site and being deposited on the street.

<u>*Reason*</u>:- to ensure suitable controls are in place prior to any works commencing to prevent water pollution from occurring.

44. Disposal of Site Water

Site water discharged to Council's stormwater system must have a suspended solid level of less than 50 mg/L. This may require treatment such as transfer to settling ponds, use of approved chemicals to settle out sediment or passing the contaminated water through a treatment device. Site water may also be disposed of through the services of a licensed liquid waste transporter.

<u>Reason</u>:- to prevent water pollution from occurring.

45. Noise from Construction Activities

Noise from construction activities associated with the development shall comply with the NSW Environment Protection Authority's Environmental Noise Manual – Chapter 171 and the *Protection of the Environment Operations Act 1997*.

- a) Level Restrictions:
 - i) Construction period of 4 weeks and under:-
 - the L₁₀ sound pressure level measured over a period of not less than 15 minutes when the construction site is in operating must not exceed the background level by more than 20 dB(A).
 - ii) Construction period greater than 4 weeks and not exceeding 26 weeks:-
 - the L₁₀ sound pressure level measured over a period of not less than 15 minutes when the construction site is in operating must not exceed the background level by more than 10 dB(A).
 - iii) All possible steps should be taken to silence construction site equipment.

<u>*Reason*</u>:- to ensure noise arising from construction activities is in accordance with relevant legislation and EPA requirements.

46. Site Compaction – Work Methodology

Prior to the issue of a Construction Certificate, a work methodology prepared by an appropriately qualified geotechnical engineer shall be submitted to the Principal Certifying Authority for approval in respect of all site compaction works. The work methodology shall address the following:-

- a) Predicted vibration emissions extending beyond the boundaries of the site generated from the construction works indicating compliance with the requirements of the NSW Environment Protection Authority's Noise Control Guidelines Vibration in Buildings; and
- Measures to minimise dust, offensive noise emissions and vibrations to demonstrate compliance with the NSW Environment Protection Authority's Noise Control Guidelines – Construction Site Noise.

<u>*Reason*</u>:- to ensure that carrying out of site compaction works is of minimal impact in the locality.

47. Dial Before You Dig

Dial Before You Dig is a free national community service designed to prevent damage and disruption to the vast pipe and cable networks which provides Australia with the essential services we use everyday – electricity, gas, communications and water.

Before you dig call "Dial before you dig" on 1100 (listen to the prompts) or facsimile 1300 652 077 (with your street no./name, side of street and the distance to the nearest cross street) or register on line at www.dialbeforeyoudig.com.au for underground utility services information for any excavation areas.

The Dial Before You Dig service is also designed to protect Australia's excavators. Whether you are a back yard renovator, an individual tradesman or a professional excavator the potential for injury, personal liability and even death exists every day. Obtaining accurate information about your work site significantly minimises these risks.

<u>*Reason*</u>: To ensure that essential services such as electricity, gas, communications and water are not affected by excavation or construction.

48. Contamination and Validation

Council will require that the applicant engage an accredited auditor under the *Contaminated Land Management Act 1997* to review the Validation Report prepared by the contaminated land consultant and issue a Site Audit Statement. The accredited auditor shall consult with Council prior to finalising and issuing the Site Audit Statement. The Site Audit Statement should allow for soil access to occur to ground level courtyards and communal open space areas within the development.

The accredited auditor shall provide Council with a copy of the Site Audit Report and Site Audit Statement, *prior to the issuing of the Occupation Certificate.*

In circumstances where the SAS conditions (if applicable) are not consistent with the consent, the consent shall prevail to the extent of the inconsistency and a Section 96 Application or further Development Application pursuant to the *Environmental Planning and Assessment Act 1979* will be required.

<u>*Reason*</u>:- to ensure the provisions of State Environmental Planning Policy No. 55 – Remediation of Land and the Contaminated Land Management Act are complied with.

49. Discovery of Additional Information During Site Works

Any new information which comes to light during remediation, demolition or construction works which has the potential to alter previous conclusions about site contamination shall be notified to the Council and the PCA immediately.

<u>*Reason:*</u>- to ensure Council is informed of any new information relevant to site conditions and site contamination associated with the development.

50. Monitoring of Field Parameters

Results of the monitoring of any field parameters such as soil, groundwater, surface water, dust or noise measurements shall be made available to Council Officers on request throughout the remediation and construction works.

<u>*Reason*</u>:- to ensure Council is informed as to monitoring of field parameters relevant to the remediation and/or construction works.

51. Off-Site Soil Disposal

Any soil disposed of offsite shall be classified in accordance with the procedures in the NSW EPA Environmental Guidelines: Assessment, Classification & Management of Liquid & Non-Liquid Wastes (1999).

<u>Reason</u>:- to ensure soil disposed off-site is classified in accordance with relevant EPA requirements.

52. Fill for Residential Premises

- (a) Should any importation of landfill material be required on the site, a validation report prepared in accordance with the Department of Environment and Conservation (DEC) (formerly known as the EPA) "Guidelines for Consultants Reporting on Contaminated Sites" shall be submitted to Council for approval. The validation report shall state in an end statement that the fill material is suitable for the proposed use on the land.
- (b) "Chain of Custody" documentation shall be kept for the transportation of validated fill material from its point of origin to its arrival at the subject premises. A record of "Chain of Custody" shall be submitted to Council within seven (7) days of the fill material being moved to or from the subject site.

<u>Reason:</u>- to ensure appropriate validation and handling of fill for residential premises.

53. Compliance with Submitted Acoustic Report

All noise control measures specified in the Environmental noise acoustic assessment prepared by Acoustic Logic Consultancy (report 20101140.1/1612A/RD/YK), shall be installed prior to the issuing of the occupation certificate. All noise reduction measures specified in the acoustic report shall be complied with at all times during the operation of the premises.

<u>*Reason*</u>:- To ensure all noise reduction measures are implemented

54. Acoustic Certification

Within three months of the premises being occupied, an acoustic report prepared by a suitably qualified person, is to be submitted to the consent authority demonstrating that the noise emitted from the premises complies with the criteria contain in the Environmental noise acoustic assessment prepared by Acoustic Logic Consultancy (report 20101140.1/1612A/RD/YK). Where the criteria are not meet the acoustic report is to include recommendation of noise control measures that are to be implemented to ensure compliance with the criteria.

<u>*Reason*</u>:- to ensure the recommendations of the acoustic report are implemented and functioning.

55. Number of Car Parking Spaces

A total of three hundred and thirty five (335) off-street car parking spaces are to be provided to the development. The spaces are to have minimum dimensions of 5.5 m x 2.4 m and be suitably sealed, marked, drained and freely accessible at all times. Visitor carparking spaces shall be a minimum width of 2.6 m.

Carparking spaces are not to be enclosed by any device, such as a wire or mesh cage, walls or other similar fixtures unless there is a minimum clear internal width of 3 metres. Carparking spaces shall not be enclosed without the prior consent of council.

<u>*Reason*</u>:- to ensure there is sufficient car parking for the development and to comply with Auburn Parking & Loading DCP.

56. Signs for Visitor Parking

Suitable signs shall be erected at the front of the property indicating the availability of visitor parking within the property. All visitor parking spaces shall be clearly signmarked.

<u>*Reason*</u>:- to ensure the visitor parking spaces are clearly identified.

57. Signs and Pavement Markings

Adequate signs and pavement markings are to be provided to direct the flow of traffic within the site. Details are to be provided prior to the issue of the construction certificate.

<u>*Reason*</u>:- to assist with traffic flow within the development.

58. Car Wash Bay

An open service area measuring at least 7.6 metres x 3.0 metres is to be provided for use by residents for car cleaning and washing activities. This area is to be suitably located, paved, graded and drained.

All waste water from the car wash bay shall be discharged to sewer under a Trade Waste Agreement from Sydney Water. This may require the installation of a pre-treatment device. Alternative water management and disposal options may be appropriate where water is recycled, minimised or re-used on the site.

The means of disposal shall comply with:-

- EPA's Environment Protection Manual for Authorised Officers: Technical Section (Car Washing Waste)
- EPA's Managing Urban Stormwater: treatment techniques

Details are to be submitted with the construction certificate.

<u>*Reason*</u>:- to designate a car washing area within the development and to ensure waste water is properly managed.

59. Vehicles Driven in Forward Direction

All vehicles must be driven in a forward direction at all times when entering or leaving the premises.

<u>*Reason*</u>:- to preserve and enhance the safe operation of the car parking area.

60. Loading and Unloading of Vehicles

All deliveries to and from the site are to be conducted from vehicles standing within designated loading areas and not on access driveways, car parking spaces or landscaped areas.

<u>*Reason*</u>:- to ensure delivery vehicles do not obstruct these designated areas of the site.

61. Protective bar to vehicular entry

A protective bar shall be installed at the vehicular entry to the development to prevent damage from vehicles that are too high or those that fail to wait for the opening of any roller shutter etc. Details and installation of the proposed protective bar shall be noted on the Construction Certificate drawings and installed prior to the issue of Occupation Certificate.

<u>*Reason:*</u>- to prevent damage from oversized vehicles when entering the premises.

62. Roller doors and shutters – silent operation

The roller doors or other shutters to the car park shall operate silently and be appropriately maintained.

<u>*Reason*</u>:- to ensure quiet operation and ongoing maintenance to car park doors.

63. Parking Level Painting

The parking levels shall be painted in a cream or white colour to maximise lux levels and promote a greater sense of security and amenity. Details of the proposed colour scheme shall be to the satisfaction of the Principal Certifying Authority prior to the issue of a Construction Certificate.

<u>Reason</u>:- to promote a greater sense of security and amenity within the basement parking area.

64. Intercom/Remote Access to Basement

An intercom and remote access system shall be provided at all vehicular access points to the basement car park and connected to all residential units. Details of the proposed intercom and remote access system to the basement car park are to be submitted with the Construction Certificate plans/specifications and the locations detailed on the construction drawings.

<u>*Reason*</u>:- to ensure that visitor car parking spaces are easily and conveniently accessible for visitors to the premises.

65. Car Parking Spaces – Restrictive Covenant

The following shall be complied with:-

- a) The on site car parking spaces, exclusive of service and visitor spaces, are not to be used by those other than the occupant or tenant of the subject building. Any occupant, tenant, lessee or registered proprietor of the development site or part thereof shall not enter into an agreement to lease, license or transfer ownership of any car parking spaces to those other than an occupant, tenant or lessee in the building.
- b) Prior to Occupation Certificate under the Environmental Planning and Assessment Act 1979 a documentary Restrictive Covenant, is to be registered on the Title of the development site pursuant to Section 88E of the Conveyancing Act 1919, to the effect of (a) above. The Covenant is to be created appurtenant to Council, at no cost to and to the satisfaction of Council.
- c) Any future strata subdivision of the site is to include a Restriction on User pursuant to Section 39 of the Strata Titles (Freehold Development) Act 1973, as amended, burdening all utility car parking allotments in the Strata Plan and/or an appropriate Restrictive Covenant pursuant to Section 88B of the Conveyancing Act 1919 burdening all car parking lots in the strata scheme.

<u>*Reason*</u>:- to ensure the car parking spaces are used in accordance with the details of the development approval.

66. Car Park and Service Vehicle Area Layout

- The layout of the car park shall comply with Australian Standard AS2890.1:2004 Parking Facilities Part 1: Off Street Parking. All parking spaces are to be line marked.
- b) The layout of the service vehicle area shall comply with Australian Standard AS2890.2:2004 Off Street Parking Part 2 Commercial Vehicle Facilities.

<u>*Reason*</u>:- to ensure that the car parking and service vehicles areas are designed and constructed to meet relevant Australian Standards.

67. Traffic Management

A management plan shall be submitted to and approved by Council for all demolition, excavation and construction traffic activities associated with the development prior to commencement of work.

<u>*Reason*</u>:- to ensure impacts of construction traffic are appropriately managed.

68. Access to Public Road

Access to a public road shall be provided for all the properties *prior to the issue of any Occupation Certificate.*

<u>Reason</u>: to ensure access to public road is provided.

69. Ventilation of The Basement Car Park

The basement car park shall be naturally or mechanically ventilated. The ventilation system shall comply with the requirements of the Building Code of Australia and relevant standards including AS1668.1 – 1998 The Use of Ventilation and Air conditioning in Buildings Part 1: Fire and Smoke Control in Multi Compartment Buildings and/or AS 1668.2-2002; The Use of ventilation and Air conditioning in Buildings Part 2: Ventilation Design for Indoor Air Contaminant Control.

The system shall be certified by a suitably qualified and experienced engineer at the completion of installation prior to the issue of an Occupation Certificate. A copy of the certificate shall be provided to the Principal Certifying Authority (PCA). A copy shall also be provided to Council if Council is not the Principal Certifying Authority.

Any mechanical ventilation provided to the basement car park shall not create an offensive odour emission nor shall it create an offensive noise and shall comply with the requirements of the Protection of Environment Operations Act and all subsequent relevant Regulations.

<u>Reason</u>:- to ensure adequate basement ventilation measures are installed

70. Materials and Finishes

Materials and finishes to the development shall be in accordance with the details of the approved plans and the following requirements:-

- a) Quality and durable materials are to be used throughout the development.
- b) The applied external paint finishes to the building shall have a minimum aggregate thickness of 200 microns.

<u>*Reason*</u>:- to ensure a high quality appearance to all materials within the development.

71. <u>Maintenance Schedule</u>

Prior to the issue of a Construction Certificate a maintenance schedule to be submitted to the Principal Certifying Authority for approval as to the ongoing maintenance and upkeep of the finishes and materials to the building. This shall include, but not be limited to the following:

- a) The exterior of the buildings being painted at least once in every ten year period
- b) The externally visible windows of the buildings being washed once every year; and
- c) Timber work (screens, fences and the like) to the building and site being protected against fading/discolouration and warping

<u>*Reason*</u>:- to ensure adequate ongoing maintenance to the development.

72. SEPP 65 – Design Verification

The following requirements arising from State Environmental Planning Policy No. 65 – Design Quality of Residential Flat Buildings must be complied with:-

- a) A certifying authority must not issue a Construction Certificate in respect of the development unless the certifying authority has received a design verification from a qualified designer, being a statement in which the qualified designer verifies that the plans and specification achieve or improve the design quality of the development for which development consent was granted, having regard to the design quality principles set out in Part 2 of State Environmental Planning Policy No. 65 Design Quality of Residential Flat Development.
- b) A certifying authority must not issue an Occupation Certificate to authorise a person to commence occupation or use of the development unless the certifying authority has received a design verification from a qualified designer, being a statement in which the qualified designer verifies that the development as shown in the plans and specifications in respect of which the Construction Certificate was issued, having regard to the design quality principles set out in Part 2 of State Environmental Planning Policy No. 65 Design Quality of Residential Flat Development.

<u>*Reason*</u>:- to ensure that the requirements of SEPP No. 65 and the EP&A Regulations are complied with in the carrying out of the development.

73. Architect – Notify Council if Changed

The architect of the project, as approved, should not be changed without prior notice to Council.

<u>*Reason*</u>:- to ensure Council is aware and kept informed of the current project architect.

74. <u>Common Wall Construction</u>

Prior to the issue of a Construction Certificate, construction drawings shall be submitted to the Principal Certifying Authority for approval to indicate that common party walls between the dwellings being constructed from solid masonry materials and not being lightweight construction.

<u>*Reason*</u>:- to ensure adequate acoustic separation between dwellings within the development.

75. Plumbing – Separation and Containment

Prior to the issue of a Construction Certificate, construction drawings shall be submitted to the Principal Certifying Authority for approval to indicate that plumbing to each dwelling will be separated and adequately contained to prevent noise transmission and vibration.

<u>*Reason*</u>:- to ensure adequate separation and containment of plumbing between dwellings.

76. <u>Timbers</u>

Prior to the issue of a Construction Certificate, construction drawings/specifications shall indicate that timbers used in the development are plantation, recycled or regrowth timbers of timbers grown on Australian farms or State forest plantations and that no old growth or rainforest timbers are to be used in any circumstances.

<u>*Reason*</u>:- to promote ecologically sustainable development by preventing the use of old growth and rainforest timbers within the development.

77. Lockable Pedestrian Entries

All shared pedestrian entries to the buildings must be lockable.

<u>*Reason:*</u>- to ensure adequate security provision to shared pedestrian entries to the development in accordance with Council's Development Control Plan requirements.

78. Underside of balconies

The underside of the balconies within the development must be designed to prevent exposed pipes and utilities being visible.

<u>*Reason*</u>:- to ensure an attractive appearance to the development in accordance with Council's Development Control Plan requirements.

79. Parking Level Appearance

- a) Basement walls to the development that are visible above ground level are to be appropriately finished and be treated to be consistent with the appearance of the building.
- b) Where the basement wall extends within 1.2m of the side or rear boundary, ventilation grilles are not to be provided within these elevations.

<u>*Reason:*</u>- to ensure that the basement walls are appropriately treated and in accordance with Council's Development Control Plan requirements.

80. Switchboards/Service Panels

Switchboards and/or service panels for utilities are not to be attached to the front facades/elevations of the building(s).

<u>*Reason:*</u>- to ensure that switchboards and service panels are appropriately located and do adversely impact on the appearance/presentation of the front building facade.

81. Reflectivity Index of Glazing

The reflectivity index (expressed as a percentage of the reflected light falling upon any surface) of external glazing for windows, walls or roof finishes of the proposed development is to be no greater than 20%. Written confirmation of the reflectivity index of materials is to be submitted with the Construction Certificate.

Note: The reflectivity index of glazing elements can be obtained from glazing manufacturers. Glass with mirrored or reflective foil finishes is unlikely to achieve compliance with this requirement.

<u>*Reason:*</u>- to ensure that excessive glare or reflectivity nuisance from glazing does not occur as a result of the development.

82. Roofing Materials – Reflectivity

Roofing materials shall be factory pre-finished with low glare and reflectivity properties to be compatible with the colours of neighbouring buildings. The Certifying Authority shall undertake an assessment in relation to the proposed roofing material to determine the potential for glare nuisance or excessive reflectivity to adjoining or nearby properties, relative to the roofing material. The Certifying Authority shall provide certification with the Construction Certificate that the selected roofing material will not cause a glare nuisance or excessive reflectivity to adjoining or nearby properties.

<u>*Reason:*</u>- to ensure that excessive glare or reflectivity nuisance from roofing materials does not occur as a result of the development.

83. Stormwater Disposal

All stormwater runoff generated from the proposed development shall be discharged by gravity means to the street pipe drainage system in Hill Road.

Reason:- to prevent localised flooding

84. Submission of Full Stormwater Disposal Details

Full stormwater drainage details showing the proposed method of stormwater collection and disposal are to be submitted to Council or the Accredited Certifier to ensure the approved stormwater plans are incorporated with the Construction Certificate.

The details shall be prepared by a suitably qualified person and must be in accordance "Auburn Development Control Plans 2000 - Stormwater Drainage" and "Australian Rainfall & Runoff 1987".

In this regard,

- The proposed stormwater system shall be generally in accordance with the stormwater plans 3550-CC-001, 3550-CC-002, 3550-CC-003, & 3550-CC-004 dated 25. 07. 2011 Prepared by Lucas Consulting Engineers.
- Stormwater runoff from courtyard paved area shall be collected and discharged by stormwater pipe system.

Note: "Auburn Development Control Plans 2000 - Stormwater Drainage" is available to purchase at Council or the document can be found at Auburn Council's web page www.auburn.nsw.gov.au

<u>*Reason*</u>:- to ensure the stormwater is suitably discharged.

85. Drainage Pipe Size

Proposed street drainage pipes shall be designed to cater for the 20 year ARI critical storm event with consideration that the site will be developed to 65 % impervious area.

In this regard,

- A designated emergency overland flow path shall be provided up to 100 year ARI storm event with a fifty percent (50%) blockage factor.
- Details shall be incorporated on the Stormwater drainage plans for Construction certificate approval.

<u>Reason</u>: to prevent localised flooding

86. Flood Risk Management

As site is affected by low flood risk, subject development shall comply with Chapter 6 of Council's 'Auburn Development Control Plans 2010 – Stormwater Drainage'. In this regard, supporting documents shall be submitted in order to ensure that the development complies with the controls in Table 5 of Auburn Development Control Plans 2000 – Stormwater Drainage.

Details shall be submitted to and approved by the Principal Certifying Authority *prior to the issue of a Construction Certificate.*

<u>Reason</u>:- to reduce flood risk to the people and properties.

87. Ramp Gradients

Circulation ramp grades shall comply with section 2.5.3 of the Australian Standard AS2890.1:2004. In this regard:

- Maximum gradient of the driveway access ramps for first 6m in to the car park shall not exceed 1 in 20 (5%). In this regard, longitudinal section of the access ramps shall be submitted in 1:20 scale.
- Detail longitudinal section of the ramps to a scale of 1:20, shall be submitted to and approved by the Principal Certifying Authority *prior to the issue of a Construction Certificate.*

<u>*Reason*</u>:- to ensure the access ramps comply with Australian Standard AS28890.1:2004.

88. <u>Headroom Clearance</u>

Headroom clearance shall comply with section 5.3 of the Australian Standard AS2890.1:2004. In accordance with As2890.1, minimum 2.3m headroom clearance shall be provided. In this regard detail longitudinal section of curved ramps to a scale of 1:20, shall be submitted to and approved by the Principal Certifying Authority *prior to the issue of a Construction Certificate.*

A Copy of the approved plan shall be submitted to Council.

<u>Reason</u>:- to ensure the access ramps comply with Australian Standard

AS28890.1:2004.

89. Works-as-Executed Plan

Prior to occupation of the building or issue of the occupation certificate, two (2) copies of the Works-as-Executed (W.A.E.) Plan prepared by a registered surveyor and certified by the design engineer shall be submitted to Council. The W.A.E. plan shall show (where applicable):-

- i. Whether all works have been completed generally with the approved drainage plans.
- ii. Any departure from the approved plan and conditions.
- iii. Any additional work that has been undertaken.
- iv. Location, levels and sizes of pipes and pits.
- v. Finished floor and finished surface levels. The location of finished levels should in general correspond with those shown on Council's approved drainage plan.
- vi. Basement pump out volumes.

NOTE: The WAE surface level shall be taken after all landscaping has been completed.

In this regard:

- The above information is to be superimposed on a full sized copy of Council approved drainage plan and is to be submitted to Council.
- Checklists A3, A4 & A5 shall be completed and shall be certified by the practicing hydraulic engineer and the registered surveyor.

<u>Reason</u>:- to account for minor variations and to ensure Council has the final details.

90. Sight Distance and Driveway

The driveway entry shall be design in accordance with AS 2890.1 2004. Prior to release of the Construction certificate, a compliance certificate from a practising civil/traffic engineer shall be submitted to Council. The above compliance certificate shall state that the Driveway design shall comply with section 3.2.4 of AS 2890.1 2004.

<u>*Reason*</u>: to ensure the sight distance and to traffic and pedestrian comply with Australian Standards.

91. Reinstatement of footpath and footpath crossing

The footpath and footpath crossing/s adjacent to the property shall be reinstated by Council at the completion of works with all costs being borne by the developer. Alternatives to the pre-payment for this work will be considered if written request is made to Council.

<u>*Reason*</u>:- to ensure the footpath and the footpath crossings are repaired from any damage caused during the construction phase.

92. Vehicle Driveway Crossings and Gutter Laybacks

Arrangements shall be made with Council for the prepaid construction of vehicular

crossings and gutter laybacks at all property entrances and exits, and for the removal of all disused driveway crossings and gutter laybacks. Alternatives to the pre-payment for this work will be considered if written request is made to Council. The gutter crossing and/or the removal of any redundant crossings must be constructed to the satisfaction of Council (and to the Council's specifications including payment of any required bonds) or the prepayment made to Council for Council to carry out the work, prior to the issue of <u>any</u> occupation certificate.

Removal of obstructions, such as power poles, trees, drainage pits and the like shall be carried out at the applicant's expense.

<u>*Reason:*</u>- to ensure that works are carried out in accordance with Council's standard.

93. Carrying Capacity of Driveways – Heavy Duty

Suitable heavy-duty driveway crossings are to be installed at all ingress/egress points to the property at the applicant's cost by Council. Alternatives to the pre-payment for this work will be considered if written request is made to Council. The gutter crossing and/or the removal of any redundant crossings must be constructed to the satisfaction of Council (and to the Council's specifications including payment of any required bonds) or the prepayment made to Council for Council to carry out the work, prior to the issue of <u>any</u> occupation certificate.

<u>*Reason*</u>:- to ensure the driveways can support the expected weight of heavy vehicles likely to frequent the site.

94. Street Boundary Levels

Street boundary levels for vehicle access and drainage purposes are to be obtained at the applicant's cost from Council's Service Planning Department. These levels are to be incorporated in all drainage submissions required under this determination.

<u>*Reason*</u>:- to ensure the correct levels are obtained and used for the development.

95. Road Opening Permit

Prior to commencement of any work on Council roads and footpaths, a road-opening permit shall be obtained from Council's Service Planning Department.

<u>Reason</u>:- to safeguard Council property against damage.

96. **Restoration Works**

Prior to commencement of any excavation work on Council roads or footpaths, the applicant shall pay for all restoration costs. The area of restoration shall be determined on site between the applicant or its contractor and Council's Contracts & Maintenance Engineer.

<u>*Reason*</u>:- to ensure that Council's infrastructure is maintained in a safe and trafficable manner.

97. Driveway Width

Driveways shall align with the proposed access ramp width. In this regard,

- Driveway widths at the property boundary shall be 6600mm.
- Separator medians shall be extended up to the property boundary.

Amended plans shall be submitted to and approved by the Principal Certifying Authority prior to the issue of a Construction Certificate.

<u>*Reason*</u>: to improve the safety and improve the vehicular maneuvering at the entrances.

98. Works within Council Controlled Lands

- (1) For drainage works:
 - a) Within Council controlled lands.
 - a) Connecting to Council's stormwater drainage system.

Inspections will be required:-

- (i) After the excavation of pipeline trenches.
- (ii) After the laying of all pipes prior to backfilling.
- (iii) After the completion of all pits and connection points.
- (2) A minimum of 48 hours notice shall be given to Council to inspect works. Inspections may be arranged by telephoning Council's Works and Services Section during office hours.
- (3) Work is not to proceed until the works are inspected and approved by Council.

Reason: to ensure works on public/Council controlled lands are carried out as per Council's requirements.

<u>Reason</u>: to ensure development complies with car parking and loading development control plan.

99. On Street Parking

The proposed on street parking plan shall comply with Australian Standard AS2890.5.

In this regard,

- a) The parking bay dimensions shall comply with Australian standard AS 2890.5..
- a) Amended on street parking layout shall be submitted and approved by the Principal Certifying Authority *prior to the issue of a Construction Certificate.*

<u>*Reason:*</u>- to ensure on street parking complies with Australian standard AS 2890.5.

100. Footpath Construction – Hill Road

Prior to the issue of the any Occupation Certificate, a new footpath shall be constructed along the Hill Road frontage.

In this regard:

- A detailed design shall be prepared in consultation with Council and submitted to Council for approval.
- All associated cost shall be borne by the applicant.

<u>Reason</u>: to provide a safe footpath for increased pedestrian use and one that will complement the Auburn Town Centre.

101. Service relocation / Adjustment

The applicant shall locate any utility services affected by the proposal and shall be responsible for any damage to, or relocation of services required by the proposal including adjustment to the levels of pit lids etc. All works shall be carried out to the satisfaction of the relevant Authority or Council.

Reason : to protect utility services

102. <u>Amenity</u>

The operation of the premises shall be conducted in such a manner as not to interfere with or materially affect the amenity of the neighbourhood by reason of noise, vibration, odour, fumes, vapour, steam, soot, ash, dust, waste water, waste products, grit, oil, or otherwise.

<u>Reason</u>:- to protect the amenity of the locality.

103. <u>Odour</u>

No offensive odour from any trade, industry or process shall be detected outside the premises by an authorised Council Officer as defined in the *Protection of the Environment Operations Act 1997*.

<u>*Reason*</u>:- to protect the surrounding locality from offensive odours.

104. Water Pollution

The operation of the premises shall be conducted in a manner which does not pollute waters as defined by the *Protection of the Environment Operations Act 1997*.

<u>*Reason*</u>:- to protect waterways and stormwater systems from pollution.

105. Removal of Litter

In addition to Council's street sweeping and cleansing operations, the owner/manager of the building shall ensure that the footpath, gutter, building entry and surrounds are kept clean and clear of litter at all times.

<u>Reason</u>:- to maintain a satisfactory level of amenity in the locality.

106. Light Overspill

Any lighting on the site shall be designed so as not to cause nuisance to other

residences in the area or to motorists on nearby roads, and to ensure no adverse impact on the amenity of the surrounding area by light overspill. All lighting shall comply with AS4282-1997 Control of the obtrusive effects of outdoor lighting.

<u>*Reason*</u>:- to ensure light overspill arising from the development does not interfere with the amenity of the locality and complies with relevant Australian Standards.

107. Final Fire Safety Certificate

Prior to the occupation of the building, the owner of the building shall submit to the Principal Certifying Authority (Council or Accredited Certifier), a **final fire safety certificate** in relation to each essential fire safety measure specified in the **fire safety schedule**, attached to the development consent or construction certificate.

Such certificate shall state that each essential fire safety measure specified:-

- a) Has been assessed by a properly qualified person, and
- b) Was found, at the date of assessment, to be capable of performing to a standard not less than that required by the current fire safety schedule for the building for which the certificate is issued.

NOTES:

- 1. As soon as practicable after a final fire safety certificate is issued, the owner of the building to which it relates:
 - i) Must cause a copy of the statement (and current fire safety schedule) to be given to the Commissioner of NSW Fire Brigades, and
 - ii) Must cause a further copy of the statement (and current copy of the current fire safety schedule) to be prominently displayed in the building.
- 2. A "fire safety measure" is defined as any measure (including any item of equipment, form of construction or fire safety strategy) that is, or is proposed to be, implemented in the building to ensure the safety of persons using the building in the event of fire.

<u>*Reason*</u>:- to ensure compliance with Regulations 149 & 171 of the Environmental Planning and Assessment Regulation 2000.

108. Annual Fire Safety Statement

The owner of any building in which fire safety measures are installed, must cause the Council to be given an **annual fire safety statement**, within 12 months after the last such statement or final fire safety certificate was issued.

The certificate shall certify:-

- a) That each essential fire safety measure has been assessed by a properly qualified person and was found, at the date of assessment, to be capable of performing to a standard not less than that required by the current fire safety schedule.
- b) That a properly qualified person has inspected the building and has certified that, as at the date of inspection, the condition of the building did not disclose any grounds for a prosecution under Division C.

NOTES:

- 1. As soon as practicable after an annual fire safety statement is issued, the owner of the building to which it relates:
 - i) must cause a copy of the statement (and current fire safety schedule) to be given to the Commissioner of NSW Fire Brigades, and
 - ii) must cause a further copy of the statement (and current copy of the current fire safety schedule) to be prominently displayed in the building.
- 2. A "fire safety measure" is defined as any measure (including any item of equipment, form of construction or fire safety strategy) that is, or is proposed to be, implemented in the building to ensure the safety of persons using the building in the event of fire.

<u>*Reason*</u>:- to ensure compliance with Regulation 171 of the Environmental Planning and Assessment Regulation 2000.

109. Fire Safety Notices

The fire-isolated stairway, fire-isolated passageway or fire-isolated ramp must contain a notice advising of "Offences relating to fire exits". The notice shall contain the wording prescribed by Clause 183 of the Environmental Planning and Assessment Regulation, 2000 and the Building Code of Australia.

<u>*Reason*</u>:- to comply with Clause 183 of the Environmental Planning and Assessment Regulation 2000 and the BCA.

110. Mechanical Ventilation Systems/Cooling Towers

The mechanical ventilation system shall comply with *Australian Standard AS1668.2* – *1991. The use of mechanical ventilation and air conditioning in buildings.* Prior to installation, the design is to be certified by a person competent to do so. At the completion of the installation of the mechanical ventilation system, the work shall be certified by a person competent to do so. The certification shall include:-

- inspection, testing and commissioning details
- date of inspection testing and commissioning
- the name and address of the individual who carried out the test
- a statement that the service has been designed, installed and is capable of operating to the above standard.

Any cooling tower installation shall be designed, installed and maintained in accordance with the requirement of the Public Health (Microbial Control) Regulation 2000 and Australian Standard *AS/NZS 3666.2:1995 Air-handling and water systems of buildings Microbial control Operation and maintenance*. All waste water from the cooling tower/humidifier/evaporative cooler/warm water system shall be discharged to sewer under a Trade Waste Agreement from Sydney Water.

A copy of the installation certificate shall be submitted to Council **prior to occupation of the building** to enable details of any cooling towers to be entered on Council's Cooling Tower register.

<u>*Reason*</u>:- to ensure compliance with the Building Code of Australia and Public Health (Microbial Control) Regulation 2000.

111. Landscaping installation & maintenance

Landscaping must be installed and maintained in accordance with Schedule A-4 -Minimum Landscaping Requirements of Auburn General Requirements Development Control Plan prior to the issue of an Occupation Certificate.

<u>*Reason*</u>:- to ensure compliance with Council's Development Control Plan requirements.

112. Irrigation to Landscape Areas

All landscaped podium areas and landscaped communal open spaces shall be provided with a water efficient (drip or similar) irrigation system.

<u>*Reason:*</u>- to ensure common landscaped areas within the development are provided with adequate irrigation.

113. Soil Depth to Landscaped Podiums

All landscaped podium areas should maintain a minimum soil planting depth of 600mm for tree provision and 300mm for turf provision.

<u>*Reason:*</u>- to ensure adequate soil depth to landscaped podium areas.

114. Paving Selection

Selection of paving for use within the development shall give consideration to materials that reduce glare and minimise surface runoff.

<u>*Reason:*</u>- to ensure appropriate paving selection within the development as required by Council's Development Control Plan.

115. Maintenance Of Proposed Street Trees

Newly planted trees on Council land (Hill Road) shall be maintained for a period of twelve months. Maintenance shall include watering, weeding, removal of rubbish from tree base, pruning, fertilizing, pest and disease control and any other activities required to maintain a healthy tree. A suitably qualified horticulturist shall undertake all maintenance work.

At the end of the twelve month period the applicant may apply to Council in writing for the hand-over of the trees and the reimbursement of bond money. Any replacement of dead or damaged trees required to be replaced by Council will result in forfeiting of the bond.

<u>*Reason*</u>:- to ensure planting and ongoing maintenance of street trees to Council's satisfaction.

116. Turf on Council's Verge

All turf on Council's verge directly adjacent to the lot shall be removed and replaced with Kikuyu turf prior to the issue of an Occupation Certificate. Levels on the verge must remain unchanged.

<u>*Reason*</u>:- to improve streetscape appearance.

117. Noise and Vibration

The use of the premises shall not give rise to any of the following when measured or assessed at "sensitive" positions within any other property. These "sensitive" positions should be selected to reflect the typical use of a property (ie any outdoor areas for day and evening but closer to the façade at night time), unless other positions can be shown to be more relevant.

- a) 'offensive noise' as defined in the Protection of the Environment Operations Act 1997.
- b) transmission of vibration to any place of different occupancy above the requirements of AS2670.
- c) a sound pressure LAeq, period at any noise sensitive position of any other premises or occupancy greater than the recommended amenity noise criteria detailed in the Department of Environment and Conservation, New South Wales (EPA) Industrial Noise Policy.
- d) a sound pressure LAeq,15min at any noise sensitive position greater than the intrusiveness criteria determined in accordance with the Department of Environment and Conservation, New South Wales (EPA) Industrial Noise Policy and does not contain any tones, low frequency or impulsive factors as defined in the Department of Environment and Conservation, New South Wales (EPA) Industrial Noise Policy table 4.1.

For assessment purposes, the above L_{Aeq} sound levels shall be assessed over a period of 10-15 minutes and adjusted in accordance with EPA guidelines for tonality, frequency weighting, impulsive characteristics, fluctuations and temporal content where necessary.

<u>Reason:</u>- to ensure adequate acoustic amenity in the locality.

118. Air Conditioning Units – Location and Acoustics

- Air conditioning units are to be located to the ground level of rear yards or within basement garages and not within the side setbacks or frontages of the property. Air conditioning units are not to be visible from the street or public place and are not to obscure windows/window frames or architectural features of the building.
- b) The operation of air conditioning units shall be so:
 - (i) as not to cause "offensive noise" as defined under the Protection of the Environment Operations Act 1997;
 - (ii) as to be inaudible at the nearest affected residence between the hours of 10.00pm and 7.00am on weekdays and 10.00pm and 8.00am on weekends and public holidays;
 - (iii) as not to discharge a condensate or moisture onto the ground surface of the premises or into a stormwater drainage system in contravention of the requirements of the Protection of the Environment Operations Act 1997.
- c) Should Council receive noise complaints from neighbouring residents in relation to the air conditioning units, Council may issue a Noise Notice. Such notice may require you to engage the services of a competent and appropriately qualified Acoustic Consultant to undertake a noise level assessment of the air conditioning unit. If the unit is assessed as exceeding the permitted noise criteria, you may be directed to provide noise attenuation measures such as an acoustic enclosure and/or relocation of the unit.

<u>Reason</u>:- to ensure that air conditioning units associated with the development are appropriately located and do not detract from the appearance of the buildings and to ensure the operation of air conditioning units does not adversely impact on the acoustic amenity of the locality.

119. Intruder Alarms

Any intruder alarm at the premises shall be fitted with a timing device in accordance with the requirements of Section 53 of the Protection of the Environment Operations (Noise Control) Regulation 2000.

<u>*Reason:*</u>- to prevent ongoing noise arising from intruder alarms and ensure compliance with relevant legislation.

120. Arrangements for Electricity and Telephone Services

Satisfactory arrangements are to be made with Energy Australia, Telstra and/or Optus for the provision of services to and within the subject land. Written evidence of such arrangements shall be submitted to the Principal Certifying Authority (Council or accredited certifier) prior to the issue of the construction certificate.

NOTE: Prior to works commencing, the applicant is advised to contact each provider to determine the location of various services to avoid damage occurring.

<u>*Reason*</u>:- to ensure these services are available to the site.

121. Arrangements for Water and Sewer Services

A Section 73 Compliance Certificate under the Sydney Water Act 1994 must be obtained.

Application must be made through an authorised Water Servicing Coordinator. Please refer to "Your Business" section of Sydney Water's web site at <u>www.sydneywater.com.au</u> then the "e-developer" icon or telephone 132 092.

Following application a "Notice of Requirements" will detail water and sewer extensions to be built or charges to be paid. Please make early contact with the **Coordinator**, since building of water/sewer extensions can be time consuming and may impact on other services and building, driveway or landscaping design.

The Section 73 Certificate must be submitted to the Principal Certifying Authority (Council or accredited certifier) prior to release of the final plan of subdivision or occupation of the development.

<u>*Reason*</u>:- to ensure that adequate water and sewer services can be provided to the site.

122. <u>Stamping of development application plans by Sydney Water</u>

The approved development application plans must be submitted to a Sydney Water <u>Quick Check agent or</u> Customer Centre to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements and if further requirements need to be met. Plans will be appropriately stamped.

Please refer to the web site www.sydneywater.com.au for:

- Quick Check agents details see Building Developing and Plumbing then Quick Check; and
- Guidelines for Building Over/Adjacent to Sydney Water Assets see Building Developing and Plumbing then Building and Renovating

or telephone 13 20 92.

Note:

The consent authority or accredited certifier must either:

- ensure that a Quick Check agent/Sydney Water has appropriately stamped the plans before the issue of any Construction Certificate; or
- if there is a combined Development/Construction Certificate application, ensure that a Quick Check agent/Sydney Water has appropriately stamped the plans prior to works commencing on site.

<u>*Reason*</u>:- to ensure the development does not damage or interfere with Sydney Water assets.

123. Aboveground Power Lines

Where practicable, all existing overhead power lines adjacent to the development site shall be relocated underground to Energy Australia standards and specifications. If not practicable to relocate the power lines underground, arrangements shall be made with Energy Australia to place the conduit to carry those power lines underground so that they can be utilized at a later date by Energy Australia. In this regard all associated costs shall be borne by the applicant.

<u>*Reason:*</u>- to improve the aesthetic quality of the area.

124. Mail Box Structure

An Australia Post approved lockable mail box structure(s) shall be centrally located to the primary street entry of the site.

<u>*Reason*</u>:- to ensure compliance with Council's Development Control Plan requirements.

125. No Advertising Approved

Advertising structures or signs shall not be erected, affixed, painted or displayed without prior Council consent.

<u>*Reason*</u>:- to prevent the proliferation of signs which will result in a degradation of the visual quality of the area.

126. Fencing/Gates and Adjoining Land

There must be no encroachment of any part of the structure/s onto the adjoining premises or onto Council's road reserve, footway or public place. Any gate openings shall be constructed so that the gates, when hung, will be fitted in such a manner that they will not open over the footway or public place.

<u>*Reason*</u>:- to ensure the fence/gates do not restrict access and that encroachments do not occur.

127. Graffiti and Vandalism Rectification

Should the external fabric of the building(s), walls to landscaped areas and like constructions be subject to graffiti or like vandalism, then within seven (7) days of this occurrence, the graffiti must be removed and the affected surface(s) returned to a condition it was in before defilement.

<u>*Reason*</u>:- to ensure graffiti and vandalism is removed from premises in a timely manner and to protect the visual appearance of the area.

128. Cleaning of facade

The owner/manager of the building shall ensure that all windows on the facade, and the facade itself, of the premises are cleaned regularly and, in any event, not less than twice in an annual period.

<u>*Reason*</u>:- to ensure regular maintenance and cleaning to the exterior of the premises.

129. <u>Telecommunications Facilities - Residential</u>

The following requirements apply to telecommunication facilities in the building:-

- a) Appropriate access and space within the plant area of the building shall be provided for a minimum of three telecommunication carriers or other providers of broad-band access by ground or satellite delivery.
- b) Appropriate ducting and cabling shall be provided for a minimum of three telecommunication carriers or other providers for telecommunication access and broad-band cabling to each apartment of the building.
- c) The details of (a) and (b) above shall be submitted for the approval of the certifying authority, prior to issue of a construction certificate for the building under the Environmental Planning and Assessment Act 1979.
- d) A separate Development Application must be submitted at the appropriate time for any external receiving device proposed to be installed. For each form of transmitter, there shall be only one common receiving device installed on the subject development.

<u>Reason:</u>- to ensure adequate provision for telecommunication facilities within the development.

130. Lighting to Publicly Accessible Areas

The following lighting requirements shall be complied with:

- a) The public areas shall be provided with lighting to ensure pedestrian safety. Such lighting shall be at a minimum level of 10 lux in the horizontal and vertical plane.
- b) Details of the lighting is to be submitted for the approval of the Principal Certifying Authority prior to issue of the Construction Certificate and location of the lighting endorsed on the construction drawings.

<u>*Reason*</u>:- to ensure publicly accessible areas of the development are provided with sufficient illumination.

131. Lighting – External Flood Lights

Exterior wall mounted flood lights shall be illuminated to a maximum level of between 25 and 50 lux at ground level. Should any substantive complaints be received or should the proposed lighting have an adverse impact on residential amenity, Council reserves the right to request modifications to the lighting arrangements.

<u>*Reason*</u>:- to ensure that external lighting does not result in any adverse impact on surrounding properties, including residential land.

132. Suitable Arrangements for Garbage and Recycling Services

Suitable arrangements for garbage and recycling services are to be made with Council prior to occupation of the building.

<u>*Reason*</u>:- to ensure adequate garbage and recycling services are provided for the development.

133. Garbage Storage and Collection

All garbage shall be removed from the site directly via the basement/at grade garbage storage area. Garbage bins shall not be stored on or collected from the footpath or kerb.

<u>*Reason*</u>:- to ensure that all garbage storage and collection is managed efficiently and without significant impact on the street.

134. Contract for Waste Collection

Prior to occupation of the premises the operator shall enter into a commercial contract for the collection of trade waste and recyclables generated at the premises. A copy of all contracts and receipts shall be kept on the premises and made available to Council Officers on request.

<u>*Reason*</u>: to ensure suitable arrangements are in place for the collection of trade waste and recyclables arising from the premises.

135. Waste And Recyclables Storage Area

The waste and recyclable storage area shall be fully enclosed, adequately ventilated and constructed with a concrete floor and concrete or cement rendered walls covering the floor. The floor shall be graded to an approved sewer connection incorporating a sump and galvanised grate cover or basket. A hot and cold hose cock shall be provided within the room. Details shall be provided with the Construction Certificate and endorsed on the construction drawings, and works completed prior to the issue of an Occupation Certificate.

<u>*Reason:*</u>- to ensure the waste and recyclables storage area is appropriately constructed and able to be readily cleaned and maintained.

136. Ongoing Waste Management

Ongoing waste management within the development shall be carried out in accordance with the approved Waste Management Plan and the following requirements:-

a) Appropriate waste management practices are to be adopted within the

development at all times.

- b) The waste storage room shall be kept in a clean, tidy and hygienic condition at all times.
- c) The waste and recyclable storage area shall be fully enclosed, adequately ventilated and constructed with a concrete floor and concrete or cement rendered walls covering the floor. The floor shall be graded to an approved sewer connection incorporating a sump and galvanised grate cover or basket. A hot and cold hose cock shall be provided within the room. Details shall be provided with the Construction Certificate and endorsed on the construction drawings, and works completed prior to the issue of an Occupation Certificate.
- d) A person shall be employed/nominated to manage the collection of waste material by Council, including, but not limited to bin placement at the road edge and retrieval of bins soon after collection of contents, cleansing of bins, storage of bins in the compound and the like.
- e) The nature strip is to be kept in a clean and tidy condition upon garbage collection.

<u>*Reason:*</u>- to ensure appropriate ongoing waste management practices within the development in accordance with Council's Development Control Plan requirements.

137. Submission of Works-as-Executed Fire Services Plan

A *works-as-executed* fire services plan is to be submitted to the Council **prior to occupation** of the development, detailing the location of the essential fire safety measures installed within the building premises.

<u>*Reason*</u>:- to ensure a record of the location and type of fire safety services is documented.

138. Occupation Certificate

A person must not commence occupation or use of the whole or part of a new building unless an occupation certificate has been issued in relation to the building or part.

The application for an Occupation Certificate must be made to the Principal Certifying Authority (Council or an accredited certifier) using the approved form.

<u>*Reason*</u>:- to comply with the requirements of Section 109M/N of the Environmental Planning and Assessment Act.