

## CONDITIONS OF DEVELOPMENT CONSENT

---

**DA No:** DA-357/2013  
**Property:** 32 Parramatta Road, LIDCOMBE NSW 2141  
**Description:** Demolition of existing site improvements and construct a four (4) to eight (8) storey hotel development with commercial premises, two function rooms, one restaurant and associated car parking, landscaping and stormwater works.

---

### 1 Approved Plans

The development is to be carried out in accordance with the approved stamped plans as numbered below:

Plan Number	Prepared By	Revision No.	Dated
Cover Page	Urbanlink Pty Ltd	B	4/1/2014
Site Plan Drawing Number 001	Urbanlink Pty Ltd	B	4/7/2014
Site Analysis Drawing Number 002	Urbanlink Pty Ltd	B	4/7/2014
Lower Basement Drawing Number 100	Urbanlink Pty Ltd	C	3/10/2014
Basement Drawing Number 101	Urbanlink Pty Ltd	C	3/10/2014
Lower Ground Floor Drawing Number 102	Urbanlink Pty Ltd	C	3/10/2014
Ground Floor Plan Drawing Number 103	Urbanlink Pty Ltd	C	3/10/2014
First Floor Plan Drawing Number 104	Urbanlink Pty Ltd	B	4/7/2014
Second Floor Plan Drawing Number 105	Urbanlink Pty Ltd	B	4/7/2014
Third Floor Plan Drawing Number 106	Urbanlink Pty Ltd	B	4/7/2014
Fourth Floor Plan Drawing Number 107	Urbanlink Pty Ltd	B	4/7/2014
Fifth Floor Plan Drawing Number 108	Urbanlink Pty Ltd	B	4/7/2014

Sixth Floor Plan Drawing Number 109	Urbanlink Pty Ltd	B	4/7/2014
Roof Plan Drawing Number 110	Urbanlink Pty Ltd	B	4/7/2014
North east Elevations Drawing Number 201	Urbanlink Pty Ltd	B	4/7/2014
South West Elevations Drawing Number 202	Urbanlink Pty Ltd	B	4/7/2014
Sections AA and BB Drawing Number 301	Urbanlink PTY	B	4/7/2014
Colours and Finishes Drawing Number 501	Urbanlink PTY	B	4/7/2014
Site and Roof Drainage Plan Drawing Number 13MB5729/D01	United Consulting Engineers Pty Ltd	C	22/9/2014
Lower Ground Floor Drainage Plan 13MB5729/D02	United Consulting Engineers Pty Ltd	C	22/9/2014
Basement Drainage Plan 13MB5729/D03	United Consulting Engineers Pty Ltd	C	22/9/2014
Drainage Details 13MB5729/D04	United Consulting Engineers Pty Ltd	C	22/9/2014
Soil and Water Management Plan Drawing Number 13MB5729/C01	United Consulting Engineers Pty Ltd		11/9/2013
Proposed Landscape Plan L/01	JEC Management Pty Ltd		23/8/2013
Proposed Landscape Plan L/02	JEC Management Pty Ltd		23/8/2013
Proposed Landscape Plan L/03	JEC Management Pty Ltd		23/8/2013

<b>Plan Number</b>	<b>Prepared By</b>	<b>Revision Number</b>	<b>Date</b>
Waste Management Plan	Urbanlink Pty Ltd		November 2013
Acoustic Report Traffic Noise Reference Number 2013-357	Acoustic Solutions Pty Ltd		September 6 201

Acoustic Report for Proposed Hotel and Restaurant Reference Number 2013-357	Acoustic Solutions Pty Ltd		June 27 2014
Section J Report (Design Statement)	Aminga Holdings Pty Ltd		10 July 2014
Hydraulic Design Statement	CBS Engineers		24/6/2014
Statement of Compliance - Access for People with a Disability	Accessible Building Solutions	C	25/10/2013
Preliminary Geotechnical Investigation Report Number 13/1553	SMEC Testing Services Pty Ltd		August 2013
Crime Risk Analysis Report	Urbanlink Pty Ltd		October 2013
Phase 2 Environmental Site Audit	Benviron Group		May 2014

except as otherwise provided by the conditions of this determination (Note:- modifications to the approved plans will require the lodgement and consideration by Council of a modification pursuant to Section 96 of the Environmental Planning and Assessment Act).

Reason:- to confirm and clarify the terms of Council's approval.

## 2. **Time period of consent**

This consent shall lapse five (5) years from the date of determination unless the approved building, engineering or construction work has been physically commenced in accordance with this consent.

Development consent for the use of land does not lapse if the approved use of any land, building or work is actually commenced prior to the date on which the consent would otherwise lapse.

Reason:- to satisfy the requirements of Section 95 of the Environmental Planning and Assessment Act.

## 3. **Auburn DCP 2007: Section 94 Development Contributions**

Development Contributions are payable in accordance with Auburn Council Council's Section 94 Development Contribution Plan 2007, which has been prepared under Section 94 of the Environmental Planning and Assessment Act 1979, as amended.

The amounts payable will be adjusted in accordance with the section titled Review of Contribution rates and are generally indexed on a quarterly basis by the Consumer Price Index CPI (all Groups Sydney) unless otherwise stated in the plan.

Contributions will be adjusted at the payment date in accordance with the plan and

payment is to be made prior to the issue of any Occupation Certificate.

Council's Development Contribution Plan 2007 is available for inspection at Council's Customer Services Centre, Civic Place, 1 Susan Street, Auburn or on line at [www.auburn.nsw.gov.au](http://www.auburn.nsw.gov.au).

A sum of \$429,932.11 is to be paid to Council for the purpose of the provision of additional services and public facilities that is likely to generate from employment generating development with the Auburn LGA.

The above sum is broken down to the following items:

Item	Amount
Employment Generating Development	\$429,932.11
<b>TOTAL</b>	<b>\$429,932.11</b>

Reason:- to ensure that the development complies with the Auburn DCP 2007: Section 94 Development Contributions.

4. **Submission of Construction Certificate**

Construction works are not to commence until such time that a construction certificate for the proposed works has been issued by Council or an Accredited Certifier.

**NOTES:**

Where an Accredited Certifier issues a construction certificate, a copy of the following documents must be forwarded to Council within 7 days of issue, together with payment of the Council's adopted registration fee: determination; application to which it relates; construction certificate issued; plans and specifications; any fire safety schedule; and any other documents lodged with the certificate.

Any modification involving building works to the approved development made under Section 96 of the Environmental Planning and Assessment Act 1979 requires the submission of an amended construction certificate.

Reason:- to comply with the requirements of Section 81A of the Environmental Planning and Assessment Act and clause 142 of the Environmental Planning and Assessment Regulation 2000.

5. **Application for a Liquor License**

If liquor is to be served on the premises, a liquor license must be obtained. In this regard, the proprietor / applicant shall make an application to the New South Wales Liquor Licensing Court for a Liquor License to permit the sale of liquor on the premise.

A copy of the Court approved Liquor License shall be submitted to the Council prior to the sale of liquor on the premises.

Reason:- a Liquor License must be obtained from the Liquor Licensing Court prior to the sale of liquor at the premises.

6. **Consolidation of lots**

The individual lots are to be consolidated into a single parcel. Written evidence of registration of consolidation by the Land and Property Information Office is to be submitted to Council prior to the granting of the occupation certificate.

*Reason:-* to ensure the whole of the land essential to the proper operation of the development is preserved.

7. **No alteration without prior Council approval**

The completed building is not to be altered externally in character or colour without the prior consent of Council.

*Reason:-* to ensure the external appearance of the development is not obtrusive or offensive and does not degrade the visual quality of the surrounding area.

8. **No laundries approved within the hotel rooms**

The laundries shown within the hotel rooms are to be deleted. The space created via the removal of the laundries may be used as a "Wet bar" area or storage space.

The details showing the changes shall be shown in the construction certificate for approval by Council or the accredited certifier.

*Reason:-* to prevent the hotel rooms from becoming serviced apartments.

9. **Building not to be adapted for another use**

The building is to be used for a hotel and function centre only and is not to be altered or adapted for another use without the prior consent of Council.

*Reason:-* the building has only been approved for this use and other uses require a separate approval of Council.

10. **Appointment of Principal Certifying Authority/Notice of Commencement of Work**

Site works are not to commence until:-

- a) a construction certificate for the building work has been issued by the consent authority, and
- b) the person having the benefit of the development consent has:-
  - i) appointed a principal certifying authority for the building work, and
  - ii) notified the principal certifying authority that the person will carry out the building work as an owner-builder, if that is the case, and
- b1) the principal certifying authority has, no later than 2 days before the building work commences:-
  - i) notified the consent authority and the council (if the council is not the consent authority) of his or her appointment, and
  - ii) notified the person having the benefit of the development consent of any

critical stage inspections and other inspections that are to be carried out in respect of the building work, and

- b2) the person having the benefit of the development consent, if not carrying out the work as an owner-builder, has:-
  - i) appointed a principal contractor for the building work who must be the holder of a contractor licence if any residential building work is involved, and
  - ii) notified the principal certifying authority of any such appointment, and
  - iii) unless that person is the principal contractor, notified the principal contractor of any critical stage inspections and other inspections that are to be carried out in respect of the building work, and
- c) the person having the benefit of the development consent has given at least 2 days' notice to the council of the person's intention to commence the erection of the building.

Reason:- to comply with the requirements of Section 81A of the Environmental Planning and Assessment Act.

#### 11. **Principal Certifying Authority**

- 1) The person having the benefit of a development consent or complying development certificate for development involving building work or subdivision work may appoint the consent authority, the council or an accredited certifier as the principal certifying authority for the development.
- 1A) Despite subsection (1), such an appointment may not be made by any contractor or other person who will carry out the building work or subdivision work unless the contractor or other person is the owner of the land on which the work is to be carried out.
- 2) Despite subsection (1), an accredited certifier must not be appointed as the principal certifying authority for development involving subdivision work unless the subdivision to which the work relates is of a kind identified by an environmental planning instrument as one in respect of which an accredited certifier may be a certifying authority.
- 3) A principal certifying authority for building work or subdivision work to be carried out on a site is required to be satisfied:-
  - a) that a construction certificate or complying development certificate has been issued for such of the building work or subdivision work as requires development consent and over which the principal certifying authority has control, before the work commences on the site, and
  - b) that the principal contractor for the work is the holder of the appropriate licence and is covered by the appropriate insurance, in each case if required by the *Home Building Act 1989*, before any residential building work over which the principal certifying authority has control commences on the site, unless the work is to be carried out by an owner-builder, and
  - c) that the owner-builder is the holder of any owner-builder permit required under the *Home Building Act 1989*, before an owner-builder commences on the site any residential building work over which the principal certifying

- d) authority has control, and that building work or subdivision work on the site has been inspected by the principal certifying authority or another certifying authority on such occasions (if any) as are prescribed by the regulations and on such other occasions as may be required by the principal certifying authority, before the principal certifying authority issues an occupation certificate or subdivision certificate for the building or work, and
  - e) that any preconditions required by a development consent or complying development certificate to be met for the work before the issue of an occupation certificate or subdivision certificate have been met, before the principal certifying authority issues the occupation certificate or subdivision certificate.
- 4) A principal certifying authority must also comply with such other requirements of a like or different nature as may be imposed on principal certifying authorities by the regulations.

**Note.** Section 81A prohibits the commencement of building work or subdivision work unless the consent authority has been notified of the appointment of a principal certifying authority for the work. Section 109D (2) prohibits the issue of an occupation certificate authorising the occupation and use of a new building except by the principal certifying authority appointed for the erection of the building. Section 109D (3) prohibits the issue of a subdivision certificate for a subdivision involving subdivision work except by the principal certifying authority appointed for the carrying out of the subdivision.

Reason:- to comply with the requirements of Section 109E of the Environmental Planning and Assessment Act.

12. **Provision of Street Numbers**

A street number is to be displayed in a prominent position at the entrance to the premises. Numbers are to be of a colour contrasting with the wall to which they are affixed.

Reason:- to clearly identify the street number of the property.

13. **Compliance with the Building Code of Australia**

All building work must be carried out in accordance with the requirements of the Building Code of Australia.

Reason:- to ensure compliance with the requirements of the Building Code of Australia and to comply with Clause 98 of the Environmental Planning and Assessment Regulation 2000.

14. **Disabled Access & Facilities**

Access and facilities for people with disabilities must be provided in accordance with the relevant requirements of the Building Code of Australia (for all new building work) and in addition, with the relevant requirements of the 'Disability (Access to Premises - Building) Standards 2010' (including for existing buildings, whether or not any works are proposed). Details of the proposed access, facilities and car parking for people with disabilities are to be included in the plans/specifications for the

**construction certificate.**

Reason:- to ensure compliance with the requirements of the Building Code of Australia.

15. **Commonwealth Disability Discrimination Act**

The Commonwealth Disability Discrimination Act 1992 commenced the 'Disability (Access for Premises - Buildings) Standards 2010' on 1 May 2011 and now applies to all new buildings and affected parts of existing buildings. Submission and/or approval of this application does not imply or confer compliance with either the Act or the new Access Standard. Applicants should satisfy themselves and make their own inquiries to the Human Rights and Equal Opportunity Commission.

Reason:- to provide advice on the requirements of the Commonwealth Disability Discrimination Act 1992.

16. **Replacement of Principal Certifying Authorities**

Unless the relevant authority so approves in writing, a person may not be appointed to replace another person as the principal certifying authority for development.

A principal certifying authority appointed to replace another principal certifying authority must ensure that notice of the appointment and of the approval of that appointment is given to the consent authority (and, if the consent authority is not the council, to the council) within 2 days of the appointment.

Reason:- to comply with the requirements of Section 109EA of the Environmental Planning and Assessment Act and clause 162 of the Environmental Planning and Assessment Regulation.

17. **Notice to Allow Inspections**

To allow a principal certifying authority or another certifying authority time to carry out critical stage inspections or any other inspections required by the principal certifying authority, the principal contractor for a building site, or the owner-builder, must notify the principal certifying authority at least 48 hours before building work is commenced at the site if a critical stage inspection is required before the commencement of the work.

Reason:- to comply with the requirements of Clause 163 of the Environmental Planning and Assessment Regulation.

18. **Erection of Signs**

A rigid and durable sign must be erected in a prominent position on any site on which building work, subdivision work or demolition work is being carried out:-

- a) showing the name, address and telephone number of the principal certifying authority for the work, and
- b) showing the name of the principal contractor (if any) for any building work and a telephone number on which that person may be contacted outside working hours, and
- c) stating that unauthorised entry to the work site is prohibited.



Any such sign is to be maintained while the building work, subdivision work or demolition work is being carried out, but must be removed when the work has been completed.

Note: Principal certifying authorities and principal contractors must also ensure that signs required by this clause are erected and maintained (see clause 227A which currently imposes a maximum penalty of \$1,100.

Reason:- to comply with the requirements of Clause 98A and 136B of the Environmental Planning and Assessment Regulations.

19. **Separate Development Consent**

No signs, whether for advertising, directory or identification purposes or for any other purpose, are to be erected on the land without the written consent of Council having first been obtained.

Reason:- to limit and control advertising.

20. **Construction/Demolition Hours**

Site works, building works and demolition works, including the delivery of materials or equipment to and from the property are to be carried out between the hours of 7.00 am and 6.00 p.m. only from Mondays to Fridays and between 8.00 am and 4.00 p.m. only on Saturdays. No construction works or deliveries for the construction are to take place on Sundays or public holidays.

Prior to commencement of any demolition or construction work the applicant is to erect signs on the site, which are clearly visible from the footpaths adjoining the site boundaries, which state the permitted construction/demolition hours. These signs must also state "Any instances of site works, building works, demolition works or deliveries outside the permitted hours can be reported to Auburn Council on 9735-1222 during office hours or 0417-287-113 outside office hours".

Reason:- to reduce nuisance to the surrounding properties during the construction period.

21. **Information required prior to the issue of Construction Certificate**

The following documentation (where applicable) is to be submitted to Council or the accredited certifier, **prior to the granting of the construction certificate:**

- a) Detailed building plans and specifications containing sufficient information to verify that the completed building will comply with the Building Code of Australia.
- b) A list of any proposed fire safety measures provided in relation to the land or any existing building on the land (*not applicable to dwellings or outbuildings*).
- c) A report prepared by a *professional engineer* detailing the proposed methods of excavation, shoring or pile construction, and what measures are to be implemented to prevent damage from occurring to adjoining or nearby premises as a result of the proposed excavation works. (NOTE: Any practices or procedures specified to avoid damage to adjoining or nearby premises are to be incorporated into the plans and specifications for the construction

- certificate).
- d) Method of ventilating the basement car park. (Note: If mechanical ventilation is required, mechanical ventilation plans shall be submitted that also confirm the minimum height clearances specified by AS 2890.1 - Car parking, will be achieved).
- e) A suitable security door being placed within the travel path situated between the two store rooms on the Lower Ground Floor. The security door shall align with the store rooms front windows / walls to ensure an entrapment space is not created within the undercroft area.

Reason:- to ensure that adequate information is submitted to enable assessment or that the development can proceed with the concurrence of others.

22. **Infrastructure Fee**

The infrastructure inspection fee in accordance with Councils Fees and Charges Schedule shall be paid prior to the issue of the Construction Certificate.

Reason:- to contribute to the cost of inspection and identification of any damage to Council's infrastructure as a result of the development.

23. **Maintain plans on-site**

A copy of the construction certificate, the approved plans & specifications and development consent conditions must be kept on the site at all times and be available to the Council officers upon request.

Reason:- to ensure a record of the approved plans are readily available.

24. **PCA - Inspection of works - general & site management**

The building works are to be inspected by the principal certifying authority (or other suitably qualified person on behalf of the applicant if permitted by the PCA) to monitor compliance with Council's approval and the relevant standards of construction.

Documentary evidence of compliance with Council's approval and relevant standards of construction is to be maintained by the principal certifying authority.

Upon inspection of each stage of construction, the principal certifying authority (or other suitably qualified person on behalf of the applicant) is also required to ensure that adequate provisions are made for the following measures (*as applicable*), to ensure compliance with the terms of Council's approval:

- Sediment control measures
- Provision of perimeter fences or hoardings for public safety and restricted access to building sites.
- Maintenance of the public place free from unauthorised materials, waste containers or other obstructions.

**ADVISORY NOTE**

*If Council is appointed as the PCA, the following critical inspections (as applicable to the development), must be arranged:*

- a) *Prior to the commencement of Building Works, ensure erosion controls PCA and the Builders signs are displayed and a temporary toilet is located on site.*
- b) *The pier holes before they are filled with concrete.*
- c) *The foundation material prior to covering.*
- d) *The steelwork when in position and before concrete is poured (footings, lintels, beams, columns, floors, walls, retaining walls or the like).*
- e) *The dampcourse level, ant capping and floor timbers before the floor materials are laid.*
- f) *The framework including roof members when completed and prior to the fixing of any internal sheets.*
- g) *Prior to covering waterproofing in any wet area.*
- h) *Fire resisting construction before concealment.*
- i) *Upper floor beams and joists before the fixing of any flooring material.*
- j) *The rainwater drainage lines within the property boundaries when completed and before covering.*
- k) *The swimming pool safety fence prior to filling the pool with water.*
- l) *Foundation material before installation of the swimming pool or laying of any bedding material.*
- m) *Pool shell reinforcement including pool coping.*
- n) *Final inspection.*

*A minimum of 48 hours notice must be provided to Council to enable the following inspections to be carried out during the course of construction.*

Reason:- to ensure the development is adequately monitored during the construction phase.

**25. Items not to be placed on roadway**

The following items must not be placed on the footpath, roadway or nature strip at any time:-

- a) Building materials, sand, waste materials or construction equipment;
- b) Bulk bins/waste skips/containers; or
- c) Other items that may cause a hazard to pedestrians.

Reason:- to ensure the public is not inconvenienced, placed in danger and to prevent harm to the environment occurring.

**26. Sign to be erected concerning unauthorised entry to the site**

A sign must be erected in a prominent position stating that unauthorised entry to the site is not permitted. The sign must also name the builder or other person responsible for the site and a telephone number at which the builder or other person can be contacted outside working hours. Where Council is not the Principal Certifying Authority, the sign shall also display the name and contact details of the nominated Principal Certifying Authority. The sign is to be removed when the building works have been completed.

Reason:- to restrict public access to the site and to provide suitable contact details in a clear and conspicuous position.

**27. Toilet accommodation for people working at the site**

Suitable toilet accommodation is to be provided at the work site at all times. If temporary toilet accommodation is proposed, it must:-

- Have a hinged door capable of being fastened from both inside and outside,
- Be constructed of weatherproof material,
- Have a rigid and impervious floor; and
- Have a receptacle for, and supply of, deodorising fluid.

Reason:- to ensure suitable toilet accommodation is provided for workers.

## 28. **Survey Report**

A Registered Surveyors check survey certificate is to be forwarded to the Principal Certifying Authority (and a copy is to be forwarded to the Council, if the Council is not the principal certifying authority), detailing compliance with Council's approval at the **following stages of construction:**

*(Setbacks and levels at commencement)*

- a) Prior to construction of the first completed floor/floor slab (prior to pouring of concrete), showing the area of land, building and boundary setbacks and verifying that the building is being constructed at the approved levels.

*(Setbacks and levels at completion)*

- b) On completion of the erection of the building showing the area of the land, the position of the building and boundary setbacks and verifying that the building has been constructed at the approved levels.

Reason:- to ensure each stage of the development complies with the approved plans.

## 29. **Excavated and Filled Areas**

All excavated and filled areas shall be battered to a slope not steeper than two (2) horizontal to one (1) vertical and the fill area shall continue a minimum of one metre past the edge of the house, or similarly be retained in accordance with a retaining wall detail approved by Council. In the event that the retaining wall exceeds 600 mm when measured vertically from the base of the cut, the wall shall be designed by a practicing Structural Engineer, the details submitted to Council, and approved prior to work commencing.

Reason:- to adequately retain excavated and filled areas and prevent soil movement, which may be detrimental to the subject or adjoining premises.

## 30. **Fencing of Construction Sites - Rental details to be provided to the PCA**

Public access to the site and building works, materials and equipment on the site is to be restricted, when work is not in progress or the site is unoccupied.

A temporary hoarding or fence is to be provided to protect the public, located to the perimeter of the site (unless the site is separated from the adjoining land by an existing structurally adequate fence, having a minimum height of 1.5 metres). Hoardings or fences are to have a minimum height of 1.8 metres and be constructed

of solid plywood sheeting (painted white) or of cyclone wire fencing with geotextile fabric attached to the inside of the fence, to provide dust control.

Hoardings or fences are to be structurally adequate and be constructed in a good and workmanlike manner and the use of poor quality materials or steel reinforcement mesh as fencing is not permissible.

The public safety provisions and temporary fences must be in place prior to the commencement of any demolition, excavation or building works and be maintained throughout construction.

**NOTE: Should ANY part of the fence or hoarding encroach beyond the boundaries of the site, it will be necessary to:-**

- **Make payment to Council for the rental of the road reserve area in accordance with Council's adopted charges (per metre per month - minimum 3 months) BEFORE the fence/hoarding is erected.**
- **Supply evidence that the road reserve rental fee has been paid to the PCA and to any authorised Council officer.**
- **Comply with Council's specifications for the erection of Class A or B Hoardings.**

Reason:- to provide protection to public places and to prevent unauthorised access to the site.

### 31. **Sedimentation Control**

Prior to the commencement of site works, the following measures are to be implemented on the site to assist with sedimentation control during the construction phase of the project:-

- a) A sediment-trapping fence using a geotechnical fabric specifically designed for such purpose and installed to manufacturer's specifications is to be placed below the construction area.
- b) Vegetation and/or existing building structures will be cleared from the construction site only, other areas to remain undisturbed.
- c) Restricting vehicle access to one designated point and having these driveways adequately covered at all times with blue metal or the like.
- d) A vehicle wheel wash, cattle grid, wheel shaker or other appropriate device, shall be installed prior to commencement of any site works or activities, to prevent mud and dirt leaving the site and being deposited on the street.
- e) Building operations such as brick cutting, washing tools or brushes and mixing mortar are not permitted on public roadways or footways or in any other locations which could lead to the discharge of materials into the stormwater drainage system.
- f) Stockpiles of topsoil, sand, aggregate, soil or other material shall not be located on any drainage line or easement, natural watercourse, footpath or roadway and shall be protected with adequate sediment controls.
- g) The installation of gutters, downpipes, and the connection of downpipes to the stormwater disposal system prior to the fixing of the roof cladding.

Such measures are to be maintained at all times to the satisfaction of Council and the Principal Certifying Authority. **Failure to do so may result in the issue of**

**penalty infringement notices.**

Reason:- to minimise soil erosion and control sediment leaving the site during construction and to prevent water pollution from occurring.

32. **Display of a warning sign for soil and water management**

Throughout the construction/remediation/demolition period, a warning sign for soil and water management must be displayed on the most prominent point of the building site, visible to both the street and site works.

Reason:- to ensure all building workers are aware of the need to maintain the sediment and erosion control devices.

33. **Engineering Design - Basement Excavation**

The following engineering details or design documentation (where appropriate) shall be submitted to the Principal Certifying Authority (Council or accredited certifier) **prior to the issuing of a construction certificate:-**

- a) Documentary evidence prepared by a suitably qualified *professional geotechnical engineer* shall be submitted to the certifying authority, that confirms the suitability and stability of the site for the proposed excavation and building as well as certifying the suitability and adequacy of the proposed design and construction of the building for the site.
- b) A report shall be prepared by a *professional engineer* and submitted to the certifying authority prior to the issuing of a construction certificate, detailing the proposed methods of excavation, shoring or pile construction, including details of vibration emissions and detailing any possible damage which may occur to adjoining or nearby premises that may be caused by the proposed building and excavation works.

Any practices or procedures specified in the engineer's report in relation to the avoidance or minimisation of structural damage to nearby premises, are to be fully complied with and incorporated into the plans and specifications for the **construction certificate**.

A copy of the engineer's report is to be submitted to the Council, if the Council is not the certifying authority.

- c) Driven type piles/shoring **must not be provided** unless a geotechnical engineer's report is submitted to the certifying authority, **prior to the issuing of a construction certificate**, which states that damage should not occur to any adjoining premises and public place as a result of the works.
- d) The installation of ground or rock anchors underneath any adjoining premises including (a public roadway or public place) must not be carried out without the specific written consent of the owners of the affected adjoining premises and (where applicable) details of compliance must be provided to the certifying authority **prior to the commencement of any excavation or building works**.

Reason:- to ensure the proposed method of excavation is suitable for the site and to prevent damage from occurring to adjoining premises.

34. **Excavations extending below the base of footings of adjoining development**

Where excavations extend below the level of the base of the footings of a building on an adjoining allotment of land, the person causing the excavation must preserve and protect the building from damage and, if necessary, underpin and support the adjoining building in an approved manner. The person causing the excavation must give the owner of the adjoining property at least seven (7) days written notice of its intention to excavate below the level of the base of the footing. The person must also furnish the adjoining property owner with particulars of the proposed work.

Reason:- to ensure the support for neighbouring buildings.

35. **Dilapidation Report - Prior to Excavation of Basement**

- (a) A dilapidation report prepared by a *professional engineer* or suitably qualified building professional shall be submitted to the Principal Certifying Authority **prior to the commencement of demolition, excavation or building works.**

The report shall detail the current condition and status of all buildings, including ancillary structures (*i.e. including dwellings, residential flat buildings, commercial/industrial building, garages, carports, verandahs, fences, retaining walls, swimming pools and driveways etc.*) located upon all of the premises adjoining the subject site.

The report is to be supported with photographic evidence of the status of the buildings and a copy of the report must also be forwarded to the Council and to the owners of each of the above stated premises, prior to the commencement of any works. The applicant shall bear the full cost of this report.

- (b) Notwithstanding (a) above, certification by a practicing professional engineer in lieu of a dilapidation report may be provided **prior to the commencement of demolition, excavation or building works** certifying that the demolition, excavation and or building works will not have an impact on **any** adjoining structure including ancillary structures (*i.e. including dwellings, residential flat buildings, commercial/industrial building, garages, carports, verandahs, fences, retaining walls, swimming pools and driveways etc.*).

The applicant shall bear the full cost of this certification and the Council or Principal Certifier reserves the right to request a full report as described in (a) above should the certification provided by the engineer be considered unacceptable or insufficient.

Reason:- to enable the monitoring of any potential damage that may be caused to adjoining premises as a result of excavating and building in close proximity to the adjoining premises.

36. **Footpath area to be illuminated**

Where any hoarding or awning is constructed over the public place, the footpath area shall be kept illuminated between sunset and sunrise.

Reason:- to ensure the safety of pedestrians when passing the site.

37. **Fencing of construction sites - Rental details to be provided to the PCA (A & B Type Hoardings)**

A separate application is to be made to Council for Approval under Section 68 of the Local Government Act 1993 to erect any hoarding or scaffolding in a public place and such application is to include:

- A payment to Council for the following fees in accordance with Council's adopted charges:
  - Hoarding/Structure Application Fee
  - Rental of Footpath Area (per metre per month - minimum 3 months rental)
  - Footpath Bond
- Submit the following documents to Council with your application:
  - Certificate of Currency for Public Liability Insurance
  - Certificate of Currency for Worker's Compensation Insurance
  - Letter indemnifying Council against claims and expenses made in relation to the existence of the structure and/or traffic provisions
  - Traffic/Pedestrian Control Plan
  - In respect to any required Type B Hoarding, structural certification prepared and sign by an appropriately qualified practising Structural Engineer
- Comply with Council's specifications for the erection of Class A Hoardings.
- Supply evidence to the PCA and to any authorised Council officer that the road reserve rental fee has been paid.

Note: Public access to the site and building works, materials and equipment on the site is to be restricted, when work is not in progress or the site is unoccupied.

A temporary hoarding or fence is to be provided to protect the public, located to the perimeter of the site (unless the site is separated from the adjoining land by an existing structurally adequate fence, having a minimum height of 1.5 metres). Hoardings or fences are to have a minimum height of 1.8 metres and be constructed of solid plywood sheeting (painted white) or of cyclone wire fencing with geotextile fabric attached to the inside of the fence, to provide dust control.

Note: A "B Class" overhead type hoarding is required to be provided to protect the public, located adjacent to the development, prior to the commencement of any works on the site which comprise:

- Any works or hoisting of materials over a public footway or adjoining premises, or
- Any building or demolition works on buildings which are over 7.5 metres in height and located within 3.6 metres of the street alignment.

Hoardings or fences are to be structurally adequate and be constructed in a good and workmanlike manner and the use of poor quality materials or steel reinforcement mesh as fencing is not permissible.

The public safety provisions and temporary fences must be in place prior to the commencement of any demolition, excavation or building works and be maintained throughout construction. Details of the proposed hoardings or fences located upon the site are to be submitted to the PCA and the public safety provision and temporary fences must be in place prior to the commencement of any site works, demolition, excavation or building works and maintained throughout construction.



Reason:- to provide protection to public places, prevent unauthorised access to the site and a safe working environment.

38. **Soil and Water Management Plan - Large sites**

A Soil and Water Management Plan (also known as an Erosion and Sediment Control Plan) shall be prepared according to the NSW EPA's *Managing Urban Stormwater: Construction Activities*. This Plan shall be implemented prior to commencement of any site works or activities. All controls in the Plan shall be maintained at all times. A copy of the Soil and Water Management Plan must be kept on-site at all times and made available to Council officers on request.

Reason:- to ensure sediment and erosion controls are maintained during the construction process to prevent water pollution from occurring.

39. **Noise from construction activities**

Noise from construction activities associated with the development shall comply with the NSW Interim Construction Noise Guidelines (DECCW) 2009.

Reason:- to ensure noise arising from construction activities is in accordance with relevant legislation and Environment Protection Authority requirements.

40. **Dial before you dig**

Dial Before You Dig is a free national community service designed to prevent damage and disruption to the vast pipe and cable networks which provides Australia with the essential services we use everyday - electricity, gas, communications and water.

Before you dig call "Dial before you dig" on 1100 (listen to the prompts) or facsimile 1300 652 077 (with your street no./name, side of street and the distance to the nearest cross street) or register on line at [www.dialbeforeyoudig.com.au](http://www.dialbeforeyoudig.com.au) for underground utility services information for any excavation areas.

The Dial Before You Dig service is also designed to protect Australia's excavators. Whether you are a back yard renovator, an individual tradesman or a professional excavator the potential for injury, personal liability and even death exists every day. Obtaining accurate information about your work site significantly minimises these risks.

Reason:- to ensure that essential services such as electricity, gas, communications and water are not affected by excavation or construction.

41. **Closed circuit television system (CCTV)**

A closed circuit television system shall be installed throughout the hotel complex to assist in reducing the incidence of crime and to improve the level of safety across the building. In addition:-

- Digital and monitored technology should be used to record images from the cameras.
- Installed surveillance equipment should be maintained in good working order and regularly tested.

Details shall be shown on the plans with the construction certificate for approval by Council or the accredited certifier.

Reason:- to improve the level of safety throughout the building complex.

42. **Signage to warn of security measures**

Warning signs shall be strategically posted around the perimeter of the property particularly near entry points to warn intruders of the security measures provided.

Directional signage shall be posted at decision making points such as entry / egress points to provide guidance to patrons.

Details shall be shown on the plans with the construction certificate for approval by Council or the accredited certifier.

Reason:- to improve the level of safety throughout the building complex.

43. **Fire Precautions during Construction**

Suitable means of fire-fighting must be installed to the degree necessary in the building under construction to allow initial fire attack by construction workers or for the fire brigade to undertake attack on the fire appropriate to the fire hazard and the height the building has reached during its construction.

Reason:- to ensure compliance with the Performance requirements EP1.5 of Part E1 Fire Fighting Equipment of BCA 2013 and to allow initial fire attack by construction workers or for the fire brigade to undertake attack on the fire.

Or

During the construction after the building has reached an effective height of 12 metres.

The required fire hydrants and fire hose reels must be operational in at least every storey that is covered by the roof or the floor structure above, except the two uppermost storeys and any required booster connections that must be installed.

Reason:- to ensure compliance with BCA 2013 E1.9 and to allow initial fire attack by construction workers or for the fire brigade to undertake attack on the fire.

44. **Submission of details and Works as Executed Fire Services Plan**

Further details and Works as Executed Fire Services Plan prepared by an appropriately qualified person is to be provided to Council for the following essential fire and life safety measures prior to the issue of the Occupation Certificate for the development:-

- Automatic Fire Suppression System.
- Fire hydrant system.
- Mechanical air handling system.

The details and information is to include but not limited to the following:-

A Works as executed fire services plan detailing the location of the essential fire and life safety measures installed within the building premises.

- Design and specification of the fire services.
- Consideration and recommendations report provided by Fire and Rescue NSW regarding the systems design and compliance (If applicable) and
- Applicable fire engineering solution report for the system.

Reason:- to ensure a record of the location and type of fire safety services is documented to ensure future compliance with the maintenance of the essential fire and life safety measures in accordance with the applied BCA requirements and relevant standards.

45. **Demolition of buildings**

The buildings shall only be demolished in accordance with the requirements of AS 2601-2001 "The Demolition of Structures".

Amongst others, precautions to be taken shall include compliance with the requirements of the WorkCover Authority of New South Wales, including but not limited to:-

- a) Protection of site workers and the general public.
- b) Erection of hoardings where appropriate.
- c) Asbestos handling and disposal where applicable.
- d) Any disused service connections shall be capped off to Council's requirements.
- e) The disposal of refuse is to be to an approved waste disposal depot.

Reason:- to ensure protection of the public, environment and to uphold public health standards. This also complies with the requirements of clause 92 of the Environmental Planning and Assessment Regulation 2000.

46. **Demolition - Lead Paint Disposal**

The demolition and disposal of materials incorporating lead such as lead paint and dustpaint shall be conducted in accordance with *AS2601-2001 Demolition of Structures*. Removal, cleaning and disposal of lead-based paint shall conform with relevant EPA guidelines including the *Lead Safe A renovator's guide to the dangers of lead*, NSW EPA, 1998. Hazardous dust shall not be allowed to escape from the site. Any existing accumulations of dust (eg; ceiling voids and wall cavities) shall be removed by the use of an industrial vacuum fitted with a high efficiency particulate air (HEPA) filter. All dusty surfaces and dust created from work shall be suppressed by a fine water spray. Water shall not be allowed to enter the street and stormwater systems. Demolition shall not be performed during high winds, which may cause dust to spread beyond the site boundaries. Please note that Council may require testing to verify that the soil lead levels are below acceptable health criteria.

Reason:- to ensure the disposal and demolition of materials incorporating lead is carried out in a safe manner in accordance with relevant regulations.

47. **Demolition - common sewerage system**

If the land to which the application relates is served by a common sewerage system that is also used by others, then measures must be placed in effect and prior to the commencement of work to ensure the operation of the sewerage system is without disruption to other joint users.

Reason:- to ensure demolition activities do not disrupt the operation of the sewerage system for other users of the system.

48. **Demolisher Details**

The demolisher/owner/applicant shall:-

- a) Lodge with Council, and at least forty-eight (48) hours prior to the commencement of work (due to the potential impact on Council's infrastructure):-
  - i) Written notice, indicating the date when demolition of the building is to commence.
  - ii) The demolisher's full name and address.
  - iii) Details of Public Liability Insurance.
- b) Comply with Australian Standard 2601 - 2001 "*Demolition of Structures*"; and,
- c) Have a current public liability/risk insurance, and policy details of such shall be submitted to Council for its records.
- d) Ensure that all possible/practicable steps are taken to prevent nuisance to the inhabitants of the surrounding neighbourhood from wind-blown dust, debris, noise and the like arising from the demolition works.

This Consent shall not preclude the demolisher from giving notice to other statutory authorities, such as Sydney Water Corporation, WorkCover, etc.

Reason:- to ensure details of the demolisher are provided to Council and relevant safety requirements are met.

49. **Demolition Works - noise and vibration**

The following shall be compiled with:-

- a) Vibration levels induced by the demolition activities shall not exceed 1mm/sec peak particle velocity (ppv) when measured at the footing of any occupied building.
- b) Vibration levels induced by the demolition activities shall not exceed 3mmsec peak particle velocity (ppv) when measured at the footing of any unoccupied building.
- c) The upper noise level from the demolition operations measured over a period of 10 minutes must not exceed the background noise level by more than 10dB(A).

Reason:- to ensure noise and vibration arising from the demolition works does not impact on the amenity of the surrounding area.

50. **Asbestos**

- a) In the event that asbestos is on a site or building under demolition or construction, WorkCover NSW is to be contacted to ascertain the appropriate response, to ensure the safety and protection of existing and future workers and residents. An Asbestos Removal Contractor licensed by WorkCover NSW is to handle/remove/transport and dispose of any products containing asbestos in a manner approved of by the Department of Environment and Conservation (DEC). Copies of tipping dockets are to be retained and able for viewing by Council officers on request.
- b) Asbestos material can only be disposed of at a landfill site nominated by Waste Services NSW for that purpose. An appointment must be made with Waste Services NSW to dispose of asbestos materials at the nominated landfill.
- c) Anyone who removes, repairs or disturbs bonded or a friable asbestos material must hold a current removal licence from Workcover NSW. Before starting work, a work site-specific permit approving each asbestos project must be obtained from Workcover NSW. A permit will not be granted without a current Workcover licence. All removal, repair or disturbance of or to asbestos material must comply with:-
  - i) Work Health and Safety Act 2011;
  - ii) *The Work Health and Safety Regulation 2011*;
  - iii) *Protection of the Environment Operations Act 1997*
  - iv) *Environmental Guidelines: Assessment, Classification and Management of Liquid and Non-Liquid Wastes, NSW EPA, May 1999*
  - v) *Waste Avoidance and Resource Recovery Act 2001*.
  - vi) *The Code of Practice for the Safe Removal of Asbestos [NOHSC: 2002 (1998)]*;
  - vii) *The Guide to the Control of Asbestos Hazards in Buildings and Structures [NOHSC: 3002 (1998)]* <http://www.nohsc.gov.au> ; and
  - viii) *The Workcover NSW Guidelines for Licensed Asbestos Removal Contractors*.

Note: The Code of Practice and Guide referred to above are known collectively as the Worksafe Code of Practice and Guidance Notes on Asbestos. They are specifically referenced in the Occupational Health and Safety Regulation 2001 under Clause 259.

Under the Work Health and Safety Regulation 2011, the Worksafe Code of Practice and Guidance Notes on Asbestos are the minimum standards for asbestos removal work.

Council does not control or regulate the Worksafe Code of Practice and Guidance Notes on Asbestos. You should make yourself aware of the requirements by visiting <http://www.workcover.nsw.gov.au> or one of Workcover NSW's offices for further advice.

- d) In order to ensure safe handling of asbestos materials, the re-use or sale of asbestos building materials is strictly prohibited.

Reason:- to ensure the safe handling, treatment and disposal of asbestos materials arising from the demolition/construction works.

51. **Services to be capped**

Prior to the commencement of demolition works, the applicant must ensure that utility services to the land upon which the building to be demolished stands, as well as the building itself, are terminated and capped in accordance with the requirements of supply authority, eg. Electricity-Supplier of Electricity to the subject premises, Gas-Supplier of Gas to the subject premises.

Reason:- to ensure all services are capped adequately.

52. **Site to be kept in a clean condition**

Upon completion of demolition works and if no new building works are commenced on site, the site shall be kept in a clean manner with landscaping and fencing to the satisfaction of Council.

Reason:- to control soil erosion, and not have any unsightly views.

53. **Neighbour 24 notification of commencement of demolition**

Prior to the commencement of work the applicant shall provide 24 hours notice in writing to the neighbours adjoining and opposite the site of the intended time and date of the start of the demolition work.

Reason:- to ensure details of the demolisher are provided to neighbours.

54. **Discovery of additional information during remediation, demolition or construction**

Any new information which comes to light during remediation, demolition or construction works which has the potential to alter previous conclusions about site contamination shall be notified to the Council and the PCA immediately.

Reason:- to ensure Council is informed of any new information relevant to site conditions and site contamination associated with the development.

55. **Off-site soil disposal**

Any soil disposed of offsite shall be classified in accordance with the procedures in the NSW EPA Environmental Guidelines: Assessment, Classification & Management of Liquid & Non-Liquid Wastes (1999).

Reason:- to ensure soil disposed off-site is classified in accordance with relevant EPA requirements.

56. **Vehicle Driveway Crossings and Gutter Laybacks**

Arrangements shall be made with Council for the prepaid construction of vehicular crossings and gutter laybacks at all property entrances and exits, and for the removal of all disused driveway crossings and gutter laybacks. Alternatives to the pre-payment for this work will be considered if written request is made to Council. The gutter crossing and/or the removal of any redundant crossings must be constructed to the satisfaction of Council (and to the Council's specifications including payment of any required bonds) or the prepayment made to Council for Council to carry out the

work, prior to the issue of any occupation certificate.

Removal of obstructions, such as power poles, trees, drainage pits and the like shall be carried out at the applicant's expense.

Reason:- to ensure that works are carried out in accordance with Council's standard.

57. **Carrying capacity of driveways - Heavy duty**

Suitable heavy-duty driveway crossings are to be installed at all ingress/egress points to the property at the applicant's cost by Council. Alternatives to the pre-payment for this work will be considered if written request is made to Council. The gutter crossing and/or the removal of any redundant crossings must be constructed to the satisfaction of Council (and to the Council's specifications including payment of any required bonds) or the prepayment made to Council for Council to carry out the work, prior to the issue of any occupation certificate.

Reason:- to ensure the driveways can support the expected weight of heavy vehicles likely to frequent the site.

58. **Street boundary levels**

Street boundary levels for vehicle access and drainage purposes are to be obtained at the applicant's cost from Council's Service Planning Department. These levels are to be incorporated in all drainage submissions required under this determination.

Reason:- to ensure the correct levels are obtained and used for the development.

59. **Road opening permit**

Prior to commencement of any work on Council roads and footpaths, a road-opening permit shall be obtained from Council's Service Planning Department.

Reason:- to safeguard Council property against damage.

60. **Restoration works**

Prior to commencement of any excavation work on Council roads or footpaths, the applicant shall pay for all restoration costs. The area of restoration shall be determined on site between the applicant or its contractor and Council's Contracts & Maintenance Engineer.

Reason:- to ensure that Council's infrastructure is maintained in a safe and trafficable manner.

61. **Street works and Auburn Traffic Committee Approval**

Prior to the issue of any Construction certificate, a detailed plan for the proposed relocation of bus stop signs and written consent from relevant authority's for the proposed relocation shall be submitted to Council for approval by the Auburn Traffic Committee.

The subject plan shall include:-

- All existing traffic facilities, signage and markings.
- All proposed traffic facilities, signage and markings.

Note: In general, the Auburn Traffic Committee approval may take a minimum of 6 weeks.

Reason:- to comply with the regulatory requirements.

62. **Power pole relocation**

The power pole identified for relocation as shown in the approved plans shall be relocated a minimum of 1.2 metres from the proposed driveway subject to relevant service providers/approvals body's written consent. A copy of the written consent shall be submitted to and approved by the Council **prior to the issue of a Construction Certificate.**

The Power pole shall be relocated **prior to the issue of any Occupation Certificate.**

Reason:- to protect utility services.

63. **Stormwater disposal**

All stormwater runoff generated from the proposed development shall be directed to the On Site Detention system prior to being discharged to Council's underground drainage system in Ostend Street.

Reason:- to prevent localised flooding.

64. **Submission of full storm water disposal details**

Full storm water drainage details showing the proposed method of storm water collection and disposal are to be submitted to Council or the Accredited Certifier to ensure the approved storm water plans are incorporated with the Construction Certificate.

The details shall be prepared by a suitably qualified person and must be in accordance "Auburn Development Control Plans 2010 - Storm water Drainage" and "Australian Rainfall & Runoff 1987". In this regard:-

The proposed storm water system shall be generally in accordance with the storm water concept plans 13MB5729/D01, 13MB5729/D02, 13MB5729/D03 and 13MB5729/D04 issue C dated 22. 09 2014 prepared by United Consulting Engineers.

All access grates to the detention facility shall be double (2/900x450) hinged grates.

Note: "Auburn Development Control Plans 2010 - Storm water Drainage" is available to purchase at Council or the document can be found at Auburn Council's web page [www.auburn.nsw.gov.au](http://www.auburn.nsw.gov.au)

Reason:- to ensure the storm water is suitably discharged.

65. **Structural Engineering Certificate**

The applicant shall submit a structural engineer's certificate of adequacy verifying



that the works as detailed on the approved plans for the storage tank have been completed under his/her supervision and that the design is adequate to support the anticipated design loads. **The certificate shall be submitted to Council with the works-as-executed plan.**

Reason:- to ensure the construction is structurally adequate.

66. **Structural detailed design of the underground tank**

A detailed structural design of the proposed underground detention tank shall be submitted to Principal Certifying Authority with the Construction Certificate.

Reason:- to ensure the structural stability.

67. **Water Reuse**

The stormwater generated from the roof area shall be reused for the irrigation of the landscape area within the subject development site.

Full details of the Water reuse facilities shall be submitted to Council or the Accredited Certifier with the Construction Certificate.

On completion, a certificate from a registered plumber shall be submitted for the pipe network. The certification shall indicate the water reuse system has been installed in accordance with the approved water reuse design plans.

Reason:- to ensure the water reuse facilities within the development are constructed and maintained in good working order.

68. **Stormwater disposal - on-site detention**

On-site stormwater detention storage is to be provided in conjunction with the stormwater disposal. The storage is to comply with "Auburn Development Control Plans 2000 - Stormwater Drainage". Where multiple detention basins with differing top water levels are used, the basins must be routed to the outlet pit independent of each other.

A positive covenant under Section 88E of the Conveyancing Act is to be created on the title of the property detailing the on-site stormwater detention system incorporated in the development. The wording of the instrument is to be submitted and approved by Council prior to lodgement at the Land Titles Office. Evidence confirming the positive covenant has been registered shall be submitted to Council prior to occupation of the building or issue of the occupation certificate.

Note:

1. Positive covenant wording shall be obtained from Council prior to lodgement.
2. Work as executed plan shall be accompanied by relevant checklists.

Reason:- to prevent localised flooding by ensuring the detention system is maintained as designed.

69. **Maintenance schedule - OSD**

Prior to the issue of the occupation certificate, a maintenance schedule of the proposed on-site detention facility shall be submitted to Council for approval with the

stormwater work-as executed plan. This maintenance schedule shall be registered as part of the positive covenant.

Reason:- to ensure the onsite detention facility is in good working order.

70. **Annual maintenance inspection of OSD**

Annual maintenance inspection summary of the onsite detention with associated certificates shall be sent to Council within the first month of every calendar year. In this regard:-

- All critical inspections shall be carried out by a qualified person.
- A maintenance log book shall be maintained as per the approved maintenance schedule on site and readily available for inspection by a Council officer.
- All associated cost shall be borne by the owner.

Reason:- to ensure the onsite detention facility is in good working order.

71. **Engineer Certificate for critical pump**

A certificate from a practising hydraulic engineer verifying that the stormwater pump installation and the design with the executed levels shall be submitted to the Council with the work as executed plan prior to the release of Occupation Certificate.

Reason:- to ensure the system has been constructed Council's standards and specifications.

72. **Basement drainage system**

Basement drainage is to comply with "Auburn development control plans 2010 stormwater drainage". In this regard:

- a) Two pump units being installed, the capacity of each being calculated on the basis of a hundred year storm recurrence interval and a storm duration of 5 (five) minutes, one pump acting in reserve capacity.
- b) The two pumps being designed to work on an alternate basis to ensure that both pumps receive equal usage and neither pump remains continuously idle.
- c) A holding well being provided within the basement, of sufficient capacity to store the discharge based on a hundred year storm recurrence interval and storm duration of ninety minutes. In addition to this an above ground storage shall be provided up to a hundred year storm recurrence interval and storm duration of two hours. The holding well is to be designed so that a minimum volume of water is retained in the well for health reasons when the pumps are in the "off" position or if there is a break in electrical supply.
- d) A storm of two hours' duration has been adopted as a basis for determining the size of the well, the assumption being that electrical supply will be reinstated within this period.
- e) The pump out system is to be independent of any gravity drainage lines,

except at the property boundary where a grated surface pit is to be constructed from which a connection will be permitted to the gravity drainage system. The invert levels of the pipes in the grated surface pit are to be such that the outlet from the pump out system is above the inlet of the gravity system.

- f) Storage areas and areas used for purposes other than car parking or access aisles are to be constructed a minimum of 100mm above the top water level.
- g) The contributing catchment area to the pump out system is to be limited to the access ramp area only and subsoil drainage.

Reason:- to prevent localised flooding.

73. **Footpath construction Parramatta Road**

The footpath adjoining the Parramatta Road frontage shall be reconstructed in accordance with the Council's Parramatta Road footpath paving requirements. Site boundary line levels shall be raised to the boundary line levels, with satisfactory end-transitions provided.

- The details of construction requirements shall be requested from the Council prior to the issue of a construction certificate.
- Detail footpath design shall be submitted and approved by Council's Works and Services section prior to the issue of a Construction Certificate.
- Street boundary levels obtained from Council shall be incorporated into the design.
- Formwork inspection and footpath inspection shall be carried out by Council.
- All associated cost shall be borne by the applicant.
- The footpath shall be constructed at the completion of works and finished to the satisfaction of Council prior to the issue of an Occupation certificate.
- All associated cost shall be borne by the applicant.

Reason:- to provide a safe footpath for increased pedestrian use and one that will complement the Auburn Council requirements.

74. **Footpath Construction Ostend Street and Mons Street**

The footpath adjoining Ostend Street and Mons Street frontage shall be reconstructed in accordance with the Council's Standard footpath construction requirements. Site boundary line levels shall be raised to the boundary line levels, with satisfactory end-transitions provided.

- Detail footpath design shall be submitted and approved by Council's Works and Services section prior to the issue of a Construction Certificate.
- Street boundary levels obtained from Council shall be incorporated into the design.
- The details of construction requirements shall be requested from the Council prior to commencement of construction.
- Formwork inspection and footpath inspection shall be carried out by Council.
- All associated cost shall be borne by the applicant.
- The footpath shall be constructed at the completion of works and finished to the satisfaction of Council prior to the issue of an Occupation certificate.
- All associated cost shall be borne by the applicant.

Reason:- to provide a safe footpath for increased pedestrian use and one that will complement the Auburn Council requirements.

75. **Works-as-Executed Plan - Drainage Plans**

Prior to occupation of the building or issue of the occupation certificate, two (2) copies of the Works-as-Executed (W.A.E.) Plan prepared by a registered surveyor and certified by the design engineer shall be submitted to Council. The W.A.E. plan shall show (where applicable):

- i) Whether all works have been completed generally with the approved drainage plans.
- ii) Any departure from the approved plan and conditions.
- iii) Any additional work that has been undertaken.
- iv) Location, levels and sizes of pipes and pits.
- v) Finished floor and finished surface levels. The location of finished levels should in general correspond with those shown on Council's approved drainage plan.
- vi) Basement pump out volumes.

NOTE:- The WAE surface level shall be taken after all landscaping has been completed.

In this regard:

- The above information is to be superimposed on a full sized copy of Council approved drainage plan and is to be submitted to Council.
- Checklists A3, A4 & A5 in the appendix of the "Auburn development control plans 2000 stormwater drainage" shall be completed and shall be certified by the practicing hydraulic engineer and the registered surveyor.

Reason:- to account for minor variations.

76. **Limit of the delivery trucks**

Larger vehicles access to the premises shall be limited to heavy rigid vehicle (HRV) that is defined in Australian standard AS2890.2.

Reason:- to ensure delivery trucks use approved loading area.

77. **Works within Council controlled lands**

For drainage works:-

- Within Council controlled lands.
- Connecting to Council's storm water drainage system.

Inspections will be required:-

- After the excavation of pipeline trenches.
- After the laying of all pipes prior to backfilling.

- After the completion of all pits and connection points.
- (2) A minimum of 48 hours notice shall be given to Council to inspect works. Inspections may be arranged by telephoning Council's Works and Services Section during office hours.
- (3) Work is not to proceed until the works are inspected and approved by Council.

Reason:- to ensure works on public/Council controlled lands are carried out as per Council's requirements.

78. **Food Premises Fitout - Compliance with Standards**

The fitout of the food premises shall comply with the requirements of *Australian Standard 4674-2004, Design, Construction and Fit-out of a Food Premises* and *Food Safety Standard 3.2.3, Food Premises & Equipment*.

Reason:- to ensure the food premises fitout complies with relevant standards.

79. **Design and Construction of Food Premises**

The design and construction of food premises must comply with the following requirements, as applicable:-

- a) No alterations to the shop or any fittings therein (including the installation of new items of equipment) are to be made without the prior approval of the Principal Certifying Authority.
- b) Areas intended to be used for storing & preparing food or for storing food packaging & equipment shall be physically separated from chemical storage areas, living & sleeping areas, toilets & change rooms, garbage & recycling facilities and all other activities likely to pose a risk of food contamination.
- c) Adequate space shall be provided on the premises for the storage of dry goods, fresh fruit & vegetables, returned food, recalled food, packaging material and utensils & equipment.
- d) All windows, doors, entrances/exits and serving latches shall be protected against the entry of pests.
- e) Where doors and windows need to be pest proofed against flying insects only, they may be protected by:-
  - i) Air curtains that effectively prevent insects entering the premises; or
  - ii) Being fitted with plastic strip curtains that effectively exclude flying insects; or
  - iii) Opening into vestibules with self-closing doors; or
  - iv) Fitting the bottom edge of doors or bottom sash of windows (where practicable) with a seal; or
  - v) Provide a fly zapper that is to remain on during business operating hours.
- f) Insect control devices shall be installed so that the devices are **not** located directly over food preparation working areas, exposed food, clean equipment

and/or unwrapped packaging material.

- g) All service pipes, drains, cables and duct penetrations shall be effectively sealed to prevent entry of pests.
- h) All service pipes conducts and electrical wiring shall either be concealed in the floor, plinths, walls & ceiling or fixed on brackets to provide a clearance at least 25mm and 100mm from the adjacent vertical and horizontal surface respectively.
- i) Spaces between adjoining structures, such a between coolroom / freezer walls and premises walls and the external roof, shall be accessible for inspection and cleaning or sealed with a suitable compound to prevent the entry of pests.
- j) The applicant shall refer to Sydney Water for trade waste requirements **prior** to the business use commencing.
- k) Grease arrestors shall not be located in areas where food, equipment or packaging materials are handled or stored.
- l) In areas where open food is handled or stored, light fittings shall be provided with fitted light diffusers to prevent contamination of food should the globe or tube shatter and allow easy access for cleaning.
- m) Floors in the food premises shall be finished with a surface that complies with Table 3.1 of AS 4674.2004.
- n) Floors in the food preparation areas shall be graded and drained to a floor waste connected to the sewerage system.
- o) The intersection of floors with walls shall be coved in accordance with diagrams 3.1 and 3.2 of AS 4674.2004.
- p) The plinths shall be of solid construction and not less than 75mm high with an impervious finish and consistent with the floor surface in table 3.1 of AS 4674 including coving.
- q) Walls in the food premises shall be of solid construction and finished with a material in accordance with Table 3.2 of AS 4674-2004.
- r) Wall surfaces shall provide a smooth even finish, free of buckles, ledges, fixing screws, picture rails, open joints, cracks & crevices.
- s) Ceilings in the food premises shall consist of a non perforated material and finished free of open joints, cracks & crevices.
- t) The intersections of walls and ceilings shall be tight jointed, sealed and dust proof.
- u) Ceilings in other areas shall be installed in accordance with the requirements of Table 3.3 of AS 4674-2004.
- v) Drop-in removable ceiling panels shall **not** be used in food preparation areas or where open food is being displayed or stored.

- w) The food premises shall be provided with a single bowl sink with supply of hot water at a temperature of not less than 45°C for washing operations only where pre-packed food, drink and uncut fruit & vegetables are being sold.
- x) The food premises shall be provided with a double bowl sink with a supply of hot and cold water through a common mixing spout. Hot water shall be provided at a temperature of at least 45°C for washing operations.
- y) All fixtures, fittings and equipment in the food premises shall be designed in accordance the requirements of Table 4.3 of AS 4674.
- z) Fixtures, fittings and equipment shall comply with one of the following options:-
  - a) movable for cleaning;
  - b) built into walls with the enclosure completely vermin proofed;
  - c) butted against walls or other equipment and the joints sealed;
  - d) installed with clearance distances compliant with Figure 4.4 of AS 4674.2004; or
  - e) if installed on a plinth, installed such that it overhangs the plinths.
- aa) All equipment used for display or storage of hot foods must be capable of maintaining such food at a temperature of not less than 60°C, and being fitted with an approved thermometer able to read easily from the outside of the appliance for the purpose of measuring this temperature.
- bb) All equipment used for display or storage of cold foods must be capable of maintaining such food at a temperature below 5°C. Frozen foods must remain in a frozen state. The coolroom and freezer must be fitted with an approved thermometer able to be read easily from the outside of the appliance for the purpose of measuring this temperature.
- cc) Hand wash basins shall be provided adjacent to each toilet, with taps that operate hands free. The hand wash basin shall be provided with a permanent supply of warm water delivered through a single outlet.
- dd) Hand wash basins shall be provided at a distance of no greater than five metres from a food preparation area where open food is handled. Hand wash basins shall be provided with taps that operate hands free and be provided with a permanent supply of warm water delivered through a single outlet.
- ee) A sufficient supply of liquid soap and disposable hand towels shall be provided at the hand wash basin.
- ff) A separate area shall be provided for the storage of employees clothing, cleaning material and equipment.
- gg) Toilet facilities shall be in accordance with the BCA and shall be separated from areas where open food is handled, displayed & stored or provided with self-closing doors and a mechanical exhaust system that operates when the sanitary compartment is in use.
- hh) Access to toilet areas shall not be provided through areas (other than the dining area) where open food is handled, displayed or stored.

- ii) All waste material shall be stored in containers with tight fitting lids at all times.
- jj) No food whether covered or uncovered shall be stored outside of the external building facade.

Reason:- to ensure the fitout complies with the food premises standards.

80. **Mechanical Ventilation/Exhaust System**

- a) Details of any proposed mechanical exhaust systems, detailing compliance with the relevant requirements of Clause F4.12 of the BCA and Australian Standard AS1668 Parts 1 & 2 (including exhaust air quantities and discharge location points) are to be submitted to Council or the Principal Certifying Authority for approval **prior to the issue of a Construction Certificate**.
- b) At the completion of the installation of the mechanical exhaust system, a certificate from the installer shall be submitted to Council or the Principal Certifying Authority indicating the following:-
  - i) inspection, testing and commissioning details,
  - ii) date of inspection testing and commissioning,
  - iii) the name and address of the individual who carried out the test, and
  - iv) a statement that the service has been designed, installed and is capable of operating to the above standard.
- c) In the event of Council receiving complaints resulting from the mechanical exhaust system, the owner/occupier shall at their own cost provide a report from a Air Quality Consultant specifying the proposed methods for the control of odour and other air impurities discharging from the premises.
- d) The mechanical exhaust vent shall extend no less than one (1) metre above the subject buildings apex, or the adjoining buildings apex in the event of a shared common wall.
- e) Any discharge to the atmosphere from the subject development shall not result in any odour or other air impurity being detected outside the boundaries of the property.
- f) Noise and vibration from the use of the mechanical exhaust and/or ventilation system shall not exceed the background noise level by more than 5dB(A) and shall not be audible in any premises of a neighbouring occupancy.

Reason:- to ensure compliance with relevant standards.

81. **Trade Waste**

The food premises must comply with the following requirements:-

- a) Liquid trade waste materials are to be disposed of in accordance with the requirements of the Sydney Water, Trade Waste Department and details of compliance are to be submitted to the certifying authority prior to the commencement of works.
- b) The disposal of waste materials in the domestic garbage service is not



permitted. All waste materials must be collected by a waste contractor authorised by the Waste Service of New South Wales and details of the proposed service to serve the development are to be submitted to Council prior to occupation of the building.

Reason:- to ensure that trade waste is properly disposed of.

82. **Foodshop notification and inspection**

- a) Foodshop notification shall be obtained from the NSW Food Authority, **prior** to commencement of business operations and a copy of the notification shall be submitted to Council. Notification can be completed on NSW Health Department's web site at [www.foodnotify.nsw.gov.au](http://www.foodnotify.nsw.gov.au)
- b) The applicant shall notify Council not less than forty-eight (48) hours **prior** to the proposed occupation of the premise to arrange for a final compliance inspection.
- c) The applicant shall not operate the food premises until an occupation certificate has been issued.

Reason:- to enable registration of the food premises and to ensure appropriate inspections are made of the food premises.

83. **Emission Control**

There are to be no emissions or discharges from the premises which will give rise to an offence under the *Protection of the Environment Operations Act 1997* and *Regulations*.

Emission control equipment shall be provided in the mechanical exhaust system serving the cooking appliances, to effectively minimise the emission of odours, vapours and oils. Details of the proposed emission control equipment must be provided in the relevant plans and specifications for the Construction Certificate for the subject works.

Reason:- to minimise any potential odour/smoke nuisance.

84. **Kitchen and Restaurant Fit out**

Details of all proposed kitchens, food preparation and storage areas used in connection with food for sale, demonstrating compliance with the Food Act 2003, Food standards Code and Australian Standard 4674 must be provided to the Principle certifying Authority for approval prior to issue of a construction certificate.

Reason:- to ensure the kitchens comply with the relevant legislation.

85. **Compliance with Acts and Regulations for shared accommodation**

The use and operation of the premises shall comply with the requirements of Part 1 Standards for places of shared accommodation in Schedule 2 - Standards enforceable by Orders of the Local Government (General) Regulation 2005 for the construction, maintenance, and operation of places of shared accommodation. The use of the premises as a hotel shall comply with the requirements of clause 46

regarding Sleeping Accommodation of the Public Health Regulation, 2012.

Reason:- to ensure the hotel is compliant with the relevant legislation.

86. **Compliance with Submitted Acoustic Report**

The recommended acoustic treatments and noise controls specified in the acoustic report prepared by Acoustic Solutions Pty Ltd (Reference 2013-357) and dated 6 September 2013 and 27 June 2014 shall be installed prior to the issuing of the occupation certificate. All noise reduction measures specified in the acoustic report shall be complied with at all times during the operation of the premises.

Reason:- the recommendations of the acoustic report are required to be incorporated into the development to reduce noise impacts.

87. **Acoustic Certification**

Within three months of the use of the premises, an acoustic report prepared by a suitably qualified person is to be submitted to the consent authority demonstrating that the noise emitted from the premises complies with the criteria contained in the acoustic report prepared by Acoustic Solutions Pty Ltd (Reference 2013-357) and dated 6 September 2013 and 27 June 2014. Where the criteria are not achieved, the acoustic report is to make new recommendations for meeting the relevant criteria. The new works are to be implemented to ensure compliance with the criteria.

Reason:- to prevent excess noise from the development.

88. **Amenity**

The operation of the premises shall be conducted in such a manner as not to interfere with or materially affect the amenity of the neighbourhood by reason of noise, vibration, odour, fumes, vapour, steam, soot, ash, dust, waste water, waste products, grit, oil, or otherwise.

Reason:- to protect the amenity of the locality.

89. **Water Pollution**

The operation of the premises shall be conducted in a manner which does not pollute waters as defined by the *Protection of the Environment Operations Act 1997*.

Reason:- to protect waterways and stormwater systems from pollution.

90. **Removal of Litter**

In addition to Council's street sweeping and cleansing operations, the owner/manager of the building shall ensure that the footpath, gutter, building entry and surrounds are kept clean and clear of litter at all times.

Reason:- to maintain a satisfactory level of amenity in the locality.

91. **Light Overspill**

Any lighting on the site shall be designed so as not to cause nuisance to other

residences in the area or to motorists on nearby roads, and to ensure no adverse impact on the amenity of the surrounding area by light overspill. All lighting shall comply with *AS4282-1997 Control of the obtrusive effects of outdoor lighting*.

Reason:- to ensure light overspill arising from the development does not interfere with the amenity of the locality and complies with relevant Australian Standards.

92. **No approval granted for a public address system or sound amplifying equipment**

A public address system or sound amplifying equipment shall not, without the consent of Council, be installed in or upon the premises so as to cause or permit the emission of sound onto any public place or nearby residential area.

Reason:- to ensure the development does not cause a noise nuisance to adjoining development.

93. **Noise and Vibration**

The use of the premises shall not give rise to any of the following when measured or assessed at “sensitive” positions within any other property. These “sensitive” positions should be selected to reflect the typical use of a property (ie any outdoor areas for day and evening but closer to the façade at night time), unless other positions can be shown to be more relevant.

- a) 'offensive noise' as defined in the Protection of the Environment Operations Act 1997.
- b) transmission of vibration to any place of different occupancy above the requirements of AS2670.
- c) a sound pressure  $L_{Aeq,period}$  at any noise sensitive position of any other premises or occupancy greater than the recommended amenity noise criteria detailed in the Department of Environment and Conservation, New South Wales (EPA) Industrial Noise Policy.
- d) a sound pressure  $L_{Aeq,15min}$  at any noise sensitive position greater than the intrusiveness criteria determined in accordance with the Department of Environment and Conservation, New South Wales (EPA) Industrial Noise Policy and does not contain any tones, low frequency or impulsive factors as defined in the Department of Environment and Conservation, New South Wales (EPA) Industrial Noise Policy table 4.1.

For assessment purposes, the above  $L_{Aeq}$  sound levels shall be assessed over a period of 10-15 minutes and adjusted in accordance with EPA guidelines for tonality, frequency weighting, impulsive characteristics, fluctuations and temporal content where necessary.

Reason:- to ensure adequate acoustic amenity in the locality.

94. **Liquor Licensed Premises**

Noise emissions from the licensed premises shall comply with the following:-

- The  $LA_{10}$  noise level emitted from the licensed premises shall not exceed 5dB above the background ( $LA_{90}$ ) noise level in any Octave Band Centre Frequency (31.5Hz to 8KHz inclusive) between the hours of 7.00am to 12.00

midnight when assessed at the nearest affected residential boundary. The background noise level shall be measured in the absence of noise emitted from the licensed premises.

- The LA10 noise level emitted from the licensed premises shall not exceed the background (LA90) noise level in any Octave Band Centre Frequency (31.5Hz to 8KHz inclusive) between the hours of 12.00 midnight to 7.00am when assessed at the nearest affected residential boundary. The background noise level shall be measured in the absence of noise emitted from the licensed premises.
- Notwithstanding compliance with the above clauses, the noise from the licensed premises shall not be audible within any habitable room in any residential premises between the hours 12.00 midnight to 7.00am.

***NOTE:** where this condition is inconsistent with the requirements imposed by the Liquor Administration Board or Liquor Licensing Court, the more stringent condition shall prevail.*

**Reason:-** to protect the environment.

95. **Air conditioning units - location and acoustics**

- a) Air conditioning units are not to be visible from the street or public place and are not to obscure windows/window frames or architectural features of the building.
- b) The operation of air conditioning units shall be so:
  - (i) as not to cause “offensive noise” as defined under the Protection of the Environment Operations Act 1997;
  - (ii) as to be inaudible at the nearest affected residence between the hours of 10.00pm and 7.00am on weekdays and 10.00pm and 8.00am on weekends and public holidays;
  - (iii) as not to discharge a condensate or moisture onto the ground surface of the premises or into a stormwater drainage system in contravention of the requirements of the Protection of the Environment Operations Act 1997.
- c) Should Council receive noise complaints from neighbouring residents in relation to the air conditioning units, Council may issue a Noise Notice. Such notice may require you to engage the services of a competent and appropriately qualified Acoustic Consultant to undertake a noise level assessment of the air conditioning unit. If the unit is assessed as exceeding the permitted noise criteria, you may be directed to provide noise attenuation measures such as an acoustic enclosure and/or relocation of the unit.

The air conditioning units are to be installed in accordance with the Recommendations made at Part 10.1 - Air conditioned units and mechanical ventilation on Page 12 of the acoustic report prepared by Acoustic Solutions Pty Ltd (Reference Number 2013-357) and dated 27 June 2014.

**Reason:-** to ensure that air conditioning units associated with the development are appropriately located and do not detract from the appearance of the buildings and to ensure the operation of air conditioning units does not adversely impact on the acoustic amenity of the locality.

96. **Intruder Alarms**

Any intruder alarm at the premises shall be fitted with a timing device in accordance with the requirements of Section 53 of the Protection of the Environment Operations (Noise Control) Regulation 2000.

Reason:- to prevent ongoing noise arising from intruder alarms and ensure compliance with relevant legislation.

97. **Arrangements for Water and Sewer Services**

A Section 73 Compliance Certificate under the Sydney Water Act 1994 must be obtained.

**Application must be made through an authorised Water Servicing Coordinator. Please refer to “Your Business” section of Sydney Water’s web site at [www.sydneywater.com.au](http://www.sydneywater.com.au) then the “e-developer” icon or telephone 132 092.**

Following application a “Notice of Requirements” will detail water and sewer extensions to be built or charges to be paid. Please make early contact **with the Coordinator**, since building of water/sewer extensions can be time consuming and may impact on other services and building, driveway or landscaping design.

The Section 73 Certificate must be submitted to the Principal Certifying Authority (Council or accredited certifier) **prior to release of the final plan of subdivision or occupation of the development.**

Reason:- to ensure that adequate water and sewer services can be provided to the site.

98. **Stamping of development application plans by Sydney Water**

The approved development application plans must be submitted to a Sydney Water Quick Check agent or Customer Centre to determine whether the development will affect Sydney Water’s sewer and water mains, stormwater drains and/or easements and if further requirements need to be met. Plans will be appropriately stamped.

Please refer to the web site [www.sydneywater.com.au](http://www.sydneywater.com.au) for:

- Quick Check agents details - see Building Developing and Plumbing then Quick Check; and
- Guidelines for Building Over/Adjacent to Sydney Water Assets - see Building Developing and Plumbing then Building and Renovating or telephone 13 20 92.

**Note:**

The consent authority or accredited certifier must either:

- ensure that a Quick Check agent/Sydney Water has appropriately stamped the plans before the issue of any Construction Certificate; or
- if there is a combined Development/Construction Certificate application, ensure that a Quick Check agent/Sydney Water has appropriately stamped the plans

prior to works commencing on site.

Reason:- to ensure the development does not damage or interfere with Sydney Water assets.

99. **Aboveground Power Lines**

Where practicable, all existing overhead power lines adjacent to the development site shall be relocated underground to Energy Australia standards and specifications. If not practicable to relocate the power lines underground, arrangements shall be made with Energy Australia to place the conduit to carry those power lines underground so that they can be utilized at a later date by Energy Australia. In this regard all associated costs shall be borne by the applicant.

Reason:- to improve the aesthetic quality of the area.

100. **Number of Car Parking Spaces**

A total of 522 off-street car parking spaces are to be provided to the development. The spaces are to have minimum dimensions of 5.5 m x 2.4 m and be suitably sealed, marked, drained and freely accessible at all times.

Carparking spaces are not to be enclosed by any device, such as a wire or mesh cage, walls or other similar fixtures unless there is a minimum clear internal width of 3 metres. Carparking spaces shall not be enclosed without the prior consent of council.

Reason:- to ensure there is sufficient car parking for the development and to comply with Auburn Parking & Loading DCP.

101. **Adequate Signs and Pavement Markings Required to Assist Traffic Flow on Site.**

Adequate signs and pavement markings are to be provided to direct the flow of traffic within the site. Details are to be provided prior to the issue of the construction certificate.

Reason:- to assist with traffic flow within the development.

102. **Vehicles Driven in Forward Direction**

All vehicles must be driven in a forward direction at all times when entering or leaving the premises.

Reason:- to preserve and enhance the safe operation of the car parking area.

103. **Loading and Unloading of Vehicles**

All deliveries to and from the site are to be conducted from vehicles standing within designated loading areas and not on access driveways, car parking spaces or landscaped areas.

Reason:- to ensure delivery vehicles do not obstruct these designated areas of the site.

104. **Driveway surface treatment**

Driveway surface treatments must finish at the property boundary.

Reason:- to ensure compliance with Council's Development Control Plan requirements.

105. **Headroom clearance - within the Basement**

The headroom clearance within the basement shall comply with the usage. In this regard, minimum 4.0m shall be provided in waste collection area and associated turning area. Other areas shall comply with AS 2890.1 and 2890.6 requirements.

Detail plans showing the compliance of above requirements shall be submitted and approved by the Principle Certifying Authority **prior to issue of a Construction Certificate.**

Reason:- to ensure headroom clearance complies with Australian Standards AS 2890.1 AS2890.6 and Council's DCP.

106. **Roads and Maritime Services Requirements**

- All construction activity associated with the development is to be contained on site or on Mons Street or Ostend Street and no construction zones will be permitted on Parramatta Road in the vicinity of the site.
- A Road Occupancy License shall be obtained from the Transport Management Centre for any works that may impact on traffic flows on Parramatta Road during construction.
- A Construction Traffic Management Plan detailing construction vehicle routes, number of trucks, hours of operation, access arrangements and traffic control shall be submitted to Roads and Maritime for determination prior to the issue of the construction certificate.
- The swept path of the longest vehicle entering and exiting the site as well as manoeuvrability through the site shall be in accordance with AUSTROADS.
- Should the post development storm water discharge from the subject site into the RMS drainage system exceed the pre development discharge, then detailed design plans and hydraulic calculations or any changes are to be submitted to Roads and Maritime Services for approval prior to the commencement of works.
- The developer is to submit all documentation relating to the excavation of the site and support structures to Roads and Maritime Services for assessment. All documentation is to be submitted at least six (6) weeks prior to the commencement of construction and the developer shall pay all the relevant costs of assessment by Roads and Maritime Services.
- If it is necessary to excavate below the level of the base of the footings of the adjoining roadways, the person acting on the consent shall provide the owners of the roadway a minimum of seven (7) days notice of the intention to excavate below the base of the footings. The notice shall include a complete description of the work to be undertaken.

- All works, regulatory signposting associated with the proposed development are to be at no cost to Roads and Maritime Services.
- A traffic management plan shall be submitted to and approved by Roads and Maritime Services and Council for all demolition, excavation and construction activities associated with the development prior to commencement of work.

Reason:- to ensure compliance with the requirements of the Roads and Maritime Services.

107. **Materials and Finishes**

Materials and finishes to the development shall be in accordance with the details of the approved plans and the following requirements:-

- a) Quality and durable materials are to be used throughout the development.
- b) The applied external paint finishes to the building shall have a minimum aggregate thickness of 200 microns.

Reason:- to ensure a high quality appearance to all materials within the development.

108. **Common Wall Construction**

Prior to the issue of a Construction Certificate, construction drawings shall be submitted to the Principal Certifying Authority for approval to indicate that common party walls between the dwellings being constructed from solid masonry materials and not being lightweight construction.

Reason:- to ensure adequate acoustic separation between dwellings within the development.

109. **Underside of balconies**

The underside of the balconies within the development must be designed to prevent exposed pipes and utilities being visible.

Reason:- to ensure an attractive appearance to the development in accordance with Council's Development Control Plan requirements.

110. **Reflectivity Index of Glazing**

The reflectivity index (expressed as a percentage of the reflected light falling upon any surface) of external glazing for windows, walls or roof finishes of the proposed development is to be no greater than 20%. Written confirmation of the reflectivity index of materials is to be submitted with the Construction Certificate.

Note: The reflectivity index of glazing elements can be obtained from glazing manufacturers. Glass with mirrored or reflective foil finishes is unlikely to achieve compliance with this requirement.

Reason:- to ensure that excessive glare or reflectivity nuisance from glazing does not occur as a result of the development.



111. **Swimming Pool**

The operation and maintenance of the swimming pool including water quality and disinfection, shall comply with the requirements of the Public Health Act 2010 and associated regulations and guidelines.

Reason:- to ensure the swimming pool remains clean in accordance with the requirements of the Public Health Act 2010.

112. **PCA - Inspection of Works - General & Site Management**

The building works are to be inspected by the principal certifying authority (or other suitably qualified person on behalf of the applicant if permitted by the PCA) to monitor compliance with Council's approval and the relevant standards of construction.

Documentary evidence of compliance with Council's approval and relevant standards of construction, is to be maintained by the principal certifying authority.

Upon inspection of each stage of construction, the principal certifying authority (or other suitably qualified person on behalf of the applicant) is also required to ensure that adequate provisions are made for the following measures (*as applicable*), to ensure compliance with the terms of Council's approval:-

- Sediment control measures
- Maintenance of the public place free from unauthorised materials, waste containers or other obstructions.

In accordance with the Swimming Pools Amendment Act 2012 all swimming pools must be registered on a state wide online register by no later than April 2013. Mandatory inspections are required to ensure ongoing compliance and appropriate fees charged.

**ADVISORY NOTE**

*If Council is appointed as the PCA, the following inspections (as applicable to the development), must be arranged:-*

- a) *Pool excavation/reinforcing steel (for inground pools).*
- b) *The swimming pool safety fence prior to filling the pool with water.*
- c) *Final inspection.*

A minimum of 24 hours notice must be provided to Council to enable the following inspections to be carried out during the course of construction.

Reason:- to ensure the development is adequately monitored during the construction phase.

113. **Child Resistant Barrier**

The proposed swimming pool shall be surrounded by a fence having a minimum of 1200 mm, measured from the outside of the enclosure with any space beneath not exceeding 100 mm:-

- a) that forms a barrier between the swimming pool; and
  - i) any residential building situated on the premises;
  - ii) the remainder of the premises; and
  - iii) any place (whether public or private) adjacent to or adjoining the premises; and
- b) that contains within its bounds no structure apart from the swimming pool and such other structures (such as diving boards and pool filtration plants) as are wholly ancillary to the swimming pool; and
- c) that is designed, constructed and installed in accordance with Australian Standard 1926.1 - Fences and Gates for Private Swimming Pools and the Swimming Pools Act 1992 and regulations.

Reason:- to ensure that the level of protection intended by the Child Resistant Barrier is provided.

114. **Maintenance of Fencing**

It is the responsibility of the pool owner to ensure that the pool fencing continues to provide the level of protection required regardless of and in response to any activity or construction on the adjoining premises. Due regard shall be given to the effect that landscaping will have on the future effectiveness of security fencing.

Reason:- to ensure that level of protection intended by the child resistant barrier is maintained.

115. **Resuscitation Poster**

A poster prepared by the Royal Life Saving Society on expired air resuscitation shall be exhibited in a prominent position adjacent to the pool.

Reason:- to aid in the case of a life threatening emergency.

116. **Discharge of Pool Waste Water**

Swimming pool waste water shall be discharged into the sewers of Sydney Water in accordance with their requirements.

Reason:- to prevent a potential nuisance arising from the discharge.

117. **Pool Registration**

In accordance with the Swimming Pools Amendment Act 2012 all swimming pools must be registered on a state wide online register. **Prior to the issue of any occupation certificate** evidence that the pool has been inspected and registered must be provided to the PCA.

Ongoing inspections for a pool compliance certificate will be the subject of payment of appropriate fees.

Reason:- to ensure compliance with the Swimming Pools Amendment Act 2012

118. **Security fencing**

All security fencing shall be on an alignment of 4.5m to the street boundary. Under no circumstances are gates to open over Council's footway or obstruct access to car parking spaces.

Reason:- to ensure the development operates in accordance with the approval and does not cause a nuisance or a hazard to the public.

119. **Use of building not to commence until conditions of consent satisfied**

The use of the premises is not to commence until all terms of this consent have been satisfied.

Reason:- to ensure compliance with the terms of the development consent.

120. **Display of goods not permitted outside building or property**

Materials, goods, plant, equipment, signage, advertising structures or the like are not to be stored, placed or displayed anywhere outside the building or property without Council approval.

Reason:- to avoid visual intrusion into areas adjoining the site.

121. **Side/Rear Boundary Fencing**

Fences located on the side or rear boundaries of the premises, behind the main building setback (not within the front yard), shall not exceed a maximum height of 1.8 metres.

In addition, the materials to be used for the new fencing along the southern boundary of the site shall be in accordance with the recommendation made on Page 12 (Part 10.2) of the Acoustic Report prepared by Acoustic Solutions Pty Ltd (Reference Number 2013-357) and dated 27 June 2014.

Reason:- to maintain reasonable levels of amenity to the adjoining premises.

122. **Fencing/gates and adjoining land**

There must be no encroachment of any part of the structure/s onto the adjoining premises or onto Council's road reserve, footway or public place. Any gate openings shall be constructed so that the gates, when hung, will be fitted in such a manner that they will not open over the footway or public place.

Reason:- to ensure the fence/gates do not restrict access and that encroachments do not occur.

123. **Patron Behaviour**

The Management/Licensee shall ensure that the behaviour of patrons entering and leaving the premises does not detrimentally affect the amenity of the neighbourhood. In this regard the management shall be responsible for the control of noise, loitering and litter generated by patrons of the premises and shall ensure that people leave the premises and area in an orderly manner.

Reason:- to ensure that the use does not have an adverse impact on the amenity of the surrounding area.

124. **Graffiti and Vandalism Rectification**

Should the external fabric of the building(s), walls to landscaped areas and like constructions be subject to graffiti or like vandalism, then within seven (7) days of this occurrence, the graffiti must be removed and the affected surface(s) returned to a condition it was in before defilement.

Reason:- to ensure graffiti and vandalism is removed from premises in a timely manner and to protect the visual appearance of the area.

125. **Target hardening strategies to reduce crime**

The following target hardening strategies shall be undertaken on site to assist in the reduction of crime in the locality:-

- a) CCTV digital cameras shall be installed in and around the premises, particularly at the entry and exit points to assist police to identify offenders of crime.
- b) CCTV digital cameras shall be installed within the area situated underneath the driveway and port cochere structure adjacent to tenancies Numbered 12 and 13 to ensure suitable monitoring of this area occurs.
- c) Warning signs strategically posted in and around the premises to warn intruders of the security measures.
- d) Additional lightning be installed in and around the premises to act as a deterrent for crime. The lighting shall be installed in accordance with the Australian Standards 1158.3 1999.

The details shall be shown in the construction plans for approval by Council or the Accredited Certifier prior to the issue of a Construction Certificate.

Reason:- to reduce the incidence of late night crime in the locality and to improve public safety late at night.

126. **Separate development application for use**

A separate development application for any proposed use must be submitted for the approval of Council prior to any fit out or use of the commercial tenancies.

Reason:- to ensure that any proposed use has Council consent.

127. **Lighting to publicly accessible areas**

The following lighting requirements shall be complied with:

- a) The public areas shall be provided with lighting to ensure pedestrian safety. Such lighting shall be at a minimum level of 10 lux in the horizontal and vertical plane.
- b) Details of the lighting is to be submitted for the approval of the Principal

Certifying Authority prior to issue of the Construction Certificate and location of the lighting endorsed on the construction drawings.

Reason:- to ensure publicly accessible areas of the development are provided with sufficient illumination.

128. **Waste and recyclables storage area:**

The waste and recyclable storage area shall be fully enclosed, adequately ventilated and constructed with a concrete floor and concrete or cement rendered walls covering the floor. The floor shall be graded to an approved sewer connection incorporating a sump and galvanised grate cover or basket. A hot and cold hose cock shall be provided within the room. Details shall be provided with the Construction Certificate and endorsed on the construction drawings, and works completed prior to the issue of an Occupation Certificate.

Reason:- to ensure the waste and recyclables storage area is appropriately constructed and able to be readily cleaned and maintained.

129. **Ongoing Waste Management**

Ongoing waste management within the development shall be carried out in accordance with the approved Waste Management Plan and the following requirements:-

- a) Appropriate waste management practices are to be adopted within the development at all times.
- b) The waste storage room shall be kept in a clean, tidy and hygienic condition at all times.
- c) The waste and recyclable storage area shall be fully enclosed, adequately ventilated and constructed with a concrete floor and concrete or cement rendered walls covering the floor. The floor shall be graded to an approved sewer connection incorporating a sump and galvanised grate cover or basket. A hot and cold hose cock shall be provided within the room. Details shall be provided with the Construction Certificate and endorsed on the construction drawings, and works completed prior to the issue of an Occupation Certificate.
- d) A person shall be employed/nominated to manage the collection of waste material by Council, including, but not limited to bin placement at the road edge and retrieval of bins soon after collection of contents, cleansing of bins, storage of bins in the compound and the like.
- e) The nature strip is to be kept in a clean and tidy condition upon garbage collection.

Reason:- to ensure appropriate ongoing waste management practices within the development in accordance with Council's Development Control Plan requirements.

130. **Final Fire Safety Certificate**

Prior to the occupation of the building, the owner of the building shall submit to the Principal Certifying Authority (Council or Accredited Certifier), a **final fire safety certificate** in relation to each essential fire safety measure specified in the **fire safety schedule**, attached to the development consent or construction certificate.

Such certificate shall state that each essential fire safety measure specified:-

- a) Has been assessed by a properly qualified person, and
- b) Was found, at the date of assessment, to be capable of performing to a standard not less than that required by the current fire safety schedule for the building for which the certificate is issued.

**NOTES:**

1. As soon as practicable after a final fire safety certificate is issued, the owner of the building to which it relates:-
  - i) Must cause a copy of the statement (and current fire safety schedule) to be given to the Commissioner of NSW Fire Brigades, and
  - ii) Must cause a further copy of the statement (and current copy of the current fire safety schedule) to be prominently displayed in the building.
2. A "fire safety measure" is defined as any measure (including any item of equipment, form of construction or fire safety strategy) that is , or is proposed to be, implemented in the building to ensure the safety of persons using the building in the event of fire.

Reason:- to ensure compliance with Regulations 149 & 171 of the Environmental Planning and Assessment Regulation 2000.

**131. Annual Fire Safety Statement**

The owner of any building in which fire safety measures are installed, must cause the Council to be given an **annual fire safety statement**, within 12 months after the last such statement or final fire safety certificate was issued.

The certificate shall certify:-

- a) That each essential fire safety measure has been assessed by a properly qualified person and was found, at the date of assessment, to be capable of performing to a standard not less than that required by the current fire safety schedule.
- b) That a properly qualified person has inspected the building and has certified that, as at the date of inspection, the condition of the building did not disclose any grounds for a prosecution under Division C.

**NOTES:**

1. As soon as practicable after an annual fire safety statement is issued, the owner of the building to which it relates:-
  - i) must cause a copy of the statement (and current fire safety schedule) to be given to the Commissioner of NSW Fire Brigades, and
  - ii) must cause a further copy of the statement (and current copy of the current fire safety schedule) to be prominently displayed in the building.
2. A "fire safety measure" is defined as any measure (including any item of equipment, form of construction or fire safety strategy) that is, or is proposed to be, implemented in the building to ensure the safety of persons using the building in the event of fire.

Reason:- to ensure compliance with Regulation 171 of the Environmental Planning and Assessment Regulation 2000.

132. **Fire Safety Notices**

The fire-isolated stairway, fire-isolated passageway or fire-isolated ramp must contain a notice advising of "Offences relating to fire exits". The notice shall contain the wording prescribed by Clause 183 of the Environmental Planning and Assessment Regulation, 2000 and the Building Code of Australia.

Reason:- to comply with Clause 183 of the Environmental Planning and Assessment Regulation 2000 and the BCA.

133. **Occupation Certificate**

A person must not commence occupation or use of the whole or part of a new building unless an occupation certificate has been issued in relation to the building or part.

The application for an Occupation Certificate must be made to the Principal Certifying Authority (Council or an accredited certifier) using the approved form.

Reason:- to comply with the requirements of Section 109M/N of the Environmental Planning and Assessment Act.