4640 NOTE: - ALL OPENINGS WITHIN 3 METERS OF THE SIDE BOUNDARY ARE TO BE PROTECTED IN ACCORDANCE TO BCA CLAUSE C3.4. - IDENTIFY EACH DOOR REQUIRED BY CLAUSE E4.5 TO BE PROVIDED WITH AN EXIT SIGN AND STATE "EXIT" AND "LEVEL" FOLLOWED BY THE FLOOR NUMBER. - SIGNAGE IN ACCORDANCE WITH AS1428.1 MUST BE PROVIDED PROVIDED ACCESSIBLE FOR ACCESSIBLE UNISEX SANITARY FACILITIES TO IDENTIFY LEFT OR RIGHT HANDED USE ACCESS TO THE COURTYARD. - TGSI'S IN ACCORDANCE TO AS1428.4.1-2009 ARE TO BE PROVIDED TO: - ANY OVERHEADOBSTRUCTION LESS THAN 2m ABOVE FLOOR - TOP AND BOTTOM OF ALL STAIRWAYS AND RAMPS (EXCEPT FIRE-ISOLATED STAIRWAYS) - WHERE AN ACCESSWAY MEETS A VEHICULAR WAY ADJACENT TO ANY PEDESTRIAN ENTRANCE TO A BUILDING D3.12 GLAZING ON AN ACCESSWAY - ANY SUCH GLAZING ON AN ACCESSWAY MUST BE CLAERLY MARKED IN ACCORDANCE WITH AS1428.1-2009 E3.6 PASSENGER LIFTS (I) HANDRAIL COMPLYING WITH THE MANDATORY HANDRAIL PROVISIONS OF AS1735.12, (II) LIFT FLOOR DIMENSIONS NOT LESS THAN 1,400MM X 1,600MM AS THE LIFT VERTICAL TRAVELS ARE GREATER THAN 12M, (III) MINIMUM CLEAR DOOR OPENING COMPLYING WITH AS1735.12, (IV) PASSENGER PROTECTION SYSTEM COMPLYING WITH AS1735.12, (V) LIFT LANDING DOORS AT THE UPPER LANDING, C A1202 (VI) LIFT CAR AND LANDING CONTROL BUTTONS COMPLYING WITH AS1735.12, (VII) LIGHTING IN ACCORDANCE WITH AS1735.12, (VIII) LIFTS SERVING MORE THAN 2 LEVELS - AUTOMATIC AUDIBLE INFORMATION WITHIN THE LIFT CAR TO INDICATE THE LEVEL EACH TIME THE LIFT CAR STOPS; AUDIBLE AND VISUAL INDICATION AT EACH LIFT LANDING TO INDICATE THE ARRIVAL OF THE LIFT CAR; AUDIBLE INFORMATION AND AUDIBLE INDICATION IS TO BE PROVIDED IN A RANGE OF BETWEEN 20-80DB(A) AT A MAXIMUM FREQUENCY OF 1500HZ; Ά A1200 (IX) EMERGENCY HANDS-FREE COMMUNICATION, INCLUDING A BUTTON THAT ALERTS A CALL CENTRE OF A PROBLEM AND A LIGHT TO SIGNAL THAT THE CALL HAS BEEN RECEIVED. NEW RAISED LANDSCAPE FOR LOADING DOCK HEADROOM THE LIFT SHALL BE DETAIL DESIGNED TO ENSURE COMPLIANCE WITH THE ABOVE AND AS1428.1 AS APPLICABLE CLEARANCE ON GF. F2.4 ACCESSIBLE SANITARY FACILITIES TO BE COMPLIANCE TO AS1428.1-2009 ALL OPENINGS WITHIN 3 METRES OF THE SOUTHERN BOUNDARY ARE TO BE PROTECTED IN ACCORDANCE TO BCA CLAUSE C3.4. BALCONY 10.0sqm 3090 BALCONY 10.0sqm 2960 BALCONY 10.0sqm BED 2 BED 1 2000 2000 4375 116 VIIIWVIIIW LIVING 2 BED 70.0sqm BED 1 BED 2 ЦIVINĠ 113 117 .'DR¥∥ DINING DINING NFT DINING BATH 2 BED 83.0sqm 2 BED 70.0sqm 2 BED 78.0sqm kπ − BATH ST. LDRY · RL 25.50 7 6 5 4 3 2 FS4 HYD. ELEC L'DRY BATH AHA--KIT Ŀ \_\_\_\_\_₩# -DINING BED 1 BED 1 DINING BED 2 BED 1 له الله الله BED 1 115 BED 2 2 BED 71.0sqm 2 BED 72.3sqm 1380 2400 2100 μivinĝ BED 2 BALCONY n 12.0sqm L<del>'IVING</del> BALCONY 11.1sqm 2.8sqm 2.8sqm 3960 3000 BOUNDARY (2324.45 SQM) 10400 4640 X,Y= 0,0  $(\mathsf{D})$ 

