

Project Name -	Belmore, 717-727 Canterbury Road	
Lift No -	1-3-5-6	2-4
Design Standard	EN81-1	
No. of Lifts	6 x Simplex Configuration	
No. of Floors	8	
No. of Front Entrances	8	6
No. of Rear Entrances	0	2
Travel (m)	15.6m (TBC)	
Headroom	3580	
Minimum Pit Depth	1150	
Clear Door Opening (WxH)	900 x 2100	
Internal Shaft Size (WxD)	1975 x 2285	1975 x 2400
Internal Car Size (WxDxH)	1400 x 2000 x 2200	1400 x 2000 x 2200
Elevator Type	KONE N MonoSpace™	
	Gearless Underslung Traction	
Counterweight Safety Gear	Not Required	
Control System	Lift Controller EcoDisc (LCE) - Serial Transmission	
Drive	Variable Voltage Variable Frequency	
Control Logic	Full Collective (FC)	
Load Rating	1200 kg	
Speed	1.0 m/s	
Landing Doors	Two Piece with 70mm Narrow Factory Clad Frames	
	Silver Brushed Stainless Steel (ST43)	
Maintenance Access Panel	Recess mounted, Silver Brushed Stainless Steel, Located on Top Floor	
Car Doors	Silver Brushed Stainless Steel (ST43)	
	2D Curtain of Light	
Car Interior Walls	Silver Brushed Stainless Steel (ST43)	
Front Wall	Silver Brushed Stainless Steel (ST43)	
Handrail	HR64 (Aluminium) Wall D	
Ceiling	CL88 (ST43)	
Floor	Local Floor	
Car Signalisation	1 x KDS 50 Car Operating Panels (COP)	2 x KDS 50 Car Operating Panels (COP)
	Round Surface Mounted Buttons – AS1735.12 Compliant	
	Car Light and Ventilation Keyswitch (OLV AU)	