

CONDITIONS OF CONSENT

- 1) The proposal shall comply with the conditions of Development Consent. A Construction Certificate shall not be issued until the plans and specifications meet the required technical standards and the conditions of this Development Consent are satisfied.
- 2) Development shall take place in accordance with Development Application No. DA-559/2016, submitted by C Stanley C/- Ghazi Al Ali Architect, accompanied by Drawing No. A 1200, A 1201, A 1202, A 1203, A 1204, A 1205, A 1206 and A 1207, Issue C, dated 21 December 2016, Drawing No. A 1208, A 1301, A 1302, A 1303, A 1304, A 1401, A 1402 and A 1403, Issue B, dated 28 October 2016, and Drawing No. A 1101, Issue A, dated 9 June 2016, prepared by Ghazi Al Ali Architect and affixed with Council's approval stamp, except where otherwise altered by the specific amendments listed hereunder and/or except where amended by the conditions contained in this approval.

The development plans shall be amended as follows:

- a) Drawing No. A 1202 (Basement 01 Floor Plan) shall be amended to accommodate a maximum of six (6) visitor car parking spaces, to ensure a minimum of seventy-two (72) residential car parking spaces are provided in accordance with *State Environmental Planning Policy (Affordable Rental Housing) 2009*. The Construction Certificate plans shall reflect this requirement.
- b) The architectural plans shall ensure full compliance with Objective 4G-1 of the *Apartment Design Guide* with respect to storage. The minimum storage areas are as follows:
 - 6m³ for one bedroom apartments;
 - 8m³ for two bedroom apartments; and
 - 10m³ for three bedroom apartments.

A minimum of 50% of the required storage is to be accommodated within each apartment. The remaining storage may be accommodated within the basement storage rooms. The Construction Certificate plans shall reflect this requirement.

- c) The corridors that are enclosed at one or both ends by louvre panels/gates (on the Ground Floor and Levels 5-10) are to be a minimum of 50% open to ensure these areas do not meet the definition of 'gross floor area' in accordance with the *State Environmental Planning Policy (Affordable Rental Housing) 2009*. The Construction Certificate plans shall reflect this requirement.
- 3) For 10 years from the date of the issue of the Occupation Certificate:

- a) Unit numbers G.01-G.06, 1.01-1.07, 2.01-2.07, 3.01-3.07, 4.01-4.07 and 5.01-5.06 (inclusive) must be used for the purposes of affordable rental housing; and
- b) All accommodation that is used for affordable rental housing must be managed by a registered community housing provider.

A restriction must be registered, before the date of the issue of the Occupation Certificate, against the title of the property, in accordance with section 88E of the *Conveyancing Act, 1919* to ensure that the requirements of this condition are met.

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF A CONSTRUCTION CERTIFICATE

Prior to the release of a Construction Certificate the following conditions MUST be satisfied and nominated fees/contributions/bonds paid:

- 4) The Certifying Authority must ensure that any certified plans forming part of the Construction Certificate are not inconsistent with this Development Consent and accompanying plans.
- 5) A detailed landscape plan prepared by a qualified landscape architect or designer is to be approved prior to the issue of a Construction Certificate. The landscape plan is to be prepared in accordance with the relevant DCP and is to show all features, built structures including retaining walls, irrigation, mulch and natural features such as significant gardens, landscaping, trees, natural drainage lines and rock outcrops that occur within 3 metres of the site boundary. The landscape plan shall consider any stormwater, hydraulic or overland flow design issues where relevant.

The concept landscape plan submitted with the application proposes seven (7) x 45L *Plumeria acutifolia*, however a minimum pot size of 100L shall be proposed for these plantings.

- 6) The landscape plan shall include the provision for the replacement of all boundary fencing. A new 1.8m fence is to be erected along all side and rear boundaries of the subject allotment at full cost to the developer. The colour of the fence is to complement the development and the fence is to be constructed of lapped and capped timber paling, sheet metal or other suitable material unless the type of material is stipulated in any flood study prepared for the site. The selection of materials and colours of the fence is to be determined in consultation with the adjoining property owners. Fencing forward of the building line shall be no higher than 1m unless otherwise approved by Council.
- 7) Approval in accordance with Council's Tree Preservation Order (TPO) is granted to lop or remove only the trees identified to be lopped or removed on the approved plans. Separate approval shall be obtained to prune or remove trees on adjoining properties or other trees located on the site.

Failure to comply with Council's TPO may result in a fine of up to \$100,000.

- 8) A soil erosion and sediment control plan must be prepared by a suitably qualified professional, in accordance with the Bankstown Demolition and Construction Guidelines and Council's Development Engineering Standards, and submitted to the certifying authority for approval prior to the issue of a construction certificate.
- 9) The Council Approved building plans, including demolition plans, must be submitted to Sydney Water for assessment. This will determine if the proposed structure(s) would affect any Sydney Water infrastructure or if there are additional requirements. Building plan approvals can be submitted online via Sydney Water Tap in™.

Please refer to www.sydneywater.com.au/tapin

For Sydney Water's Guidelines for building over or next to assets, visit www.sydneywater.com.au 'Plumbing, building & developing' then 'Building Plan Approvals' or call 13000 TAPIN.

Prior to release of a construction certificate Sydney Water must issue either a Building Plan Assessment letter which states that your application is approved, or the appropriate plans must be stamped by a Water Servicing Coordinator.

- 10) A Construction Certificate shall not be issued until written proof that all bonds, fees and/or contributions as required by this consent have been paid to the applicable authority.
- 11) A long service levy payment which is 0.35% of the total cost of the work is to be paid to the Building and Construction Industry Long Service Payments Corporation.
- 12) Pursuant to section 80A(1) of the Environmental Planning and Assessment Act 1979, and the Bankstown City Council Section 94A Development Contributions Plan 2009 (Section 94A Plan), a contribution of \$80,717.65 shall be paid to Council.

The amount to be paid is to be adjusted at the time of actual payment, in accordance with the provisions of the Section 94A plan. The contribution is to be paid before the issue of the construction certificate.

Note: The Section 94A Contributions Plans may be inspected at Council's Customer Service Centre, located at Upper Ground Floor, Civic Tower, 66-72 Rickard Road, Bankstown, between the hours of 8.30am-5.00pm Monday to Friday.

- 13) Finished surface levels of all internal works and at the street boundary, including driveways, landscaping and drainage structures, must be as

shown on the approved plans. The levels at the street boundary must be consistent with the Street Boundary Alignment Levels issued by Council.

- 14) A Work Permit shall be applied for and obtained from Council for the following engineering works in front of the site, at the applicant's expense:
- a) A heavy duty VFC at the property boundary on Stanley Street, setback a minimum of 600mm from the existing power pole. The existing stormwater lintel in conflict with this VFC shall be removed and replaced to Council's satisfaction.
 - b) Drainage connection to Council's system.
 - a) The pavement on Cross Street is to be full-width asphalt with concrete unit paver banding and header course to BCC Standard Drawing S-024. The pavement on Stanley Street is to match existing concrete 1.5m pathway with grassed verge and boundary strip either side. An arborist shall attend the site during excavation and replacement of the concrete pathway, with respect to the retention and protection of the street trees on Stanley Street.
 - c) Removal of all driveway surfaces, reinstatement of laybacks to kerb and gutter and reshaping of the footway, all associated with redundant VFCs.
 - d) Repair of any damage to the public road including the footway occurring during development works.
 - e) Reinstatement of the footway reserve and adjustment or relocation of existing public utility services to match the footway design levels as proposed on the approved Work Permit. Adjustment or relocation to any public utility services shall be carried out to the requirements of the public utility authority.

Note: As a site survey and design is required to be prepared by Council in order to determine the necessary information, payment for the Work Permit should be made at least twenty one (21) days prior to the information being required and must be approved prior to the issue of the Construction Certificate.

- 15) Stormwater drainage from the development shall be designed so as to comply with Council's Development Engineering Standards and the requirements of the BASIX Certificate. A final detailed stormwater drainage design shall be prepared by a qualified Professional Civil Engineer in accordance with the above requirements and shall generally be in accordance with the concept Stormwater Plan No. 20160113, Issue A, dated 23/11/2016, prepared by SGC Engineering Value. The final plan shall be certified by the design engineer that it complies with Council's Development Engineering Standards, the BASIX Certificate and the relevant Australian Standards.
- 16) Where Council approved cut or fill exceeds 200mm and stable batter of 1 vertical to 3 horizontal maximum grade cannot be achieved, then a masonry or other proprietary material retaining wall, intended and suitable

for that purpose, shall be constructed within the development site. Note, filling of the site needs specific approval from Council.

The retaining wall shall be located so that it will not impede or obstruct the natural flow of stormwater. Retaining walls exceeding 600mm in height shall be designed by a qualified professional Civil/Structural Engineer. Plans and details prepared and signed by the Engineer are to be submitted to the Principal Certifying Authority (PCA) prior to the issue of the Construction Certificate.

All works associated with the construction of the wall, including backfilling and drainage, is to be located wholly within the allotment boundaries.

- 17) An all-weather pavement shall be designed to withstand the anticipated wheel loads for all areas subjected to vehicular movements. Internal pavements specification prepared and certified by all qualified professional Civil Engineer to comply with the relevant Australian Standards, shall be submitted to the Principal Certifying Authority (PCA) for approval prior to the issue of a construction certificate.
- 18) The development is to be carried out in accordance with the commitments shown on the BASIX Certificate. The BASIX commitments approved with this Development Application are to be reflected in the Construction Certificate plans and specifications. Any proposed changes to the BASIX commitments after the Construction Certificate has been issued will require an updated BASIX Certificate and a new Construction Certificate.
- 19) A Construction Certificate shall not be issued until design verification from a qualified designer has been received. The design verification is a statement in which the qualified designer verifies that the plans and specifications achieve or improve the design quality of the development of which Development Consent was granted, having regard to the design quality principles set out in Schedule 1 of SEPP No. 65.
- 20) The development, containing 70 residential units, requires allocation of waste and recycling bins based on 120L/unit/week for both services:
 - 8 x 1100L bulk garbage bins (collected weekly);
 - 8 x 1100L bulk recycling bins (collected weekly); and
 - 10 x 240L garden organics bins (collected fortnightly).

Bin Type	Height	Width	Depth
240 Litres	1080mm	580mm	735mm
1100 Litres	1470mm	1370mm	1245mm

The Construction Certificate plans shall ensure that the permanent bin storage area in the basement is sufficient in size to accommodate 16 x 1100L bins and 10 x 240L garden organics bins side-by-side with equal and convenient access to all bins by residents, as well as sufficient room for manoeuvring bins. The area should minimise floor space to prevent

residents from dumping unwanted waste that does not fit in the bins. The room shall be signposted 'Waste & Recycling' on the entrance door. The door and entrance area shall be at least 2500mm in width.

The temporary bin holding area at ground level must be sufficient in size to accommodate 16 x 1100L bins with sufficient room for manoeuvring bins. The collection area shall be within 10 metres of the property boundary on Cross Street, with convenient layback to the roadway (or remain flat to the truck loading area).

Any modifications to the permanent bin storage area or the temporary bin holding area must not impact the provision of parking or communal open space, unless prior approval is obtained.

- 21) The developer shall apply to the Bankstown Traffic Committee to have 'No Parking Waste Nights Only' signage at the Cross Street frontage. The developer shall apply and pay for the signage prior to the issue of a Construction Certificate.
- 22) The developer is to apply to Council's Traffic Engineer for a Works Zone across the frontage of Cross Street. This is subject to recommendation by the Bankstown Traffic Committee and must be approved and paid for prior to the issue of a Construction Certificate.
- 23) The Construction Certificate plans shall ensure that the splay edges on the sides of the driveway are kept clear and comply with the sight distance triangle requirements in accordance with Australian Standards.
- 24) Prior to the issue of any Construction Certificate for this development, the applicant must obtain approval from Council for a Site, Pedestrian and Traffic Management Plan. This Plan must address the measures that will be implemented for the protection of adjoining properties, pedestrian safety and traffic management and other requirements as specified below.

A PRIVATE CERTIFIER CANNOT APPROVE YOUR SITE, PEDESTRIAN & TRAFFIC MANAGEMENT PLAN

This plan shall include details of the following:

- a) Proposed ingress and egress points for vehicles to and from the construction site;
- b) Proposed protection of pedestrians, adjacent to the construction site;
- c) Proposed hoardings, scaffolding and/or fencing to secure the construction site;
- d) Proposed pedestrian management whilst vehicles are entering/exiting the construction site;
- e) Proposed measures to be implemented for the protection of all public roads and footway areas surrounding the construction site from

- building activities, crossings by heavy equipment, plant and materials delivery and static load from cranes, concrete pumps and the like;
- f) Proposed method of loading and unloading excavation machines, building material, construction materials and waste containers during the construction period;
- g) Proposed traffic control measures such as advanced warning signs, barricades, warning lights, after hours contact numbers etc are required to be displayed and shall be in accordance with Council's and the NSW Roads and Maritime Services requirements and AS1742.3.
- h) Proposed method of support of any excavation, adjacent to adjoining buildings or the public road. The proposed method of support is to be certified by a Civil Engineer with National Professional Engineering Registration (NPER) in the construction of civil works.
- i) Proposed measures to be implemented in order to ensure that no soil/excavated material is transported on wheels or tracks of vehicles or plant and deposited on the public road.
- j) Proposed measures for protection of the environment including procedures to control environmental impacts of work e.g. sediment control, proper removal, disposal or recycling of waste materials, protection of vegetation and control/prevention of pollution i.e. water, air noise, land pollution.

The approved Site, Pedestrian and Traffic Management Plan is to be implemented prior to the commencement of any works on the construction site. The applicant will be required to pay for inspections by Council Officers in accordance with Council's adopted fees and charges.

In addition a RMS Approval / Road Occupancy Licence will be required for works on Regional or State Roads or within 100m of a traffic facility including roundabouts and traffic signals. Refer to Council's Development Engineering Standards for a list of Regional and State Roads.

- 25) As any works within, or use of, the footway or public road for construction purposes requires separate Council approval under Section 138 of the Roads Act 1993 and/or Section 68 of the Local Government Act 1993, Council requires that prior to any Construction Certificate for this development being issued, a Works Permit and or a Roadway/Footpath Building Occupation Permit shall be obtained where one or more of the following will occur, within, on or over the public footway or public road:

A PRIVATE CERTIFIER CANNOT ISSUE THESE PERMITS

WORKS REQUIRING A 'WORKS PERMIT'

- a) Dig up, disturb, or clear the surface of a public footway or public road,
- b) Remove or interfere with a structure or tree (or any other vegetation) on a public footway or public road,
- c) Connect a road (whether public or private) to a classified road,

- d) Undertake footway, paving, vehicular crossing (driveway), landscaping or stormwater drainage works within a public footway or public road,
- e) Install utilities in, under or over a public road,
- f) Pump water into a public footway or public road from any land adjoining the public road,
- g) Erect a structure or carry out a work in, on or over a public road
- h) Require a work zone on the public road for the unloading and or loading of vehicles
- i) Pump concrete from within a public road,
- j) Stand a mobile crane within a public road
- k) Store waste and recycling containers, skips, bins and/or building materials on any part of the public road.
- l) The work is greater than \$25,000.
- m) Demolition is proposed.
- n) Subdivision is proposed.
- o) A Swimming pool is proposed.

Assessment of Works Permits (a to e) includes the preparation of footway design levels, vehicular crossing plans, dilapidation reports and issue of a Road Opening Permit.

All proposed works within the public road and footway shall be constructed under the supervision and to the satisfaction of Council. The applicant/developer shall arrange for necessary inspections by Council whilst the work is in progress.

For commercial or multi-unit residential developments within the designated CBD or an urban village area, footway design and construction and street tree supply, installation and tree hole detailing shall be as per the Council master plan for that area. Full width footways are to be supplied and installed at full cost to the developer to specification as supplied by Council. Layout plan of pavement to be submitted to Council for approval prior to the issue of the Works Permit.

All Council fees applicable, minimum restoration charges and inspection fees shall be paid prior to the assessment of the Work Permit in accordance with Council's adopted fees and charges. Note: Additional fees after approval will be charged where the Work Permit requires occupation of the Road or Footpath ie Hoardings, Work Zones etc.

In determining a Works Permit, Council can impose conditions and require inspections by Council Officers.

Forms can be obtained from Council's Customer Service counter located on the ground floor of Council's administration building at 66 - 72 Rickard Road, Bankstown or Council's website www.bankstown.nsw.gov.au

Part of any approval will require the person or company carrying out the work to carry public liability insurance to a minimum value of ten million

dollars. Proof of the policy is to be provided to Council prior to commencing any work approved by the Work Permit including the Road Opening Permit and must remain valid for the duration of the works.

The commencement of any works on public land, including the footway or public road, may incur an on the spot fine of not less than \$1100 per day that work continues without a Works Permit and/or a Roadway/Footpath Building Occupation Permit.

All conditions attached to the permit shall be strictly complied with prior to occupation of the development. Works non-conforming to Council's specification (includes quality of workmanship to Council's satisfaction) shall be rectified by the Council at the applicant's expense.

- 26) The subject site is affected by local overland flooding and shall comply with the following:
 - a) The minimum habitable floor level of the proposed structure(s) shall be constructed to RL 17.5m AHD including freeboard. All approved construction details shall be consistent with this requirement.
- 27) The pump out drainage system for the access ramp and basement car parking area shall be provided in accordance with Council's Development Engineering Standards. Engineering details and specifications shall be submitted to the Principal Certifying Authority (PCA) for approval prior to the issue of any Construction Certificate.
- 28) Engineering details and manufacturers specifications for the pumps, switching system and sump pit shall be submitted to the Principal Certifying Authority (PCA) for approval prior to issue of any Construction Certificate.
- 29) For internal driveways with a gradient exceeding 10% (1 in 10), longitudinal profiles of all vehicular driveways and ramps shall be submitted for approval by the Principal Certifying Authority (PCA) prior to the issue of the Construction Certificate. The maximum grade of the driveway/ramp shall not exceed **25%** and shall comply with AS 2890.1. The profile shall be drawn at a reduction ratio of 1 to 25 vertical and horizontal and shall be related to the datum used for the issue of the footway design levels and shall also show the road centre line levels, Council issued footway design levels and gutter levels. Council's Car Clearance Profile in Council's Development Engineering Standards, (Plan No. S 006) shall be used to design the profile.
- 30) The basement of the development is located adjacent to a Council Public Road Reserve. Separate approval and Work Permit is to be obtained from Council for any temporary or permanent anchoring works under Council's Public Road.

- 31) The route for transportation to and from the development site of bulk and excavation materials shall generally be by the shortest possible route to the nearest "regional road", with every effort to avoid school zones on public roads. The applicant shall nominate the route for approval by Council prior to commencement of any work on the site. An Agreement to Council's satisfaction, signed by the applicant/owner specifying the approved route and acknowledging responsibility to pay Council for damages to public property adjacent to the site shall be lodged with Council prior to release of any Construction Certificate. All damage must be rectified upon completion of work.

CONDITIONS TO BE SATISFIED PRIOR TO CONSTRUCTION

- 32) The building / subdivision work in accordance with the development consent must not be commenced until:
- a. a construction certificate for the building / subdivision work has been issued by the council or an accredited certifier, and
 - b. the person having benefit of the development consent has:
 - i. appointed a principal certifying authority for the building / subdivision work, and
 - ii. notified the principal certifying authority that the person will carry out the building work as an owner-builder, if that is the case, and
 - c. the person having the benefit of the development consent, if not carrying out the building work as an owner-builder, has:
 - i. appointed a principal contractor for the building work who must be the holder of a contractor licence if any residential building work is involved, and
 - ii. notified the principal certifying authority of any such appointment, and
 - iii. unless the person is the principal contractor, notified the principal contractor of any critical stage inspections and other inspections that are to be carried out in respect of the building work, and
 - d. the person having the benefit of the development consent has given at least 2 days' notice to the council of the person's intention to commence the building / subdivision work.
- 33) Existing trees within the vicinity of the construction works or paths of travel for construction vehicles accessing the development that are to be retained shall be protected with temporary fencing of a style non injurious to tree roots, placed 2m from the trunk base of the existing tree to prevent

damage during construction, and retained in accordance with Council's Tree Preservation Order. There is to be no stockpiling of materials within the 2m fenced zone.

34) Trees removal: On-site

There are no trees to be retained on this site. All tree removal works must comply with the *Amenity Tree Industry – Code of Practice, 1998* (Workcover, NSW).

35) Tree Removal: Nature Strip / Council Reserve

Approval is granted for the removal of the following trees:

Species	Location
Two (2) x <i>Callistemon viminalis</i> (Bottlebrush)	Council naturestrip, Cross Street frontage, forward of the property line
One (1) x <i>Melaleuca decora</i> (White Feather Honey Myrtle).	Council naturestrip, Cross Street frontage, forward of the property line

The tree removal works are subject to the following conditions:

- a) All tree removal works must be carried out by a qualified arborist with a minimum of AQF (Australian Qualification Framework) Certificate III in Arboriculture;
- b) The tree removal contractor must hold a Public Liability Insurance Certificate of Currency with a minimum indemnity of \$20 million, together with a NSW Workers Compensation Insurance Certificate of Currency;
- c) The tree removal work must comply with the *Amenity Tree Industry – Code of Practice, 1998* (Workcover, NSW);
- d) The tree stump is to be ground to 300mm below ground level. Investigation to locate underground services shall be the responsibility of the applicant.
- e) All tree material shall be removed from site, and the nature strip shall be backfilled, compacted and restored to the original level
- f) The site must be maintained in a safe condition at all times;
- g) Appropriate hazard signage to be in place at all times during the tree works.

All other street vegetation not specifically identified above is to be retained and protected from construction damage and pruning.

36) Tree Retention and Protection: Nature Strip / Council Reserve

The following trees located on Council's nature strip are to be retained and protected as per the conditions below. Failure to comply with these conditions is an offence and may incur a fine or lead to prosecution.

Species	Location
Two (2) x <i>Lophostemon confertus</i> (Brushbox)	Council's naturestrip, forward of the property line at Nos. 13 and 15 Stanley Street

- a) Tree protection measures shall comply with *Australian Standard AS4970-2009 Protection of trees on development sites*.
 - b) The tree protection fencing is to be constructed of chain wire mesh 1.80 metres high, supported by steel posts and shall remain in place throughout the duration of site works. The fence is to be installed prior to demolition / construction and shall not be removed or altered
 - c) A durable, weather resistant sign is to displayed in a prominent location on the fencing of each protection zone having a minimum dimension of 500mm high x 400mm wide of similar design and layout as per Appendix C, *Australian Standard AS4970-2009 Protection of trees on development sites* clearly showing clearly showing:
 - The development consent number
 - The name and contact number of the nominated consultant arborist or site manager;
 - Indication that access into the Tree Protection Zone is not permitted.
 - d) No vehicular access, excavations for construction or installation of services shall be carried out within the fenced off Tree Protection Zone.
 - e) All utility services, pipes, stormwater lines and pits are to be located outside the fenced off Tree Protection Zone.
 - f) Building materials, chemical storage, site sheds, wash out areas, and similar shall not be located within the fenced off Tree Protection Zone.
 - g) Trees marked for retention must not to be damaged or used to display signage, or as fence or cable supports for any reason.
- 37) Suitable erosion and sediment control measures shall be erected in accordance with the plans accompanying the Construction Certificate prior to the commencement of construction works and shall be maintained at all times.
 - 38) Council warning sign for Soil and Water Management must be displayed on the most prominent point of the site, visible to both the street and site works. The sign must be displayed throughout the construction period.
 - 39) Prior to the commencement of work, the applicant must provide a temporary on-site toilet if access to existing toilets on site is not adequate.
 - 40) A section 73 compliance certificate under the Sydney Water Act 1994 must be obtained from Sydney Water Corporation. Make early application for the certificate, as there may be water and sewer pipes to be built and this can take some time. This can also impact on other services and building, driveway or landscape design.

Application must be made through an authorised Water Servicing Coordinator. For help either visit www.sydneywater.com.au > Building and Developing > Developing your Land > Water Servicing Coordinator or telephone 13 20 92.

- 41) Prior to the commencement of work, a fence must be erected around the area of the works, except where an existing 1.8m high boundary fence is in good condition and is capable of securing the area. Any new fencing shall be temporary (such as cyclone wire) and at least 1.8m high. All fencing is to be maintained for the duration of construction to ensure that the work area is secured.

Where the work is located within 3.6m of a public place then a Type A or Type B hoarding must be constructed appropriate to the works proposed. An application for a Work Permit for such hoarding must be submitted to Council for approval prior to the commencement of work.

- 42) A sign shall be displayed on the site indicating the name of the person responsible for the site and a telephone number of which that person can be contacted during and outside normal working hours or when the site is unattended.
- 43) In the case of residential building work for which the Home Building Act 1989 requires there to be a contract of insurance in force in accordance with Part 6 of the Act, that such a contract of insurance is in force before any building work authorised to be carried out by the consent commences.
- 44) Residential building work within the meaning of the Home Building Act 1989 must not be carried out unless the principal certifying authority for the development to which the work relates (not being the council) has given the council written notice of the following information:
- a. in the case of work for which a principal certifying is required to be appointed:
 - i. the name and licence number of the principal contractor, and
 - ii. the name of the insurer by which the work is insured under Part 6 of the Act,
 - b. in the case of work to be done by an owner-builder:
 - i. the name of the owner-builder, and
 - ii. If the owner-builder is required to hold an owner-builder permit under that Act, the number of the owner-builder permit.

If arrangements for doing the residential building work are changed while the work is in progress so that the information notified becomes out of date, further work must not be carried out unless the principal certifying

authority for the development to which the work relates (not being the council) has given the council written notice of the updated information.

- 45) A sign must be erected in a prominent position on any site on which building work, subdivision work or demolition work is being carried out:
- a. showing the name, address and telephone number of the principal certifying authority for the work, and
 - b. showing the name of the principal contractor (if any) for any building work and a telephone number on which that person may be contacted outside working hours, and
 - c. stating that unauthorised entry to the work site is prohibited.

Any such sign is to be maintained while the building work, subdivision work or demolition work is being carried out, but must be removed when the work has been completed.

- 46) Permission is granted for the demolition of the structures currently existing on the property, subject to strict compliance with the following:
- a) The developer is to notify adjoining residents seven (7) working days prior to demolition. Such notification is to be clearly written on A4 size paper giving the date demolition will commence and be placed in the letterbox of every premises (including every residential flat or unit, if any) either side, immediately at the rear of, and directly opposite the demolition site.
 - b) Written notice is to be given to Canterbury-Bankstown Council for inspection prior to demolition. Such written notice is to include the date when demolition will commence and details of the name, address, business hours and contact telephone number and licence number of the demolisher. The following building inspections shall be undertaken by Canterbury-Bankstown Council:
 - (i) A *precommencement* inspection shall be carried out by Council when all the site works required as part of this consent are installed on the site and prior to demolition commencing.
 - (ii) A *final* inspection shall be carried out by Council when the demolition works have been completed to ensure that the site is left in a satisfactory manner, in accordance with the conditions of this consent.

Note: Payment of an inspection fee at Council's current rate will be required prior to each inspection. Council requires 24 hours notice to carry out inspections. Arrangements for inspections can be made by phoning **9707 9410, 9707 9412 or 9707 9635.**

- c) Prior to demolition, the applicant must erect a sign at the front of the property with the demolisher's name, license number, contact phone number and site address.
- d) Prior to demolition, the applicant must erect a 2.4m high temporary fence or hoarding between the work site and any public place. Access to the site shall be restricted to Authorised Persons Only and the site shall be secured against unauthorised entry when the building work is not in progress or the site is otherwise unoccupied. Where demolition is to occur within 3m of a public place a Work Permit application for the construction of a Class A or Class B hoarding shall be submitted to Council for approval.
- e) The demolition plans must be submitted to the appropriate Sydney Water Office to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements. If the development complies with Sydney Water's requirements, the demolition plans will be stamped indicating that no further requirements are necessary.
- f) Demolition is to be carried out in accordance with the appropriate provisions of Australian Standard AS2601-2001.
- g) The hours of demolition work shall be limited to between 7.00am and 6.00pm on weekdays, 7.00am and 1.00pm on Saturdays and no work shall be carried out on Sundays and public holidays, and weekends (Saturdays and Sundays) adjacent to public holidays.
- h) Where materials containing asbestos cement are to be removed, demolition is to be carried out by licensed contractors who have current Workcover Accreditation in asbestos removal.
- i) Hazardous or intractable wastes arising from the demolition process shall be removed and disposed of in accordance with the requirements of WorkCover NSW and the NSW EPA 'Environmental Guidelines: Assessment, Classification and Management of Liquid and Non-Liquid Wastes 2004'.
- j) Demolition procedures shall maximise the reuse and recycling of demolished materials in order to reduce the environmental impacts of waste disposal.
- k) During demolition, the public footway and public road shall be clear at all times and shall not be obstructed by any demolished material or vehicles. The public road and footway shall be swept (NOT hosed) clean of any material, including clay, soil and sand. (NOTE: If required, Council will clean the public road/footway at the applicant's expense). On the spot fines may be levied by Council against the demolisher and or owner for failure to comply with this condition.

- l) All vehicles leaving the site with demolition materials shall have their loads covered and vehicles shall not track soil and other material onto the public roads and footways and the footway shall be suitably protected against damage when plant and vehicles access the site. All loading of vehicles with demolished materials shall occur on site.
 - m) The burning of any demolished material on site is not permitted and offenders will be prosecuted.
 - n) Care shall be taken during demolition to ensure that existing services on the site (ie. sewer, electricity, gas, phone) are not damaged. Any damage caused to existing services shall be repaired by the relevant authority at the applicant's expense.
 - o) Suitable erosion and sediment control measures shall be erected prior to the commencement of demolition works and shall be maintained at all times.
 - p) Prior to the demolition of any building constructed before 1970, a Work Plan shall be prepared and submitted to Council in accordance with Australian Standard AS2601-2001 by a person with suitable expertise and experience. The Work Plan shall outline the identification of any hazardous materials, including surfaces coated with lead paint, method of demolition, the precautions to be employed to minimise any dust nuisance and the disposal methods for hazardous materials.
- 47) Prior to the commencement of works, dilapidation reports shall be prepared by the developer and a copy provided to the respective property owners, for the properties immediately adjoining the subject site at Nos. 17 Stanley Street and 6 Cross Street. The reports must clearly identify the condition of existing structures on the adjoining properties prior to the commencement of works. All care shall be taken during the excavation and construction process to ensure adjoining structures are protected, and should any change in condition occur from that recorded in the dilapidation report, the rectification of such shall be at full cost to the developer of the subject site.

CONDITIONS TO BE SATISFIED DURING CONSTRUCTION

- 48) The hours of site works shall be limited to between 7.00am and 6.00pm on weekdays and 7.00am and 1.00pm on Saturdays. No work shall be carried out on Sundays and public holidays, and weekends (Saturdays and Sundays) adjacent to public holidays.
- 49) The building work must be carried out in accordance with the requirements of the Building Code of Australia.

- 50) The developer is to ensure that the works do not contravene Ausgrid's Technical Standards and statutory requirements with regard to the safe and reliable operation and maintenance of its network.

Any work undertaken near overhead power lines shall be done in accordance with:

- Workcover Document ISSC 23 "Working Near Overhead Power Lines";
- Ausgrid's Network Standards, in particular NS220 "Overhead Design Section 13 Clearances"; and
- Ausgrid's Electrical Safety Rules.

Excavation works near underground cables shall be done in accordance with Ausgrid Network Standard 156 "Working Around Ausgrid Cables".

- 51) Prior to the ground floor slab being poured, an identification report by a Registered Surveyor must be submitted to the principal certifying authority verifying that the proposed buildings finished ground floor level and siting to the property boundaries conforms to the approved plans.
- 52) All Civil and Hydraulic engineering works on site must be carried out in accordance with Council's Development Engineering Standards. All Civil and Hydraulic engineering works associated with Council's assets and infrastructure must be carried out in accordance with Council's Work Permit requirements and to Council's satisfaction.
- 53) All excavations and backfilling must be executed safely and in accordance with the relevant Australian Standards.
- 54) If soil conditions require it, retaining walls or other approved methods of preventing movement of the soil must be provided, and adequate provisions must be made for drainage. Separate approval may be required for retaining walls should they be required.
- 55) If the development involves an excavation that extends below the level of the base of the footings of a building on adjoining land, the person having the benefit of the development consent must, at the person's own expense:
- a. protect and support the adjoining premises from possible damage from the excavation, and
 - b. where necessary, underpin the adjoining premises to prevent any such damage.
- 56) All boundary fencing behind the building line shall be replaced by a 1.8m high lapped and capped timber or sheet metal fence, or as stipulated in a flood study prepared for the site, or as determined in consultation with the adjoining property owners at the developer's expense. Fencing forward of

the building line shall be no higher than 1m unless otherwise approved by Council.

- 57) The stormwater drainage system shall be constructed in accordance with Council's Development Engineering Standards and the engineering plans and details approved by the Principal Certifying Authority (PCA). Should the developer encounter any existing, live, underground stormwater drainage pipes, which carry flow from upstream properties, the developer must maintain the stormwater flow and re-route the stormwater pipes around the subject building or structures at the developer's expense.
- 58) A suitably qualified Professional Civil or Structural Engineer shall be engaged by the developer to carry out inspections relating to construction of internal driveways and parking areas. The work shall be carried out in accordance with the approved plans and specifications and certification from the Civil or Structural Engineer is to be provided upon completion.
- 59) Prior to the commencement of work, the builder shall prepare a photographic record of the road reserve which clearly shows its condition prior to works occurring on site. For the entirety of demolition, subdivision or construction works, there shall be no stockpiling of building spoil, materials, or storage of equipment on the public road, including the footway and the road reserve shall be maintained in a safe condition at all times. No work shall be carried out on the public road, including the footway, unless a Work Permit authorised by Council has been obtained.

CONDITIONS TO BE SATISFIED PRIOR TO OCCUPATION

- 60) The occupation or use of the building must not be commenced unless an occupation certificate has been issued for the building.
- 61) A final Occupation Certificate shall not be issued until all conditions relating to demolition, construction and site works of this development consent are satisfied and Council has issued a Work Permit Compliance Certificate.
- 62) Consolidation of the existing allotments must be registered by the office of Land and Property Information prior to the issue of an occupation certificate.
- 63) Seventy-eight (78) off-street car spaces being provided in accordance with the submitted plans. This shall comprise:

Seventy-two (72) residential spaces
Six (6) residential visitor spaces

Three (3) of the above car parking spaces are to be provided for people with mobility impairment in accordance with AS 2890.1. All car parking spaces shall be allocated and marked according to these requirements.

- 64) Landscaping is to be installed in accordance with the approved landscape plan. All works and methods nominated and materials and plants specified on the approved landscape plan are to be completed prior to the issue of an occupation certificate. The landscaping shall be maintained for the life of the development.

65) Replacement Trees: On-Site

In line with Council's policy to maintain and increase tree cover in the Council area, the applicant is to plant in accordance with the landscape plan required by Condition 5 and in accordance with the requirements below:

- a) Replacement trees are to be a minimum container size of 100 litres. They shall comply with *NATSPEC Specifying Trees: a guide to assessment of tree quality* (2003) or *Australian Standard AS 2303 – 2015 Tree stock for landscape use* (2003) and be planted and maintained in accordance with Council's standard specification.
- b) Tree species used are not to include conifers, palms, Casuarinaceae, or any of the exempted plant species listed under clause 2.4 of Bankstown Development Control Plan 2015 Part B11– Tree Preservation Order.
- c) The trees are to be planted no closer than 3.5 metres from the wall of any approved dwelling on the property. Trees/shrubs proposed for planting along the rear boundaries shall be located no closer than 1.0 metres from the rear boundary.
- d) All new plantings shall be located so future growth will not be in conflict with electricity wires. Consideration should be given to the location of new electricity poles and wires so that sufficient space is provided.
- e) If there is conflict between the planting locations and this condition of consent, planting locations are to be adjusted so that they comply with the written consent.
- f) The replacement trees are to be planted prior to the issue of an occupation certificate.
- g) The replacement trees to be planted shall be maintained in a healthy and vigorous condition until they attain a height of 5.0 metres whereby they will be protected by Bankstown Development Control Plan 2015 Part B11– Tree Preservation Order.
- h) If the replacement trees are found to be faulty, damaged, dying or dead before being protected by Bankstown Development Control Plan 2015 Part B11– Tree Preservation Order; the tree/s shall be replaced with the same species at no cost to Council.

66) Replacement Trees: Footpath

The applicant is to plant the following replacement trees on the nature strip forward of the property. The trees shall have a container size not less than 200 litres, shall comply with *NATSPEC Specifying Trees: a guide to assessment of tree quality* (2003) or *Australian Standard AS 2303 – 2015*

Tree stock for landscape use and be planted and maintained in accordance with Council's street tree planting specifications Standard Drawing No. S-207A.

Species	Location
Six (6) x <i>Corymbia maculata</i> (Spotted Gum)	On the nature strip forward of the property on Cross Street, planted at approx. 8 metre spacings
One (1) x <i>Lophostemon confertus</i> (Brush Box)	On the nature strip forward of the property on Stanley Street

Investigation to locate underground services shall be the responsibility of the applicant. Should such services be located and there is a reasonable belief that damage may occur to those services by the new plantings, the applicant is to:

- a) Carry out engineering works to protect those services from damage; or
- b) Relocate the plantings to a more suitable location following written approval from Bankstown City Council; or
- c) Substitute the approved tree species with an alternative species following written approval from Bankstown City Council.

The trees shall be planted by a qualified landscape contractor and to the satisfaction of Council's Tree Management Officer.

The Applicant shall contact Council to book an inspection by the Tree Management Officer of the completed tree planting prior to the issue of an occupation certificate. Inspections must be booked at least 5 working days prior to being required.

- 67) A suitably qualified Professional Civil Engineer shall certify that the driveways, parking bays, and service areas have been constructed in accordance with the approved plans and specifications. Such Certification shall be submitted prior to the issue of the Occupation Certificate or occupation of the site.
- 68) Lighting must be provided to the entries of the dwellings, driveways and parking areas to promote a high level of safety and security at night and during periods of low light. Lighting provided should be hooded, shielded or directed away from neighbouring dwellings to minimise glare and associated nuisances to residents.
- 69) The premises must be readily identified from the street with the allocated house numbers. Numbering of the development without Council's written approval is not permitted. An official "house numbering" letter will be sent to the applicant indicating the proposed house numbers of the new development. Note: The house numbers of the development are subject

to change depending of the type on subdivision that may occur at a later stage.

- 70) Prior to the issue of any Occupation Certificate a design verification from a qualified designer shall be submitted to the Principal Certifying Authority. The design verification is a statement in which the qualified designer verifies that the development has been constructed as shown in the plans and specifications in respect of which the Construction Certificate was issued, having regard to the design quality principles set out in Schedule 1 of SEPP No. 65.
- 71) A registered surveyor shall prepare a Work As Executed Plan, and a suitably qualified Hydraulic Engineer shall provide certification of the constructed on-site stormwater detention system.

The Work As Executed information shall be shown in red on a copy of the approved stormwater plan and shall include all information specified in Council's Development Engineering Standards. The Work As Executed plan shall be submitted to the Hydraulic Engineer prior to certification of the on-site stormwater detention system.

The engineer's certification of the on-site stormwater detention system should be carried out similar to Council's standard form "On-Site Stormwater Detention System - Certificate of Compliance", contained in Council's Development Engineering Standards.

A copy of the Work As Executed Plan and Hydraulic Engineer's Certification shall be submitted to Council for information prior to issue of the final occupation certificate.

- 72) The developer shall register, on the title of the subject property, a Restriction on the Use of Land and Positive Covenant, in accordance with the standard terms for "Registration of OSD on title", as outlined in Council's Development Engineering Standards and in accordance with the appropriate provisions of the Conveyancing Act.

Note: The location of the "On-Site Stormwater Detention System" shall be shown on the plan of subdivision where subdivision is proposed. Where subdivision is not proposed the location of the "On-Site Stormwater Detention System" shall be included on an A4 size site plan attached to the Section 88E Instrument and registered on the title prior to the issue of the final occupation certificate.

The developer shall submit to Council evidence of the final registration of the Restriction and Positive Covenant on the title of the property.

- 73) A Copy of the Work Permit Compliance Certificate shall be submitted to the PCA Prior to the issue of the Occupation Certificate.

- 74) The Section 73 compliance certificate under the Sydney Water Act 1994 must be submitted to the principal certifying authority before occupation of the development / release of the plan of subdivision.