



**TOWER 2, LEVEL 23
DARLING PARK, 201 SUSSEX ST
SYDNEY NSW 2000**

URBIS.COM.AU
Urbis Pty Ltd
ABN 50 105 256 228

14 November 2016

Ms Nicole Askew

Camden Council
PO Box 183
CAMDEN NSW 2570

Dear Nicole,

AMENDMENT TO DEVELOPMENT APPLICATION (DA/2016/925): PROPOSED CAR PARK OPERATION AND MANAGEMENT

On the 12 of August 2016 a Development Application was lodged to Camden Council for alterations and additions to a commercial building to be used as a medical centre incorporating a pharmacy together with the reconfiguration of an existing car park at 19 Queen Street Narellan (DA/2016/925).

In response to the concerns of Council and the members of the public, the applicant seeks to amend the proposed operation and management of the medical centre car park.

Consistent with the proposed and notified development, the medical centre includes 81 off-street car parks. Patients and staff of the medical centre will be able to access the car parks from Queen Street, via an existing shared access road. Access to the car park area will be controlled by a boom gate between the existing shared access road and the new medical centre car park.

The applicant seeks to modify the operation, by allowing patient and visitors of the medical centre to have a two (2) or three (3) hour free parking period. The aim of the proposal is to introduce two Paid Parking Schedules (A and B) that can be alternated at the site by the operator.

- Paid Parking Schedule A permits a free parking period of 2 hours for customers of the Medical Centre.
- Paid parking Schedule B proposes to increase the free parking period by 1 hour, to allow a total of 3 hours free parking for customers.

Flexibility is required to ensure the Medical Centre operator is able to effectively respond to the potential future car parking demand. Allowing the operator to alternate the minimum free parking period will increase efficiency of the medical Centre to benefit patients. The minimum 2 hours free parking will be maintained at all times. After the free parking period has expired the paid parking scheme will apply.

The proposed amendment to the management and operation of the car park is reflected in the amended Operational Management Plan prepared by Shellshear Young and Traffic Impact Assessment prepared by Cardno enclosed.

If you have any questions please don't hesitate to contact me on (02) 8233 7657.



Yours sincerely,

A handwritten signature in black ink, appearing to read "J McDowall". The signature is fluid and cursive, with a long horizontal stroke at the end.

Jocelyn McDowall
Consultant - Planning

CC Simon Smith (ssmith@sjb.com.au)

Enc Operational Management Plan
Traffic Impact Assessment

OPERATIONAL MANAGEMENT PLAN

NARELLAN MEDICAL CENTRE

19 Queen Street, Narellan, NSW 2567

LOT 2. DP10854322.



PRIMARY HEALTH CARE LTD

Applicant: Urbis Pty Ltd, L23, Tower 2, Darling Park, 202 Sussex Street, Sydney, NSW 2000.

31th October 2016

VERSION CONTROL

Version	Author	Role	Date	Reviewed
v1.6	Colin Davidson	Project Architect	31/10/2016	
v1.6		Director	31/10/2016	Matthew Young

CONTENTS

1. INTRODUCTION
2. FIT OUT AND OPERATION
3. HOURS OF OPERATION
4. STAFFING AND MEDICAL SERVICES
5. CAR PARKING
6. LANDSCAPE MAINTENANCE
7. EXTERNAL LIGHTING CONTROL
8. WASTE MANAGEMENT PLAN

1. INTRODUCTION

This Operational Management Plan accompanies a Development Application (DA) to Camden Council for the development of a medical centre at 19 Queen Street, Narellan.

Summary of Proposed Development

The development proposes the alterations, additions and fit out of an existing two storey office building and associated external works for provision of a new medical centre to be operated by Primary Health Care Limited.

2. FIT OUT AND OPERATION

The fit out and operation of the medical centre will comply with the Medical Board of Australia, Australia Health Practitioner Regulatory Agency and the NSW Department of Health Regulations.

The fit out of any rooms used for medical procedures will comply with the Australian Health Infrastructure Alliance 'Australian Health facilities guidelines'.

The private medical practice operating from the proposed medical centre will be satisfy the licensing requirements of the Private Health Facilities Act and Private Health facilities regulations 2010 (as revised).

The fit out of any rooms containing radiation equipment will comply with the Radiation Control Act, Radiation Control Amendment Act and the Radiation Control Regulations.

3. HOURS OF OPERATION

The proposed medical centre comprises a range of component activities that are operated and managed by Primary Health Care.

The proposed hours of operation are Monday – Sunday 7.00am – 10.00pm.

4. STAFFING AND MEDICAL SERVICES

During construction approximately 80 persons will be employed during the peak activity period.

Upon completion the centre will be operated by approximately 36 staff. The extended hours of the medical centre mean that some staff may undertake shift work. For example: morning shift; afternoon shift.

Medical Services

The proposed medical services comprise:

- | | |
|-------------------------|--|
| · General Practitioners | 17 consultation rooms |
| · Specialists | 7 consultation rooms |
| · Treatment room | 4 bed and 1 bed treatment rooms attended by up to 3 nurses |
| · Radiology clinic | 1 radiologists supported by up to 3 staff |
| · Physiotherapy | 1 physiotherapist supported by 1 staff |
| · Dental clinic | 3 surgeries operated by 2 dentists supported by 2 nurses or hygienists |
| · Pathology collection | 1 collection room attended by up to 2 staff |
| · Reception and Admin. | 3 receptions and administration areas attended by up to 8 staff |
| · Pharmacy | 1 pharmacist supported by 2 staff |

5. CAR PARKING

Car Park Description

The proposal includes off-street parking for 81 cars. Patients and staff will access the medical centre car park from Queen Street via an existing shared access road, access to the parking will be controlled by a boom gate between the existing shared access road and the new medical centre car park. Patients will exit the medical centre car park via existing access point to Queen Street, also controlled by a boom gate.

Site servicing uses Queen Street entry and exits points as described above order for a semi-rigid waste collection vehicle to enter and leave the site in a forward direction.

Staff Car Park Access

Staff will access a designate parking area using an automated access system. This system is activated by an electronic security FOB device that opens an automatic gate to access the staff car park. Exit activation is via a ground induction loop that opens the gate upon approach.

Patient and Visitor Car Park Access

During business hours access to patient and visitor parking is controlled by boom gates.

Parking Controls

The patient and visitor car park will operate as paid parking with a 2 or 3 hour free parking period.

Patients accessing the site will enter via Queen Street and take a ticket prior to entering the centre. Upon exit a patient will enter a validated ticket into a ticket acceptance unit to raise the boom gate and depart the site.

A freestanding traffic control sign (nominally 0.5sqm) is proposed to be located adjacent to the entry. It will display information on car parking payment rates and free waiver period.

Visitor Parking Equipment

· Entry Gate

A ticket splitter will be located at the entry to the patient car park. This is connected to the boom gate that will open to allow access once a ticket is taken. A pressure sensor detects when a vehicle is at the machine and only then can a ticket be taken from the machine. The boom arm is not activated by the loop so if a car tailgates the boom gate will come down. There is also an intercom button which visitors can push for assistance.

· Exit Gate

A ticket reader will be located at the exit of the patient car park. This is connected to the boom gate that will open to allow exit once a paid ticket is inserted. A pressure sensor detects when a vehicle is at the machine and only then can a ticket be inserted into the machine. The boom arm is not activated by the loop so if a car tailgates the boom gate will come down. There is an intercom button they can push for assistance.

· Automatic Pay Machine

An APM will be located near the medical centre entrance, this is where users pay for their parking ticket if they stay longer than the advertised free parking period. They do this by inserting their ticket into the pay machine and then paying the fee that is displayed on the monitor. There is also an intercom button they can push for assistance and a lost ticket button. The APM has the option of paying by cash or credit card.

6. LANDSCAPE MAINTENANCE

A landscape maintenance schedule is included as part of Primary Health Care Landscape Guidelines as prepared by Taylor Brammer Landscape Architects.

Please refer to the relevant extract from the Landscape Guidelines which has been included as part of this submission.

7. EXTERNAL LIGHTING

Carpark and perimeter security lighting will be installed on the eastern, western and northern boundaries mounted at approx. 6m poles. The external lighting shall be controlled by a light sensitive photo electric cell (dusk to dawn) sensor with the ability to be switched off automatically at a predetermined time.

Refer to the lighting calculation plan prepared by Inlite, July 2016 and included as part of this development application.

8. WASTE MANAGEMENT PLAN

Refer to Waste Management Plan prepared by Shellshear Young, May 2016 and included as part of this development application submission.

Traffic Impact Assessment

Narellan Medical Centre

80816368



Prepared for
Shellshear Young Pty Ltd

04 November 2016

Contact Information

Cardno (NSW / ACT) Pty Ltd
Trading as Cardno Ltd (ASX: CDD)
ABN 95 001 145 035

Level 9 – The Forum
203 Pacific Highway
St Leonards NSW 2065

Telephone: (02) 9496 7700
Facsimile: (02) 9439 5170
International: +61 2 9496 7700

Sydney.traffic@cardno.com.au
www.cardno.com

Author(s):



Kathy Lee
Junior Traffic Engineer



Approved By:

Tim Sullivan
Traffic Engineering Team Leader

Document Information

Prepared for	Shellshear Young Pty Ltd
Project Name	Narellan Medical Centre
File Reference	808_16_368 Narellan Medical Centre TIA.docx
Job Reference	80816368
Date	4 November 2016

Version Number	7
-----------------------	----------

Document History

Version	Effective Date	Description of Revision	Prepared by:	Reviewed by:
R007	04/11/2016	Revised Final Report	Kathy Lee	Aaron Tran
R006	09/08/2016	Revised Final Report	Kathy Lee	Aaron Tran
R005	04/08/2016	Final Report (Post pre-DA meeting)	Kathy Lee	Aaron Tran
R004	28/07/2016	Revised v2 Final Report (Post pre-DA meeting)	Kathy Lee	Aaron Tran
R003	20/06/2016	Revised v1 Final Report	Kathy Lee	Tim Sullivan
R002	16/05/2016	Final Report	Kathy Lee	Tim Sullivan
R001	29/04/2016	Draft Report	Kathy Lee	Tim Sullivan

© Cardno. Copyright in the whole and every part of this document belongs to Cardno and may not be used, sold, transferred, copied or reproduced in whole or in part in any manner or form or in or on any media to any person other than by agreement with Cardno.

This document is produced by Cardno solely for the benefit and use by the client in accordance with the terms of the engagement. Cardno does not and shall not assume any responsibility or liability whatsoever to any third party arising out of any use or reliance by any third party on the content of this document.

Table of Contents

1	Introduction	1
1.1	Overview	1
1.2	Scope of Works	2
1.3	Reference Documents	2
2	Existing Situation	3
2.1	Site Location	3
2.2	Existing Road Network	3
2.2.2	Camden Valley Way	4
2.2.3	Queen Street	4
2.2.4	Elyard Street	4
2.2.5	Hume Street	5
2.3	Existing Public Transport Services	5
2.3.1	Bus Services	5
2.4	Pedestrian Infrastructure	10
2.5	Existing Car Parking Context	11
2.5.1	On-street Parking Provision	11
2.6	Key intersections	12
2.6.2	Queen Street/ Elyard Street	13
2.6.3	Queen Street/ Hume Street	13
2.7	Baseline Traffic Assessment	14
2.7.2	Base Scenario Intersection Performance	15
2.7.3	Base Scenario Mid-block Capacity	16
3	Traffic Assessment	17
3.1	Development Overview	17
3.2	Development Traffic Generation	17
3.3	Development Trip Distribution and Assignment	18
3.4	Committed Developments	20
3.5	Impact of Development	20
3.5.1	Intersection Performance	20
3.5.2	Mid-block Capacity	20
3.5.3	Background Traffic Growth	21
3.5.4	Opening Year 2017 Scenario – Future Base + Development	21
3.5.5	Opening Year + 10 Years Scenario – Base + Development (2027)	22
4	Site Access	25
4.2	Swept Path Analysis for Narellan Medical Centre	25
4.3	Swept Path Analysis for 12m Truck Vehicle	28
5	Car Park Design	29
5.1	Car Parking Minimum Requirements	29
5.1.1	Narellan Medical Centre	29
5.1.2	Camden Council Library	29
5.2	Sight Distance and Pedestrian Sight Lines	30
5.3	Car Park Operation	32
5.3.1	Patron Car Park Access	32
5.3.2	Staff Car Park Access	32
5.3.3	Boom Gate Operation	32

6 Conclusion**33**

Appendices

Appendix A SURVEY RESULTS**Appendix B** SIDRA MOVEMENT SUMMARIES**Appendix C** SWEPT PATH ANALYSIS

Tables

Table 2-1	Functional Road Classifications	3
Table 2-2	Administrative Road Classifications	3
Table 2-3	Typical Bus Service Frequencies	6
Table 2-4	Intersection Traffic Efficiency	15
Table 2-5	Intersection Summary for Peak Hour of Service for Base Scenario	16
Table 2-6	Mid-block AM Peak Hour of Service for Base Scenario	16
Table 2-7	Mid-block PM Peak Hour of Service for Base Scenario	16
Table 3-1	Narellan Medical Centre Proposed Details	17
Table 3-2	Intersection Summary for Peak Hour - Base + Development Scenario	20
Table 3-3	Intersection Summary for Peak Hour of Service for Base Scenario	20
Table 3-4	Mid-block AM Peak Hour of Service for Base + Development Scenario	20
Table 3-5	Mid-block PM Peak Hour of Service for Base + Development Scenario	21
Table 3-6	Intersection Summary for Peak Hour of Service for Opening Year (2017) Future Base + Development	21
Table 3-7	Intersection Summary for Peak Hour of Service for Base Scenario	21
Table 3-8	Mid-block AM Peak Hour of Service for Future Base (2017) + Development Scenario	22
Table 3-9	Mid-block PM Peak Hour of Service for Future Base (2017) + Development Scenario	22
Table 3-10	Intersection Summary for Peak Hour of Service for Opening Year + 10 Years (2027)	23
Table 3-11	Intersection Summary for Peak Hour of Service for Base Scenario	23
Table 3-12	Mid-block PM Peak Hour of Service for Future + 10 Years (2027) Scenario	23
Table 3-13	Mid-block AM Peak Hour of Service for Future + 10 Years (2027) Scenario	24

Figures

Figure 1-1	Narellan Medical Centre Location	1
Figure 2-1	Camden Valley Way Ownership	4
Figure 2-2	Existing Bus Stop Locations	5
Figure 2-3	Bus Route S17, 899 Network Map	7
Figure 2-4	Bus Route 891, 893 Network Map	8
Figure 2-5	Bus Route 890C, 894 Network Map	9
Figure 2-6	Designated Pedestrian Footpath Network	10
Figure 2-7	On Street Parking Restrictions	11
Figure 2-8	Assessed Intersection Locations	12

Figure 2-9	Queen Street / Elyard Street Intersection Layout	13
Figure 2-10	Queen Street / Hume St Intersection Layout	14
Figure 3-1	Proposed Narellan Medical Centre Site Plan	17
Figure 3-2	Development Trip Assignment – AM Peak	19
Figure 3-3	Development Trip Assignment – PM Peak	19
Figure 4-1	Proposed Narellan Medical Centre Site Plan	25
Figure 4-2	B99 Vehicle Swept Path	26
Figure 4-3	SRV Swept Path – Forward Park	27
Figure 4-4	MRV Swept Path	27
Figure 4-5	12m Truck Swept Path – Exiting on to Queen Street	28
Figure 5-1	Camden Council Parking Rates for Health Service Facility/ Medical Centres	29
Figure 5-2	Minimum Sight Distances	30
Figure 5-3	Minimum Sight Lines for Pedestrian	30
Figure 5-4	Minimum Sight Lines for Proposed Exit	31
Figure 5-5	Typical Boom Gate Configuration	31
Figure 5-6	Car Park Entry Boom Gate	32

1 Introduction

1.1 Overview

Cardno has been engaged by Shellshear Young Pty Ltd to undertake a Traffic Impact Assessment (TIA) for the Development Application (DA) associated with the proposed Narellan Medical Centre (NMC) located at 19 Queen St, Narellan. The development shown in **Figure 1-1** is located within the Camden Council local government area and will include a medical centre with a Gross Floor Area (GFA) of 1552m² and a reconfiguration of the existing carpark to include 81 parking spaces.

This TIA report is the result of collaboration between Cardno and Shellshear Young Pty Ltd and discussions with Council and their independent planner from JBL Consulting.

The location of the proposed site is generally bounded by:

- > Elyard Street to the north;
- > Queen Street to the East; and
- > Hume Street to the south.



Background: Nearmap (accessed April 2016)

Figure 1-1 Narellan Medical Centre Location

1.2 Scope of Works

This report documents the traffic impacts of the proposed NMC including the following scope of works:

- > Undertake traffic surveys during the AM and PM for the following intersections:
 - Queen Street/ Elyard Street (Roundabout)
 - Queen Street/ Hume St (Priority)
- > Assess existing and proposed traffic volumes during peak hour periods using collected survey data and RMS guidelines.
- > Undertake capacity analysis of the aforementioned intersections plus the site access using SIDRA INTERSECTION 6.1 (SIDRA) modelling software for the scenarios below:
 - Baseline Scenario
 - Future Baseline Scenario (anticipated opening year of 2017) plus Development
 - Future Baseline Scenario plus 10 years plus Development
- > Assess on-site statutory car parking requirements of the proposed development based on parking rates stipulated in the Camden Council's DCP Chapter E3 and the RMS Guide to Traffic Generation Developments (2002) document and provide justification on the number of parking spaces proposed
- > Propose site access / egress arrangements with commentary on suitability and visibility requirements in line with Australian Standards
- > Provide advice to the design team (including swept path analysis) on the parking supply, site access and general layout
- > Review and acknowledge existing DA conditions for the Camden Council Library (No. 1467/2003)
- > Detail car park boom gate operation and justify the use
- > Assessment of the latest car park layout design including swept path analysis.

1.3 Reference Documents

The following documents have been reviewed and referenced in this report:

- > Development Application No. 1467/2003 – 19 Queen Street Narellan
- > Camden Council Development Control Plan (2011)
- > Guide to Traffic Generating Developments (RTA, 2002)
- > Guide to Traffic Generating Developments – Updated traffic surveys (RMS, TDT 2013/04a)
- > Australian Standards 2890.1:2004, AS 2890.2:2002 and 2890.6:2009
- > Campbelltown Camden Integrated Transport Strategy (2006).

2 Existing Situation

2.1 Site Location

The proposed Narellan Medical Centre (NMC) is located at 19 Queen St, Narellan as shown in **Figure 1-1**. The subject site measures 5,700 m² in area and lies within the Camden Council local government area.

A two-storey office building is currently situated on the development site bound by Elyard Street to the north, Queen Street to the west and Hume Street on the western and eastern boundary.

Other existing developments in close proximity to the site include:

- > To the north, approximately 100m from the NMC is the Narellan Library, which is situated adjacent to the site at the intersection of Queen Street and Elyard Street.
- > Further North is Narellan Town Centre along Elyard Street between Queen St and Somerset Avenue.
- > On the western and southern boundary are one and two storey residential properties situated along Queen Street and Hume Street respectively.

2.2 Existing Road Network

The existing road network can be described using the Roads and Maritime Services (RMS) Functional Classification of Roads and the Schedule of Classified Roads and Unclassified Regional Roads outlined in **Table 2-1** and **Table 2-2** respectively. The existing road network surrounding the NMC are as follows:

- > Camden Valley Way
- > Queen Street
- > Elyard Street
- > Hume Street

Table 2-1 Functional Road Classifications

Road Classification	Description
Arterial Road	This is typically a main road carrying in excess of 15,000 vehicles per day and over 1,500 vehicles per hour in the peak period. They predominantly carry traffic from one region to another, forming principal avenues of communication for metropolitan traffic movements.
Sub-Arterial Road	This is typically a secondary road carrying between 5,000 and 20,000 vehicles per day, and over 500 to 2,000 vehicles per hour in the peak period. They predominantly carry traffic from one sub-region to another forming secondary inter-regional transport links.
Collector Road	This is typically a minor road carrying between 2,000 and 10,000 vehicles per day, and over 250 to 10,000 vehicles per hour in the peak period. They provide a link between local areas and regional roads, carrying low traffic volumes. At volumes greater than 5,000 vehicles per day, residential amenity begins to decline noticeably.
Local Road	This is typically a local street carrying less than 2,000 vehicles per day and 250 vehicles per hour in the peak period. They provide immediate access to individual houses and carry low volumes of traffic.

Table 2-2 Administrative Road Classifications

State Classified Road	Major roads which are managed and financed by RMS
Regional Road	Locally roads managed and financed by local councils.

2.2.2 Camden Valley Way

According to the Road and Maritime Schedule of Classified Roads, Camden Valley way is a State Arterial Road from Appin Road at Campbelltown via Narellan Road to the Northern Road intersection. From the Northern Road intersection to Murray Street at Camden, Camden Valley Way is classified as a Regional Road. The ownership of Camden Valley Way in the vicinity of the proposed site is outlined in **Figure 2-1**. It is a divided two lane, two way road with a sign posted speed limit of 60km/h and a school zone between Queen Street and Wilson Crescent.



Figure 2-1 Camden Valley Way Ownership

2.2.3 Queen Street

Queen Street is Local Road under the authority of Camden Council. It provides access between Camden Valley Way and the Camden Bypass via Narellan Town Centre. Queen Street is an undivided two way, two lane road with a speed limit of 50km/h. Queen Street provides an access and egress to the Narellan Town Centre carpark.

2.2.4 Elyard Street

Elyard Street is a Local Road under the authority of Camden Council. It is a two way, two lane Local Road which connects to Camden Valley Way via Richardson Road and Somerset Avenue towards Camden in the West and Campbelltown to the south. A speed limit of 50km/h applies to Elyard Road including a school zone between Richardson Road and Queen Street. Elyard Street also provides pedestrian access to the Narellan Town Centre.

2.2.5 Hume Street

Hume Street is Local Road under the authority of Camden Council. It is a two way, two lane Local Road which merges into Rudd Street providing access to residential allotments. The eastern leg of Hume Street is one way exit lane limited to private access.

2.3 Existing Public Transport Services

Currently there is no railway network within the vicinity of the proposed site, Macarthur Station in the Campbelltown area is the closest train station. However, there are a number of bus routes which service the area.

2.3.1 Bus Services

The subject site is situated in close proximity to the Narellan Town Centre and Narellan Library. As such, there are a number of bus routes that operate along Queen Street, Elyard Street and Somerset Avenue and Camden Valley Way. These buses are operated by Busabout and Picton Buslines. There is a bus stop at the front of the development site on Queen Street.

The bus stop locations surrounding the site are displayed in **Figure 2-2** and bus frequencies of buses that operate within the local area are outlined in **Table 2-3**. Corresponding bus network maps are displayed in **Figure 2-3**, **Figure 2-4** and **Figure 2-5**.




Background: Nearmap (accessed April 2016)

Figure 2-2 Existing Bus Stop Locations


Table 2-3 Typical Bus Service Frequencies

Bus Route	Route Description	Weekday Peak	Weekday Off-Peak	Weekend Peak	Weekend Off-peak
899	Camden to Catherine Field	n/a	3 services	n/a	Saturday only – 2 services
899	Catherine Field to Camden	3 services	3 services	n/a	Saturday only - 2 services
891	Curran Hills and Mt Anna Loop	1 service	5 services	n/a	2 services
893	Narellan to Campbelltown	6 services	22 services	Saturday -5 services Sunday 3 services	Saturday – 16 services Sunday – 7 services
893	Campbelltown to Narellan	8 services	21 services	Saturday -3 services Sunday - 3 services	Saturday -19 services Sunday - 8 services
890C	Camden to Campbelltown	4 services	6 services	Saturday -3 services	Saturday -6 services
890C	Campbelltown to Camden	1 service	7 services	Saturday -3 services	Saturday -7 services
894	Bridgewater to Campbelltown	5 services	5 services	n/a	n/a
894	Campbelltown to Bridgewater	6 services	8 services	n/a	n/a
S17	Narellan & Campbelltown to Picton	n/a	1 service	Saturday – 1 service	Saturday – 1 services
S17	Picton to Narellan & Campbelltown	n/a	1 service	Saturday – 1 services	Saturday – 1 services
900	Narellan & Campbelltown to Picton	n/a	1 service	Saturday – 1 services	Saturday – 1 services
900	Picton to Narellan & Campbelltown	n/a	1 service	Saturday – 1 services	Saturday – 1 services




(Source: Busabout)

Figure 2-3 Bus Route S17, 899 Network Map



(Source: Busabout)

Figure 2-4 Bus Route 891, 893 Network Map



(Source: Busabout)

Figure 2-5 Bus Route 890C, 894 Network Map

Based on the availability of local bus services and proximity of bus stops to the proposed development, it is reasonable to expect that some staff and customers of the NMC would arrive by bus. In particular, the site is well connected to the suburbs of Campbelltown and Camden. This will help to reduce the traffic generation and relieve parking pressure of the site.

2.4 Pedestrian Infrastructure

As shown in **Figure 2-6**, there are existing pedestrian footpath provisions which facilitate pedestrian movement towards the Narellan Town Centre. Designated concrete footpaths are generally provided on one side of the surrounding road network and footpaths on both sides closer to the Narellan Town Centre.



Background: Nearmap (accessed April 2016)

Figure 2-6 Designated Pedestrian Footpath Network

It is reasonable to expect some staff and customers to walk to the proposed NMC. Based on the assessment of the existing pedestrian footpath network, there will be adequate pedestrian footpaths to accommodate for pedestrian access to the proposed development site.

2.5 Existing Car Parking Context

2.5.1 On-street Parking Provision

On-street car parking provisions surround the subject site are displayed in **Figure 2-7**.

2.5.1.1 *Queen Street*

Queen Street generally does not provide on-street parking. Residential side streets that intersect Queen Street, Lord Street and Hume Street provide unrestricted parking.

2.5.1.2 *Elyard Street*

Elyard Street generally consists of unrestricted parking with No Stopping zones located near intersections and Bus Zones.

2.5.1.3 *Hume Street*

Hume Street consists of unrestricted parking on both sides of the road on the western leg. The eastern leg of Hume Street is restricted to private access only.



Background: Nearmap (accessed April 2016)

Figure 2-7 On Street Parking Restrictions

2.6 Key intersections

The following two intersections outlined in **Figure 2-8** were included in this traffic assessment due to their proximity to the site, and are considered to be the two intersections most likely to be affected by traffic generated by the proposed development.

- > Queen Street / Elyard Street (roundabout)
- > Queen Street / Hume Street (priority)



Background: Nearmap (accessed April 2016)

Figure 2-8 Assessed Intersection Locations

2.6.2 Queen Street/ Elyard Street

This is a roundabout intersection where Queen Street forms the northern and southern leg and Elyard Street forms the eastern and western leg. All approaches have one lane in each direction. Refer to intersection layout in **Figure 2-9**.




Figure 2-9 Queen Street / Elyard Street Intersection Layout

2.6.3 Queen Street/ Hume Street

This intersection is a four-way priority-controlled intersection, with Queen Street given priority. All approaches have one lane in each direction with the exception of Hume Street on the eastern side with only one lane westbound. Refer to intersection layout in **Figure 2-10**.




Figure 2-10 Queen Street / Hume St Intersection Layout

2.7 Baseline Traffic Assessment

Vehicle intersection counts were conducted on Saturday 2 April 2016 and Thursday 7 April 2016 at the intersections listed in Section 2.6. Refer to **Appendix A** for survey outputs.

The traffic surveys identified that the AM peak hour is 8:30am to 9:30am at both intersections. The PM peak hour is 4:30pm to 5:30pm at the Queen Street/ Elyard Street intersection and 4:00pm to 5:00pm at the Queen Street / Hume Street intersection.

Capacity analysis of the two intersections was performed using SIDRA 6.1 to determine the traffic efficiency namely the level of service (LOS), Degree of Saturation (DOS) and Average Vehicle Delay (AVD) for the existing traffic conditions.

The LOS is a quantitative measure of traffic efficiency based on a number of traffic factors such as speed, time, manoeuvrability, traffic volumes, driver experience and operating costs. As per the RMS Guide to Traffic Generating Developments, the LOS can be categorised from A to F as outlined in **Table 2-4**. Generally, a LOS C is acceptable whereby the driver experience limited manoeuvrability, however operating speeds and delays are still reasonable.

The AVD provides a measure of the operational performance of an intersection as indicated in **Table 2-4** which relates AVD to LOS. The AVDs should be taken as a guide only as longer delays could be tolerated in some locations (i.e. inner city conditions) and on some roads (i.e. minor side street intersecting with a major arterial route). For traffic signals, the average delay over all movements should be taken. For roundabouts and priority control intersections (sign control) the critical movement for level of service assessment should be that movement with the highest average delay.

The DOS is another measure of the operational performance of individual intersections. For intersections controlled by traffic signals both queue length and delay increase rapidly as DOS approaches 1. DOS in the order of 0.7 generally represents satisfactory intersection operation and a DOS above 0.9 may have a significant impact on queue lengths.

Table 2-4 Intersection Traffic Efficiency

LoS	Traffic Signal/Roundabout	Giveaway / Stop Sign / T-Junction	AVD (seconds/ vehicle)
A	Good Operation	Good Operation	< 14
B	Good with acceptable delays and spare capacity	Acceptable delays and spare capacity	15 to 28
C	Satisfactory	Satisfactory, but accident study required	29 to 42
D	Operating near capacity	Near Capacity & accident study required	43 to 56
E	At Capacity, at signals incidents will cause excessive delays	At capacity, requires other control mode	57 to 70
F	Unsatisfactory and requires additional capacity. Roundabouts require other control mode	Unsatisfactory and requires additional capacity.	>70

2.7.2 Base Scenario Intersection Performance

Input of survey results into SIDRA 6.1 produced the intersection assessment summarised in **Table 2-5**. The key measure of intersection operating performance is LOS. The intersection performance of existing base scenario indicates LOS A in both the AM and PM peak periods for both intersections.

Table 2-5 Intersection Summary for Peak Hour of Service for Base Scenario

Location	Control type	AM			PM		
		DOS	AVD (seconds)	LOS	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Roundabout	0.457	1.6	A	0.435	2.1	A
Queen Street/ Hume Street	Priority Controlled	0.101	0.2	A	0.122	0.4	A

2.7.3 Base Scenario Mid-block Capacity

The SIDRA 6.1 results for mid-block capacity of existing conditions based on survey data are summarised in **Table 2-6** and **Table 2-7**. Results indicate the all mid-block capacities operate at a 'Good' LOS A during the peak hour periods which indicates no current issues with road network capacity.

Table 2-6 Mid-block AM Peak Hour of Service for Base Scenario

Location	Direction	Volume (vehicles/hour)	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Northbound	213	0.193	6.0	A
	Westbound	206	0.182	5.4	A
	Southbound	191	0.207	6.3	A
	Eastbound	493	0.457	5.4	A
Queen Street/ Hume Street	Northbound	193	0.101	0	A
	Westbound	30	0.033	5.8	A
	Southbound	94	0.050	0.1	A
	Eastbound	12	0.009	5.2	A

Table 2-7 Mid-block PM Peak Hour of Service for Base Scenario

Location	Direction	Volume (vehicles/hour)	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Northbound	172	0.202	8.0	A
	Westbound	339	0.383	7.1	A
	Southbound	478	0.435	7.0	A
	Eastbound	320	0.296	5.0	A
Queen Street/ Hume Street	Northbound	109	0.058	0.1	A
	Westbound	98	0.110	6.3	A
	Southbound	230	0.122	0.3	A
	Eastbound	7	0.005	5.1	A

3 Traffic Assessment


3.1 Development Overview

The proposed development is a two-storey medical centre with access and egress to the facility via existing entrance and exits on Queen Street. As shown in Figure 3-1, the NMC is located within the Camden Council area and a reconfiguration of the existing car park to separate the medical facility parking and Camden Council parking is proposed. The GFA of the development is 1686m².

Details of the proposed NMC is outlined in **Table 3-1** and **Figure 3-1**.

Table 3-1 Narellan Medical Centre Proposed Details

Facility	Consulting Rooms
Chemist	n/a
General Practitioner	17
Specialist Practitioner	7
Radiologist	1
Dental Surgery	3
Physiotherapist	1



(Source: Shellshear Young Pty Ltd)

Figure 3-1 Proposed Narellan Medical Centre Site Plan

3.2 Development Traffic Generation

Development traffic generation was derived from RMS's Guide to Traffic Generating Developments Version 2.2 (2002) based on traffic generation rates for extended hours medical centres. Using an AM peak hour

generation rate of 10.4 vehicle/hour/100m² and a PM peak hour generation rate of 8.8 vehicle/hour/100m², the following development trip generation were estimated based on a GFA of 1686m²:

- > PM peak hour generation – 149 Vehicles/Hour
- > AM peak hour generation – 176 Vehicles/ Hour

Note that during the design process the GFA has been revised from 1686m² to 1552m². The following traffic analysis has maintained the use of 1686m² GFA and subsequently provides a conservative development traffic yield considering the maximum number of development trips generated.

3.3 Development Trip Distribution and Assignment

The distribution of traffic generated by the proposed NMC has been determined by using the Australian Bureau of Transport Statistics' Journey to Work 2011 (BTS 2011 JTW) data. The data captures the employment distribution and commute patterns of workers and residents based on locality. By considering the geographical location of vehicles that travel to and from Narellan the following traffic distribution assumptions have been made:

- > All vehicles will access and egress the site via Queen Street.
- > Directional distribution of the traffic accessing the subject site:
 - Based on traffic entering and exiting the development within the peak period. This assumption excludes staff and thus a 60 IN, 40 OUT (AM) and 40 IN, 60 OUT (PM) assumption has been made whereby vehicles will enter the car park in the AM and exit in the PM peak hours.
 - Camden, Campbelltown, Wollondilly and Bringelly were the main origins and destinations of vehicle trips.
 - For travel towards/ from Camden, Bringelly and Campbelltown, it was considered that residents and workers use Camden Valley Way via Elyard Street to the north of the subject site.
 - For travel towards/ from Wollondilly, residents and workers use Camden Bypass to the south of the subject site.
 - A 89% northbound split towards Queen Street/ Elyard Street intersection and 11% southbound split towards the Queen Street/ Hume Street intersection was used based on the above considerations.

From the trip generation and distribution assumptions discussed, the overall development trip assignments for AM and PM peak hours are shown in **Figure 3-2** and **Figure 3-3**.




Figure 3-2 Development Trip Assignment – AM Peak




Figure 3-3 Development Trip Assignment – PM Peak

3.4 Committed Developments

After consultation with Camden Council, it was noted that a child care centre for 88 children on 25 Somerset Avenue has been approved and potential day spa with 19 treatment rooms on 37 Elyard Street is in the final stages of development approvals. However, the trips generated from these committed developments are anticipated to have only a minor impact on the intersections being assessed, therefore the trip generation of the committed development has not been included in this report.

3.5 Impact of Development

3.5.1 Intersection Performance

The intersection performance with development traffic is summarised in **Table 3-2**. The SIDRA results indicate that although there is an increase in DOS and AVD, the intersections of interest all remain at a LOS A (Good Operation) in both the AM and PM peak period after the application of development trips.

Table 3-2 Intersection Summary for Peak Hour - Base + Development Scenario

Location	Control type	AM			PM		
		DOS	AVD (seconds)	LOS	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Roundabout	0.519	1.8	A	0.464	2.5	A
Queen Street/ Hume Street	Priority Controlled	0.109	0.2	A	0.127	0.4	A

Table 3-3 Intersection Summary for Peak Hour of Service for Base Scenario

Location	Control type	AM			PM		
		DOS	AVD (seconds)	LOS	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Roundabout	0.457	1.6	A	0.435	2.1	A
Queen Street/ Hume Street	Priority Controlled	0.101	0.2	A	0.122	0.4	A

3.5.2 Mid-block Capacity

The existing mid-block road capacity plus development is summarised in **Table 3-4** and **Table 3-5**. The application of development trips resulted in the same LOS as the base scenario in **Table 2-6** and **Table 2-7**

Table 3-4 Mid-block AM Peak Hour of Service for Base + Development Scenario

Location	Direction	Volume (vehicles/hour)	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Northbound	276	0.242	5.8	A
	Westbound	226	0.209	5.7	A
	Southbound	191	0.219	6.8	A
	Eastbound	568	0.519	6.1	A
Queen Street/ Hume Street	Northbound	209	0.109	0.1	A
	Westbound	30	0.033	5.9	A
	Southbound	102	0.054	0.1	A
	Eastbound	12	0.009	5.2	A

Table 3-5 Mid-block PM Peak Hour of Service for Base + Development Scenario

Location	Direction	Volume (vehicles/hour)	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Northbound	172	0.202	8	A
	Westbound	339	0.383	7.1	A
	Southbound	478	0.435	7.0	A
	Eastbound	320	0.296	5.0	A
Queen Street/ Hume Street	Northbound	109	0.058	0.1	A
	Westbound	98	0.110	6.3	A
	Southbound	230	0.122	0.3	A
	Eastbound	7	0.005	5.1	A

3.5.3 Background Traffic Growth

The background traffic growth rate was determined based on the RMS Annual Average Daily Traffic data. RMS collects traffic data at key count stations within the New South Wales (NSW) road network. Historical volumes on Camden Valley Way at Elderslie were obtained. The north bound volume produced the highest percentage growth rate of 0.6% p.a on Camden Valley Way. However, as a conservative assessment a 2% per annum (p.a) average annual growth rate has been applied to the survey data to account for background growth of the Future Opening Year and Future Opening Year plus 10 Years Scenarios.

3.5.4 Opening Year 2017 Scenario – Future Base + Development

A 2% linear growth rate per year has been applied to background traffic for the Opening Year + Development Scenario. It estimates the traffic volumes and intersection performance on the road network including development at the anticipated opening year of 2017.

3.5.4.1 Intersection Performance

Intersection performance of the Opening year 2017 Scenario are summarised in **Table 3-6**. The application of development traffic and background growth indicates an increase in the DOS and AVD in both intersections. However, the LOS remains unchanged at a 'Good' LoS A at both intersections during peak AM and PM periods.

Table 3-6 Intersection Summary for Peak Hour of Service for Opening Year (2017) Future Base + Development

Location	Control type	AM			PM		
		DOS	AVD (seconds)	LOS	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Roundabout	0.553	2.1	A	0.485	2.7	A
Queen Street/ Hume Street	Priority Controlled	0.110	0.2	A	0.132	0.4	A

Table 3-7 Intersection Summary for Peak Hour of Service for Base Scenario

Location	Control type	AM			PM		
		DOS	AVD (seconds)	LOS	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Roundabout	0.457	1.6	A	0.435	2.1	A
Queen Street/ Hume Street	Priority Controlled	0.101	0.2	A	0.122	0.4	A

3.5.4.2 Mid-block Capacity

The SIDRA intersection analysis results are displayed in **Table 3-8** and **Table 3-9**. Both mid-block capacity and intersection performance results indicate LOS remains at a 'Good' level with minimal impact on the AVD with the application of a one year growth rate.

Table 3-8 Mid-block AM Peak Hour of Service for Future Base (2017) + Development Scenario

Location	Direction	Volume (vehicles/hour)	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Northbound	281	0.257	5.9	A
	Westbound	236	0.227	5.9	A
	Southbound	202	0.243	7.2	A
	Eastbound	583	0.553	6.4	A
Queen Street/ Hume Street	Northbound	211	0.110	0.1	A
	Westbound	29	0.032	6.1	A
	Southbound	106	0.057	0.2	A
	Eastbound	14	0.011	5.3	A

Table 3-9 Mid-block PM Peak Hour of Service for Future Base (2017) + Development Scenario

Location	Direction	Volume (vehicles/hour)	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Northbound	258	0.308	8.1	A
	Westbound	365	0.439	7.8	A
	Southbound	491	0.485	7.7	A
	Eastbound	373	0.355	5.7	A
Queen Street/ Hume Street	Northbound	120	0.064	0.2	A
	Westbound	98	0.114	6.6	A
	Southbound	248	0.132	0.3	A
	Eastbound	9	0.007	5.3	A

3.5.5 Opening Year + 10 Years Scenario – Base + Development (2027)

A 2% growth rate has been applied to background traffic over a 10 year period for the Opening Year + 10 Years Scenario. It estimates the traffic volume on the road network including development 10 years after the opening year 2017.

3.5.5.1 Intersection Performance

The intersection performance of the Opening Year plus 10 Years Scenario SIDRA results are displayed in **Table 3-10**. Results indicate the intersections are anticipated to operate at 'Good' LOS in both AM and PM peak periods. As expected, the overall traffic flow increases, resulting in higher AVD. The Queen Street/ Elyard Street intersection continues to sustain the highest peak hour traffic volumes, with the highest AVD in the PM peak hour on Elyard Street westbound direction.

Table 3-10 Intersection Summary for Peak Hour of Service for Opening Year + 10 Years (2027)

Location	Control type	AM			PM		
		DOS	AVD (seconds)	LOS	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Roundabout	0.703	3.8	A	0.637	4.9	A
Queen Street/ Hume Street	Priority Controlled	0.134	0.2	A	0.134	0.2	A

Table 3-11 Intersection Summary for Peak Hour of Service for Base Scenario

Location	Control type	AM			PM		
		DOS	AVD (seconds)	LOS	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Roundabout	0.457	1.6	A	0.435	2.1	A
Queen Street/ Hume Street	Priority Controlled	0.101	0.2	A	0.122	0.4	A

3.5.5.2 Mid-block Capacity

The mid –block capacity of the Opening Year plus 10 Years Scenario results are presented in **Table 3-12** and **0**. Results indicate an overall traffic volume increase in the road network. In comparison with the Opening Year Base Scenario DOS and AVD increase, however the LOS remains unchanged at a ‘Good’ LOS A.

Table 3-12 Mid-block PM Peak Hour of Service for Future + 10 Years (2027) Scenario


Location	Direction	Volume (vehicles/hour)	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Northbound	332	0.319	6.4	A
	Westbound	287	0.287	6.3	A
	Southbound	249	0.333	8.1	A
	Eastbound	697	0.703	9.5	A
Queen Street/ Hume Street	Northbound	256	0.134	0.1	A
	Westbound	37	0.044	6.5	A
	Southbound	129	0.069	0.2	A
	Eastbound	18	0.016	5.6	A

Table 3-13 Mid-block AM Peak Hour of Service for Future + 10 Years (2027) Scenario

Location	Direction	Volume (vehicles/hour)	DOS	AVD (seconds)	LOS
Queen Street/ Elyard Street	Northbound	298	0.403	9.5	A
	Westbound	448	0.612	11.8	A
	Southbound	608	0.637	10.1	A
	Eastbound	449	0.452	6.3	A
Queen Street/ Hume Street	Northbound	153	0.081	0.2	A
	Westbound	121	0.154	7.2	A
	Southbound	302	0.161	0.3	A
	Eastbound	12	0.011	5.6	A

4 Site Access

Access to the proposed development will be via an existing driveway on Queen Street. Staff and patients will enter through the northern entrance and exit via the southern driveway. As shown in **Figure 4-1**, access and egress for the proposed NMC will be controlled by a boom gate.



(Source: Shellshear Young Pty Ltd)

Figure 4-1 Proposed Narellan Medical Centre Site Plan

4.2 Swept Path Analysis for Narellan Medical Centre

Swept path analysis was conducted to test the vehicle access into the proposed development. In accordance with AS 2890.1:2004 and 2890.2:2002, the standard design vehicles below have been used for the analysis:

- > B99 Vehicle (99th percentile passenger vehicle)
- > Small Rigid Vehicle (SRV)
- > Medium Rigid Vehicle (MRV)

The manoeuvres assessed include:

- > B99 Vehicle enter via patron boom gates,
- > B899 Vehicle enter via staff boom gates; reverse direction manoeuvre into Car Space 3; forward manoeuvre exit out of staff boom gates.
- > SRV enter via patron boom gates, forward direction manoeuvre into Emergency Vehicle car space; reserve direction manoeuvre out of car space; forward direction exit out of patron boom gates.
- > MRV enter via patron boom gates

Assumptions for the analysis include:


- > Existing Queen Street entry and exit driveways provide satisfactory entry and exit manoeuvres for the vehicle types listed above.
- > Vehicles are parked directly opposite the patron boom gate entrance in the Camden Council area.

- > B99 Vehicle can cross over the eastern car space line marking as it exits the staff car park.
- > B99 Vehicle can use the entire extent of the boom gate entrance.

Assuming the B99 Vehicle can cross over line-markings and the entire extent of the boom gate can be accessed in the staff car park, results shown in **Appendix C** and **Figure 4-2** indicate Car Space 3 can accommodate a B99 vehicle parking into Car Space 3 and exit via staff boom gates through to the Queen Street exit. However, due to the limited manoeuvrability into Car Space 3, it is recommended that this space be left unattended and to be used as additional space for other staff vehicles to manoeuvre in and out of the car park.


From **Figure 4-3**, **Figure 4-3** and **Figure 4-4**, the patrons' boom gate can accommodate the SRV and the MRV. Both the SRV and the MRV can manoeuvre through the car park and exit through the Queen Street exit.

The full swept path assessments are attached in **Appendix C**.




(Layout: Shellshear Young Pty Ltd)

Figure 4-2 B99 Vehicle Swept Path



(Layout: Shellshear Young Pty Ltd)

Figure 4-3 SRV Swept Path – Forward Park



(Layout: Shellshear Young Pty Ltd)

Figure 4-4 MRV Swept Path

4.3 Swept Path Analysis for 12m Truck Vehicle

Swept path analysis was conducted to test a 12m vehicle access along the perimeter of proposed development via the State Emergency Services (SES) facility. A preliminary assessment using a custom 12m truck with the following dimensions was analysed:

- > Length: 12ms
- > Width: 2.55ms
- > Wheelbase: 6.8ms

The manoeuvres assessed include:

- > 12m truck forward direction entry via Camden Council parking entrance (adjacent to NMC patron entry boom gates),
- > 12m truck forward direction exit out of Camden Council parking exit via Hume Street
- > 12m truck exit out of Hume Street onto Queen Street

Assumptions for the analysis include:

- > Existing Queen Street entry and exit driveways provide satisfactory entry and exit manoeuvres for the vehicle type listed above.
- > Vehicles are parked directly opposite the patron boom gate entrance in the Camden Council area.

Results in **Appendix C** show the entry and exits of the Camden Council car park (on the perimeter of the proposed development) can accommodate a 12 meter vehicle travelling in one forward direction through parking aisle.

As shown in **Figure 4-5**, swept path assessment of the 12m vehicle exiting on to Queen Street indicated the vehicle could encroach on to the adjacent property upon a left turn exit. The adjacent property is part of the existing conditions and Council trucks are currently exiting on to Queen Street from this driveway. Based on these existing conditions, the 12m truck exit manoeuvre was considered acceptable, given the truck is currently exiting the driveway and the adjacent land is under the same title as the proposed site.




Figure 4-5 12m Truck Swept Path – Exiting on to Queen Street

The full swept path assessment is attached in **Appendix C**.

5 Car Park Design

5.1 Car Parking Minimum Requirements

The development proposes to reconfigure the existing car park. The existing car park is primarily utilised by Camden Council Library patrons. This section of the report assesses the proposed car parking design against the minimum requirements identified in the Camden Development Control Plan 2011 and Camden Council Library DA conditions stipulated in DA No. 1467/2003.

5.1.1 Narellan Medical Centre

The Camden Development Control Plan 2011 (Camden DCP) Part B stipulates a minimum requirement for the number of parking spaces required for a medical centre. As outlined in **Figure 4-6**, the Camden DCP outlines four parking spaces per 100m² Gross Floor Area (GFA). The proposed medical centre is 1686m² therefore requires 68 car parking spaces to be provided. The proposed development complies with Camden Council's requirement by providing 81 parking spaces including two accessible parking spaces, 14 staff parking spaces, one loading bay and one emergency vehicle car space.

Health Care	
Health Service Facility / Medical Centre	4 car parking spaces per 100m ² GFA
Hospital / Veterinary hospital	Assessment to be based on merit taking into consideration the proposed uses and equivalent rates for similar uses as prescribed in this DCP.

(Source: Camden Council Development Control Plan 2011)

Figure 5-1 Camden Council Parking Rates for Health Service Facility/ Medical Centres


5.1.2 Camden Council Library

Provision for 73 car spaces of minimum width 2.6m are stipulated in Condition 17 of the Camden Council Library DA No. 1467/2003. The proposed development retains 73 car spaces of minimum width 2.6m for Camden Library Council patrons. Therefore, the proposed development complies with the Camden Council Library DA No. 1467/2003.

5.2 Sight Distance and Pedestrian Sight Lines


The minimum sight distance requirements are as per AS2890.1:2004. The sight distance requirements sets out the minimum sight distance for a driver to exit a car park or driveway on to a frontage road. For a 50km/hr frontage on Queen Street, a minimum sight distance of 45ms and a desirable sight distance of 69ms is required. An assessment of these requirements shows there are no vegetation or permanent obstruction impeding on the sight distance. As shown in **Figure 4-7**, the development car park layout meets the minimum requirements for sight distance.

Minimum sight lines for pedestrian requirements are displayed in **Figure 4-8**. Sight distance to pedestrians sets out the minimum requirements from the property line to allow pedestrian and vehicle visibility when vehicles leave a car park or driveway. These sight distance triangles are applied in context in **Figure 4-9**.




(Layout: Shellshear Young Pty Ltd)

Figure 5-2 Minimum Sight Distances



(Source: AS 2890.1:2004)

Figure 5-3 Minimum Sight Lines for Pedestrian



(Background: Shellshear Young Pty Ltd)

Figure 5-4 Minimum Sight Lines for Proposed Exit

As can be seen in **Figure 4-9**, the sight distance assessment reveals that the boom gates are located within the sight triangles for pedestrians. This is considered to be acceptable, given that the obstruction is highly unlikely to impede on visibility of a large object such as a moving vehicle. An example of the proposed boom gate is shown in **Figure 4-10**.




Figure 5-5 Typical Boom Gate Configuration

5.3 Car Park Operation

This section of the report outlines the car park operation of the proposed development. NMC patrons and staff access the car park via the existing driveways to and from Queen Street. Entry to the NMC car park is controlled by boom gates. NCM patrons and staff will have access to on-site parking at all operational times. The key purpose of the boom gate operation is to prevent non-NMC patron and staff vehicles from occupying the car spaces dedicated for NMC patrons and staff.

This car park operation has been approved for use in other Primary Health Care Medical Centres in Australia including Warringah (NSW), Wyong (NSW), Ringwood (VIC) and Phillip (ACT).

5.3.1 Patron Car Park Access

The patron and visitor car park will operate as a paid parking area (after a two or three hour free period) to deter patrons and non-patrons alike from utilising the car park for long term periods. This encourages car park spaces to turn-over and decreases the chance that an arriving NMC patron cannot find a car space. It is noted that the application of the parking fee is not intended as a means of raising revenue for the medical centre.

Patrons will enter the access road via the Queen Street driveway with access granted upon ticket retrieval at the entry boom gate. Exit out of the car park on to Queen Street is granted once a paid ticket is validated at the exit boom gate.

5.3.2 Staff Car Park Access

Designated car parking spaces are provided within the proposed NMC car park for NMC staff members only. An automated access system is implemented for this entry and exit. Car park entry is activated by an electronic security device that opens an automatic gate. Exit activation is induced via a ground induction loop that opens the gate upon approach.

5.3.3 Boom Gate Operation

5.3.3.1 Entry Gate

The car park design has allowed for two vehicles to queue at the boom gate entrance to the NMC car park without impacting external circulating car park traffic as presented in **Figure 5-6**. Entry to the car park will be implemented with a ticket splitter. Upon ticket retrieval, the boom gate opens and entry to the car park is granted. A pressure sensor detects when a vehicle is at the machine and only then can a ticket be taken from the machine. The boom arm is not activated by the loop so if a car tailgates the boom gate will come down. There is also an intercom button visitors can push for assistance if the boom gate should ever malfunction.




Figure 5-6 Car Park Entry Boom Gate

5.3.3.2 Exit Gate

A ticket reader connected to a boom gate is installed at the car park exit. The boom gate opens once a paid ticket is inserted and the patron can exit the car park. A pressure sensor detects when a vehicle is at the machine and only then can a ticket be inserted into the machine. The boom arm is not activated by the loop so if a car tailgates the boom gate will come down. There is an intercom button they can push for assistance if the boom gate should ever malfunction.

6 Conclusion

This report has been prepared to assess the traffic and transport impacts of the proposed Narellan Medical Centre on 19 Queen Street, Narellan. The assessment has considered the following scenarios:

- > Existing 2016 Scenario without development;
- > Opening Year 2017 including development; and
- > Opening Year plus 10 Years (2027) including development.

The assessment of the above scenarios results in the following findings:

- > The proposed medical centre is expected to generate approximately 176 vehicle trips in the AM peak hour and 149 vehicle trips in the PM peak hour periods.
- > Existing 2016 Scenario and the Opening Year plus 10 Years (2027) Scenario have a good Level of Service (LOS) A at both Queen Street / Elyard and Queen Street / Hume Street intersections.
- > Based on the assessment of the existing public transport network, it is reasonable to expect some staff and customers of the proposed site to arrive by bus. Access to the proposed site is supported by an adequate number of public bus routes well connected to the suburbs of Campbelltown and Camden.
- > It is reasonable to expect some staff and customers to walk to the proposed NMC. Based on the assessment of the existing pedestrian footpath network, there will be adequate infrastructure to accommodate pedestrian access to the proposed development site.
- > The Camden Council DCP (2011) stipulates a minimum number of car parking spaces for a medical centre development. The proposed development complies with the minimum parking requirements. A total of 81 parking spaces have been proposed including two accessible car spaces, 14 staff parking spaces, one loading bay and one emergency vehicle car space have been proposed.
- > The Camden Council Library DA Conditions indicate 73 car spaces of minimum width 2.6m be provided for the library. The proposed development maintains this provision and therefore complies with the Camden Council Library DA Conditions.
- > The proposed operation of the car park is effective in deterring non-NMC patrons occupying car spaces and in preventing long term stays. This operation has been approved for use in other Primary Health Care Medical Centres in Australia including Warringah (NSW), Wyoming (NSW), Ringwood (VIC) and Phillip (ACT).
- > An investigation into vehicle site access using swept paths of relevant vehicles was performed. The vehicles include a standard B99, Small Rigid Vehicle (SRV) and Medium Rigid Vehicle (MRV) to assess the swept paths of cars, emergency vehicles such as ambulances and large waste trucks. Results indicate that the proposed car park layout can accommodate the B99, SRV and MRV vehicles.
- > An investigation into vehicle access through the Camden Council car park on the perimeter of the development site was performed. Assessment of a 12m vehicle swept path shows that the perimeter car park entrance and exit can accommodate the 12m vehicle.
- > Swept path assessment of the 12m vehicle exiting on to Queen Street indicated the vehicle could encroach on to the adjacent property upon a left turn exit. The adjacent property is part of the existing conditions and Council trucks are currently exiting on to Queen Street from this driveway. Based on these existing conditions, the 12m truck exit manoeuvre was considered acceptable, given the truck is currently exiting the driveway and the adjacent land is under the same title as the proposed site.
- > A review of the minimum sight distance and sight lines for pedestrian safety was undertaken for the proposed car park exit. Results show that the car park exit satisfies the minimum driver sight distances. The sight line for pedestrian safety assessment reveals that the boom gates are located within safe sight triangles for pedestrians.

Narellan Medical Centre

APPENDIX


A

SURVEY RESULTS

Job No. : N2294
Client : Cardno
Suburb : Narellan
Location : 1. Queen St / Elyard St

Day/Date : Thu, 7th April 2016
Weather : Fine
Description : Classified Intersection Count
: 15 mins Data

Classifications	Class 1	Class 2	Class 3	Class 4
	Cars	Trucks	Buses	Cyclists




Approach	Queen St															Elyard St																								
Direction	Direction 1 (Left Turn)					Direction 2 (Through)					Direction 3 (Right Turn)					Direction 3U (U Turn)					Direction 4 (Left Turn)					Direction 5 (Through)					Direction 6 (Right Turn)					Direction 6U (U Turn)				
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total					
8:00 to 8:15	4	0	0	0	4	4	8	1	0	0	9	14	0	1	0	15	1	0	0	0	0	1	16	0	2	0	0	18	14	0	0	0	14	4	0	0	0	4		
8:15 to 8:30	2	0	0	0	2	14	0	0	0	14	18	0	0	3	0	21	0	0	0	0	0	17	0	2	0	0	19	18	1	0	0	0	7	0	0	0	0			
8:30 to 8:45	7	0	0	0	7	20	0	0	0	20	37	0	2	0	0	39	0	0	0	0	0	18	0	1	0	0	19	17	0	0	0	17	6	1	0	0	0			
8:45 to 9:00	14	0	0	0	14	29	0	0	0	29	22	0	1	0	0	23	0	0	0	0	0	15	0	1	0	0	16	21	0	0	0	21	15	0	0	0	0			
9:00 to 9:15	0	0	0	0	0	35	0	0	0	35	7	0	1	0	0	8	0	0	0	0	0	9	0	1	0	0	10	19	0	0	0	19	13	1	0	0	2			
9:15 to 9:30	2	0	0	0	2	18	0	0	0	18	16	0	1	0	0	17	0	0	0	0	0	14	0	1	0	0	15	24	3	0	0	27	9	0	0	1	0			
9:30 to 9:45	4	0	0	0	4	16	0	0	0	16	16	0	0	0	0	16	0	0	0	0	0	8	0	0	0	0	8	18	0	0	0	18	13	0	0	0	1			
9:45 to 10:00	12	0	0	0	12	9	0	0	0	9	10	0	1	0	0	11	0	0	0	0	0	13	0	2	0	0	15	23	2	0	0	25	13	1	0	0	1			
AM Totals	45	0	0	0	45	149	1	0	0	150	140	0	10	0	0	150	1	0	0	0	1	110	0	10	0	0	120	154	6	0	0	160	87	3	0	1	13			
16:00 to 16:15	15	0	0	0	15	14	0	0	0	14	22	0	1	0	0	23	1	0	0	0	1	24	0	3	0	0	27	35	2	0	0	37	7	0	0	0	5			
16:15 to 16:30	9	0	0	0	9	14	0	0	0	14	16	0	2	0	0	18	0	0	0	0	0	12	0	1	0	0	13	30	0	0	0	30	12	0	0	0	4			
16:30 to 16:45	13	0	0	0	13	11	0	0	0	11	15	0	0	0	0	15	0	0	0	0	0	18	1	2	0	0	21	44	0	0	0	44	10	0	0	0	3			
16:45 to 17:00	4	0	0	0	4	18	0	0	0	18	19	0	2	0	0	21	0	0	0	0	0	17	0	1	0	0	18	32	1	0	0	33	12	1	0	0	4			
17:00 to 17:15	11	0	0	0	11	23	0	0	0	23	21	0	1	0	0	22	0	0	0	0	0	22	0	0	0	0	22	53	1	0	0	54	13	0	0	0	6			
17:15 to 17:30	3	0	0	0	3	14	0	0	0	14	14	0	2	0	0	16	1	0	0	0	1	30	0	2	0	0	32	46	1	0	0	47	16	0	0	0	3			
17:30 to 17:45	4	0	0	0	4	6	0	0	0	6	9	0	1	0	0	10	0	0	0	0	0	20	1	2	0	0	23	49	0	0	0	49	13	0	0	0	1			
17:45 to 18:00	4	0	0	0	4	9	0	0	0	9	17	0	2	0	0	19	0	0	0	0	0	17	0	1	0	0	18	46	0	0	0	46	9	0	1	0	2			
PM Totals	63	0	0	0	63	109	0	0	0	109	133	0	11	0	0	144	2	0	0	0	2	160	2	12	0	0	174	335	5	0	0	340	92	1	1	0	28			

Approach	Queen St															Elyard St															Crossing Pedestrians																		
Direction	Direction 7 (Left Turn)					Direction 8 (Through)					Direction 9 (Right Turn)					Direction 9U (U Turn)					Direction 10 (Left Turn)					Direction 11 (Through)													Direction 12 (Right Turn)					Direction 12U (U Turn)					
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	A	B	C	D	E	F	G	H	Total					
8:00 to 8:15	11	2	1	0	14	7	1	0	0	8	8	0	0	0	8	3	1	0	0	4	29	0	0	0	29	53	0	1	0	54	8	0	0	0	8	0	0	0	0	0	0	0	2	5	1	1	0	9	
8:15 to 8:30	24	1	0	0	25	10	0	0	0	10	8	0	0	0	8	3	1	0	0	4	29	0	0	0	29	53	0	1	0	54	8	0	0	0	8	0	0	0	0	0	2	5	2	0	0	16			
8:30 to 8:45	20	2	1	0	23	9	0	0	0	9	10	0	0	0	10	1	0	0	0	1	37	0	0	0	37	65	0	2	0	67	10	0	0	0	10	3	0	0	0	0	1	0	5	7	3	0	9		
8:45 to 9:00	14	1	1	0	16	15	0	0	0	15	9	1	0	0	10	2	0	0	0	2	44	0	0	0	44	76	1	4	0	81	4	0	0	0	4	1	0	0	0	1	0	0	0	1	2	0	8		
9:00 to 9:15	13	1	0	0	14	24	0	0	0	24	7	0	0	0	7	0	0	0	0	0	86	1	1	0	88	46	0	1	0	47	14	0	0	0	14	1	0	0	0	0	1	1	0	1	0	0	3	0	5
9:15 to 9:30	21	4	1	0	26	24	0	0	0	24	12	0	0	0	12	0	0	0	0	0	64	0	0	0	64	22	1	1	0	24	7	0	0	0	7	1	0	0	0	1	0	0	0	5	1	0	0	6	
9:30 to 9:45	16	2	2	0	20	20	0	0	0	20	16	0	0	0	16	0	0	0	0	0	53	0	0	0	53	19	1	2	0	22	7	0	0	0	7	2	0	0	0	2	0	0	0	9	1	2	1	13	
9:45 to 10:00	25	3	1	0	29	25	0	0	0	25	25	0	0	0	25	0	0	0	0	0	62	1	0	0	63	21	1	0	0	22	10	0	0	0	10	0	0	0	0	0	0	2	4	5	0	2	13		
AM Totals	144	16	7	0	167	134	1	0	0	135	95	1	0	0	96	6	1	0	0	7	395	2	1	0	398	336	4	11	0	351	69	0	0	0	69	8	0	0	0	8	1	0	2	7	37	21	8	3	79
16:00 to 16:15	24	2	0	0	26	28	0	0	0	28	45	0	0	0	45	0	0	0	0	0	57	1	0	0	58	21	0	1	0	22	7	0	0	0	7	0	0	0	0	0	2	0	0	4	4	1	0	1	12
16:15 to 16:30	21	0	0	0	21	46	0	0	0	46	57	0	0	0	57	1	0	0	0	1	50	0	0	0	50	30	1	1	0	32	7	0	0	0	7	1	0	0	0	1	0	0	0	2	9	0	0	11	
16:30 to 16:45	25	0	1	0	26	33	0	0	0	33	55	0	0	0	55	0	0	0	0	0	39	0	0	0	39	25	0	2	0	27	6	0	0	0	6	1	0	0	0	1	0	0	2	3	4	5	2	2	18
16:45 to 17:00	16	0	2	0	18	39	0	0	0	39	52	0	0	0	52	3	0	0	0	3	44	0	0	0	44	24	1	1	0	26	5	0	0	0	5	1	0	0	0	1	0	0	2	2	1	6	0	1	12
17:00 to 17:15	22	0	1	0	23	40	0	0	0	40	57	0	0	0	57	2	0	0	0	2	42	0	0	0	42	35	1	2	0	38	5	1	0	0	6	1	0	0	0	1	1	0	2	0	3	2	0	2	10
17:15 to 17:30	19	0	0	0	19	39	0	0	0	39	70	1	0	0	71	1	0	0	0	1	49	0	0	0	49	24	1	2	0	27	7	0	0	0	7	1	0	0	0	1	0	0	0	2	3	1	0	6	
17:30 to 17:45	19	0	1	0	20	37	0	0	0	37	36	1	0	0	37	1	0	0	0	1	46	0	0	0	46	31	0	0	0	31	3	0	0	0	3	0	0	0	0	0	0	4	2	4	2	0	1	13	
17:45 to 18:00	16	0	1	0	17	33	0	0	0	33	41	0	0	0	41	3	0	0	0	3	46	0	0	0	46	39	0	2	0	41	3	0	0	0	3	2	0	0	0	2	0	2	2	2	8	0	1	17	
PM Totals	182	2	6	0	190	295	0	0	0	295	413	2	0	0	415	11	0	0	0	11	373	1	0	0	374	229	4	11	0	244	43	1	0	0	44	7	0	0	0	7	1	4	12	13	22	36	3	8	8

Job No. #REF!
 Client #REF!
 Suburb #REF!
 Location #REF!

Day/Date : Thu, 7th April 2016
 Weather : Fine
 Description : Classified Intersection Count
 : Hourly Summary




Approach	Queen St															Elyard St																								
Direction	Direction 1 (Left Turn)					Direction 2 (Through)					Direction 3 (Right Turn)					Direction 3U (U Turn)					Direction 4 (Left Turn)					Direction 5 (Through)					Direction 6 (Right Turn)					Direction 6U (U Turn)				
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total					
8:00 to 9:00	27	0	0	0	27	71	1	0	0	72	91	0	7	0	98	1	0	0	0	1	66	0	6	0	72	70	1	0	0	71	39	1	0	0	40	8	0	0	0	8
8:15 to 9:15	23	0	0	0	23	98	0	0	0	98	84	0	7	0	91	0	0	0	0	0	59	0	5	0	64	75	1	0	0	76	48	2	0	0	50	9	0	0	0	9
8:30 to 9:30	23	0	0	0	23	102	0	0	0	102	82	0	5	0	87	0	0	0	0	0	56	0	4	0	60	81	3	0	0	84	51	1	0	0	52	9	0	1	0	10
8:45 to 9:45	20	0	0	0	20	98	0	0	0	98	61	0	3	0	64	0	0	0	0	0	46	0	3	0	49	82	3	0	0	85	50	1	0	0	51	8	0	1	0	9
9:00 to 10:00	18	0	0	0	18	78	0	0	0	78	49	0	3	0	52	0	0	0	0	0	44	0	4	0	48	84	5	0	0	89	48	2	0	0	50	4	0	1	0	5
AM Totals	45	0	0	0	45	149	1	0	0	150	140	0	10	0	150	1	0	0	0	1	110	0	10	0	120	154	6	0	0	160	87	3	0	0	90	12	0	1	0	13
16:00 to 17:00	41	0	0	0	41	57	0	0	0	57	72	0	5	0	77	1	0	0	0	1	71	1	7	0	79	141	3	0	0	144	41	1	0	0	42	13	2	1	0	16
16:15 to 17:15	37	0	0	0	37	66	0	0	0	66	71	0	5	0	76	0	0	0	0	0	69	1	4	0	74	159	2	0	0	161	47	1	0	0	48	15	1	1	0	17
16:30 to 17:30	31	0	0	0	31	66	0	0	0	66	69	0	5	0	74	1	0	0	0	1	87	1	5	0	92	175	3	0	0	178	51	1	0	0	52	14	1	1	0	16
16:45 to 17:45	22	0	0	0	22	61	0	0	0	61	63	0	6	0	69	1	0	0	0	1	89	1	5	0	95	180	3	0	0	183	54	1	0	0	55	13	1	0	0	14
17:00 to 18:00	22	0	0	0	22	62	0	0	0	62	61	0	6	0	67	1	0	0	0	1	89	1	5	0	95	194	2	0	0	196	51	0	1	0	52	12	0	0	0	12
PM Totals	63	0	0	0	63	109	0	0	0	109	133	0	11	0	144	2	0	0	0	2	160	2	12	0	174	335	5	0	0	340	92	1	1	0	94	25	2	1	0	28

Approach	Queen St																				Elyard St																				Crossing Pedestrians									
Direction	Direction 7 (Left Turn)					Direction 8 (Through)					Direction 9 (Right Turn)					Direction 9U (U Turn)					Direction 10 (Left Turn)					Direction 11 (Through)					Direction 12 (Right Turn)					Direction 12U (U Turn)														
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	A	B	C	D	E	F	G	H	Total						
8:00 to 9:00	69	6	3	0	78	41	1	0	0	42	35	1	0	0	36	6	1	0	0	7	130	0	0	0	130	228	1	7	0	236	31	0	0	0	31	4	0	0	0	4	0	0	1	5	19	11	6	0	42	
8:15 to 9:15	71	5	2	0	78	58	0	0	0	58	34	1	0	0	35	6	1	0	0	7	196	1	1	0	198	240	1	8	0	249	36	0	0	0	36	5	0	0	0	5	1	0	2	3	14	13	5	0	38	
8:30 to 9:30	68	8	3	0	79	72	0	0	0	72	38	1	0	0	39	3	0	0	0	3	231	1	1	0	233	209	2	8	0	219	35	0	0	0	35	6	0	0	0	6	1	0	2	1	14	12	5	0	35	
8:45 to 9:45	64	8	4	0	76	83	0	0	0	83	44	1	0	0	45	2	0	0	0	2	247	1	1	0	249	163	3	8	0	174	32	0	0	0	32	5	0	0	0	5	1	0	1	1	18	6	4	1	32	
9:00 to 10:00	75	10	4	0	89	93	0	0	0	93	60	0	0	0	60	0	0	0	0	0	265	2	1	0	268	108	3	4	0	115	38	0	0	0	38	4	0	0	0	4	1	0	1	2	18	10	2	3	37	
AM Totals	144	16	7	0	167	134	1	0	0	135	95	1	0	0	96	6	1	0	0	7	395	2	1	0	398	336	4	11	0	351	69	0	0	0	69	8	0	0	0	8	1	0	2	7	37	21	8	3	79	
16:00 to 17:00	86	2	3	0	91	146	0	0	0	146	209	0	0	0	209	4	0	0	0	4	190	1	0	0	191	100	2	5	0	107	25	0	0	0	25	3	0	0	0	3	0	2	4	9	11	21	2	4	53	
16:15 to 17:15	84	0	4	0	88	158	0	0	0	158	221	0	0	0	221	6	0	0	0	6	175	0	0	0	175	114	3	6	0	123	23	1	0	0	24	4	0	0	0	4	1	0	6	5	10	22	2	5	51	
16:30 to 17:30	82	0	4	0	86	151	0	0	0	151	234	1	0	0	235	6	0	0	0	6	174	0	0	0	174	108	3	7	0	118	23	1	0	0	24	4	0	0	0	4	1	0	6	5	10	16	3	5	46	
16:45 to 17:45	76	0	4	0	80	155	0	0	0	155	215	2	0	0	217	7	0	0	0	7	181	0	0	0	181	114	3	5	0	122	20	1	0	0	21	3	0	0	0	3	1	0	8	4	10	13	1	4	41	
17:00 to 18:00	76	0	3	0	79	149	0	0	0	149	204	2	0	0	206	7	0	0	0	7	183	0	0	0	183	129	2	6	0	137	18	1	0	0	19	4	0	0	0	4	1	2	8	4	11	15	1	4	46	
PM Totals	162	2	6	0	170	295	0	0	0	295	413	2	0	0	415	11	0	0	0	11	373	1	0	0	374	229	4	11	0	244	43	1	0	0	44	7	0	0	0	7	1	4	12	13	22	36	3	8	99	

Job No. #REF!
 Client #REF!
 Suburb #REF!
 Location #REF!

Day/Date : Thu, 7th April 2016
 Weather : Fine
 Description : Classified Intersection Count
 : Peak Hour Summary



Approach		Queen St					Elyard St					Queen St					Elyard St					Grand Total
Time Period		Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	
AM	8:30 to 9:30	207	0	5	0	212	197	4	5	0	206	181	9	3	0	193	481	3	9	0	493	1,104
PM	16:30 to 17:30	167	0	5	0	172	327	6	6	0	339	473	1	4	0	478	309	4	7	0	320	1,309


Approach		Queen St					Elyard St					Queen St					Elyard St					Grand Total
Time Period		Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	
8:00 to 9:00		190	1	7	0	198	183	2	6	0	191	151	9	3	0	163	393	1	7	0	401	953
8:15 to 9:15		205	0	7	0	212	191	3	5	0	199	169	7	2	0	178	477	2	9	0	488	1,077
8:30 to 9:30		207	0	5	0	212	197	4	5	0	206	181	9	3	0	193	481	3	9	0	493	1,104
8:45 to 9:45		179	0	3	0	182	186	4	4	0	194	193	9	4	0	206	447	4	9	0	460	1,042
9:00 to 10:00		145	0	3	0	148	180	7	5	0	192	228	10	4	0	242	415	5	5	0	425	1,007
AM Totals		335	1	10	0	346	363	9	11	0	383	379	19	7	0	405	808	6	12	0	826	1,960
16:00 to 17:00		171	0	5	0	176	266	7	8	0	281	445	2	3	0	450	318	3	5	0	326	1,233
16:15 to 17:15		174	0	5	0	179	290	5	5	0	300	469	0	4	0	473	316	4	6	0	326	1,278
16:30 to 17:30		167	0	5	0	172	327	6	6	0	339	473	1	4	0	478	309	4	7	0	320	1,309
16:45 to 17:45		147	0	6	0	153	336	6	5	0	347	453	2	4	0	459	318	4	5	0	327	1,286
17:00 to 18:00		136	0	6	0	142	346	3	6	0	355	436	2	3	0	441	334	3	6	0	343	1,281
PM Totals		307	0	11	0	318	612	10	14	0	636	881	4	6	0	891	652	6	11	0	669	2,514

Job No. #
Client #
Suburb #
Location #


Day/Date : Thu, 7th April 2016
Weather : Fine
Description : Classified Intersection Count
Intersection Diagram



Hour Starting Vehicle Type
AM Totals All Vehicles



Day/Date	: Thu, 7th April 2016
Weather	: Fine
Description	: Classified Intersection Count




Class 1	Class 2	Class 3	Class 4
Cars	Trucks	Buses	Cyclists

Approach	Queen St															Hume St																								
Direction	Direction 1 (Left Turn)					Direction 2 (Through)					Direction 3 (Right Turn)					Direction 3U (U Turn)					Direction 4 (Left Turn)					Direction 5 (Through)					Direction 6 (Right Turn)					Direction 6U (U Turn)				
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total					
8:00 to 8:15	0	0	0	0	0	31	0	1	0	32	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	2	0	0	0	0	0				
8:15 to 8:30	0	0	0	0	0	36	0	1	0	39	0	0	0	0	0	2	0	0	0	0	2	0	0	0	0	4	0	0	0	0	4	0	0	0	0	0				
8:30 to 8:45	0	0	0	0	0	61	0	2	0	63	0	0	0	0	0	2	0	0	0	0	2	0	0	0	0	7	0	0	0	0	7	0	0	0	0	0				
8:45 to 9:00	0	0	0	0	0	53	0	1	0	54	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	7	0	0	0	0	7	0	0	0	0	0				
9:00 to 9:15	0	0	0	0	0	44	0	1	0	45	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1	0	0	0	0	1	0	0	0	0	0				
9:15 to 9:30	0	0	0	0	0	29	0	1	0	30	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	5	0	0	0	0	5	0	0	0	0	0				
9:30 to 9:45	0	0	0	0	0	35	0	0	0	35	0	0	0	0	0	2	0	0	0	0	2	0	0	0	0	5	0	0	0	0	5	0	0	0	0	0				
9:45 to 10:00	1	0	0	0	1	19	1	1	0	21	0	0	0	0	0	3	1	0	0	0	4	0	0	0	0	11	0	0	0	0	11	0	0	0	0	0				
AM Totals	1	0	0	0	1	308	1	10	0	319	0	0	0	0	0	12	1	0	0	0	13	0	0	0	0	42	0	0	0	0	42	0	0	0	0	0				
16:00 to 16:15	1	0	0	0	1	30	0	1	0	31	0	0	0	0	0	7	0	0	0	7	0	0	0	0	21	0	0	0	0	21	0	0	0	0	0	0				
16:15 to 16:30	1	0	0	0	1	24	0	2	0	26	0	0	0	0	0	3	0	0	0	3	0	0	0	0	16	0	0	0	0	16	0	0	0	0	0	0				
16:30 to 16:45	1	0	0	0	1	22	0	0	0	22	0	0	0	0	0	9	0	0	0	9	0	0	0	0	15	0	0	0	0	15	0	0	0	0	0	0				
16:45 to 17:00	0	0	0	0	0	25	0	2	0	27	0	0	0	0	0	8	0	0	0	8	0	0	0	0	14	0	0	0	0	14	0	0	0	0	0	0				
17:00 to 17:15	1	0	0	0	1	20	0	2	0	22	0	0	0	0	0	9	0	0	0	9	0	0	0	0	25	0	0	0	0	25	0	0	0	0	0	0				
17:15 to 17:30	0	0	0	0	0	17	0	1	0	18	0	0	0	0	0	5	0	0	0	5	0	0	0	0	10	0	0	0	0	10	0	0	0	0	0	0				
17:30 to 17:45	0	0	0	0	0	18	0	2	0	20	0	0	0	0	0	4	0	0	0	4	0	0	0	0	4	0	0	0	0	4	0	0	0	0	0	0				
17:45 to 18:00	0	0	0	0	0	21	0	1	0	22	0	0	0	0	0	5	0	0	0	5	0	0	0	0	7	0	0	0	0	7	0	0	0	0	0	0				
PM Totals	4	0	0	0	4	177	0	11	0	188	0	0	0	0	0	50	0	0	0	50	0	0	0	0	112	0	0	0	0	112	0	0	0	0	0	0				

Approach	Queen St															Hume St															Crossing Pedestrians																
Direction	Direction 7 (Left Turn)					Direction 8 (Through)					Direction 9 (Right Turn)					Direction 10 (Left Turn)					Direction 11 (Through)					Direction 12 (Right Turn)													Direction 12U (U Turn)								
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	A	B	C	D	E	F	G	H	I	J		
8:00 - 8:15	0	0	0	0	0	39	0	1	0	20	3	0	0	0	0	3	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	2
8:15 - 8:30	0	0	0	0	0	11	0	2	0	13	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0		
8:30 - 8:45	0	0	0	0	0	15	0	1	0	16	0	0	0	0	0	0	0	0	0	0	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
8:45 - 9:00	0	0	0	0	0	16	0	0	0	17	1	0	0	0	0	1	0	0	0	0	0	4	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	2		
9:00 - 9:15	0	0	0	0	0	30	0	1	0	31	1	0	0	0	0	1	0	0	0	0	0	2	0	0	0	0	0	1	0	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	2	
9:15 - 9:30	0	0	0	0	0	27	0	1	0	28	0	0	0	0	0	0	2	0	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	2	
9:30 - 9:45	0	0	0	0	0	20	0	1	0	21	2	0	0	0	0	2	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0	0	1	0	2	0	0	0	0	0	0	0	3		
9:45 - 10:00	0	0	0	0	0	29	0	2	0	31	2	0	0	0	0	2	0	0	0	0	0	1	29	0	2	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	2	
AM Totals	0	0	0	0	0	167	0	10	0	177	9	0	0	0	0	9	0	0	0	0	17	0	0	0	0	0	17	0	0	0	0	0	2	0	0	0	0	0	0	1	4	9	1	0	0	0	15
16:00 - 16:15	0	0	0	0	0	56	0	2	0	58	4	0	0	0	0	4	0	0	0	0	0	2	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	1	5	2	0	0	0	0	0	9	
16:15 - 16:30	0	0	0	0	0	52	0	0	0	53	2	0	0	0	0	2	0	0	0	0	0	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3	0	0	0	0	0	0	1	
16:30 - 16:45	0	0	0	0	0	49	1	2	0	52	4	0	0	0	0	4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3	0	6	2	1	0	0	0	0	0	12		
16:45 - 17:00	0	0	0	0	0	54	0	1	0	55	2	0	0	0	0	2	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	0	0	0	0	0	0	0	4	
17:00 - 17:15	0	0	0	0	0	54	1	0	0	55	4	0	0	0	0	4	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	0	0	0	0	0	0	0	4		
17:15 - 17:30	0	0	0	0	0	70	0	3	0	73	3	0	0	0	0	3	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
17:30 - 17:45	0	0	0	0	0	54	0	1	0	55	2	0	0	0	0	2	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
17:45 - 18:00	0	0	0	0	0	50	0	1	0	51	1	0	0	0	0	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	2	
PM Totals	0	0	0	0	0	439	2	11	0	452	22	0	0	0	0	22	1	0	0	0	0	10	0	0	0	0	10	0	0	0	0	0	1	0	0	0	1	3	11	14	4	1	0	0	0	30	

Job No. #REF!
 Client #REF!
 Suburb #REF!
 Location #REF!
 Day/Date : Thu, 7th April 2016
 Weather : Fine
 Description : Classified Intersection Count
 : Hourly Summary




Approach	Queen St															Hume St																								
Direction	Direction 1 (Left Turn)					Direction 2 (Through)					Direction 3 (Right Turn)					Direction 3U (U Turn)					Direction 4 (Left Turn)					Direction 5 (Through)					Direction 6 (Right Turn)					Direction 6U (U Turn)				
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total					
8:00 to 9:00	0	0	0	0	0	181	0	7	0	188	0	0	0	0	0	0	0	0	0	0	5	0	0	0	0	5	0	0	0	0	20	0	0	0	0	20				
8:15 to 9:15	0	0	0	0	0	194	0	7	0	201	0	0	0	0	0	0	0	0	0	0	6	0	0	0	0	6	0	0	0	0	19	0	0	0	0	19				
8:30 to 9:30	0	0	0	0	0	187	0	5	0	192	0	0	0	0	0	0	0	0	0	0	5	0	0	0	0	5	0	0	0	0	20	0	0	0	0	20				
8:45 to 9:45	0	0	0	0	0	161	0	3	0	164	0	0	0	0	0	0	0	0	0	0	5	0	0	0	0	5	0	0	0	0	18	0	0	0	0	18				
9:00 to 10:00	1	0	0	0	1	127	1	3	0	131	0	0	0	0	0	0	0	0	0	0	7	1	0	0	0	8	0	0	0	0	22	0	0	0	0	22				
AM Totals	1	0	0	0	1	368	1	30	0	319	0	0	0	0	0	0	0	0	0	0	12	1	0	0	0	13	0	0	0	0	42	0	0	0	0	42				
16:00 to 17:00	3	0	0	0	3	101	0	5	0	106	0	0	0	0	0	0	0	0	0	0	27	0	0	0	0	27	0	0	0	0	66	0	0	0	0	66				
16:15 to 17:15	3	0	0	0	3	91	0	6	0	97	0	0	0	0	0	0	0	0	0	0	29	0	0	0	0	29	0	0	0	0	70	0	0	0	0	70				
16:30 to 17:30	2	0	0	0	2	84	0	5	0	89	0	0	0	0	0	0	0	0	0	0	31	0	0	0	0	31	0	0	0	0	64	0	0	0	0	64				
16:45 to 17:45	1	0	0	0	1	80	0	7	0	87	0	0	0	0	0	0	0	0	0	0	26	0	0	0	0	26	0	0	0	0	53	0	0	0	0	53				
17:00 to 18:00	1	0	0	0	1	76	0	6	0	82	0	0	0	0	0	0	0	0	0	0	23	0	0	0	0	23	0	0	0	0	46	0	0	0	0	46				
PM Totals	4	0	0	0	4	177	0	31	0	188	0	0	0	0	0	0	0	0	0	0	50	0	0	0	0	50	0	0	0	0	112	0	0	0	0	112				

Approach	Queen St																		Hume St																		Crossing Pedestrians												
Direction	Direction 7 (Left Turn)					Direction 8 (Through)					Direction 9 (Right Turn)					Direction 9U (U Turn)					Direction 10 (Left Turn)					Direction 11 (Through)					Direction 12 (Right Turn)					Direction 12U (U Turn)													
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	A	B	C	D	E	F	G	H	Total					
8:00 to 9:00	0	0	0	0	0	61	0	5	0	66	4	0	0	0	4	0	0	0	0	0	11	0	0	0	0	11	0	0	0	0	0	0	0	0	0	0	0	3	3	0	0	0	0	0	6				
8:15 to 9:15	0	0	0	0	0	72	0	5	0	77	2	0	0	0	2	0	0	0	0	0	11	0	0	0	0	11	0	0	0	0	1	0	0	0	0	0	0	3	3	0	0	0	0	0	6				
8:30 to 9:30	0	0	0	0	0	88	0	4	0	92	2	0	0	0	2	0	0	0	0	0	11	0	0	0	0	11	0	0	0	0	1	0	0	0	0	0	1	4	1	0	0	0	0	6					
8:45 to 9:45	0	0	0	0	0	93	0	4	0	97	4	0	0	0	4	0	0	0	0	0	9	0	0	0	0	9	0	0	0	0	2	0	0	0	0	2	0	0	0	0	0	1	1	6	1	0	0	9	
9:00 to 10:00	0	0	0	0	0	106	0	5	0	111	5	0	0	0	5	0	0	0	0	0	6	0	0	0	0	6	0	0	0	0	2	0	0	0	0	2	0	0	0	0	0	1	1	6	1	0	0	9	
AM Totals	0	0	0	0	0	367	0	30	0	377	0	0	0	0	0	0	0	0	0	0	17	0	0	0	0	17	0	0	0	0	2	0	0	0	0	2	0	0	0	0	0	1	4	9	1	0	0	15	
16:00 to 17:00	0	0	0	0	0	211	1	6	0	218	12	0	0	0	12	0	0	0	0	0	6	0	0	0	0	6	0	0	0	0	1	0	0	0	0	1	0	0	0	0	1	3	5	14	4	1	0	0	28
16:15 to 17:15	0	0	0	0	0	209	2	4	0	215	12	0	0	0	12	0	0	0	0	0	5	0	0	0	0	5	0	0	0	0	0	0	0	0	0	0	3	8	9	2	1	0	0	0	23				
16:30 to 17:30	0	0	0	0	0	227	2	6	0	235	13	0	0	0	13	0	0	0	0	0	4	0	0	0	0	4	0	0	0	0	0	0	0	0	0	0	0	3	8	6	2	1	0	0	0	20			
16:45 to 17:45	0	0	0	0	0	232	1	5	0	238	11	0	0	0	11	0	0	0	0	0	5	0	0	0	0	5	0	0	0	0	0	0	0	0	0	0	0	8	0	0	0	0	0	0	8				
17:00 to 18:00	0	0	0	0	0	228	1	5	0	234	10	0	0	0	10	1	0	0	0	0	4	0	0	0	0	4	0	0	0	0	0	0	0	0	0	0	0	6	0	0	0	0	0	0	6				
PM Totals	0	0	0	0	0	439	2	31	0	452	22	0	0	0	22	1	0	0	0	1	10	0	0	0	0	10	0	0	0	0	1	0	0	0	0	1	0	0	0	0	1	3	11	14	4	1	0	0	34

Job No. #REF!
 Client #REF!
 Suburb #REF!
 Location #REF!


Day/Date : Thu, 7th April 2016
 Weather : Fine
 Description : Classified Intersection Count
 : Peak Hour Summary



Approach		Queen St					Hume St					Queen St					Hume St					Grand Total
Time Period		Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	
AM	8:30 to 9:30	187	0	5	0	192	25	0	0	0	25	90	0	4	0	94	12	0	0	0	12	323
PM	16:00 to 17:00	104	0	5	0	109	93	0	0	0	93	223	1	6	0	230	7	0	0	0	7	439

Approach		Queen St					Hume St					Queen St					Hume St					Grand Total
Time Period		Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	
8:00	to 9:00	181	0	7	0	188	25	0	0	0	25	65	0	5	0	70	11	0	0	0	11	294
8:15	to 9:15	194	0	7	0	201	25	0	0	0	25	74	0	5	0	79	12	0	0	0	12	317
8:30	to 9:30	187	0	5	0	192	25	0	0	0	25	90	0	4	0	94	12	0	0	0	12	323
8:45	to 9:45	161	0	3	0	164	23	0	0	0	23	97	0	4	0	101	11	0	0	0	11	299
9:00	to 10:00	128	1	3	0	132	29	1	0	0	30	111	0	5	0	116	8	0	0	0	8	286
AM Totals		309	1	10	0	320	54	1	0	0	55	176	0	10	0	186	19	0	0	0	19	580
16:00	to 17:00	104	0	5	0	109	93	0	0	0	93	223	1	6	0	230	7	0	0	0	7	439
16:15	to 17:15	94	0	6	0	100	99	0	0	0	99	221	2	4	0	227	5	0	0	0	5	431
16:30	to 17:30	86	0	5	0	91	95	0	0	0	95	240	2	6	0	248	4	0	0	0	4	438
16:45	to 17:45	81	0	7	0	88	79	0	0	0	79	243	1	5	0	249	5	0	0	0	5	421
17:00	to 18:00	77	0	6	0	83	69	0	0	0	69	239	1	5	0	245	4	0	0	0	4	401
PM Totals		181	0	11	0	192	162	0	0	0	162	462	2	11	0	475	11	0	0	0	11	840


Day/Date : Thu, 7th April 2016
Weather : Fine
Description : Classified Intersection Count
: Intersection Diagram



Job No. : N2294
Client : Cardno
Suburb : Narellan
Location : 1. Queen St / Elyard St

Day/Date : Sat, 2nd Apr 2016
Weather : Fine
Description : Classified Intersection Count
: 15 mins Data

Classifications	Class 1	Class 2	Class 3	Class 4
	Cars	Trucks	Busess	Cyclists




Approach	Queen St															Elyard St																								
Direction	Direction 1 (Left Turn)					Direction 2 (Through)					Direction 3 (Right Turn)					Direction 3U (U Turn)					Direction 4 (Left Turn)					Direction 5 (Through)					Direction 6 (Right Turn)					Direction 6U (U Turn)				
Time Period	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total					
11:00 to 11:15	8	0	0	0	8	17	0	0	0	17	17	0	0	0	17	0	0	0	0	0	13	0	0	0	13	26	0	0	0	26	6	0	0	0	6	1	0	0	0	1
11:15 to 11:30	6	1	0	0	7	22	0	0	0	22	15	0	1	0	16	0	0	0	0	0	10	0	1	0	11	19	0	0	0	19	9	0	0	0	9	2	0	0	0	2
11:30 to 11:45	6	0	0	0	6	16	0	0	0	16	14	0	0	0	14	0	0	0	0	0	17	0	1	0	18	29	1	0	0	30	11	0	0	0	11	2	0	0	0	2
11:45 to 12:00	6	0	0	0	6	19	0	0	0	19	11	0	2	0	13	1	0	0	0	1	12	0	1	0	13	25	0	0	0	25	10	0	0	0	10	2	0	0	0	2
12:00 to 12:15	7	0	0	0	7	13	0	0	0	13	12	0	1	0	13	0	0	0	0	0	17	0	0	0	17	42	0	0	0	42	12	0	0	0	12	6	0	0	0	6
12:15 to 12:30	4	0	0	0	4	12	0	0	0	12	6	0	0	0	6	0	0	0	0	0	14	1	1	0	16	23	1	0	0	24	14	0	0	0	14	1	0	0	0	1
12:30 to 12:45	1	0	0	0	1	12	0	0	0	12	11	1	1	0	13	1	0	0	0	1	17	0	1	0	18	22	0	0	0	22	8	0	0	0	8	0	0	0	0	0
12:45 to 13:00	2	1	0	0	3	13	0	0	0	13	11	0	2	0	13	0	0	0	0	0	17	0	0	0	17	26	0	0	0	26	7	0	0	0	7	2	0	0	0	2
Total	40	2	0	0	42	124	0	0	0	124	97	1	7	0	105	2	0	0	0	2	117	1	5	0	123	212	2	0	0	214	77	0	0	0	77	16	0	0	0	16

Approach	Queen St																		Elyard St																		Crossing Pedestrians												
Direction	Direction 7 (Left Turn)					Direction 8 (Through)					Direction 9 (Right Turn)					Direction 9U (U Turn)					Direction 10 (Left Turn)					Direction 11 (Through)					Direction 12 (Right Turn)					Direction 12U (U Turn)													
Time Period	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	Cars	Trucks	Busess	Cyclists	Total	A	B	C	D	E	F	G	H	Total					
11:00 to 11:15	22	1	1	0	24	39	0	0	0	39	35	1	0	0	36	0	0	0	0	0	71	0	0	0	71	27	0	1	0	28	8	0	0	0	8	1	0	0	0	1	0	0	0	0	5	9	0	0	14
11:15 to 11:30	26	1	0	0	27	35	0	0	0	35	45	0	0	0	45	2	0	0	0	2	81	1	0	0	82	15	1	0	0	16	5	0	0	0	5	1	0	0	0	1	0	0	0	1	5	5	2	2	15
11:30 to 11:45	28	0	0	0	28	40	0	0	0	40	36	0	0	0	36	1	0	0	0	1	69	0	0	0	69	27	0	1	0	28	10	0	0	0	10	5	0	0	0	5	2	0	1	0	9	9	2	1	24
11:45 to 12:00	25	0	0	0	25	34	0	0	0	34	47	0	0	0	47	1	0	0	0	1	57	1	0	0	58	32	0	0	0	32	9	0	0	0	9	2	0	0	0	2	0	0	0	4	16	4	0	1	25
12:00 to 12:15	28	1	1	0	30	33	0	0	0	33	46	0	0	0	46	1	0	0	0	1	54	0	0	0	54	30	0	2	0	32	7	0	0	0	7	2	0	0	0	2	0	0	1	0	7	6	1	0	15
12:15 to 12:30	23	0	0	0	23	36	0	0	0	36	41	0	0	0	41	1	0	0	0	1	56	1	0	0	57	29	1	0	0	30	5	0	0	0	5	3	0	0	0	3	0	0	0	1	8	7	0	0	16
12:30 to 12:45	24	1	0	0	25	21	0	0	0	21	42	0	0	0	42	1	0	0	0	1	51	0	0	0	51	20	0	0	0	20	6	0	0	0	6	0	0	0	0	0	0	0	1	2	4	7	0	0	14
12:45 to 13:00	25	0	0	0	25	30	0	0	0	30	45	1	0	0	46	1	0	0	0	1	39	1	0	0	40	27	0	1	0	28	6	0	0	0	6	0	0	0	0	0	1	1	0	6	15	0	0	27	
Total	201	4	2	0	207	268	0	0	0	268	337	2	0	0	339	8	0	0	0	8	478	4	0	0	482	207	2	5	0	214	56	0	0	0	56	14	0	0	0	14	2	1	4	8	60	66	5	4	150

Job No. : N2294
 Client : Cardno
 Suburb : Narellan
 Location : 1. Queen St / Elyard St


Day/Date : Sat, 2nd Apr 2016
 Weather : Fine
 Description : Classified Intersection Count
 : Hourly Summary



Approach	Queen St															Elyard St																								
Direction	Direction 1 (Left Turn)					Direction 2 (Through)					Direction 3 (Right Turn)					Direction 3U (U Turn)					Direction 4 (Left Turn)					Direction 5 (Through)					Direction 6 (Right Turn)					Direction 6U (U Turn)				
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total					
11:00 to 12:00	26	1	0	0	27	74	0	0	0	74	57	0	3	0	60	1	0	0	0	1	52	0	3	0	55	99	1	0	0	100	36	0	0	0	36	7	0	0	0	7
11:15 to 12:15	25	1	0	0	26	70	0	0	0	70	52	0	4	0	56	1	0	0	0	1	56	0	3	0	59	115	1	0	0	116	42	0	0	0	42	12	0	0	0	12
11:30 to 12:30	23	0	0	0	23	60	0	0	0	60	43	0	3	0	46	1	0	0	0	1	60	1	3	0	64	119	2	0	0	121	47	0	0	0	47	11	0	0	0	11
11:45 to 12:45	18	0	0	0	18	56	0	0	0	56	40	1	4	0	45	2	0	0	0	2	60	1	3	0	64	112	1	0	0	113	44	0	0	0	44	9	0	0	0	9
12:00 to 13:00	14	1	0	0	15	50	0	0	0	50	40	1	4	0	45	1	0	0	0	1	65	1	2	0	68	113	1	0	0	114	41	0	0	0	41	9	0	0	0	9
Total	40	2	0	0	42	124	0	0	0	124	97	1	7	0	105	2	0	0	0	2	117	1	5	0	123	212	2	0	0	214	77	0	0	0	77	16	0	0	0	16

Approach	Queen St																				Elyard St																				Crossing Pedestrians								
Direction	Direction 7 (Left Turn)					Direction 8 (Through)					Direction 9 (Right Turn)					Direction 9U (U Turn)					Direction 10 (Left Turn)					Direction 11 (Through)					Direction 12 (Right Turn)					Direction 12U (U Turn)													
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	A	B	C	D	E	F	G	H	Total					
11:00 to 12:00	101	2	1	0	104	148	0	0	0	148	163	1	0	0	164	4	0	0	0	4	278	2	0	0	280	101	1	2	0	104	32	0	0	0	32	9	0	0	0	9	2	0	1	5	35	27	4	4	78
11:15 to 12:15	107	2	1	0	110	142	0	0	0	142	174	0	0	0	174	5	0	0	0	5	261	2	0	0	263	104	1	3	0	108	31	0	0	0	31	10	0	0	0	10	2	0	2	5	37	24	5	4	79
11:30 to 12:30	104	1	1	0	106	143	0	0	0	143	170	0	0	0	170	4	0	0	0	4	236	2	0	0	238	118	1	3	0	122	31	0	0	0	31	12	0	0	0	12	2	0	2	5	40	26	3	2	80
11:45 to 12:45	100	2	1	0	103	124	0	0	0	124	176	0	0	0	176	4	0	0	0	4	218	2	0	0	220	111	1	2	0	114	27	0	0	0	27	7	0	0	0	7	0	0	2	7	35	24	1	1	70
12:00 to 13:00	100	2	1	0	103	120	0	0	0	120	174	1	0	0	175	4	0	0	0	4	200	2	0	0	202	106	1	3	0	110	24	0	0	0	24	5	0	0	0	5	0	1	3	3	25	39	1	0	72
Total	201	4	2	0	207	268	0	0	0	268	337	2	0	0	339	8	0	0	0	8	478	4	0	0	482	207	2	5	0	214	56	0	0	0	56	14	0	0	0	14	2	1	4	8	60	66	5	4	150

Day/Date	: Sat, 2nd Apr 2016
Weather	: Fine
Description	: Classified Intersection Count




	Class 1	Class 2	Class 3	Class 4
Classifications	Cars	Trucks	Buses	Cyclists

Approach	Queen St															Hume St																								
Direction	Direction 1 (Left Turn)					Direction 2 (Through)					Direction 3 (Right Turn)					Direction 3U (U Turn)					Direction 4 (Left Turn)					Direction 5 (Through)					Direction 6 (Right Turn)					Direction 6U (U Turn)				
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total					
11:00 to 11:15	0	0	0	0	0	31	0	0	0	31	0	0	0	0	0	3	0	0	0	0	3	0	0	0	0	0	7	0	0	0	7	0	0	0	0	0				
11:15 to 11:30	0	0	0	0	0	31	0	1	0	32	0	0	0	0	0	2	0	0	0	0	2	1	0	0	0	1	6	0	0	0	6	0	0	0	0	0				
11:30 to 11:45	0	0	0	0	0	31	1	0	0	32	0	0	0	0	0	4	0	0	0	0	4	0	0	0	0	0	7	0	0	0	7	0	0	0	0	0				
11:45 to 12:00	1	0	0	0	1	32	0	2	0	34	0	0	0	0	0	2	0	0	0	0	2	0	0	0	0	0	7	0	0	0	7	0	0	0	0	0				
12:00 to 12:15	0	0	0	0	0	30	0	0	0	30	0	0	0	0	0	5	0	0	0	0	5	0	0	0	0	0	7	0	0	0	7	0	0	0	0	0				
12:15 to 12:30	0	0	0	0	0	21	0	1	0	22	0	0	0	0	0	3	0	0	0	0	3	0	0	0	0	0	3	0	0	0	3	0	0	0	0	0				
12:30 to 12:45	0	0	0	0	0	16	0	0	0	16	0	0	0	0	0	4	0	0	0	0	4	0	0	0	0	0	5	0	0	0	5	0	0	0	0	0				
12:45 to 13:00	0	0	0	0	0	22	1	3	0	26	0	0	0	0	0	2	0	0	0	0	2	0	0	0	0	0	5	0	0	0	5	0	0	0	0	0				
Total	1	0	0	0	1	214	2	7	0	223	0	0	0	0	0	25	0	0	0	0	25	1	0	0	0	1	47	0	0	0	47	0	0	0	0	0				

Approach	Queen St																Hume St																Crossing Pedestrians							
Direction	Direction 7 (Left Turn)				Direction 8 (Through)				Direction 9 (Right Turn)				Direction 9U (U Turn)				Direction 10 (Left Turn)				Direction 11 (Through)				Direction 12 (Right Turn)				Direction 12U (U Turn)											
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	A	B	C	D	E	F	G	H	Total	
11:00 to 11:15	0	0	0	0	0	42	0	1	0	43	3	0	0	0	3	0	0	0	0	0	7	0	0	0	7	0	0	0	0	0	0	0	0	2	3	0	0	0	0	5
11:15 to 11:30	0	0	0	0	0	50	0	1	0	51	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	2		
11:30 to 11:45	0	0	0	0	0	44	0	1	0	45	4	0	0	0	4	0	0	0	0	0	1	0	0	0	1	0	0	0	0	1	0	0	1	1	0	0	0	2		
11:45 to 12:00	0	0	0	0	0	48	0	0	0	48	1	0	0	0	1	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0	0	1		
12:00 to 12:15	0	0	0	0	0	49	0	1	0	50	3	0	0	0	3	0	2	0	0	0	2	0	0	0	2	0	0	0	0	0	0	0	0	2	0	0	0	2		
12:15 to 12:30	0	0	0	0	0	47	1	1	0	49	4	0	0	0	4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	2			
12:30 to 12:45	0	0	0	0	0	34	0	1	0	35	4	0	0	0	4	1	0	0	0	1	5	0	0	0	5	0	0	0	0	0	0	1	0	0	0	0	1			
12:45 to 13:00	0	0	0	0	0	37	0	0	0	37	3	0	0	0	3	0	1	0	0	0	1	0	0	0	1	0	0	0	0	0	0	0	0	1	0	0	0	1		
Total	0	0	0	0	0	351	1	6	0	358	22	0	0	0	22	1	0	0	0	1	18	0	0	0	18	0	0	0	0	1	0	0	4	6	4	1	0	0		

Job No. : N2294
 Client : Cardno
 Suburb : Narellan
 Location : 2. Queen St / Hume St

Day/Date : Sat, 2nd Apr 2016
 Weather : Fine
 Description : Classified Intersection Count
 : Hourly Summary




Approach	Queen St															Hume St																								
Direction	Direction 1 (Left Turn)					Direction 2 (Through)					Direction 3 (Right Turn)					Direction 3U (U Turn)					Direction 4 (Left Turn)					Direction 5 (Through)					Direction 6 (Right Turn)					Direction 6U (U Turn)				
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total					
11:00 to 12:00	1	0	0	0	1	125	1	3	0	129	0	0	0	0	0	0	0	0	0	0	11	0	0	0	11	1	0	0	0	1	27	0	0	0	27	0	0	0	0	0
11:15 to 12:15	1	0	0	0	1	124	1	3	0	128	0	0	0	0	0	0	0	0	0	0	13	0	0	0	13	1	0	0	0	1	27	0	0	0	27	0	0	0	0	0
11:30 to 12:30	1	0	0	0	1	114	1	3	0	118	0	0	0	0	0	0	0	0	0	0	14	0	0	0	14	0	0	0	0	0	24	0	0	0	24	0	0	0	0	0
11:45 to 12:45	1	0	0	0	1	99	0	3	0	102	0	0	0	0	0	0	0	0	0	0	14	0	0	0	14	0	0	0	0	0	22	0	0	0	22	0	0	0	0	0
12:00 to 13:00	0	0	0	0	0	89	1	4	0	94	0	0	0	0	0	0	0	0	0	0	14	0	0	0	14	0	0	0	0	0	20	0	0	0	20	0	0	0	0	0
Total	1	0	0	0	1	214	2	7	0	223	0	0	0	0	0	0	0	0	0	0	25	0	0	0	25	1	0	0	0	1	47	0	0	0	47	0	0	0	0	0

Approach	Queen St																				Hume St																				Crossing Pedestrians							
Direction	Direction 7 (Left Turn)					Direction 8 (Through)					Direction 9 (Right Turn)					Direction 9U (U Turn)					Direction 10 (Left Turn)					Direction 11 (Through)					Direction 12 (Right Turn)					Direction 12U (U Turn)												
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	A	B	C	D	E	F	G	H	Total				
11:00 to 12:00	0	0	0	0	0	184	0	3	0	187	8	0	0	0	8	0	0	0	0	0	10	0	0	0	10	0	1	0	0	0	1	0	0	0	0	1	0	3	4	2	0	0	0	10				
11:15 to 12:15	0	0	0	0	0	191	0	3	0	194	8	0	0	0	8	0	0	0	0	0	5	0	0	0	5	0	1	0	0	0	1	0	0	0	0	1	0	1	1	4	0	0	0	7				
11:30 to 12:30	0	0	0	0	0	188	1	3	0	192	12	0	0	0	12	0	0	0	0	0	4	0	0	0	4	0	1	0	0	0	1	0	0	0	0	1	0	1	3	2	0	0	0	7				
11:45 to 12:45	0	0	0	0	0	178	1	3	0	182	12	0	0	0	12	1	0	0	0	1	8	0	0	0	8	0	0	0	0	0	0	0	0	0	0	1	0	1	2	2	0	0	0	6				
12:00 to 13:00	0	0	0	0	0	167	1	3	0	171	14	0	0	0	14	1	0	0	0	1	8	0	0	0	8	0	0	0	0	0	0	0	0	0	0	0	0	1	2	2	1	0	0	6				
Total	0	0	0	0	0	351	1	6	0	358	22	0	0	0	22	1	0	0	0	1	18	0	0	0	18	0	1	0	0	0	1	0	0	0	1	0	4	6	4	1	0	0	16					

Job No. : N2294
 Client : Cardno
 Suburb : Narellan
 Location : 1. Queen St / Elyard St

Day/Date : Sat, 2nd Apr 2016
 Weather : Fine
 Description : Classified Intersection Count
 : Peak Hour Summary




Approach	Queen St					Elyard St					Queen St					Elyard St					Grand Total
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	
11:15 to 12:15	148	1	4	0	153	225	1	3	0	229	428	2	1	0	431	406	3	3	0	412	1,225

Approach	Queen St					Elyard St					Queen St					Elyard St					Grand Total
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	
11:00 to 12:00	158	1	3	0	162	194	1	3	0	198	416	3	1	0	420	420	3	2	0	425	1,205
11:15 to 12:15	148	1	4	0	153	225	1	3	0	229	428	2	1	0	431	406	3	3	0	412	1,225
11:30 to 12:30	127	0	3	0	130	237	3	3	0	243	421	1	1	0	423	397	3	3	0	403	1,199
11:45 to 12:45	116	1	4	0	121	225	2	3	0	230	404	2	1	0	407	363	3	2	0	368	1,126
12:00 to 13:00	105	2	4	0	111	228	2	2	0	232	398	3	1	0	402	335	3	3	0	341	1,086
Total	263	3	7	0	273	422	3	5	0	430	814	6	2	0	822	755	6	5	0	766	2,291

Job No. : N2294
 Client : Cardno
 Suburb : Narellan
 Location : 2. Queen St / Hume St

Day/Date : Sat, 2nd Apr 2016
 Weather : Fine
 Description : Classified Intersection Count
 : Peak Hour Summary



Approach	Queen St					Hume St					Queen St					Hume St					Grand Total
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	
11:15 to 12:15	125	1	3	0	129	41	0	0	0	41	199	0	3	0	202	6	0	0	0	6	378


Approach	Queen St					Hume St					Queen St					Hume St					Grand Total
Time Period	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	Cars	Trucks	Buses	Cyclists	Total	
11:00 to 12:00	126	1	3	0	130	39	0	0	0	39	192	0	3	0	195	11	0	0	0	11	375
11:15 to 12:15	125	1	3	0	129	41	0	0	0	41	199	0	3	0	202	6	0	0	0	6	378
11:30 to 12:30	115	1	3	0	119	38	0	0	0	38	200	1	3	0	204	5	0	0	0	5	366
11:45 to 12:45	100	0	3	0	103	36	0	0	0	36	191	1	3	0	195	8	0	0	0	8	342
12:00 to 13:00	89	1	4	0	94	34	0	0	0	34	182	1	3	0	186	8	0	0	0	8	322
Total	215	2	7	0	224	73	0	0	0	73	374	1	6	0	381	19	0	0	0	19	697

Day/Date : Sat, 2nd Apr 2016
Weather : Fine
Description : Classified Intersection Count
: Intersection Diagram



Hour Starting: 

Vehicle Type: 




Job No. : N2294
 Client : Cardno
 Suburb : Narellan
 Location : 2. Queen St / Hume St

Day/Date : Sat, 2nd Apr 2016
 Weather : Fine
 Description : Classified Intersection Count
 : Intersection Diagram



Hour Starting Vehicle Type

Total All Vehicles



Narellan Medical Centre

APPENDIX

B

SIDRA MOVEMENT SUMMARIES

INTERSECTION SUMMARY



Site: Base AM Queen St / Elyard St

Base AM Queen St / Elyard St 0830 - 0930
Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	45.5km/h	45.7 km/h	
Travel Distance (Total)	1131.5veh-km/h	2008.1 pers-km/h	
Travel Time (Total)	24.9veh-h/h	43.9pers-h/h	
Demand Flows (Total)	1103veh/h	1957pers/h	
Percent Heavy Vehicles (Demand)	3.4%		
Degree of Saturation	0.457		
Practical Spare Capacity	85.9%		
Effective Intersection Capacity	2413veh/h		
Control Delay (Total)	1.74veh-h/h	3.14pers-h/h	
Control Delay (Average)	5.7sec	5.8sec	
Control Delay (Worst Lane)	6.3sec		
Control Delay (Worst Movement)	11.0sec	11.0sec	
Geometric Delay (Average)	4.1sec		
Stop-Line Delay (Average)	1.6sec		
Idling Time (Average)	0.0sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	3.2veh		
95% Back of Queue - Distance (Worst Lane)	23.2m		
Queue Storage Ratio (Worst Lane)	0.02		
Total Effective Stops	644veh/h	1139pers/h	
Effective Stop Rate	0.58per veh	0.58per pers	
Proportion Queued	0.50	0.49	
Performance Index	47.2	47.2	
Cost (Total)	856.18\$/h	856.18\$/h	
Fuel Consumption (Total)	93.6L/h		
Carbon Dioxide (Total)	222.0kg/h		
Hydrocarbons (Total)	0.018kg/h		
Carbon Monoxide (Total)	0.181kg/h		
NOx (Total)	0.233kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base AM Queen St / Hume St

Base AM Queen St / Hume St 0830 - 0930

Giveway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	49.3km/h	49.6km/h	
Travel Distance (Total)	332.4veh-km/h	660.7pers-km/h	
Travel Time (Total)	6.7veh-h/h	13.3pers-h/h	
Demand Flows (Total)	329veh/h	654pers/h	
Percent Heavy Vehicles (Demand)	2.7%		
Degree of Saturation	0.101		
Practical Spare Capacity	873.5%		
Effective Intersection Capacity	3268veh/h		
Control Delay (Total)	0.07veh-h/h	0.09pers-h/h	
Control Delay (Average)	0.8sec	0.5sec	
Control Delay (Worst Lane)	5.8sec		
Control Delay (Worst Movement)	6.4sec	6.4sec	
Geometric Delay (Average)	0.6sec		
Stop-Line Delay (Average)	0.2sec		
Idling Time (Average)	0.0sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.1veh		
95% Back of Queue - Distance (Worst Lane)	0.8m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	25veh/h	32pers/h	
Effective Stop Rate	0.08per veh	0.05per pers	
Proportion Queued	0.04	0.03	
Performance Index	7.0	7.0	
Cost (Total)	212.14\$/h	212.14\$/h	
Fuel Consumption (Total)	21.5L/h		
Carbon Dioxide (Total)	50.8kg/h		
Hydrocarbons (Total)	0.004kg/h		
Carbon Monoxide (Total)	0.040kg/h		
NOx (Total)	0.026kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base PM Queen St / Elyard St

Base PM Queen St / Elyard St 1630-1730
Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	45.7km/h	45.9km/h	
Travel Distance (Total)	1346.0veh-km/h	2266.1 pers-km/h	
Travel Time (Total)	29.5veh-h/h	49.4pers-h/h	
Demand Flows (Total)	1309veh/h	2204pers/h	
Percent Heavy Vehicles (Demand)	2.5%		
Degree of Saturation	0.435		
Practical Spare Capacity	95.3%		
Effective Intersection Capacity	3007veh/h		
Control Delay (Total)	2.42veh-h/h	4.10pers-h/h	
Control Delay (Average)	6.7sec	6.7sec	
Control Delay (Worst Lane)	8.0sec		
Control Delay (Worst Movement)	12.2sec	12.2sec	
Geometric Delay (Average)	4.5sec		
Stop-Line Delay (Average)	2.1sec		
Idling Time (Average)	0.1sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	3.0veh		
95% Back of Queue - Distance (Worst Lane)	21.4m		
Queue Storage Ratio (Worst Lane)	0.02		
Total Effective Stops	846veh/h	1425pers/h	
Effective Stop Rate	0.65per veh	0.65per pers	
Proportion Queued	0.57	0.58	
Performance Index	59.0	59.0	
Cost (Total)	999.98\$/h	999.98\$/h	
Fuel Consumption (Total)	111.4L/h		
Carbon Dioxide (Total)	263.3kg/h		
Hydrocarbons (Total)	0.022kg/h		
Carbon Monoxide (Total)	0.221kg/h		
NOx (Total)	0.229kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base PM Queen St / Hume St

Base PM Queen St / Hume St 1600 - 1700
Giveway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	48.6km/h	49.1 km/h	
Travel Distance (Total)	448.7veh-km/h	858.4pers-km/h	
Travel Time (Total)	9.2veh-h/h	17.5pers-h/h	
Demand Flows (Total)	444veh/h	850pers/h	
Percent Heavy Vehicles (Demand)	2.7%		
Degree of Saturation	0.122		
Practical Spare Capacity	628.6%		
Effective Intersection Capacity	3650veh/h		
Control Delay (Total)	0.20veh-h/h	0.25pers-h/h	
Control Delay (Average)	1.7sec	1.0sec	
Control Delay (Worst Lane)	6.3sec		
Control Delay (Worst Movement)	6.9sec	6.9sec	
Geometric Delay (Average)	1.3sec		
Stop-Line Delay (Average)	0.4sec		
Idling Time (Average)	0.1sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.4veh		
95% Back of Queue - Distance (Worst Lane)	2.7m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	74veh/h	97pers/h	
Effective Stop Rate	0.17per veh	0.11per pers	
Proportion Queued	0.10	0.07	
Performance Index	10.2	10.2	
Cost (Total)	287.90\$/h	287.90\$/h	
Fuel Consumption (Total)	30.2L/h		
Carbon Dioxide (Total)	71.5kg/h		
Hydrocarbons (Total)	0.006kg/h		
Carbon Monoxide (Total)	0.056kg/h		
NOx (Total)	0.039kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base + Dev AM Queen St / Elyard St

Base + Development AM Queen St / Elyard St 0830 - 0930
Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	45.4km/h	45.6km/h	
Travel Distance (Total)	1294.0veh-km/h	2203.2pers-km/h	
Travel Time (Total)	28.5veh-h/h	48.3pers-h/h	
Demand Flows (Total)	1261veh/h	2147pers/h	
Percent Heavy Vehicles (Demand)	3.0%		
Degree of Saturation	0.519		
Practical Spare Capacity	63.8%		
Effective Intersection Capacity	2430veh/h		
Control Delay (Total)	2.12veh-h/h	3.64pers-h/h	
Control Delay (Average)	6.1sec	6.1sec	
Control Delay (Worst Lane)	6.8sec		
Control Delay (Worst Movement)	11.5sec	11.5sec	
Geometric Delay (Average)	4.2sec		
Stop-Line Delay (Average)	1.8sec		
Idling Time (Average)	0.1sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	4.0veh		
95% Back of Queue - Distance (Worst Lane)	28.2m		
Queue Storage Ratio (Worst Lane)	0.02		
Total Effective Stops	773veh/h	1314pers/h	
Effective Stop Rate	0.61per veh	0.61per pers	
Proportion Queued	0.54	0.54	
Performance Index	55.4	55.4	
Cost (Total)	956.60\$/h	956.60\$/h	
Fuel Consumption (Total)	106.7L/h		
Carbon Dioxide (Total)	252.6kg/h		
Hydrocarbons (Total)	0.021kg/h		
Carbon Monoxide (Total)	0.206kg/h		
NOx (Total)	0.242kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base + Dev PM Queen St / Elyard St

Base + Development PM Queen St / Elyard St 1630-1730
Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	45.5km/h	45.7 km/h	
Travel Distance (Total)	1482.4veh-km/h	2429.5 pers-km/h	
Travel Time (Total)	32.6veh-h/h	53.2pers-h/h	
Demand Flows (Total)	1442veh/h	2364pers/h	
Percent Heavy Vehicles (Demand)	2.3%		
Degree of Saturation	0.464		
Practical Spare Capacity	83.0%		
Effective Intersection Capacity	3105veh/h		
Control Delay (Total)	2.84veh-h/h	4.65pers-h/h	
Control Delay (Average)	7.1sec	7.1 sec	
Control Delay (Worst Lane)	7.9sec		
Control Delay (Worst Movement)	12.7sec	12.7sec	
Geometric Delay (Average)	4.6sec		
Stop-Line Delay (Average)	2.5sec		
Idling Time (Average)	0.2sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	3.3veh		
95% Back of Queue - Distance (Worst Lane)	23.2m		
Queue Storage Ratio (Worst Lane)	0.02		
Total Effective Stops	987veh/h	1617pers/h	
Effective Stop Rate	0.68per veh	0.68per pers	
Proportion Queued	0.62	0.62	
Performance Index	66.8	66.8	
Cost (Total)	1086.70\$/h	1086.70\$/h	
Fuel Consumption (Total)	122.5L/h		
Carbon Dioxide (Total)	289.5kg/h		
Hydrocarbons (Total)	0.023kg/h		
Carbon Monoxide (Total)	0.242kg/h		
NOx (Total)	0.237kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base + Dev AM Queen St / Hume St

Base + Development AM Queen St / Hume St 0830 - 0930
 Giveaway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	49.3km/h	49.5km/h	
Travel Distance (Total)	356.7veh-km/h	689.8pers-km/h	
Travel Time (Total)	7.2veh-h/h	13.9pers-h/h	
Demand Flows (Total)	353veh/h	683pers/h	
Percent Heavy Vehicles (Demand)	2.5%		
Degree of Saturation	0.109		
Practical Spare Capacity	799.3%		
Effective Intersection Capacity	3239veh/h		
Control Delay (Total)	0.08veh-h/h	0.09pers-h/h	
Control Delay (Average)	0.8sec	0.5sec	
Control Delay (Worst Lane)	5.9sec		
Control Delay (Worst Movement)	6.5sec	6.5sec	
Geometric Delay (Average)	0.6sec		
Stop-Line Delay (Average)	0.2sec		
Idling Time (Average)	0.0sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.1veh		
95% Back of Queue - Distance (Worst Lane)	0.8m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	28veh/h	36pers/h	
Effective Stop Rate	0.08per veh	0.05per pers	
Proportion Queued	0.04	0.03	
Performance Index	7.5	7.5	
Cost (Total)	222.51\$/h	222.51\$/h	
Fuel Consumption (Total)	22.9L/h		
Carbon Dioxide (Total)	54.3kg/h		
Hydrocarbons (Total)	0.004kg/h		
Carbon Monoxide (Total)	0.042kg/h		
NOx (Total)	0.027kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base + Dev PM Queen St / Hume St

Base + Development PM Queen St / Hume St 1600 - 1700

Giveaway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	48.7km/h	49.1 km/h	
Travel Distance (Total)	466.8veh-km/h	880.2pers-km/h	
Travel Time (Total)	9.6veh-h/h	17.9pers-h/h	
Demand Flows (Total)	462veh/h	871pers/h	
Percent Heavy Vehicles (Demand)	2.6%		
Degree of Saturation	0.127		
Practical Spare Capacity	614.9%		
Effective Intersection Capacity	3628veh/h		
Control Delay (Total)	0.21veh-h/h	0.25pers-h/h	
Control Delay (Average)	1.6sec	1.0sec	
Control Delay (Worst Lane)	6.4sec		
Control Delay (Worst Movement)	7.0sec	7.0sec	
Geometric Delay (Average)	1.2sec		
Stop-Line Delay (Average)	0.4sec		
Idling Time (Average)	0.1sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.4veh		
95% Back of Queue - Distance (Worst Lane)	2.8m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	75veh/h	97pers/h	
Effective Stop Rate	0.16per veh	0.11per pers	
Proportion Queued	0.10	0.07	
Performance Index	10.6	10.6	
Cost (Total)	295.22\$/h	295.22\$/h	
Fuel Consumption (Total)	31.3L/h		
Carbon Dioxide (Total)	74.0kg/h		
Hydrocarbons (Total)	0.006kg/h		
Carbon Monoxide (Total)	0.058kg/h		
NOx (Total)	0.039kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base + 2% Growth AM Queen St / Elyard St

Base + 2% Growth (2017) AM Queen St / Elyard St 0830 - 0930
Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	45.4km/h	45.6km/h	
Travel Distance (Total)	1176.8veh-km/h	2239.9pers-km/h	
Travel Time (Total)	25.9veh-h/h	49.1pers-h/h	
Demand Flows (Total)	1147veh/h	2183pers/h	
Percent Heavy Vehicles (Demand)	4.4%		
Degree of Saturation	0.481		
Practical Spare Capacity	76.9%		
Effective Intersection Capacity	2387veh/h		
Control Delay (Total)	1.86veh-h/h	3.63pers-h/h	
Control Delay (Average)	5.9sec	6.0sec	
Control Delay (Worst Lane)	6.5sec		
Control Delay (Worst Movement)	11.1sec	11.1sec	
Geometric Delay (Average)	4.1sec		
Stop-Line Delay (Average)	1.8sec		
Idling Time (Average)	0.1sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	3.5veh		
95% Back of Queue - Distance (Worst Lane)	25.0m		
Queue Storage Ratio (Worst Lane)	0.02		
Total Effective Stops	687veh/h	1302pers/h	
Effective Stop Rate	0.60per veh	0.60per pers	
Proportion Queued	0.52	0.52	
Performance Index	49.9	49.9	
Cost (Total)	954.32\$/h	954.32\$/h	
Fuel Consumption (Total)	100.6L/h		
Carbon Dioxide (Total)	239.1kg/h		
Hydrocarbons (Total)	0.021kg/h		
Carbon Monoxide (Total)	0.199kg/h		
NOx (Total)	0.298kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base + 2% Growth PM Queen St / Elyard St

Base + 2% Growth (2017) PM Queen St / Elyard St 1630-1730
Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	45.6km/h	45.9km/h	
Travel Distance (Total)	1393.4veh-km/h	2471.1 pers-km/h	
Travel Time (Total)	30.5veh-h/h	53.9pers-h/h	
Demand Flows (Total)	1355veh/h	2404pers/h	
Percent Heavy Vehicles (Demand)	3.2%		
Degree of Saturation	0.456		
Practical Spare Capacity	86.5%		
Effective Intersection Capacity	2974veh/h		
Control Delay (Total)	2.59veh-h/h	4.66pers-h/h	
Control Delay (Average)	6.9sec	7.0sec	
Control Delay (Worst Lane)	8.2sec		
Control Delay (Worst Movement)	12.7sec	12.7sec	
Geometric Delay (Average)	4.6sec		
Stop-Line Delay (Average)	2.3sec		
Idling Time (Average)	0.2sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	3.2veh		
95% Back of Queue - Distance (Worst Lane)	22.9m		
Queue Storage Ratio (Worst Lane)	0.02		
Total Effective Stops	899veh/h	1597pers/h	
Effective Stop Rate	0.66per veh	0.66per pers	
Proportion Queued	0.60	0.60	
Performance Index	62.3	62.3	
Cost (Total)	1092.83\$/h	1092.83\$/h	
Fuel Consumption (Total)	118.9L/h		
Carbon Dioxide (Total)	281.7kg/h		
Hydrocarbons (Total)	0.024kg/h		
Carbon Monoxide (Total)	0.240kg/h		
NOx (Total)	0.300kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base + 2% Growth AM Queen St / Hume St

Base + 2% Growth (2017) AM Queen St / Hume St 0830 - 0930
 Giveaway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	49.3km/h	49.6km/h	
Travel Distance (Total)	343.5veh-km/h	732.2pers-km/h	
Travel Time (Total)	7.0veh-h/h	14.8pers-h/h	
Demand Flows (Total)	340veh/h	725pers/h	
Percent Heavy Vehicles (Demand)	3.2%		
Degree of Saturation	0.104		
Practical Spare Capacity	841.4%		
Effective Intersection Capacity	3266veh/h		
Control Delay (Total)	0.08veh-h/h	0.09pers-h/h	
Control Delay (Average)	0.8sec	0.5sec	
Control Delay (Worst Lane)	6.0sec		
Control Delay (Worst Movement)	6.5sec	6.5sec	
Geometric Delay (Average)	0.7sec		
Stop-Line Delay (Average)	0.2sec		
Idling Time (Average)	0.0sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.1veh		
95% Back of Queue - Distance (Worst Lane)	0.7m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	27veh/h	36pers/h	
Effective Stop Rate	0.08per veh	0.05per pers	
Proportion Queued	0.04	0.03	
Performance Index	7.3	7.3	
Cost (Total)	233.82\$/h	233.82\$/h	
Fuel Consumption (Total)	22.5L/h		
Carbon Dioxide (Total)	53.4kg/h		
Hydrocarbons (Total)	0.004kg/h		
Carbon Monoxide (Total)	0.042kg/h		
NOx (Total)	0.030kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Base + 2% Growth PM Queen St / Hume St

Base + 2% Growth (2017) PM Queen St / Hume St 1600 - 1700
 Giveaway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	48.6km/h	49.1 km/h	
Travel Distance (Total)	462.8veh-km/h	933.6 pers-km/h	
Travel Time (Total)	9.5veh-h/h	19.0 pers-h/h	
Demand Flows (Total)	458veh/h	924 pers/h	
Percent Heavy Vehicles (Demand)	3.3%		
Degree of Saturation	0.127		
Practical Spare Capacity	617.3%		
Effective Intersection Capacity	3620veh/h		
Control Delay (Total)	0.21 veh-h/h	0.26 pers-h/h	
Control Delay (Average)	1.7sec	1.0sec	
Control Delay (Worst Lane)	6.5sec		
Control Delay (Worst Movement)	7.0sec	7.0sec	
Geometric Delay (Average)	1.3sec		
Stop-Line Delay (Average)	0.4sec		
Idling Time (Average)	0.1sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.4veh		
95% Back of Queue - Distance (Worst Lane)	2.8m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	77veh/h	102 pers/h	
Effective Stop Rate	0.17 per veh	0.11 per pers	
Proportion Queued	0.10	0.07	
Performance Index	10.5	10.5	
Cost (Total)	311.33\$/h	311.33\$/h	
Fuel Consumption (Total)	31.7L/h		
Carbon Dioxide (Total)	75.1kg/h		
Hydrocarbons (Total)	0.006kg/h		
Carbon Monoxide (Total)	0.059kg/h		
NOx (Total)	0.047kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Future Baseline Scenario (2017) AM Queen St / Elyard St

Future Baseline + 2% Growth (2017) + Development AM Queen St / Elyard St 0830 - 0930 Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	45.3km/h	45.5km/h	
Travel Distance (Total)	1336.3veh-km/h	2431.3pers-km/h	
Travel Time (Total)	29.5veh-h/h	53.5pers-h/h	
Demand Flows (Total)	1302veh/h	2369pers/h	
Percent Heavy Vehicles (Demand)	3.8%		
Degree of Saturation	0.553		
Practical Spare Capacity	53.7%		
Effective Intersection Capacity	2355veh/h		
Control Delay (Total)	2.29veh-h/h	4.21pers-h/h	
Control Delay (Average)	6.3sec	6.4sec	
Control Delay (Worst Lane)	7.2sec		
Control Delay (Worst Movement)	11.7sec	11.7sec	
Geometric Delay (Average)	4.2sec		
Stop-Line Delay (Average)	2.1sec		
Idling Time (Average)	0.1sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	4.3veh		
95% Back of Queue - Distance (Worst Lane)	31.2m		
Queue Storage Ratio (Worst Lane)	0.03		
Total Effective Stops	827veh/h	1500pers/h	
Effective Stop Rate	0.64per veh	0.63per pers	
Proportion Queued	0.58	0.57	
Performance Index	59.0	59.0	
Cost (Total)	1055.86\$/h	1055.86\$/h	
Fuel Consumption (Total)	113.6L/h		
Carbon Dioxide (Total)	269.6kg/h		
Hydrocarbons (Total)	0.023kg/h		
Carbon Monoxide (Total)	0.224kg/h		
NOx (Total)	0.308kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Future Baseline Scenario (2017) AM Queen St / Hume St

Future Baseline + 2% Growth (2017) + Development AM Queen St / Hume St 0830 - 0930
 Giveway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	49.3km/h	49.6km/h	
Travel Distance (Total)	363.7veh-km/h	756.4pers-km/h	
Travel Time (Total)	7.4veh-h/h	15.3pers-h/h	
Demand Flows (Total)	360veh/h	749pers/h	
Percent Heavy Vehicles (Demand)	3.1%		
Degree of Saturation	0.110		
Practical Spare Capacity	788.8%		
Effective Intersection Capacity	3265veh/h		
Control Delay (Total)	0.08veh-h/h	0.10pers-h/h	
Control Delay (Average)	0.8sec	0.5sec	
Control Delay (Worst Lane)	6.1sec		
Control Delay (Worst Movement)	6.6sec	6.6sec	
Geometric Delay (Average)	0.6sec		
Stop-Line Delay (Average)	0.2sec		
Idling Time (Average)	0.0sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.1veh		
95% Back of Queue - Distance (Worst Lane)	0.8m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	27veh/h	36pers/h	
Effective Stop Rate	0.08per veh	0.05per pers	
Proportion Queued	0.04	0.03	
Performance Index	7.7	7.7	
Cost (Total)	241.85\$/h	241.85\$/h	
Fuel Consumption (Total)	23.7L/h		
Carbon Dioxide (Total)	56.1kg/h		
Hydrocarbons (Total)	0.004kg/h		
Carbon Monoxide (Total)	0.044kg/h		
NOx (Total)	0.031kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Future Baseline Scenario (2017) PM Queen St / Elyard St

Future Baseline + 2% Growth (2017) + Development PM Queen St / Elyard St 1630-1730 Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	45.4km/h	45.7km/h	
Travel Distance (Total)	1528.8veh-km/h	2633.2pers-km/h	
Travel Time (Total)	33.6veh-h/h	57.7pers-h/h	
Demand Flows (Total)	1487veh/h	2562pers/h	
Percent Heavy Vehicles (Demand)	3.0%		
Degree of Saturation	0.485		
Practical Spare Capacity	75.1%		
Effective Intersection Capacity	3064veh/h		
Control Delay (Total)	3.02veh-h/h	5.24pers-h/h	
Control Delay (Average)	7.3sec	7.4sec	
Control Delay (Worst Lane)	8.1sec		
Control Delay (Worst Movement)	13.2sec	13.2sec	
Geometric Delay (Average)	4.6sec		
Stop-Line Delay (Average)	2.7sec		
Idling Time (Average)	0.3sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	3.5veh		
95% Back of Queue - Distance (Worst Lane)	24.8m		
Queue Storage Ratio (Worst Lane)	0.02		
Total Effective Stops	1044veh/h	1799pers/h	
Effective Stop Rate	0.70per veh	0.70per pers	
Proportion Queued	0.65	0.65	
Performance Index	70.4	70.4	
Cost (Total)	1180.11\$/h	1180.11\$/h	
Fuel Consumption (Total)	130.1L/h		
Carbon Dioxide (Total)	307.9kg/h		
Hydrocarbons (Total)	0.026kg/h		
Carbon Monoxide (Total)	0.261kg/h		
NOx (Total)	0.309kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Future Baseline Scenario (2017) PM Queen St / Hume St

Future Baseline + 2% Growth (2017) + Development PM Queen St / Hume St 1600 - 1700
Giveaway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	48.6km/h	49.1 km/h	
Travel Distance (Total)	480.0veh-km/h	954.2pers-km/h	
Travel Time (Total)	9.9veh-h/h	19.4pers-h/h	
Demand Flows (Total)	475veh/h	944pers/h	
Percent Heavy Vehicles (Demand)	3.2%		
Degree of Saturation	0.132		
Practical Spare Capacity	604.5%		
Effective Intersection Capacity	3606veh/h		
Control Delay (Total)	0.22veh-h/h	0.26pers-h/h	
Control Delay (Average)	1.6sec	1.0sec	
Control Delay (Worst Lane)	6.6sec		
Control Delay (Worst Movement)	7.1sec	7.1sec	
Geometric Delay (Average)	1.2sec		
Stop-Line Delay (Average)	0.4sec		
Idling Time (Average)	0.1sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.4veh		
95% Back of Queue - Distance (Worst Lane)	2.8m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	78veh/h	103pers/h	
Effective Stop Rate	0.16per veh	0.11per pers	
Proportion Queued	0.10	0.07	
Performance Index	10.9	10.9	
Cost (Total)	318.24\$/h	318.24\$/h	
Fuel Consumption (Total)	32.7L/h		
Carbon Dioxide (Total)	77.4kg/h		
Hydrocarbons (Total)	0.006kg/h		
Carbon Monoxide (Total)	0.061kg/h		
NOx (Total)	0.048kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Future + 10 years (2027) Scenario AM Queen St / Elyard St

Future Baseline + 10 Years 2% Growth (2027) + Development Trip AM Queen St / Elyard St 0830 - 0930 Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	44.5km/h	44.7 km/h	
Travel Distance (Total)	1606.2veh-km/h	2991.8 pers-km/h	
Travel Time (Total)	36.1veh-h/h	66.9pers-h/h	
Demand Flows (Total)	1565veh/h	2915pers/h	
Percent Heavy Vehicles (Demand)	4.2%		
Degree of Saturation	0.703		
Practical Spare Capacity	20.8%		
Effective Intersection Capacity	2225veh/h		
Control Delay (Total)	3.49veh-h/h	6.56pers-h/h	
Control Delay (Average)	8.0sec	8.1 sec	
Control Delay (Worst Lane)	9.5sec		
Control Delay (Worst Movement)	14.3sec	14.3sec	
Geometric Delay (Average)	4.2sec		
Stop-Line Delay (Average)	3.8sec		
Idling Time (Average)	0.6sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	8.3veh		
95% Back of Queue - Distance (Worst Lane)	59.7m		
Queue Storage Ratio (Worst Lane)	0.05		
Total Effective Stops	1183veh/h	2186pers/h	
Effective Stop Rate	0.76per veh	0.75per pers	
Proportion Queued	0.70	0.69	
Performance Index	84.7	84.7	
Cost (Total)	1336.76\$/h	1336.76\$/h	
Fuel Consumption (Total)	140.4L/h		
Carbon Dioxide (Total)	333.3kg/h		
Hydrocarbons (Total)	0.029kg/h		
Carbon Monoxide (Total)	0.280kg/h		
NOx (Total)	0.405kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Future + 10 years (2027) Scenario PM Queen St / Elyard St

Future Baseline + 10 Years 2% Growth (2027) + Development Trip PM Queen St / Elyard St 1630-1730 Roundabout

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	44.4km/h	44.6km/h	
Travel Distance (Total)	1853.7veh-km/h	3230.3pers-km/h	
Travel Time (Total)	41.7veh-h/h	72.4pers-h/h	
Demand Flows (Total)	1803veh/h	3143pers/h	
Percent Heavy Vehicles (Demand)	3.2%		
Degree of Saturation	0.637		
Practical Spare Capacity	33.5%		
Effective Intersection Capacity	2831veh/h		
Control Delay (Total)	4.75veh-h/h	8.32pers-h/h	
Control Delay (Average)	9.5sec	9.5sec	
Control Delay (Worst Lane)	11.8sec		
Control Delay (Worst Movement)	17.5sec	17.5sec	
Geometric Delay (Average)	4.6sec		
Stop-Line Delay (Average)	4.9sec		
Idling Time (Average)	1.1sec		
Intersection Level of Service (LOS)	LOS A		
95% Back of Queue - Vehicles (Worst Lane)	6.4veh		
95% Back of Queue - Distance (Worst Lane)	45.6m		
Queue Storage Ratio (Worst Lane)	0.04		
Total Effective Stops	1522veh/h	2654pers/h	
Effective Stop Rate	0.84per veh	0.84per pers	
Proportion Queued	0.78	0.78	
Performance Index	104.3	104.3	
Cost (Total)	1509.13\$/h	1509.13\$/h	
Fuel Consumption (Total)	162.8L/h		
Carbon Dioxide (Total)	385.7kg/h		
Hydrocarbons (Total)	0.033kg/h		
Carbon Monoxide (Total)	0.331kg/h		
NOx (Total)	0.419kg/h		

Level of Service (LOS) Method: Delay (RTA NSW).

Intersection LOS value for Vehicles is based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Future + 10 years (2027) Scenario AM Queen St / Hume St

Future Baseline + 10 Year 2% Growth (2027) + Development Trip AM Queen St / Hume St 0830 - 0930
Giveaway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	49.3km/h	49.5km/h	
Travel Distance (Total)	444.6veh-km/h	969.8pers-km/h	
Travel Time (Total)	9.0veh-h/h	19.6pers-h/h	
Demand Flows (Total)	440veh/h	960pers/h	
Percent Heavy Vehicles (Demand)	3.4%		
Degree of Saturation	0.134		
Practical Spare Capacity	631.2%		
Effective Intersection Capacity	3283veh/h		
Control Delay (Total)	0.11veh-h/h	0.13pers-h/h	
Control Delay (Average)	0.9sec	0.5sec	
Control Delay (Worst Lane)	6.5sec		
Control Delay (Worst Movement)	7.1sec	7.1sec	
Geometric Delay (Average)	0.7sec		
Stop-Line Delay (Average)	0.2sec		
Idling Time (Average)	0.1sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.1veh		
95% Back of Queue - Distance (Worst Lane)	1.0m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	36veh/h	49pers/h	
Effective Stop Rate	0.08per veh	0.05per pers	
Proportion Queued	0.05	0.03	
Performance Index	9.5	9.5	
Cost (Total)	309.31\$/h	309.31\$/h	
Fuel Consumption (Total)	29.3L/h		
Carbon Dioxide (Total)	69.5kg/h		
Hydrocarbons (Total)	0.006kg/h		
Carbon Monoxide (Total)	0.054kg/h		
NOx (Total)	0.041kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

INTERSECTION SUMMARY



Site: Future + 10 years (2027) Scenario PM Queen St / Hume St

Future Base + 10 Years 2% Growth (2027) + Development Trip PM Queen St / Hume St 1600 - 1700
 Giveaway / Yield (Two-Way)

Intersection Performance - Hourly Values			
Performance Measure	Vehicles	Persons	
Travel Speed (Average)	48.5km/h	49.0km/h	
Travel Distance (Total)	594.2veh-km/h	1207.5pers-km/h	
Travel Time (Total)	12.2veh-h/h	24.6pers-h/h	
Demand Flows (Total)	588veh/h	1195pers/h	
Percent Heavy Vehicles (Demand)	3.4%		
Degree of Saturation	0.161		
Practical Spare Capacity	418.5%		
Effective Intersection Capacity	3651veh/h		
Control Delay (Total)	0.29veh-h/h	0.36pers-h/h	
Control Delay (Average)	1.8sec	1.1sec	
Control Delay (Worst Lane)	7.2sec		
Control Delay (Worst Movement)	7.9sec	7.9sec	
Geometric Delay (Average)	1.2sec		
Stop-Line Delay (Average)	0.6sec		
Idling Time (Average)	0.2sec		
Intersection Level of Service (LOS)	NA		
95% Back of Queue - Vehicles (Worst Lane)	0.6veh		
95% Back of Queue - Distance (Worst Lane)	3.9m		
Queue Storage Ratio (Worst Lane)	0.00		
Total Effective Stops	103veh/h	136pers/h	
Effective Stop Rate	0.18per veh	0.11per pers	
Proportion Queued	0.12	0.08	
Performance Index	13.6	13.6	
Cost (Total)	402.88\$/h	402.88\$/h	
Fuel Consumption (Total)	40.8L/h		
Carbon Dioxide (Total)	96.8kg/h		
Hydrocarbons (Total)	0.008kg/h		
Carbon Monoxide (Total)	0.077kg/h		
NOx (Total)	0.064kg/h		

Level of Service (LOS) Method: Delay (HCM 2000).

NA: Intersection LOS for Vehicles is Not Applicable for two-way sign control since the average intersection delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

MOVEMENT SUMMARY



Site: Base AM Queen St / Elyard St

Base AM Queen St / Elyard St 0830 - 0930

Roundabout

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
4	L2	23	0.0	0.193	4.3	LOS A	1.1	7.6	0.40	0.55	45.8
5	T1	102	0.0	0.193	4.3	LOS A	1.1	7.6	0.40	0.55	46.7
6	R2	87	5.7	0.193	8.3	LOS A	1.1	7.6	0.40	0.55	46.7
6u	U	1	0.0	0.193	9.9	LOS A	1.1	7.6	0.40	0.55	50.3
Approach		213	2.3	0.193	6.0	LOS A	1.1	7.6	0.40	0.55	46.6
NorthEast: Elyard St											
7	L2	60	6.7	0.182	4.1	LOS A	1.0	7.5	0.37	0.52	46.0
8	T1	84	3.6	0.182	4.1	LOS A	1.0	7.5	0.37	0.52	46.9
9	R2	52	1.9	0.182	8.0	LOS A	1.0	7.5	0.37	0.52	46.9
9u	U	10	10.0	0.182	9.8	LOS A	1.0	7.5	0.37	0.52	47.6
Approach		206	4.4	0.182	5.4	LOS A	1.0	7.5	0.37	0.52	46.7
NorthWest: Queen St											
10	L2	79	13.9	0.207	5.6	LOS A	1.2	8.8	0.56	0.63	45.6
11	T1	72	0.0	0.207	5.3	LOS A	1.2	8.8	0.56	0.63	46.6
12	R2	39	2.6	0.207	9.3	LOS A	1.2	8.8	0.56	0.63	46.6
12u	U	1	0.0	0.207	11.0	LOS A	1.2	8.8	0.56	0.63	47.3
Approach		191	6.3	0.207	6.3	LOS A	1.2	8.8	0.56	0.63	46.2
SouthWest: Elyard St											
1	L2	233	0.9	0.457	5.0	LOS A	3.2	23.2	0.57	0.60	41.7
2	T1	219	4.6	0.457	5.2	LOS A	3.2	23.2	0.57	0.60	46.8
3	R2	35	0.0	0.457	9.0	LOS A	3.2	23.2	0.57	0.60	46.9
3u	U	6	0.0	0.457	10.7	LOS A	3.2	23.2	0.57	0.60	47.6
Approach		493	2.4	0.457	5.4	LOS A	3.2	23.2	0.57	0.60	44.3
All Vehicles		1103	3.4	0.457	5.7	LOS A	3.2	23.2	0.50	0.58	45.5

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY

▽ Site: Base AM Queen St / Hume St

Base AM Queen St / Hume St 0830 - 0930
 Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
1	L2	1	0.0	0.101	4.6	LOS A	0.0	0.0	0.00	0.00	49.5
2	T1	192	2.6	0.101	0.0	LOS A	0.0	0.0	0.00	0.00	50.0
Approach		193	2.6	0.101	0.0	NA	0.0	0.0	0.00	0.00	50.0
NorthEast: Hume St											
4	L2	5	0.0	0.033	4.8	LOS A	0.1	0.8	0.29	0.58	45.9
5	T1	5	0.0	0.033	4.3	LOS A	0.1	0.8	0.29	0.58	45.9
6	R2	20	0.0	0.033	6.4	LOS A	0.1	0.8	0.29	0.58	45.3
Approach		30	0.0	0.033	5.8	LOS A	0.1	0.8	0.29	0.58	45.5
NorthWest: Queen St											
8	T1	92	4.3	0.050	0.0	LOS A	0.0	0.1	0.02	0.01	49.9
9	R2	2	0.0	0.050	5.2	LOS A	0.0	0.1	0.02	0.01	48.9
Approach		94	4.3	0.050	0.1	NA	0.0	0.1	0.02	0.01	49.9
SouthWest: Hume St											
10	L2	11	0.0	0.009	5.1	LOS A	0.0	0.2	0.28	0.51	46.0
12	R2	1	0.0	0.009	6.0	LOS A	0.0	0.2	0.28	0.51	45.6
Approach		12	0.0	0.009	5.2	LOS A	0.0	0.2	0.28	0.51	45.9
All Vehicles		329	2.7	0.101	0.8	NA	0.1	0.8	0.04	0.08	49.3

Level of Service (LOS) Method: Delay (HCM 2000).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base PM Queen St / Elyard St

Base PM Queen St / Elyard St 1630-1730
Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
4	L2	31	0.0	0.202	6.1	LOS A	1.2	8.3	0.62	0.71	45.0
5	T1	66	0.0	0.202	6.2	LOS A	1.2	8.3	0.62	0.71	45.9
6	R2	74	6.8	0.202	10.3	LOS A	1.2	8.3	0.62	0.71	46.1
6u	U	1	0.0	0.202	11.8	LOS A	1.2	8.3	0.62	0.71	49.4
Approach		172	2.9	0.202	8.0	LOS A	1.2	8.3	0.62	0.71	45.8
NorthEast: Elyard St											
7	L2	93	6.5	0.383	6.3	LOS A	2.5	18.4	0.68	0.72	45.5
8	T1	178	1.7	0.383	6.2	LOS A	2.5	18.4	0.68	0.72	46.3
9	R2	52	1.9	0.383	10.2	LOS A	2.5	18.4	0.68	0.72	46.3
9u	U	16	12.5	0.383	12.2	LOS A	2.5	18.4	0.68	0.72	49.7
Approach		339	3.5	0.383	7.1	LOS A	2.5	18.4	0.68	0.72	46.3
NorthWest: Queen St											
10	L2	86	4.7	0.435	5.0	LOS A	3.0	21.4	0.55	0.64	45.4
11	T1	151	0.0	0.435	5.0	LOS A	3.0	21.4	0.55	0.64	46.2
12	R2	235	0.4	0.435	8.9	LOS A	3.0	21.4	0.55	0.64	46.2
12u	U	6	0.0	0.435	10.6	LOS A	3.0	21.4	0.55	0.64	49.7
Approach		478	1.0	0.435	7.0	LOS A	3.0	21.4	0.55	0.64	46.1
SouthWest: ElyardSt											
1	L2	174	0.0	0.296	4.5	LOS A	1.8	13.3	0.47	0.55	42.0
2	T1	118	8.5	0.296	4.7	LOS A	1.8	13.3	0.47	0.55	47.4
3	R2	24	4.2	0.296	8.6	LOS A	1.8	13.3	0.47	0.55	47.3
3u	U	4	0.0	0.296	10.2	LOS A	1.8	13.3	0.47	0.55	51.1
Approach		320	3.4	0.296	5.0	LOS A	1.8	13.3	0.47	0.55	44.4
All Vehicles		1309	2.5	0.435	6.7	LOS A	3.0	21.4	0.57	0.65	45.7

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base PM Queen St / Hume St

Base PM Queen St / Hume St 1600 - 1700

Giveaway / Yield (Two-Way)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen st											
1	L2	3	0.0	0.058	4.6	LOS A	0.0	0.0	0.00	0.02	49.4
2	T1	106	4.7	0.058	0.0	LOS A	0.0	0.0	0.00	0.02	49.9
Approach		109	4.6	0.058	0.1	NA	0.0	0.0	0.00	0.02	49.9
NorthEast: Hume st											
4	L2	27	0.0	0.110	5.3	LOS A	0.4	2.7	0.37	0.64	45.6
5	T1	5	0.0	0.110	4.7	LOS A	0.4	2.7	0.37	0.64	45.6
6	R2	66	0.0	0.110	6.9	LOS A	0.4	2.7	0.37	0.64	45.0
Approach		98	0.0	0.110	6.3	LOS A	0.4	2.7	0.37	0.64	45.2
NorthWest: Queen St											
8	T1	218	3.2	0.122	0.0	LOS A	0.1	0.6	0.03	0.03	49.8
9	R2	12	0.0	0.122	4.9	LOS A	0.1	0.6	0.03	0.03	48.8
Approach		230	3.0	0.122	0.3	NA	0.1	0.6	0.03	0.03	49.7
SouthWest: Hume St											
10	L2	6	0.0	0.005	4.8	LOS A	0.0	0.1	0.19	0.50	46.2
12	R2	1	0.0	0.005	6.4	LOS A	0.0	0.1	0.19	0.50	45.7
Approach		7	0.0	0.005	5.1	LOS A	0.0	0.1	0.19	0.50	46.1
All Vehicles		444	2.7	0.122	1.7	NA	0.4	2.7	0.10	0.17	48.6

Level of Service (LOS) Method: Delay (HCM 2000).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base + Dev AM Queen St / Elyard St

Base + Development AM Queen St / Elyard St 0830 - 0930
Roundabout

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
4	L2	73	0.0	0.242	4.3	LOS A	1.4	10.2	0.42	0.56	45.8
5	T1	102	0.0	0.242	4.3	LOS A	1.4	10.2	0.42	0.56	46.8
6	R2	100	5.0	0.242	8.3	LOS A	1.4	10.2	0.42	0.56	46.7
6u	U	1	0.0	0.242	10.0	LOS A	1.4	10.2	0.42	0.56	50.4
Approach		276	1.8	0.242	5.8	LOS A	1.4	10.2	0.42	0.56	46.5
NorthEast: Elyard St											
7	L2	80	5.0	0.209	4.5	LOS A	1.2	8.6	0.44	0.56	45.9
8	T1	84	3.6	0.209	4.5	LOS A	1.2	8.6	0.44	0.56	46.8
9	R2	52	1.9	0.209	8.4	LOS A	1.2	8.6	0.44	0.56	46.8
9u	U	10	10.0	0.209	10.3	LOS A	1.2	8.6	0.44	0.56	47.5
Approach		226	4.0	0.209	5.7	LOS A	1.2	8.6	0.44	0.56	46.5
NorthWest: Queen St											
10	L2	79	13.9	0.219	6.2	LOS A	1.3	9.6	0.62	0.68	45.3
11	T1	72	0.0	0.219	5.8	LOS A	1.3	9.6	0.62	0.68	46.3
12	R2	39	2.6	0.219	9.8	LOS A	1.3	9.6	0.62	0.68	46.3
12u	U	1	0.0	0.219	11.5	LOS A	1.3	9.6	0.62	0.68	47.0
Approach		191	6.3	0.219	6.8	LOS A	1.3	9.6	0.62	0.68	45.9
SouthWest: Elyard St											
1	L2	233	0.9	0.519	5.2	LOS A	4.0	28.2	0.62	0.64	41.4
2	T1	219	4.6	0.519	5.3	LOS A	4.0	28.2	0.62	0.64	46.5
3	R2	110	0.0	0.519	9.2	LOS A	4.0	28.2	0.62	0.64	46.5
3u	U	6	0.0	0.519	10.9	LOS A	4.0	28.2	0.62	0.64	47.2
Approach		568	2.1	0.519	6.1	LOS A	4.0	28.2	0.62	0.64	44.3
All Vehicles		1261	3.0	0.519	6.1	LOS A	4.0	28.2	0.54	0.61	45.4

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base + Dev PM Queen St / Elyard St

Base + Development PM Queen St / Elyard St 1630-1730
Roundabout

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
4	L2	94	0.0	0.294	6.4	LOS A	1.8	12.9	0.66	0.73	45.0
5	T1	66	0.0	0.294	6.4	LOS A	1.8	12.9	0.66	0.73	45.9
6	R2	91	5.5	0.294	10.5	LOS A	1.8	12.9	0.66	0.73	46.0
6u	U	1	0.0	0.294	12.1	LOS A	1.8	12.9	0.66	0.73	49.4
Approach		252	2.0	0.294	7.9	LOS A	1.8	12.9	0.66	0.73	45.6
NorthEast: Elyard St											
7	L2	104	5.8	0.411	6.7	LOS A	2.8	20.1	0.72	0.75	45.4
8	T1	178	1.7	0.411	6.6	LOS A	2.8	20.1	0.72	0.75	46.2
9	R2	52	1.9	0.411	10.5	LOS A	2.8	20.1	0.72	0.75	46.2
9u	U	16	12.5	0.411	12.7	LOS A	2.8	20.1	0.72	0.75	49.5
Approach		350	3.4	0.411	7.5	LOS A	2.8	20.1	0.72	0.75	46.1
NorthWest: Queen St											
10	L2	86	4.7	0.464	5.6	LOS A	3.3	23.2	0.62	0.69	45.2
11	T1	151	0.0	0.464	5.5	LOS A	3.3	23.2	0.62	0.69	46.0
12	R2	235	0.4	0.464	9.4	LOS A	3.3	23.2	0.62	0.69	46.0
12u	U	6	0.0	0.464	11.1	LOS A	3.3	23.2	0.62	0.69	49.5
Approach		478	1.0	0.464	7.5	LOS A	3.3	23.2	0.62	0.69	45.9
SouthWest: ElyardSt											
1	L2	174	0.0	0.339	4.7	LOS A	2.2	15.8	0.51	0.59	41.8
2	T1	118	8.5	0.339	4.9	LOS A	2.2	15.8	0.51	0.59	47.1
3	R2	66	1.5	0.339	8.7	LOS A	2.2	15.8	0.51	0.59	47.0
3u	U	4	0.0	0.339	10.4	LOS A	2.2	15.8	0.51	0.59	50.7
Approach		362	3.0	0.339	5.6	LOS A	2.2	15.8	0.51	0.59	44.4
All Vehicles		1442	2.3	0.464	7.1	LOS A	3.3	23.2	0.62	0.68	45.5

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base + Dev AM Queen St / Hume St

Base + Development AM Queen St / Hume St 0830 - 0930
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
1	L2	5	0.0	0.109	4.6	LOS A	0.0	0.0	0.00	0.01	49.4
2	T1	204	2.5	0.109	0.0	LOS A	0.0	0.0	0.00	0.01	49.9
Approach		209	2.4	0.109	0.1	NA	0.0	0.0	0.00	0.01	49.9
NorthEast: Hume St											
4	L2	5	0.0	0.033	4.8	LOS A	0.1	0.8	0.30	0.59	45.8
5	T1	5	0.0	0.033	4.5	LOS A	0.1	0.8	0.30	0.59	45.9
6	R2	20	0.0	0.033	6.5	LOS A	0.1	0.8	0.30	0.59	45.3
Approach		30	0.0	0.033	5.9	LOS A	0.1	0.8	0.30	0.59	45.5
NorthWest: Queen St											
8	T1	100	4.0	0.054	0.0	LOS A	0.0	0.1	0.01	0.01	49.9
9	R2	2	0.0	0.054	5.2	LOS A	0.0	0.1	0.01	0.01	48.9
Approach		102	3.9	0.054	0.1	NA	0.0	0.1	0.01	0.01	49.9
SouthWest: Hume St											
10	L2	11	0.0	0.009	5.2	LOS A	0.0	0.2	0.29	0.51	46.0
12	R2	1	0.0	0.009	6.1	LOS A	0.0	0.2	0.29	0.51	45.5
Approach		12	0.0	0.009	5.2	LOS A	0.0	0.2	0.29	0.51	45.9
All Vehicles		353	2.5	0.109	0.8	NA	0.1	0.8	0.04	0.08	49.3

Level of Service (LOS) Method: Delay (HCM 2000).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base + Dev PM Queen St / Hume St

Base + Development PM Queen St / Hume St 1600 - 1700
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen st											
1	L2	3	0.0	0.061	4.6	LOS A	0.0	0.0	0.00	0.01	49.4
2	T1	113	4.4	0.061	0.0	LOS A	0.0	0.0	0.00	0.01	49.9
Approach		116	4.3	0.061	0.1	NA	0.0	0.0	0.00	0.01	49.9
NorthEast: Hume st											
4	L2	27	0.0	0.112	5.3	LOS A	0.4	2.8	0.39	0.65	45.5
5	T1	5	0.0	0.112	4.9	LOS A	0.4	2.8	0.39	0.65	45.6
6	R2	66	0.0	0.112	7.0	LOS A	0.4	2.8	0.39	0.65	45.0
Approach		98	0.0	0.112	6.4	LOS A	0.4	2.8	0.39	0.65	45.2
NorthWest: Queen St											
8	T1	229	3.1	0.127	0.0	LOS A	0.1	0.6	0.03	0.03	49.8
9	R2	12	0.0	0.127	5.0	LOS A	0.1	0.6	0.03	0.03	48.8
Approach		241	2.9	0.127	0.3	NA	0.1	0.6	0.03	0.03	49.7
SouthWest: Hume St											
10	L2	6	0.0	0.005	4.9	LOS A	0.0	0.1	0.20	0.50	46.2
12	R2	1	0.0	0.005	6.6	LOS A	0.0	0.1	0.20	0.50	45.7
Approach		7	0.0	0.005	5.1	LOS A	0.0	0.1	0.20	0.50	46.1
All Vehicles		462	2.6	0.127	1.6	NA	0.4	2.8	0.10	0.16	48.7

Level of Service (LOS) Method: Delay (HCM 2000).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base + 2% Growth AM Queen St / Elyard St

Base + 2% Growth (2017) AM Queen St / Elyard St 0830 - 0930
Roundabout

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
4	L2	24	0.0	0.202	4.4	LOS A	1.1	8.1	0.42	0.57	45.7
5	T1	104	0.0	0.202	4.4	LOS A	1.1	8.1	0.42	0.57	46.6
6	R2	90	6.7	0.202	8.5	LOS A	1.1	8.1	0.42	0.57	46.6
6u	U	1	0.0	0.202	10.0	LOS A	1.1	8.1	0.42	0.57	50.2
Approach		219	2.7	0.202	6.1	LOS A	1.1	8.1	0.42	0.57	46.5
NorthEast: Elyard St											
7	L2	63	7.9	0.195	4.2	LOS A	1.1	8.2	0.38	0.53	45.9
8	T1	87	4.6	0.195	4.2	LOS A	1.1	8.2	0.38	0.53	46.9
9	R2	55	3.6	0.195	8.1	LOS A	1.1	8.2	0.38	0.53	46.9
9u	U	12	16.7	0.195	10.0	LOS A	1.1	8.2	0.38	0.53	47.5
Approach		217	6.0	0.195	5.5	LOS A	1.1	8.2	0.38	0.53	46.6
NorthWest: Queen St											
10	L2	83	15.7	0.224	5.8	LOS A	1.3	9.7	0.58	0.65	45.4
11	T1	74	0.0	0.224	5.4	LOS A	1.3	9.7	0.58	0.65	46.5
12	R2	41	4.9	0.224	9.5	LOS A	1.3	9.7	0.58	0.65	46.4
12u	U	4	0.0	0.224	11.1	LOS A	1.3	9.7	0.58	0.65	47.2
Approach		202	7.4	0.224	6.5	LOS A	1.3	9.7	0.58	0.65	46.0
SouthWest: Elyard St											
1	L2	240	1.7	0.481	5.2	LOS A	3.5	25.0	0.60	0.62	41.6
2	T1	226	5.3	0.481	5.3	LOS A	3.5	25.0	0.60	0.62	46.8
3	R2	36	0.0	0.481	9.2	LOS A	3.5	25.0	0.60	0.62	46.8
3u	U	7	0.0	0.481	10.9	LOS A	3.5	25.0	0.60	0.62	47.5
Approach		509	3.1	0.481	5.6	LOS A	3.5	25.0	0.60	0.62	44.2
All Vehicles		1147	4.4	0.481	5.9	LOS A	3.5	25.0	0.52	0.60	45.4

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base + 2% Growth PM Queen St / Elyard St

Base + 2% Growth (2017) PM Queen St / Elyard St 1630-1730
Roundabout

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
4	L2	32	0.0	0.215	6.3	LOS A	1.3	9.0	0.64	0.72	45.0
5	T1	68	0.0	0.215	6.4	LOS A	1.3	9.0	0.64	0.72	45.9
6	R2	77	7.8	0.215	10.6	LOS A	1.3	9.0	0.64	0.72	46.0
6u	U	2	0.0	0.215	12.0	LOS A	1.3	9.0	0.64	0.72	49.3
Approach		179	3.4	0.215	8.2	LOS A	1.3	9.0	0.64	0.72	45.8
NorthEast: Elyard St											
7	L2	97	8.2	0.410	6.5	LOS A	2.8	20.3	0.70	0.74	45.4
8	T1	183	2.2	0.410	6.4	LOS A	2.8	20.3	0.70	0.74	46.3
9	R2	55	3.6	0.410	10.4	LOS A	2.8	20.3	0.70	0.74	46.2
9u	U	19	21.1	0.410	12.7	LOS A	2.8	20.3	0.70	0.74	49.4
Approach		354	5.1	0.410	7.4	LOS A	2.8	20.3	0.70	0.74	46.2
NorthWest: Queen St											
10	L2	89	5.6	0.456	5.2	LOS A	3.2	22.9	0.58	0.65	45.3
11	T1	154	0.0	0.456	5.1	LOS A	3.2	22.9	0.58	0.65	46.1
12	R2	241	0.8	0.456	9.1	LOS A	3.2	22.9	0.58	0.65	46.1
12u	U	7	0.0	0.456	10.8	LOS A	3.2	22.9	0.58	0.65	49.7
Approach		491	1.4	0.456	7.2	LOS A	3.2	22.9	0.58	0.65	46.0
SouthWest: ElyardSt											
1	L2	178	0.0	0.312	4.7	LOS A	2.0	14.2	0.50	0.57	42.0
2	T1	123	9.8	0.312	4.9	LOS A	2.0	14.2	0.50	0.57	47.4
3	R2	25	4.0	0.312	8.7	LOS A	2.0	14.2	0.50	0.57	47.2
3u	U	5	0.0	0.312	10.4	LOS A	2.0	14.2	0.50	0.57	51.0
Approach		331	3.9	0.312	5.1	LOS A	2.0	14.2	0.50	0.57	44.4
All Vehicles		1355	3.2	0.456	6.9	LOS A	3.2	22.9	0.60	0.66	45.6

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base + 2% Growth AM Queen St / Hume St

Base + 2% Growth (2017) AM Queen St / Hume St 0830 - 0930
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
1	L2	2	0.0	0.104	4.6	LOS A	0.0	0.0	0.00	0.01	49.5
2	T1	197	3.0	0.104	0.0	LOS A	0.0	0.0	0.00	0.01	50.0
Approach		199	3.0	0.104	0.1	NA	0.0	0.0	0.00	0.01	49.9
NorthEast: Hume St											
4	L2	6	0.0	0.032	4.8	LOS A	0.1	0.7	0.28	0.59	45.8
5	T1	2	0.0	0.032	4.4	LOS A	0.1	0.7	0.28	0.59	45.8
6	R2	21	0.0	0.032	6.5	LOS A	0.1	0.7	0.28	0.59	45.2
Approach		29	0.0	0.032	6.0	LOS A	0.1	0.7	0.28	0.59	45.4
NorthWest: Queen St											
8	T1	95	5.3	0.052	0.0	LOS A	0.0	0.2	0.02	0.02	49.8
9	R2	3	0.0	0.052	5.2	LOS A	0.0	0.2	0.02	0.02	48.9
Approach		98	5.1	0.052	0.2	NA	0.0	0.2	0.02	0.02	49.8
SouthWest: Hume St											
10	L2	12	0.0	0.011	5.1	LOS A	0.0	0.3	0.28	0.52	46.0
12	R2	2	0.0	0.011	6.1	LOS A	0.0	0.3	0.28	0.52	45.5
Approach		14	0.0	0.011	5.3	LOS A	0.0	0.3	0.28	0.52	45.9
All Vehicles		340	3.2	0.104	0.8	NA	0.1	0.7	0.04	0.08	49.3

Level of Service (LOS) Method: Delay (HCM 2000).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Base + 2% Growth PM Queen St / Hume St

Base + 2% Growth (2017) PM Queen St / Hume St 1600 - 1700
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen st											
1	L2	4	0.0	0.060	4.6	LOS A	0.0	0.0	0.00	0.02	49.4
2	T1	109	5.5	0.060	0.0	LOS A	0.0	0.0	0.00	0.02	49.9
Approach		113	5.3	0.060	0.2	NA	0.0	0.0	0.00	0.02	49.9
NorthEast: Hume st											
4	L2	28	0.0	0.112	5.3	LOS A	0.4	2.8	0.38	0.64	45.5
5	T1	2	0.0	0.112	4.8	LOS A	0.4	2.8	0.38	0.64	45.6
6	R2	68	0.0	0.112	7.0	LOS A	0.4	2.8	0.38	0.64	45.0
Approach		98	0.0	0.112	6.5	LOS A	0.4	2.8	0.38	0.64	45.1
NorthWest: Queen St											
8	T1	225	4.0	0.127	0.0	LOS A	0.1	0.7	0.03	0.03	49.7
9	R2	13	0.0	0.127	4.9	LOS A	0.1	0.7	0.03	0.03	48.8
Approach		238	3.8	0.127	0.3	NA	0.1	0.7	0.03	0.03	49.7
SouthWest: Hume St											
10	L2	7	0.0	0.007	4.9	LOS A	0.0	0.2	0.20	0.51	46.2
12	R2	2	0.0	0.007	6.5	LOS A	0.0	0.2	0.20	0.51	45.7
Approach		9	0.0	0.007	5.2	LOS A	0.0	0.2	0.20	0.51	46.1
All Vehicles		458	3.3	0.127	1.7	NA	0.4	2.8	0.10	0.17	48.6

Level of Service (LOS) Method: Delay (HCM 2000).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Future Baseline Scenario (2017) AM Queen St / Elyard St

Future Baseline + 2% Growth (2017) + Development AM Queen St / Elyard St 0830 - 0930
Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
SouthEast: Queen St											
4	L2	73	0.0	0.257	4.4	LOS A	1.5	10.9	0.45	0.57	45.8
5	T1	104	0.0	0.257	4.5	LOS A	1.5	10.9	0.45	0.57	46.7
6	R2	103	5.8	0.257	8.5	LOS A	1.5	10.9	0.45	0.57	46.7
6u	U	1	0.0	0.257	10.1	LOS A	1.5	10.9	0.45	0.57	50.3
Approach		281	2.1	0.257	5.9	LOS A	1.5	10.9	0.45	0.57	46.5
NorthEast: Elyard St											
7	L2	82	6.1	0.227	4.7	LOS A	1.3	9.5	0.46	0.58	45.8
8	T1	87	4.6	0.227	4.7	LOS A	1.3	9.5	0.46	0.58	46.7
9	R2	55	3.6	0.227	8.6	LOS A	1.3	9.5	0.46	0.58	46.7
9u	U	12	16.7	0.227	10.6	LOS A	1.3	9.5	0.46	0.58	47.4
Approach		236	5.5	0.227	5.9	LOS A	1.3	9.5	0.46	0.58	46.4
NorthWest: Queen St											
10	L2	83	15.7	0.243	6.5	LOS A	1.5	10.9	0.65	0.70	45.1
11	T1	74	0.0	0.243	6.0	LOS A	1.5	10.9	0.65	0.70	46.2
12	R2	41	4.9	0.243	10.1	LOS A	1.5	10.9	0.65	0.70	46.1
12u	U	4	0.0	0.243	11.7	LOS A	1.5	10.9	0.65	0.70	46.9
Approach		202	7.4	0.243	7.2	LOS A	1.5	10.9	0.65	0.70	45.7
SouthWest: Elyard St											
1	L2	240	1.7	0.553	5.5	LOS A	4.3	31.2	0.66	0.67	41.3
2	T1	226	5.3	0.553	5.7	LOS A	4.3	31.2	0.66	0.67	46.4
3	R2	110	0.0	0.553	9.5	LOS A	4.3	31.2	0.66	0.67	46.4
3u	U	7	0.0	0.553	11.2	LOS A	4.3	31.2	0.66	0.67	47.1
Approach		583	2.7	0.553	6.4	LOS A	4.3	31.2	0.66	0.67	44.2
All Vehicles		1302	3.8	0.553	6.3	LOS A	4.3	31.2	0.58	0.64	45.3

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Future Baseline Scenario (2017) AM Queen St / Hume St

Future Baseline + 2% Growth (2017) + Development AM Queen St / Hume St 0830 - 0930
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
1	L2	2	0.0	0.110	4.6	LOS A	0.0	0.0	0.00	0.01	49.5
2	T1	209	2.9	0.110	0.0	LOS A	0.0	0.0	0.00	0.01	50.0
Approach		211	2.8	0.110	0.1	NA	0.0	0.0	0.00	0.01	50.0
NorthEast: Hume St											
4	L2	6	0.0	0.032	4.9	LOS A	0.1	0.8	0.30	0.59	45.7
5	T1	2	0.0	0.032	4.5	LOS A	0.1	0.8	0.30	0.59	45.8
6	R2	21	0.0	0.032	6.6	LOS A	0.1	0.8	0.30	0.59	45.2
Approach		29	0.0	0.032	6.1	LOS A	0.1	0.8	0.30	0.59	45.3
NorthWest: Queen St											
8	T1	103	4.9	0.057	0.0	LOS A	0.0	0.2	0.02	0.02	49.8
9	R2	3	0.0	0.057	5.2	LOS A	0.0	0.2	0.02	0.02	48.9
Approach		106	4.7	0.057	0.2	NA	0.0	0.2	0.02	0.02	49.8
SouthWest: Hume St											
10	L2	12	0.0	0.011	5.2	LOS A	0.0	0.3	0.30	0.52	45.9
12	R2	2	0.0	0.011	6.2	LOS A	0.0	0.3	0.30	0.52	45.5
Approach		14	0.0	0.011	5.3	LOS A	0.0	0.3	0.30	0.52	45.9
All Vehicles		360	3.1	0.110	0.8	NA	0.1	0.8	0.04	0.08	49.3

Level of Service (LOS) Method: Delay (HCM 2000).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Future Baseline Scenario (2017) PM Queen St / Elyard St

Future Baseline + 2% Growth (2017) + Development PM Queen St / Elyard St 1630-1730
Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
SouthEast: Queen St											
4	L2	95	0.0	0.308	6.6	LOS A	1.9	13.7	0.68	0.75	45.0
5	T1	68	0.0	0.308	6.6	LOS A	1.9	13.7	0.68	0.75	45.8
6	R2	93	6.5	0.308	10.8	LOS A	1.9	13.7	0.68	0.75	46.0
6u	U	2	0.0	0.308	12.3	LOS A	1.9	13.7	0.68	0.75	49.3
Approach		258	2.3	0.308	8.1	LOS A	1.9	13.7	0.68	0.75	45.6
NorthEast: Elyard St											
7	L2	108	7.4	0.439	7.0	LOS A	3.1	22.3	0.74	0.77	45.3
8	T1	183	2.2	0.439	6.8	LOS A	3.1	22.3	0.74	0.77	46.1
9	R2	55	3.6	0.439	10.8	LOS A	3.1	22.3	0.74	0.77	46.1
9u	U	19	21.1	0.439	13.2	LOS A	3.1	22.3	0.74	0.77	49.2
Approach		365	4.9	0.439	7.8	LOS A	3.1	22.3	0.74	0.77	46.0
NorthWest: Queen St											
10	L2	89	5.6	0.485	5.8	LOS A	3.5	24.8	0.64	0.70	45.1
11	T1	154	0.0	0.485	5.7	LOS A	3.5	24.8	0.64	0.70	45.9
12	R2	241	0.8	0.485	9.6	LOS A	3.5	24.8	0.64	0.70	45.9
12u	U	7	0.0	0.485	11.3	LOS A	3.5	24.8	0.64	0.70	49.4
Approach		491	1.4	0.485	7.7	LOS A	3.5	24.8	0.64	0.70	45.8
SouthWest: ElyardSt											
1	L2	178	0.0	0.355	4.8	LOS A	2.3	16.9	0.53	0.60	41.8
2	T1	123	9.8	0.355	5.1	LOS A	2.3	16.9	0.53	0.60	47.1
3	R2	67	1.5	0.355	8.9	LOS A	2.3	16.9	0.53	0.60	46.9
3u	U	5	0.0	0.355	10.5	LOS A	2.3	16.9	0.53	0.60	50.6
Approach		373	3.5	0.355	5.7	LOS A	2.3	16.9	0.53	0.60	44.4
All Vehicles		1487	3.0	0.485	7.3	LOS A	3.5	24.8	0.65	0.70	45.4

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Future Baseline Scenario (2017) PM Queen St / Elyard St

Future Baseline + 2% Growth (2017) + Development PM Queen St / Elyard St 1630-1730
Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
4	L2	95	0.0	0.308	6.6	LOS A	1.9	13.7	0.68	0.75	45.0
5	T1	68	0.0	0.308	6.6	LOS A	1.9	13.7	0.68	0.75	45.8
6	R2	93	6.5	0.308	10.8	LOS A	1.9	13.7	0.68	0.75	46.0
6u	U	2	0.0	0.308	12.3	LOS A	1.9	13.7	0.68	0.75	49.3
Approach		258	2.3	0.308	8.1	LOS A	1.9	13.7	0.68	0.75	45.6
NorthEast: Elyard St											
7	L2	108	7.4	0.439	7.0	LOS A	3.1	22.3	0.74	0.77	45.3
8	T1	183	2.2	0.439	6.8	LOS A	3.1	22.3	0.74	0.77	46.1
9	R2	55	3.6	0.439	10.8	LOS A	3.1	22.3	0.74	0.77	46.1
9u	U	19	21.1	0.439	13.2	LOS A	3.1	22.3	0.74	0.77	49.2
Approach		365	4.9	0.439	7.8	LOS A	3.1	22.3	0.74	0.77	46.0
NorthWest: Queen St											
10	L2	89	5.6	0.485	5.8	LOS A	3.5	24.8	0.64	0.70	45.1
11	T1	154	0.0	0.485	5.7	LOS A	3.5	24.8	0.64	0.70	45.9
12	R2	241	0.8	0.485	9.6	LOS A	3.5	24.8	0.64	0.70	45.9
12u	U	7	0.0	0.485	11.3	LOS A	3.5	24.8	0.64	0.70	49.4
Approach		491	1.4	0.485	7.7	LOS A	3.5	24.8	0.64	0.70	45.8
SouthWest: ElyardSt											
1	L2	178	0.0	0.355	4.8	LOS A	2.3	16.9	0.53	0.60	41.8
2	T1	123	9.8	0.355	5.1	LOS A	2.3	16.9	0.53	0.60	47.1
3	R2	67	1.5	0.355	8.9	LOS A	2.3	16.9	0.53	0.60	46.9
3u	U	5	0.0	0.355	10.5	LOS A	2.3	16.9	0.53	0.60	50.6
Approach		373	3.5	0.355	5.7	LOS A	2.3	16.9	0.53	0.60	44.4
All Vehicles		1487	3.0	0.485	7.3	LOS A	3.5	24.8	0.65	0.70	45.4

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Future + 10 years (2027) Scenario AM Queen St / Elyard St

Future Baseline + 10 Years 2% Growth (2027) + Development Trip AM Queen St / Elyard St 0830 - 0930 Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
SouthEast: Queen St											
4	L2	79	0.0	0.319	4.8	LOS A	2.0	14.4	0.52	0.62	45.5
5	T1	127	0.0	0.319	4.9	LOS A	2.0	14.4	0.52	0.62	46.5
6	R2	124	6.5	0.319	9.0	LOS A	2.0	14.4	0.52	0.62	46.4
6u	U	2	0.0	0.319	10.5	LOS A	2.0	14.4	0.52	0.62	50.1
Approach		332	2.4	0.319	6.4	LOS A	2.0	14.4	0.52	0.62	46.3
NorthEast: Elyard St											
7	L2	96	6.3	0.287	5.0	LOS A	1.7	12.9	0.52	0.61	45.6
8	T1	107	4.7	0.287	5.0	LOS A	1.7	12.9	0.52	0.61	46.5
9	R2	68	4.4	0.287	9.0	LOS A	1.7	12.9	0.52	0.61	46.5
9u	U	16	18.8	0.287	11.0	LOS A	1.7	12.9	0.52	0.61	47.1
Approach		287	5.9	0.287	6.3	LOS A	1.7	12.9	0.52	0.61	46.2
NorthWest: Queen St											
10	L2	102	15.7	0.333	7.5	LOS A	2.2	16.2	0.75	0.78	44.7
11	T1	91	0.0	0.333	6.9	LOS A	2.2	16.2	0.75	0.78	45.7
12	R2	51	5.9	0.333	11.1	LOS A	2.2	16.2	0.75	0.78	45.7
12u	U	5	0.0	0.333	12.6	LOS A	2.2	16.2	0.75	0.78	46.4
Approach		249	7.6	0.333	8.1	LOS A	2.2	16.2	0.75	0.78	45.3
SouthWest: Elyard St											
1	L2	294	2.0	0.703	8.7	LOS A	8.3	59.7	0.83	0.87	40.2
2	T1	276	5.4	0.703	8.9	LOS A	8.3	59.7	0.83	0.87	44.9
3	R2	118	0.0	0.703	12.6	LOS A	8.3	59.7	0.83	0.87	45.0
3u	U	9	0.0	0.703	14.3	LOS A	8.3	59.7	0.83	0.87	45.6
Approach		697	3.0	0.703	9.5	LOS A	8.3	59.7	0.83	0.87	42.8
All Vehicles		1565	4.2	0.703	8.0	LOS A	8.3	59.7	0.70	0.76	44.5

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Future + 10 years (2027) Scenario PM Queen St / Elyard St

Future Baseline + 10 Years 2% Growth (2027) + Development Trip PM Queen St / Elyard St 1630-1730 Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
4	L2	103	0.0	0.403	7.9	LOS A	2.7	19.5	0.79	0.84	44.3
5	T1	83	0.0	0.403	7.9	LOS A	2.7	19.5	0.79	0.84	45.1
6	R2	109	5.5	0.403	12.1	LOS A	2.7	19.5	0.79	0.84	45.3
6u	U	3	0.0	0.403	13.6	LOS A	2.7	19.5	0.79	0.84	48.5
Approach		298	2.0	0.403	9.5	LOS A	2.7	19.5	0.79	0.84	44.9
NorthEast: Elyard St											
7	L2	131	8.4	0.612	11.0	LOS A	6.0	43.9	0.90	1.01	43.3
8	T1	224	2.2	0.612	10.7	LOS A	6.0	43.9	0.90	1.01	44.1
9	R2	68	4.4	0.612	14.8	LOS B	6.0	43.9	0.90	1.01	44.1
9u	U	25	24.0	0.612	17.5	LOS B	6.0	43.9	0.90	1.01	46.9
Approach		448	5.6	0.612	11.8	LOS A	6.0	43.9	0.90	1.01	44.0
NorthWest: Queen St											
10	L2	116	6.0	0.637	8.3	LOS A	6.4	45.6	0.80	0.86	44.0
11	T1	188	0.0	0.637	8.1	LOS A	6.4	45.6	0.80	0.86	44.8
12	R2	295	1.0	0.637	12.1	LOS A	6.4	45.6	0.80	0.86	44.8
12u	U	9	0.0	0.637	13.8	LOS A	6.4	45.6	0.80	0.86	48.1
Approach		608	1.6	0.637	10.1	LOS A	6.4	45.6	0.80	0.86	44.7
SouthWest: ElyardSt											
1	L2	217	0.0	0.452	5.4	LOS A	3.2	23.5	0.63	0.66	41.6
2	T1	151	9.9	0.452	5.7	LOS A	3.2	23.5	0.63	0.66	46.8
3	R2	74	2.7	0.452	9.5	LOS A	3.2	23.5	0.63	0.66	46.7
3u	U	7	0.0	0.452	11.1	LOS A	3.2	23.5	0.63	0.66	50.3
Approach		449	3.8	0.452	6.3	LOS A	3.2	23.5	0.63	0.66	44.1
All Vehicles		1803	3.2	0.637	9.5	LOS A	6.4	45.6	0.78	0.84	44.4

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Future + 10 years (2027) Scenario AM Queen St / Hume St

Future Baseline + 10 Year 2% Growth (2027) + Development Trip AM Queen St / Hume St 0830 - 0930
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen St											
1	L2	3	0.0	0.134	4.6	LOS A	0.0	0.0	0.00	0.01	49.5
2	T1	253	3.2	0.134	0.0	LOS A	0.0	0.0	0.00	0.01	49.9
Approach		256	3.1	0.134	0.1	NA	0.0	0.0	0.00	0.01	49.9
NorthEast: Hume St											
4	L2	8	0.0	0.044	4.9	LOS A	0.1	1.0	0.34	0.62	45.5
5	T1	3	0.0	0.044	4.9	LOS A	0.1	1.0	0.34	0.62	45.6
6	R2	26	0.0	0.044	7.1	LOS A	0.1	1.0	0.34	0.62	45.0
Approach		37	0.0	0.044	6.5	LOS A	0.1	1.0	0.34	0.62	45.1
NorthWest: Queen St											
8	T1	125	5.6	0.069	0.0	LOS A	0.0	0.2	0.03	0.02	49.8
9	R2	4	0.0	0.069	5.4	LOS A	0.0	0.2	0.03	0.02	48.9
Approach		129	5.4	0.069	0.2	NA	0.0	0.2	0.03	0.02	49.8
SouthWest: Hume St											
10	L2	15	0.0	0.016	5.3	LOS A	0.1	0.4	0.33	0.54	45.8
12	R2	3	0.0	0.016	6.7	LOS A	0.1	0.4	0.33	0.54	45.4
Approach		18	0.0	0.016	5.6	LOS A	0.1	0.4	0.33	0.54	45.8
All Vehicles		440	3.4	0.134	0.9	NA	0.1	1.0	0.05	0.08	49.3

Level of Service (LOS) Method: Delay (HCM 2000).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

MOVEMENT SUMMARY



Site: Future + 10 years (2027) Scenario PM Queen St / Hume St

Future Base + 10 Years 2% Growth (2027) + Development Trip PM Queen St / Hume St 1600 - 1700
 Giveaway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
SouthEast: Queen st											
1	L2	5	0.0	0.081	4.6	LOS A	0.0	0.0	0.00	0.02	49.4
2	T1	148	5.4	0.081	0.0	LOS A	0.0	0.0	0.00	0.02	49.9
Approach		153	5.2	0.081	0.2	NA	0.0	0.0	0.00	0.02	49.9
NorthEast: Hume st											
4	L2	35	0.0	0.154	5.6	LOS A	0.6	3.9	0.45	0.70	45.1
5	T1	3	0.0	0.154	5.6	LOS A	0.6	3.9	0.45	0.70	45.2
6	R2	83	0.0	0.154	7.9	LOS A	0.6	3.9	0.45	0.70	44.6
Approach		121	0.0	0.154	7.2	LOS A	0.6	3.9	0.45	0.70	44.7
NorthWest: Queen St											
8	T1	286	4.2	0.161	0.0	LOS A	0.1	0.9	0.04	0.03	49.7
9	R2	16	0.0	0.161	5.1	LOS A	0.1	0.9	0.04	0.03	48.8
Approach		302	4.0	0.161	0.3	NA	0.1	0.9	0.04	0.03	49.7
SouthWest: Hume St											
10	L2	9	0.0	0.011	5.0	LOS A	0.0	0.3	0.26	0.52	46.0
12	R2	3	0.0	0.011	7.4	LOS A	0.0	0.3	0.26	0.52	45.6
Approach		12	0.0	0.011	5.6	LOS A	0.0	0.3	0.26	0.52	45.9
All Vehicles		588	3.4	0.161	1.8	NA	0.6	3.9	0.12	0.18	48.5

Level of Service (LOS) Method: Delay (HCM 2000).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).


HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

Narellan Medical Centre

APPENDIX

C

SWEPT PATH ANALYSIS



NOT TO SCALE

VEHICLE LEGEND


- VEHICLE BODY PATH
- VEHICLE CENTRELINE
- 300mm CLEARANCE FROM VEHICLE BODY
- ASSUMED SPEED 5km/h

Preliminary Plan
FOR DISCUSSION PURPOSES ONLY
SUBJECT TO CHANGE
WITHOUT NOTIFICATION

© Cardno Limited
All Rights Reserved.
This document is produced by Cardno Limited solely for the benefit of and use by the client in accordance with the terms of the retainer. Cardno Limited does not and shall not assume any responsibility or liability whatsoever to any third party arising out of any use or reliance by third party on the content of this document.

Cardno
Shaping the Future
Cardno (NSW/ACT) Pty Ltd | ABN 95 001 145 035
Level 9, The Forum, 203 Pacific Highway
St. Leonards, NSW 2065
Tel: 02 9496 7700 Fax: 02 9439 5170
Web: www.cardno.com.au

Client	SHELLSHEAR YOUNG PTY LTD
Project	NARELLAN MEDICAL CENTRE 19 QUEEN STREET NARELLAN
Title	SWEPT PATH 12 METER TRUCK SWEPT PATH



NOT TO SCALE

VEHICLE LEGEND


- VEHICLE BODY PATH
- VEHICLE CENTRELINE
- 300mm CLEARANCE FROM VEHICLE BODY
- ASSUMED SPEED 5km/h

Preliminary Plan
FOR DISCUSSION PURPOSES ONLY
SUBJECT TO CHANGE
WITHOUT NOTIFICATION

© Cardno Limited
All Rights Reserved.
This document is produced by Cardno Limited solely for the benefit of and use by the client in accordance with the terms of the retainer. Cardno Limited does not and shall not assume any responsibility or liability whatsoever to any third party arising out of any use or reliance by third party on the content of this document.

Cardno
Shaping the Future
Cardno (NSW/ACT) Pty Ltd | ABN 95 001 145 035
Level 9, The Forum, 203 Pacific Highway
St. Leonards, NSW 2065
Tel: 02 9496 7700 Fax: 02 9439 5170
Web: www.cardno.com.au

Client **SHELLSHEAR YOUNG PTY LTD**
Project **NARELLAN MEDICAL CENTRE
19 QUEEN STREET NARELLAN**
Title **SWEPT PATH
B99 PASSENGER VEHICLE SWEPT PATH**



NOT TO SCALE

VEHICLE LEGEND


- VEHICLE BODY PATH
- VEHICLE CENTRELINE
- 300mm CLEARANCE FROM VEHICLE BODY
- ASSUMED SPEED 5km/h

Preliminary Plan
FOR DISCUSSION PURPOSES ONLY
SUBJECT TO CHANGE
WITHOUT NOTIFICATION

© Cardno Limited
All Rights Reserved.
This document is produced by Cardno Limited solely for the benefit of and use by the client in accordance with the terms of the retainer. Cardno Limited does not and shall not assume any responsibility or liability whatsoever to any third party arising out of any use or reliance by third party on the content of this document.

Cardno
Shaping the Future
Cardno (NSW/ACT) Pty Ltd | ABN 95 001 145 035
Level 9, The Forum, 203 Pacific Highway
St. Leonards, NSW 2065
Tel: 02 9496 7700 Fax: 02 9439 5170
Web: www.cardno.com.au

Client **SHELLSHEAR YOUNG PTY LTD**
Project NARELLAN MEDICAL CENTRE
19 QUEEN STREET NARELLAN
Title **SWEPT PATH**
MEDIUM RIGID VEHICLE (MRV) SWEPT PATH



NOT TO SCALE

VEHICLE LEGEND

- VEHICLE BODY PATH
- VEHICLE CENTRELINE
- 300mm CLEARANCE FROM VEHICLE BODY
- ASSUMED SPEED 5km/h

Preliminary Plan
FOR DISCUSSION PURPOSES ONLY
SUBJECT TO CHANGE
WITHOUT NOTIFICATION

© Cardno Limited
All Rights Reserved.
This document is produced by Cardno Limited solely for the benefit of and use by the client in accordance with the terms of the retainer. Cardno Limited does not and shall not assume any responsibility or liability whatsoever to any third party arising out of any use or reliance by third party on the content of this document.

Cardno
Shaping the Future
Cardno (NSW/ACT) Pty Ltd | ABN 95 001 145 035
Level 9, The Forum, 203 Pacific Highway
St. Leonards, NSW 2065
Tel: 02 9496 7700 Fax: 02 9439 5170
Web: www.cardno.com.au

Client	SHELLSHEAR YOUNG PTY LTD
Project	NARELLAN MEDICAL CENTRE 19 QUEEN STREET NARELLAN
Title	SWEPT PATH SMALL RIGID VEHICLE (SRV) SWEPT PATH