

CONDITIONS OF CONSENT

- 1) The proposal shall comply with the conditions of Development Consent. A Construction Certificate shall not be issued until the plans and specifications meet the required technical standards and the conditions of this Development Consent are satisfied.
- 2) Development shall take place in accordance with Development Application No.DA-74/2017, submitted by Mr Tony Owen, accompanied by drawings listed in the table below affixed with Council's approval stamp dated 6 June 2017, except where otherwise altered by the specific amendments listed hereunder and/or except where amended by the conditions contained in this approval.

Drawing Number	Drawing Title	Revision	Prepared By	Dated
A004	Site Plan	B	Towy Owen Partners	31.03.2017
A006	Setback Plan	B		31.03.2017
A007	Demolition Plan	B		31.03.2017
A090	Basement Level 2	B		31.03.2017
A10	Basement Level 1	B		31.03.2017
A101	Ground Floor Plan	B		31.03.2017
A102	Typical Plan – Level 1, 2, 3	B		31.03.2017
A103	Typical Plan – Level 4,5	B		31.03.2017
A104	Roof Plan	B		31.03.2017
A150	Adaptable Units	B		31.03.2017
A200	East Elevation	B		31.03.2017
A201	North Elevation	B		31.03.2017
A202	South Elevation	B		31.03.2017
A203	West Elevation	B		31.03.2017
A300	Section A	B		31.03.2017
A301	Section B	B		31.03.2017
A310	Fire Hydrant and Sprinkler Booster Detail	B		31.03.2017

The development plans shall be amended as follows:

- a) The skylights associated with Apartment Nos. 506 and 507 (as shown on the roof plan and the floor plan) shall be replaced with clerestory windows. The windows are to have a northern orientation and allow a minimum of two (2) hours solar access into the living areas of each apartment between 9am and 3pm during mid-winter. The windows are to be placed above the kitchens of apartments 506 and 507, as marked in red on the approved plans.

- b) Privacy screening shall be provided to all balconies on levels 1, 2, 3, 4 & 5 on the north, south and western elevations to a minimum of 50% of the length of the balcony (as measured parallel to the adjoining property boundary). The privacy screening shall be angled/moveable to allow for the sun to penetrate in mid-winter to ensure all apartments that currently receive the minimum 2 hours solar access during mid-winter continue to achieve the minimum standard once the screening is in place. Details of such shall be submitted to and approved by the PCA prior to the issue of a Construction Certificate.
- c) The following amendments are to be made to the car parking layout within the basement:
 - a. Parking space No. 28 on Basement Level 1 is required to have an additional width of 300mm.
 - b. Spaces 04 and 05 on Basement Level 1 shall be marked as Visitor parking instead of Spaces 07 and 08

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF A CONSTRUCTION CERTIFICATE

Prior to the release of a Construction Certificate the following conditions MUST be satisfied and nominated fees/contributions/bonds paid:

- 3) The Certifying Authority must ensure that any certified plans forming part of the Construction Certificate are not inconsistent with this Development Consent and accompanying plans.
- 4) A detailed landscape plan prepared by a qualified landscape architect or designer is to be approved prior to the issue of a Construction Certificate. The landscape plan is to be prepared in accordance with the relevant DCP and is to show all features, built structures including retaining walls, irrigation, mulch and natural features such as significant gardens, landscaping, trees, natural drainage lines and rock outcrops that occur within 3 metres of the site boundary. The landscape plan shall consider any stormwater, hydraulic or overland flow design issues where relevant.
- 5) The landscape plan shall include the provision for the replacement of all boundary fencing. A new 1.8m fence (solid) is to be erected along all side and rear boundaries of the subject allotment at full cost to the developer. An additional 300mm of privacy screening shall be attached to the top of the 1.8m high fence. The colour of the fence is to complement the development and the fence is to be constructed of lapped and capped timber paling, sheet metal or other suitable material unless the type of material is stipulated in any flood study prepared for the site. The selection of materials and colours of the fence is to be determined in consultation

with the adjoining property owners. Fencing forward of the building line shall be no higher than 1m unless otherwise approved by Council.

- 6) Approval in accordance with Council's Tree Preservation Order (TPO) is granted to lop or remove only the trees identified to be lopped or removed on the approved plans. Separate approval shall be obtained to prune or remove trees on adjoining properties or other trees located on the site. Failure to comply with Council's TPO may result in a fine of up to \$100,000.
- 7) The minimum headroom clearances above car parking spaces in the basement located directly underneath the on-site detention (OSD) tank or any other obstacle suspended from the basement's ceiling, must be maintained as per AS 2890.1 and AS 2890.6 at 2.2m and 2.5m respectively. Details shall be submitted to and approved by the PCA prior to the issue of a Construction Certificate.
- 8) The bin rooms are to be constructed of masonry material and fully enclosed with a roof and a roller door (or similar) to fully contain the bins in order to limit the visual impact and the potential for odours adversely impacting on the occupants of the development. Details are to be submitted to the PCA prior to the issue of a Construction Certificate.
- 9) A soil erosion and sediment control plan must be prepared by a suitably qualified professional, in accordance with the Bankstown Demolition and Construction Guidelines and Council's Development Engineering Standards, and submitted to the certifying authority for approval prior to the issue of a construction certificate.
- 10) The Council Approved building plans, including demolition plans, must be submitted to Sydney Water for assessment. This will determine if the proposed structure(s) would affect any Sydney Water infrastructure or if there are additional requirements. Building plan approvals can be submitted online via Sydney Water Tap in™.

Please refer to www.sydneywater.com.au/tapin

For Sydney Water's Guidelines for building over or next to assets, visit www.sydneywater.com.au 'Plumbing, building & developing' then 'Building Plan Approvals' or call 13000 TAPIN.

Prior to release of a construction certificate Sydney Water must issue either a Building Plan Assessment letter which states that your application is approved, or the appropriate plans must be stamped by a Water Servicing Coordinator.

- 11) A Construction Certificate shall not be issued until written proof that all bonds, fees and/or contributions as required by this consent have been paid to the applicable authority.

- 12) A long service levy payment which is 0.35% of the total cost of the work is to be paid to the Building and Construction Industry Long Service Payments Corporation.
- 13) Pursuant to section 80A(1) of the Environmental Planning and Assessment Act 1979, and the Bankstown City Council Section 94A Development Contributions Plan 2009 (Section 94A Plan) , a contribution of \$190,901.63 shall be paid to Council.

The amount to be paid is to be adjusted at the time of actual payment, in accordance with the provisions of the Section 94A plan. The contribution is to be paid before the issue of the construction certificate.

Note: The Section 94A Contributions Plans may be inspected at Council's Customer Service Centre, located at Upper Ground Floor, Civic Tower, 66-72 Rickard Road, Bankstown, between the hours of 8.30am-5.00pm Monday to Friday.

- 14) Finished surface levels of all internal works and at the street boundary, including driveways, landscaping and drainage structures, must be as shown on the approved plans. The levels at the street boundary must be consistent with the Street Boundary Alignment Levels issued by Council.
- 15) Stormwater drainage from the development shall be designed so as to comply with Council's Development Engineering Standards and the requirements of the BASIX Certificate. A final detailed stormwater drainage design shall be prepared by a qualified Professional Civil Engineer in accordance with the above requirements and shall generally be in accordance with the concept stormwater plan project No. 20160175, drawing no. SW02, SW03 (as marked in red), SW04, SW05, revision C, dated 1/02/2017, prepared by SGC Engineering Value. The final plan shall be certified by the design engineer that it complies with Council's Development Engineering Standards, the BASIX Certificate and the relevant Australian Standards. The plan is to be amended as marked in red, to remove the existing 225 diameter drainage system which exists within the footway, which drains the existing Child Care Centre. The developer must extend the Council drainage system from the northwest corner of Percy Street and Macauley Avenue and reconstruct as street drainage with a minimum 375 diameter pipeline, terminating in a kerb inlet pit with 2.4 meter long lintel. The developer must instruct the Hydraulic Engineer to amend the plans and submit them to Council for the Work Permit Application.
- 16) Where Council approved cut or fill exceeds 200mm and stable batter of 1 vertical to 3 horizontal maximum grade cannot be achieved, then a masonry or other proprietary material retaining wall, intended and suitable for that purpose, shall be constructed within the development site. Note, filling of the site needs specific approval from Council.

The retaining wall shall be located so that it will not impede or obstruct the natural flow of stormwater. Retaining walls exceeding 600mm in height shall be designed by a qualified professional Civil/Structural Engineer. Plans and details prepared and signed by the Engineer are to be submitted to the Principal Certifying Authority (PCA) prior to the issue of the Construction Certificate.

All works associated with the construction of the wall, including backfilling and drainage, is to be located wholly within the allotment boundaries.

- 17) The applicant shall apply to the Bankstown Traffic Committee for the installation of a Works Zone at the site's frontage to Percy Street, 8 weeks in advance of when construction is scheduled to begin. If timed or full time No Parking signs are required for sight distance/waste collection, these shall be applied for at the same time and installed when the Works Zone is removed
- 18) A Work Permit shall be applied for and obtained from Council for the following engineering works in front of the site, at the applicant's expense:
 - a) A Heavy Duty VFC at the property boundary with a maximum width of 6 metres at the property boundary and a Medium Duty VFC of a maximum width of 2 metres at the property boundary for the removal of waste bins.
 - b) Drainage connection to Council's system. The pipe within the road reserve shall be extended from the northwest corner of Percy Street and Macquarie Avenue as a 375 diameter RCP including kerb inlet pit with 2.4 metre lintel, to the north of the proposed driveway. The kerb inlet pit must be in front of the development site and must not be located in front an adjoining property.
 - c) Maintain the existing 1.2 metre wide concrete footway paving along the sites entire frontage or replace damaged paving with new paving.
 - d) Concrete kerb and gutter along the sites entire frontage.
 - e) Removal of all driveway surfaces, reinstatement of laybacks to kerb and gutter and reshaping of the footway, all associated with redundant VFCs.
 - f) Repair of any damage to the public road including the footway occurring during development works.
 - g) Reinstatement of the footway reserve and adjustment or relocation of existing public utility services to match the footway design levels as proposed on the approved Work Permit. Adjustment or relocation to any public utility services shall be carried out to the requirements of the public utility authority.

Note: As a site survey and design is required to be prepared by Council in order to determine the necessary information, payment for the Work Permit should be made at least twenty one (21) days prior to the information being required and must be approved prior to the issue of the Construction Certificate.

- 19) An all weather pavement shall be designed to withstand the anticipated wheel loads for all areas subjected to vehicular movements. Internal pavements specification prepared and certified by all qualified professional Civil Engineer to comply with the relevant Australian Standards, shall be submitted to the Principal Certifying Authority (PCA) for approval prior to the issue of a construction certificate.
- 20) The pump out drainage system for the access ramp and basement car parking area shall be provided in accordance with Council's Development Engineering Standards. Engineering details and specifications shall be submitted to the Principal Certifying Authority (PCA) for approval prior to the issue of any Construction Certificate.
- 21) Engineering details and manufacturers specifications for the pumps, switching system and sump pit shall be submitted to the Principal Certifying Authority (PCA) for approval prior to issue of any Construction Certificate.
- 22) The basement of the development is located adjacent to a Council Public Road Reserve. Separate approval and Work Permit is to be obtained from Council for any temporary or permanent anchoring works under Council's Public Road
- 23) The Construction Certificate plans shall include details of the garbage receptacle area. The garbage receptacle area shall not be visible from the street. The garbage receptacle area shall be located within the building or screened from the street by dense landscaping.
- 24) Prior to the issue of any Construction Certificate for this development, the applicant must obtain approval from Council for a Site, Pedestrian and Traffic Management Plan. This Plan must address the measures that will be implemented for the protection of adjoining properties, pedestrian safety and traffic management and other requirements as specified below.

A PRIVATE CERTIFIER CANNOT APPROVE YOUR SITE, PEDESTRIAN & TRAFFIC MANAGEMENT PLAN

This plan shall include details of the following:

- a) Proposed ingress and egress points for vehicles to and from the construction site;
- b) Proposed protection of pedestrians, adjacent to the constructions site;
- c) Proposed hoardings, scaffolding and/or fencing to secure the construction site;
- d) Proposed pedestrian management whilst vehicles are entering/exiting the construction site;
- e) Proposed measures to be implemented for the protection of all public roads and footway areas surrounding the construction site from

- building activities, crossings by heavy equipment, plant and materials delivery and static load from cranes, concrete pumps and the like;
- f) Proposed method of loading and unloading excavation machines, building material, construction materials and waste containers during the construction period;
- g) Proposed traffic control measures such as advanced warning signs, barricades, warning lights, after hours contact numbers etc are required to be displayed and shall be in accordance with Council's and the NSW Roads and Maritime Services requirements and AS1742.3.
- h) Proposed method of support of any excavation, adjacent to adjoining buildings or the public road. The proposed method of support is to be certified by a Civil Engineer with National Professional Engineering Registration (NPER) in the construction of civil works.
- i) Proposed measures to be implemented in order to ensure that no soil/excavated material is transported on wheels or tracks of vehicles or plant and deposited on the public road.
- j) Proposed measures for protection of the environment including procedures to control environmental impacts of work e.g. sediment control, proper removal, disposal or recycling of waste materials, protection of vegetation and control/prevention of pollution i.e. water, air noise, land pollution.

The approved Site, Pedestrian and Traffic Management Plan is to be implemented prior to the commencement of any works on the construction site. The applicant will be required to pay for inspections by Council Officers in accordance with Council's adopted fees and charges.

In addition a RMS Approval / Road Occupancy Licence will be required for works on Regional or State Roads or within 100m of a traffic facility including roundabouts and traffic signals. Refer to Council's Development Engineering Standards for a list of Regional and State Roads.

- 25) As any works within, or use of, the footway or public road for construction purposes requires separate Council approval under Section 138 of the Roads Act 1993 and/or Section 68 of the Local Government Act 1993, Council requires that prior to any Construction Certificate for this development being issued, a Works Permit and or a Roadway/Footpath Building Occupation Permit shall be obtained where one or more of the following will occur, within, on or over the public footway or public road:

A PRIVATE CERTIFIER CANNOT ISSUE THESE PERMITS

WORKS REQUIRING A 'WORKS PERMIT'

- a) Dig up, disturb, or clear the surface of a public footway or public road,
- b) Remove or interfere with a structure or tree (or any other vegetation) on a public footway or public road,
- c) Connect a road (whether public or private) to a classified road,

- d) Undertake footway, paving, vehicular crossing (driveway), landscaping or stormwater drainage works within a public footway or public road,
- e) Install utilities in, under or over a public road,
- f) Pump water into a public footway or public road from any land adjoining the public road,
- g) Erect a structure or carry out a work in, on or over a public road
- h) Require a work zone on the public road for the unloading and or loading of vehicles
- i) Pump concrete from within a public road,
- j) Stand a mobile crane within a public road
- k) Store waste and recycling containers, skips, bins and/or building materials on any part of the public road.
- l) The work is greater than \$25,000.
- m) Demolition is proposed.
- n) Subdivision is proposed.
- o) A Swimming pool is proposed.

Assessment of Works Permits (a to e) includes the preparation of footway design levels, vehicular crossing plans, dilapidation reports and issue of a Road Opening Permit.

All proposed works within the public road and footway shall be constructed under the supervision and to the satisfaction of Council. The applicant/developer shall arrange for necessary inspections by Council whilst the work is in progress.

For commercial or multi-unit residential developments within the designated CBD or an urban village area, footway design and construction and street tree supply, installation and tree hole detailing shall be as per the Council master plan for that area. Full width footways are to be supplied and installed at full cost to the developer to specification as supplied by Council. Layout plan of pavement to be submitted to Council for approval prior to the issue of the Works Permit.

All Council fees applicable, minimum restoration charges and inspection fees shall be paid prior to the assessment of the Work Permit in accordance with Council's adopted fees and charges. Note: Additional fees after approval will be charged where the Work Permit requires occupation of the Road or Footpath ie Hoardings, Work Zones etc.

In determining a Works Permit, Council can impose conditions and require inspections by Council Officers.

Forms can be obtained from Council's Customer Service counter located on the ground floor of Council's administration building at 66 - 72 Rickard Road, Bankstown or Council's website www.bankstown.nsw.gov.au

Part of any approval will require the person or company carrying out the work to carry public liability insurance to a minimum value of ten million

dollars. Proof of the policy is to be provided to Council prior to commencing any work approved by the Work Permit including the Road Opening Permit and must remain valid for the duration of the works.

The commencement of any works on public land, including the footway or public road, may incur an on the spot fine of not less than \$1100 per day that work continues without a Works Permit and/or a Roadway/Footpath Building Occupation Permit.

All conditions attached to the permit shall be strictly complied with prior to occupation of the development. Works non-conforming to Council's specification (includes quality of workmanship to Council's satisfaction) shall be rectified by the Council at the applicant's expense.

- 26) The route for transportation to and from the development site of bulk and excavation materials shall generally be by the shortest possible route to the nearest "regional road", with every effort to avoid school zones on public roads. The applicant shall nominate the route for approval by Council prior to commencement of any work on the site. An Agreement to Council's satisfaction, signed by the applicant/owner specifying the approved route and acknowledging responsibility to pay Council for damages to public property adjacent to the site shall be lodged with Council prior to release of any Construction Certificate. All damage must be rectified upon completion of work.
- 27) Prior to the issue of any Construction Certificate a design verification from a qualified designer shall be submitted to the Principal Certifying Authority. The design verification is a statement in which the qualified designer verifies that the development as shown in the plans and specifications in respect of which the Construction Certificate was issued, having regard to the design quality principles set out in Part 2 of SEPP No. 65.
- 28) The development is to be carried out in accordance with the commitments shown on the BASIX Certificate. The BASIX commitments approved with this Development Application are to be reflected in the Construction Certificate plans and specifications. Any proposed changes to the BASIX commitments after the Construction Certificate has been issued will require an updated BASIX Certificate and a new Construction Certificate.
- 29) For internal driveways with a gradient exceeding 10% (1 in 10), longitudinal profiles of all vehicular driveways and ramps shall be submitted for approval by the Principal Certifying Authority (PCA) prior to the issue of the Construction Certificate. The maximum grade of the driveway/ramp shall not exceed **25%** and shall comply with AS 2890.1. The profile shall be drawn at a reduction ratio of 1 to 25 vertical and horizontal and shall be related to the datum used for the issue of the footway design levels and shall also show the road centre line levels, Council issued footway design levels and gutter levels. Council's Car Clearance Profile in Council's Development Engineering Standards, (Plan No. S 006) shall be used to design the profile.

- 30) Sight distance triangle for pedestrians at the exit driveway shall comply with Figure 3.3 of AS2890.1-2004.

CONDITIONS TO BE SATISFIED PRIOR TO CONSTRUCTION

- 31) Permission is granted for the demolition of structures currently existing on the property, subject to strict compliance with the following: -

- a) The developer is to notify adjoining residents seven (7) working days prior to demolition. Such notification is to be clearly written on A4 size paper giving the date demolition will commence and be placed in the letterbox of every premises (including every residential flat or unit, if any) either side, immediately at the rear of, and directly opposite the demolition site.
- b) Written notice is to be given to Canterbury-Bankstown Council for inspection prior to demolition. Such written notice is to include the date when demolition will commence and details of the name, address, business hours and contact telephone number and licence number of the demolisher. The following building inspections shall be undertaken by Canterbury-Bankstown Council:
 - (i) A *precommencement* inspection shall be carried out by Council when all the site works required as part of this consent are installed on the site and prior to demolition commencing.
 - (ii) A *final* inspection shall be carried out by Council when the demolition works have been completed to ensure that the site is left in a satisfactory manner, in accordance with the conditions of this consent.

NOTE: Payment of an inspection fee at Council's current rate will be required prior to each inspection. Council requires 24 hours notice to carry out inspections. Arrangements for inspections can be made by phoning **9707 9410, 9707 9412 or 9707 9635.**

- c) Prior to demolition, the applicant must erect a sign at the front of the property with the demolisher's name, license number, contact phone number and site address.
- d) Prior to demolition, the applicant must erect a 2.4m high temporary fence or hoarding between the work site and any public place. Access to the site shall be restricted to Authorised Persons Only and the site shall be secured against unauthorised entry when the building work is not in progress or the site is otherwise unoccupied. Where demolition is to occur within 3m of a public place a Work Permit application for the construction of a Class A or Class B hoarding shall be submitted to Council for approval.

- e) The demolition plans must be submitted to the appropriate Sydney Water Office to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements. If the development complies with Sydney Water's requirements, the demolition plans will be stamped indicating that no further requirements are necessary.
- f) Demolition is to be carried out in accordance with the appropriate provisions of Australian Standard AS2601-2001.
- g) The hours of demolition work shall be limited to between 7.00am and 6.00pm on weekdays, 7.00am and 1.00pm on Saturdays and no work shall be carried out on Sundays and public holidays, and weekends (Saturdays and Sundays) adjacent to public holidays.
- h) Where materials containing asbestos cement are to be removed, demolition is to be carried out by licensed contractors who have current Workcover Accreditation in asbestos removal.
- i) Hazardous or intractable wastes arising from the demolition process shall be removed and disposed of in accordance with the requirements of WorkCover NSW and the NSW EPA 'Environmental Guidelines: Assessment, Classification and Management of Liquid and Non-Liquid Wastes 2004'.
- j) Demolition procedures shall maximise the reuse and recycling of demolished materials in order to reduce the environmental impacts of waste disposal.
- k) During demolition, the public footway and public road shall be clear at all times and shall not be obstructed by any demolished material or vehicles. The public road and footway shall be swept (NOT hosed) clean of any material, including clay, soil and sand. (NOTE: If required, Council will clean the public road/footway at the applicant's expense). On the spot fines may be levied by Council against the demolisher and or owner for failure to comply with this condition.
- l) All vehicles leaving the site with demolition materials shall have their loads covered and vehicles shall not track soil and other material onto the public roads and footways and the footway shall be suitably protected against damage when plant and vehicles access the site. All loading of vehicles with demolished materials shall occur on site.
- m) The burning of any demolished material on site is not permitted and offenders will be prosecuted.
- n) Care shall be taken during demolition to ensure that existing services on the site (ie. sewer, electricity, gas, phone) are not damaged. Any damage caused to existing services shall be repaired by the relevant authority at the applicant's expense.

- o) Suitable erosion and sediment control measures shall be erected prior to the commencement of demolition works and shall be maintained at all times.
 - p) Prior to the demolition of any building constructed before 1970, a Work Plan shall be prepared and submitted to Council in accordance with Australian Standard AS2601-2001 by a person with suitable expertise and experience. The Work Plan shall outline the identification of any hazardous materials, including surfaces coated with lead paint, method of demolition, the precautions to be employed to minimise any dust nuisance and the disposal methods for hazardous materials.
- 32) The building / subdivision work in accordance with the development consent must not be commenced until:
 - a. a construction certificate for the building / subdivision work has been issued by the council or an accredited certifier, and
 - b. the person having benefit of the development consent has:
 - i. appointed a principal certifying authority for the building / subdivision work, and
 - ii. notified the principal certifying authority that the person will carry out the building work as an owner-builder, if that is the case, and
 - c. the person having the benefit of the development consent, if not carrying out the building work as an owner-builder, has:
 - i. appointed a principal contractor for the building work who must be the holder of a contractor licence if any residential building work is involved, and
 - ii. notified the principal certifying authority of any such appointment, and
 - iii. unless the person is the principal contractor, notified the principal contractor of any critical stage inspections and other inspections that are to be carried out in respect of the building work, and
 - d. the person having the benefit of the development consent has given at least 2 days' notice to the council of the person's intention to commence the building / subdivision work.
- 33) Prior to the commencement of works, a dilapidation report shall be prepared by the developer and a copy provided to directly adjoining property owners to the north, south and west of the subject site. The report

must clearly identify the condition of existing structures on adjoining properties prior to the commencement of works. All care shall be taken during the construction process to ensure adjoining structures are protected, and should any change in condition occur from that recorded in the dilapidation report, the rectification of such shall be at full cost to the developer of the subject site.

- 34) Existing trees within the vicinity of the construction works or paths of travel for construction vehicles accessing the development that are to be retained shall be protected with temporary fencing of a style non injurious to tree roots, placed 2m from the trunk base of the existing tree to prevent damage during construction, and retained in accordance with Council's Tree Preservation Order. There is to be no stockpiling of materials within the 2m fenced zone.
- 35) Suitable erosion and sediment control measures shall be erected in accordance with the plans accompanying the Construction Certificate prior to the commencement of construction works and shall be maintained at all times.
- 36) Council warning sign for Soil and Water Management must be displayed on the most prominent point of the site, visible to both the street and site works. The sign must be displayed throughout the construction period.
- 37) Prior to the commencement of work, the applicant must provide a temporary on-site toilet if access to existing toilets on site is not adequate.
- 38) A section 73 compliance certificate under the Sydney Water Act 1994 must be obtained from Sydney Water Corporation. Make early application for the certificate, as there may be water and sewer pipes to be built and this can take some time. This can also impact on other services and building, driveway or landscape design.

Application must be made through an authorised Water Servicing Coordinator. For help either visit www.sydneywater.com.au > Building and Developing > Developing your Land > Water Servicing Coordinator or telephone 13 20 92.

- 39) Prior to the commencement of work, a fence must be erected around the area of the works, except where an existing 1.8m high boundary fence is in good condition and is capable of securing the area. Any new fencing shall be temporary (such as cyclone wire) and at least 1.8m high. All fencing is to be maintained for the duration of construction to ensure that the work area is secured.

Where the work is located within 3.6m of a public place then a Type A or Type B hoarding must be constructed appropriate to the works proposed. An application for a Work Permit for such hoarding must be submitted to Council for approval prior to the commencement of work.

- 40) A sign shall be displayed on the site indicating the name of the person responsible for the site and a telephone number of which that person can be contacted during and outside normal working hours or when the site is unattended.
- 41) In the case of residential building work for which the Home Building Act 1989 requires there to be a contract of insurance in force in accordance with Part 6 of the Act, that such a contract of insurance is in force before any building work authorised to be carried out by the consent commences.
- 42) Residential building work within the meaning of the Home Building Act 1989 must not be carried out unless the principal certifying authority for the development to which the work relates (not being the council) has given the council written notice of the following information:
- a. in the case of work for which a principal certifying is required to be appointed:
 - i. the name and licence number of the principal contractor, and
 - ii. the name of the insurer by which the work is insured under Part 6 of the Act,
 - b. in the case of work to be done by an owner-builder:
 - i. the name of the owner-builder, and
 - ii. If the owner-builder is required to hold an owner-builder permit under that Act, the number of the owner-builder permit.

If arrangements for doing the residential building work are changed while the work is in progress so that the information notified becomes out of date, further work must not be carried out unless the principal certifying authority for the development to which the work relates (not being the council) has given the council written notice of the updated information.

- 43) A sign must be erected in a prominent position on any site on which building work, subdivision work or demolition work is being carried out:
- a. showing the name, address and telephone number of the principal certifying authority for the work, and
 - b. showing the name of the principal contractor (if any) for any building work and a telephone number on which that person may be contacted outside working hours, and
 - c. stating that unauthorised entry to the work site is prohibited.

Any such sign is to be maintained while the building work, subdivision work or demolition work is being carried out, but must be removed when the work has been completed.

CONDITIONS TO BE SATISFIED DURING CONSTRUCTION

- 44) The hours of site works shall be limited to between 7.00am and 6.00pm on weekdays and 7.00am and 1.00pm on Saturdays. No work shall be carried out on Sundays and public holidays, and weekends (Saturdays and Sundays) adjacent to public holidays.
- 45) The building work must be carried out in accordance with the requirements of the Building Code of Australia.
- 46) Prior to the ground floor slab being poured, an identification report by a Registered Surveyor must be submitted to the principal certifying authority verifying that the proposed buildings finished ground floor level and siting to the property boundaries conforms to the approved plans.
- 47) All Civil and Hydraulic engineering works on site must be carried out in accordance with Council's Development Engineering Standards. All Civil and Hydraulic engineering works associated with Council's assets and infrastructure must be carried out in accordance with Council's Work Permit requirements and to Council's satisfaction.
- 48) All excavations and backfilling must be executed safely and in accordance with the relevant Australian Standards.
- 49) If soil conditions require it, retaining walls or other approved methods of preventing movement of the soil must be provided, and adequate provisions must be made for drainage. Separate approval may be required for retaining walls should they be required.
- 50) If the development involves an excavation that extends below the level of the base of the footings of a building on adjoining land, the person having the benefit of the development consent must, at the person's own expense:
 - a. protect and support the adjoining premises from possible damage from the excavation, and
 - b. where necessary, underpin the adjoining premises to prevent any such damage.
- 51) All boundary fencing behind the building line shall be replaced by a 1.8m high lapped and capped timber or sheet metal fence, or as stipulated in a flood study prepared for the site, or as determined in consultation with the adjoining property owners at the developer's expense. Fencing forward of

the building line shall be no higher than 1m unless otherwise approved by Council.

- 52) The stormwater drainage system shall be constructed in accordance with Council's Development Engineering Standards and the engineering plans and details approved by the Principal Certifying Authority (PCA). Should the developer encounter any existing, live, underground stormwater drainage pipes, which carry flow from upstream properties, the developer must maintain the stormwater flow and re-route the stormwater pipes around the subject building or structures at the developer's expense.
- 53) The wastewater from the car wash bay shall be collected and disposed of, in accordance with the requirements contained in Council's Development Engineering Standards.
- 54) A suitably qualified Professional Civil or Structural Engineer shall be engaged by the developer to carry out inspections relating to construction of internal driveways and parking areas. The work shall be carried out in accordance with the approved plans and specifications and certification from the Civil or Structural Engineer is to be provided upon completion.
- 55) If acid sulfate soils are encountered during excavation and/or construction works; all work is to cease and Bankstown City Council notified immediately. The acid sulfate soil situation is to then be evaluated by an appropriately qualified and experienced environmental consultant who has proven experience in the assessment and management of acid sulfate soils. An appropriate response is to be determined by the applicant, which is agreed to by Council, prior to re-commencement of works.
- 56) The stormwater drainage system shall be constructed in accordance with Council's Development Engineering Standards and the engineering plans and details approved by the Principal Certifying Authority (PCA). Should the developer encounter any existing, live, underground stormwater drainage pipes, which carry flow from upstream properties, the developer must maintain the stormwater flow and re-route the stormwater pipes around the subject building or structures at the developer's expense.
- 57) Prior to the commencement of work, the builder shall prepare a photographic record of the road reserve which clearly shows its condition prior to works occurring on site. For the entirety of demolition, subdivision or construction works, there shall be no stockpiling of building spoil, materials, or storage of equipment on the public road, including the footway and the road reserve shall be maintained in a safe condition at all times. No work shall be carried out on the public road, including the footway, unless a Work Permit authorised by Council has been obtained.

CONDITIONS TO BE SATISFIED PRIOR TO OCCUPATION

- 58) The occupation or use of the building must not be commenced unless an occupation certificate has been issued for the building.
- 59) A final Occupation Certificate shall not be issued until all conditions relating to demolition, construction and site works of this development consent are satisfied and Council has issued a Work Permit Compliance Certificate.
- 60) The developer shall register, on the title of the subject property, a Restriction on the Use of Land and Positive Covenant, in accordance with the standard terms for "Registration of OSD on title", as outlined in Council's Development Engineering Standards and in accordance with the appropriate provisions of the Conveyancing Act. Where subdivision is not proposed, the surveyor shall show the location of the "On-Site Stormwater Detention System" on an A4 size site plan attached to the Section 88E Instrument to be registered, on the title of the subject property, prior to the issue of the Final Occupation Certificate.

Alternatively, where subdivision is proposed, the developer shall register, on the title of the subject property, a Restriction on the Use of Land and Positive Covenant, in accordance with the standard terms for "Registration of OSD on title", as outlined in Council's Development Engineering Standards and in accordance with the appropriate provisions of the Conveyancing Act. The surveyor shall show the location of the "On-Site Stormwater Detention System" on the plan of subdivision. The developer shall submit evidence of the final registration of the Restriction and Positive Covenant on the title of the property, to Council.

- 61) Prior to the issue of any Occupation Certificate a design verification from a qualified designer shall be submitted to the Principal Certifying Authority. The design verification is a statement in which the qualified designer verifies that the development has been constructed as shown in the plans and specifications in respect of which the Construction Certificate was issued, having regard to the design quality principles set out in Schedule 1 of SEPP No. 65.
- 62) Sixty-nine (69) off-street car spaces being provided in accordance with the submitted plans.
- 63) Landscaping is to be installed in accordance with the approved landscape plan. All works and methods nominated and materials and plants specified on the approved landscape plan are to be completed prior to the issue of an occupation certificate. The landscaping shall be maintained for the life of the development.
- 64) A suitably qualified Professional Civil Engineer shall certify that the driveways, parking bays, and service areas have been constructed in accordance with the approved plans and specifications. Such Certification

shall be submitted prior to the issue of the Occupation Certificate or occupation of the site.

- 65) Lighting must be provided to the entries of the dwellings, driveways and parking areas to promote a high level of safety and security at night and during periods of low light. Lighting provided should be hooded, shielded or directed away from neighbouring dwellings to minimise glare and associated nuisances to residents.

Any lighting of the premises shall be installed in accordance with Australian Standard AS 4282 – Control of the Obtrusive Effects of Outdoor Lighting so as to avoid annoyance to the occupants of adjoining premises or glare to motorists on nearby roads. Flashing, moving or intermittent lights or signs are prohibited. The intensity, colour or hours of illumination of the lights shall be varied at Council's discretion if Council considers there to be adverse effects on the amenity of the area.

- 66) Prior to the issue of an Occupation Certificate, signage shall be erected clearly allocating storage areas within the basement to the apartments as marked on the plans. In addition signage shall clearly allocated the following car parking space to the apartments specified as they are accessed via the parking space:

Basement Level 2

- a) Car space No. 28 dedicated to apartment No. 403; and
 - b) Car space No. 29 dedicated to apartment No. 307; and
 - c) Car space No. 30 dedicated to apartment No. 303; and
 - d) Car space No. 31 dedicated to apartment No. 304; and
- 67) The premises must be readily identified from the street with the allocated house numbers. Numbering of the development without Council's written approval is not permitted. An official "house numbering" letter will be sent to the applicant indicating the proposed house numbers of the new development. Note: The house numbers of the development are subject to change depending of the type on subdivision that may occur at a later stage.
- 68) For 10 years from the date of the issue of the occupation certificate:
- a) The following units proposed to be used for the purposes of affordable housing must be used for the purposes of affordable housing:
 - Ground floor: G07
 - Level 2: 202, 205, 206, 207, 208, 209, 210 & 211
 - Level 3: 301, 302, 305, 306, 307, 308,
 - Level 4: 403 & 404
 - Level5: 503 & 504

- b) All accommodation that is used for affordable housing must be managed by a registered community housing provider.

A restriction must be registered, before the date of the issue of the occupation certificate, against the title of the property, in accordance with section 88E of the Conveyancing Act 1919, that will ensure that the requirements of this condition are met.

- 69) The Section 73 compliance certificate under the Sydney Water Act 1994 must be submitted to the principal certifying authority before occupation of the development / release of the plan of subdivision.
- 70) A Copy of the Work Permit Compliance Certificate shall be submitted to the PCA Prior to the issue of the Occupation Certificate.

USE OF THE SITE

- 71) There are to be no emissions or discharges from the premises which will give rise to an offence under the *Protection of the Environment Operations Act 1997* and *Regulations*.

In this regard, the operation of the premises and plant and equipment shall not give rise to a sound pressure level at any affected premises that exceeds the background $L_{A90, 15min}$ noise level, measured in the absence of the noise source/s under consideration by 5dB(A). The source noise level shall be assessed as an $L_{Aeq, 15min}$ and adjusted in accordance with the NSW Environment Protection Authority's Industrial Noise Policy and Environmental Noise Control Manual (sleep disturbance).

- 72) The bulk garbage and recycling bins shall be serviced by Council from the temporary bin storage room at the front of the premises as a 'wheel in, wheel back' service. The waste bin storage room located at the front of the site is to be used only for the temporary storage of the bins a maximum of twelve (12) hours prior to collection and twelve (12) hours after collection. The bins shall be stored in the basement waste storage room at all other times. A contractor shall be engaged (at no cost to Council) to manoeuvre bins back and forth from the basement on a regular basis for collection times.
- 73) All landscaping on the site shall be maintained at all times in accordance with the landscape plan.
- 74) The bin rooms are to be constructed of masonry material and fully enclosed with a roof and a roller door (or similar) to fully contain the bins in order to limit the visual impact and the potential for odours adversely impacting on the occupants of the development. Bins are to be appropriately stored within the dedicated area at all times.

SCHEDULE A: ADVICE TO APPLICANTS

Inspection of building works shall be undertaken as determined by the PCA. If Bankstown Council has been nominated as the PCA then details of inspection type and number required will be determined prior to the issue of a construction certificate.

Where a combined development consent is issued for demolition of buildings and construction of new work, a Construction Certificate must be obtained for the work, including demolition.

Also, before you dig, call "Dial before you Dig" on 1100 (listen to the prompts) or facsimile 1300 652 077 (with your street no./name, side of street and distance to nearest cross street) for underground utility services information for any excavation areas.

For further information regarding this notice please contact Kristy Bova in Development Services on 9707 9853.

Yours faithfully,

Kristy Bova
DEVELOPMENT ASSESSMENT OFFICER