Traffic Assessment Report Amendment 1 Lot 1 DP 109606 Princes Highway, Frogs Hollow

26 April 2018

Prepared for:

Sport Aviation Flight College Australia Ltd

18 Elizabeth Parade, Tura Beach

NSW 2548

Prepared by:

Tasman Engineering Consultants

Project No. S-518

Structural, Civil, Geotechnical & Environmental Engineers

ABN 870 83 813 556

Office 1, Main Street Centre, 62 Main Street, Merimbula, NSW Tel: (02) 6495-4776

Table of Contents

1.0 General	. 2
2.0 Traffic Flow Analysis	.2
2.1 Sapphire Coast Kart Club	.2
2.2 Bega District Model Club	.2
2.3 Revised Traffic Flow Analysis	.2
3.0 Headwalls and Drainage Infrastructure	. 3
4.0 Intersection Concept Design Revisions Based on 19 m Vehicle	. 3
5.0 Stage 1 Concept Design	.4
6.0 Southbound Through Lane (Reverse Curve)	.4
7.0 Formation Widening Batter Protection	.4
8.0 Trees Within the Clear Zone	.4
9.0 Safe Intersection Site Distance	.5
10.0 Flight Path Circuits and Low Flying Aircraft Crossing the Highway Alignment	. 5

APPENDICIES

Appendix A- Figures

Appendix B- Traffic Flow Analysis

1.0 General

The purpose of the updated Traffic Assessment and Concept Design is to address RMS concerns summarized in RMS correspondence to Bega Valley Shire Council dated 20 Feb 2018 RMS reference STH08/02093/03.

Specifically RMS has requested clarification and additional information in order to adequately assess the impacts the development would have on the Princes Highway. RMS is concerned that the proposed access treatments addressed in in the Traffic Assessment Report for the site dated 21-Dec-2017 and their timing may not be appropriate.

TEC has prepared a revised traffic flow analysis and determined that potential traffic volumes generated by the Sapphire Coast Kart Club (SCKC) under the approved development consent would preclude the use of a BAR BAL type intersection. The revised traffic flow analysis is addressed in detail below.

RMS has indicated that there are concerns with the suitability of the proposed CHR/AUL to cater for the ultimate traffic demands. TEC has prepared a revised CHR/AUL intersection Concept Plan and made the following revisions.

- 1. The headwalls on the existing drainage culvert within the intersection have been moved to a position outside the clear zone.
- 2. A 19 m articulated vehicle template has been used to evaluate the storage component of the CHR turn lane.
- 3. The revised plan has shown through lane widths, widened shoulder widths and offsets to property boundaries in a number of locations on the revised Concept Plan.
- 4. RMS has highlighted what appears to be a reverse curve in the proposed alignment for the Prices Highway immediately south of the proposed intersection. The revised Concept Plan shows a local widening of the formation opposite the intersection to accommodate a 19 m vehicle
- 5. The formation widening required to develop the CHR has been up dated to include a safety barrier.
- Trees which may require removal because they are either within the clear zone or have a
 potential impact on safe intersection site distance have been noted on the revised Concept
 Plan.
- 7. The safe intersection site distance has been shown in the revised Concept Plan.

A revised Concept Plan is included in Appendix A

2.0 Traffic Flow Analysis

Current traffic which utilizes the existing access to the Frogs Hollow airfield consists of traffic to and from the airstrip by the airfield owner, the Bega District Model Club (BDMC) and the SCKC.

2.1 Sapphire Coast Kart Club

According to the SCKC Secretary Stage 2 of the approved consent – the Go-Kart Hire proposal- has not been achieved to date. It is unlikely to eventuate due to the facility upgrade that would be required, which the committee are not in a financial position to undertake. Further, there has not been sufficient demand or interest to justify moving forward with this proposal.

SCKC stages club race events on Sundays which are expected to generate traffic flow up to approximately 30 vehicles. SCKC may also stage kart practice days on Saturday which would also be expected to generate approximately 30 vehicles.

The SCKC Secretary has indicated that were the facility to operate as a hire cart facility approximately 10 vehicles per day may be expected to access the SCKC during peak season. While Condition 2 of the development consent 1998.1165 as amended on 8 may 2012 indicates hours of operation for the proposed hire cart facility as Mon to Sun 8 am - 8 pm it is presumed that were the SCKC facilities to operate as a hire cart facility the customerl traffic would arrive after 9 am.

2.2 Bega District Model Club

Members of the BDMC have also been interviewed regarding their utilization of the access. The BDMC uses the airfield on Wednesdays and Sundays between approximately 8 am and 12 noon. Up to 12 vehicles may access the site.

The BDMC facilities at the Frogs Hollow Airfield currently do not have development consent, according to Council records. It is the intention of SAFC to purchase the property. Therefore existing and future tenants would be required to enter into a formal lease agreement. Additionally evidence of development consent for operation would be necessary. Therefore it has been assumed that if the SAFC was in operation the BDMC would not be operating from the site without a development application being first submitted to Council for consideration.

2.3 Revised Traffic Flow Analysis

The attached spread sheet (**Appendix B**) indicates traffic numbers by stage and allows for traffic using the access for the Kart Club. Traffic flows for the BDMC are not included in the analysis. Traffic flows for the SCKC are not included in the peak hour analysis.

RMS has indicated that a justification is required for the estimated staff numbers in each stage of the proposed development. The proposed staff numbers have been developed based on the flight instructor's experience of the numbers necessary to support the number of students in each stage. The staff numbers are consistent with staff student ratios at other flight schools such as Port Macquarie and as proposed at Kempsey. The attached spread sheet (**Appendix B**) shows that the arrival and departure of the proposed non-resident staff is staggered throughout the day. It is noted that the capacity of the intersection during the peak hour is at the upper limit of flows allowed by the warrant for a BAL/BAR. The spread sheet also shows that the contribution to traffic flows during and after Stage 2 clearly show the necessity for upgrade to a CHR/AUL intersection therefore it is proposed that the CHR/AUL intersection treatment be implemented at Stage 1.

Weekend traffic which may include a SCKC race as well as bus traffic to and from the SAFC Airfield during Stage 1 is estimated to be up to approximately 35 vehicles per day during the weekend morning peak hour. Weekend

morning peak hour right hand turn into the facility for 35 vehicles would exceed the warrant for the BAR/BAL as well as the CHR(s)/AUL(s) which supports the justification for implementing a CHR/AUL intersection treatment at Stage 1.

RMS has indicated that the practical absorption capacity calculations be up dated as part of the revised traffic flow analysis. Practical absorption capacity has been calculated based on a CHR/AUL intersection treatment. **Table 1** summarises the practical absorption capacity for the intersection for the morning peak hour traffic entering the facility and the afternoon peak hour traffic leaving the facility.

Table 1 – Intersection Absorption Capacity								
Stage 1	Qm (v/hr)	Qt (v/hr)	ta (sec)	tf (sec)	Cp(v/hr)			
RH in	381	8	4	2	1046			
RH out	489	4	14	3	174			
LH out	187	5	14	3	501			
Stage 9								
RH in	561	17	4	4	899			
RH out	715	18	14	3	79			
LH out	272	17	14	3	373			

Qm = major stream flow. Qt = minor stream (turn) flow. ta= critical acceptance gap, tf= follow up headway, RTA Road Design Guide, Section 4 Intersections At Grade, Table A4.1. Cp= Practical Absorption Capacity, RTA Road Design Guide, Section 4 Intersections At Grade, Figure A4.1.

The morning right hand turn into the facility is opposed by the northbound traffic, the south bound major flow has not been included in the calculation because the CHR intersection treatment allows the RHT traffic flow to be isolated of the major stream flow.

3.0 Headwalls and Drainage Infrastructure

Batter slopes adjacent to the intersection in the area of the existing drainage infrastructure were determined to be in the range of 6:1 (H:V) to flat. AGRD Part 6 Table 4.1 lists clear zone off sets from the edge of the travel way. In this case for a 100 kph speed zone and an ADT of 3676 vehicles, the edge distance would be 10 m. The revised Concept Plan shows the proposed location of headwalls and drainage infrastructure in the intersection which have been relocated beyond the 10 m clear zone.

4.0 Intersection Concept Design Revisions Based on 19 m Vehicle

The RMS 19 m vehicle template has been applied to the proposed CHR/AUL intersection and the geometry of the intersection has been revised.

Storage has been re-evaluated for the CHR turn treatment based on the method outlined in AGTM Part 3 resulting in one storage space for a 19 m vehicle.

The length of the deceleration lane has been re-evaluated using AGRD Part 4A, based on a 100 kph speed zone. The resulting deceleration length is 155 m including the taper. The taper length of 32 m was calculated based on a 3.5 m lane with and a design speed of 100 kph using AGRD Part 4 Figure A30. The total length of the CHR deceleration lane including storage is 174 m and has not been reduced for slope. Consideration of slope would shorten the deceleration distance by 10 % and would be incorporated in the final design

Similarly the deceleration and taper lengths for the AUL treatment have been re-evaluated resulting in a deceleration length of 186 m which has been factored up by 20% to account for the down-hill approach grade of 3-4%. The taper length of 32 m was calculated based on a 3.5 m lane with and a design speed of 100 kph using AGRD Part 4A requirements for a rural AUL turn treatment.

The revised concept design has modified outside edge of the south bound lane to accommodate a 19m vehicle executing a right hand turn on to the Prince's Highway. The edge line modification will also involve changes to the edge of pavement, the drain as well as the cut bank.

5.0 Stage 1 Concept Design

The Concept Design Plan for the CHR/AUL for Stage 1 of the proposed development has been revised to show:

Shoulder width at a number of locations;

Edge of pavement;

Through Lane width at a number of locations;

Width of widened shoulders at a number of locations; and

Offset of proposed works to property boundary in area of proposed works.

6.0 Southbound Through Lane (Reverse Curve)

RMS has requested clarification regarding the eastern edge line of the south bound through lane which appears to show a reverse curve. The intent of the previous design was not to show a reverse curve but to preserve the 3.5 m through lane width around the widest point of the proposed median. The concept plan has been revised to show edge line and shoulder extended to the east in order to accommodate the 19m vehicle turning template as well as the 3.5 m through lane width.

7.0 Formation Widening Batter Protection

RMS has indicated that the formation widening on the northern approach to the intersection may require batter protection. The concept plan has been revised to show a barrier along the proposed fill batter.

8.0 Trees Within the Clear Zone

RMS has indicated that a number of trees within the clear zone were not shown on the previous plan and may require protection or removal. The Concept Plan has been revised to show the approximate location of trees which would require protection or removal.

9.0 Safe Intersection Site Distance

The revised concept plan shows the required safe intersection site distance in both directions from the intersection.

10.0 Flight Path Circuits and Low Flying Aircraft Crossing the Highway Alignment.

RMS has raised the matter of potential driver distraction by aircraft using circuits 09 and 27 which cross the highway at an elevation of 0 - 500.


A height of 500 ft above ground level is reached in the departure manoeuvre prior to commencement of the turn" crosswind" and is maintained in the approach manoeuvre at the end of the turn to "base" leg. It is also noted that many major and regional airports are located adjacent to or in the vicinity of highways, where the potential for driver distraction might also exist. Such airports are used by larger aircraft than that proposed at Frog Hollow and the highways experience greater traffic volumes than the Princes Highway at Frogs Hollow.


In response to these concerns it is considered that standard warning signage for potential low flying aircraft could be erected at an appropriate location on the Princes Highway. Details would be provided to RMS satisfaction as part of the final intersection design.


Tasman Engineering Consultants


Austin F. Legler, CP. Eng.


Appendix A- Figures














Appendix B- Traffic Flow Analysis

	vised Week Day Traffic Schedule 26-4-		ha	T-1-1 -0-1									
Time	Traffic category	Type (in/out)	hours	Total vehicles at each stage									
6 am - 7am				1	2	3	4	5	6	7	8	9	
o am 7am	Squadron Leaders Morning	In	7:00 am-5:00 pm	6	9	12	15	18	21	24	27	30	
	Squadron Assistants Morning	In	7:00 am-5:00 pm	6	9	12 4	15	18	21	24	27 4	30	
	Kitchen/café/giftshop staff	In	6:00 am- 8:00 pm two shifts breckfast & lunch then dinner	4	4	4	4	4	4	4	4	4	
7 am - 8 am	Chief flight insructor	In	7:30 am-4:30 pm	2	3	4	5	6	7	8	9	10	
	Flight instructors	In	7:30 am-4:30 pm	8	12	16	20	24	28	32	36	40	
	Ground staff Food service	In	8:00 am - 4:00 pm	8	8	12	12 2	12	12	12	12	12 2	
	Water Service	In In	Daily deliveries Weekly deliveries	2 1	2 1	2 1	1	2 1	2 1	2 1	2 1	1	
8 am-9 am	Management	In	9:00am-5 :00 pm	4	4	4	4	4	4	4	4	4	
	Aviation english instructors	In	8:30 am-4:00 pm	4	6	8	10	12	14	16	18	20	
	Admin & support	In .	9:00 am- 5:00 pm	3	3	5	5	5	5	5	5	5	
	Food service Water Service	Out Out	Daily deliveries from Bega Weekly deliveries from Bega	2	1	1	2	1	2	1	2	2	
	Fuel Service	In	Weekily deliveries from Bega	1	1	1	1	1	1	1	1	1	
	Maintenance Service	in	Variable	1	1	1	1	1	1	1	1	1	
			Total turn traffic	16	18	22	24	26	28	30	32	34	
			Qtr From Bega Qtl From Merimbula	8 8	9 9	11 11	12 12	13 13	14 14	15 15	16 16	17 17	
			Qr North bound	373	386	406	426	447	470	493	518		C 15 Oct assessment report
			QI south bound	165	172	180	189	199	209	219	230	242 TEC	C 15 Oct assessment report
			Qm (RHT)= Qtl+Qr	381	395	417	438	460	484	508	534		njor stream flow
			Qm (LHT)= Ql Warrant AGRD Part 4 p 98	165 CHR(s)/AUL(s) CHR(s)/A	172 UL(s) CHI	180 R/AUL CH	189 R/AUL CH	199 R/AUL CH	209 IR/AUL CH	219 IR/AUL CH	230 IR/AUL CI		ajor stream flow
9 am -10 am	Fuel Service	Out	Weekily deliveries return to Bega	1	1	1	1	1	1	1	1	1	
	Maintenance Service	Out Out	Variable return to Bega	1	1	1	1	1	1 1	1	1 1	1	
	Go cart hire track	In	8:00 am-8:00 pm	10	10	10	10	10	10	10	10	10	
	Driver education	In	9:00 am- 5:00 pm	12	12	12	12	12	12	12	12	12	
10 am-11 am	Flight theory instructors	In	8:30 am-4:00 pm	2	3	4	5	6	7	8	9	10	
11 am-12 pm													
1200 100													
12pm-1pm	Squadron leaders Morning	Out	7:00 am-5:00 pm	6	9	12	15	18	21	24	27	30	
	Squadron leaders afternoon	in	7:00 am-5:00 pm	6	9	12	15	18	21	24	27	30	
	Squadron Assistants Morning Squadron Assistants Afternoon	Out In	7:00 am-5:00 pm 7:00 am-5:00 pm	3 3	5 4	6 6	8 7	9 9	10 11	12 12	14 13	15 15	
4 2	oquadi om rissistantes ritternison		, loo am stoe pm	Š	·	v	•	J			13	13	
1pm-2 pm													
2 pm-3 pm													
3 pm-4 pm	Kitchen/café/giftshop staff	In	6:00 am- 8:00 pm two shifts breckfast & lunch then dinner	4	4	4	4	4	4	4	4	4	
4 pm- 5 pm	1/2 Ground staff	Out	8:00 am - 4:00 pm	4	4	6	6	6	6	6	6	6	
	Flight theory instructors	Out	8:30 am-4:00 pm	1	2	3	4	5	6	7	8	9	
	Aviation english instructors	Out	8:30 am-4:00 pm	4	6	8	10	12	14	16	18	20	
			Total turn traffic	9	12	17	20	23	26	29	32	35	
			Qtl Qtr	5 4	6 6	8 9	10 10	11 12	13 13	14 15	16 16	17 18	
			Qr Merimbula	187	193	203	213	224	235	247	259	272	
			QI Bega	302	315	331	347	365	383	402	422	443	
			Qtl+Ql Qtr+Qr	307	321	339 212	357 223	376 236	396 248	416 262	438 275	460 290	
			Qtr+Qr Qm (RHT)= Ql+Qr	191 489	199 508	534	560	589	618	649	681	715	
			Qm (LHT)= Qtl	187	193	203	213	224	235	247	259	272	
			Warrant AGRD Part 4 p 98	CHR/AUL CHR/AUL	. CHI	R/AUL CH	R/AUL CH	R/AUL CH	IR/AUL CH	IR/AUL CH	IR/AUL CI	HR/AUL	
5 nm 0 nm	Squadron leaders	Out		12	18	24	20	26	42	48	54	60	
5 pm-8 pm	Squadron leaders Squadron Assistants	Out		12 6	18 9	24 12	30 15	36 18	42 21	48 24	54 27	30	
	Management	Out		4	4	4	4	4	4	4	4	4	
	Admin & support	Out		3	3	5	5	5	5	5	5	5	
	Gocart hire track Driver education	Out Out		10 12	10 12	10 12	10 12	10 12	10 12	10 12	10 12	10 12	
	Chief flight insructor	Out		2	3	4	12 5	6	12 7	8	9	10	
	Flight instructors	Out		8	12	16	20	24	28	32	36	40	
	1/2 Ground staff	Out	7.00 0.00	4	4	6	6	6	6	6	6	6	
	Recreational bus Recreational bus	Out In	7:00 pm- 9:00 pm 7:00 pm- 9:00 pm	2 2	2 2	2 2	2 2	2 2	2 2	2 2	2 2	2 2	
			p p	_	_	-	-	_	-	-	_	-	