

architecture

SCHEDULE 3 STANDARDS CONCERNING ACCESSIBILITY AND USEABILITY FOR HOSTELS AND SELF-CONTAINED DWELLINGS

Standards	Compliance
Part 1 Standards applying to hostels and self-contained dwellings	a stad
1 Application of standards in this Part	noted
The standards set out in this Part apply to any seniors housing that consists of	
hostels or self-contained dwellings. 2 Siting standards	
2 Sitting Standards	
(1) Wheelchair access If the whole of the site has a gradient of less than 1:10, 100% of the dwellings must have wheelchair access by a continuous accessible path of travel (within the meaning of AS 1428.1) to an adjoining public road.	Complies. Path of travel has been designed to AS1428.1
 (2) If the whole of the site does not have a gradient of less than 1:10: (a) the percentage of dwellings that must have wheelchair access must equal the proportion of the site that has a gradient of less than 1:10, or 50%, whichever is the greater, and (b) the wheelchair access provided must be by a continuous accessible path of travel (within the meaning of AS 1428.1) to an adjoining public road or an internal road or a driveway that is accessible to all residents. Note. For example, if 70% of the site has a gradient of less than 1:10, then 70% of the dwellings must have wheelchair access as required by this subclause. If more than 50% of the site has a gradient greater than 1:10, development for the purposes of seniors housing is likely to be unable to meet these requirements. 	Complies. A direct and compliant access path to the Pacific Highway has been provided.
(3) Common areas Access must be provided in accordance with AS 1428.1 so that a person using a wheelchair can use common areas and common facilities associated with the development.	Compliant access to common areas has been provided.
3 Security	
Pathway lighting: (a) must be designed and located so as to avoid glare for pedestrians and adjacent dwellings, and (b) must provide at least 20 lux at ground level.	Pathway lighting will comply with this standard.
4 Letterboxes	
Letterboxes: (a) must be situated on a hard-standing area and have wheelchair access and circulation by a continuous accessible path of travel (within the meaning of AS 1428.1), and (b) must be lockable, and (c) must be located together in a central location adjacent to the street entry or, in the case of self-contained dwellings, must be located together in one or more central locations adjacent to the street entry.	Complies. Letterboxes are located in the main street entry lobby and are lockable.

CALDERFLOWER

architecture

E Drivete and accommodation	T
5 Private car accommodation	
If car parking (not being car parking for employees) is provided: (a) car parking spaces must comply with the requirements for parking for persons with a disability set out in AS 2890, and (b) 5% of the total number of car parking spaces (or at least one space if there are fewer than 20 spaces) must be designed to enable the width of the spaces to be increased to 3.8 metres, and (c) any garage must have a power-operated door, or there must be a power point and an area for motor or control rods to enable a power-operated door to be installed at a later date.	Complies. Car parking is in a secure Level 1 Basement. The car spaces have been designed to AS 2890.
6 Accessible entry	
Every entry (whether a front entry or not) to a dwelling, not being an entry for employees, must comply with clauses 4.3.1 and 4.3.2 of AS 4299.	Complies. Entry to the units is from a common lobby compliant to AS 4299 Adaptable Housing.
7 Interior: general	
 (1) Internal doorways must have a minimum clear opening that complies with AS 1428.1. (2) Internal corridors must have a minimum unobstructed width of 1,000 millimetres. (3) Circulation space at approaches to internal doorways must comply with AS 1428.1. 	Complies. Interior doorways and circulation spaces are compliant to AS 1428.1.
8 Bedroom	
At least one bedroom within each dwelling must have: (a) an area sufficient to accommodate a wardrobe and a bed sized as	
follows: (i) in the case of a dwelling in a hostel—a single-size bed, (ii) in the case of a self-contained dwelling—a queen-size bed,	
and (b) a clear area for the bed of at least: (i) 1,200 millimetres wide at the foot of the bed, and (ii) 1,000 millimetres wide beside the bed between it and the wall, wardrobe or any other obstruction, and (c) 2 double general power outlets on the wall where the head of the bed is likely to be, and	Complies. Main bedrooms are designed for a queen size bed with required clear areas.
 (d) at least one general power outlet on the wall opposite the wall where the head of the bed is likely to be, and (e) a telephone outlet next to the bed on the side closest to the door and a general power outlet beside the telephone outlet, and (f) wiring to allow a potential illumination level of at least 300 lux. 	Power and telephone outlets will be compliant, and the wiring will allow illumination level of at least 300 lux.
9 Bathroom	
At least one bathroom within a dwelling must be on the ground (or main) floor and have the following facilities arranged within an area that provides for circulation space for sanitary facilities in accordance with AS 1428.1:	Complies. Bathroom in each unit has been designed to AS 1428.1.
(a) a slip-resistant floor surface,(b) a washbasin with plumbing that would allow, either immediately or in the future, clearances that comply with AS 1428.1,	



architecture

(c) a shower that complies with AS 1428.1, except that the following must be	
accommodated either immediately or in the future:	
(i) a grab rail,	
(ii) portable shower head,	
(iii) folding seat,	
(d) a wall cabinet that is sufficiently illuminated to be able to read the labels of items	
stored in it,	
(e) a double general power outlet beside the mirror.	
10 Toilet	
dwelling must have at least one toilet on the ground (or main) floor and be a visitable	Complies. Bathroom in each unit has
toilet that complies with the requirements for sanitary facilities of AS 4299.	been designed to AS 1428.1.
11 Surface finishes	Complies. Balconies and external paved
	areas will have slip resistance rating
Balconies and external paved areas must have slip-resistant surfaces.	compliant to AS 1428.1
Note. Advise regarding finishes may be obtained from AS 1428.1.	p
12 Door hardware	
Door handles and hardware for all doors (including entry doors and other external	Complies. Door handles and hardware
doors) must be provided in accordance with AS 4299.	will comply with AS 4299.
13 Ancillary items	
Switches and power points must be provided in accordance with AS 4299.	Complies. Switches and power points will
Omitorios ana ponor pointo mast so provided in accordance mitrino 4255.	comply with AS 4299.
Part 2 Additional standards for salf contained dwellings	Comply Will A3 4299.
Part 2 Additional standards for self-contained dwellings	
14 Application of standards in this Part	
The standards set out in this Part apply in addition to the standards set out in Part 1 to	Noted.
any seniors housing consisting of self-contained dwellings.	
15 Living room and dining room	
(1) A living room in a self-contained dwelling must have:	Complies. Living and dining rooms
(a) a circulation space in accordance with clause 4.7.1 of AS	comply with AS 4299.
, ,	Comply with AG 4299.
4299, and	
(b) a telephone adjacent to a general power outlet.	
(2) A living room and dining room must have wiring to allow a potential	
illumination level of at least 300 lux.	
16 Kitchen	
A kitchen in a self-contained dwelling must have:	
j	
(a) a circulation space in accordance with clause 4.5.2 of AS 4299, and	Complies. Kitchens comply with AS 4299.
	Compiles. Ritoriens comply with AC 4233.
(b) a circulation space at door approaches that complies with AS 1428.1,	
and (a) the following fittings in accordance with the relevant subslavess of	
(c) the following fittings in accordance with the relevant subclauses of	
clause 4.5 of AS 4299:	
(i) benches that include at least one work surface at least 800	
millimetres in length that comply with clause 4.5.5 (a),	
(ii) a tap set (see clause 4.5.6),	
(ii) a tap set (see clause 4.5.6),	
(ii) a tap set (see clause 4.5.6), (iii) cooktops (see clause 4.5.7), except that an isolating switch	

CALDERFLOWER

architecture

Complies. Units are on a single floor on each level.
Complies. A lift complying with BCA has been provided.
Complies. Laundry in a form of a closet has been provided for each unit. It contains a washing machine and a dryer.
Complies. All units have compliant linen storage.
Complies A garbage chute has been provided to the lift lobbies of each floor which collects the waste in the Level 1
Basement.