PROPOSED SERVICES THE LOCATION AND EXTENT OF PROPOSED SERVICES IS

WARNING

BEWARE OF UNDERGROUND SERVICES THE LOCATIONS OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.



HORNSBY SHIRE COUNCIL, MR548 MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH

392 GALSTON ROAD, GALSTON **GALSTON GRANGE DEVELOPMENT**

CODE	NAME	
GE	GENERAL	
RD	ROAD ALIGNMENT AND DETAIL	
υr	UTILITIES	
SM	STORMWATER MANAGEMENT	
PV	PAVEMENT	
RF	ROADSIDE FURNITURE AND LINEMARKING	
LS	LANDSCAPING	
RC	ROAD CROSS SECTIONS	
PW	PROPERTY WORKS	
SO	SETOUT DETAILS	
440	MOOFILANGOUG	

SHEET INDEX

DIAL BEFORE
YOU DIG

MID DURAL ROAD OF WORK

LOCALITY PLAN

COPYRIGHT ACKNOWLEDGEMENT

DETAILED DESIGN

DDAWING LIST

DRAWING LIST	
DS2016-002140-DD-GE-0200 DS2016-002140-DD-GE-0201 DS2016-002140-DD-GE-0201A DS2016-002140-DD-GE-0202	COVER SHEET, INDEX & LEGEND GENERAL NOTES SHEET 1 OF 2 GENERAL NOTES SHEET 2 OF 2 SITE PLAN
DS2016-002140-DD-RD-0203 DS2016-002140-DD-RD-0204	ROAD & PAVEMENT DETAIL PLAN LONGITUDINAL SECTION
DS2016-002140-DD-RC-0205 DS2016-002140-DD-RC-0206 DS2016-002140-DD-RC-0207 DS2016-002140-DD-RC-0208	CROSS SECTIONS SHEET 1 OF 4 CROSS SECTIONS SHEET 2 OF 4 CROSS SECTIONS SHEET 3 OF 4 CROSS SECTIONS SHEET 4 OF 4
DS2016-002140-DD-PV-0214 DS2016-002140-DD-PV-0215	TYPICAL DETAILS SHEET - SHEET 1 OF 2 TYPICAL DETAILS SHEET - SHEET 2 OF 2
DS2016-002140-DD-RF-0216	LINE MARKING AND SIGNAGE PLAN
DS2016-002140-DD-SO-0217 DS2016-002140-DD-SO-0218	SETOUT PLAN SHEET 1 OF 2 SETOUT PLAN SHEET 2 OF 2
DS2016-002140-DD-MS-0219 DS2016-002140-DD-MS-0220 DS2016-002140-DD-MS-0221 DS2016-002140-DD-MS-0222	TURNING PATHS PLAN CONSTRUCTION VEHICLE TURNING PATHS RETAINING WALL PLAN & SETOUTS RETAINING WALL LONG SECTIONS

DS2016-002140-DD-SM-0200 DRAINAGE PLAN

DS2016-002140-DD-SM-0201 CATCHMENT PLAN DS2016-002140-DD-SM-0209 DRAINAGE LONGITUDINAL SECTIONS DS2016-002140-DD-SM-0210 DRAINAGE PIT SCHEDULE

Transport Roads & Maritime Services These plans are accepted for

DESCRIPTION PROPOSED WORKS KERB INLET PIT (KIP) o 🗎 🗐 GRATED PIT (GP) JUNCTION PIT (JP) xFS.207.35 FINISHED SURFACE LEVELS x BE.206.95 BULK EARTHWORKS LEVEL KERB RETURN REFERENCE NUMBER KERB AND GUTTER (STD 150mm HIGH RTA SM TYPE KERB RTA SF TYPE KERB RADIUS TO FACE OF KERR DIMENSION (UNITS - METRES) PROPOSED GUARD RAI EXISTING WORKS GAS MAIN SEWER MAIN WATER MAIN TELECOMMUNICATION CABLES SERVICE TO BE DECOMISSIONE ABBREVIATIONS INVERT LEVEL FINISHED FLOOR LEVEL PRAM RAMP CHAINAGE UNLESS NOTED OTHERWISI

GENERAL LEGEND

FOR CONSTRUCTION

									1 011 00110	11100110	/11
DRAWING FILE LOCATION / NAME X\\111403 - Geiston-Grange Retirement-Village\6BIM6_3 MHT MIE\6_3_4 MHT UD\Mid Dural Road Drawings\	NDS2016-002140-DD-GE-0200.dwg	LINEAR REFERENCING			PLOT BY Aseip	CLIENT		HORNSBY SHIRE COUNCIL MID DURAL ROAD ROAD WORKS IN	N ASSOCIATION WITH		А3
PREPARED BY MEINHARDT	DESIGNED	REVIEWED	VERIFIED	RMS PROJECT MANAGER NAME NOUHAD FARAH		NSW	Roads & Mantime	392 GALSTON ROAD, GALSTON GALSTON GRANGE DEVELOPMEN			
WEINTAKOT	SIGNED	SIGNED	SIGNED	TITLE PROJECT ENGINEER VALIDATION AND ACCEPTANCE	OE TUECE		Services	RMS PROJECT No. 002140	DESIGN PROJECT No. 111403	SHEET 1 OF	: 23
	TITLE CIVIL ENGINEER	TITLE ASSOCIATE DIRECTOR	TITLE ASSOCIATE	DRAWINGS AND THE DESIGN SI THEREON IS TO BE CARRIED OF	HOWN	BRANCH NAM	ME				PART 01
	DATE	DATE	DATE	SEPARATE PROCESS	UI UNDER	SECTION NA DEPARTMEN		FC FC		GE-0200	E
									© Roads a	and Maritime Se	arvices

THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL, SERVICES AND OTHER CONSULTANTS DRAWINGS THE SPECIFICATIONS AND WITH SUCH OTHER WRITTEN INSTRUCTIONS AS MAY BE ISSUED DURING THE COURSE OF THE TENDER AND CONTRACT.

IF ANY DISCREPANCY COCURS ON THE DRAWINGS OR BETWEEN DRAWINGS AND SPECIFICATION THE CONTRACTOR SHALL REFER THE DISCREPANCY TO MEINHARDT FOR WRITTEN CLARIFICATION BEFORE PROCEEDING WITH THE

3 ALL WORKMANSHIP AND MATERIALS SHALL COMPLY WITH THE RMS QA SPECIFICATION FOR ROADWORKS AND THE

RELEVANT CURRENT AUSTRALIAN STANDARDS AS APPROPRIATE.

4. ALL DIMENSIONS SHOWN SHALL BE VERIFIED ON SITE. DRAWINGS MUST NOT BE SCALED.

5. ONLY SUBSTITUTIONS APPROVED IN WRITING BY MEINHARDT SHALL BE ACCEPTED.

5. DURING CONSTRUCTION THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING ALL STRUCTURES AND WORKS IN A STABLE CONDITION AND SHALL ENSURE NO PART SHALL BE OVER STRESSED DURING CONS

PRELIMINARIES

1. THE CONTRACTOR SHALL ALLOW FOR PROVIDING MATERIALS AND WORK WHICH IS INCIDENTAL TO THE ITEMS

SPECIFIED AND WHICH WOULD BE NECESSARY TO ACHIEVE THE RESULTS REQUIRED BY THE DRAWINGS.

2. THE CONTRACTOR WILL BE DEEMED TO HAVE INSPECTED THE SITE OF THE WORKS, ASSESSED AVAILABLE ACCESS. INQUIRED INTO THE LOCATION OF AUTHORITIES UNDERGROUND ASSETS. EXAMINED THE GEOTECHNICAL REPORT AND THE NATURE OF THE GROUND AND OBTAINED THE LOCAL CLIMATE AND RAINFALL INFORMATION.

SAFETY REQUIREMENTS

THE CONTRACTOR SHALL INSURE THAT AT ALL TIMES, THE MEANS AND METHODS OF CARRYING OUT THE WORK
TO BE UNDERTRIKEN CONFORM WITH THE STANDARDS AND REQUIREMENTS OF THE OCCUPATIONAL HEALTH AND
SAFETY ACT AND ANY OTHER APPLICABLE LEGISLATION, CODES OF PRACTICE AND STANDARDS.
ALL PERSONNEL WORKING ADJACENT TO A TRAFFICABLE ROAD OF FORMATION SHALL WEAR RED SAFETY VESTS,
THE CONTRACTOR SHALL PROTECT THE PUBLIC FROM DANGERS INHERENT IN EXCAVATIONS, OBSTRUCTIONS,
WORKING PLANT AND FALLING OBJECTS. SUCH MEASURES THAT ARE TRAKEN SHALL BE ADEQUATE TO MAINTAIN
THE SAFETY OF THE PUBLIC DURING PERIODS OUTSIDE NORMAL, WORKING HOUSE ON SITE.
THE CONTRACTOR SHALL ENSURE THAT ALL TRENCH EXCAVATION FOR INSTALLATION OF PIPEWORKS, OR OTHER
WORKING DEDTER CORPORTED THAN AS METERS MIST BE CONTINUOUSLY SURGEWESTED AND THE MEMORY OF THE PUBLIC PLANT AS LETTERS AND THE THAN AS METERS AND SET OF THE PUBLIC DEPTAINS AS METERS. WORKS) OF DEPTHS GREATER THAN 1.5 METRES MUST BE CONTINUOUSLY SUPERVISED AND AT ALL TIMES BE

4. ALL WORK WITHIN ROAD RESERVES. PUBLIC PROPERTY OR PRIVATE PROPERTY - SHALL BE EXECUTED STRICTLY IN ACCORDANCE WITH THE REQUIREMENTS OF THE RELEVANT AUTHORITY OR LAND OWNER.

5 CONTRACTOR SHALL ORTAIN FROM THE RELEVANT AUTHORITIES DETAILS OF ALL EXISTING SERVICES WITHIN THE VICINITY OF THE WORKS AND SHALL BE HELD SOLELY RESPONSIBLE FOR ANY DAMAGE CAUSED TO EXISTING SERVICES DURING THE EXECUTION OF THE WORKS

SERVICES DURING THE EXECUTION OF THE WORKS. THE CONTRACTOR SHALL COMPLY WITH AND GIVE NOTICES REQUIRED BY ANY ACT OF PARLIAMENT, ORDINANCE REQUIATION OR BY-LAW OF ANY AUTHORITY HAVING JURISDICTION OVER THE WORKS AND SHALL PAY ALL FEES OR CHARGES LEGALLY DEMANDRABLE UNDER ANY SUCH ACT OF PARLIAMENT, ORDINANCE, REQUIATION OR BY-LAW. PRIOR TO WORKS, THE CONTRACTOR SHALL UNDERTAKE AN EXISTING DEFECTS INSPECTION AND REPORT TO LIST ANY EXISTING DAMAGE TO ROADS, FOOTPATHS, KERBS CROSSINGS CHANNELS NATURE STRIPS, ETC, SUCH LISTS SHALL BE PREPARED IN DUPLICATE BY THE CONTRACTOR AND A COPY SENT TO THE SUPERINTENDENT.

SITEWORKS NOTES

1. THE CONTRACTOR SHALL LIAISE DIRECTLY WITH ALL SERVICE AUTHORITIES INVOLVED AND SHALL COMPLY WITH

ALL THEIR REGULATIONS AND REQUIREMENTS.

2. ALL LEVELS SHOWN ARE TO AUSTRALIAN HEIGHT DATUM, UNLESS STATED OTHERWISE, ALL COORDINATES SHOWN

. ALL LEVELS SHOWN ARE TO AUSTRALIAN HEIGHT DATUM, UNLESS STATED OTHERWISE. ALL COORDINATES SHOWN ARE TO AUSTRALIAN MAY GRID, UNLESS STATED OTHERWISE, BASE SURVEY & SETOUT HAS BEEN SUPPLIED BY OTHERS & SHALL BE CONFRIMED ON SITE BY CONTRACTOR PRIOR TO CONSTRUCTION.

SERVICE INFORMATION SHOWN IS BASED ON PLANS SUPPLIED AND IS APPROXIMATE ONLY. ACTUAL LOCATION CAN ONLY BE DETERMINED BY EXCAVATION. THE CONTRACTOR SHALL LIAISE WITH SERVICE AUTHORITIES FOR SERVICE LOCATIONS. THE CONTRACTOR SHALL PROTECT ALL SERVICES AND SHALL RECTIFY ANY DAMAGE AT HIS EXPENSE. ALL WORKS IN PUBLIC LANDS SHALL BE TO THE APPROVAL AND SATISFACTION OF THE RELEVANT AUTHORITY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND OBTAINING RELEVANT AUTHORITY.

EXISTING SURFACE CONTOURS SHOWN ARE INTERPOLATED FROM SPOT HEIGHTS AND ARE APPROXIMATE ONLY THE CONTRACTOR MUST VERIFY ALL DIMENSIONS AND EXISTING LEVELS ON SITE PRIOR TO COMMENCEMENT OF WORK, AND REPORT ANY DISCREPANCIES TO THE SUPERINTENDENT.

7. ALL EXISTING SERVICES (INCLUDING ANY NOT SHOWN ON THE PLANS) MUST BE ACCURATELY LOCATED IN POSITION

AND LEVEL PRIOR TO ANY EXCAVATION. ANY DISCREPANCIES SHALL BE REPORTED TO THE SUPERINTENDENT. MINIMUM SERVICE CLEARANCES SHALL BE MAINTAINED FROM THE RELEVANT SERVICE AUTHORITY. 8. ALL DIMENSIONS AND SET OUTS SHOWN ARE EITHER TO FACE OF BUILDING, GRID LINES OR LIP OF KERB, UNLESS

SHOWN OTHERWISE.

9. CONTRACTOR SHALL BE ISSUED AN ELECTRONIC COPY OF THE CIVIL DETAIL PLANS IN AUTOCAD DWG FORMAT FOR SET OUT PURPOSES. ALL DIMENSIONS SHOWN ON PLAN SHALL OVER RIDE SETOUT POINTS SELECTED FROM ELECTRONIC FILE PROVIDED.

10. THE CONTRACTOR SHALL ARRANGE FOR ALL SETTING OUT BY A REGISTERED SURVEYOR.

11. THE CONTRACTOR SHALL OBTAIN ALL REGULATORY AUTHORITY APPROVALS.

12. WHERE NEW WORKS ABUT EXISTING, THE CONTRACTOR MUST ENSURE THAT A SMOOTH AND EVEN PROFILE, FREE FROM A DIRECT CONTRACTOR OF SHALL OBTAINED.

FROM ABRUPT CHANGES IS OBTAINED.
13. SAWCUT EXISTING KERBIKERS & CHANNEL AND PAVING WHERE NEW WORKS, ARE TO MATCH EXISTING WORKS,
14. BUILDING AND SITE MAINTENANCE PROGRAM IS TO INCORPORATE REGULAR FLUSHING OF ALL STORMMATER PITS,
PIPES, DOWNPIPES, SUB-SOIL DRAINS AND ASSOCIATED FITTINGS TO AVOID BLOCKAGES WITHIN THE SYSTEM.

15 ALL DISTURBED AREAS SHALL BE RESTORED TO THEIR ORIGINAL CONDITION LINESS SPECIFIED OTHERWISE 16. EXCAVATED TRENCHES SHALL BE COMPACTED TO THE SAME DENSITY AS THE ADJACENT NATURAL MATERIAL. ANY SURSIDENCES DURING THE PERIOD TO BE RECTIFIED AS DIRECTED BY THE SUPERINTENDENT

17. THE CONTRACTOR SHALL KEEP THE SITE WELL DRAINED AND COMPLETELY FREE OF STANDING WATER AT ALL

TIMES.

18. GRADE EVENLY BETWEEN FINISHED SURFACE SPOT LEVELS. (FINISHED SURFACE CONTOURS ARE SHOWN FOR CLARITY ONLY.) WHERE FINISHED SURFACE SPOT LEVELS ARE NOT SHOWN THE SURFACE SHALL BE GRADED SMOOTHLY SO THAT IT WILL DRAIN FREELY. AND TO MATCH THE LEVELS OF ADJACENT SURFACES OR STRUCTURES.

19. ANY EXISTING TREES WHICH FORW PART OF THE FINAL LANDSCAPING PLAN WILL BE PROTECTED FROM CONSTRUCTION ACTIVITIES IN ACCORDANCE WITH THE LANDSCAPE ARCHITECTS DETAILS AND/OR BY

a) PROTECTING THEM WITH BARRIER FENCING OR SIMILAR MATERIALS INSTALLED OUTSIDE THE ORIP LINE.

IN ENSIGNING THAT MOTHING IS MAILED TO THEM.

b) ENSURING THAT NOTHING IS NAILED TO THEM. PROHIBITING PAVING, GRADING, SEDIMENT WASH OR PLACING OF STOCKPILES WITHIN THE DRIP LINE

EXCEPT AS ADVISED BY A QUALIFIED ARBORIST.

20. RECEPTORS FOR CONCRETE AND MORTAR SLURRIES. PAINTS, ACID WASHINGS, LIGHT-WEIGHT WASTE MATERIALS AND LITTER ARE TO BE EMPTIED AS NECESSARY, DISPOSAL OF WASTE SHALL BE IN A MANNER APPROVED BY THE SUPERINTENDENT OR AS SPECIFIED IN THE WASTE MANAGEMENT PLAN.

PROVISION FOR TRAFFIC

DRAWING FILE LOCATION / NAME

UNLESS OTHERWISE SPECIFIED, THE CONTRACTOR SHALL MAKE PROVISION FOR TRAFFIC, IN ACCORDANCE WITH RMS QA SPECIFICATION FOR ROADWORKS OR AUSTRALIAN STANDARD AS1742 "MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES".

THE CONTRACTOR SHALL ASCERTAIN AND COMPLY WITH THE REQUIREMENTS OF THE AUTHORITY RESPONSIBLE

THE CONTRACTOR SHALL SO CONDUCT THE OPERATIONS AS TO MINIMISE OBSTRUCTION AND INCONVENIENCE TO THE PUBLIC, AND SHALL NOT HAVE UNDER CONSTRUCTION A GREATER LENGTH OR AMOUNT OF WORK THA BE MANAGED PROPERLY WITH DUE REGARD TO THE CONVENIENCE OF THE PUBLIC.

EARTHWORKS (CONTINUED)

WHEN A SURFACE IS UNABLE TO SUPPORT CONSTRUCTION EQUIPMENT OR IT IS NOT POSSIBLE TO COMPACT THE OVERLYING MATERIALS BECAUSE OF HIGH MOISTURE CONTENT. THEN ONE OR MORE OF THE FOLLOWING ALTERNATIVE ACTIONS MAY BE

(I) ALLOW THE MATERIAL TO DRY TO A MOISTURE CONTENT WHICH ALLOW IT TO BE COMPACTED AND ALLOW THE PLACEMENT AND (II) SCARIEY THE MATERIAL TO A DEPTH OF 200MM AND WORK AS NECESSARY TO ACCELERATE DRYING RECOMPACT AS SPECIFIED

(II) SCARIFY THE MATERIAL TO A DEPTH OF 200AM AND WORK AS NECESSARY TO ACCELERATE DRYING, RECOMPACT AS SPECIFIED WHEN MOISTURE CONTENT APPROXIMATES OPTIMUM (III) EXCAVATE AND REPLACE THE SOFT MATERIAL. THE ACTION TO BE ADOPTED SHALL BE ATTHE CONTRACTOR'S DISCRETION AND EXPENSE, BUT SHALL BE ADVISED TO THE SUPERIMENDENT BEFORE ACTION COMMENCES. IF THE CONTRACTOR ELECTS PURSUANT TO (I) ABOVE TO ALLOW THE MATERIAL TO DRY, RESULTING DELAYS, IF ANY, SHALL NOT CONSTITUTE GROUNDS FOR AN EXTENSION OF CONTRACT PERIOD OF DATE OF PRACTICAL COMPLETION. THE FINISHED SUBGRADE SHALL NOT BE DISTRIBED BY TRAFFIC OR OTHER OPERATIONS, AND SHALL BE PROTECTED AND MAINTAINED BY THE CONTRACTOR UNIT. THE FIRST LAYER OF FILL OR SUB-BASE IS PLACED THEREON. THE SUBGRADE SHALL BE RECEIVED AND CANDIE TEST YEAR OF THE PROTECTED AND CANDIE TEST YEARD OF THE CONTRACTOR UNIT. THE FIRST LAYER OF FILL OR SUB-BASE IS PLACED THEREON. THE SUBGRADE SHALL BE RECEIVED AND CANDIE TEST YEAR OF THE PROTECTED AND CANDIE TEST YEAR OF THE YEAR OF THE ADDRESS AND AND AND THE SUBGRADE SHALL BE REPORTED.

KEPT DRAINED AND COMPLETELY FREE OF STANDING WATER AT ALL TIMES. THE CONTRACTOR SHALL PLAN AND CARRY OUT THE WHOLE OF THE WORKS TO MINIMISE THE EFFECTS OF RUN-OFF AND EROSION ON THE SITE AND ON DOWNSTREAM AREAS. HE SHALL AVOID UNNECESSARY GROUND DISTURBANCE AND PROVIDE AS NECESSARY FOR THE PROPER CONTROL OF STORMWATER RUN-OFF AT EVERY STAGE OF THE WORKS ALL IN ACCORDANCE WITH "MANAGING

FOR THE PROPER CONTROL OF STORMMATER RUN-OFF AT EVERY STAGE OF THE WORKS ALL IN ACCORDANCE WITH "MANAGING URBAN STORMMATER / SOIL AND CONSTRUCTION" (LAND.COM "BLUE BOOK")
PRIOR TO THE COMMENCEMENT OF EARTHWORKS TOPSOIL IS TO BE STRIPPED WITHIN THE LIMITS OF THE EARTHWORKS AND FROM ANY AREAS TO BE COVERED BY PAVING, STRUCTURES OR FILL, AND ALL AREAS WHICH ARE TO SUPPORT PAVEMENTS, EMBANKMENTS, STRUCTURES AND THE LINE OF FILLING UNDER SUCH WORKS, SHALL BE STRIPPED CLEAR OF ALL TREES, LOGS, STUMPS, SCRUB, GRASS, ROOT GROWTH, CULTIVATED SOIL, WET OR SPONCY NATURAL SOIL, DECAYED VEGETABLE MATTER AND ANY OTHER DELETERIOUS SUSTANCE. THE CONTRACTOR SHALL BREAK UP AND REMOVE ALL ASPHALT AND CONCRETE MATERIAL UPON WHICH FILL OR PAVEMENT SHALL BE PLACED.
ALL MATERIAL WITHIN THE LIMIT OF THE EARTHWORKS SHALL BE WHOLLY REMOVED.
FILL ALL HOLES WITH APPROVED MATERIAL IN MAXIMUM SOMM COMPACTED THICKNESS LAYERS COMPACTED TO THE DENSITY TO THE ADJOINING UNDSTURBED SOIL AND TO THE APPROVAL OF THE SUPERINTENDENT.

MOISTURE CONDITION THE NATURAL SUBGRADE TO WITHIN THE RANGE 97% TO 103% OF STANDARD OPTIMUM MOISTURE CONTENT AND COMPACT TO ACHIEVE A MINIMUM STANDARD DRY DENSITY RATIO TO A MINIMUM DEPTH OF 200MM. IF REQUIRED THE AREA SHOULD BE TYNED AND SCARIFIED FULL DEPTH TO FACILITATE THIS PROCESS.

SHOULD BE I THEN AND SOMETHED FOLL DEFINIO FORMALIATE THIS PROCESS.
ANY SOFT WEAK OR INSTANTE AREAS EXPOSED BY THE COMPACTION PROCESS. OR DURING TEST ROLLING, AND WHICH DO NOT

ANY SOFT, WEAK OR UNISTABLE AREAS EXPOSED BY THE COMPACTION PROCESS, OR DURING TEST ROLLING, AND WHICH DO NOT RESPOND TO PURTHER COMPACTION OR MIGHTURE COMPITIONING SHALL BE EXCAVATED AND REPLACED. THE CONTRACTOR SHALL BE DEEMED TO HAVE ASSESSED THE EXTENT OF UNSTABLE AREAS AND SHALL BE DEEMED TO HAVE INCLUDED IN THE CONTRACT SUM FOR ALL ACTIVITIES REQUIRED FOR UNSTABLE AREA RECTRICATION INCLUDING THE DELIVERY, PLACING AND COMPACTING OF APPROVED MATERIAL AS WELL AS THE EXCAVATION AND DISPOSAL OF REPLACED MATERIAL. EXCAVATION TO THE UNES, LEVELS AND GRADES AS REQUIRED FOR UNDERGROUND SERVICES SPECIFIED IN THE RELEVANT SERVICES SETTIONS, INCLUDING DRAINAGE, HYDRALLIC, ELECTRICAL AND THE LIKE UNLESS OTHERWISS SPECIFIED MAKE THE TRENCHES STRAIGHT BETWEEN MANHOLES, INSPECTION POINTS, JULICTIONS AND THE LIKE, WITH VERTICAL SIDES AND UNIFORM GRADES. DEPTH SHALL BE AS REQUIRED BY THE RELEVANT SERVICES SUCH OTHER OBSTRUCTIONS INCLUDING ROOTS, STUMPS, BOULDERS AND THE LIKE WHICH MAY, IN THE OPINION OF THE SUPERINTENDENT, INTERFERE WITH THE PROPER FUNCTIONING OF THE SERVICE, LAY AND BE OSERVICES IN ACCORDANCE WITH THE RELEVANT SERVICES SERVICITION IN SECTION.

FUNCTIONING OF THE SERVICE, LAY AND BED SERVICES IN ACCORDANCE WITH THE RELEVANT SERVICES SPECIFICATION SECTION BACKFILL AND COMPACT SERVICE TRENCHES AS SOON AS POSSIBLE AFTER APPROVAL OF LAID AND BEDDED SERVICE. COMPACT BACKFILL IN PIPE TRENCHES SO THAT THE PIPE IS BUTTRESSED BY THE WALLS OF THE TRENCH.

WHERE FILLING IS DESIGNATED BY THE CONTRACT OR IS SHOWN ON THE DRAWINGS AS STRUCTURAL OR CONTROLLED FILL THE CONTRACTOR SHALL ENGAGE AN INDEPENDENT GEOTECHNICAL TESTING AUTHORITY TO SUPERVISE SUBGRADE PREPARATION FILL PLACEMENT, COMPACTION AND TO UNDERTAKE SAMPLING AND TESTING AND REPORTING TO SATISFY THE REQUIREMENTS OF

FILL PLACEMENT, COMPACTION AND TO UNDERTAKE SAMPLING AND TESTING AND REPORTING TO SATISFY THE REQUIREMENTS OF THIS SPECIFICATION AND THOSE OF AS 2370 AND AS 3798, FOR CONTROLLED FILL.

NO FILL SHALL BE PLACED OVER LAYERS NOT TESTED AND HAVING SATISFACTORY RESULTS, WHERE EXCAVATED MATERIAL IS NOT SUITABLE FOR FILLING, FILL MATERIAL, AS SPECIFIED IN THIS SPECIFICATION SECTION, "IMPORTED FILL" SHALL BE USED. ALL FILL MATERIAL SHALL BE PLACED IN MAXIMUM 200mm THICK LAYERS AND COMPACTED AT OPTIMUM MOISTURE CONTENT (-OR -2%) TO ACHIEVE A DRY DENSITY DETERMINED IN ACCORDANCE WITH AS 1289.5.1.1-2003-METHODS OF TESTING SOILS FOR ENGINEERING PURPOSES OF NOT LESS THAN THE FOLLOWING STANDARD MINIMUM DRY DENSITY - LOCATION.

STANDARD DRY DENSITY VEHICULAR PAVED AREAS NON-VEHICULAR PAVED AREAS ANDSCAPED AREAS

LANDSCAPED AREAS 95%

13. UNLESS OTHERWISE PERMITTED, NO FILLING SHALL BE PLACED AGAINST ANY STRUCTURES, WING WALLS OR RETAINING WALLS UNLESS OTHERWISE PERMITTED, NO FILLING SHALL BE PLACED AGAINST ANY STRUCTURES, WING WALLS OR RETAINING WALLS WITHIN FOURTEEN DAYS OF CASTING, STRUT WALLS AS NECESSARY TO PREVENT MOVEMENT DURING FLOING AND COMPACTION. PLACE AND COMPACT FILLING OVER AND AROUND PIPES, CLLVERTS, BRIDGES AND OTHER STRUCTURES SO AS TO AVOID UNBALANCED LOADING OR MOVEMENT. UNLESS OTHERWISE DETAILED BACKFILL AT STRUCTURES SHALL BE FILLED AS FOLLOWS. WHERE THE GAP BETWEEN THE STRUCTURE AND UNDISTURBED GROUND EXCEEDS ZIM, BACKFILL THE WITHIN 20 OF THE STRUCTURE WITH DGS20 SUBBASE FINE CRUSHED ROCK AND BACKFILL IN THE ZONE BEYOND ZM OF THE STRUCTURE WITH STRUCTURE WITH MITH ZONE DESCONDED FOR CK.

UNLESS OTHERWISE DETAILED, MATERIAL WITHIN 300mm OF WEEPHOLES SHALL BE AN APPROVED GRANULAR FILTER MEDIUM OF COARSE SAND OR CRUSHED STONE WRAPPED AND SURROUNDED WITH AN APPROVED GEOTEXTILE SEPARATION LAYER.

HORIZONTAL.

NO POINT SHALL BE GREATER THAN + OR - 100mm FROM THE DESIGN LOCATION.

VERTICAL SUBGRADE LEVEL +0, -25mm PAVEMENT DESIGN SUBGRADE 1.EVEL +0 -25mm

OTHER. +50, +50mm STRAIGHTNESS (EXCLUDES ROCK): MAXIMUM 20MM DEPARTURE FROM 3M STRAIGHT EDGE LAID: PARALLEL TO ROAD CENTER LIN

DESIGN LOT CODE

- NOKMAL TO INTENDED CONTIONS
AREAS UPON WHICH FILLS ARE TO BE CONSTRUCTED, ALL LAYERS OF FILLING, AND MATERIAL'S LESS THAN 150mm BELOW
PERMANENT SUBGRADE LEVEL IN CUTTINGS, SHALL BE COMPACTED SO AS TO BE CAPABLE OF WITHSTANDING TEST ROLLING,
WITHOUT VISIBLE DEFORMATION OR SPRINGING, WITH A PNEUMATIC TYPED ROLLER OR HIGHWAY TRUCK BALLASTED TO COMPLY
WITH THE FOLLOWING:

MITH THE FULLOWING."
PREUMATIC TYRED - NOT LESS THAN 3 T PER TYRE WITH TYRES INFLATED TO 550 KPa.
HIGHWAY TRUCK - WITH REAR AXLE OR AXLES LOADED TO NOT LESS THAN 8 T EACH WITH TYRES INFLATED TO 550KPa.
TEST ROLLING SHALL BE CARRIED OUT IMMEDIATELY BEFORE CVERLYING LAYERS ARE PLACED.

WHERE TEST ROLLING IS REQUIRED AT SOME LATER DATE, THE SURFACE SHALL BE MOISTURE CONDITIONED AS AND GIVEN NOT

COVERAGES OF THE TEST ROLLER BEFORE TEST ROLLING COMMENCES. 16. THE WORK SHALL NOT BE ACCEPTED AS COMPLETE LIMESS ALL TEST RESULTS ARE PROVIDED TO THE SUPERINTENDENT. THE

THE WORK SHALL NOT BE ACCEPTED AS COMPLETE UNLESS ALL TEST RESULTS ARE PROVIDED TO THE SUPERINTENDENT. THE CONTRACTOR SHALL PROVIDE ALL MATERIAL PROPERTY AND QUALITY TEST RESULTS TO THE SUPERINTENDENT. THE CONTRACTOR SHALL PROGRAM THE EARTHWORKS OPERATION SO THAT THE WORKING AREAS ARE ADEQUATELY DRAINED DURING THE PERIOD OF CONSTRUCTION. THE SUPERACE SHALL BE GRADED AND SEALED OF TO REMOVE DEPRESSIONS, ROLLER MARKS AND SIMILAR WHICH WOULD ALLOW WATER TO POND AND PENETRATE THE UNDERLYING MATERIAL ANY DAMAGE RESULTING FROM THE CONTRACTOR NOT OBSERVING THESE REQUIREMENTS SHALL BE RECTIFIED BY THE CONTRACTOR AT THEIR OWN EXPENSE.

TESTING OF THE FILL MATERIAL SHALL BE CARRIED OUT BY AN APPROVED NATA REGISTERED LABORATORY AT THE CONTRACTORS EVOICING.

DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING

THE CONTRACTOR SHALL COMPLY WITH RMS QA SPECIFICATIONS FOR ROADWORKS AND THE CURRENT EDITIONS OF THE AUSTRALIAN STANDARDS: AS 1289 TESTING SOILS FOR ENGINEERING PURPOSES

AS 3798 GUIDELINES ON EARTHWORKS FOR COMMERCIAL AND RESIDENTIAL DEVELOPMENTS

ALL WORK SHALL COMPLY WITH THE PROJECT GEOTECHNICAL REPORT.
THE CONTRACTOR SHALL BE RESPONSIBLE FOR CARRYING OUT ALL CONTROL AND COMPLIANCE EXAMINATION AND TESTING OF MATERIALS AND WORK UNLESS OTHERWISE SPECIFIED. ALL TESTS SHALL BE UNDERTAKEN IN ACCORDANCE WITH THE APPROPRIATE AUSTRALIAN STANDARD TEST METHOD, WHERE THERE IS NO RELEVANT AUSTRALIAN STANDARD TEST METHOD. THEN THE CURRENT APPROPRIATE RTAITEST METHOD OR OTHER SPECIFIED TEST METHOD SHALL BE USED. ALL TESTS SHALL BE CONDUCTED BY EXPERIENCED TESTING OFFICERS IN A LABORATORY ACCREDITED BY THE NATIONAL ASSOCIATION OF

DETERMINATION OF THE NATURE AND QUANTITY(IES) OF THE EXISTING SITE MATERIALS SHALL BE THE RESPONSIBILITY. OF THE DETERMINATION OF THE NATURE AND QUANTITY(ES) OF THE EXISTING SITE MATERIALS SHALL BE THE RESPONSIBILITY OF CONTRACTOR. WHERE INCLUDED IN THE DOCUMENTS, GEOTECHNICAL REPORTS ARE INCLUDED FOR INFORMATION ONLY. INTERPRETATION OF THE REPORTS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. USE OF ON-SITE MATERIAL WITHIN THE WORKS SHALL ONLY BE PERMITTED WHERE THE MATERIAL EITHER. ILS SPECIALLY STATED WITHIN THE DOCUMENTS AS BEING USED IN THE WORKS, OR ILS PERMITTED BY THE SUPERINTENDENT & GEOTECHNICAL TESTING JENGINEER ALL FILL MATERIAL SHALL BE FROM A SOURCE APPROVED BY THE SUPERINTENDENT AND SHALL COMPLY WITH THE COLUMNING.

a) FREE FROM ORGANIC AND PERISHABLE MATTER; b) MAXIMUM PARTIC! F SIZE 75mm: AND

c) PLASTICITY INDEX - BETWEEN 2% AND 15%.

ALL DRAINAGE PIPES Ø375mm AND ABOVE SHALL BE SPIGOT AND SOCKET REINFORCED CONCRETE PIPES WITH RUBBER RING JOINTS (UNO).

ALL DRAINAGE PIPES LESS THAN OR EQUAL TO Ø225mm SHALL BE UPVC DWV GRADE CLASS SNB IN ACCORDANCE WITH ASANZS1260 2009-PVC-U PIPES AND FITTINGS FOR DRAIN, WASTE AND VENT APPLICATION WITH SOLVENT WELDED JOINTS (UNO).

ALL PIPE JUNCTIONS UP TO AND INCLUDING Ø450mm AND TAPERS, SHALL BE VIA PURPOSE MADE FITTINGS (UNO). MINIMUM GRADE TO STORMWATER LINES TO BE 1%/LINO)

EQUIVALENT STRENGTH FIBROUS REINFORCED CONCRETE AND/OR VITRIFIED CLAY PIPE MAY BE USED SUBJECT TO APPROVAL

BY THE SUBEDINTENDENT AND CONSENT AUTHODIT

BY THE SUPERINTENDENT AND CONSENT AUTHORITY.

TRENCHES MUST BE KEPT CLEAR OF WATER AT ALL TIMES AND TIMEFRED WHERE NECESSARY TO PREVENT COLLAPSE.

WHERE STORMWATER LINES PASS UNDER FLOOR SLABS DWY GRADE WPVC RUBBER RING JOINTS ARE TO BE USED (UNK
PIPES SHALL BEAR EVENLY ON THE BED PREPARED AS SPECIFIED ABOVE AND LAID WITH THE SOCKETS POINTED UPGRY
PIPES SHALL BE LAID IN STRAIGHT LINES, TO TRUE INVERT LEVELS AND GRADES AS SHOWN ON PLANS. EACH PIPE SHALL SAPERATELY BONED BETWEEN ACCURATELY ESTABLISHED GRADE POINTS. THE CONTRACTOR SHALL ADHERE TO THE

UNLESS NOTED OTHERWISE, BEDDING SHALL BE TYPE H2 FOR PIPES NOT UNDER PAVEMENTS AND TYPE HS3 FOR PIPES UNDER

PAVEMENTS IN ACCORDANCE WITH ASINZS3725 (2007) - DESIGN FOR INSTALLATION OF BURIED CONCRETE PIPES.

BACKFILL TRENCH WITH SAND OR APPROVED GRANULAR BACKFILL TO 300mm (MIN) ABOVE THE PIPE. WHERE THE PIPE IS UNDER PAVEMENT'S BACKFILL REMAINDER OF TRENCH TO PAVEMENT SUBGRADE WITH SAND OR APPROVED GRAVEL SUB-BASE COMPACTED IN 150mm LAYERS TO 98% STANDARD MAXIMUM DRY DENSITY. THE CONTRACTOR IS TO ENSURE COMPACTION FOLIPMENT IS APPROPRIATE FOR THE PIPE CLASS USED

ALL PIPE JOINTING SHALL BE CARRIED OUT IN ACCORDANCE WITH THE MANUFACTURER'S WRITTEN SPECIFICATIONS FOR THE

TYPE OF PIPE BEING USED.

3. CONTRACTOR TO SUPPLY AND INSTALL ALL FITTINGS AND SPECIALS INCLUDING VARIOUS PIPE ADAPTORS TO ENSURE PROPER CONNECTION BETWEEN DISSIMILAR PIPEWORK.

4. ALL CONNECTIONS TO EXISTING DRAINAGE PITS SHALL BE MADE IN A TRADESMAN-LIKE MANNER AND THE INTERNAL WALL OF THE PIRT AT THE POINT OF ENTRY SHALL BE CAMENT RENDERED TO ENSURE A SMOOTH FINISH WITH NO PROTIFUSION.

15. WHERE ANY PIPE IS CUT INTO A LARGER PIPE, SUCH CONNECTION SHALL BE NEATLY MADE AND NO PART OF THE PIPE OR DOWNPIPE SHALL BE ALLOWED TO PROJECT, ANY CUT-IN JUNCTION SHALL BE MADE IN THE TO PHALF OF THE LARGER PIPE. SUCH JUNCTION OF SHALL BE UNREDUNDED WITH A MEAT COLLAR OF CEMENT MORTRA AS DIRECTED OR AS DETAILED ON THE DRAWNINGS, JUNCTIONS BETWEEN PVC PIPES SHALL USE PROPRIETY FITTINGS INTENDED FOR THE PURPOSE.

15. THE FIRED OF THE DRAWNINGS, JUNCTIONS BETWEEN PVC PIPES SHALL USE PROPRIETY FITTINGS INTENDED FOR THE PURPOSE.

16. THE FIRED OF THE DRAWNINGS. JUNCTIONS BETWEEN PVC PIPES SHALL USE PROPRIETY FITTINGS INTENDED FOR THE PURPOSE.

THE ENDS OF PIPES WHICH CONNECT WITH SIDE ENTRY, JUNCTION OR OTHER PITS SHALL BE NEATLY CUT TO FIT THE INNER FACE OF THE CONCRETE. WHERE UPVC PIPES ENTER/LEAVE PITS A RUBBER RING JOINT MANHOLE COUPLING SHALL BE CAST

INTO THE PIT WALL BEDDING HAUNCH AND OVERLAY MATERIALS SHALL CONFORM TO THE DETAILS SHOWN ON THE DRAWINGS ALL PITS AND ENDWALLS SHALL BE CONSTRUCTED IN THE POSITIONS AND TO THE LEVELS SHOWN ON THE DRAWINGS OR AS DIRECTED BY THE SUPERINTENDENT, LOCATION OF ALL IAD PITS TO BE CONFIRMED WITH SUPERINTENEND & LANDSCAP DIRECTION THE SOPERIMENDENT, EXCEPTION OF ALL MOTHS TO BE CONSTRUCTION WITH SOPERIMENEND & LAI ARCHITECT BEFORE CONSTRUCTION.

COUNCIL'S CONSTRUCTION PIT DETAILS TO TAKE PRECEDENCE TO THE CONSTRUCTION DETAILS SHOWN IN THIS

DOCUMENTATION, PRECAST PITS OR ALTERNATIVE DESIGN TYPES CAN BE USED SUBJECT TO COUNCIL / PCA APPROVAL. (IAD

ONLY)
PIT COVERS SHALL BE PLACED IN ACCORDANCE WITH THE DETAIL SITE PLANS AND PIT SCHEDULE (IF PROVIDED) IN REGARD TO
TYPE, SIZE, LOCATION AND LEVEL. THE BASE OF EACH PIT SHALL BE INFILLED AND SHAPED WITH CONCRETE OR CEMENT
MORTAR TO PROVIDE A SMOOTH FLOW PATH. PITS DEEPER THAN 1000mm SHALL HAVE STEP IRONS INSTALLED IN ACCORDANCE WITH THE LOCAL OR STATUTORY AUTHORITY

19. ALL DOWNPIPES SHALL BE CONNECTED TO AT THE END OF A PIPE OR ELBOW AND WHICH THEY SHALL ENTER CENTRALLY. WHERE PVC DOWNPIPES AND UNDERGROUND DRAINAGE ARE USED, THE DOWNPIPES SHALL BE CONNECTED TO THE UNDERGROUND DRAINS WITH SUITABLE STANDARD FITTINGS, BENDS ETC AND WITH SOLVENT JOINTS. THE CONTRACTOR SHALL I AY AND GRADE DRAINS FROM DOWNPIPES TO COMPLY WITH THE REQUIREMENTS FOR PIPE MATERIAL AND COVER REQUIRED. BY AS3500.3. WHERE THE REQUIREMENTS OF AS3500.3 CANNOT BE MET THE CONTRACTOR SHALL REFER THE MATTER TO THE

NI POLY APPARATUS AND MATERIALS NECESSARY FOR AND CARRY OUT THE TESTS REQUIRED BY THE SPECIFICATION OF SUPPLY APPARATION AND MATERIALS NECESSARY FOR, AND CARRY OUT THE 1851 REQUIRED BY THE SPECIFICATION ARE REGULATORY AUTHORITIES, IN THE PRESENCE OF THE SUPPRINTEDIDENT AND THE RELEVANT AUTHORITY. LEAVE PIPE JOIN EXPOSED TO ENABLE OBSERVATION DURING THE TESTS, ENSURE PVC SOLVENT CEMENT JOINTS HAVE BEEN CURED FOR AT LEAST 24 HOURS SEPORE TESTING. THE CONTRACTOR SHALL PRESSURE TEST WITH WATER, ALL STORMWATER PIPEWORK IN OR UNDER ANY STRUCTURES, IN

22. WHERE SHOWN IN THE DOCUMENTS OR WHERE THE GRADE OF THE PIPELINE IS ≥15%, CONCRETE BULKHEADS SHALL BE CONSTRUCTED AT EVERY SECOND JOINT, THE AXIS OF THE BULKHEAD SHALL BE VERTICAL WITH A MINIMUM TOP WIDTH OF 200mm, UNLESS OTHERWISE DIRECTED THE TOP OF BULKHEADS SHALL EXTEND TO WITHIN 300mm OF FINISHED SURFACE LEVEL OR TO THE SUBGRADE LEVEL WHERE THE PIPELINE IS UNDER A ROAD PAYEMENT. ON EACH SIDE OF THE PIPE AT THE LEVEL OF THE TRENCH INVEST 100mm DIA PIPES SHALL PASS THROUGH THE BUILKHEAD, SLICH PIPES SHALL BE BUILED WITH FIRREGLASS WOOL OR OTHER APPROVED FILTER MATERIAL. THE BULKHEAD SHALL BE LOCATED DIRECTLY BEHIND THE DOWNSTREAM COLLAR SO AS NOT TO ENCASE THE JOINT, REFER TO DETAILS SHEET.



PLOT DATE / TIME

PLOT BY

CLIENT

EXISTING SERVICES

EXISTING SERVICES HAVE BEEN PLOTTED FROM SUPPLIED DATA AND AS SUCH THEIR ACCURACY CANNOT BE GUARANTEED. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ESTABLISH THE LOCATION AND LEVEL OF ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF ANY WORK, ANY DISCREPANCIES SHALL BE REPORTED TO THE SUPERINTEMDENT. THE CONTRACTOR SHALL ALLOW FOR THE CAPPING OFF EXCAVATION AND REMOVAL IF REQUIRED OF ALL REDUNDANT EXISTING SERVICES IN AREAS AFFECTED BY WORKS WITHIN THE CONTRACT AREA, AS SHOWN ON THE DRAWINGS UNLESS

DIRECTED OTHERWISE BY THE SUPERINTENDENT.
THE CONTRACTOR SHALL ENSURE THAT AT ALL TIMES SERVICES TO ALL BUILDINGS NOT AFFECTED BY THE WORKS ARE NOT

DISKUPPLE). IF FECONTRACTOR SHALL CONSTRUCT TEMPORARY SERVICES TO MAINTAIN EXISTING SUPPLY TO BUILDINGS REMAINING IN OPERATION DURING WORKS TO THE SATISFACTION AND APPROVAL OF THE SUPERINTENDENT. ONCE DIVERSION IS COMPLETE AND COMMISSIONED THE CONTRACTOR SHALL REMOVE ALL SUCH TEMPORARY SERVICES AND MAKE GOOD TO THE SATISFACTION OF THE SUPERINTENDENT AND THE RELEVANT SERVICE AUTHORITY

GOOD TO THE SATISFACTION OF THE SUPERINTENDENT AND THE RELEVANT SERVICE AUTHORITY.

INTERRUPTION TO SUPPLY OF EXISTING SERVICES SHALL BE DONE SO AS NOT TO CAUSE ANY INCONVENIENCE TO THE

PRINCIPAL. THE CONTRACTOR IS TO GAIN APPROVAL FROM THE SUPERINTENDENT FOR TIME OF INTERRUPTION - THE

CONTRACTOR IS RESPONSIBLE FOR ALL LUISION.

ALL BRANCH GAS AND WHATER SERVICES UNDER DRIVEWAYS AND BRICK PAVING SHALL BE LOCATED IN 80mm DIA UPVC SEWER

GRADE CONDUITS EXTENDING A MINIMUM OF 500mm BEYOND THE EDGE OF PAVING.

CLEARANCE AND COVER REQUIREMENTS SHALL BE OBTAINED FROM THE RELEVANT SERVICE AUTHORITY BEFORE

COMMENCEMENT OF WORKS AND SHALL BE ADHERED TO AT ALL TIMES.

CARE IS TO BE TAKEN WHEN EXCAVATION BARE PASITIONS SERVICES. NO MECHANICAL EXCAVATIONS ARE TO BE UNDERTAKEN

OVER TELECOM OR ELECTRICAL SERVICES. HAND EXCAVATE IN THESE AREAS ONLY.

SERVICE TRENCHES AND CONDUITS

MATERIAL SHALL COMPLY WITH RMS OA SPECIFICATIONS FOR ROADWORKS AND THE CURRENT EDITIONS OF THE FOLLOWING AUSTRALIAN STANDARDS.
AS 2032 CODE OF PRACTICE FOR UPVC PIPE SYSTEMS.
AS 2032 CODE OF PRACTICE FOR UPVC PIPE SYSTEMS.
AS 3003, NATIONAL PLUMBING AND DRAINAGE CODE, PART 3 STORMNATER DRAINAGE.
ELECTRICAL, WATER & GAS DUCTING CONDUITS SHALL BE IN ACCORDANCE WITH THE RELEVANT AUTHORITY DEPOLIPBELEUTS.

REQUIREMENTS.

CONTRACTOR TO COORDINATE SHARED TRENCH AND LIASE WITH NBN Co / GAS / TELSTRA FOR SUPPLY AND PLACEMENT

CONTRACTOR TO COORDINATE SHARED TRENCH AND LIASE WITH NBN Co / GAS / TELSTRA FOR SUPPLY AND PLACEMENT OF CONDUIT AND GIVE MINIMUM 14 DAYS PRIOR TO THE NEED FOR DUCTING TO BE INSTALLED. DRAW WIRES SHALL BE 2,8mm HIGH TENSILE GALVANISED DRAW WIRE.

ALL EXCAVATION AND BACKER I SHALL BE IN ACCORDANCE WITH THE STORMWATER DRAINAGE AND BASE AND

SUBBASE-CRUSHED ROCK SECTION. BEDDING AND HAUNCHING SHALL COMPLY WITH THE REQUIREMENTS OF AS2032 UNLESS OVERRIDEN BY THE REQUIREMENTS OF THE RELEVANT AUTHORITY OR THE RELEVANT SERVICES SECTIONS OF THE SPECIFICATION, LOW

PERMEABILITY BEDDING AND BACKFILL SHALL BE PROVIDED, WHERE SHOWN ON THE PLAN OR OTHERWISE DIRECTED

WHERE SERVICES OR CONDUITS ARE PLACED UNDER PAVEMENT THE COVER FROM TOP OF THE SERVICE OR CONDUIT TO THE PAVEMENT SURFACE SHALL, UNLESS SHOWN OTHERWISE ON THE DRAWINGS OR REQUIRED BY SERVICE AUTHORITIES BE NOT LESS THAN 750MM AND TO THE INVERT LEVEL OF OPEN DRAINS SHALL BE NOT LESS THAN 600mm. UNLESS OTHERWISE APPROVED BY THE SUPERINTENDENT, CROSSING OF PAVEMENT SHALL BE MADE SQUARE OR NEAR SQUARE WITH THE DIRECTION OF TRAFFIC.

WHERE IT IS NECESSARY FOR EXISTING ASPHALT OR CONCRETE PAVEMENTS TO BE CUT THEY SHALL BE SAWN FOR THE

FULL DEPTH OF ASPHALT OR CONCRETE. CONDUITS SHALL BE PLACED UNDER LANDSCAPE OR NON-PAVED AREAS WITH NOT LESS THAN 450mm COVER UNLESS A GREATER DEPTH IS REQUIRED BY THE RELEVANT AUTHORITY OR SERVICES SECTION OF THE SPECIFICATION

END DUCT CROSSINGS 500mm BEHIND KERBS UNLESS SHOWN OTHERWISE ON THE DRAWINGS. END DUCT CROSSINGS END DUCT CROSSINGS 500mm BEHIND KERBS UNLESS SHOWN OTHERWISE ON THE DRAWINGS. END DUCT CROSSINGS 1000mm CLEAR OF THE PAWENT WHERE THERE IS NO KERB, UNLESS SHOWN OTHERWISE ON THE DRAWINGS. LOCATE DUCTS TO AVOID OTHER SERVICES AND WITH STRAIGHT LINES AND GRADES UNLESS DIRECTED OTHERWISE. EACH UNUSED CONDUIT IN EACH CONDUIT BANK SHALL BE FITTED WITH A SINGLE UNJOINED LENGTH OF DRAW WIRE OF A LENGTH COUAL TO THE LENGTH OF THE DUCT PLUS 2 METERS.

CAP BOTH ENDS OF ALL UNISED CONDUITS WITH STANDARD UPVC CAPS OR APPROVED WATERTIGHT CAP. LEAVE ENDS OF CONDUITS EXPOSED UNTIL THEIR LOCATIONS HAVE BEEN RECORDED BY THE RELEVANT AUTHORITIES.

SUBSOIL DRAINAGE

THE CONTRACTOR SHALL COMPLY WITH RMS QA SPECIFICATIONS FOR ROADWORKS FOR ALL SUBSOIL DRAINAGE WORKS. WHERE SUBSOIL DRAINAGE LINES PASS UNDER FLOOR SLABS AND VEHICULAR PAVEMENTS, UNSLOTTED UPVC DWV GRADE CLASS SMP PIPE SHALL BE USED. PROVIDE SUBSOIL DRAINAGE IN ACCORDANCE WITH COUNCIL SPECIFICATIONS WITH CONTINUOUS FALL TO DOWNSTREAM

PITS LOCATED AS SHOWN ON PLAN AND AS MAYBE DIRECTED BY COUNCIL / SUPERINTENDENT.

ALL SUBSOIL DRAINAGE PIPES SHALL BE 20100MM CLASS 400 PERFORATED DRAINAGE PIPE LAID AT 1.04MIN GRADE,
WRAPPED IN GEOFABRIC (UNO) AND BE LAID AT A MIN DEPTH OF 400mm BELOW PAVEMENT SUB-BASE COURSE.

BASE AND SUBBASE-CRUSHED ROCK

RETESTS SHALL BE BORNE BY THE CONTRACTOR

ALL WORKMANSHIP AND MATERIALS SHALL COMPLY WITH RMS QA SPECIFICATIONS FOR ROADWORKS AND THE CURRENT EDITIONS OF THE MISS-PEC AND RELEVANT AUSTRALIAN STANDARDS.

WHERE IT IS SPECIFIED THAT WATER SHALL BE ADDED TO THE CRUSHED ROCK PRIOR TO DELIVERY, SUCH WATER SHALL

BE CLEAR AND SUBSTANTIALLY FREE FROM DETRIMENTAL IMPURITIES SUCH AS SOILS, SALTS, ACIDS, ALKALIS AND

VEGETARI E SURSTANCES WHERE SPECIFIED CEMENT SHALL COMPLY WITH THE REQUIREMENTS OF EITHER AUSTRALIAN STANDARD SPECIFICATION

WHERE SPECIFIED CEMENT SHALL COMPLY WITH THE REDUIREMENTS OF EITHER AUSTRALIAN STANDARD SPECIFICATION AS 1315-PORTLAND CEMENT OR AS 1317-BLENDED CEMENT. THE SUBGRADE, OR PREVIOUS PAVEMENT COURSE, SHALL HAVE BEEN TESTED AND ACCEPTANCE CRITERIA MET BEFORE THE PLACING OF THE NEXT COURSE WILL BE PERMITTED. CRUSHED ROCK MATERIAL SHALL NOT BE PLACED ON A WATERLOGGED SUBGRADE OR LOWER COURSE. THE MOISTURE CONTENT OF THE CRUSHED ROCK SHALL BE MAINTAINED WITHIN -2%, -2% OF OPTIMUM MOISTURE CONTENT AT ALL TIMES DURING SPREADING AND COMPACTION. ACCOMPACTION. ACCOMPACTED AS SOON AS POSSIBLE AFTER SPREADING AND WHILE THE MOISTURE CONTENT IS WITHIN THE SPECIFIED RANGE TO ACHIEVE A UNIFORM DENSITY IN THE LAYER. AT THE COMPACTION OF EACH LAYER WITHIN THE COURSE, THE CONTRACTOR SHALL ARRANGE FOR THE LAYER TO BE TESTED FOR COMPLIANCE WITH THE REQUIRED DENSITY, ALL TEST RESULTS SHALL BE SUBMITTED TO THE SUPERINTEDION OF THE REST TEST SETS OF SUPERACE TREATMENT.

8 WHERE TEST RESULTS INDICATE THE AREA FAILS TO COMPLY WITH THE REQUIRED DENSITY CRITERIA. THE CONTRACTOR SHALL RE-ROLL LOGSEN RE-WATER RE-COMPACT OR REMOVE AND REPLACE THE LAYER AS DIRECTED BY THE TENDENT. TO ACHIEVE A LAYER COMPLYING IN FULL WITH THIS SPECIFICATION, COSTS OF RECTIFICATION AND

FOR CONSTRUCTION

HORNSBY SHIRE COUNCIL 29/07/2016 2:21:41 PM X\111403 - Galston-Grange Retirement-Village\6BIM6_3 MHT MIE\6_3_4 MHT UD\Mid Dural Road Drawings\DS2016-002140-DD-GE-0201-201A.dwg Aseip MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON EXTERNAL REFERENCE FILES REV DATE AMENDMENT / REVISION DESCRIPTION WVR No. APPROVAL SCALES ON A3 SIZE DRAWING DRAWINGS / DESIGN PREPARED BY TITLE NAME DATE Transport GALSTON GRANGE DEVELOPMENT 29-07-16 ISSUED FOR 100% DESIGN DEVELOPMENT D.CREARY Roads & Maritime 04-11-16 INCORPORATED RMS COMMENTS DATED 03-08-2016 DRG CHECK M.GRINHAM GENERAL NOTES SHEET 1 OF 2 Services 27-11-17 INCORPORATED BRS COMMENTS DATED 22-12-2016 DESIGN A PHAM SHEET 02 OF 23 05-06-17 INCORPORATED RMS COMMENTS DATED 16-05-2017 SK DESIGN CHECK S.DUNSTONE RMS REGISTRATION No. DS2016 / 002140 Meinhardt Australia Ptv Ltd BRANCH NAME DESIGN MINGR P.ENOCH ISSUE STATUS CO-ORDINATE SYSTEM HEIGHT DATUM SECTION NAME GE-0201 PROJECT MINGR P.ENOCH DEPARTMENT NAME MGA ZONE 56

<u>GENERAL</u> ASPHALTIC CONCRETE MIX DESIGN, MANUFACTURE, PLACING AND COMPACTION SHALL BE IN ACCORDANCE WITH RMS QA

PAVEMENT PREPARATION
2. THE EXISTING SURFACE TO BE SEALED, SHALL BE DRY AND BROOMED BEFORE COMMENCEMENT OF WORK TO ENSURE COMPLETE REMOVAL OF ALL FOREIGN AND LOOSE MATTER.
3. ALL DEPRESSIONS OR UNEVEN AREAS ARE TO BE TACK-COATED AND BROUGHT UP TO GENERAL LEVEL OF PAVEMENT WITH ASPHALTIC CONCRETE BEFORE LAYING OF MAIN COURSE.

TACK COAT

THE WHOLE OF THE AREA TO BE SHEETED WITH ASPHALTIC CONCRETE SHALL BE LIGHTLY AND EVENLY COATED WITH

THE WHOLE OF THE AREA TO BE SHEETED WITH ASPHALTIC CONCRETE SHALL BE LIGHTLY AND EVENLY COATED WITH

THE WHOLE OF THE AREA TO BE SHEETED WITH ASPHALTIC CONCRETE SHALL BE LIGHTLY AND EVENLY COATED WITH

THE WHOLE OF THE AREA TO BE SHEETED WITH ASPHALTIC CONCRETE SHALL BE LIGHTLY AND EVENLY COATED WITH

THE WHOLE OF THE AREA TO BE SHEETED WITH ASPHALTIC CONCRETE SHALL BE LIGHTLY AND EVENLY COATED WITH

THE WHOLE OF THE AREA TO BE SHEETED WITH ASPHALTIC CONCRETE SHALL BE LIGHTLY AND EVENLY COATED WITH

THE WHOLE OF THE AREA TO BE SHEETED WITH ASPHALTIC CONCRETE SHALL BE LIGHTLY AND EVENLY COATED WITH

THE WHOLE OF THE AREA TO BE SHEETED WITH ASPHALT BE BE SHEETED WITH BE SHEETED WITH ASPHALT BE SHEETED WITH ASPHALT BE SHEETED WITH BE SHEETED WITH

SPREADING
5. ALL ASPHALTIC CONCRETE SHALL BE SPREAD WITH A SELF PROPELLED PAVING MACHINE.

THE ASPHALTIC CONCRETE SHALL BE LAID AT A MIX TEMPERATURE AS SHOWN BELOWROAD SURFACE MIX
TEMP IN SHADE ("C) TEMPERATURES("C)

20+
ASPHALTIC CONCRETE SHALL NOT BE LAID WHEN THE ROAD SURFACE IS WET OR WHEN COLD WINDS CHILL THE MIX TO ADVERSELY AFFECT TEMPERATURE OF MIX DURING SPREADING AND COMPACTION OPERATIONS.

<u>19</u> The number of Joints Both Longitudinal and transverse shall be kept to a minimum. The Density and Surface Finish at Joints Shall be similar to those of the remainder of the Layer

COMPACTION

10 ALL COMPACTION SHALL BE UNDERTAKEN USING SELF PROPELLED ROLLERS.

INITIAL ROLLING SHALL BE COMPLETED BEFORE THE MIX TEMPERATURE FALLS BELOW 11.5°C SECONDARY ROLLING SHALL BE COMPLETED BEFORE THE MIX TEMPERATURE FALLS BELOW 60°C.

FINISHED PAVEMENT PROPERTIES

13. FINISHED SURFACES SHALL BE SMOOTH, DENSE AND TRUE TO SHAPE AND SHALL NOT VARY MORE THAN 10mm FROM THE SPECIFIED PLAN LEVEL AT ANY POINT AND SHALL NOT DEVIATE FROM THE BOTTOM OF A 3m STRAIGHT EDGE LAID. IN ANY DIRECTION BY MORE THAN 5mm.

CONCRETE NOTES

GENERAL CONCRETE MIX DESIGN, MANUFACTURE, PLACING AND COMPACTION SHALL BE IN ACCORDANCE WITH RMS QA SPECIFICATIONS

USE "AS3972-1997-PORTLAND AND BLENDED CEMENTS-TYPE GP" CEMENT (UNO).
ALL CONCRETE SHALL BE SUBJECT TO PROJECT CONTROL, SAMPLE AND TESTING TO AS3600-2001-CONCRETE

STRUCTURES.
CONSOLIDATE BY VIBRATION, CURE SURFACES AS SHOWN ON THE PLANS OR AS DIRECTED IN THE SPECIFICATION OR AS

DIRECTED BY THE SUPERINTENDENT.
FIX REINFORCEMENT AS SHOWN ON DRAWINGS, THE TYPE AND GRADE IS INDICATED BY A SYMBOL AS SHOWN BELOW. HOT ROLLED DEFORMED BAR, GRADE 500

PLAIN ROUND BAR, GRADE 250

HARD DRAWN WIRE FABRIC SQUARE OR SL/RL

RECTANGULAR FOLLOWING THIS SYMBOL A NUMERAL INDICATES THE SPECIFIED DIAMETER. PROVIDE BAR SUPPORTS OR SPACERS TO PROVIDE CONCRETE COVER AS DETAILED TO ALL REINFORCEMENT.

CONCRETE PAVEMENTS

1. CONCRETE MIX PARAMETERS -

MIX PARAMETERS
a) MAXIMUM AGGREGATE SIZE 20mm

b) FLEXURAL STRENGTH AT 28 DAYS = 3.5 MPa (Fc=32MPa)

c) FLEXURAL STRENGTH AT 90 DAYS = 3.85 MPa

d) MAXIMUM STRENGEMENT RATIO = 0.55

e) MAXIMUM SHRINKING LUMIT = 850 MICRON STRAINS (AS1012 pt 13)

f) MINIMUM CEMENT CONTENT = 300kg/m² g) CEMENT TO BE TYPE "SL" (NORMAL CEMENT) to AS3972

h) SLUMP = 80mm SAWN JOINTS ARE TO BE CUT NOT SOONER THAN 24 HOURS AND NOT LATER THAN 48 HOURS AFTER CONCRETE POUR TO AVOID DAMAGING THE SURFACE DURING SAWCUT OR AS DIRECTED BY THE SUPINTENDENT

AVOID DAMAGING THE SURFACE DURING SANCUT OR AS DIRECTED BY THE SUPINTENDENT.

JOINT LAYOUT SHALL BE AS DETAILED ON THE PLANS.
PROVIDE: 10mm WIDE EXPANSION JOINTS BETWEEN ALL BUILDINGS, OTHER STRUCTURES AND PAVEMENTS.
BOND BREAKER TO BE TWO (2) UNIFORM COATS OF BITUMEN EMULSION ALL OVER THE EXPOSED SURFACE AND ON END.

DOWELS AND TE BARS TO MEET STRENGTH REQUIREMENTS OF STRUCTURAL GRADE STEEL IN ACCORDANCE WITH AS ISO

302-2005-GEOMETRICAL PRODUCT SPECIFICATIONS. DOWELS AND TIE BARS SHALL BE
a) STRAIGHT,

b) TO LENGTH SPECIFIED,
c) ALL DOWELS TO BE HOT DIP GALVANNSED,
d) SAWN TO LENGTH HOT CROPPED.

DIMENSIONS OF SEALANT RESERVOIR DEPENDANT ON THE SEALANT TYPE ADOPTED. SUPERINTENDENT APPROVAL TO BE
OBTAINED FOR SEALANT RADS RESERVOIR DIMENSIONS AND DETAIL PROPOSED BY THE CONTRACTOR. REFER TO PLANS
FOR TYPICAL ARRANGEMENT AND SEALANT

FOR TYPICAL ARRANGEMENT AND SEALANT.
PRIOR TO THE PLACEMENT OF CONCRETE IN THE ADJACENT SLAB, 'ABLEFLEX' FILLER SHALL BE ADHERED TO THE ALREADY CAST AND CLEANED CONCRETE FACE USING AN APPROVED WATERPROOF ADHESIVE. ADHESIVE SHALL BE LIBERALLY APPLIED TO THE FULL FACE OF THE CONCRETE SLAB TO BE COVERED BY THE FILLER, AND ON THE FULL FACE

OF TIRE PALLEY TO BE ADMINISED.

THE BASE CONTRES SHALL BE KEPT MOIST (NOT WET) BY SPRINKLING WITH WATER IMMEDIATELY PRIOR TO POURING THE CONCRETE.

ALL WORK TO BE FINISHED TO SATISFY ITS INTENDED USE AS SHOWN ON THE PLANS, AND / OR IN ACCORDANCE WITH THE SPECIFICATION.

KERBING NOTES

1. ALL CONCRETE KERBS TO HAVE A MINIMUM CHARACTERISTIC COMPRESSIVE STRENGTH Fc=25MPa (UNO).

2. ALL KERBS, DISH DRAINS, etc. TO BE CONSTRUCTED ON 75mm MINIMUM BASE COURSE.

3. KERB EXPANSION JOINTS SHALL BE FORMED FROM 10mm COMPRESSIBLE CORK FILLER BOARD FOR THE FULL DEPTH OF THE SECTION.

EXPANSION JOINTS SHALL BE LOCATED AT DRAINAGE PITS, ON TANGENT POINTS OF CURVES AND ELSEWHERE AT 6m

REV DATE AMENDMENT / REVISION DESCRIPTION

INCORPORATED BRS COMMENTS DATED 22-12-2016

27-01-17

05-06-17

MAXIMUM SPACING (UNO).
TOOLED JOINTS SHALL BE MIN 3mm WIDE AND LOCATED AT MAXIMUM 3m SPACING. INTEGRAL KERB JOINTS SHALL MATCH THE LOCATION OF THE PAVEMENT JOINTING.

LINEMARKING MATERIALS, LAYOUT, TYPE & WORKS TO BE IN ACCORDANCE RMS QA SPECIFICATIONS FOR ROADWORKS
THE SCOPE OF WORK SHALL INCLIDE ALL PAVEMENT MARKINGS TO ROADS AND CARPARKS.
THE WORK CARRIED OUT AND TESTING PERFORMED SHALL COMPLY WITH THE CURRENT, RELEVANT AUS-SPEC SPECIFICATIONS &

AUSTRALIAN STANDARDS WHERE NECESSARY.
ALL MARKINGS SHALL BE SPOTTED OUT AND APPROVED BY THE SUPERINTENDENT PRIOR TO APPLICATION.

PAINT SHALL BE APPLIED AT A WET THICKNESS OF BETWEEN 0.35mm - 0.45mm.

UNLESS OTHERWISE SPECIFIED, PERMITTED OR SHOWN ON THE DRAWINGS, PAINT SHALL BE WHITE, WITHOUT GLASS BEADS.

EITHER SOLVENT OR WATERBORNE AND COMPLYING WITH THE REQUIREMENTS OF THE AUSTRALLAN STANDARD

PAINT SHALL ONLY BE APPLIED TO CLEAN AND DRY SURFACES.

PAINT SHALL ONLY BE APPLIED TO CLEAM AND DRY SURFACES.
ALL LONGTUDINAL LINES SHALL BE APPLIED BY A SELF-PROPELED MACHINE.
LINEMARKING REMOVAL SHALL BE CARRIED OUT BY GRINDING OR SANDBLASTING, REMOVAL BY BURNING WILL NOT BE PERMITTED.
THE EXTENT OF LINEMARKING TO BE ERADICATED SHALL BE COMFIRMED ON SITE PRIOR TO REMOVAL ANY MARKINGS INCORRECTLY
REMOVED SHALL BE REINSTATED AT THE CONTRACTOR'S EXPENSE.
ALL MARKINGS SHALL BE COMPLETED IN A WORKMAN LIKE MANNER AND BE STRAIGHT, SMOOTH AND WITH EVEN CURVES. ANY
NON-CONFORMING WORK, SHALL BE REMOVED AND REINSTATED AT THE DIRECTION OF THE SUPERINTENDENT AT THE CONTRACTORS
EVENSES.

IF FINAL SEAL LAYER LAID, ALL LINEMARKING SHALL BE THERMOPLASTIC.



Transport Roads & Maritime Services

These plans are accepted for construction

Vande Project Manager Date 07/08//7

FOR CONSTRUCTION

DRAWINGS / DESIGN PREPARED BY APPROVAL SCALES ON A3 SIZE DRAWING DRAWN DESIGN Meinhardt Australia Pty Ltd DESIGN MNGR PENOCH CO-ORDINATE SYSTEM HEIGHT DATUM

DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING

DESIGN LOT CODE

WVR No.

PLOT DATE / TIME PLOT BY CLIENT 29/07/2016 2:21:41 PM Aseip NAME DATE Transport D.CREARY **NSW** M.GRINHAM DRG CHECK Services A PHAM

BRANCH NAME

SECTION NAME

DEPARTMENT NAME

TITLE

DESIGN CHECK

PROJECT MINGR P.ENOCH

S.DUNSTONE

Roads & Maritime

HORNSBY SHIRE COUNCIL MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON GALSTON GRANGE DEVELOPMENT

ISSUE STATUS

GENERAL NOTES SHEET 2 OF 2

SHEET 03 OF 23 RMS REGISTRATION No. DS2016 / 002140 PART 01 GE-0201A B


© Roads and Maritime Services

A3

DRAWING FILE LOCATION / NAME EXTERNAL REFERENCE FILES

DRAWING FILE LOCATION / NAME

X1111403 - Galston-Grange Refrement-Village16BIM6_3 MHT MIE16_3_4 MHT UDIMid Oural Road Drawings1DS2016-002140-DD-GE-0201-201A.dwg




FOR CONSTRUCTION

PLOT DATE / TIME 29/07/2016 2:21:41 PM HORNSBY SHIRE COUNCIL
MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH
392 GALSTON ROAD, GALSTON
GALSTON GRANGE DEVELOPMENT DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING PLOT BY LShusharina DRAWING FILE LOCATION / NAME DESIGN LOT CODE X:\\111403 - Galston-Grange Retirement-Villa Transport
Roads & Maritime
Services DRAWINGS / DESIGN PREPARED BY EXTERNAL REFERENCE FILES REV DATE AMENDMENT / REVISION DESCRIPTION APPROVAL SCALES ON A3 SIZE DRAWING DATE A 29-07-16 B 04-11-16 C 27-01-17 D 05-06-17 ISSUED FOR 100% DESIGN DEVELOPMENT D.CREARY INCORPORATED RMS COMMENTS DATED 03-08-2016 SK SK SK DRG CHECK M.GRINHAM SITE PLAN NO. OF DRAWINGS UPDATED
INCORPORATED RMS COMMENTS DATED 16-05-2017 SHEET 04 OF 23 DESIGN A.PHAM PREPARED FOR

BRANCH NAME

SECTION NAME

DEPARTMENT NAME RMS REGISTRATION No. DS2016 / 002140 DESIGN CHECK S.DUNSTONE
DESIGN MNGR P.ENOCH Meinhardt Australia Pty Ltd ISSUE STATUS FC CO-ORDINATE SYSTEM HEIGHT DATUM SHEET No. GE-0202 PROJECT MNGR P.ENOCH




PROPOSED SERVICES

THE LOCATION AND EXTENT OF PROPOSED SERVICES IS INDICATIVE ONLY AND ARE NOT TO BE USED FOR CONSTRUCTION. REFER TO AUTHORISED DOCUMENTATION BY RELEVANT AUTHORITY FOR CONSTRUCTION DETAILS



WARNING

BEWARE OF UNDERGROUND SERVICES THE LOCATIONS OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.



MID DURAL ROAD LONGITUDINAL SECTION (FOLLOW EXISTING LEVEL)



Project Manager Date. 0.7/08//7

FOR CONSTRUCTION


DRAWING FILE LOCATION / NAME


X.111403 - Galation-Grange Retirement-Village16BIIM6_3 MHT MIEV6_3_4 MHT UDUMid Dural Road DrawingsIDS2016-002140-DD-RD-0204.dwg HORNSBY SHIRE COUNCIL MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING DESIGN LOT CODE PLOT DATE / TIME PLOT BY I CLIENT 29/07/2016 2:21:41 PM LShusharina 392 GALSTON ROAD, GALSTON DRAWINGS / DESIGN PREPARED BY Transport EXTERNAL REFERENCE FILES REV DATE AMENDMENT / REVISION DESCRIPTION WVR No. | APPROVAL SCALES ON A3 SIZE DRAWING TITLE NAME DATE 1:1000 H 0 5 10 15 20 25m GALSTON GRANGE DEVELOPMENT LS-ROAD-MID DURAL A 29-07-16 ISSUED FOR 100% DESIGN DEVELOPMENT DRAWN D.CREARY Roads & Maritime 04-11-16 **NSW** DRG CHECK M.GRINHAM LONGITUDINAL SECTION Services PE PE PE 15-12-16 SCALE BAR UPDATED SK SK SK 1 2 3 4 5m DESIGN A.PHAM NO. OF DRAWINGS UPDATED SCALE 1 1000 HORIZONTAL 05-06-17 INCORPORATED RMS COMMENTS DATED 16-05-2017 1 200 VERTICAL AT ORIGINAL SIZE DESIGN CHECK S.DUNSTONE RMS REGISTRATION No. DS2016 / 002140 Meinhardt Australia Pty Ltd BRANCH NAME SECTION NAME DESIGN MNGR P.ENOCH ISSUE STATUS CO-ORDINATE SYSTEM HEIGHT DATUM PROJECT MINGR P.ENOCH DEPARTMENT NAME


RD-0204


SHEET 06 OF 23


A3






















Transport Roads & Maritime NSW Services These plans are accepted for

construction

Project Manager Date 2.7/08/17

LEGEND



CATCHMENT NAME AND CATCHMENT AREA



WARNING

PROPOSED SERVICES THE LOCATION AND EXTENT OF PROPOSED SERVICES IS INDICATIVE ONLY AND ARE NOT TO BE USED FOR CONSTRUCTION. REFER TO AUTHORISED DOCUMENTATION BY RELEVANT AUTHORIST DOCUMENTATION BY RELEVANT AUTHORITY FOR CONSTRUCTION DETAILS

WARNING

BEWARE OF UNDERGROUND SERVICES THE LOCATIONS OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.

FOR CONSTRUCTION

8								
	DRAWING FILE LOCATION / NAME				DESIGN LO	T CODE	DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS	DRAWING
22	X:\111403 - Galston-Grange Retirement-Village\6BIM16_3 MHT MIE\6_3_4	MHTU	OMid Dural Ros	ad Drawings1DS2016-002140-DD-SM-0200-0201.dwg				
	EXTERNAL REFERENCE FILES	REV	DATE	AMENDMENT / REVISION DESCRIPTION	WVR No.	APPROVAL	SCALES ON A3 SIZE DRAWING	DRAWINGS / DESIGN PREPARED BY
- 5	X-111403-IE-BASE	Α	14-11-16	INCORPORATED RMS COMMENTS DATED 03-08-2016	SK	PE		
2	X-111403-IE-BASE DRAI	В	15-12-16	INCORPORATED RMS COMMENTS DATED 03-08-2016	SK	PE	0 2.5 5 7.5 10 12.5m	
-	X-111403-IE-BASE CATC	C	27-01-17	INCORPORATED BRS COMMENTS DATED 22-12-2016	SK	PE		
0	X-111403-IE-DESIGN CONTOURS	D	05-06-17	INCORPORATED RMS COMMENTS DATED 16-05-2017	SK	PE	SCALE 1:500 AT ORIGINAL SIZE	
_	X-111403-Survey				3			
_	X103976-00-SURVEY							Meinhardt Australia Pty Ltd
			l				AA ABBULLET SVATELL LICIBUT DATUM	

MGA ZONE 56

AHD

	TITLE	NAME
	DRAWN	D.CREARY
	DRG CHECK	M.GRINHA
	DESIGN	A.PHAM
	DESIGN CHECK	S.DUNSTO
ty Ltd	DESIGN MINGR	P.ENOCH
	PROJECT MNGR	P.ENOCH

PLOT DATE / TIME 29/07/2016 2:		PLOT S Aseig		CLIENT	
TITLE	NAME		DATE	A STATE	Transport
DRAWN	D.CREARY				Roads & Maritir
DRG CHECK	M.GRINHAM			NSW	Services
DESIGN	A.PHAM			401201211	
DESIGN CHECK	S.DUNSTONE			PREPARED FOR	
DESIGN MNGR	P.ENOCH			BRANCH NAM SECTION NA	
PROJECT MNGR	P.ENOCH			DEPARTMEN	

Transport Roads & Maritime Services


HORNSBY SHIRE COUNCIL MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON GALSTON GRANGE DEVELOPMENT

CATCHMENT PLAN

SHEET 12 OF 23

A3

RMS REGISTRATION No. DS2016 / 002140 ISSUE STATUS SM-0201



PIT SCHEDULE

PIT		INTERNAL		INLET		OUTLET		PIT		REMARKS
NAME	TYPE	WD	LEN	DIA	INV LEV	DIA	INV LEV	SETOUT RL	DEPTH	
377	ENGPIPE			175	197 350					EXISTING
La silva				450	197 740	£5.	197 360	1/E.25(I	1,790	EAISTING
112	EHSTING					15/1	198.500	199.531	1.250	EXISTING
1/2A	IP	2000	850	375	197.943	450	197.923	199,400	1,577	
1/3	SA2	2000	850	375	198.519	375	198.382	199.881	1.599	AS PER RMS STANDARD DRAWING R0220-50
1/4	SA2	2000	850	450	199.369	375	199,281	200,712	1,531	AS PER RMS STANDARD DRAWING R0220-50
				375	199.281					
1/5	SA2	2000	850	375	200,385	375	200,343	201.751	1,508	AS PER RMS STANDARD DRAWING R0220-50
1/6	SA2	2000	850	375	200.872	375	200,852	202,317	1,565	AS PER RMS STANDARD DRAWING R0220-50
1/7	IP IP			375	201,243	375	201,163	202.624	1,561	
1/8	SA2	2000	850	375	201.471	375	201,451	202,680	1,329	AS PER RMS STANDARD DRAWING R0220-50
1/9	SA2	2000	850			375	201.532	202.537	1.105	AS PER RMS STANDARD DRAWING R0220-50
2/1	SA2	2000	850	375	199.437	450	199.417	200.785	1.468	AS PER RMS STANDARD DRAWING R0220-50
2/2	SA2	2000	850	375	200.424	375	200.373	201.774	1.501	AS PER RMS STANDARD DRAWING R0220-50
										-
2/4	SA2	2000	850			375	200.804	202.183	1.479	AS PER RMS STANDARD DRAWING R0220-50
3/4	ENGPIES.			351	153:400					EXIDENCE

Transport Roads & Maritime NSW Services These plans are accepted for

construction /

Project Managet Date: 0.7/08/17....

ALL RCP PIPES ARE CLASS 3 AND RUBBER RING JOINTED. DRAINAGE CONSTRUCTED AS PER THE RMS SPECIFICATION R11.

FOR CONSTRUCTION

N CONTROL OF THE CONT DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING DESIGN LOT CODE DRAWINGS / DESIGN PREPARED BY WVR No. | APPROVAL | SCALES ON A3 SIZE DRAWING A 29-07-16
B 04-11-16
C 27-01-17
D 28-04-17
E 05-06-17 ISSUED FOR 100% DESIGN DEVELOPMENT INCORPORATED RMS COMMENTS DATED 03-08-2016 SK SK SK SK INCORPORATED RMS COMMENTS DATED 13-03-2017 INCORPORATED RMS COMMENTS DATED 16-05-2017 Meinhardt Australia Pty Ltd 14-07-17 INCORPORATED RMS COMMENTS DATED 04-07-2017 HEIGHT DATUM CO-ORDINATE SYSTEM MGA ZONE 56 AHD

PLOT DATE / TIME 29/07/2016 2:21:41 PM PLOT BY Aseip TITLE NAME DRAWN D.CREARY DRG CHECK M.GRINHAM DESIGN A.PHAM DESIGN CHECK S.DUNSTONE DESIGN MNGR P.ENOCH PROJECT MINGR P.ENOCH

DATE Services

BRANCH NAME SECTION NAME DEPARTMENT NAME

Transport Roads & Maritime

HORNSBY SHIRE COUNCIL MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON A3

GALSTON GRANGE DEVELOPMENT

ISSUE STATUS

PIT SCHEDULE SHEET 14 OF 23 RMS REGISTRATION No. DS2016 / 002140

SM-0210 © Roads and Maritime Services

MID DURAL ROAD ASPHALT FULL **DEPTH ROAD PAVEMENT SPECIFICATION**


DESIGN PARAMETERS

- 7.6 x 10 DESA (ESA) DSAR 5 (SAR 5) - 8,66 x 10 DSAR 7 (SAR 7) - 1,31 x 10* SUBGRADE DESIGN CBR (%) - 3

LAYER	MATERIAL NAME	THICKNESS (mm)	BINDER TYPE	
Z	AC14	50	AR450 BITUMEN	
Y	AC20	150	AR450 BITUMEN	İ
×	LOW CUTTER SEAL	7		
W	SMZ	300	~~~	K
٧	SUBGRADE	3% CI	BR (Min.)	

FLEXIBLE PAVEMENT NOTES:

- ALL EARTHWORKS INCLUDING SUBGRADE PREPARATION SHALL BE AS PER RMS
 SPECIFICATION R44
 THE PAVEMENT THICKNESS SHALL BE SUBJECT TO SUBGRADE TESTING BY REGISTERED
- NATA LABRATORY
 THE SMZ LAYER IS A STANDARD REQUIREMENT IN RMS PAVEMENTS AND SHOULD COMPLY TO THE RMS OA SPECIFICATION 3071



CONCRETE VEHICULAR CROSSING / **BUS SHELTER PAVEMENT**

NOT TO SCALE (TO BE CONSTRUCTED SIMILAR TO RMS STANDARD DRAWING DS 2012/00293 SHEET 3)

CROSSING & BUS SHELTER PAVING NOTES:

- ISOLATION JOINTS MUST BE PROVIDED AT THE FIRST JOINT AWAY FROM JUNCTIONS WITH FLEXIBLE PAVEMENTS AND STRUCTURES, AND AT (max.) INTERMEDIATE CENTRES OF 17.5m (E.G. THREE SHEETS OF 6m LENGTH MESH.
- 2. ISOLATION JOINTS CAN BE CONSTRUCTED AS FORMED JOINTS (BY

- 2. ISOLATION JOINTS CAN BE CONSTRUCTED AS FORMED JOINTS (BY CHEQUERBOARD PAVING SEQUENCE), OR BY FULL DEPTH SAWCUT.

 3. PLACE A FULL DEPTH ISOLATION JOINT AROUND ALL ABUTTING STRUCTURES SUCH AS PITS, UTILITY SERVICES, POWER POLES, KERBS.

 4. THE OPTIONS FOR RUDO-DAY CONSTRUCTION JOINTS ARE AS FOLLOWS

 (i) TRANSVERSE CONSTRUCTION/FORMED/TIED JOINTS MAY BE USED. THEY MUST BE LOCATED EITHER MIDWAY BETWEEN ISOLATION JOINTS OR IN LEU OF A TRANSVERSE HINGETHED/SAWN JOINT. THEY MUST NOT BE USED IN LIEU OF A TRANSVERSE HINGETHED/SAWN JOINT. THEY MUST NOT BE USED IN LIEU OF A TRANSVERSE HINGETHED/SAWN JOINT. THEY MUST NOT BE USED IN LIEU OF A ISOLATION JOINT.


 5. COMPLY WITH RMS SPECIFICATIONS RS3 AND R173. CONCRETE MUST BE IN ACCORDANCE WITH RMS RS3 BUT WITH A MINIMUM COMPRESSIVE STRENGTH OF 32.0 MPs.
- OF 32.0 MPs.


 6. SELF-EXPANDING CORK SEALANTS MUST FILL THE FULL JOINT CAVITY TO
- PREVENT THE INCRESS OF INCOMPRESSIBLE MATERIALS.

 7. SUB BASE MUST BE 150mm THICK TRAFFIC CATEGORY D MATERIAL IN ACCORDANCE WITH RMS SPECIFICATION 3051, COMPACTED IN ACCORDANCE WITH RMS R173. MOISTEN THE SUB BASE WITH WATER BEFORE PLACING THE
- 8. DEBOND TYPE TRANSVERSE CONSTRUCTION/FORMED/TIED JOINTS TO PREVENT
- BEBOND TYPE TRANSVERSE CONSTRUCTION/FORMED/TIED JOINTS TO PREVENT CHEMICAL BONDING.
 SHOURE BEINFORCING STEEL IS PLACED TO PROVIDE 30mm MINIMUM COVER BELOW THE SAWCUT.
 WHERE FILLING UNDER PROPOSED BUS BAY AND VEHICULAR CROSSING IS NECESSARY, SUCH FILLING SHALL CONSIST OF GRANULAR MATERIAL. OF 20mm MAXIMUM SIZE AND SHALL BE SPREAD IN LYERS OF A MAXIMUM THICKNESS OF 150mm AND CONSOLIDATED TO PROVIDE A 95% COMPACTION WHEN TESTED UNDER THE MODIFIED PROCTOR METHOD AS PER HORNISBY SHIRE COUNCIL'S VEHICULAR CROSSING SPECIFICATION


TYPICAL CONCRETE FOOTPATH PAVEMENT JOINTING NOTES:

- 1 ALL FOOTPATH PAVEMENTS TO BE JOINTED AS SHOWN ON DRAWINGS
- 1. ALL FOOTPATH PAVEMENTS TO BE JOINTED AS SHOWN ON DRAWINGS.
 2. SAWN JOINTS (SC) SHOULD GENERALLY BE LOCATED AT A MAXIMUM OF 3M. CENTRES,
 3. PROVIDE ZOMM WIDE FULL DEPTH ISOLATION JOINTS (IJ) BETWEEN BUILDINGS,
 SERVICE PITS AND ALL CONCRETE OR UNIT PAVERS.
 4. SET OUT FOOTPATH PAVEMENT JOINTING GENERALLY AS FOLLOWS.
 5. PROVIDE 2N12 TRIMMER BARS AT ALL RE-ENTRANT CORNERS.
 6. WHERE FILLING UNDER PROPOSED CONCRETE FOOTPATH IS NECESSARY; SUCH
 FILLING SHALL CONSIST OF GRANULAR MATERIAL OF ZOMM MAXIMUM SIZE AND SHALL
 BE SPREAD IN LAYERS OF A MAXIMUM THICKNESS OF 150mm AND CONSOLIDATED TO
 BEDOUDE A 86X COMBACTION WHEN TESTED LINGED THE MODISIER PROTOR METHOD PROVIDE A 95% COMPACTION WHEN TESTED UNDER THE MODIFIED PROCTOR METHOD AS PER HORNSBY SHIRE COUNCIL'S VEHICULAR CROSSING SPECIFICATION







MID DURAL ROAD ASPHALT MILL AND RESHEET SPECIFICATION



ISOLATION JOINT (IJ) SCALE 1 40








TEMPORARY SEAL

- INITIAL 3-5 SAWCU


'DOW-CORNING 888' SILICONE SEALANT TO BE STRICTLY IN ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS. PREFERABLY INSTALLED BY A SPECIALIST,

100 CLOSED CELL EXPANDED

SA TYPE KERB (SA) N.T.5:




MEDIAN ISLAND DETAIL SCALE 1 40



TRANSVERSE CONSTRUCTION/FORMED/TIED JOINT OF CONCRETE VEHICULAR CROSSING/BUS SHELTER PAVEMENT

AT START AND END OF DAILY PAVING OPERATIONS. SEE NOTE 4 SCALE NTS



SF TYPE KERB (SF)

SM TYPE KERB (SM)



Transport Roads & Maritime Services

These plans are accepted for construction

Project Manager Date 07/08/17

SECTION NAME

DEPARTMENT NAME

FOR CONSTRUCTION

DRAWING FILE LOCATION / NAME DESIGN LOT CODE DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING PLOT DATE / TIME 🙁 X\111403 - Galston-Grange Retirement-Villagel6BIM6_3 MHT MIE\6_3_4 MHT UD\Mid Dural Road DrawingsIDS2016-002140-DD-PV-0214-0215.dwg EXTERNAL REFERENCE FILES REV DATE AMENDMENT / REVISION DESCRIPTION WVR No. APPROVAL SCALES ON A3 SIZE DRAWING DRAWINGS / DESIGN PREPARED BY TITLE NAME A 29-07-16 ISSUED FOR 100% DESIGN DEVELOPMENT
B 14-11-16 INCORPORATED RMS COMMENTS DATED 03 DRAWN INCORPORATED RMS COMMENTS DATED 03-08-2016 DRG CHECK 14-12-16 INCORPORATED RMS COMMENTS DATED 03-08-2016 DESIGN 27-01-17 INCORPORATED BRS COMMENTS DATED 22-12-2016 INCORPORATED RMS PAVEMENT COMMENTS DATED 13-03-2017 07-04-17 Meinhardt Australia Pty Ltd 2404-17 INCORPORATED RMS PAVEMENT COMMENTS DATED 13-03-2017 DESIGN MNGR P.FNOCH CO-ORDINATE SYSTEM HEIGHT DATUM INCORPORATED RMS PAVEMENT COMMENTS DATED 16-05-2017 05-05-17 PROJECT MINGR P.ENOCH MGA ZONE 56 AHD INCORPORATED RMS PAVEMENT COMMENTS DATED 04-07-2017

PLOT BY CLIENT 29/07/2016 2:21:41 PM Aseip DATE D.CREARY M.GRINHAM A.PHAM DESIGN CHECK S.DUNSTONE BRANCH NAME

Transport Roads & Maritime Services

HORNSBY SHIRE COUNCIL MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON GALSTON GRANGE DEVELOPMENT

TYPICAL DETAILS SHEET

RMS REGISTRATION No. DS2016 / 002140 ISSUE STATUS

© Roads and Maritime Services

D.D.A. PEDESTRIAN

FOOTWAY 2,0 m

120mm THICK 25MPa CONCRETE

-75 THICK APPROVED GRANULAR FILL

MAX. 2.5%


TYPICAL SECTION


PEDESTRIAN FOOTWAY

ROAD SIDE


PV-0214

SHEET 15 OF 23





LONGITUDINAL CONSTRUCTION JOINT REINSTATEMENT



CONCRETE DRAINAGE PIPE TRENCH DETAIL - NON PAVED AREAS





These plans are accepted for construction

Project Manager Date 07/08/17

FOR CONSTRUCTION

DRAWING FILE LOCATION / NAME DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING PLOT BY HORNSBY SHIRE COUNCIL A3 🙁 X1111403 - Galston-Grange Retirement-Villagei6BIMi6_3 MHT MIE16_3_4 MHT UDUMid Dural Road DrawingsIDS2016-002140-DD-PV-0214-0215.dwg 29/07/2016 2:21:41 PM syenikapati MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH REV DATE AMENDMENT / REVISION DESCRIPTION SCALES ON A3 SIZE DRAWING DRAWINGS / DESIGN PREPARED BY 392 GALSTON ROAD, GALSTON EXTERNAL REFERENCE FILES TITLE Transport INCORPORATED RMS COMMENTS DATED 03-08-2016 D.CREARY GALSTON GRANGE DEVELOPMENT DRAWN Roads & Maritime NSW 14-12-16 27-01-17 INCORPORATED RMS COMMENTS DATED 03-08-2016 DRG CHECK M.GRINHAM TYPICAL DETAILS SHEET INCORPORATED BRS COMMENTS DATED 22-12-2016 Services DESIGN A.PHAM SHEET 16 OF 23 07-04-17 INCORPORATED RMS PAVEMENT COMMENTS DATED 13-03-2017 INCORPORATED RMS PAVEMENT COMMENTS DATED 16-05-2017 05-06-17 RMS REGISTRATION No. DS2016 / 002140 DESIGN CHECK | S.DUNSTONE BRANCH NAME SECTION NAME DEPARTMENT NAME 14-07-17 INCORPORATED RMS PAVEMENT COMMENTS DATED 04-07-2017 Meinhardt Australia Pty Ltd DESIGN MNGR P.ENOCH CO-ORDINATE SYSTEM MGA ZONE 56 02,08,17 INCORPORATED RMS PAVEMENT COMMENTS DATED 02-08-2017 K₩ PV-0215 AHD PROJECT MINGR P.ENOCH






OUR AND MAY BE INCOMPLETE IF COPIED | 145 | 50mm ON A3 SIZE ORIGINAL






MC200

JOIN DRAWING BELOW



MID



		SET	OUT TABL	E - KERB	KR I		
Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.Angle
IP1	0.000	318047.495	6274720.204	112*22'33.01"			
IP2	5.786	318052.868	6274717.992		-50.5	11.571	13°07'41.85°
IP3	11.571	318058.604	6274717.058				
IP4	24,612	318071,499	6274715,113				
IP5	30,106	318076.937	6274714.296		-100.5	10.988	6°15'51.02°
CT	35.600	318082.432	6274714.077	92*16'52.15*			
TC	57.126	318103.941	6274713.220	92*16'52.15*		ENEE JOH	
IP6	62.247	318109.062	6274713.016	10	99.5	10,241	5*53'49,71*
IP7	67.367	318114,135	6274712,287				
IP8	76.907	318123.578	6274710.930		-1992.8	19.079	0°32'54.80"
IP9	86,447	318133,033	6274709,663				
IP10	87.923	318134.502	6274709.467		14.5	2.954	11°40'18.98°
СТ	89.400	318135.901	6274708.977	109°18'06.04°			
IP11	102.346	318148.119	6274704.697				
IP12	105,188	318150.809	6274703.756		-30.5	5.683	10°40'31.44°
IP13	108,029	318153,626	6274703,328				
IP14	118,943	318164.419	6274701.691		503.7	21.829	2°28'58.78°
IP15	129.858	318175.130	6274699,588				
IP16	137.836	318182.959	6274698.050		-496.3	15.956	1°50'31.31°
IP17	145.814	318190.834	6274696,765				
[P18	150,548	318195,591	6274695,989		-20.5	9,468	26*27'43,92"
IP19	155.282	318200.195	6274697.414	72*48*18.16*	1		

B278*33725* DURAL

		SET	OUT TABL	E - KERB	KR G		
Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.Angle
1P1	0.000	318073.389	6274695.018	8*39'48.67"			
TC	1.771	318073.656	6274696.769	8*39'48.67*			
IP2	9.242	318075.090	6274706.180		-9.5	14.942	90*07'05.50*
CT	16,713	318065,676	6274707,595	278*32'43,17"			1
TC	27.456	318055.052	6274709.191	278°32'43.17"			
IP3	32,120	318050.427	6274709.886		-50.5	9.328	10"35'00.11"
IP4	36.784	318045.752	6274709.720	267°57'43.06°			

Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.Angle
IP1	0.000	318264,527	6274675.298	297*20'14,54*			
IP2	8.202	318257,177	6274679.098		-50.5	16.404	18°36'39.95"
CT	16.404	318248.998	6274680.353	278*43'34,59*			
TC	19,981	318245.462	6274680,896	278°43'34,59"			
IP3	25.148	318240.350	6274681.681		-100.5	10,334	5*53'29,55"
СТ	30.315	318235.185	6274681.936	272°50'05.04"			
TC	54.139	318211.391	6274683.115	272"50"05.04"			
IP4	59.089	318206.442	6274683,360		99.5	9.901	5*42'04.07"
CT	64.039	318201,543	6274684,095	278*32'09.10"			
IP5	70.389	318195.263	6274685.038				
IP6	76.221	318189,496	6274685,903		-492.8	11,663	1"21'21,46"
1P7	82.052	318183.710	6274686.632				
IP8	83,517	318182.251	6274686,816		14,5	2,931	11*34'48.90*
CT	84,983	318180,859	6274687.289	288*45'36.54*			
IP9	96.771	318169.697	6274691.080				
IP10	99,861	318166,761	6274692 077		-30,5	6.181	11*36'39,45*
IP11	102.952	318163.684	6274692.463				
IP12	114,371	318152,351	6274693,884		503.7	22,84	2*35'52,81*
IP13	125.791	318141.094	6274695.818				
IP14	135.109	318131.911	6274697.396		-1996.3	18.635	0"32'05.43"
CC	144.426	318122.714	6274698.887	279*12'44.47"			
IP15	145.409	318121.740	6274699.045		-10.5	1,967	10"43'55.65"
IP16	146.393	318120.754	6274699.019				
IP17	162.958	318104.200	6274698.428				i i
IP18	163.844	318103.312	6274698.396		9.5	1.771	10°41'02.59°
IP19	164.730	318102.434	6274698.530		-119H 22		
IP20	166.349	318100.833	6274698.773		-1992.8	3.238	0*05'35,16"
CT	167.968	318099.232	6274699,013	278*32'43.17*			
TC	179.730	318087.601	6274700.761	278*32'43.17*			
IP21	185.612	318080.199	6274701.873	0	-7.5	11,766	89*52'54.50"
CT	191.495	318079.072	6274694.474	188*39'48.67*	1		
IP21	185.612	318080.199	6274701.873		-7.5	11.766	

FOR	CONSTRUCTION	
IOI	CONSTITUTION	ı

A3

8								
	DRAWING FILE LOCATION / NAME				DESIGN LO	T CODE	DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS	DRAWING
23	X:\111403 - Galston-Grange Retirement-Village\68IM16_3 MHT MIE\6_3_4	MHTU	O'Mid Dural Ros	d Drawings\DS2016-002140-DD-SO-0217.dwg				
,	EXTERNAL REFERENCE FILES	REV	DATE	AMENDMENT / REVISION DESCRIPTION	WVR No.	APPROVAL	SCALES ON A3 SIZE DRAWING	DRAWINGS / DESIGN PREPARED BY
7	X - 111403 - SetoulGR	A	29-07-16	ISSUED FOR 100% DESIGN DEVELOPMENT				
2	X - 111403 - IE - BASE	В	14-11-16	INCORPORATED RMS COMMENTS DATED 03-08-2016	SK	PE	0 2.5 5 7.5 10 12.5m	
	X - 111403 - IE - BASE PAVE	C	15-12-16	INCORPORATED RMS COMMENTS DATED 03-08-2016	SK	PE	2.0 0 1.0 10 12.011	MEINHARDT
₽	X - 111403 - IE - DESIGN CONTOURS	D	27-01-17	NO. OF DRAWINGS UPDATED	SK	PE	SCALE 1:500 AT ORIGINAL SIZE	
		E	07-04-17	REVISED DRAWING PRESENTATION	SK	PE	OUTLE TOWN TO THOMP IS SEEN	
2		F	05-06-17	INCORPORATED RMS COMMENTS DATED 16-05-2017	SK	PE		Meinhardt Australia Pty Ltd
							CO-ORDINATE SYSTEM HEIGHT DATUM	
0							MGA ZONE 56 AHD	

PLOT DATE / TIME 29/07/2016 2:		PLOT		CLIENT
TITLE	NAME		DATE	Trar
DRAWN	D.CREARY			NICIAL ROA
DRG CHECK	M.GRINHAM			NSW Serv
DESIGN	A.PHAM			33,24,24,1, 7, 33,1,
DESIGN CHECK	S.DUNSTONE			PREPARED FOR
DESIGN MNGR	P.ENOCH			BRANCH NAME SECTION NAME
PROJECT MNGR	P.ENOCH			DEPARTMENT NAME

DATE	Transport Roads & Maritime Services
	PREPARED FOR
	BRANCH NAME SECTION NAME

ROAD

HORNSBY SHIRE COUNCIL MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON GALSTON GRANGE DEVELOPMENT

SETOUT PLAN SHEET 1 OF 2 RMS REGISTRATION No DS2016 / 002140

ISSUE STATUS

SHEET No. SO-0217 © Roads and Maritime Services

SHEET 18 OF 23



PROPOSED SERVICES


THE LOCATION AND EXTENT OF PROPOSED SERVICES IS INDICATIVE ONLY AND ARE NOT TO BE USED FOR CONSTRUCTION. REFER TO AUTHORISED DOCUMENTATION BY RELEVANT AUTHORITY FOR CONSTRUCTION DETAILS





WARNING

BEWARE OF UNDERGROUND SERVICES
THE LOCATIONS OF UNDERGROUND SERVICES ARE
APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD
BE PROVEN ON SITE. NO GUARANTEE IS GIVEN THAT ALL
EXISTING SERVICES ARE SHOWN.



LIP PROFILE SETOUT

KERB ALIGNMENTS

ALIGNMENT G

 Point no
 Easting
 Northing
 RL

 G1
 318073.656
 6274696.769
 202.5

 G2
 318065.676
 6274707.595
 202.6

 Curve no
 I
 Radius
 Arc
 A
 B
 X
 Y
 I
 Mid point RL

 G1 - G2
 90.118
 9.5
 14.942
 2.789
 2.064
 3.640
 3.084
 3.736
 202.632

ALIGNMENT H

 Point no
 Easting Northing RL

 H1
 318087.601
 6274700.761
 202.501

 H2
 318079.072
 6274694.474
 202.650

Curve no I Radius Arc A 8 X Y I Mid point RL H1 - H2 89.882 7.5 11.766 2.191 1.622 2.867 2.431 2.941 202.550


		SET	OUT KERE	3 ISLAND	- IS J		
Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.Angle
CC	0.000	318055,106	6274713.212	185°30'42.12°			
IP2	0.228	318055.079	6274712.929		-0.3	0.455	86°57'58.95"
ст	0.455	318055,360	6274712,886	98*32'43,17"			
TC	43.328	318097.757	6274706.516	98*32'43.17"			
IP3	44,387	318098.805	6274706.358		-20	2.118	6*04'02,11*
СТ	45,446	318099.864	6274706.312	92*28'41,06"			
TC	47.240	318101.656	6274706.235	92°28'41.06"			
IP4	47.468	318101,941	6274706.223		-0.3	0.455	86°57'58.95°
СС	47.695	318101.968	6274706.506	5*30'42.12*			
IP5	47,923	318101,995	6274706,789		-0.3	0.455	86*57"58.95*
ст	48.151	318101.714	6274706.831	278°32'43.17"			
TC	91.023	318059.317	6274713.202	278*32'43.17*			
IP6	92.082	318058.269	6274713.359		-20	2.118	6"04'02.11"
СТ	93.141	318057.210	6274713.405	272*28'41.06*			
TC	94.935	318055,417	6274713.483	272°28'41.06°			
IP1	95,163	318055.133	6274713.495		-0.3	0.455	86°57'58.95°
CC	95.391	318055,106	6274713.212	185°30'42.12"			


		SET	OUT KERE	ISLAND -	ISK		
Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.Angle
IP1	0.000	318154.614	6274699.443	275*34'39.13*			
IP2	2.937	318151.652	6274699.732		-15	5.875	22*26'26.30*
IP3	5.875	318148.805	6274698.869				
IP4	6,077	318148,575	6274698.799		-0.3	0.405	77*17'43.36*
CC	6.280	318148,593	6274698.560	175°50'26.53"			
IP5	6.482	318148.610	6274698.321		-0.3	0.405	77°17'43.36"
CT	6.684	318148,847	6274698,285	98°32'43.17°			
TC	12.231	318154.332	6274697.461	98°32'43.17°			
IP6	12.466	318154,628	6274697,417		-0.3	0,471	90°00'00.00°
CT	12.702	318154,673	6274697,713	8*32'43.17*			
TC	14.104	318154.881	6274699.100	8"32'43.17"			
IP7	14,348	318154,928	6274699,412		-0.3	0.487	92°58'10.06"
IP8	14.591	318154.614	6274699.443	275*34'33.11"			


		SETO	UT KERE	3 ISLAND	- IS L		
Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A,Length	D.Angle
IP1	0,000	318157,896	6274696.912	97*20'27.09"			
IP2	2.937	318160.847	6274696,531		-15	5.875	22*26'26.30*
IP3	5.875	318163.720	6274697,307				
IP4	6.077	318163.952	5274697.369		-0.3	0,405	77*17'43,36"
cc	6.280	318163.942	6274697.609	357*36'14.49"			
IP5	6.482	318163.932	6274697.548		-0.3	0.405	77*17'43.36*
СТ	6.684	318163.696	6274697.891	280°18'31.13"			
TC	12.231	318158.239	6274698.884	280°18'31.13°			
IP6	12.466	318157,944	6274698,938		-0.3	0.471	90*00'00,00*
ст	12.702	318157.890	6274698,642	190°18'31.13"			
TC	14,104	318157.639	6274697.263	190°18'31,13"			
IP7	14.348	318157.583	6274696.952		-0.3:	0.48?	92°58'10.06"
\$P8	14.591	318157.896	6274696.911	97*20*21.07*			


FOR CONSTRUCTION

ĕ													
	DRAWING FILE LOCATION / NAME			DESIGN L	T CODE	DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF	THIS DRAWING	PLOT DATE / TIME PLOT BY 29/07/2016 2:21:41 PM Aseip		PLOT BY	CLIENT	HORNSBY SHIRE COUNCIL	Δ3
22	X:\111403 - Galston-Grange Retirement-Village\6BIM\6_3 MHT MIE\6_3_4	MHT UD\Mid Dural R	oad Drawings\DS2016-002140-DD-SO-0218.dwg	l						Aseip		MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH	IAU
0	EXTERNAL REFERENCE FILES	REV DATE	AMENDMENT / REVISION DESCRIPTION	WVR No.	APPROVAL	SCALES ON A3 SIZE DRAWING	DRAWINGS / DESIGN PREPARED BY	TITLE	NAME	DATE	Transport	392 GALSTON ROAD, GALSTON	
	X - 111403 - Setout	A 29-07-16	ISSUED FOR 100% DESIGN DEVELOPMENT					DRAWN	D.CREARY		Section 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	GALSTON GRANGE DEVELOPMENT	
	X - 111403 - IE - BASE	B 14-11-16	INCORPORATED RMS COMMENTS DATED 03-08-2016	SK	PE	0 5 10 15 20 25m	MEIN-MRDT	DRG CHECK	M.GRINHAM		NSW Roads & Maritime Services	SETOUT PLAN	
	X - 111403 - IE - BASE PAVE	C 27-01-17 D 07-04-17	NO, OF DRAWINGS UPDATED REVISED DRAWING PRESENTATION	SK	PE nc			DESIGN	A.PHAM		GOVERNMENT I SEI VICES	SHEET 2 OF 2	SHEET 19 OF 23
-	X - 111403 - IE - DESIGN CONTOURS	E 05-06-17	INCORPORATED RMS COMMENTS DATED 16-05-2017	SK	PE PE	SCALE 1:500 AT ORIGINAL SIZE			S.DUNSTONE		PREPARED FOR	RMS REGISTRATION No. DS2016 / 002140	PART
10		1		1			Meinhardt Australia Pty Ltd				BRANCH NAME	D32010 / 002140	01
		1				CO-ORDINATE SYSTEM HEIGHT DATUM		DESIGN MNGR				ISSUE STATUS EDMS No.	SHEET No. ISSUE
0						MGA ZONE 56 AHD		PROJECT MINGR	P.ENOCH		DEPARTMENT NAME	FC	SO-0218 ISSUE
												© Roads a	nd Maritime Services









RETAINING WALL 2 (RW2) LONG SECTION



FOR CONSTRUCTION

30														
	DRAWING FILE LOCATION / NAME		-		DESIGN LO	T CODE	DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS	S DRAWING	PLOT DATE / TIME		PLOT 8		CLIENT	
135	X:\111403 - Galston-Grange Retirement-Village\6BIM\6_3 MHT MIE\6_3_4	MHT U	DWid Dural Ro	ad Drawings\DS2016-002140-DD-MS-0221-0222.dwg					29/07/2016 2:	21:41 PM	Aseip		- DA4 -	
	EXTERNAL REFERENCE FILES	REV	DATE	AMENDMENT / REVISION DESCRIPTION	WVR No.	APPROVAL	SCALES ON A3 SIZE DRAWING	DRAWINGS / DESIGN PREPARED BY	TITLE	NAME		DATE	SUMME	Tra
2	X - 111403 - SetoutGR	Α	14-11-16	INCORPORATED RMS COMMENTS DATED 03-08-2016	SK	PE	1:200 H 0 1 2 3 4 5m		DRAWN	D.CREARY			NICW	Roa
_	X - 103976-00-Survey	В	15-12-16	INCORPORATED RMS COMMENTS DATED 03-08-2016	SK	PE		A/E:NJJ/DIT	DRG CHECK	M.GRINHAM			NSW	
	X - 111403 - IE - BASE	C	27-01-16	NO. OF DRAWINGS UPDATED	SK	PE ne	1:100 V 0 0.5 1.0 1.5 2.0 2.5m	// EIN74311	DESIGN	A.PHAM			GOVERNMENT I	J EI
-	X - 111403 - IE - BASE PAVE	E	28-04-17 05-06-17	INCORPORATED RMS COMMENTS DATED 13-03-2017 INCORPORATED RMS COMMENTS DATED 16-05-2017	SK	l nc	SCALE 1.200 HORIZONTAL	22111111111					PREPARED FOR	
	X - 111403 - IE - DESIGN CONTOURS	=	105-06-17	INCORPORATED RMS COMMENTS DATED 10-03-2017	- ov	""	1/100 VERTICAL AT ORIGINAL SIZE	Meinhardt Australia Pty Ltd		S.DUNSTONE	1		BRANCH NAME	E
2	-	ļ				-	CO-ORDINATE SYSTEM HEIGHT DATUM	_ mellinalut Australia Fty Ltu	DESIGN MNGR	P.ENOCH			SECTION NAM	
_						1	MGA ZONE 56 AHD		PROJECT MNGR	P.ENOCH			DEPARTMENT	

OT DATE / TIME 9/07/2016 2:	PLOT :		CLIENT		
TLE	NAME		DATE	2000	Transport
RAWN	WN D.CREARY				Roads & Maritime
RG CHECK	CHECK M.GRINHAM				Services
ESIGN	A.PHAM				
ESIGN CHECK	CHECK S.DUNSTONE			PREPARED FOR	·
	S.DUNSTUNE				

HORNSBY SHIRE COUNCIL MID DURAL ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON GALSTON GRANGE DEVELOPMENT RETAINING WALL LONG SECTONS

ISSUE STATUS

SHEET 23 OF 23 $_{\text{RMS}}$ REGISTRATION No. $\,$ DS2016 / 002140 $\,$

A3

MS-0222 © Roads and Maritime Services

COLOUR AND MAY BE INCOMPLETE IF COPIED 40 | 145 | 150mm on a3 SIZE ORIGINAL

WARNING

PROPOSED SERVICES THE LOCATION AND EXTENT OF PROPOSED SERVICES IS INDICATIVE ONLY AND ARE NOT TO BE USED FOR CONSTRUCTION, REFER TO AUTHORISED DOCUMENTATION BY RELEVANT AUTHORITY FOR CONSTRUCTION DETAILS



SHEET INDEX

UTILITIES

PAVEMENT

LANDSCAPING PROPERTY WORKS

WARNING

BEWARE OF UNDERGROUND SERVICES THE LOCATIONS OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD RE PROVEN ON SITE NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.



HORNSBY SHIRE COUNCIL, MR 161 GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH

392 GALSTON ROAD, GALSTON

GALSTON GRANGE DEVELOPMENT

DETAILED DESIGN



LOCALITY PLAN

DRAWING LIST DS2014-000149-DD-GE-0100 COVER SHEET, INDEX & LEGEND DS2014-000149-DD-GE-0101 GENERAL NOTES SHEET 1 OF 2 DS2014-000149-DD-GE-101A GENERAL NOTES SHEET 2 OF 2 SITE PLAN DS2014-000149-DD-GE-0102 DS2014-000149-DD-RD-0103 ROAD & PAVEMENT DETAIL PLAN DS2014-000149-DD-RD-0104 LONGITUDINAL SECTION DS2014-000149-DD-RC-0105 CROSS SECTIONS SHEET 2 OF 4 DS2014-000149-DD-RC-0106 DS2014-000149-DD-RC-0107 CROSS SECTIONS SHEET 3 OF 4 DS2014-000149-DD-RC-0108 DS2014-000149-DD-PV-0109 TYPICAL DETAILS SHEET 1 OF 2 DS2014-000149-DD-PV-0110 TYPICAL DETAILS SHEET 2 OF 2 DS2014-000149-DD-UT-0110 EXISTING SERVICES PLAN DS2014-000149-DD-RF-0111 LINE MARKING AND SIGNAGE P

DS2014-000149-DD-SO-0112 SETOUT PLAN SHEET 1 OF 2

Services These plans are accepted for construction

Transport

Roads & Maritime

SETOUT PLAN SHEET 2 OF 2 DS2014-000149-DD-MS-0115 CONSTRUCTION VEHICLE TURNING PATHS PLAN


DS2014-000149-DD-SM-0130 DRAINAGE PLAN DS2014-000149-DD-SM-0131 CATCHMENT PLAN

DS2014-000149-DD-MS-0114 TURNING PATHS PLAN

DS2014-000149-DD-MS-0120 MISCELLANEOUS DETAILS

DS2014-000149-DD-SO-0113





EOD CONSTRUCTION

WING FILE LOCATION / NAME 11403 - Galston-Grange Retirement-Village\6BIM6_3 MHT MIE16_3_4 MHT UD\Galston	n Road - drawings\DS2014-000149-DD-GE-0100.dwg	LINEAR REFERENCING START: 0000, 0000, XX, 00.000 FINISH:	0000, 0000, XX, 00.000	PLOT DATE / TIME 3/11/2014 2:14:27 PM	PLOT BY Aseip	CLIENT			OAD ROAD WORKS IN ASSOCIATION	FION WITH	A3
EPARED BY	DESIGNED	REVIEWED	VERIFIED	RMS PROJECT MANAGER		THE REAL PROPERTY.	Transport	392 GALSTON ROAD, GALSTON GRANGE D			
EINHARDT				NAME NOUHAD FARAH			Roads & Maritime	GALSTON GRANGE D	DEVELOPMENT		
EINHARDT	SIGNED	signed	. SIGNED	TITLE PROJECT ENGINE			Services	RMS PROJECT No. 000149	DESIGN PROJECT NO 111403	SHEET 1 OF	21
	NAME ANH PHAM	NAME STEVE DUNSTONE	NAME PAUL ENOCH	VALIDATION AND ACCEPTA DRAWINGS AND THE DESI		PREPARED FOR BRANCH NAM	ME		S2014 / 000149		PART 01
	TITLE CIVIL ENGINEER	TITLE ASSOCIATE DIRECTOR	TITLE ASSOCIATE	THEREON IS TO BE CARRI SEPARATE PROCESS		SECTION NA DEPARTMEN	ME	ISSUE STATUS FC	EDMS No.	SHEET No. GE-0100	ISSUE D
	DATE	DATE	DATE		ED OUT UNDER			FC FC		SHEET No. GE-0100 s and Maritime So	er

 THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL, SERVICES AND OTHER
CONSULTANTS DRAWINGS THE SPECIFICATIONS AND WITH SUCH OTHER WRITTEN INSTRUCTIONS AS MAY BE ISSUED
DURING THE COURSE OF THE TENDER AND CONTRACT.
 IF ANY DISCREPANCY OCCURS ON THE DRAWINGS OR BETWEEN DRAWINGS AND SPECIFICATION, THE CONTRACTOR SHALL REFER THE DISCREPANCY TO MEINHARDT FOR WRITTEN CLARIFICATION BEFORE PROCEEDING WITH THE

3 ALL WORKMANSHIP AND MATERIALS SHALL COMPLY WITH THE RMS QA SPECIFICATION FOR ROADWORKS AND THE

RELEVANT CURRENT AUSTRALIAN STANDARDS AS APPROPRIATE.
4. ALL DIMENSIONS SHOWN SHALL BE VERIFIED ON SITE, DRAWINGS MUST NOT BE SCALED.

ONLY SUBSTITUTIONS APPROVED IN WRITING BY MEINHARDT SHALL BE ACCEPTED.

DURING CONSTRUCTION THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING ALL STRUCTURES AND WORKS IN A STABLE CONDITION AND SHALL ENSURE NO PART SHALL BE OVER STRESSED DURING CONSTRUCTION

PRELIMINARIES

1. THE CONTRACTOR SHALL ALLOW FOR PROVIDING MATERIALS AND WORK WHICH IS INCIDENTAL TO THE ITEMS.

THE CONTRACTOR STALL, ALLOW YOUR PROVIDING MATERIALS AND WORK WHILE IS INCLIDENTAL. TO THE TIEMS
SPECIFIED AND WHICH WOULD BE NECESSARY TO ACHEVE THE RESULTS REQUIRED BY THE DRAWINGS.
 THE CONTRACTOR WILL BE DEEMED TO HAVE INSPECTED THE SITE OF THE WORKS, ASSESSED AVAILABLE ACCESS, INCLIRED INTO THE LOCATION OF AUTHORITIES UNDERGROUND ASSETS, EXAMINED THE GEOTECHNICAL REPORT AND THE NATURE OF THE GROUND AND OBTAINED THE LOCAL CLIMATE AND RAINFALL INFORMATION.

TY REQUIREMENTS;

CONTRACTOR SHALL ENSURE THAT AT ALL TIMES, THE MEANS AND METHODS OF CARRYING OUT THE WORK.

TAKEN CONFORM WITH THE STANDARDS AND REQUIREMENTS OF THE OCCUPATIONAL HEALTH AND SAFET

OTHER APPLICABLE LEGISLATION, CODES OF PRACTICE AND STANDARDS

ALL PERSONNEL WORKING ADJACENT TO A TRAFFICABLE ROAD OR FORMATION SHALL WEAR RED SAFETY VESTS THE CONTRACTOR SHALL PROTECT THE PUBLIC FROM DANGERS INHERENT IN EXCAVATIONS, OBSTRUCTIONS WORKING PLANT AND FALLING OBJECTS. SUCH MEASURES THAT ARE TAKEN SHALL BE ADEQUATE TO MAINTAIN THE SAFETY OF THE PUBLIC DURING PERIODS OUTSIDE NORMAL, WORKING HOURS ON SITE. THE CONTRACTOR SHALL ENSURE THAT ALL TRENCH EXCAVATION FOR INSTALLATION OF PIPEWORKS FOR OTHER WORKS) OF DEPTHS GREATER THAN 1.5 METRES MUST BE CONTINUOUSLY SUPERVISED AND AT ALL TIMES BE

A DEGUATELY SUPPORTED.

A LLL WORK WITHIN ROAD RESERVES, PUBLIC PROPERTY OR PRIVATE PROPERTY - SHALL BE EXECUTED STRICTLY IN ACCORDANCE WITH THE REQUIREMENTS OF THE RELEVANT AUTHORITY OR LAND OWNER.

5. CONTRACTOR SHALL OBTAIN FROM THE RELEVANT AUTHORITIES DETAILS OF ALL EXISTING SERVICES WITHIN THE VICINITY OF THE WORKS AND SHALL BE HELD SOLELY RESPONSIBLE FOR ANY DAMAGE CAUSED TO EXISTING SERVICES DURING THE EXECUTION OF THE WORKS.

5. THE CONTRACTOR SHALL COMPLY WITH AND GIVE NOTICES REQUIRED BY ANY ACT OF PARLIAMENT, ORDINANCE DEGUIR TOOL BY ALL MAY BE ANY AUTHORITY AND AND THE THE WORKS AND SMALL DAY ALL SEES OF

REGULATION OR BY-LAW OF ANY AUTHORITY HAVING JURISDICTION OVER THE WORKS AND SHALL PAY ALL FEES OR

CHARGES LEGALLY DEMANDALE UNDER ANY SUCH ACT OF PARLIAMENT, ORDINANCE, REGULATION OR SYLAW.

PRIOR TO WORKS, THE CONTRACTOR SHALL UNDERTAKE AN EXISTING DEFECTS, INSPECTION AND REPORT TO LIST.
ANY PAISTING DAMAGE TO ROADS, FOOTPATHS, KERBS CROSSINGS CHANNELS NATURE STRIPS, ETC. SUCH LISTS. SHALL BE PREPARED IN DUPLICATE BY THE CONTRACTOR AND A COPY SENT TO THE SUPERINTENDENT

1. THE CONTRACTOR SHALL LIAISE DIRECTLY WITH ALL SERVICE AUTHORITIES INVOLVED AND SHALL COMPLY WITH

ALL THEIR REGULATIONS AND REQUIREMENTS.
2. ALL LEVELS SHOWN ARE TO AUSTRALIAN HEIGHT DATUM, UNLESS STATED OTHERWISE. ALL COORDINATES SHOWN

ARE TO AUSTRALIAN MAP GRID, UNLESS STATED OTHERWISE. BASE SURVEY & SET OUT HAS BEEN SUPPLIED BY OTHERS & SHALL BE CONFINED ON SITE BY CONTRACTOR PRIOR TO CONSTRUCTION.

3. SERVICE INFORMATION SHOWN IS BASED ON PLANS SUPPLIED AND IS APPROXIMATE ONLY. ACTUAL LOCATION CAN ONLY BE DETERMINED BY EXCAVATION. THE CONTRACTOR SHALL LIAISE WITH SERVICE AUTHORITIES FOR SERVICE OCATIONS THE CONTRACTOR SHALL PROTECT ALL SERVICES AND SHALL RECTIFY ANY DAMAGE AT HIS EXPENSE 4 ALL WORKS IN PUBLIC LANDS SHALL RE TO THE APPROVAL AND SATISFACTION OF THE RELEVANT AUTHORITY. THE

CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND OBTAINING RELEVANT AUTHORITY

CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND OBTAINING RELEVANT AUTHORITY WRITTEN APPROVAL OF THE WORKS.

5. EXISTING SURFACE CONTOURS SHOWN ARE INTERPOLATED FROM SPOT HEIGHTS AND ARE APPROXIMATE ONLY.

6. THE CONTRACTOR MUST VERIFY ALL DIMENSIONS AND EXISTING LEVELS ON SITE PRIOR TO COMMENCEMENT OF WORK, AND REPORT ANY DISCREPANCIES TO THE SUPERINTENDENT.

7. ALL EXISTING SERVICES (INCLUDING ANY NOT SHOWN ON THE PLANS) MUST BE ACCURATELY LOCATED IN POSITION AND LEVEL PRIOR TO ANY EXCAVATION. ANY DISCREPANCIES SHALL BE REPORTED TO THE SUPERINTENDENT.

MINIMINIA SERVICES (PAGINGES SHALL BE AUSTRAINED DEATH THE DEED FROM TERROPICE THE AUSTRALIANCE SHALL BE REPORTED TO THE SUPERINTENDENT.

MINIMUM SERVICE CLEARANCES SHALL BE MAINTAINED FROM THE RELEVANT SERVICE AUTHORITY.

8. ALL DIMENSIONS AND SET OUTS SHOWN ARE EITHER TO FACE OF BUILDING, GRID LINES OR LIP OF KERB, UNLESS 9. CONTRACTOR SHALL BE ISSUED AN ELECTRONIC COPY OF THE CIVIL DETAIL PLANS IN AUTOCAD DWG FORMAT FOR

SET OUT PURPOSES, ALL DIMENSIONS SHOWN ON PLAN SHALL OVER RIDE SETOUT POINTS SELECTED FROM ELECTRONIC FILE PROVIDED.

10. THE CONTRACTOR SHALL ARRANGE FOR ALL SETTING OUT BY A REGISTERED SURVEYOR. THE CONTRACTOR SHALL OBTAIN ALL REGULATORY AUTHORITY APPROVALS

11. THE CONTRACTOR SHALL OBTAIN ALL REGULATORY AUTHORITY APPROVALS.

12. WHERE NEW WORKS ABLUT EXISTING, THE CONTRACTOR MUST ENSURE THAT A SMOOTH AND EVEN PROFILE, FREE FROM ABRUPT CHANGES IS OBTAINED.

13. SAWCUT EXISTING KERBIKERS & CHANNEL AND PAVING WHERE NEW WORKS, ARE TO MATCH EXISTING WORKS.

14. BUILDING AND SITE MAINTENANCE PROGRAM IS TO INCORPORATE REGULAR FLUSHING OF ALL STORMWATER PITS, PIPES, DOWNPIPES, SUB-SOIL DRAINS AND ASSOCIATED FITTINGS TO AVIOD BLOCKAGES WITHIN THE SYSTEM.

15. ALL DISTURBED AREAS SHALL BE RESTORED TO THEIR ORIGINAL CONDITION, INLIESS SPECIFIED OTHERWISE.

16. EXCAVATED TREACHES SHALL BE COMPACTED TO THE SAME DENSITY AS THE ADJACENT NATURAL MATERIAL ANY SUBSIDENCES DURING THE PEPRION TO BE RECTIFIED AS OTHERS.

SUBSIDENCES DURING THE PERIOD TO BE RECTIFIED AS DIRECTED BY THE SUPERINTENDENT 17. THE CONTRACTOR SHALL KEEP THE SITE WELL DRAINED AND COMPLETELY FREE OF STANDING WATER AT ALL

18. GRADE EVENLY BETWEEN FINISHED SURFACE SPOT LEVELS. (FINISHED SURFACE CONTOURS ARE SHOWN FOR CLARITY ONLY) WHERE FINISHED SURFACE SPOT LEVELS ARE NOT SHOWN THE SURFACE SHALL BE GRADED

CLARITY ONLY) WHERE PINISHED SURFACE SHOT LEVELS ARE NOT SHOWN THE SURFACE SHALL BE GRADLED
SMOOTHLY SO THAT IT WILL DRAIN PREELY, AND TO MATCH THE LEVELS OF ADACEM'S INSTRACES OR STRUCTURES.
19. ANY EXISTING TREES WHICH FORM PART OF THE FINAL LANDSCAP BAY WILL BE PROTECTED FROM
CONSTRUCTION ACTIVITIES IN ACCORDANCE WITH THE LANDSCAPE ARCHITECTS DETAILS ANDIOR BY,
a) PROTECTING THEM WITH BARRIER FENCING OR SIMILAR MATERIALS INSTALLED OUTSIDE THE DRIP LINE,
b) ENSURING THAT NOTHINGS IN ANLECT TO THEM,
c) PROHIBITING PAVING, GRADING, SEDIMENT WASHOR PLACING OF STOCKPILES WITHIN THE DRIP LINE
EXCEPT AS ADVISED BY A QUALIFIED ARBORIST.

EXCEPT AS ADVISED BY A QUALIFIED ARBORIST.

20. RECEPTORS FOR CONCRETE AND MORTAR SLURRIES, PAINTS, ACID WASHINGS, LIGHT-WEIGHT WASTE MATERIALS
AND LITTER ARE TO BE EMPTIED AS NECESSARY. DISPOSAL OF WASTE SHALL BE IN A MANNER APPROVED BY THE
SUPERINTENDENT OR AS SPECIFIED IN THE WASTE MANAGEMENT PLAN.

UNLESS OTHERWISE SPECIFIED, THE CONTRACTOR SHALL MAKE PROVISION FOR TRAFFIC, IN ACCORDANCE WITH RMS QA SPECIFICATION FOR ROADWORKS OR AUSTRALIAN STANDARD AS1742 "MANUAL OF UNIFORM TRAFFIC DEVICES*

THE CONTRACTOR SHALL ASCERTAIN AND COMPLY WITH THE REQUIREMENTS OF THE AUTHORITY RESPONSIBLE

THE CONTRACTOR SHALL SO CONDUCT THE OPERATIONS AS TO MINIMISE OBSTRUCTION AND INCONVENIENCE TO THE PUBLIC, AND SHALL NOT HAVE UNDER CONSTRUCTION A GREATER LENGTH OR AMOUNT OF WORK THAN CAN BE MANAGED PROPERLY WITH DUE REGARD TO THE CONVENIENCE OF THE PUBLIC.

EARTHWORKS (CONTINUED)

WHEN A SURFACE IS UNABLE TO SUPPORT CONSTRUCTION EQUIPMENT OR IT IS NOT POSSIBLE TO COMPACT THE OVERLYING MATERIALS BECAUSE OF HIGH MOISTURE CONTENT. THEN ONE OR MORE OF THE FOLLOWING ALTERNATIVE ACTIONS MAY BE

(I) ALLOW THE MATERIAL TO DRY TO A MOISTURE CONTENT WHICH ALLOW IT TO BE COMPACTED AND ALLOW THE PLACEMENT AND

OVERLYING MATERIAL
(II) SCARIFY THE MATERIAL TO A DEPTH OF 200MM AND WORK AS NECESSARY TO ACCELERATE DRYING. RECOMPACT AS SPECIFIED

(II) SCARIFY THE MATERIAL TO A DEPTH OF 200MM AND WORK AS NECESSARY TO ACCELERATE DRYING, RECOMPACT AS SPECIFIED WHEN MOISTURE CONTENT APPROXIMATES OPTIMUM (III) EXCAVATE AND REPLACE THE SOFT MATERIAL. THE ACTION TO BE ADOPTED SHALL BE AT THE CONTRACTOR'S DISCRETION AND EXPENSE, BUT SHALL BE ADVISED TO THE SUPERINTENDENT BEFORE ACTION COMMENCES. IF THE CONTRACTOR ELECTS PURSUANT TO (I) ABOVE TO ALLOW THE MATERIAL TO DRY, RESULTING DELAYS, IF ANY, SHALL NOT CONSTITUTE OPENIONS OF AN EXCHASION OF CONSTITUTE OF PRACTICAL CONDICITION.

CONSTITUTE GROUNDS FOR AN EXTENSION OF CONTRACT PERIOD OR DATE OF PRACTICAL COMPLETION.
THE FINISHED SUBGRADE SHALL NOT BE DISTURBED BY TRAFFIC OR OTHER OPERATIONS, AND SHALL BE PROTECTED AND

MAINTAINED BY THE CONTRACTOR UNTIL THE FIRST LAYER OF FILL OR SUB-BASE IS PLACED THEREON. THE SUBGRADE SHALL BE KEPT DRAINED AND COMPLETELY FREE OF STANDING WATER AT ALL TIMES. THE CONTRACTOR SHALL PLAN AND CARRY OUT THE WHOLE OF THE WORKS TO MINIMISE THE EFFECTS OF RUN. OFF AND FROSION

THE CONTRACTOR SHALL PLAN AND CARRY OUT THE WHOLE OF THE WORKS TO MINIMISE THE EFFECTS OF RUIN-OFF AND EROSION ON THE SITE AND ON DOWNSTREAM AREAS, HE SHALL AVOID UNNECESSARY GROUND DISTURBANCE AND PROVIDE AS NECESSARY FOR THE PROPER CONTROL OF STORMMATER RUN-OFF AT EVERY STAGE OF THE WORKS ALL IN ACCORDANCE WITH "MANAGING URBAN STORMWATER I SOIL AND CONSTRUCTION" (LANDCOM "BLUE BOOK")
PRIOR TO THE COMMENCEMENT OF EARTHWORKS TOPSOIL IS TO BE STRIPPED WITHIN THE LIMITS OF THE EARTHWORKS AND FROM ANY AREAS TO BE COVERED BY PAVING, STRUCTURES OR FILL, AND ALL AREAS WHICH ARE TO SUPPORT PAVEMENTS.
EMBANKMENTS, STRUCTURES AND THE LINE OR FILLING UNDER SUCH WORKS, SHALL BE STRIPPED CLEAR OF ALL TREES, LOGS, STUMPS, SCRUB, GRASS, ROOT GROWTH, CULTIVATED SOIL, WET OR SPONGY NATURAL SOIL, DECAYED VEGETABLE MATTER AND ANY OTHER DELETERIOUS SUBSTANCE. THE CONTRACTOR SHALL BREAK UP AND REMOVE ALL ASPHALT AND CONCRETE MATERIAL IDRING WITHOUT WASHING AND THE OF DECAYED VEGETABLE MATTER AND LIPON WHICH FILL OR PAVEMENTS SHALL BY PLACED. UPON WHICH FILL OR PAVEMENT SHALL BE PLACED. ALL MATERIAL WITHIN THE LIMIT OF THE EARTHWORKS SHALL BE WHOLLY REMOVED.

THE ADJOINING UNDISTURBED SOIL AND TO THE APPROVAL OF THE SUPERINTENDENT.

THE ADJOINING UNDISTURBED SOIL AND TO THE APPROVAL OF THE SUPERINTENDENT.

THE ADDITIONAL ORDER OF THE ATTERAL SUBGRADE TO WITHIN THE RANGE 97% TO 103% OF STANDARD OPTIMUM MOISTURE CONTENT AND COMPACT TO ACHIEVE A MINIMUM STANDARD DRY DENSITY RATIO TO A MINIMUM DEPTH OF 200MM IF REQUIRED THE AREA SHOULD BE TYNED AND SCARLEIED FULL DEPTH TO EACH TLATE THIS PROCESS.

SHOULD BE TYNED AND SCARIFIED FULL DEPTH TO FACILITATE THIS PROCESS.

ANY SOFT, WEAK OR UNSTRULE AREAS EXPOSED BY THE COMPACTION PROCESS, OR DURING TEST ROLLING, AND WHICH DO NOT RESPOND TO FURTHER COMPACTION OR MOISTURE CONDITIONING SHALL BE EXCAVATED AND REPLACED.

THE CONTRACTOR SHALL BE DEEMED TO HAVE ASSESSED THE EXTENT OF UNSTRULE AREAS AND SHALL BE DEEMED TO HAVE INCLUDED IN THE CONTRACT SUM FOR ALL ACTIVITIES REQUIRED FOR UNSTRULE AREAS AND SHALL BE DEEMED TO HAVE PLACING AND COMPACTING OF APPROVED MATERIAL AS WELL AS THE EXCAVATION AND DISPOSAL OF REPLACED MATERIAL EXCAVATION TO THE UINS, LEVELS AND GRADES AS REQUIRED FOR UNDERGROUND SERVICES SPECIFIED IN THE RELEVANT SERVICES SECIFIED IN THE RELEVANT SERVICES SECITIONS, INCLUDING DRAINAGE, PHORAULC, ELECTRICAL AND THE LIKE, UNLESS OTHERWISE SPECIFIED MAKE THE TRENCHES STRAIGHT BETWEEN MANHOLES, INSPECTION POINTS, JUNCTIONS AND THE LIKE, WITH VERTICAL SIDES AND UNIFORM GRADES LEPTH SHALL BE AS REPUILIBLED BY THE BIT SERVICES AND ITS EPROVING CHIT BACK POOTS ENCOUNTERED IN

GRADES, DEPTH SHALL BE AS REQUIRED BY THE RELEVANT SERVICES AND ITS BEDDING, CUT BACK ROOTS ENCOUNTERED IN TRENCHES TO LESS THAN 600mm CLEAR OF THE RELEVANT SERVICE, REMOVE SUCH OTHER OBSTRUCTIONS INCLUDING ROOTS. STUMPS, BOULDERS AND THE LIKE WHICH MAY, IN THE OPINION OF THE SUPERINTENDENT, INTERFERE WITH THE PROPER FUNCTIONING OF THE SERVICE, LAY AND BED SERVICES IN ACCORDANCE WITH THE RELEVANT SERVICES SPECIFICATION SECTION

10. BACKFILL AND COMPACT SERVICE TRENCHES AS SOON AS POSSIBLE AFTER APPROVAL OF LAID AND REDDED SERVICE. COMPACT

BACKFILL AND COMPACT SERVICE TRENCHES AS SOON AS POSSIBLE AFTER APPROVAL OF LAID AND BEDDED SERVICE. COMPACT BACKFILL IN PIPE TRENCHES SO THAT THE PIPE IS BUTTRESSED BY THE WALLS OF THE TRENCH.

WHERE FILLING IS DESIGNATED BY THE CONTRACT OR IS SHOWN ON THE DRAWINGS AS STRUCTURAL OR CONTROLLED FILL THE CONTRACTOR SHALL ENGAGE AN INDEPENDENT GEOTECHNICAL TESTING AUTHORITY TO SUPERVISE SUBGRADE PREPARATION, RILL PLACEMENT, COMPACTION AND TO HORPITAKE SAMPLING AND TESTING AND REPORTING TO SATISTY THE REQUIREMENTS OF THIS SPECIFICATION AND THOSE OF AS 2870 AND AS 3798, FOR CONTROLLED FILL.

NO FILL SHALL BE PLACED OVER LAYERS NOT TESTED AND HAVING SATISFACTORY RESULTS, WHERE EXCAVATED MATERIAL IS NOT SUITABLE FOR FILLING, FILL MATERIAL, AS SPECIFIED IN THIS SPECIFICATION SECTION, "IMPORTED FILL" SHALL BE USED. ALL FILL MATERIAL SHALL BE PLACED IN MAXIMUM 200mm THICK LAYERS AND COMPACTED AT OPTIMISM MOISTURE CONTENT (~OR ~2%) TO ACHIEVE A DRY DENISTY DETERMINED IN ACCORDANCE WITH AST289.5.1.1-2003-METHODS OF TESTING SOILS FOR ENGINEERING PURPOSES OF NOT LESS THAN THE FOLLOWING STANDARD MINIMUM DRY DENSITY LOCATION.

STANDARD DRY DENSITY DETERMINED IN ACCORDANCE WITH AST289.5.1.1-2003-METHODS OF TESTING SOILS FOR ENGINEERING PURPOSES OF NOT LESS THAN THE FOLLOWING STANDARD MINIMUM DRY DENSITY.

STANDARD DRY DENSITY DETERMINED IN ACCORDANCE WITH AST289.5.1.1-2003-METHODS OF TESTING SOILS FOR ENGINEERING PURPOSES OF NOT LESS THAN THE FOLLOWING STANDARD MINIMUM DRY DENSITY.

STANDARD DRY DENSITY LOCATION UNDER BUILDING SLABS 98% 95% 95% VEHICULAR PAVED AREAS NON-VEHICULAR PAVED AREAS

I ANDSCAPED AREAS LANDSCAPED AREAS

53.3

IMPESS OTHERWISE PERMITTED NO SHAING SHAIL BE PLACED AGAINST ANY STRUCTURES. WING WALLS OR RETAINING WALLS.

UNLESS OTHERWISE PERMITTED, NO FILLING SHALL BE PLACED AGAINST ANY STRUCTURES, WING WALLS OR RETAINING WALLS WITHIN FOURTEEN DAYS OF CASTING, STRUT WALLS AS NECESSARY TO PREVENT MOVEMENT DURING PLACING AND COMPACTION, PLACE AND COMPACT FILLING OVER AND AROUND PIPES, CILIVERTS, BRIDGES AND OTHER STRUCTURES SO AS TO AVOID UNBALANCED LOADING OR MOVEMENT. UNLESS OTHERWISE DETAILED BACKFILL AT STRUCTURES SHALL BE FILLED AS FOLLOWS WHERE THE GAP BETWEEN THE STRUCTURE AND UNDISTURBED GROUND EXCEEDS ZIM, BACKFILL THE OWN THINK ZO OF THE STRUCTURE WITH DGS20 SUBBASE FINE CRUSHED ROCK AND BACKFILL IN ZEED ON OF THE STRUCTURE WITH MOST OF THE STRUCTURE WITH DGS20 SUBBASE FINE CRUSHED ROCK.

UNLESS OTHERWISE DETAILED, MATERIAL WITHIN 300mm OF WEEPHOLES SHALL BE AN APPROVED GRANULAR FILTER MEDIUM OF COARSE SAND OR CRUSHED STONE WRAPPED AND SURROUNDED WITH AN APPROVED GEOTEXTILE SEPARATION LAYER.

NO POINT SHALL BE GREATER THAN + OR - 100mm FROM THE DESIGN LOCATION.

VERTICAL SUBGRADE LEVEL. +0. -25mm PAVEMENT DESIGN SURGRADE

LEVEL. +0, -25mm OTHER: +60 -50mm

STRAIGHTNESS (EXCLUDES ROCK) MAXIMUM 20MM DEPARTURE FROM 3M STRAIGHT EDGE LAID

STRAIGHTNESS (EXCLUDES ROCK), MAXIMUM 20MM DEPARTURE FROM 3M STRAIGHT EDGE LAID

- PARALLET TO ROAD CENTER LINE

- NORMAL TO INTENDED CONTOURS

- NORMAL TO INTENDED CONTOURS

- NORMAL TO INTENDED CONTOURS

- REAS UPON WHICH FILLS ARE TO BE CONSTRUCTED, ALL LAYERS OF FILLING, AND MATERIALS LESS THAN 150mm BELOW

PERMANENT SUBGRADE LEVEL IN CUTTINGS, SHALL BE COMPACTED SO AS TO BE CAPABLE OF WITHSTANDING TEST ROLLING,

WITHOUT VISIBLE DEFORMATION OR SPRINGING, WITH A PNEUMATIC TYRED ROLLER OR HIGHWAY TRUCK BALLASTED TO COMPLY

WITH THE FOLLOWING
PNEUMATIC TYRED - NOT LESS THAN 3 T PER TYRE WITH TYRES INFLATED TO 550 KPa.

PRECIMENT FIRED FOR LESS THAN 3 F PER TITLE WHITE TITLES INFORMED SOURCE.

HIGHWAY TRUCK - WITH REAR AXLE OR AXLES LOADED TO NOT LESS THAN 8 T EACH WITH TYRES INFLATED TO 550KP&
TEST ROLLING SHALL BE CARRIED OUT IMMEDIATELY BEFORE OVERLYING LAYERS ARE PLACED. WHERE TEST ROLLING IS REQUIRED AT SOME LATER DATE, THE SURFACE SHALL BE MOISTURE CONDITIONED AS AND GIVEN NOT

COVERAGES OF THE TEST ROLLER REFORE TEST ROLLING COMMENCES.

COVERAGES OF THE 1EST ROLLEN BEPORE 1EST ROLLING COMMENCES.

THE WORK SHALL NOT BE ACCEPTED AS COMPLETE UNLESS ALL TEST RESULTS ARE PROVIDED TO THE SUPERINTENDENT. THE CONTRACTOR SHALL PROVIDE ALL MATERIAL PROVERTY AND QUALITY TEST RESULTS TO THE SUPERINTENDENT. THE CONTRACTOR SHALL PROORGAM THE BEARTHWORKS OPERATION SO THAT THE WORKING AREAS ARE ADEQUATELY DRAINED DURING THE PERIOD OF CONSTRUCTION. THE SUPERACE SHALL BE GRADED AND SEALED OFF TO REMOVE DEPRESSIONS, ROLLER MARKS AND SIMILAR WHICH WOULD ALLOW WATER TO POND AND PENETRATE THE UNDERFLYING MATERIAL POY ADMAGE RESULTING FROM THE CONTRACTOR NOT OBSERVING THESE REQUIREMENTS SHALL BE RECTIFIED BY THE CONTRACTOR AT THEIR CONNECTION.

OWN EXPENSE.
TESTING OF THE FILL MATERIAL SHALL BE CARRIED OUT BY AN APPROVED NATA REGISTERED LABORATORY AT THE CONTRACTORS

EARTHWORKS

1 THE CONTRACTOR SHALL COMPLY WITH RMS QA SPECIFICATIONS FOR ROADWORKS AND THE CURRENT EDITIONS OF AS 1289 TESTING SOILS FOR ENGINEERING PURPOSES

AS 1289 TESTING SOILS FOR ENGINEERING PURPOSES
AS 3798 GUIDELINES ON EARTHWORKS FOR COMMERCIAL AND RESIDENTIAL DEVELOPMENTS
ALL WORK SHALL COMPLY WITH THE PROJECT GEOTECHNICAL REPORT.
THE CONTRACTOR SHALL BE RESPONSIBLE FOR CARRYING OUT ALL CONTROL AND COMPLIANCE EXAMINATION AND
TESTING OF MATERIALS AND WORKLUMESS OTHERWISE SPECIFIED, ALL TESTS SHALL BE UNDERTAKEN IN
ACCORDANCE WITH THE APPROPRIATE AUSTRALIAN STANDARD TEST METHOD. WHERE THERE IS NO RELEVANT
AUSTRALIAN STANDARD TEST METHOD THEM THE CURRENT APPROPRIATE TAT TEST METHOD OR OTHER SPECIFIED
TEST METHOD SHALL BE USED ALL TESTS SHALL BE CONDUCTED BY EXPERIENCED TESTING OFFICERS IN A
LABORATORY ACCREDITED BY THE NATIONAL ASSOCIATION OF TESTING AUTHORITIES HALL
DETERMINATION OF THE NATURE AND QUANTITY(ES) OF THE EXISTING SITE MATERIALS SHALL BE THE
DESPONSIBILITY OF THE CONTRACTOR WHERE INCLINED IN SEP DOCUMENTS. CENTECHNICAL BEPORTS ARE

RESPONSIBILITY OF THE CONTRACTOR, WHERE INCLUDED IN THE DOCUMENTS, GEOTECHNICAL REPORTS ARE INCLUDED FOR INFORMATION ONLY. INTERPRETATION OF THE REPORT/S SHALL BE THE RESPONSIBILITY OF

GAE OF ORSHE MATERIAL WITHIN THE WORKS SHALL ONLY BE PERMITTED WHERE THE MATERIAL EITHER. IL IS SPECIALLY STATED WITHIN THE DOCUMENTS AS BEING USED IN THE WORKS, OR IL IS PERMITTED BY THE SUPPENITENDENT A GEOTECHNICAL TESTING / ENGINEER ALL FILL MATERIAL SHALL BE FROM A SOURCE APPROVED BY THE SUPPENITENDENT AND SHALL COMPLY WITH THE FOLLOWING. LISE OF ON-SITE MATERIAL WITHIN THE WORKS SHALL ONLY BE PERMITTED WHERE THE MATERIAL FITHER.

OLLOWING a) FREE FROM ORGANIC AND PERISHABLE MATTER,
b) MAXIMUM PARTICLE SIZE 75mm, AND
c) PLASTICITY INDEX - BETWEEN 2% AND 15%.

STORMWATER DRAINAGE

THE CONTRACTOR SHALL COMPLY WITH PMS OF SPECIFICATIONS FOR ROADWORKS FOR ALL STORMWATER DRAINAGE WORKS ALL DRAINAGE PIPES Ø375mm AND ABOVE SHALL BE SPIGOT AND SOCKET REINFORCED CONCRETE PIPES WITH RUBBER RIN

JOINTS (UNO).

ALL DRAINAGE PIPES LESS THAN OR EQUAL TO 8225mm SHALL BE UPVC DWV GRADE CLASS SN8 IN ACCORDANCE WITH
ASNIZS1280 2009-PVC-U PIPES AND FITTINGS FOR DRAIN, WASTE AND VENT APPLICATION WITH SOLVENT WELDED JOINTS (UNO).

ALL PIPE JUNCTIONS UP TO AND INCLUDING 8450mm AND TAPERS, SHALL BE VIA PURPOSE MADE FITTINGS (UNO).

MINIMUM GRADE TO STORMWATER LINES TO BE 1% (UNO).
EQUIVALENT STRENGTH FIBROUS REINFORCED CONCRETE AND/OR VITRIFIED CLAY PIPE MAY BE USED SUBJECT TO APPROVAL

BY THE SUPERINTENDENT AND CONSENT AUTHORITY.

TRENCHES MUST BE KEPT CLEAR OF WATER AT ALL TIMES AND TIMBERED WHERE NECESSARY TO PREVENT COLLAPSE WHERE STORMWATER LINES PASS UNDER FLOOR SLABS DWV GRADE uPVC RUBBER RING JOINTS ARE TO BE USED (UNO).

PIPES SHALL BEAR EVENLY ON THE 8ED PREPARED AS SPECIFIED ABOVE AND LAID WITH THE SOCKETS POINTED UPGRADE. ALL PIPES SHALL BE LAID IN STRAIGHT LINES TO TRUE INVERT LEVELS AND GRADES AS SHOWN ON PLANS. EACH PIPE SHALL BE SEPARATELY BONED BETWEEN ACCURATELY ESTABLISHED GRADE POINTS. THE CONTRACTOR SHALL ADHERE TO THE

SEPARATELY BONED BETWEEN ACCURATELY ESTABLISHED GRADE POINTS. THE CONTRACTOR SHALL ADHERE TO THE SUPERINTENDENT'S WRITTEN APPROVAL.

UNLESS NOTED OTHERWISE, BEDDING SHALL BE TYPE HZ FOR PIPES NOT UNDER PAVEMENTS AND TYPE HS3 FOR PIPES UNDER PAVEMENTS IN ACCORDANCE WITH ASANZS372S (2007). DESIGN FOR INSTALLATION OF BURIED CONCRETE PIPES.

BACKFILL TRENCH WITH SAND OR APPROVED GRANULAR BACKFILL TO 300mm (MN) ABOVE THE PIPE. WHERE THE PIPE IS UNDER PAVEMENTS BACKFILL REMAINDER OF TRENCH TO PAVEMENT SUBGRADE WITH SAND OR APPROVED GRAVEL SUB-BASE COMPACTED IN 150mm LAYERS TO 98% STANDARD MAXIMUM DRY DENSITY. THE CONTRACTOR IS TO ENSURE COMPACTION EQUIPMENT IS APPROPRIATE FOR THE PIPE CLASS USED.

ALL PIPE JOINTING SHALL BE CARRIED OUT IN ACCORDANCE WITH THE MANUFACTURER'S WRITTEN SPECIFICATIONS FOR THE TYPE OF PIPE BRING LISEO.

TYPE OF PIPE BEING USED.

13. CONTRACTOR TO SUPPLY AND INSTALL ALL FITTINGS AND SPECIALS INCLUDING VARIOUS PIPE ADAPTORS TO ENSURE PROPER CONNECTION BETWEEN DISSIMILAR PIPEWORK.

14. ALL CONNECTIONS TO EXISTING DRAINAGE PITS SHALL BE MADE IN A TRADESMAN-LIKE MANNER AND THE INTERNAL WALL OF

THE PIT AT THE POINT OF ENTRY SHALL BE CEMENT RENDERED TO ENSURE A SMOOTH FINISH WITH NO THE INTERVAL.

15. WHERE ANY PIPE IS CUT INTO A LARGER PIPE, SUCH CONNECTION SHALL BE MEATLY MADE AND NO PART OF THE PIPE OR DOWNIPPE SHALL BE ALLOWED TO PROJECT, ANY CUT-IN JUNCTION SHALL BE MADE IN THE TOP HALF OF THE LARGER PIPE.

SUCH JUNCTION TO CONCRETE PIPES SHALL BE SURROUNDED WITH A NEAT COLLAR OF CEMENT MORTAR AS DIRECTED OR AS

SUCH JUNCTION TO CONCRETE PIPES SHALL BE SURROUNDED WITH A NEAT COLLAR OF CEMENT MORTAR AS DIRECTED OR AS DETAILED ON THE DRAWINGS, JUNCTIONS BETWEEN PVC PIPES SHALL USE PROPRIETY FITTINGS INTENDED FOR THE PURPOSE. THE ENDS OF PIPES WHICH CONNECT WITH SIDE ENTRY, JUNCTION OR OTHER PITS SHALL BE NEATLY CUT TO FIT THE INNER FACE OF THE CONCRETE. WHERE UPVC PIPES ENTERALEAVE PITS A RUBBER RING JOINT MANHOLE COUPLING SHALL BE CAST INTO THE PIT WALL BEDDING, HAUNCH AND OVERLAY MATERIALS SHALL CONFORM TO THE OFAILS, SHOWN ON THE DRAWINGS ALL PITS AND ENDWALLS SHALL BE CONSTRUCTED IN THE POSITIONS AND TO THE LEVELS SHOWN ON THE DRAWINGS OR AS DIRECTED BY THE SUPPRINTENDENT, LOCATION OF ALL IAD PITS TO BE CONFIRMED WITH SUPERINTENEND & LANDSCAPE APPLIANCED REPORT CONSTRUCTION.

COUNCIL'S CONSTRUCTION PIT DETAILS TO TAKE PRECEDENCE TO THE CONSTRUCTION DETAILS SHOWN IN DOCUMENTATION, PRECAST PITS OR ALTERNATIVE DESIGN TYPES CAN BE USED SUBJECT TO COUNCIL / PCA APPROVAL, (IAD PIT COVERS SHALL BE PLACED IN ACCORDANCE WITH THE DETAIL SITE PLANS AND PIT SCHEDULE (IF PROVIDED) IN REGARD TO

TYPE, SIZE, LOCATION AND LEVEL. THE BASE OF EACH PIT SHALL BE INFILLED AND SHAPED WITH CONCRETE OR CEMENT MORTAR TO PROVIDE A SMOOTH FLOW PATH

PITS DEEPER THAN 1000mm SHALL HAVE STEP IRONS INSTALLED IN ACCORDANCE WITH THE LOCAL OR STATUTORY AUTHORITY

REQUIREMENTS.
ALL DOWNIPPES SHALL BE CONNECTED TO AT THE END OF A PIPE OR ELBOW AND WHICH THEY SHALL ENTER CENTRALLY,
WHERE PVC DOWNIPPES AND UNDERGROUND DRAINAGE ARE USED, THE DOWNIPPES SHALL BE CONNECTED TO THE
UNDERGROUND DRAINS WITH SUITABLE STANDARD FITTINGS, BEINDS ETC AND WITH SOLVENT JOINTS, THE CONTRACTOR SHALL
LAY AND GRADE DRAINS FROM DOWNIPPES TO COMPLY WITH THE REQUIREMENTS FOR PIPE MATERIAL AND COVER REQUIRED
BY ASSOCIA, WHERE THE REQUIREMENTS OF AS3500.3 CANNOT BE MET THE CONTRACTOR SHALL REFER THE MATTER TO THE

20. SUPPLY APPARATUS AND MATERIALS NECESSARY FOR, AND CARRY OUT THE TESTS REQUIRED BY THE SPECIFICATION OR REGULATORY AUTHORITIES, IN THE PRESENCE OF THE SUPERINTENDENT AND THE RELEVANT AUTHORITY. LEAVE PIPE JOINTS EXPOSED TO ENABLE OBSERVATION DURING THE TESTS. ENSURE PVC SOLVENT CEMENT JOINTS HAVE BEEN CURED FOR AT EAST 24 HOURS BEFORE TESTING.

LEAST 24 HOURS BEFORE TESTING. THE CONTRACTOR SHALL PRESSURE TEST WITH WATER, ALL STORMWATER PIPEWORK IN OR UNDER ANY STRUCTURES, IN ACCORDANCE WITH AS 3500 3 WHERE SHOWN IN THE DOCUMENTS OR WHERE THE GRADE OF THE PIPELINE IS ≥15% CONCRETE BUILKHEADS SHALL BE

WHERE SHOWN IN THE DOCUMENTS OR WHERE THE GRADE OF THE PIPELINE IS \$15%, CONCRETE BULKHEADS SHALL BE CONSTRUCTED AT EVERY SECOND JOINT, THE AUS OF THE BULKHEAD SHALL BE VERTICA, WITH A MINIMUM POWIDTH OF 200mm, UNLESS OTHERWISE DIRECTED THE TOP OF BULKHEADS SHALL EXTEND TO WITHIN 300mm OF FINISHED SURFACE LEVEL OR TO THE SUBGRADE LEVEL WHERE THE PIPELINE IS UNDER A ROAD PAVEMENT. ON EACH SIDE OF THE PIPELINE IS THE LEVEL OF THE THENCH INVERT 100mm DIA PIPES SHALL PASS THROUGH THE BULKHEAD. SUCH PIPES SHALL BE FILLED WITH FIBREGLASS WOOL OR OTHER APPROVED FILTER MATERIAL. THE BULKHEAD SHALL BE LOCATED DIRECTLY BEHIND THE DOWNSTREAM COLLAR SO AS NOT TO ENCASE THE JOINT, REFER TO DETAILS SHEET.



EXISTING SERVICES

EXISTING SERVICES HAVE BEEN PLOTTED FROM SUPPLIED DATA AND AS SUCH THEIR ACCURACY CANNOT BE GUARANTEED. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ESTABLISH THE LOCATION AND LEVEL OF ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF ANY WORK, ANY DISCREPANCIES HALL BE REPORTED TO THE SUPPERNITENDENT. THE CONTRACTOR SHALL ALLOW FOR THE CAPPING OFF, EXCAVATION AND REMOVAL IF REQUIRED OF ALL REDUNDANT

EXISTING SERVICES IN AREAS AFFECTED BY WORKS WITHIN THE CONTRACT AREA, AS SHOWN ON THE DRAWINGS UNLESS

DIRECTED OTHERWISE BY THE SUPERINTENDENT THE CONTRACTOR SHALL ENSURE THAT AT ALL TIMES SERVICES TO ALL BUILDINGS NOT AFFECTED BY THE WORKS ARE NOT

DISKUPTED.

JE REQUIRED. THE CONTRACTOR SHALL CONSTRUCT TEMPORARY SERVICES TO MAINTAIN EXISTING SUPPLY TO BUILDINGS. ANNING IN OPERATION DURING WORKS TO THE SATISFACTION AND APPROVAL OF THE SUPERINTENDENT ONCE REMAINING IN OPERATION DURING WORKS TO THE SATISFACTION AND APPROVAL OF THE SUPERINTENDENT. ONCE DIVERSION IS COMPLETE AND COMMISSIONED THE CONTRACTOR SHALL REMOVE ALL SUCH TEMPORARY SERVICES AND MAKE GOOD TO THE SATISFACTION OF THE SUPERINTENDENT AND THE RELEVANT SERVICE AUTHORITY. INTERRUPTION TO SUPPLY OF EXISTING SERVICES SHALL BE DONE SO AS NOT TO CAUSE ANY INCONVENIENCE TO THE PRINCIPLE. THE CONTRACTOR IS TO GAIN APPROVAL FROM THE SUPERINTENDENT FOR TIME OF INTERRUPTION - THE CONTRACTOR IS TO GAIN APPROVAL FROM THE SUPERINTENDENT FOR TIME OF INTERRUPTION - THE CONTRACTOR IS RESPONSIBLE FOR ALL LIAISON. ALL BRANCH GAS AND WATER SERVICES UNDER RIVEWAYS AND BRICK PAVING SHALL BE LOCATED IN 80mm DIA UPVC SEWER GRADE CONDUITS EXTENDING A MINIMUM OF 500mm BEYOND THE EDGE OF PAVING. CLEARANCE AND COVER REQUIREMENTS SHALL BE OBTAINED FROM THE RELEVANT SERVICE AUTHORITY BEFORE COMMISSIONED FOR AND COVER REQUIREMENTS SHALL BE OBTAINED FROM THE RELEVANT SERVICE AUTHORITY BEFORE COMMISSIONED FOR ALL THESE OF THE STALL THE SERVICE AUTHORITY BEFORE

COMMENCEMENT OF WORKS AND SHALL BE ADHERED TO AT ALL TIMES.

CARE IS TO BE TAKEN WHEN EXCAVATING NEAR EXISTING SERVICES. NO MECHANICAL EXCAVATIONS ARE TO BE UNDERTAKEN
OVER TELECOM OR ELECTRICAL SERVICES. HAND EXCAVATE IN THESE AREAS ONLY.

SERVICE TRENCHES AND CONDUITS

1 MATERIAL SHALL COMPLY WITH RMS OA SPECIFICATIONS FOR ROADWORKS AND THE CURRENT EDITIONS OF THE FOLLOWING LISTRALIAN STANDARDS

AS 2053 MON-METALLIC CONDUITS AND FITTINGS

AS 263 NON-METALLIC CONDUITS AND FITTINGS.
AS 2632 CODE OF PRACTICE FOR UPVC PIE SYSTEMS.
AS 3503 NATIONAL PLUMBING AND DRAINAGE CODE, PART 3 STORMWATER DRAINAGE.
ELECTRICAL, WATER & GAS DUCTING CONDUITS SHALL BE IN ACCORDANCE WITH THE RELEVANT AUTHORITY REQUIREMENTS.
CONTRACTOR TO COORDINATE SHARED TRENCH AND LIASE WITH NBN CO /GAS / TELSTRA FOR SUPPLY AND PLACEMENT OF
COMDUIT AND GIVE MINIMUM 14 DAYS PRIOR TO THE NEED FOR DUCTING TO BE INSTALLED.
DRAW WIRES SHALL BE 2 SIMM INGLIF MENT GALVANNESD DRAW WIRES.
ALL EXCAVATION AND BACKFILL SHALL BE IN ACCORDANCE WITH THE STORMWATER DRAINAGE AND BASE AND
SUBBASE. GIVENSED DROYS ESCITION.

SUBBASE-CRUSHED ROCK SECTION.
BEDDING AND HAUNCHING SHALL COMPLY WITH THE REQUIREMENTS OF AS2032 UNLESS OVERRIDEN BY THE REQUIREMENTS OF THE RELEVANT AUTHORITY OR THE RELEVANT SERVICES SECTIONS OF THE SPECIFICATION. LOW PERMEABILITY BEDOING AND BACKFILL SHALL BE PROVIDED. WHERE SHOWN ON THE PLAN OR OTHERWISE DIRECTED.

WHERE SERVICES OR CONDUITS ARE PLACED UNDER PAVEMENT THE COVER FROM TOP OF THE SERVICE OR CONDUIT TO THE PAVEMENT SURFACE SHALL, UNLESS SHOWN OTHERWISE ON THE DRAWINGS OR REQUIRED BY SERVICE AUTHORITIES, BE NOT LESS THAN 750MM AND TO THE INVEST LEVEL OF OPEN DRAINS SHALL BE NOT LESS THAN 600mm. INLESS OTHERWISE APPROVED BY THE SUPERINTENDENT, CROSSING OF PAVEMENT SHALL BE MADE SQUARE OR NEAR

UNLESS OTHERWISE APPROVED BY THE SUPERINTENDENT, CROSSING OF PAVEMENT SHALL BE MADE SQUARE OR NEAR SQUARE WITH THE DIRECTION OF TRAFFIC.
WHERE IT IS NECESSARY FOR EXISTING ASPHALT OR CONCRETE PAVEMENTS TO BE CUT THEY SHALL BE SAWN FOR THE FULL DEPTH OF ASPHALT OR CONCRETE.
CONDUTS SHALL BE PLACED UNDER LANDSCAPE OR NON-PAVED AREAS WITH NOT LESS THAN 450mm COVER UNLESS A GREATER DEPTH IS REQUIRED BY THE RELEVANT AUTHORITY OR SERVICES SECTION OF THE SPECIFICATION.
END DUCT CROSSINGS 500mm BEHIND KERS UNLESS SHOWN OTHERWISE ON THE DRAWNIGS. END DUCT CROSSINGS 1000mm CLEAR OF THE PAVEMENT WHERE THERE IS NO KERS, UNLESS SHOWN OTHERWISE ON THE DRAWNIGS. LOCATE DUCTS TO AVOID OTHER SERVICES AND WITH STRAIGHT LINES AND GRADES UNLESS DIRECTED OTHERWISE EACH LINUSED CONDUIT IN EACH CONDUIT BANK SHALL BE FITTED WITH A SINGLE UNJOINED LENGTH OF DRAW WIRE OF A LENGTH FOUAL TO THE LENGTH OF THE DUCT PLUS 2 METERS.

CAP BOTH ENDS OF ALL UNUSED CONDUITS WITH STANDARD UPVC CAPS OR APPROVED WATERTIGHT CAP. LEAVE ENDS OF CONDUITS EXPOSED UNTIL THEIR LOCATIONS HAVE BEEN RECORDED BY THE RELEVANT AUTHORITIES.

SUBSOIL DRAINAGE

THE CONTRACTOR SHALL COMPLY WITH RMS DA SPECIFICATIONS FOR ROADWORKS FOR ALL SUBSOIL DRAINAGE WORKS. WHERE SUBSOIL DRAINAGE LINES PASS UNDER FLOOR SLABS AND VEHICULAR PAVEMENTS, UNSLOTTED JPVC DWV GRADE

CLASS SN® PIPE SHALL BE USED.
PROVIDE SUBSOIL DRAINAGE IN ACCORDANCE WITH COUNCIL SPECIFICATIONS WITH CONTINUOUS FALL TO DOWNSTREAM PITS

LOCATED AS SHOWN ON PLAN AND AS MAYBE DIRECTED BY COUNCIL/SUPERINTENDENT.

ALL SUBSOLI DRAINAGE PIPES SHALL BE Ø100mm CLASS 400 PERFORATED DRAINAGE PIPE LAID AT 1.0%MIN GRADE WRAPPED IN
GEOFABRIG (UNO) AND BE LAID AT A NIN DEPTH OF 400mm BELOW PAVEMENT SUB-BASE COURSE.

BASE AND SUBBASE-CRUSHED ROCK

ALL WORKMANSHIP AND MATERIALS SHALL COMPLY WITH RMS OA SPECIFICATIONS FOR ROADWORKS AND THE CURRENT

ALL WORKMANSHIP AND MATERIALS SHALL COMPLY WITH RINS QA SPECIFICATIONS FOR ROADWORKS AND THE CURRENT EDITIONS OF THE AUS-SPEC AND RELEVANT AUSTRALIAN STANDARDS.
WHERE IT IS SPECIFIED THAT WATER SHALL BE ADDED TO THE CRUSHED ROCK PRIOR TO DELIVERY, SUCH WATER SHALL BE CLEAR AND SUBSTANTALLY FREE FROM DETRIMENTAL IMPURITIES SUCH AS SOILS, SALTS, ACIDS, ALKALIS AND VEGETABLE SUBSTANCES.
WHERE SPECIFIED CEMENT SHALL COMPLY WITH THE REQUIREMENTS OF EITHER AUSTRALIAN STANDARD SPECIFICATION AS 1315-PORTLAND CEMENT OR AS 1317-BLENDED CEMENT.
THE SUBGRADE, OR PREVIOUS PAYEMENT COURSE, SHALL HAVE BEEN TESTED AND ACCEPTANCE CRITERIA MET BEFORE THE PLACING OF THE NEXT COURSE WILL BE PERMITTED, CRUSHED ROCK MATERIAL SHALL NOT BE PLACED ON A WATERLOGGED SUBGRADE OF LOWER COURSE.

SUBGRADE OR LOWER COURSE. THE MOISTURE CONTENT OF THE CRUSHED ROCK SHALL BE MAINTAINED WITHIN -2%, +2% OF OPTIMUM MOISTURE CONTENT AT

ALL TIMES DURING SPREADING AND COMPACTION,
EACH LAYER SHALL BE COMPACTED AS SOON AS POSSIBLE AFTER SPREADING AND WHILE THE MOISTURE CONTENT IS WITHIN

EACH LAYER SHALL BE COMPACTED AS SOON AS POSSIBLE AFTER SPREADING AND WHILE THE MOIST UND. CONTENT IS WITHIN THE SPECIFIED RANGE TO ACHIEVE A DIMPORD MENSITY IN THE LAYER. AT THE COMPACTION OF EACH LAYER WITHIN THE COURSE, THE CONTRACTOR SHALL ARRANGE FOR THE LAYER TO BE TESTED FOR COMPLIANCE WITH THE REQUIRED DENSITY. ALL TEST RESULTS SHALL BE SUBMITTED TO THE SUPERINTENDENT FOR APPROVAL PRIOR TO CONSTRUCTION OF THE NEXT COURSE OR SURFACE TREATMENT.

WHERE TEST RESULTS INDICATE THE AREA FAILS TO COMPLY WITH THE REQUIRED DENSITY CRITERIA, THE CONTRACTOR SHALL RE-ROLL, LOOSEN, RE-WATER, RE-COMPACT, OR REMOVE AND REPLACE THE LAYER AS DIRECTED BY THE SUPERINTENDENT, TO ACHIEVE A LAYER COMPLYING IN FULL WITH THIS SPECIFICATION, COSTS OF RECTIFICATION AND RETESTS SHALL BE BORNE BY THE CONTRACTOR.

FOR CONSTRUCTION

© Roads and Maritime Services

DRAWING FILE LOCATION / NAME DESIGN LOT CODE DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING PLOT BY HORNSBY SHIRE COUNCIL 3/11/2014 2:21:41 PM MR 161 - GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH X:1111403 - Galston-Grange Retirement-Village\68IM\6_3 MHT MIE\6_3_4 MHT UD\Galston Road - drawings\DS2014-000149-DD-GE-0101.dwg Aseip 392 GALSTON ROAD, GALSTON REV DATE AMENDMENT / REVISION DESCRIPTION APPROVAL SCALES ON A3 SIZE DRAWING DRAWINGS / DESIGN PREPARED BY TITLE NAME DATE Transport EXTERNAL REFERENCE FILES GALSTON GRANGE DEVELOPMENT 08-07-16 ISSUED FOR 100% DESIGN DEVELOPMENT D.CREARY **Roads & Maritime** NSW B 02-11-16 INCORPORATED RMS COMMENTS DATED 21-07-2016 GENERAL NOTES SHEET 1 OF 2 DRG CHECK M.GRINHAM Services 27-01-17 INCORPORATED BRS COMMENTS DATED 22-12-2017 SHEET 02 OF 21 A.PHAM DESIGN 05-06-17 $\begin{array}{c} \text{RMS REGISTRATION No.} & DS2014 \ / \ 000149 \end{array}$ S.DUNSTONE DESIGN CHECK BRANCH NAME Meinhardt Australia Ptv I td DESIGN MNGR P.ENOCH ISSUE STATUS SECTION NAME CO-ORDINATE SYSTEM HEIGHT DATUM GE-0101 PROJECT MINGR P ENOCH DEPARTMENT NAME AHD

GENERAL ASPHALTIC CONCRETE MIX DESIGN, MANUFACTURE, PLACING AND COMPACTION SHALL BE IN ACCORDANCE WITH RMS QA

- PAVEMENT PREPARATION
 2. THE EXISTING SURFACE TO BE SEALED, SHALL BE DRY AND BROOMED BEFORE COMMENCEMENT OF WORK TO ENSURE
- THE EXISTING SURFACE TO BE SEALED, SPALL BE DAT AND BROUGHED BEFORE COMMERCEMENT OF WORK TO ENSURE COMPLETE REMOVAL OF ALL FOREIGN AND LOOSE MATTER.

 ALL DEPRESSIONS OR UNEVEN AREAS ARE TO BE TACK-COATED AND BROUGHT UP TO GENERAL LEVEL OF PAVEMENT WITH ASPHALTIC CONCRETE BEFORE LAYING OF MAIN COURSE.
- TACK COAT

 THE WHOLE OF THE AREA TO BE SHEETED WITH ASPHALTIC CONCRETE SHALL BE LIGHTLY AND EVENLY COATED WITH RAPID SETTING BITUMEN. APPLICATION SHALL BE BY MEANS OF A MECHANICAL SPRAYER WITH SPRAY BAR.
- SPREADING
 5. ALL ASPHALTIC CONCRETE SHALL BE SPREAD WITH A SELF PROPELLED PAVING MACHINE.
 6. THE ASPHALTIC CONCRETE SHALL BE LAID AT A MIX TEMPERATURE AS SHOWN BELOW-MIX TEMPERATURES(*C) TEMP IN SHADE (°C)

NOT PERMITTED 15 - 25

- ASPHALTIC CONCRETE SHALL NOT BE LAID WHEN THE ROAD SURFACE IS WET OR WHEN COLD WINDS CHILL THE MIX TO ADVERSELY AFFECT TEMPERATURE OF MIX DURING SPREADING AND COMPACTION OPERATIONS.
- S THE NUMBER OF JOINTS BOTH LONGITUDINAL AND TRANSVERSE SHALL BE KEPT TO A MINIMUM. THE DENSITY AND SURFACE FINISH AT JOINTS SHALL BE SIMILAR TO THOSE OF THE REMAINDER OF THE LAYER.

- COMPACTION

 10 ALL COMPACTION SHALL BE UNDERTAKEN USING SELF PROPELLED ROLLERS.

 11. INITIAL ROLLING SHALL BE COMPLETED BEFORE THE MIX TEMPERATURE FALLS BELOW 11.5°C.

 12. SECONDARY ROLLING SHALL BE COMPLETED BEFORE THE MIX TEMPERATURE FALLS BELOW 60°C.

FINISHED PAVEMENT PROPERTIES

12. FINISHED SURFACES SHALL BE SMOOTH, DENSE AND TRUE TO SHAPE AND SHALL NOT VARY MORE THAN 10mm FROM THE SPECIFIED HAN LEVEL AT ANY POINT AND SHALL NOT DEVIATE FROM THE BOTTOM OF A 3m STRAIGHT EDGE LAID IN ANY DIRECTION BY MORE THAN 5mm.

CONCRETE NOTES

GENERAL CONCRETE MIX DESIGN, MANUFACTURE, PLACING AND COMPACTION SHALL BE IN ACCORDANCE WITH RMS QA SPECIFICATIONS

- USE "AS3972-1997-PORTLAND AND BLENDED CEMENTS-TYPE GP" CEMENT (UNO).
 ALL CONCRETE SHALL BE SUBJECT TO PROJECT CONTROL SAMPLE AND TESTING TO AS3600-2001-CONCRETE
- CONSOLIDATE BY VIBRATION. CURE SURFACES AS SHOWN ON THE PLANS OR AS DIRECTED IN THE SPECIFICATION OR AS
- DIRECTED BY THE SUPERINTENDENT.
 FIX REINFORCEMENT AS SHOWN ON DRAWINGS. THE TYPE AND GRADE IS INDICATED BY A SYMBOL AS SHOWN BELOW

- FIX REINFORCEMENT AS SHOWN ON DRAWINGS. THE TYPE AND GRADE IS INDICATED BY A SYMBOL AS SHOWN!

 N HOT ROLLED DEFORMED BAR, GRADE 500

 R PLAIN ROUND BAR, GRADE 250

 SL / RL HARD DRAWN WIRE FABRIC SOUARE OR

 RECTANGULAR FOLLOWING THIS SYMBOL A NUMERAL INDICATES THE SPECIFIED DIAMETER.

 PROVIDE BAR SUPPORTS OR SPACERS TO PROVIDE CONCRETE COVER AS DETAILED TO ALL REINFORCEMENT.
- CONCRETE PAVEMENTS

 1. CONCRETE MIX PARAMETERS

 - MIX PARAMETERS
 a) MAXIMUM AGGREGATE SIZE 20mm

 b) FLEXURAL STRENGTH AT 28 DAYS = 3.5 MPa (Fc=32MPa)

 c) FLEXURAL STRENGTH AT 90 DAYS = 3.85 MPa

 - d) MAXIMUM WATER/CEMENT RATIO = 0.55 e) MAXIMUM SHRINKAGE LIMIT = 650 MICRON STRAINS (AS1012 of 13)
 - f) MINIMUM CEMENT CONTENT = 300kg/m²
 g) CEMENT TO BE TYPE "SL" (NORMAL CEMENT) to AS3972
- h) SI UMP = 80mm
- SAWN JOINTS ARE TO BE CUT NOT SOONER THAN 24 HOURS AND NOT LATER THAN 48 HOURS AFTER CONCRETE POUR TO

- SAMM JOINTS ARE TO BE CUT NOT SOONER THAN 24 HOURS AND NOT LATER THAN 48 HOURS AFTER CONCRETE POUR TO AVOID DAMAGING THE SURFACE DURING SAWCUT OR AS DIRECTED BY THE SUPINTENDENT.
 JOINT LAYOUT SHALL BE AS DETAILED ON THE PLANS.
 PROVIDE 10mm WIDE EXPANSION JOINTS BETWEEN ALL BUILDINGS, OTHER STRUCTURES AND PAVEMENTS.
 BOND BREAKER TO BE TWO (2) UNIFORM COATS OF BITUMEN EMULSION ALL OVER THE EXPOSED SURFACE AND ON END.
 DOWELS AND TIE BARS TO MEET STRENGTH REQUIREMENTS OF STRUCTURAL GRADE STEEL IN ACCORDANCE WITH AS ISO 302-2005-GEOMETRICAL PRODUCT SPECIFICATIONS. DOWELS AND TIE BARS SHALL BE-
- a) STRAIGHT,
 b) TO LENGTH SPECIFIED,
 c) ALL DOWELS TO BE HOT DIP GALVANISED,
- G) ALL DUMEDS TO BE ONLY INFO SECTIONALS,

 (I) SAWN TO LENGTH NOT CROPPED.

 DIMENSIONS OF SEALANT RESERVOIR DEPENDANT ON THE SEALANT TYPE ADOPTED. SUPERINTENDENT APPROVAL TO BE

 OBTAINED FOR SEALANT AND RESERVOIR DIMENSIONS AND DETAIL PROPOSED BY THE CONTRACTOR, REFER TO PLANS
- FOR TYPICAL ARRANGEMENT AND SEALANT.
- FOR TYPICAL ARRANGEMENT AND SEALANT.

 PRIOR TO THE PLACEMENT OF CONCRETE IN THE ADJACENT SLAB, 'ABLEFLEX' FILLER SHALL BE ADHERED TO THE ALREADY CAST AND CLEANED CONCRETE FACE USING AN APPROVED WATERPROOF ADHESIVE. ADHESIVE SHALL BE LIBERALLY APPLIED TO THE FULL FACE OF THE CONCRETE SLAB TO BE COVERED BY THE FILLER, AND ON THE FULL FACE OF THE FILLER TO BE ADHERED.

 THE BASE COURSE SHALL BE KEPT MOIST (NOT WET) BY SPRINKLING WITH WATER IMMEDIATELY PRIOR TO POURING THE PROMOPETER.
- CONCRETE.

 ALL WORK TO BE FINISHED TO SATISFY ITS INTENDED USE AS SHOWN ON THE PLANS, AND FOR IN ACCORDANCE WITH THE

- KERBING NOTES

 1.
 ALL CONCRETE KERBS TO HAVE A MINIMUM CHARACTERISTIC COMPRESSIVE STREINGTH Fo≈25MPa (UNO).

 2.
 ALL KERBS, DISH DRAINS, etc. TO BE CONSTRUCTED ON 75mm MINIMUM BASE COURSE.

 3.
 KERB BZPANSION JOINTS SHALL BE FORMED FROM 10mm COMPRESSIBLE CORK FILLER BOARD FOR THE FULL DEPTH OF
- EXPANSION JOINTS SHALL BE LOCATED AT DRAINAGE PITS, ON TANGENT POINTS OF CURVES AND ELSEWHERE AT 6m
- EAPARSON JOINTS SPALL BE LOCATED AT DRAINAGE PITS, ON TAMGENT POINTS OF MAXIMUM SPACING (UNO).

 TOOLED JOINTS SHALL BE MIN 3mm WIDE AND LOCATED AT MAXIMUM 3m SPACING. INTEGRAL KERB JOINTS SHALL MATCH THE LOCATION OF THE PAVEMENT JOINTING.

- LINEMARKING
- LINEMARKING MATERIALS, LAYOUT, TYPE & WORKS TO BE IN ACCORDANCE RIMS QA SPECIFICATIONS FOR ROADWORKS THE SCOPE OF WORK SHALL INCLUDE ALL PAVEMENT MARKINGS TO ROADS AND CARPARKS.
 THE WORK CARRIED OUT AND TESTING PERFORMED SHALL COMPLY WITH THE CURRENT, RELEVANT AUS-SPEC
- SPECIFICATIONS & AUSTRALIAN STANDARDS WHERE NECESSARY.
- ALL MARKINGS SHALL BE SPOTTED OUT AND APPROVED BY THE SUPERINTENDENT PRIOR TO APPLICATION. PAINT SHALL RE APPLIED AT A WET THICKNESS OF RETWEEN 0.35mm - 0.45mm
- FRANTS STALE DE AFFELDER A WELL FILLANDESS OF BETWEEN USURING VANDRIA.

 WILLESS OTHERWISE SPECIFIED, PERMITTED OR SHOWN ON THE DRAWINGS, PAINT SHALL BE WHITE, WITHOUT GLASS
 BEADS, EITHER SOLVENT OR WATERBORNE AND COMPLYING WITH THE REQUIREMENTS OF THE AUSTRALIAN STANDARD
- BEADS, EITHER SOLVENT OR WATERBORNE AND COMPLYING WITH THE REQUIREMENTS OF THE AUSTRALIAN STANDARD PAINT SHALL ONLY BE APPLIED TO CLEAN AND DRY SURFACES.

 ALL LONGITUDINAL LINES SHALL BE APPLED BY A SELF-PROPELLED MACHINE.
 LINEMARKING REMOVAL SHALL BE CARRIED OUT BY GRINDING OR SANDBLASTING. REMOVAL BY BURNING WILL NOT BE
- PERMITTED.
 THE EXTENT OF LINEMARKING TO BE ERADICATED SHALL BE CONFIRMED ON SITE PRIOR TO REMOVAL, ANY MARKINGS INCORRECTLY REMOVED SHALL BE REINSTATED AT THE CONTRACTOR'S EXPENSE.
 ALL MARKINGS SHALL BE COMPLETED IN A WORKMAN LIKE MANNER AND BE STRAIGHT, SMOOTH AND WITH EVEN CURVES. ANY NON-CONFORMING WORK, SHALL BE REMOVED AND REINSTATED AT THE DIRECTION OF THE SUPERINTENDENT AT
- 10. IF FINAL SEAL LAYER LAID, ALL LINEMARKING SHALL BE THERMOPLASTIC.



FOR CONSTRUCTION

DRAWING FILE LOCATION / NAME X1111403 - Galston-Grange Retirement-Villagel6BIM6_3 MHT MIE16_3_4 MHT UDIGalston Road - drawingstDS2014-000149-DD-GE-0101.dwg EXTERNAL REFERENCE FILES

REV DATE AMENDMENT / REVISION DESCRIPTION APPROVAL SCALES ON A3 SIZE DRAWING WVR No. 27-01-2017 INCORPORATED BRS COMMENT DATED 22-12-2016 05-06-2017 INCORPORATED BRS COMMENT DATED 16-05-2016 SK

DESIGN LOT CODE

Meinhardt Australia Pty Ltd

DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING

AHD

MGA ZONE 56

3/11/2014 2:21:41 PM Aseip NAME DATE D.CREARY DRAWN DRG CHECK M.GRINHAM DESIGN A.PHAM DESIGN CHECK S. DUNSTONE DESIGN MNGR P.ENOCH PROJECT MINGR P.ENOCH

Transport **Roads & Maritime NSW** Services

BRANCH NAME

SECTION NAME

DEPARTMENT NAME

HORNSBY SHIRE COUNCIL MR 161 - GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON

ISSUE STATUS

GALSTON GRANGE DEVELOPMENT GENERAL NOTES SHEET 2 OF 2

SHEET 03 OF 21 RMS REGISTRATION No. DS2014 / 000149

> GE-0101A © Roads and Maritime Services






FOR CONSTRUCTION

HORNSBY SHIRE COUNCIL
MR 161 - GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH
392 GALSTON ROAD, GALSTON
GALSTON GRANGE DEVELOPMENT PLOT DATE / TIME 3/11/2014 2:21:41 PM PLOT BY Aseip DRAWING FILE LOCATION / NAME DESIGN LOT CODE DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING DRAWING FILE LOCATION / NAME

X1111403 - Galston-Grange Retirement-Village(6BIM6_3 MHT MIE)6_3_4 MHT UDIGalston Road - drawings\DS2014-000149-DD-GE-0102.dwg EXTERNAL REFERENCE FILES REV DATE AMENDMENT / REVISION DESCRIPTION SCALES ON A3 SIZE DRAWING Transport ISSUED FOR 100% DESIGN DEVELOPMENT D.CREARY Roads & Maritime 02-11-16 27-01-17 INCORPORATED RMS COMMENTS DATED 21-07-2016
NO. OF DRAWINGS UPDATED SITE PLAN DRG CHECK M.GRINHAM Services SHEET 04 OF 21 DESIGN A.PHAM RMS REGISTRATION No. DS2014 / 000149 PREPARED FOR

BRANCH NAME
SECTION NAME
DEPARTMENT NAME DESIGN CHECK S.DUNSTONE INCORPORATED RMS COMMENTS DATED 16-05-2017 Meinhardt Australia Pty Ltd DESIGN MNGR P.ENOCH ISSUE STATUS FC CO-ORDINATE SYSTEM MGA ZONE 56 HEIGHT DATUM AHD GE-0102 PROJECT MINGR P.ENOCH




PROPOSED SERVICES

THE LOCATION AND EXTENT OF PROPOSED SERVICES IS
INDICATIVE ONLY AND ARE NOT TO BE USED FOR
CONSTRUCTION REFER TO AUTHORISED DOCUMENTATION
BY RELEVANT AUTHORITY FOR CONSTRUCTION DETAILS.



WARNING

BEWARE OF UNDERGROUND SERVICES THE LOCATIONS OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE. NO GUARANTEE IS GYEN THAT ALL EXISTING SERVICES ARE SHOWN.




GALSTON ROAD LONGITUDINAL SECTION MC100 FOLLOW EXISTING ROADS LEVELS





FOR CONSTRUCTION


-	DRAWING FILE LOCATION / NAME				DESIGN L	OT CODE	DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF TH	IIS DRAWING	PLOT DATE / TIME		PLOT BY	CLIENT		HORNSBY SHIRE COUNCIL			A3
<u> </u>	X.I111403 - Galston-Grange Retirement-Village\6BIM\6_3 MHT MIE\6_3_4 MH	T UD\Gals	ton Road -	- drawings\DS2014-000149-DD-RD-0104.dwg				7	3/11/2014 2:2	21:41 PM	Aseip			MR 161 - GALSTON ROAD ROAD WOR	RKS IN ASSOCIATION	I WITH	-
<u> </u>	EXTERNAL REFERENCE FILES R	EV DAT	E	AMENDMENT / REVISION DESCRIPTION	WVR No.	APPROVAL	SCALES ON A3 SIZE DRAWING	DRAWINGS / DESIGN PREPARED BY	TITLE	NAME	DATE			392 GALSTON ROAD, GALSTON			1
± 5€	LS-ROAD-GALSTON A	A 08-0	7-16	ISSUED FOR 100% DESIGN DEVELOPMENT			1:1000 H 0 5 10 15 20 25m		DRAWN	D.CREARY		AMMIN		GALSTON GRANGE DEVELOPMENT			
₹ ₹		B 02-1		INCORPORATED RMS COMMENTS DATED 21-07-2016	SK	PE		A/E-NIJ/IDET	DRG CHECK	M.GRINHAM		NSW	Roads & Maritime Services	LONGITUDINAL SECTION			
S		C 15-1:	- 1	SCALE BAR UPDATED INCORPORATED BRS COMMENTS DATED 22-12-2016	SK	PE	1:200 V 0 1 2 3 4 5m	// I=IIY74XI/I	DESIGN	A.PHAM		GOVERNENT	TOCI VICES			SHEET 06 OF)F 21
\$ -	8	E 05-0		INCORPORATED BRS COMMENTS DATED 22-12-2016 INCORPORATED RMS COMMENTS DATED 16-05-2016	SK	PE	SCALE 1 1000 HORIZONTAL 1:200 VERTICAL	Market and Assessed Decised	DESIGN CHECK	S.DUNSTONE		PREPARED FOR		RMS REGISTRATION No. DS2014 /	000149		PART 01
Ž ≂			- 1				AT ORIGINAL SIZE CO-ORDINATE SYSTEM HEIGHT DATUM	Meinhardt Australia Pty Ltd	DESIGN MNGR	P.ENOCH		BRANCH NA		ISSUE STATUS	EDMS No.	SHEET No.	ISSUE
Ë,		1					MGA ZONE 56 AHD		PROJECT MNGR	P.ENOCH		DEPARTME		FC		RD-0104	E
			_												@ Poads ar	d Maritime Se	aniicae


THIS DRAWING MAY BE PREPARED IN COLOUR AND MAY BE INCOMPLETE IF COPIED IN IS 120 125 130 135 140 145 150mm ON AS SIZE ORIGINAL












DESIGN PARAMETERS


- 7.6 x 10 ⁵
- 8.66 x 10 ⁵
- 1.31 x 10 ⁶ DESA (ESA) DSAR 5 (SAR 5) DSAR 7 (SAR 7) SUBGRADE DESIGN CBR (%)

LAYER	MATERIAL NAME	THICKNESS (mm)	BINDER TYPE
Z	AC14	50	AR450 BITUMEN
Υ	AC20	150	AR450 BITUMEN
Х	LOW CUTTER SEAL	7	
w	SMZ	300	~~~
٧	SUBGRADE (3% CI	BR (MIN.)


FLEXIBLE PAVEMENT NOTES:


- ALL EARTHWORKS INCLUDING SUBGRADE PREPARATION SHALL BE AS PER RMS
- SPECIFICATION R44
 THE PAVEMENT THICKNESS SHALL BE SUBJECT TO SUBGRADE TESTING BY REGISTERED NATA LABRATORY
- THE SMZ LAYER IS A STANDARD REQUIREMENT IN RMS PAVEMENTS AND SHOULD COMPLY TO THE RMS QA SPECIFICATION 3071






SAWCUT JOINT (SC) SCALE 1 40







TYPICAL SECTION PEDESTRIAN FOOTWAY

PLOT DATE / TIME


PLOT BY

CLIENT

SF TYPE KERB (SF)


SM TYPE KERB (SM)

SCALE 1.40




TYPICAL CONCRETE FOOTPATH PAVEMENT JOINTING NOTES:

- 1. ALL FOOTPATH PAVEMENTS TO BE JOINTED AS SHOWN ON DRAWINGS
- 1. ALL FOOTPATH PAVEMENTS TO BE JOINTED AS SHOWN ON DRAWINGS.
 2. SAWN JOINTS (SC) SHOULD GENERALLY BE LOCATED AT A MAXIMUM OF 3M. CENTRES,
 3. PROVIDE 20MM WIDE FULL DEPTH ISOLATION JOINTS (IJ) BETWEEN BUILDINGS,
 SERVICE PITS AND ALL CONCRETE OR UNIT PAVERS.
 4. SET OUT FOOTPATH PAVEMENT JOINTING GENERALLY AS FOLLOWS.
 5. PROVIDE 2H12 TRIMMER BARS AT ALL RE-ENTRANT CORNERS.
 6. WHERE FILLING UNDER PROPOSED CONCRETE FOOTPATH IS NECESSARY, SUCH
 FILLING SHALL CONSIST OF GRANULAR MATERIAL OF 20mm MAXIMUM SIZE AND SHALL
 BE SPREAD IN LAYERS OF A MAXIMUM THICKNESS OF 150mm AND CONSCULDATED TO
 PROVIDE A 95% COMPACTION WHEN TESTED UNDER THE MODIFIED PROCTOR METHOD
 AS PER HORNSBY SHIRE COUNCIL'S VEHICULAR CROSSING SPECIFICATION



DESIGN LOT CODE



CONCRETE VEHICULAR CROSSING / **BUS SHELTER PAVEMENT**

NOT TO SCALE (TO BE CONSTRUCTED SIMILAR TO RMS STANDARD DRAWING DS 2012/00293 SHEET 3)

CROSSING & BUS SHELTER PAVING NOTES:

- 1. ISOLATION JOINTS MUST BE PROVIDED AT THE FIRST JOINT AWAY FROM JUNCTIONS WITH FLEXIBLE PAVEMENTS AND STRUCTURES, AND AT (max.) INTERMEDIATE CENTRES OF 17.5m (EG. THREE SHEETS OF 6m LENGTH MESH, LESS LAPS.
 2. ISOLATION JOINTS CAN BE CONSTRUCTED AS FORMED JOINTS (BY CHEQUERBOARD PAVING SEQUENCE), OR BY FULL DEPTH SAWCUT.
 3. PLACE A FULL DEPTH ISOLATION JOINT AROUND ALL ABUTING STRUCTURES SUCH AS PITS, UTILITY SERVICES, POWER POLES, KERBS.
 4. THE OPTIONS FOR END-OF-DAY CONSTRUCTION JOINTS ARE AS FOLLOWS (1) TRANSVERSE CONSTRUCTION-FORMED/TED JOINTS MAY BE USED. THEY MUST BE LOCATED ETHER MIDWAY BETWEEN ISOLATION JOINTS OR IN LIEU OF A TRANSVERSE HINDER/TEDSAWN JOINT, THEY MUST NOT BE USED.

- LIEU OF A TRANSVERSE HINGE/TIED/SAWN JOINT, THEY MUST NOT BE USED. IN LIFE OF A ISOLATION JOINT
- IN LIEU OF A ISOLATION JOINT.

 (ii) PAVING MAY BE TERMINATED AT A ISOLATION JOINT.

 5. COMPLY WITH RMS SPECIFICATIONS RS3 AND R173. CONCRETE MUST BE IN ACCORDANCE WITH RMS RS3 BUT WITH A MINIMUM COMPRESSIVE STRENGTH
- ACCORDANCE WITH RMS R53 BUT WITH A MINIMUM COMPRESSIVE STRENGTH OF 32.0 MPa.


 5. SELF-EXPANDING CORK SEALANTS MUST FILL THE FULL JOINT CAVITY TO PREVENT THE INGRESS OF INCOMPRESSIBLE MATERIALS.

 7. SUB BASE MUST BE 150mm THICK TRAFFIC CATEGORY D MATERIAL IN ACCORDANCE WITH RMS SPECIFICATION 3051, COMPACTED IN ACCORDANCE WITH RMS R173. MOISTEN THE SUB BASE WITH WATER BEFORE PLACING THE CANDIDETE.
- CONCRETE.

 8. DEBOND TYPE TRANSVERSE CONSTRUCTION/FORMED/TIED JOINTS TO PREVENT CHEMICAL BONDING.
- ENSURE REINFORCING STEEL IS PLACED TO PROVIDE 30mm MINIMUM COVER BFI.OW THE SAWCUT.

DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING

10. WHERE FILLING LINDER PROPOSED BUS BAY AND VEHICLE AR CROSSING IS . WHERE FILLING UNDER PROPOSED BUS BAY AND VEHICULAR CROSSING IS MECESSARY; SUCH FILLING SHALL CONSIST OF GRANULAR MATERIAL OF 20mm MAXIMUM SIZE AND SHALL BE SPREAD IN LAYERS OF A MAXIMUM THICKNESS OF 150mm AND CONSCLIDATED TO PROVIDE A 95% COMPACTION WHEN TESTED UNDER THE MODIFIED PROCTOR METHOD AS PER HORNSBY SHIRE COUNCIL'S VEHICULAR CROSSING SPECIFICATION



TRANSVERSE CONSTRUCTION/FORMED/TIED JOINT OF CONCRETE VEHICULAR CROSSING/BUS SHELTER PAVEMENT

AT START AND END OF DAILY PAVING OPERATIONS, SEE NOTE 4 SCALE NTS



HORNSBY SHIRE COUNCIL


FOR CONSTRUCTION

A3 3/11/2014 2:21:41 PM 🞖 . X1111403 - Galston-Grange Retirement-Village\6BIM6 3 MHT MIE\6 3 4 MHT UD\Galston Road - drawings\DS2014-000149-DD-PV-0109-110,dwg Aseip MR 161 - GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON DRAWINGS / DESIGN PREPARED BY EXTERNAL REFERENCE FILES REV DATE AMENDMENT / REVISION DESCRIPTION WVR No. APPROVAL SCALES ON A3 SIZE DRAWING TITLE NAME DATE Transport GALSTON GRANGE DEVELOPMENT 08-07-16 ISSUED FOR 100% DESIGN DEVELOPMENT DRAWN D CREARY Roads & Maritime NSW 02-11-16 INCORPORATED RMS COMMENTS DATED 21-07-2016 M.GRINHAM DRG CHECK Services 14-12-16 INCORPORATED RMS COMMENTS DATED 21-07-2016 TYPICAL DETAILS SHEET SHEET 11 OF 21 DESIGN A.PHAM 27-01-17 NO. OF DRAWINGS UPDATED 07-04-17 INCORPORATED RMS PAVEMENT COMMENTS DATED 13-03-2017 DESIGN CHECK S.DUNSTONE PREPARED FOR RMS REGISTRATION No. DS2014 / 000149 Meinhardt Australia Pty Ltd BRANCH NAME 24-04-17 INCORPORATED RMS PAVEMENT COMMENTS DATED 13-03-2017 SK DESIGN MNGR P.ENOCH ISSUE STATUS CO-ORDINATE SYSTEM HEIGHT DATUM SECTION NAME PV-0109 05-06-17 INCORPORATED RMS PAVEMENT COMMENTS DATED 16-05-2017 H PROJECT MINGR P.ENOCH DEPARTMENT NAME INCORPORATED RMS PAVEMENT COMMENTS DATED 04-07-2017 © Roads and Maritime Services

DRAWING FILE LOCATION / NAME

INCOMPLETE IF COPIED 172E ORIGINAL

EDGE DETAIL TO SHOW PAVEMENT/KERB INTERFACE




LONGITUDINAL CONSTRUCTION JOINT NEW CONSTRUCTION - CONFINED


OTES:
THE TACKCOAT MUST BE APPLIED AT AN APPLICATION
RATE OF BETWEEN 0.15 Im ² AND 0.30 I/m² OF
RESIDUAL BITUMEN FOR JOINTS THE APPLICATION
RATE MUST BE DOUBLED ON VERTICAL FACES
ASPHALT COMPACTION SHOULD COMPLY WITH RMS
R116 SPECIFICATION

REMOVE 50mm THICK EXISTING PAVEMENT AND LAID 50mm THICK NEW AC14 WEARING COURSE EXISTING PAVEMENT NEW PAVEMENT ________AC20 SMZ

> TRANSVERSE CONSTRUCTION JOINT REINSTATEMENT



TRANSVERSE CONSTRUCTION JOINT **NEW CONSTRUCTION**



LONGITUDINAL CONSTRUCTION JOINT REINSTATEMENT

> Transport Roads & Maritime Services These plans are accepted for construction

Project Manager Date #7/08/17

FOR CONSTRUCTION

DRAWING FILE LOCATION / NAME DESIGN LOT CODE DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING NAME TO STATE THE PROPERTY OF REV DATE AMENDMENT / REVISION DESCRIPTION APPROVAL | SCALES ON A3 SIZE DRAWING EXTERNAL REFERENCE FILES WVR No. INCORPORATED RMS COMMENTS DATED 21-07-2016 INCORPORATED RMS COMMENTS DATED 21-07-2016 14-12-16 27-01-17 NO. OF DRAWINGS UPDATED 07-04-17 INCORPORATED RMS PAVEMENT COMMENTS DATED 13-03-2017 05-06-17 INCORPORATED RMS PAVEMENT COMMENTS DATED 16-05-2017 14-06-17 INCORPORATED RMS PAVEMENT COMMENTS DATED 04-07-2017 CO-ORDINATE SYSTEM

MEIN-ARDI Meinhardt Australia Pty Ltd

DRAWINGS / DESIGN PREPARED BY

HEIGHT DATUM

AHD

PLOT DATE / TIME PLOT BY 3/11/2014 2:21:41 PM Aseip NAME TITLE DATE D.CREARY DRAWN DRG CHECK M.GRINHAM DESIGN A.PHAM DESIGN CHECK S,DUNSTONE BRANCH NAME SECTION NAME DESIGN MINGR P.ENOCH

PROJECT MNGR P.ENOCH


CLIENT Transport Roads & Maritime **NSW** Services PREPARED FOR

DEPARTMENT NAME

HORNSBY SHIRE COUNCIL MR 161 - GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON GALSTON GRANGE DEVELOPMENT

TYPICAL DETAILS SHEET SHEET 12 OF 21 RMS REGISTRATION No. DS2014 / 000149 ISSUE STATUS SHEET No. PV-0110

© Roads and Maritime Services





BEWARE OF UNDERGROUND SERVICES THE LOCATIONS OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.

EXISTING	PROPOSED	DESCRIPTION
— — Ex.DR —		STORMWATERPIPE
— — EnG—	G G	GAS MAIN
— — B.T —	T	TELSTRA COPPER CABLE
	———E U/G ———	UNDERGROUND ELECTRICITY
	——E O/H ——	OVERHEAD ELECTRICITY
Ex5-	ss	SEWERMAIN
Et.W-	w	WATERMAIN
		STRÉET LIGHTING

FOR CONSTRUCTION

_								WWW.FFOO.tom.so
25 30	DRAWING FILE LOCATION / NAME X:1111403 - Galston-Grange Retirement-Villaget6BIM6_3 MHT MIE16_3_4	MHT U	D\Galston Road	- drawingsiDS2014-000149-DD-UT-0110.dwg	DESIGN LO	T CODE	DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THI	S DRAWING
20	EXTERNAL REFERENCE FILES	REV	DATE	AMENDMENT / REVISION DESCRIPTION	WVR No.	APPROVAL	SCALES ON A3 SIZE DRAWING	DRAWINGS / DESIGN PREPARED BY
12	X-111403-IE-BASE	Α	08-07-16	ISSUED FOR 100% DESIGN DEVELOPMENT				
12	X-111403-IE-BASE TEXT	8	02-11-16	INCORPORATED RMS COMMENTS DATED 21-07-2016	SK	PE	0 2.5 5 7.5 10 12.5m	
	X-111403-Existing services	С	15-12-16	SCALE BAR UPDATED	SK	PE	0 2:3 3 1:3 10 12:311	WEIN-MRDT
9	gal da-02c modify	D	27-01-17	NO, OF DRAWINGS UPDATED	SK	PE	SCALE 1500 AT ORIGINAL SIZE	
П	B1418-DETAIL modify	E	28-04-17	INCORPORATED RMS COMMENTS DATED 13-03-17	SK	PE	SCALE 1300 AT ORIGINAL SIZE	
LC.		F	05-06-17	INCORPORATED RMS COMMENTS DATED 16-05-17	SK	PE	1 110-11-1	Meinhardt Australia Pty Ltd

CO-ORDINATE SYSTEM

HEIGHT DATUM

	PLOT DATE / TIME 3/11/2014 2:2	
	TITLE	NAME
The second party of the second of	DRAWN	D.CREARY
MSUL	DRG CHECK	M.GRINHAM
	DESIGN	A.PHAM
-P- Divided	DESIGN CHECK	S.DUNSTONE
alia Pty Ltd	DESIGN MINGR	P.ENOCH
	PROJECT MNGR	P.ENOCH


LOT B		CLIENT
	DATE	Transport
		Roads & Maritime
		NSW Services
		PREPARED FOR
		BRANCH NAME
+		SECTION NAME DEPARTMENT NAME
_		

HORNSBY SHIRE COUNCIL
MR 161 - GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH
392 GALSTON ROAD, GALSTON
GALSTON GRANGE DEVELOPMENT

EXISTING SERVICES PLAN

SHEET 13 OF 21 RMS REGISTRATION No. DS2014 / 000149 ISSUE STATUS FC SHEET No. UT-0110

© Roads and Maritime Services



Transport Roads & Maritime NSW Services These plans are accepted for construction

LEGEND

PROPOSED LINEMARKING - REFER RMS DOCUMENT DELINEATION SECTION 4 - LONGITUDINAL MARKINGS

PROJECT MINGR P.ENOCH

- ALL LINE MARKING SHOULD BE CONSTRUCTED IN ACCORDANCE TO RMS STANDARDS.
- 2. ALL SIGNS TO BE LOCATED IN ACCORDANCE WITH RMS STANDARDS.

REF	SIGN	CODE
#1	GIVE	R1-2
#2	KEEP	R2-3
#3	ONLY	R2-14
#5	BUS	R5-20(L)
#6	BUS	R5-20(R)
#5	BUS	R5-20(L)

	#10 / #11-						
REF	SIGN	CODE					
#6	BUS	R5-20(R)					
#7	NO STOPPING	R5-400(L)					
#8	NO STOPPING	R5-400(R)					
#9	NO STOPPING	R5-400(L+R)					
#10		W6-1B					
#11	REFUGE	W8-25B					
FOR CONCERNATION							

FOR CONSTRUCTION

55 30	DRAWING FILE LOCATION / NAME X1111403 - Galston-Grange Retirement-Village16BIM6_3 MHT M	MENS 3 A MUT LI	NGereton Pos	d . drawings1DS2014.000140.DD.DS.J1111 dug	DESIGN LO	OT CODE	DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF T	THIS DRAWING
	EXTERNAL REFERENCE FILES		DATE	AMENDMENT / REVISION DESCRIPTION	WVR No.	APPROVAL	SCALES ON A3 SIZE DRAWING	DRAWINGS / DESIGN
20	X - 111403 - Survey	A	08-07-16	ISSUED FOR 100% DESIGN DEVELOPMENT				
72	X - 111403 - IE - BASE	В	02-11-16	INCORPORATED RMS COMMENTS DATED 21-07-2016	SK	PE	0 2.5 5 7.5 10 12.5m	4 4
	3306	c	15-12-16	INCORPORATED RMS COMMENTS DATED 21-07-2016	SK	PE		///-
10		D	27-01-16	INCORPORATED BRS COMMENTS DATED 22-12-2016	SK	PE	SCALE 1 500 AT ORIGINAL SIZE	///
		E	28-04-17	INCORPORATED BRS COMMENTS DATED 13-03-2017	SK	PE		
S		F	05-06-17	INCORPORATED RMS COMMENTS DATED 16-05-2017	SK	PE		Meinh
							CO-ORDINATE SYSTEM HEIGHT DATUM	
0							MGA ZONE 56 AHD	


DRAWINGS / DESIGN PREPARED BY
MEIN-ARDT
Meinhardt Australia Pty Ltd

PLOT DATE / TIME 3/11/2014 2:2		Aseip	CLIENT	
TITLE	NAME	DATE	white the	Transpo
DRAWN	D.CREARY			Roads &
DRG CHECK	M.GRINHAM		NSW	Services
DESIGN	A.PHAM			
DESIGN CHECK	S.DUNSTONE		PREPARED FOR	45
DESIGN MNGR	P.ENOCH		BRANCH NAM	
PROJECT MINGR	P.ENOCH		DEPARTMEN	

1	HORNSBY SHIRE COUNCIL
	MR 161 - GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH
	392 GALSTON ROAD, GALSTON
	GALSTON GRANGE DEVELOPMENT

LINE MARKING & SIGNAGE PLAN

SHEET 14 OF 21 RMS REGISTRATION No. DS2014 / 000149 ISSUE STATUS RF-0111




	SETOUT ROAD CL - MC 100									
Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.Angle			
IP1	0,000	318238.721	6274408.140	10*45'43.25*						
TC	15.521	318241.619	6274423.389	10°45'43.25"						
IP2	35.767	318245.483	6274443.714		80	40,491	28°59'58.82°			
CT	56.013	318258.715	6274459.618	39*45'42.07*						
TC	96.282	318284.471	6274490.573	39*45'42.07*			1			
IP3	105.607	318290.438	6274497.744	1	300	18 651	3*33'43.26*			
CT	114.932	318296.838	6274504,530	43*19'25.33*						
TC	128.085	318305.862	6274514.099	43*19'25.33"						
IP4	144,077	318316,877	6274525,777		150	31,985	12°13'02.33°			
CT	160,070	318330.113	6274534,861	55*32'27,66"						
IP5	175,249	318342.629	6274543,449	55*32*27.66*			T			

Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.Angle
IP1	0.000	318233.419	6274405.084	21"38'03.34"			
IP2	6.907	318235.981	6274411.545		-50.5	13.814	15°40′24.54
CT	13.814	318236.703	6274418.458	5°57'38.80°			
TC	35,403	318238.945	6274439,930	5°57'38,80°			
IP3	36.746	318239,085	6274441.275		9.5	2.687	16*12'14.4
CC	38.089	318239.596	6274442.527	22*09'53.23*			
IP4	45,549	318242.417	6274449,454		83	14,918	10*17'53.3
CC	53.008	318246.432	6274455.764	32°27'46.61°			
IP5	60,251	318252.254	6274464,915		-7.5	14,487	110°40'19.9
IP6	67.495	318241,636	6274467,132	281*47*26.67*			

Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.An
		ļ			Radiopilal	ALCHGUI	D.AII
IP1	0,000	318249.846	6274469.531	126*47'51.43*			
IP2	7.216	318257.069	6274464.128		-9.5	14.431	87*02'0
CT	14,431	318262,839	6274471,063	39°45'42.07"			
TC	14,520	318262.896	6274471,131	39°45'42,07°			
IP3	19.504	318266,094	6274474,975		-50,5	9,968	11°18'3
CT	24.488	318268.476	6274479.371	28*27'06,31"			
TC	32.433	318272.261	6274486,356	28°27'06.31"			
IP4	37.319	318274,596	6274490,666		49,5	9,771	11°18'3
CT	42,204	318277.731	6274494.434	39°45'42.07°			
TC	43.467	318278,539	6274495.404	39*45'42.07*			
IP5	46.598	318280.542	6274497.811		307.2	6.261	1*10'0
CT	49.728	318282.593	6274500.176	40*55'46.22"			-
TC	55.710	318286.511	6274504.695	40°55'46.22°			
IP6	57.141	318287.452	6274505.780		14.5	2.862	11°18'3
CT	58.572	318288.587	6274506.659	52*14'21.98"			
TC	73.902	318300.707	6274516,047	52°14'21,98"			
IP7	75,841	318302,242	6274517.236		-30,5	3,878	7*17'0
IP8	77.780	318303,613	6274518,610				
IP9	83.191	318307.439	6274522.441		123.7	10.821	5*00'4
IP10	88.602	318311,584	6274525,924	1			
IP11	93,930	318315.679	6274529.364		-50.5	10,656	12*05%
IP12	99.258	318318 963	6274533 585	37*52'37.43*		İ	

		SETOUT TA	ABLE - KER	B KR C (LIF	OF KERB)		
Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.Angle
IP1	0.000	318345.817	6274538.671	251*49'05.80"			
IP2	7.788	318338.358	6274536.221		-50.5	15.577	17°40'21.89°
IP3	15.577	318331.995	6274531.623				
IP4	25.822	318323.670	6274525.606		-116.3	20.491	10*05'41.55"
CT	36.067	318316,527	6274518.223	224°03'02,42"			
TC	54,384	318303.792	6274505,059	224°03'02.42"			
IP5	63,154	318297,679	6274498.739		-100.5	17,54	9*59'58,49*
ст	71,924	318292.756	6274491.455	214*03'03.93"		·	
TC	85,508	318285,149	6274480.200	214"03'03.93"			
IP6	90.467	318282,371	6274476.088		99.5	9,917	5°42'38.14"
CT	95.425	318279,197	6274472.273	219°45'42.07"			
TC	113.411	318267.693	6274458.448	219*45'42.07*			
IP7	114.842	318266.775	6274457.344		14.5	2.862	11*18'35.76*
CT	116.273	318265.658	6274456.442	231*04'17.82*			=
TC	123.129	318260.325	6274452.134	231*04'17.82*			
IP8	129.772	318255.073	6274447.892		-30.5	13.287	24°57'38.77"
IP9	136.416	318252.102	6274441.830				
IP10	142,320	318249,468	6274436.547				
IP11	144,463	318248.510	6274434.625		-30.5	4,287	8°03'13.21"
IP12	146,607	318247,831	6274432,588	1			
1P13	153,507	318245,642	6274426,024		-76.3	13.801	10°21'50.05"
1P14	160,408	318244,669	6274419.173				
IP15	166,084	318243,868	6274413,530		-50.5	11.351	12*52'42.30"
IP16	171.759	318244,345	6274407.851	175*12'01,27*			

					********					IP4	37.319	318274,596	6274490,666		49.5	9,771	11*18'35,76*		IP6	90,467	318282,371	6274476.088		99.5	9,917	5°42'38.14"
	IP5	175,249	318342.629	6274543,449	55*32*27.66*					CT	42,204	318277,731	6274494,434	39°45'42.07°					СТ	95.425	318279,197	6274472,273	219*45'42.07"		-	
					D 1/D 4 // 1D	OF KEDDY	-			TC	43,467	318278.539	6274495.404	39°45'42.07°					TC	113.411	318267.693	6274458.448	219*45'42.07"			
			SETOUTTA	ARLE - KEK	B KR A (LIP	OF KEKR)				IP5	46.598	318280.542	6274497.811		307.2	6.261	1*10'04.16"		IP7	114.842	318266.775	6274457.344		14.5	2.862	11*18'35.76*
	Pt	Chainage	Easting	Northing	Bearing	Rad/Spiral	A.Length	D.A	ngle	СТ	49.728	318282.593	6274500.176	40*55'46.22"					СТ	116.273	318265.658	6274456.442	231"04"17.82"			-
	IP1	0.000	318233.419	6274405.084	21"38'03.34"			1		TC	55.710	318286.511	6274504.695	40*55'46.22*					TC	123.129	318260.325	6274452.134	231*04'17.82*			
	IP2	6.907	318235.981	6274411.545		-50.5	13.814	15°40	24.54"	IP6	57.141	318287.452	6274505.780		14.5	2.862	11*18'35.76*		IP8	129.772	318255.073	6274447.892		-30.5	13.287	24°57'38.77*
	СТ	13.814	318236.703	6274418.458	5°57'38.80°					СТ	58.572	318288.587	6274506.659	52*14"21.98"					IP9	136.416	318252.102	6274441.830				
	TC	35,403	318238.945	6274439,930	5°57'38,80°					TC	73.902	318300.707	6274516,047	52°14'21.98°					IP10	142,320	318249.468	6274436,547				
	IP3	36.746	318239,085	6274441.275		9.5	2.687	16°12	14,43"	IP7	75,841	318302,242	6274517.236		-30,5	3,878	7*17'03,86*		IP11	144.463	318248.510	6274434.625		-30.5	4,287	8°03'13,21"
	CC	38,089	318239.596	6274442.527	22°09′53,23°					IP8	77.780	318303.613	6274518.610				-		IP12	146,607	318247,831	6274432,588				
	IP4	45,549	318242.417	6274449,454		83	14,918	10°17	53.38*	IP9	83.191	318307.439	6274522.441		123.7	10.821	5*00'44,38*		IP13	153,507	318245,642	6274426,024		-76.3	13.801	10*21'50.05"
	CC	53.008	318246,432	6274455.764	32°27'46.61°					IP10	88.602	318311,584	6274525.924						IP14	160,408	318244,669	6274419.173				
	IP5	60,251	318252.254	6274464,915		-7.5	14,487	110°4	"19.94"	IP11	93,930	318315.679	6274529.364		-50.5	10.656	12*05'25.10*		IP15	166,084	318243,868	6274413,530		-50,5	11.351	12*52'42.30*
	IP6	67.495	318241,636	6274467,132	281*47*26.67*				2	IP12	99,258	318318,963	6274533,585	37*52'37.43*					IP16	171.759	318244,345	6274407.851	175*12'01,27*			
																								-	00.001	OTDLICT
111403 - Gals	LOCATION / NAME	Village\6BIM\6_3 MHT						DESIGN LOT		ESIGN MODEL FILE(S) L						PLOT DATE / TIME 3/11/2014 2:21	:41 PM	PLOT BY Aseip	CLIENT	1		MR 161	BY SHIRE COUN - GALSTON ROA	ICIL AD ROAD WOR		STRUCTI
111403 - Gals TERNAL REF	ston-Grange Retirement FERENCE FILES	Villaget6BIMt6_3 MHT	REV D	ATE AMENDA	ENT / REVISION DES	CRIPTION				ESIGN MODEL FILE(S) L CALES ON A3 SIZE DRA			WING AWINGS / DESIGN PREPA	RED BY		3/11/2014 2:21	:41 PM NAME		stillitz.	Trans	sport	MR 161 392 GAI	- GALSTON ROAD, G	ICIL AD ROAD WOR ALSTON		
111403 - Gals TERNAL REF 111403 - Sel	ston-Grange Retirement FERENCE FILES toutGR	Village\6BIM\6_3 MHT	REV D	ATE AMENDA 3-07-16 ISSUED I	ENT / REVISION DES	CRIPTION		WVR No.	APPROVAL S	CALES ON A3 SIZE DRA	WING	DR	AWINGS / DESIGN PREPA			3/11/2014 2:21 TITLE DRAWN	:41 PM NAME D.CREARY	Aseip		Roads	s & Maritir	MR 161 392 GAL GALSTO	- GALSTON ROA LSTON ROAD, G ON GRANGE DE	ICIL AD ROAD WOR ALSTON		
111403 - Gals TERNAL REF 111403 - Set 111403 - Sur	ston-Grange Retirement FERENCE FILES toutGR rvey	Villege\6BIM\6_3 MHT	REV D/ A 08 B 02	ATE AMENDA 3-07-16 ISSUED I 2-11-16 INCORPO	MENT / REVISION DESC FOR 100% DESIGN DE ORATED RMS COMME	CRIPTION		WVR No.	APPROVAL S	CALES ON A3 SIZE DRA	wing 5 7.5 10 12.	DR	AWINGS / DESIGN PREPA		77	3/11/2014 2:21 TITLE DRAWN DRG CHECK	1:41 PM NAME D.CREARY M.GRINHAM	Aseip	stillitz.	Trans Roads	s & Maritir	me MR 161 392 GAL GALSTO SETO	- GALSTON ROA LSTON ROAD, G ON GRANGE DEV OUT PLAN	ICIL AD ROAD WOR ALSTON		TION WITH
111403 - Gals TERNAL REF 111403 - Sel	ston-Grange Retirement FERENCE FILES toutGR rvey	Village\6BIM6_3 MHT	REV D/ A 08 B 02	ATE AMENDA 3-07-16 ISSUED I 2-11-16 INCORPO 5-12-16 SCALE B	ENT / REVISION DES	CRIPTION		WVR No.	APPROVAL S	CALES ON A3 SIZE DRA	wing 5 7.5 10 12.	DR)ī	3/11/2014 2:21 TITLE DRAWN DRG CHECK	:41 PM NAME D.CREARY	Aseip		Roads	s & Maritir	MR 161 392 GAL GALSTO	- GALSTON ROA LSTON ROAD, G ON GRANGE DEV OUT PLAN	ICIL AD ROAD WOR ALSTON		TION WITH
111403 - Gals TERNAL REF 111403 - Set 111403 - Sur 111403 - IE - 06	ston-Grange Retirement FERENCE FILES toutGR rvey	Villaget6BIM6_3 MHT	REV DA A 08 B 02 C 15 D 27	ATE AMENDA 3-07-16 ISSUED I 2-11-16 INCORPO 5-12-16 SCALE B 7-01-17 NO. OF C	MENT / REVISION DESC FOR 100% DESIGN DE DRATED RMS COMME IAR UPDATED DRAWINGS UPDATED D DRAWING PRESENT.	CRIPTION VELOPMENT NTS DATED 21-07-2010 ATION		WVR No.	APPROVAL S	CALES ON A3 SIZE DRA	wing 5 7.5 10 12.	DR	AWINGS / DESIGN PREPA	V -1 431		3/11/2014 2:21 TITLE DRAWN DRG CHECK	:41 PM NAME D.CREARY M.GRINHAM A.PHAM	Aseip	NSW SOMEWHAT PREPARED FOR	Roads Service	s & Maritir	MR 161 392 GAL GALSTO SETO SHEET	- GALSTON ROAD, G LSTON ROAD, G DN GRANGE DE OUT PLAN 1 OF 2	ICIL AD ROAD WOR ALSTON VELOPMENT	RKS IN ASSOCIA	TION WITH
111403 - Gals TERNAL REF 111403 - Set 111403 - Sur 111403 - IE - 06	ston-Grange Retirement FERENCE FILES toutGR rvey - BASE	Village\6BIM6_3 MHT	REV DA A 08 B 02 C 15 D 22 E 07 F 28	ATE AMENDN 8-07-16 ISSUED I 2-11-16 INCORPO 5-12-16 SCALE B 7-01-17 NO. OF 0 7-04-17 REVISED 8-04-17 INCORPO	MENT / REVISION DESC FOR 100% DESIGN DE ORATED RMS COMME MAR UPDATED ORAWINGS UPDATED ODRAWING PRESENT. ORATED RMS COMME	CRIPTION VELOPMENT NTS DATED 21-07-2010 ATION INTS DATED 13-03-17		WVR No. SK SK SK SK SK SK	APPROVAL S PE PE PE PE PE PE	0 2.5	5 7.5 10 12. 0 AT ORIGINAL SIZE	5m	AWINGS / DESIGN PREPA			3/11/2014 2:21 TITLE DRAWN DRG CHECK DESIGN	:41 PM NAME D.CREARY M.GRINHAM A.PHAM S.DUNSTONE	Aseip	NSW 90XERNERT PREPARED FOR BRANCH NA	Roads Service	s & Maritir	MR 161 392 GAL GALSTO SETO SHEET RMS REGI	- GALSTON ROAD, G LSTON ROAD, G DN GRANGE DE DUT PLAN 1 OF 2 STRATION NO. DS	ICIL AD ROAD WOR ALSTON	000149	TION WITH SHEET 15
11403 - Gals TERNAL REF 111403 - Set 111403 - Sur 111403 - IE -	ston-Grange Retirement FERENCE FILES toutGR rvey - BASE	Village\6BIM\6_3 MHT	REV DA A 08 B 02 C 15 D 27 E 07	ATE AMENDN 8-07-16 ISSUED I 2-11-16 INCORPO 5-12-16 SCALE B 7-01-17 NO. OF 0 7-04-17 REVISED 8-04-17 INCORPO	MENT / REVISION DESC FOR 100% DESIGN DE DRATED RMS COMME IAR UPDATED DRAWINGS UPDATED D DRAWING PRESENT.	CRIPTION VELOPMENT NTS DATED 21-07-2010 ATION INTS DATED 13-03-17		WVR No. SK SK SK SK	PE PE PE PE PE PE PE PE PE PE PE PE PE P	CALES ON A3 SIZE DRA	wing 5 7.5 10 12.	5m	AWINGS / DESIGN PREPA	V -1 431		3/11/2014 2:21 TITLE DRAWN DRG CHECK DESIGN DESIGN CHECK	:41 PM NAME D.CREARY M.GRINHAM A.PHAM S.DUNSTONE P.ENOCH	Aseip	NSW SOMEWHAT PREPARED FOR	Roads Service ME	s & Maritir	MR 161 392 GAL GALSTO SETO SHEET	- GALSTON ROAD, G LSTON ROAD, G DN GRANGE DE DUT PLAN 1 OF 2 STRATION NO. DS	ICIL AD ROAD WOR ALSTON VELOPMENT	RKS IN ASSOCIA	TION WITH



X - 111403 - IE - BASE 3306

X - 111403 - SetoutGR

08-07-16 ISSUED FOR 100% DESIGN DEVELOPMENT INCORPORATED RMS COMMENTS DATED 21-07-2016 15-12-16 SCALE BAR UPDATED 27-01-17 NO. OF DRAWINGS UPDATED 07-04-17 REVISED DRAWING PRESENTATION INCORPORATED RMS COMMENTS DATED 13-03-17 05-06-17 INCORPORATED RMS COMMENTS DATED 16-05-17

2,5 5 7,5 10 12,5m CO-ORDINATE SYSTEM HEIGHT DATUM

PE PE PE

Meinhardt Australia Pty Ltd

TITLE NAME DATE D.CREARY DRAWN DRG CHECK M.GRINHAM DESIGN A.PHAM DESIGN CHECK S.DUNSTONE DESIGN MINGR P.ENOCH PROJECT MINGR P.ENOCH

Transport Roads & Maritime Services


PREPARED FOR BRANCH NAME SECTION NAME DEPARTMENT NAME 392 GALSTON ROAD, GALSTON

GALSTON GRANGE DEVELOPMENT

ISSUE STATUS

SETOUT PLAN SHEET 16 OF 21 SHEET 2 OF 2 DS2014 / 000149

> SO-0113 © Roads and Maritime Services



DESIGN LOT CODE

WVR No. | APPROVAL | SCALES ON A3 SIZE DRAWING

CO-ORDINATE SYSTEM

REV DATE AMENDMENT / REVISION DESCRIPTION

ISSUED FOR 100% DESIGN DEVELOPMENT

INCORPORATED RMS COMMENTS DATED 21-07-2016

SCALE BAR UPDATED
INCORPORATED BRS COMMENTS DATED 22-12-2016

INCORPORATED BRS COMMENTS DATED 13-03-2017 INCORPORATED RMS COMMENTS DATED 16-05-2017

08-07-16

02-11-16

15-12-16 27-01-17

28-04-17 05-06-17

DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING

2,5 5 7,5 10 12,5m

HEIGHT DATUM

DRAWINGS / DESIGN PREPARED BY

MEIN-ARD

Meinhardt Australia Pty Ltd

HORNSBY SHIRE COUNCIL MR 161 - GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH

SHEET 17 OF 21

MS-0114

© Roads and Maritime Services

392 GALSTON ROAD, GALSTON

TURNING PATHS PLAN

ISSUE STATUS

GALSTON GRANGE DEVELOPMENT

RMS REGISTRATION No. DS2014 / 000149

PLOT BY LShusharina

DATE

NSW

PREPARED FOR BRANCH NAME SECTION NAME

DEPARTMENT NAME

Transport

Services

Roads & Maritime

PLOT DATE / TIME

TITLE

DRAWN

DESIGN

3/11/2014 2:21:41 PM

NAME

DRG CHECK M.GRINHAM

DESIGN CHECK S,DUNSTONE

DESIGN MNGR P.ENOCH

PROJECT MNGR P.ENOCH

D.CREARY


A.PHAM


Z.1111403 - Galston-Grange Retirement-Villaget6BIM6_3 MHT MIE16_3_4 MHT UDtGalston Road - drawingstDS2014-000149-DD-MS-0114.dwg X-111403-364-00, X-111403-IE-BASE ₽ B1418-DETAIL modify

DRAWING FILE LOCATION / NAME

EXTERNAL REFERENCE FILES

X - 111403 - IE - TURNING









Transport Roads & Maritime Services

These plans are accepted for construction

Project Manager Date 07/08/17

A. SINGLE STRIP METHOD

- 1. BURY THE TOP END OF THE ORGANIC FIBRE REINFORCED MESH STRIP (JUTE MESH) IN A TRENCH 150 OR MORE IN DEPTH.
- 2. TAMP THE TRENCH FULL OF SOIL. SECURE WITH A ROW OF PINS - MINIMUM NUMBER 8.
- 3. LAY MESH ALONG DRAIN WITHOUT STRETCHING THE MESH.
- 4. OVERLAP-BURY UPPER END OF LOWER STRIP AS IN 1 AND 2. OVERLAP END OF TOP STRIP 150 AND STAPLE.
- 5. EROSION STOP FOLD OF MESH BURIED IN SLIT TRENCH AND TAMPED; DOUBLE ROW OF STAPLES.
- 6. STAPLE THE MESH ALONG EACH EDGE AND CENTRE WITH TWO PINS ON EACH EDGE AND 1 IN CENTRE PER METRE OF MESH.
- 7. AFTER SEEDING AND LAYING JUTE MESH, APPLY A SLOW-BREAKING MEDIUM SETTING ANIONIC BITUMEN EMULSION AT A RATE IN ACCORDANCE WITH THE ROADS AND MARITIME SERVICES SPECIFICATION R111 SPRAYED BITUMINOUS SURFACING (WITH BITUMEN EMULSION). A HEAVIER APPLICATION IS TO BE MADE ON OUTER EDGES AND JOINTS.
- 8. ANIONIC BITUMEN TO BE APPLIED IN ALL INSTANCES EXCEPT UPON THE SUPERINTENDENTS DISCRETION FOR ENVIRONMENTAL REASONS.

B. TWO OR MORE STRIPS METHOD

- 1. PROCEED AS FOR SINGLE STRIP FOR EACH ROW. PROVIDE 150 OVERLAP BETWEEN ADJOINING STRIPS AND STAPLE ALONG TOP EDGE BETWEEN STRIPS
- 2. AFTER SEEDING AND LAYING JUTE MESH, APPLY A SLOW-BREAKING MEDIUM SETTING ANIONIC BITUMEN EMULSION AT A RATE IN ACCORDANCE WITH THE SPECIFICATION, A HEAVIER APPLICATION IS TO BE MADE ON OUTER EDGES AND JOINTS.
- 3. ANIONIC BITUMEN TO BE APPLIED IN ALL INSTANCES EXCEPT UPON THE SUPERINTENDENTS DISCRETION FOR ENVIRONMENTAL REASONS.

1. PRIOR TO PLACING THE ORGANIC FIBRE REINFORCED MESH (JUTE MESH), THE DRAIN SHALL BE PREPARED IN ACCORDANCE WITH ROADS AND MARITIME SERVICES SPECIFICATION R11 STORMWATER DRAINAGE.

FOR CONSTRUCTION

DRAWING FILE LOCATION / NAME DESIGN LOT CODE DESIGN MODEL FILE(S) USED FOR DOCUMENTATION OF THIS DRAWING X:\111403 - Galston-Grange Retirement-Village\6BIM\6_3 MHT MIE\6_3_4 MHT UD\Galston Road - drawings\DS2014-000149-DD-MS-0120.dwg EXTERNAL REFERENCE FILES REV DATE AMENDMENT / REVISION DESCRIPTION WVR No APPROVAL SCALES ON A3 SIZE DRAWING 02-11-16 INCORPORATED RMS COMMENTS DATED 21-07-2016 27-01-17 NO. OF DRAWINGS UPDATED INCORPORATED RMS COMMENTS DATED 13-03-2017 28-04-17 05-06-17 INCORPORATED RMS COMMENTS DATED 16-05-2017 Meinhardt Australia Pty Ltd CO-ORDINATE SYSTEM HEIGHT DATUM

TITLE DRAWN DRG CHECK DESIGN DESIGN CHECK DESIGN MINGR P.ENOCH PROJECT MINGR P.ENOCH

PLOT DATE / TIME

PLOT BY CLIEN1 3/11/2014 2:21:41 PM Aseip DATE D.CREARY M.GRINHAM Services A.PHAM S.DUNSTONE BRANCH NAME SECTION NAME

DEPARTMENT NAME

Transport Roads & Maritime

HORNSBY SHIRE COUNCIL MR 161 - GALSTON ROAD ROAD WORKS IN ASSOCIATION WITH 392 GALSTON ROAD, GALSTON GALSTON GRANGE DEVELOPMENT

MISCELLANEOUS DETAILS

SHEET 19 OF 21

A3

RMS REGISTRATION No. DS2014 / 000149 ISSUE STATUS MS-0120

