BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Multi Dwelling

Certificate number: 1730063M_03

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

This certificate is a revision of certificate number 1730063M submitted to the consent authority or certifier on 30 January 2024 with application DA16 - 2023 - 707 - 1.

It is the responsibility of the applicant to verify with the consent authority that the original, or any revised certificate, complies with the requirements of Schedule 1 Clause 2A, 4A or 6A of the Environment Planning and Assessment Regulation 2000

Secretary

Date of issue: Wednesday, 18 December 2024

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



Project summary										
Project name	4 Vardon Road, Fern Bay_03									
Street address	4 VARDON ROAD FERN BAY 2295									
Local Government Area	PORT STEPHENS									
Plan type and plan number	Deposited Plan -									
Lot no.	4									
Section no.	82314									
No. of residential flat buildings	3									
Residential flat buildings: no. of dwellings	125									
Multi-dwelling housing: no. of dwellings	47									
No. of single dwelling houses	0									
Project score										
Water	42 -	Farget 40								
Thermal Performance	V Pass	Farget Pass								
Energy	✓ 61	Farget 58								
Materials	-100	Γarget n/a								

Certificate Prepared by

Name / Company Name: Evergreen Energy Consultants Pty Ltd

ABN (if applicable): 91601503717

Description of project

Project address

Project name	4 Vardon Road, Fern Bay_03
Street address	4 VARDON ROAD FERN BAY 2295
Local Government Area	PORT STEPHENS
Plan type and plan number	Deposited Plan -
Lot no.	4
Section no.	82314
Project type	
No. of residential flat buildings	3
Residential flat buildings: no. of dwellings	125
Multi-dwelling housing: no. of dwellings	47
No. of single dwelling houses	0
Site details	
Site area (m²)	65756
Roof area (m²)	11714
Non-residential floor area (m ²)	0
Residential car spaces	207
Non-residential car spaces	0

Common area landscape 1000 Common area lawn (m²) Common area garden (m²) 1000 Area of indigenous or low water use 0 species (m²) Assessor details and thermal loads Assessor number DMN/16/1742 Certificate number 0009131130 Climate zone 15 **Project score** Water 42 Target 40 **Thermal Performance** Target Pass 4 Pass Energy 61 Target 58 Materials -100 Target n/a

Description of project

The tables below describe the dwellings and common areas within the project

Residential flat buildings - Building 1, 46 dwellings, 5 storeys above ground

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)
1.01	2	132.2	0	0	0	1.02	2	103.3	0	0	0	1.03	3	141	0	0	0	1.04	3	141	0	0	0
1.05	2	111.1	0	0	0	1.06	3	148.5	0	0	0	1.07	3	133.6	0	0	0	1.08	3	153.6	0	0	0
1.09	2	119.3	0	0	0	1.10	2	103.3	0	0	0	1.11	3	150.8	0	0	0	2.01	2	132.2	0	0	0
2.02	2	103.3	0	0	0	2.03	3	141	0	0	0	2.04	3	141	0	0	0	2.05	2	111.1	0	0	0
2.06	3	148.5	0	0	0	2.07	3	133.6	0	0	0	2.08	3	153.6	0	0	0	2.09	2	119.3	0	0	0
2.10	2	103.3	0	0	0	2.11	3	150.8	0	0	0	3.01	3	165.3	0	0	0	3.02	2	103.3	0	0	0
3.03	3	141	0	0	0	3.04	3	141	0	0	0	3.05	2	111.2	0	0	0	3.06	3	148.5	0	0	0
3.07	3	133.7	0	0	0	3.08	3	153.6	0	0	0	3.09	2	119.3	0	0	0	4.01	3	168.6	0	0	0
4.02	3	286.6	0	0	0	4.03	3	225.7	0	0	0	4.04	3	169.8	0	0	0	G.01	2	132.2	0	0	0
G.02	2	103.3	0	0	0	G.03	3	141	0	0	0	G.04	3	141	0	0	0	G.05	2	111.1	0	0	0
G.06	3	148.5	0	0	0	G.07	3	133.6	0	0	0	G.08	3	153.6	0	0	0	G.09	2	119.6	0	0	0
G.10	2	103.3	0	0	0	G.11	3	150.8	0	0	0				·								
Dwelling no.	No. of bedrooms	-	Unconditioned floor te direction te directio	Area of garden & lawn (m²)	Indigenous species (min area m²)	Dwelling 2,	No. of bedrooms	-	Unconditioned floor area (m ²)	Area of garden & lawn (m²)	Indigenous species (min area m ²)	Dwelling no.	ound bedrooms		Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)
Dwelli	No. of	Condi area (I	Uncor area (i	Area d Iawn (Indige (min a	Dwelli	No. of	Condi area (I	Uncor area (i	Area d Iawn (Indige (min a	Dwelli	No. of	Condi area (I	Uncor area (i	Area d lawn (Indige (min a	Dwelli	No. of	Condi area (I	Uncor area (i	Area d Iawn (Indige (min a

BASIX Department of Planning, Housing and Infrastructure

0

0

2 132.6 0

1.01

www.basix.nsw.gov.au Version: 4.03

0

0

2 103.3 0

1.02

Version: 4.03 / EUCALYPTUS_03_01_0 Certifica

1.03

3 142.6 0

0

0

0

1.04 3 142.6 0

0

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
1.05	2	103.3	0	0	0	1.06	2	132.2	0	0	0	1.07	3	150.8	0	0	0	1.08	2	103.3	0	0	0
1.09	2	103.3	0	0	0	1.10	3	150.8	0	0	0	2.01	2	132.2	0	0	0	2.02	2	103.3	0	0	0
2.03	3	142.6	0	0	0	2.04	3	142.6	0	0	0	2.05	2	103.3	0	0	0	2.06	2	132.2	0	0	0
2.07	3	150.8	0	0	0	2.08	2	103.3	0	0	0	2.09	2	103.3	0	0	0	2.10	3	150.8	0	0	0
3.01	2	132.2	0	0	0	3.02	2	103.3	0	0	0	3.03	3	142.6	0	0	0	3.04	3	142.6	0	0	0
3.05	2	103.3	0	0	0	3.06	2	132.2	0	0	0	3.07	3	150.8	0	0	0	3.08	2	103.3	0	0	0
3.09	2	103.3	0	0	0	3.10	3	150.8	0	0	0	4.01	3	215.8	4.6	0	0	4.02	3	187.7	11.3	0	0
4.03	3	187.7	11.3	0	0	4.04	3	215.8	4.6	0	0	G.01	2	132.2	0	0	0	G.02	2	103.3	0	0	0
G.03	3	142.6	0	0	0	G.04	3	142.6	0	0	0	G.05	2	103.3	0	0	0	G.06	2	132.2	0	0	0
G.07	3	150.8	0	0	0	G.08	2	103.3	0	0	0	G.09	2	103.3	0	0	0	G.10	3	150.8	0	0	0
Resid	len	tial fla	t build	dings ·	- Buildi	ng 3, 3	35 0	dwellir	ngs, 5	storey	vs abov	ve gro	und	k	- L		S				or		w

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)
1.01	3	132.2	0	0	0	1.02	2	113.9	0	0	0	1.03	2	113.9	0	0	0	1.04	3	132.2	0	0	0
1.05	3	150.8	0	0	0	1.06	2	113.3	0	0	0	1.07	2	113.3	0	0	0	1.08	3	150.8	0	0	0
2.01	3	132.2	0	0	0	2.02	2	113.9	0	0	0	2.03	2	113.9	0	0	0	2.04	3	132.2	0	0	0
2.05	3	150.8	0	0	0	2.06	2	113.3	0	0	0	2.07	2	113.3	0	0	0	2.08	3	150.8	0	0	0
3.01	3	132.2	0	0	0	3.02	2	113.9	0	0	0	3.03	2	113.9	0	0	0	3.04	3	132.2	0	0	0
3.05	3	150.8	0	0	0	3.06	2	113.3	0	0	0	3.07	2	113.3	0	0	0	3.08	3	150.8	0	0	0
4.01	3	198.3	15.2	0	0	4.02	3	188.2	0	0	0	4.03	3	198.3	15.2	0	0	G.01	3	132.2	0	0	0
G.02	2	113.9	0	0	0	G.03	2	113.9	0	0	0	G.04	3	132.2	0	0	0	G.05	3	150.8	0	0	0

BASIX Department of Planning, Housing and Infrastructure

www.basix.nsw.gov.au Version: 4.03 / EUC

Version: 4.03 / EUCALYPTUS_03_01_0 Certificate No.: 1730063M_03 Web

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
G.06	2	113.3	0	0	0	G.07	2	113.3	0	0	0	G.08	3	150.8	0	0	0						

Multi-dwelling houses

Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & lawn (m²)	Indigenous species (min area m²)	Dwelling no.		Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)	Dwelling no.	No. of bedrooms	Conditioned floor area (m²)	Unconditioned floor area (m²)	Area of garden & Iawn (m²)	Indigenous species (min area m²)
S1.01	2	141.4	7.3	50	0	S1.02	2	141.4	7.3	50	0	S1.0	3 3	149.4	8	50	0	S1.04	2	141.4	7.3	50	0
S1.05	3	149.4	8	50	0	S1.06	2	141.4	7.3	50	0	S1.0	7 2	139.7	8.4	50	0	S1.08	3	149.4	8	50	0
S2.01	3	149.4	8	50	0	S2.02	2	141.4	7.3	50	0	S2.0	3 2	141.4	7.3	50	0	S2.04	3	149.4	8	50	0
S2.05	2	141.4	7.3	50	0	S2.06	2	141.4	7.3	50	0	S3.0	1 2	169.2	9.6	50	0	S3.02	2	141.4	7.3	50	0
S3.03	3	149.4	8	50	0	S4.01	3	149.4	8	50	0	S4.0	2 2	141.4	7.3	50	0	S4.03	2	141.4	7.3	50	0
S4.04	3	149.4	8	50	0	S4.05	2	141.4	7.3	50	0	S5.0	1 2	141.4	7.3	50	0	S5.02	3	149.4	8	50	0
S5.03	2	141.4	7.3	50	0	S5.04	2	141.4	7.3	50	0	S5.0	5 3	149.4	8	50	0	S5.06	2	141.4	7.3	50	0
S5.07	2	141.4	7.3	50	0	S6.01	3	149.4	8	50	0	S6.0	2 2	141.4	7.3	50	0	S6.03	2	141.4	7.3	50	0
S6.04	3	149.4	8	50	0	S6.05	2	141.4	7.3	50	0	S6.0	6 3	152.4	6.6	50	0	S7.01	3	176.1	15.1	50	0
S7.02	3	176.1	15.1	50	0	S8.01	3	147.3	16.8	50	0	S8.0	2 3	147.3	16.8	50	0	S8.03	3	147.3	16.8	50	0
S8.04	3	147.3	16.8	50	0	S9.01	3	147.3	16.8	50	0	S9.0	2 3	147.3	16.8	50	0	S9.03	3	147.3	16.8	50	0
S9.04	3	147.3	16.8	50	0	S9.05	3	147.3	16.8	50	0	S9.0	6 3	147.3	16.8	50	0						

Description of project

Common area

Undercover car park area (Building 3)

Ground floor lobbys (Building 3)

All 3rd floor lobbys (Building 3)

The tables below describe the dwellings and common areas within the project

Floor area (m²)

1495

88

88

Common areas of unit building - Building 1

Common area	Floor area (m²)	Common area	Floor area (m²)	Common area	Floor area (m²)
Undercover car park area (Building 1)	2028	Garbage rooms (Building 1)	61	All service rooms (Building 1)	35
Residential storage	94	Ground floor lobbys (Building 1)	125.5	All 1st floor lobbys (Building 1)	125.5
All 2nd floor lobbys (Building 1)	125.5	All 3rd floor lobbys (Building 1)	125.5	All 4th floor lobbys (Building 1)	74.5

Common areas of unit building - Building 2

Common area	Floor area (m²)
Undercover car park area (Building 2)	1935
Ground floor lobbys (Building 2)	106
All 3rd floor lobbys (Building 2)	106
Lift bank (No. 2)	-

Common areas of unit building - Building 3

Common area	Floor area (m²)
Garbage rooms (Building 2)	64
All 1st floor lobbys (Building 2)	106
All 4th floor lobbys (Building 2)	64
Lift bank (No. 3)	-

Common area	Floor area (m²)
All service rooms (Building 2)	35
All 2nd floor lobbys (Building 2)	106
Lift bank (No. 1)	-

Common area	Floor area (m²)	Common area	Floor area (m²)
Garbage rooms (Building 3)	64	All service rooms (Building 3)	35
All 1st floor lobbys (Building 3)	88	All 2nd floor lobbys (Building 3)	88
All 4th floor lobbys (Building 3)	88		

Schedule of BASIX commitments

1. Commitments for Residential flat buildings - Building 1

(a) Buildings

(i) Materials

(b) Dwellings

(i) Water

(ii) Energy

(iii) Thermal Performance

(c) Common areas and central systems/facilities

(i) Water

(ii) Energy

2. Commitments for Residential flat buildings - Building 2

(a) Buildings

(i) Materials

(b) Dwellings

(i) Water

(ii) Energy

(iii) Thermal Performance

(c) Common areas and central systems/facilities

(i) Water

(ii) Energy

3. Commitments for Residential flat buildings - Building 3

(a) Buildings

(i) Materials

(b) Dwellings

(i) Water

(ii) Energy

(iii) Thermal Performance

(c) Common areas and central systems/facilities

(i) Water

(ii) Energy

4. Commitments for multi-dwelling housing

(a) Dwellings

(i) Water

(ii) Energy

(iii) Thermal Performance and Materials

5. Commitments for single dwelling houses

(a) Dwellings

(i) Water

(ii) Energy

(iii) Thermal Performance and Materials

6. Commitments for common areas and central systems/facilities for the development (non-building specific)

(b) Common areas and central systems/facilities

(i) Water

(ii) Energy

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carriedout. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

1. Commitments for Residential flat buildings - Building 1

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			>
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		>	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	~	~	~
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			>

Floor types									
Floor type	Area (m2)	Insulation	Low emissions option						
suspended floor above garage, frame: suspended concrete slab	1457	fibreglass batts or roll	30% cement substitute						
floors above habitable rooms, frame: suspended concrete slab	4986	fibreglass batts or roll	30% cement substitute						

External wall types									
External wall type	Construction type	Area (m2)	Low emissions option	Insulation					
External wall type 1	framed (fibre cement sheet or boards),frame:heavy steel post and beam frame	3538.7	30% cement substitute	fibreglass batts or roll					

BASIX Department of Planning, Housing and Infrastructure

	Internal wall types							
Internal wall type	Construction type	Area (m2)	Insulation					
Internal wall type 1	plasterboard, frame:light steel frame	3538.7	-					

Reinforcement concrete frames/columns								
Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option						
no	-	-						

	Ceiling and roof types								
Ceiling and roof type Area (m ²) Roof Insulation Ceiling Insulation									
framed - metal roof, frame: light steel frame	1732	foil backed blanket	fibreglass batts or roll						

	Glazing types		Frame types						
Single glazing (m ²)	Double glazing (m²)	Triple glazing (m ²)	Aluminium frames (m²)	Timber frames (m ²)	uPVC frames (m²)	Steel frames (m ²)	Composite frames (m²)		
2663.2	-	-	2663.2	-	-	-	-		

(b) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			1
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	~	~	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		>	~
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		`	~
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		~	~
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		~	~
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	>	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		~	
(g) The pool or spa must be located as specified in the table.	>	v	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	~

	Fixtures					Appliances Individual poo			dual pool	Individual spa				
Dwelling no.	All shower- heads	All toilet flushing systems	kitchen	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish- washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
	4 star (> 4.5 but <= 6 L/min)	4 star	4 star	4 star	-	not specified	3 star	-	-	-	-	-	-	-

BASIX Department of Planning, Housing and Infrastructure

			Alter	native water sou	irce								
Dwelling no.	Alternative water Size supply systems		Size Configuration		Landscape Toile connection coni (s)			ndry nection	Pool top- up	Spa top-up			
II dwellings	dwellings No alternative water												
ii) Energy							Show on DA plans		w on CC/CDC s & specs	Certifier check			
(a) The applica	ant must comply with the con	nmitments listed	pelow in carrying out the developm	ent of a dwelling	listed in a table	below.							
supplied by	a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below. b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.												
			d laundry of the dwelling, the ventilate the operation control specified for		cified for that roo	om in			~	~			
headings of cooling or such areas	of the "Cooling" and "Heating" heating system is specified ir	" columns in the t the table for "Liv	n/s specified for the dwelling under able below, in/for at least 1 living/b /ing areas" or "Bedroom areas", the conditioning system, then the syst	edroom area of tl en no systems ma	he dwelling. If n ay be installed i	o n any			~	~			
the table b lighting" fo specified for	elow (but only to the extent s r each such room in the dwel	pecified for that r ling is fluorescen hen the light fittir	elling which is referred to in a head oom or area). The applicant must o t lighting or light emitting diode (LE ligs in that room or area must only l	ensure that the "p D) lighting. If the	rimary type of a term "dedicated	rtificial d" is			~	~			
the table b			elling which is referred to in a head oom or area). The applicant must e				>		×	~			
g) This comm	nitment applies if the applican	t installs a water	heating system for the dwelling's p	ool or spa. The a	applicant must:								
			dividual Pool" column of the table ant must install a timer, to control t			nstall			~				
(bb) ins			dividual Spa" column of the table b ant must install a timer to control th		vely must not in	stall			~				
a	ant must install in the dwelling	g:											

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and (cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		~	~
 (i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated". 			

	Hot water	Hot water Bathroom ventilation system Kitchen ventilation system			lation system	Laundry vent	ilation system
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control
All dwellings		individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off

	Cooling		Hea	ting	Natural lighting	
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bathrooms or toilets	Main kitchen
All dwellings	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	0	-

	Inc	dividual pool		Individual sp	Da		Appliances ot	her efficiency	/ measures	
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	electric cooktop & electric oven	3 star	4 star	-	-

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	>		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		~	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		~	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	~	~	~
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	~	~	~
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	~		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		~	

	Thermal loads			
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)	
1.01	23.8	33.9	57.700	
1.02	9.8	17.7	27.500	
1.03	19.1	16.1	35.200	
1.04	21.3	15.3	36.600	

		Thermoliando	
		Thermal loads	
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)
1.05	10.3	13.2	23.500
1.06	22.2	26.6	48.800
1.07	25.1	34.5	59.600
1.08	51.90	25.8	77.700
1.09	31.1	23.4	54.500
1.10	45.5	18.7	64.200
1.11	51.6	32.7	84.300
2.01	37.2	32.2	69.400
2.02	10.4	17.3	27.700
2.03	19.3	15.6	34.900
2.04	21.9	14.9	36.800
2.05	11	12.7	23.700
2.06	23	26.2	49.200
2.07	26	34.4	60.400
2.08	53.1	25.4	78.500
2.09	32.2	22.6	54.800
2.10	37.2	18.6	55.800
2.11	51.4	28.3	79.700
3.01	46.4	28.4	74.800
3.02	25.10	20.9	46.000
3.03	32.4	18.0	50.400
3.04	32.9	15.1	48.000
3.05	19.6	13.4	33.000
3.06	30.8	25.3	56.100
3.07	42.1	33.1	75.200
3.08	52.70	26.9	79.600
3.09	35.3	22.2	57.500
l.01	47.8	9.9	57.700
.02	52.1	10.3	62.400
4.03	52.3	21.3	73.600
4.04	53.0	8.6	61.600

BASIX Department of Planning, Housing and www.basix.nsw.gov.au Version: 4.03 / EUCALYPTUS_03_01_0 Certificate No.: 1730063M_03 Wednesday, 18 December 2024 page 15/52 Infrastructure

		Thermal loads				
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)			
G.01	45	34.8	79.800			
G.02	20.7	15.3	36.000			
G.03	27.1	14.0	41.100			
G.04	27.7	14.7	42.400			
G.05	23.8	12.60	36.400			
G.06	40.60	23.9	64.500			
G.07	39.9	32.7	72.600			
G.08	50.5	17.4	67.900			
G.09	47.30	17.0	64.300			
G.10	46.9	12.4	59.300			
All other dwellings	53.4	20.2	73.600			

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		~	>
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	~	>	~
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	~	>	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		~	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		~	~
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		v	>

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common	no common facility	no common facility	4 star	no common laundry facility
areas				

Central systems	Size	Configuration	Connection (to allow for)
Fire sprinkler system (No. 1)		So that fire sprinkler test water is contained within the fire sprinkler system for re-use, rather than disposed.	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		~	~
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		~	~
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	>	~	~

Common area ventilation system			Common area lighting			
Common area	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS	
Undercover car park area (Building 1)	no mechanical ventilation	-	light-emitting diode	motion sensors	-	
Garbage rooms (Building 1)	no mechanical ventilation	-	light-emitting diode	motion sensors	-	
All service rooms (Building 1)	no mechanical ventilation	-	light-emitting diode	motion sensors	-	
Residential storage	no mechanical ventilation	-	light-emitting diode	motion sensors	-	
Ground floor lobbys (Building 1)	ventilation exhaust only	time clock or BMS controlled	light-emitting diode	motion sensors	-	
All 1st floor lobbys (Building 1)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-	
All 2nd floor lobbys (Building 1)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-	
All 3rd floor lobbys (Building 1)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-	
All 4th floor lobbys (Building 1)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-	

Central energy systems	Туре	Specification
Lift bank (No. 1)	gearless traction with V V V F motor and regenerative drive	Number of levels (including basement): 5 number of levels from the bottom of the lift shaft to the top of the lift shaft: 6 number of lifts: 2 lift load capacity: >= 1001 kg but <= 1500kg
Lift bank (No. 2)	gearless traction with V V V F motor and regenerative drive	Number of levels (including basement): 5 number of levels from the bottom of the lift shaft to the top of the lift shaft: 6 number of lifts: 2 lift load capacity: >= 1001 kg but <= 1500kg

2. Commitments for Residential flat buildings - Building 2

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			~
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		<	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	~	~	~
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			~

Floor types									
Floor type	Area (m2)	Insulation	Low emissions option						
suspended floor above garage, frame: suspended concrete slab	1292	fibreglass batts or roll	30% cement substitute						
floors above habitable rooms, frame: suspended concrete slab	4684	fibreglass batts or roll	30% cement substitute						

	External wall types										
External wall type	Construction type	Area (m2)	Low emissions option	Insulation							
External wall type 1	framed (fibre cement sheet or boards),frame:heavy steel post and beam frame	3330	30% cement substitute	fibreglass batts or roll							

Internal wall types								
Internal wall type	Construction type	Area (m2)	Insulation					
Internal wall type 1	plasterboard, frame:light steel frame	3330	-					

Reinforcement concrete frames/columns								
Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option						
no	-	-						

	Ceiling and roof types								
Ceiling and roof type	Area (m²)	Roof Insulation	Ceiling Insulation						
framed - metal roof, frame: light steel frame	1465	foil backed blanket	fibreglass batts or roll						

	Glazing types		Frame types						
Single glazing (m ²)	Double glazing (m²)	Triple glazing (m²)	Aluminium frames (m²)	Timber frames (m ²)	uPVC frames (m²)	Steel frames (m ²)	Composite frames (m²)		
2486.4	-	-	2486.4	-	-	-	-		

(b) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			1
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	~	~	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		>	~
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		`	~
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		~	~
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		~	~
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	>	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		~	
(g) The pool or spa must be located as specified in the table.	>	v	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	~

	Fixtures					Appliances Individ			dual pool		Individual spa			
Dwelling no.	All shower- heads	All toilet flushing systems	kitchen	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish- washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
	4 star (> 4.5 but <= 6 L/min)	4 star	4 star	4 star	-	not specified	3 star	-	-	-	-	-	-	-

BASIX Department of Planning, Housing and Infrastructure

	Alternative water source											
Dwelling no.	Alternative water supply systems	Size	Configuration	juration Landscape Toilet Laundry Pool top- connection connection up (s)		Spa top-up						
II dwellings	No alternative water supply	-	-		-	-	-		-	-		
ii) Energy							Show on DA plans		w on CC/CDC s & specs	Certifier check		
(a) The applica	ant must comply with the con	nmitments listed	pelow in carrying out the developm	ent of a dwelling	listed in a table	below.						
supplied by	y that system. If the table spe	cifies a central h	ed for the dwelling in the table belo ot water system for the dwelling, th water is supplied by that central sy	en the applicant			~		~	~		
			d laundry of the dwelling, the ventilate the operation control specified for		cified for that roo	om in			~	~		
headings of cooling or such areas	of the "Cooling" and "Heating" heating system is specified ir	" columns in the t the table for "Liv	n/s specified for the dwelling under able below, in/for at least 1 living/b /ing areas" or "Bedroom areas", the conditioning system, then the syst	edroom area of tl en no systems ma	he dwelling. If n ay be installed i	o n any			~	~		
the table b lighting" fo specified for	elow (but only to the extent s r each such room in the dwel	pecified for that r ling is fluorescen hen the light fittir	elling which is referred to in a head oom or area). The applicant must o t lighting or light emitting diode (LE ligs in that room or area must only l	ensure that the "p D) lighting. If the	rimary type of a term "dedicated	rtificial d" is			~	~		
the table b			elling which is referred to in a head oom or area). The applicant must e				>		×	~		
g) This comm	nitment applies if the applican	t installs a water	heating system for the dwelling's p	ool or spa. The a	applicant must:							
			dividual Pool" column of the table ant must install a timer, to control t			nstall			~			
(bb) ins			dividual Spa" column of the table b ant must install a timer to control th		vely must not in	stall			~			
a	ant must install in the dwelling	g:										

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and (cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		~	~
 (i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated". 		<u> </u>	

	Hot water	Hot water Bathroom ventilation system Kitchen ventilation system			Laundry ventilation system		
Dwelling no.	Hot water system	Each bathroom Operation control Each kitchen Operation contro		Operation control	Each laundry	Operation control	
All dwellings	gas instantaneous - 6 star	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off

	Cooling		Hea	ting	Natural lighting	
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bathrooms or toilets	Main kitchen
All dwellings	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	0	-

	Inc	dividual pool		Individual sp	Da		Appliances ot	ner efficiency	/ measures	
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	electric cooktop & electric oven	3 star	4 star	-	-

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	>		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		~	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		~	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	~	~	~
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	v	~	~
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	~		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		~	

	Thermal loads				
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)		
1.01	23.9	33.7	57.600		
1.02	39.2	21.6	60.800		
1.03	26.6	21.7	48.300		
1.04	25.1	19.3	44.400		

		Thermal loads	
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)
1.05	33.3	21.3	54.600
1.06	40.7	34.9	75.600
1.07	38.7	33.8	72.500
1.08	27.60	23.7	51.300
1.09	28.9	25.4	54.300
1.10	23.3	31.5	54.800
2.01	24.7	32.9	57.600
2.02	40.4	21.3	61.700
2.03	27.5	21.3	48.800
2.04	26	19.4	45.400
2.05	34.5	20.9	55.400
2.06	41.90	34.8	76.700
2.07	39.8	33.3	73.100
2.08	28.5	23.6	52.100
2.09	30	25.1	55.100
2.10	24.3	31	55.300
3.01	33.4	31.3	64.700
3.02	44.1	22.7	66.800
3.03	36.7	27.0	63.700
3.04	34.7	26.1	60.800
3.05	38	26.1	64.100
3.06	53.4	32.9	86.300
3.07	51.80	33.8	85.600
3.08	36.8	28.5	65.300
3.09	39.8	30.9	70.700
3.10	31.8	31.8	63.600
1.01	53.10	17.9	71.000
4.02	51.60	19	70.600
4.03	49	17.9	66.900
4.04	51.50	16.2	67.700
G.01	31.3	33.5	64.800

BASIX Department of Planning, Housing and www.basix.nsw.gov.au Version: 4.03 / EUCALYPTUS_03_01_0 Certificate No.: 1730063M_03 Wednesday, 18 December 2024 page 25/52 Infrastructure

		Thermal loads						
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)					
G.02	52.9	18.5	71.400					
G.03	36.7	20.4	57.100					
G.04	34.3	18.4	52.700					
G.05	44.2	20.1	64.300					
G.06	50.3	29.2	79.500					
G.07	45	34	79.000					
G.08	33.7	21.9	55.600					
G.09	36.9	23.7	60.600					
All other dwellings	28.7	30.2	58.900					

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		~	>
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	~	>	~
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	~	>	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		~	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		~	~
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		v	>

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common	no common facility	no common facility	4 star	no common laundry facility
areas				

Central systems	Size	Configuration	Connection (to allow for)
Fire sprinkler system (No. 2)		So that fire sprinkler test water is contained within the fire sprinkler system for re-use, rather than disposed.	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		~	~
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		~	~
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	>	~	~

	Common area v	ventilation system		Common area lighting	
Common area	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS
Undercover car park area (Building 2)	no mechanical ventilation	-	light-emitting diode	motion sensors	-
Garbage rooms (Building 2)	no mechanical ventilation	-	light-emitting diode	motion sensors	-
All service rooms (Building 2)	no mechanical ventilation	-	light-emitting diode	motion sensors	-
Ground floor lobbys (Building 2)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-
All 1st floor lobbys (Building 2)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-
All 2nd floor lobbys (Building 2)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-
All 3rd floor lobbys (Building 2)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-
All 4th floor lobbys (Building 2)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-
Lift bank (No. 1)	-	-	light-emitting diode	connected to lift call button	-
Lift bank (No. 2)	-	-	light-emitting diode	connected to lift call button	-
Lift bank (No. 3)	-	-	light-emitting diode	connected to lift call button	-

Central energy systems	Туре	Specification
· · · · ·	V F motor and regenerative drive	Number of levels (including basement): 5 number of levels from the bottom of the lift shaft to the top of the lift shaft: 6 number of lifts: 2 lift load capacity: >= 1001 kg but <= 1500kg

3. Commitments for Residential flat buildings - Building 3

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			~
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		<	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	~	~	~
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			~

Floor types									
Floor type	Area (m2)	Insulation	Low emissions option						
suspended floor above garage, frame: suspended concrete slab	1060	fibreglass batts or roll	30% cement substitute						
floors above habitable rooms, frame: suspended concrete slab	3764	fibreglass batts or roll	30% cement substitute						

	External wall types										
External wall type	Construction type	Area (m2)	Low emissions option	Insulation							
External wall type 1	framed (fibre cement sheet or boards),frame:heavy steel post and beam frame	2519.8	30% cement substitute	fibreglass batts or roll							

Internal wall types								
Internal wall type	Construction type	Area (m2)	Insulation					
Internal wall type 1	plasterboard, frame:light steel frame	2519.8	-					

Reinforcement concrete frames/columns									
Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option							
no	-	-							

	Ceiling and roof types								
Ceiling and roof type	Area (m²)	Roof Insulation	Ceiling Insulation						
framed - metal roof, frame: light steel frame	1148	foil backed blanket	fibreglass batts or roll						

	Glazing types			Frame types						
Single glazing (m ²)	Double glazing (m²)	Triple glazing (m²)	Aluminium frames (m²)	Timber frames (m ²)	uPVC frames (m²)	Steel frames (m ²)	Composite frames (m²)			
1998.5	-	-	1998.5	-	-	-	-			

(b) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			1
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	~	~	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		>	~
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		v	~
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		~	~
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		~	~
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	>	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		~	
(g) The pool or spa must be located as specified in the table.	>	v	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	~

	Fixtures					Appli	ances	Individual pool			Individual spa			
Dwelling no.	All shower- heads	All toilet flushing systems	kitchen	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish- washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
	4 star (> 4.5 but <= 6 L/min)	4 star	4 star	4 star	-	not specified	3 star	-	-	-	-	-	-	-

BASIX Department of Planning, Housing and Infrastructure

	Alternative water source											
Dwelling no.	Alternative water supply systems	Size	Configuration	Landscape connectionToilet connectionLaundry connectionPool top- up(s)		Spa top-up						
II dwellings	No alternative water supply	-	-		-	-	-		-	-		
ii) Energy							Show on DA plans		w on CC/CDC s & specs	Certifier check		
(a) The applica	ant must comply with the con	nmitments listed	pelow in carrying out the developm	ent of a dwelling	listed in a table	below.						
supplied by	y that system. If the table spe	cifies a central h	ed for the dwelling in the table belo ot water system for the dwelling, th water is supplied by that central sy	en the applicant			~		~	~		
			d laundry of the dwelling, the ventilate the operation control specified for		cified for that roo	om in			~	~		
headings of cooling or such areas	of the "Cooling" and "Heating" heating system is specified ir	" columns in the t the table for "Liv	n/s specified for the dwelling under able below, in/for at least 1 living/b /ing areas" or "Bedroom areas", the conditioning system, then the syst	edroom area of tl en no systems ma	he dwelling. If n ay be installed i	o n any			~	~		
the table b lighting" fo specified for	elow (but only to the extent s r each such room in the dwel	pecified for that r ling is fluorescen hen the light fittir	elling which is referred to in a head oom or area). The applicant must o t lighting or light emitting diode (LE ligs in that room or area must only l	ensure that the "p D) lighting. If the	rimary type of a term "dedicated	rtificial d" is			~	~		
the table b			elling which is referred to in a head oom or area). The applicant must e				>		×	~		
g) This comm	nitment applies if the applican	t installs a water	heating system for the dwelling's p	ool or spa. The a	applicant must:							
			dividual Pool" column of the table ant must install a timer, to control t			nstall			~			
(bb) ins			dividual Spa" column of the table b ant must install a timer to control th		vely must not in	stall			~			
a	ant must install in the dwelling	g:										

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and		~	٢
(cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		~	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		 Image: A set of the set of the	

	Hot water	Hot water Bathroom ventilation system Kitchen ventilation system			Laundry ventilation system		
Dwelling no.	Hot water system	ter system Each bathroom Operation control		Each kitchen	Operation control	Each laundry	Operation control
All dwellings	gas instantaneous - 6 star	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off

	Cooling		Hea	ting	Natural lighting	
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bathrooms or toilets	Main kitchen
All dwellings	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	0	-

	Individual pool		Individual sp	spa Appliances other efficiency measur			/ measures			
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	electric cooktop & electric oven	3 star	4 star	-	-

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	>		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		~	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		~	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	~	~	~
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	v	~	~
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	~		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		`	

	Thermal loads				
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)		
1.01	17.5	34.1	51.600		
1.02	23.8	21.7	45.500		
1.03	18.3	23.5	41.800		
1.04	36.8	35.3	72.100		

	Thermal loads						
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)				
1.05	33.50	34.9	68.400				
1.06	21.4	29.4	50.800				
1.07	23.10	25.9	49.000				
1.08	21.80	31.8	53.600				
2.01	18.2	33.6	51.800				
2.02	24.8	21.2	46.000				
2.03	19.3	23.2	42.500				
2.04	37.9	34.7	72.600				
2.05	34.3	34.4	68.700				
2.06	22.1	28.9	51.000				
2.07	24.1	25.7	49.800				
2.08	22.80	31.3	54.100				
5.01	27.5	31.4	58.900				
3.02	29.3	23.8	53.100				
3.03	25.6	25.7	51.300				
3.04	50.3	30.1	80.400				
3.05	50	31.4	81.400				
3.06	31.50	32.4	63.900				
3.07	32.7	30.7	63.400				
3.08	35.2	30.5	65.700				
4.01	49.3	28.8	78.100				
1.02	49.4	13.8	63.200				
4.03	52	26.4	78.400				
G.01	29.4	31.4	60.800				
G.02	34.2	20.8	55.000				
G.03	27.1	24.9	52.000				
G.04	53.00	30.6	83.600				
G.05	41.5	33.4	74.900				
G.06	29	27.5	56.500				
G.07	32.30	25.7	58.000				
All other dwellings	32.1	32.1	64.200				

BASIX Department of Planning, Housing and www.basix.nsw.gov.au Version: 4.03 / EUCALYPTUS_03_01_0 Certificate No.: 1730063M_03 Wednesday, 18 December 2024 page 35/52 Infrastructure

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		~	>
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	~	>	~
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	~	>	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		~	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		~	~
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		v	~

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common	no common facility	no common facility	4 star	no common laundry facility
areas				

Central systems	Size	Configuration	Connection (to allow for)
Fire sprinkler system (No. 3)		So that fire sprinkler test water is contained within the fire sprinkler system for re-use, rather than disposed.	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		~	~
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		~	<
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	>	~	~

	Common area v	entilation system	Common area lighting				
Common area	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS		
Undercover car park area (Building 3)	no mechanical ventilation	-	light-emitting diode	motion sensors	-		
Garbage rooms (Building 3)	no mechanical ventilation	-	light-emitting diode	motion sensors	-		
All service rooms (Building 3)	no mechanical ventilation	-	light-emitting diode	motion sensors	-		
Ground floor lobbys (Building 3)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-		
All 1st floor lobbys (Building 3)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-		
All 2nd floor lobbys (Building 3)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-		
All 3rd floor lobbys (Building 3)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-		
All 4th floor lobbys (Building 3)	ventilation (supply + exhaust)	time clock or BMS controlled	light-emitting diode	motion sensors	-		

4. Commitments for multi-dwelling housing

(a) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	~	~	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		>	>
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		>	>
(e) The applicant must install:			
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		v	~
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		~	-
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	~	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		>	
(g) The pool or spa must be located as specified in the table.	~	v	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	~

			Fixture	es		Appli	ances		Indiv	dual pool			ndividual spa	a
Dwelling no.	All shower- heads	All toilet flushing systems	taps	bathroom	HW recirculation or diversion	All clothes washers	All dish- washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
All dwellings	4 star (> 4.5 but <= 6 L/min)	4 star	4 star	4 star	-	-	-	-	-	-	-	-	-	-

BASIX Department of Planning, Housing and Infrastructure

			Alternative	water source						
Dwelling no.	Alternative water supply systems	Size	Configuration		Landscape connection			Laundry Pool top- connection up		Spa top-up
II dwellings	Individual water tank (No. 1)	Tank size (min) 2000 liters	To collect run-off from at least: 40 square metres of roof area;	yes		-	yes		-	-
(ii) Energy							Show on DA plans		w on CC/CDC s & specs	Certifier check
 (a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below. (b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system. 									~	~
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.									~	~
headings c cooling or	of the "Cooling" and "Heating'	" columns in the n the table for "Li	m/s specified for the dwelling under the "L table below, in/for at least 1 living/bedroor ving areas" or "Bedroom areas", then no s	n area of the dwelli ystems may be ins	ing. If n	o n any			~	~
	ving areas and bedrooms.		r conditioning system, then the system mu	st provide for day/	night zo	ning				
between liv (e) This comm the table b lighting" fo specified fo	itment applies to each room elow (but only to the extent s r each such room in the dwel	pecified for that lling is fluorescen then the light fitti	velling which is referred to in a heading to room or area). The applicant must ensure at lighting or light emitting diode (LED) ligh ngs in that room or area must only be cap	the "Artificial lightin that the "primary ty ting. If the term "de	ng" colu ype of a	mn of rtificial " is			~	~
(e) This comm the table b lighting" fo specified fo lighting or (f) This commi the table b	nitment applies to each room elow (but only to the extent s r each such room in the dwel or a particular room or area, t light emitting diode (LED) ligh itment applies to each room of	pecified for that lling is fluorescent then the light fitti hting.	velling which is referred to in a heading to room or area). The applicant must ensure nt lighting or light emitting diode (LED) ligh	the "Artificial lightin that the "primary ty ting. If the term "de able of being used he "Natural lighting	ng" colu ype of a edicatec for fluor g" colum	mn of rtificial " is rescent n of	~		~	~
(e) This comm the table b lighting" fo specified fo lighting or l (f) This commi the table b fitted with a	itment applies to each room elow (but only to the extent s r each such room in the dwel or a particular room or area, t light emitting diode (LED) ligh itment applies to each room of elow (but only to the extent s a window and/or skylight.	pecified for that lling is fluorescent then the light fitti hting. or area of the dw pecified for that	velling which is referred to in a heading to room or area). The applicant must ensure it lighting or light emitting diode (LED) ligh ngs in that room or area must only be cap elling which is referred to in a heading to t	the "Artificial lightin that the "primary ty ting. If the term "de able of being used he "Natural lighting that each such roo	ng" colur ype of a edicatec for fluor g" colur om or ar	mn of rtificial " is rescent n of	~		• •	✓ ✓
(e) This comm the table b lighting" fo specified fo lighting or l (f) This commi the table b fitted with a (g) This comm (aa) ins	itment applies to each room elow (but only to the extent s r each such room in the dwel or a particular room or area, t light emitting diode (LED) ligh itment applies to each room of elow (but only to the extent s a window and/or skylight. hitment applies if the applican stall the system specified for the	pecified for that lling is fluorescent then the light fitti hting. For area of the dw specified for that the pool in the "I	velling which is referred to in a heading to room or area). The applicant must ensure at lighting or light emitting diode (LED) ligh angs in that room or area must only be cap elling which is referred to in a heading to t room or area). The applicant must ensure	the "Artificial lightin that the "primary ty ting. If the term "de able of being used he "Natural lighting that each such roo spa. The applicant or alternatively mu	ng" colury ype of a edicated for fluor g" colum om or ar t must:	mn of rtificial " is rescent n of ea is	~		 	✓ ✓

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		~	
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and		~	~
(cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		~	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		~	
(j) The applicant must install the photovoltaic system specified for the dwelling under the "Photovoltaic system" heading of the "Alternative energy" column of the table below, and connect the system to that dwelling's electrical system.	~	~	~

	Hot water	Bathroom ven	tilation system	Kitchen venti	lation system	Laundry ventilation system		
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control	
All dwellings	gas instantaneous - 6 star	individual fan, ducted to façade or roof		individual fan, ducted to façade or roof		individual fan, ducted to façade or roof	manual switch on/off	

	Coo	bling	Hea	ting	Natural lighting		
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bathrooms or toilets	Main kitchen	
All dwellings	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	1-phase airconditioning - ducted / EER 2.5 - 3.0	1	yes	

	Inc	dividual pool		Individual sp	ba	Appliances other efficiency measures				
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	electric cooktop & electric oven	3 star	4 star	no	yes

		Alternative energy	
Dwelling no.	Photovoltaic system (min rated electrical output in peak kW)	Photovoltaic collector installation	Orientation inputs
All dwellings	-	-	-

(iii) Thermal Performance and Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	>		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		~	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		~	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	~	~	~
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	~	~	~
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	>		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		~	

		Thermal loads								
		I hermal loads								
Dwelling no.	Area adjusted heating load (in MJ/m²/yr)	Area adjusted cooling load (in MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)							
S1.01	25.7	19	44.700							
S1.02	27.4	18.9	46.300							
S1.03	35.6	15.4	51.000							
S1.04	33.8	17.2	51.000							
S1.05	19.7	17.6	37.300							
S1.06	27.3	19	46.300							
S1.07	33	12.2	45.200							
S1.08	32.4	15.4	47.800							
S2.01	14	17.3	31.300							
S2.02	31.1	18.1	49.200							
S2.03	31.2	17.8	49.000							
S2.04	14.6	17.3	31.900							
\$2.05	31.2	18.1	49.300							
\$2.06	31.1	17.9	49.000							
\$3.01	26.5	19.9	46.400							
\$3.02	16.6	16.3	32.900							
\$3.03	29.9	18.6	48.500							
54.01	31.2	15.5	46.700							
S4.02	24.3	19	43.300							
\$4.03	24.2	19.2	43.400							
S4.04	32.6	15.3	47.900							
S4.05	30.6	18.5	49.100							
\$5.01	25.9	19.1	45.000							
\$5.04	26.8	18.9	45.700							
\$5.07	33.1	17.3	50.400							
\$6.01	30.6	15.3	45.900							
6.02	23.7	19	42.700							
6.03	23.6	19.1	42.700							
6.04	31.7	15.5	47.200							
S6.05	30.7	19.0	49.700							
56.06	19.5	28.1	47.600							

BASIX Department of Planning, Housing and www.basix.nsw.gov.au Version: 4.03 / EUCALYPTUS_03_01_0 Certificate No.: 1730063M_03 Wednesday, 18 December 2024 page 42/52 Infrastructure

		Thermal loads							
Dwelling no.		Area adjusted he	eating load (in MJ/m²/yr)	Area adjusted cooling load (in	MJ/m²/yr)	Area adjusted total load (in MJ/m²/yr)			
S7.01		25.6		25.0		50.600			
S7.02		23.3		21.5		44.800			
S8.01		26.3		14.3		40.600			
S8.03		25.9		14.3		40.200			
S9.01		24.9		14.6		39.500			
S5.02, S5.05		35		15.3		50.300			
S5.03, S5.06		26.7		19.1		45.800			
S8.04, S9.06		32.9		14.2		47.100			
S9.03, S9.05		25.9		14.2		40.100			
All other dwellings		33.8		14.1		47.900			
				Construction of floors and wal	ls				
Dwelling no.	Concrete (m²)	slab on ground	Suspended floor with open subfloor (m²)	Suspended floor with enclosed subfloor (m²)	Suspended fl garage (m ²)	oor above	Primarily rammed earth mudbrick walls		
S1.07	148.1		-	-	-		no		

S1.07	148.1	-	-	-	no
S3.01	178.8	-	-	-	no
S7.01, S7.02	191.2	-	-	-	no
S8.01, S8.02, S8.03, S8.04, S9.01, S9.02, S9.03, S9.04, S9.05, S9.06	164.1	-	-	-	no
S1.03, S1.05, S1.08, S2.01, S2.04, S3.03, S4.01, S4.04, S5.02, S5.05, S6.01, S6.04, S6.06	157.4	-	-	-	no
All other dwellings	148.7	-	-	-	no

	Floor types	i								
	Concrete slab on ground				Suspended flo	or above encl	osed subfloor	Suspended floor above open subfloor		
Dwelling no.	Area (m²)	Insulation	Low emissions option	Dematerialisation	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation
S1.07	148.1	fibreglass batts or roll	-	conventional slab	-	-	-	-		-
S3.01	178.8	fibreglass batts or roll	-	conventional slab	-	-	-	-	-	-
S7.01, S7.02	191.2	fibreglass batts or roll	-	conventional slab	-	-	-	-	-	-
S8.01, S8.02, S8.03, S8.04, S9.01, S9.02, S9.03, S9.04, S9.05, S9.06	164.1	fibreglass batts or roll	-	conventional slab	-	-	-	-	-	-
S1.03, S1.05, S1.08, S2.01, S2.04, S3.03, S4.01, S4.04, S5.02, S5.05, S6.01, S6.04, S6.06	157.4	fibreglass batts or roll	-	conventional slab	-	-	-	-	-	-
All other dwellings	148.7	fibreglass batts or roll	-	conventional slab	-	-	-	-	-	-

	Floor types										
	First floor above habitable rooms or mezzanine			Suspended floor above garage			Garage floor				
Dwelling no.	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation	Construction type	Area (m²)	Insulation	Low emissions option	Dematerialisation
All dwellings	-	-	-	-	-	-	concrete slab on ground	36	fibreglass batts or roll	-	conventional slab

	External walls												
		Extern	nal wall type 1				External wall type 2						
Dwelling no.	Wall type	Area (m²)	Insulation		Low emiss	sions	Wall typ)e	Area	(m²)	Insulation		Low emissions option
All dwellings	brick veneer, frame : timber - H2 treated softwood	120	fibreglass batt roll	ts or	-		-		-		-		-
	External walls												
		External wall type 3								External v	all type 4		
Dwelling no.	Wall type	Area (m²)	Insulation		Low emiss	sions	Wall typ	be	Area	(m²)	Insulation		Low emissions option
All dwellings	-	-	-		-		-		-		-		-
	Internal walls												
		walls shared witl	n garage			nternal	wall type	1			Internal wa	all type	2
Dwelling no.	Wall type	Area (m²)	Insulation	Wall		Area (I		Insulatio	n	Wall type	Area (m ²		Insulation
All dwellings	plasterboard, frame: timber - H2 treated softwood	35.3	fibreglass batts or roll	plaste frame:	rboard, : timber reated	110.6		-		-	-		-
	Ceiling and roo	f											
	Fla	t ceiling / pitched	roof		Raked ceil	ing / pit	ched or s	killion roof			Flat ceiling	/ flat r	oof
Dwelling no.	Construction type	Area (m²)	Insulation	Cons type	struction	Area (I	m²)	Insulatio	n	Construction type	on Area (m ²	²)	Insulation
All dwellings	framed - metal roof, frame: timber - H2 treated softwood	157	Ceiling:fibreglass batts or roll,Roof: foil backed blanket	-		-		Ceiling:,R	oof:	-	-		Ceiling:,Roof:

BASIX Department of Planning, Housing and Infrastructure

	Glazing type				Frame types					
Dwelling no.	Single glazing (m²)	Double glazing (m²)	Triple glazing (m²)	Aluminium frames (m²)	Timber frames (m²)	uPVC frames (m²)	Steel frames (m²)	Composite frames (m²)		
All dwellings	50.1	-	-	50.1	-	-	-	-		

5. Commitments for single dwelling houses

(a) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.	Î		
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	>	>	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		~	~
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		~	~
(e) The applicant must install:			1
(aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and		~	v
(bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		~	-
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	~	~	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		>	
(g) The pool or spa must be located as specified in the table.	~	×	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	~	~	~
(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	~	~	~
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		~	~

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		~	~
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		~	~
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	>	~	~
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must:			
(aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and		~	
(bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		~	
(h) The applicant must install in the dwelling:			
(aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		~	
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and		~	~
(cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		~	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		~	
(j) The applicant must install the photovoltaic system specified for the dwelling under the "Photovoltaic system" heading of the "Alternative energy" column of the table below, and connect the system to that dwelling's electrical system.	~	~	~
(iii) Thermal Performance and Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			

(iii) Thermal Performance and Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	>		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		>	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		•	~
(g) Where there is an in-slab heating or cooling system, the applicant must:	~	×	~
(aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or			
(bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.			
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	~	~	~
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	v		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		v	

6. Commitments for common areas and central systems/facilities for the development (non-building specific)

(b) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		~	>
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	>	~	•
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	>	~	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		~	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		~	~
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		~	>

Common area	nmon area Showerheads rating Toilets rating		Taps rating	Clothes washers rating
All common areas	no common facility	no common facility	4 star	no common laundry facility

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		~	>
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		~	>
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	>	~	>

Central energy systems	Туре	Specification
Other	-	-

Notes

- 1. In these commitments, "applicant" means the person carrying out the development.
- 2. The applicant must identify each dwelling, building and common area listed in this certificate, on the plans accompanying any development application, and on the plans and specifications accompanying the application for a construction certificate / complying development certificate, for the proposed development, using the same identifying letter or reference as is given to that dwelling, building or common area in this certificate.
- 3. This note applies if the proposed development involves the erection of a building for both residential and non-residential purposes (or the change of use of a building for both residential and non-residential purposes). Commitments in this certificate which are specified to apply to a "common area" of a building or the development, apply only to that part of the building or development to be used for residential purposes.
- 4. If this certificate lists a central system as a commitment for a dwelling or building, and that system will also service any other dwelling or building within the development, then that system need only be installed once (even if it is separately listed as a commitment for that other dwelling or building).
- 5. If a star or other rating is specified in a commitment, this is a minimum rating.
- 6. All alternative water systems to be installed under these commitments (if any), must be installed in accordance with the requirements of all applicable regulatory authorities. NOTE: NSW Health does not recommend that stormwater, recycled water or private dam water be used to irrigate edible plants which are consumed raw, or that rainwater be used for human consumption in areas with potable water supply.

Legend

- 1. Commitments identified with a " 🕊 " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).
- 2. Commitments identified with a "V" in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.
- 3. Commitments identified with a "" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled. (Note: a certifying authority must not issue an occupation certificate (either interim or final) for a building listed in this certificate, or for any part of such a building, unless it is satisfied that each of the commitments whose fulfillment it is required to monitor in relation to the building or part, has been fulfilled).